



HADRONS

ELECTRICALS

AC GRILLS, FANS & MOULDING INJECTION PARTS

BUILT TO PERFORM. BUILT TO LAST.

Reliable Connections. Complete Safety.



PREMIUM
QUALITY



DURABLE &
RELIABLE



PRECISION
ENGINEERED



100%
RECYCLABLE



OEM GRADE
QUALITY

1. WINDOW AC FRONT GRILLS – 1.0 TON / 1.5 TON / 2.0 TON

1.0 TON



CONSTRUCTION DETAILS	SPECIFICATION
Application	Window AC – 1.0 Ton
Material	ABS (Virgin Grade)
Process	Injection Moulding
Overall Size (W x H x D)	560 x 375 x 45 mm
Louver Type	Horizontal Fixed + Vertical Adjustable
Wall Thickness	2.5 ± 0.3 mm
Rib Thickness	2.0 ± 0.3 mm
Weight	620 ± 30 g
Color	Off White / Ivory / Custom
Finish	Textured

1.5 TON



CONSTRUCTION DETAILS	SPECIFICATION
Application	Window AC – 1.5 Ton
Material	ABS (Virgin Grade)
Process	Injection Moulding
Overall Size (W x H x D)	660 x 425 x 50 mm
Louver Type	Horizontal Fixed + Vertical Adjustable
Wall Thickness	2.6 ± 0.3 mm
Rib Thickness	2.2 ± 0.3 mm
Weight	720 ± 30 g
Color	Off White / Ivory / Custom
Finish	Textured

2.0 TON



CONSTRUCTION DETAILS	SPECIFICATION
Application	Window AC – 2.0 Ton
Material	ABS (Virgin Grade)
Process	Injection Moulding
Overall Size (W x H x D)	715 x 480 x 52 mm
Louver Type	Horizontal Fixed + Vertical Adjustable
Wall Thickness	2.8 ± 0.3 mm
Rib Thickness	2.4 ± 0.3 mm
Weight	880 ± 40 g
Color	Off White / Ivory / Custom
Finish	Textured

2. AC OUTDOOR (ODU) & INDOOR (IDU) FANS – DIFFERENT TONNAGE



	ODU FAN – 1.0 TON	ODU FAN – 1.5 TON	ODU FAN – 2.0 TON	IDU TANGENTIAL FAN – 1.0 TON	IDU TANGENTIAL FAN – 1.5 TON	IDU TANGENTIAL FAN – 2.0 TON
Application	Outdoor Unit (ODU)	Outdoor Unit (ODU)	Outdoor Unit (ODU)	Indoor Unit (IDU)	Indoor Unit (IDU)	Indoor Unit (IDU)
Material	PP + 20% GF	PP + 20% GF	PP + 20% GF	ABS / PP	ABS / PP	ABS / PP
Process	Injection Moulding	Injection Moulding	Injection Moulding	Injection Moulding	Injection Moulding	Injection Moulding
No. of Blades	5	5	5	–	–	–
Diameter / Length	Ø 350 mm	Ø 400 mm	Ø 450 mm	Length 510 mm	Length 670 mm	Length 880 mm
Shaft Diameter	Ø 12 mm	Ø 12 mm	Ø 12 mm / 14 mm	Ø 60 mm	Ø 60 mm	Ø 60 mm
Angle of Blade	32°	32°	32°	–	–	–
Weight	430 ± 20 g	520 ± 20 g	640 ± 20 g	900 ± 30 g	1200 ± 30 g	1200 ± 30 g
Color	Black	Black	Black	Black	Black	Black
Balance	Dynamic Balanced	Dynamic Balanced	Dynamic Balanced	Dynamic Balanced	Dynamic Balanced	Dynamic Balanced
Features	High Air Flow, Low Noise	High Air Flow, Low Noise	High Air Flow, Low Noise	Smooth Air Flow, Low Vibration	Smooth Air Flow, Low Vibration	Smooth Air Flow, Low Vibration

3. OTHER AC MOULDING INJECTION PARTS

AC FRONT PANEL



Material	ABS
Process	Injection Moulding
Wall Thickness	2.5 ± 0.3 mm
Weight	950 ± 30 g
Color	Off White

AC SIDE PANEL



Material	ABS
Process	Injection Moulding
Wall Thickness	2.2 ± 0.3 mm
Weight	850 ± 30 g
Color	Off White

AC TOP COVER



Material	ABS
Process	Injection Moulding
Wall Thickness	2.2 ± 0.3 mm
Weight	700 ± 30 g
Color	Off White

AC CONTROL BOX COVER




Material	ABS
Process	Injection Moulding
Wall Thickness	2.0 ± 0.3 mm
Weight	250 ± 10 g
Color	Off White

FAN MOTOR COVER (ODU)



Material	PP + 20% GF
Process	Injection Moulding
Wall Thickness	2.2 ± 0.3 mm
Weight	180 ± 10 g
Color	Off White / Grey

FAN MOTOR BASE (ODU)



Material	PP + 20% GF
Process	Injection Moulding
Wall Thickness	2.2 ± 0.3 mm
Weight	160 ± 10 g
Color	Off White / Grey


DRAIN PAN (IDU)




Material	ABS
Process	Injection Moulding
Wall Thickness	2.0 ± 0.3 mm
Weight	600 ± 20 g
Color	Off White

4. TYPICAL CONSTRUCTION DETAILS

WINDOW AC FRONT GRILL (SECTION VIEW)




AC FAN BLADE (SECTION VIEW)



TANGENTIAL FAN (SECTION VIEW)



TYPICAL RIB DESIGN (ALL PARTS)



KEY FEATURES

- ✓ High impact & heat resistant material
- ✓ UV stabilized for long life
- ✓ Excellent dimensional accuracy
- ✓ Smooth finish & superior aesthetics
- ✓ Designed for easy assembly & fitment
- ✓ 100% inspection before dispatch

OEM CUSTOMIZATION

- ✓ Customized design as per drawing / sample
- ✓ Dedicated tooling & fixtures
- ✓ Multiple colour options available
- ✓ Low MOQ & on-time delivery
- ✓ 100% quality assurance
- ✓ Long term supply partnership

APPLICATIONS



Window AC



Split AC
(IDU & ODU)



VRF / VRV
Systems



Commercial
AC Systems



Industrial
Applications



SAFE POWER.
TOTAL PROTECTION.



PREMIUM QUALITY.
BUILT TO LAST.



POWERING PERFORMANCE
EVERY TIME.



MADE IN INDIA.
TRUSTED GLOBALLY.



+91 124 436 9700
info@hadrons.co.in
www.hadrons.co.in