

## WIEN2k 21.1 Install with gfortran

July 10, 2022

Linux Operating System Version (lsb\_release -a): Ubuntu 22.04 LTS

Fortran Compiler Version (gfortran --version): gfortran 11.2.0

WIEN2k Version (cat \$WIENROOT/WIEN2k\_VERSION): 21.1 (Release 14/4/2021)

The Ubuntu 22.04 LTS was already installed, but if that is needed it should be available at:

<https://ubuntu.com/download/desktop>

Operating system packages that were needed were installed before proceeding with step 1 given below. If that hasn't been done, then install them:

```
username@computername:~$ sudo apt update
```

```
...
```

```
username@computername:~$ sudo apt upgrade
```

```
...
```

```
username@computername:~$ sudo apt install tcsh gfortran make autoconf libtool git
```

```
...
```

```
username@computername:~$ sudo apt install gnuplot gnuplot-x11 libgd-dev
```

```
...
```

```
username@computername:~$ sudo apt install libquadmath0 build-essential libglu1-mesa-dev libtogl-dev tcl-dev tk-dev libfftw3-dev libxmu-dev
```

```
...
```

Note: If prompted with "Do you want to continue [Y/n]", enter: Y.

The XCrySDen 1.6.2 was installed using:

```
username@computername:~$ sudo apt install xcrysdn
```

Of note, for xcrysdn to work, you may need to set Wayland to X as described at:

<https://askubuntu.com/questions/1410256/how-do-i-use-x-instead-of-wayland-on-22-04>

1. The following was entered into the terminal to install libxc:

```
username@computername:~/Desktop$ cd ~
```

```
username@computername:~$ wget
```

```
http://www.tddft.org/programs/libxc/down.php?file=5.2.3/libxc-5.2.3.tar.gz
```

```
...
```

```
username@computername:~$ tar xvf down.php\?file=5.2.3%2Flibxc-5.2.3.tar.gz
```

```
...
```

```
username@computername:~$ cd libxc-5.2.3/
```

```
username@computername:~/libxc-5.2.3$ autoreconf -i --force
```

```
...
```

```
username@computername:~/libxc-5.2.3$ ./configure FC=gfortran CC=gcc --prefix=$HOME/libxc-5.2.3
```

```
...
username@computername:~/libxc-5.2.3$ make
...
username@computername:~/libxc-5.2.3$ make check
...
PASS: xc-run_testsuite
```

```
=====
Testsuite summary for libxc 5.2.3
=====
```

```
=====
# TOTAL: 1
# PASS: 1
# SKIP: 0
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
```

```
...
username@computername:~/libxc-5.2.3$ make install
...
username@computername:~/libxc-5.2.3$ ls ~/libxc-5.2.3/lib
libxc.a libxcf03.a libxcf03.la libxcf90.a libxcf90.la libxc.la pkgconfig
```

2. The following was entered into the terminal to install OpenBLAS:

```
username@computername:~/libxc-5.2.3$ cd ~
username@computername:~$ git clone https://github.com/xianyi/OpenBLAS.git
...
username@computername:~$ cd OpenBLAS/
username@computername:~/OpenBLAS$ make FC=gfortran CC=gcc
...
OpenBLAS build complete. (BLAS CBLAS LAPACK LAPACKE)

OS           ... Linux
Architecture ... x86_64
BINARY       ... 64bit
C compiler   ... GCC (cmd & version : gcc (Ubuntu 11.2.0-19ubuntu1) 11.2.0)
Fortran compiler ... GFORTRAN (cmd & version : GNU Fortran (Ubuntu 11.2.0-19ubuntu1) 11.2.0)
Library Name  ... libopenblas_zenp-r0.3.20.a (Multi-threading; Max num-threads is 12)
...
username@computername:~/OpenBLAS$ ls ~/OpenBLAS/libopenblas*
/home/username/OpenBLAS/libopenblas.a
```

```

/home/username/OpenBLAS/libopenblas.so
/home/username/OpenBLAS/libopenblas.so.0
/home/username/OpenBLAS/libopenblas_zenp-r0.3.20.a
/home/username/OpenBLAS/libopenblas_zenp-r0.3.20.so
username@computername:~/OpenBLAS$ gedit ~/.bashrc
...
XCRYSDEN_TOPDIR=/usr/bin
XCRYSDEN_LIB_BINDIR=/usr/lib/
export XCRYSDEN_TOPDIR XCRYSDEN_LIB_BINDIR

export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/home/username/OpenBLAS
...
username@computername:~/OpenBLAS$ source ~/.bashrc

```

3. The following was entered into the terminal to install Open MPI:

```

username@computername:~/OpenBLAS$ cd ~
username@computername:~$ wget https://download.open-mpi.org/release/open-mpi/v4.1/openmpi-4.1.4.tar.gz
...
username@computername:~$ tar xvf openmpi-4.1.4.tar.gz
...
username@computername:~$ cd openmpi-4.1.4/
username@computername:~/openmpi-4.1.4$ ./configure --prefix=$HOME/openmpi-4.1.4
...
Open MPI configuration:
-----
Version: 4.1.4
Build MPI C bindings: yes
Build MPI C++ bindings (deprecated): no
Build MPI Fortran bindings: mpif.h, use mpi, use mpi_f08
MPI Build Java bindings (experimental): no
Build Open SHMEM support: false (no spml)
Debug build: no
Platform file: (none)

Miscellaneous
-----
CUDA support: no
HWLOC support: internal
Libevent support: internal
Open UCC: no
PMIx support: Internal

Transports
-----

```

Cisco usNIC: no  
Cray uGNI (Gemini/Aries): no  
Intel Omnipath (PSM2): no  
Intel TrueScale (PSM): no  
Mellanox MXM: no  
Open UCX: no  
OpenFabrics OFI Libfabric: no  
OpenFabrics Verbs: no  
Portals4: no  
Shared memory/copy in+copy out: yes  
Shared memory/Linux CMA: yes  
Shared memory/Linux KNEM: no  
Shared memory/XPMEM: no  
TCP: yes

#### Resource Managers

-----  
Cray Alps: no  
Grid Engine: no  
LSF: no  
Moab: no  
Slurm: yes  
ssh/rsh: yes  
Torque: no

#### OMPI File Systems

-----  
DDN Infinite Memory Engine: no  
Generic Unix FS: yes  
IBM Spectrum Scale/GPFS: no  
Lustre: no  
PVFS2/OrangeFS: no

username@computername:~/openmpi-4.1.4\$ make all install

...

username@computername:~/openmpi-4.1.4\$ gedit ~/.bashrc

...

export PATH=\$PATH:/home/username/openmpi-4.1.4/bin

export

LD\_LIBRARY\_PATH=\$LD\_LIBRARY\_PATH:/home/username/OpenBLAS:/home/username/  
openmpi-4.1.4/lib

...

username@computername:~/openmpi-4.1.4\$ source ~/.bashrc

username@computername:~/openmpi-4.1.4\$ which mpicc  
/home/username/openmpi-4.1.4/bin/mpicc

4. The following was entered into the terminal to install fftw:

```
username@computername:~/openmpi-4.1.4$ cd ~
username@computername:~$ wget http://www.fftw.org/fftw-3.3.10.tar.gz
...
username@computername:~$ tar xvf fftw-3.3.10.tar.gz
...
username@computername:~$ cd fftw-3.3.10/
username@computername:~/fftw-3.3.10$ ./configure FCC=gfortran CC=gcc MPICC=mpicc --
enable-mpi --prefix=$HOME/fftw-3.3.10
...
username@computername:~/fftw-3.3.10$ make
...
username@computername:~/fftw-3.3.10$ make install
...
username@computername:~/fftw-3.3.10$ ls ~/fftw-3.3.10/include ~/fftw-3.3.10/lib
/home/username/fftw-3.3.10/include:
fftw3.f  fftw3.h  fftw3l-mpi.f03  fftw3-mpi.h
fftw3.f03  fftw3l.f03  fftw3-mpi.f03  fftw3q.f03

/home/username/fftw-3.3.10/lib:
cmake  libfftw3.a  libfftw3.la  libfftw3_mpi.a  libfftw3_mpi.la  pkgconfig
```

5. The following was entered into the terminal to install ScaLAPACK:

```
username@computername:~/fftw-3.3.10$ cd ~
username@computername:~$ wget https://github.com/Reference-
ScaLAPACK/scalapack/archive/refs/tags/v2.2.0.tar.gz
...
username@computername:~$ tar xvf v2.2.0.tar.gz
...
username@computername:~$ cd scalapack-2.2.0/
username@computername:~/scalapack-2.2.0$ cp SLmake.inc.example SLmake.inc
username@computername:~/scalapack-2.2.0$ gedit SLmake.inc
username@computername:~/scalapack-2.2.0$ cat SLmake.inc
#####
#
# Program:      ScaLAPACK
#
# Module:      SLmake.inc
#
# Purpose:     Top-level Definitions
#
# Creation date: February 15, 2000
#
```

```

# Modified:      October 13, 2011
#
# Send bug reports, comments or suggestions to scalapack@cs.utk.edu
#
#####
#
# C preprocessor definitions: set CDEFS to one of the following:
#
# -DNoChange (fortran subprogram names are lower case without any suffix)
# -DUpCase   (fortran subprogram names are upper case without any suffix)
# -DAdd_     (fortran subprogram names are lower case with "_" appended)

CDEFS      = -DAdd_

#
# The fortran and C compilers, loaders, and their flags
#

FC          = mpifort -fallow-argument-mismatch
CC          = mpicc
NOOPT       = -O0
FCFLAGS     = -O3
CCFLAGS     = -O3
FCLOADER    = $(FC)
CCLOADER    = $(CC)
FCLOADFLAGS = $(FCFLAGS)
CCLOADFLAGS = $(CCFLAGS)

#
# The archiver and the flag(s) to use when building archive (library)
# Also the ranlib routine. If your system has no ranlib, set RANLIB = echo
#

ARCH        = ar
ARCHFLAGS   = cr
RANLIB      = ranlib

#
# The name of the ScaLAPACK library to be created
#

SCALAPACKLIB = libscalapack.a

#
# BLAS, LAPACK (and possibly other) libraries needed for linking test programs
#

```

```

BLASLIB    = -L/home/username/OpenBLAS -lopenblas
LAPACKLIB   =
LIBS       = $(LAPACKLIB) $(BLASLIB)
username@computername:~/scalapack$ make
...
username@computername:~/scalapack$ gedit ~/.bashrc
...
export
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/home/username/OpenBLAS:/home/username/
openmpi-4.1.4/lib:/home/username/scalapack-2.2.0
...
username@computername:~/scalapack-2.2.0$ source ~/.bashrc
username@computername:~/scalapack-2.2.0$ ls ~/scalapack-2.2.0/lib*
/home/username/scalapack/libscalapack.a

```

6. Go to:  
[http://www.wien2k.at/reg\\_user/index.html](http://www.wien2k.at/reg_user/index.html)
7. Click "Code download (after registration)"
8. Enter your username and password that you were given when you purchased WIEN2k.
9. Click the link "here" in "You can download the complete source code (about 140 MB) from here" to download "WIEN2k\_21.1.tar". You should now have the source code package for WIEN2k 21.1.
10. If you have the folder "WIEN2k" in your Linux operating system home directory (for example at /home/username/WIEN2k, where username is replaced by your user name). You can rename it something else, such as "WIEN2k19.2".
11. The following was entered into the terminal to install WIEN2k 21.1:

```

username@computername:~/scalapack-2.2.0$ cd ~
username@computername:~$ mkdir WIEN2k
username@computername:~$ cd WIEN2k/
username@computername:~/WIEN2k$ ls
WIEN2k_21.1.tar
username@computername:~/WIEN2k$ tar xvf WIEN2k_21.1.tar
...
username@computername:~/WIEN2k$ gunzip *.gz
username@computername:~/WIEN2k$ chmod +x ./expand_lapw
username@computername:~/WIEN2k$ export LC_NUMERIC=en_US.UTF-8
username@computername:~/WIEN2k$ ./expand_lapw
...
continue (y/n)

```

y  
...

Applied patches at: <https://github.com/gsabowien2k-patches/tree/master/21.1>

username@computername:~/WIEN2k\$ ./siteconfig

...

continue or stop (c/s) c

Press RETURN to continue

...

Selection: LG

...

Press RETURN to continue

...

Your compiler: gfortran

...

Your compiler: gcc

...

Press RETURN to continue

...

Hit Enter to continue

...

Would you like to use LIBXC (usually not needed, ONLY for experts who want to play with different DFT options. It must have been installed before)? (y,N):

y

...

Do you want to automatically search for LIBXC installations? (Y,n):

Y

Please specify a comma separated list of directories to search! (If no list is entered, /usr/lib64, /usr/local and /opt will be searched as default):  
/home/username/libxc-5.2.3

...

Pick one of the following (enter the number of the line of your choice or 0 to manually specify a path)!:

/home/username/libxc-5.2.3/src/.libs/libxc.a

/home/username/libxc-5.2.3/lib/libxc.a

2

...

Press RETURN to continue

...

Do you want to automatically search for FFTW installations? (Y,n):

Y

Please specify a comma separated list of directories to search! (If no list is entered, /usr/lib64, /usr/local and /opt will be searched as default):  
/home/username/fftw-3.3.10



Finding the required fftw3 library-files in /home/username/fftw-3.3.10 ....

/home/username/fftw-3.3.10/.libs/libfftw3.a

/home/username/fftw-3.3.10/lib/libfftw3.a

Your present FFTW choice is: FFTW3

Present FFTW root directory is:

Do you want to use a FFTW version from the list above? (Y,n):

Y

Please enter the line number of the chosen version or enter 0 to manually specify your choice!:

2

...

Please specify the target architecture of your FFTW library (e.g. lib64) or accept present choice (enter): lib

...

Please specify the name of your FFTW library or accept present choice (enter): fftw3

...

Is this correct? (Y,n): Y

...

Selection: R

Real libraries=-L/home/username/OpenBLAS -lopenblas -lpthread

...

Selection: O

...

Compiler options=-ffree-form -O2 -ftree-vectorize -march=native -ffree-line-length-none -ffpe-summary=none -fallow-argument-mismatch

...

Selection: X

...

Selection: F

Enter the name of your LIBXC fortran interface!: xcf03

...

Selection: B

...

Current settings:

M OpenMP switch: -fopenmp

O Compiler options: -ffree-form -O2 -ftree-vectorize -march=native -ffree-line-length-none -ffpe-summary=none -fallow-argument-mismatch

L Linker Flags: \$(FOPT) -L../SRC\_lib

P Preprocessor flags '-DParallel'

R R\_LIBS (LAPACK+BLAS): -L/home/username/OpenBLAS -lopenblas -lpthread

F FFTW options: -DFFTW3 -I/home/username/fftw-3.3.10/include

FFTW-LIBS: -L/home/username/fftw-3.3.10/lib -lfftw3

X LIBX options: -DLIBXC -I/home/username/libxc-5.2.3/include

LIBXC-LIBS: -L/home/username/libxc-5.2.3/lib -lxcf03 -lxc

```

...
Selection: S
...
    Press RETURN to continue
...
    Shared Memory Architecture? (y/N):y
    Do you know/need a command to bind your jobs to specific nodes?
    (like taskset -c). Enter N / your_specific_command: N
...
    Do you have MPI, ScaLAPACK, ELPA, or MPI-parallel FFTW installed and intend
    to run finegrained parallel?
...
    (y/N) y
...
    Your compiler: mpifort
...
    Do you want to use a present ScaLAPACK installation? (Y,n): Y
...
    Please specify the target architecture of your ScaLAPACK libraries (e.g. intel64)!:
    Please specify the root path of your ScaLAPACK installation!:
    ScaLAPACK root: /home/username/scalapack-2.2.0
    Please specify the name of your ScaLAPACK library!:
    ScaLAPACK library: scalapack
    Please specify the root path of your BLACS installation!:
    BLACS root:
    Please specify the name of your BLACS library!:
    BLACS library:
...
    Is this correct? (Y,n): Y
...
    Do you want to use ELPA? (y,N):
    N

        Press RETURN to continue
...
    Please enter your choice of additional libraries!:
    $(R_LIBS) -lmpi
...
    Is this correct? (Y,n): Y
...
    Please specify your parallel compiler options or accept the recommendations (Enter - default)!:
    -ffree-form -O2 -ftree-vectorize -march=native -ffree-line-length-none -ffpe-summary=none -
    fallow-argument-mismatch

    Please specify your MPIRUN command or accept the recommendations (Enter - default)!:

```

Please specify your parallel OMP\_SWITCH (type "del" to blank it)  
or accept the recommendations (Enter - default)!:

Please specify your MPIRUN command or accept the recommendations (Enter - default)!:

Press RETURN to continue

...

Current settings:

Parallel compiler : mpifort  
SCALAPACK\_LIBS : -L/home/username/scalapack-2.2.0/ -lscalapack  
FFTW\_PLIBS : -lfftw3\_mpi  
ELPA\_OPT :  
ELPA\_LIBS :  
FPOPT(par.comp.options): -ffree-form -O2 -ftree-vectorize -march=native -ffree-line-length-none -ffpe-summary=none  
OMP\_SWITCH : -fopenmp  
MPIRUN command : mpirun -np \_NP\_ -machinefile \_HOSTS\_\_EXEC\_

parallel execution:

RP\_LIBS : \$(R\_LIBS) -lmpi

...

Selection: S

...

Press RETURN to continue

...

Selection: Q

...

Selection: A

...

Compile time errors (if any) were:

<= It should be blank here if successful.

Check file compile.msg in the corresponding SRC\_\* directory for the  
compilation log and more info on any compilation problem.

Press RETURN to continue

...

Please enter the full path of the perl program: /usr/bin/perl

...

Press RETURN to continue

...

Please enter the full path to your temporary directory: /tmp

...

Press RETURN to continue

...

12. If it is the first time installing WIEN2k on the computer, enter in the terminal:

```
username@computername:~/WIEN2k$ ./userconfig_lapw
```

...

Specify your preferred editor (default is emacs):  
editor shall be: gedit

Set editor to gedit (Y/n) Y

Specify your preferred DATA directory, where your cases should be  
stored (for /home/username/WIEN2k, just enter RETURN key):  
DATA directory: /home/username/wiendata

Set DATA directory to /home/username/wiendata (Y/n) Y

Specify your preferred scratch directory, where big case.vector files  
can be stored (Recommended is a local directory (maybe /scratch), not a  
NFS directory. For your working directory, just enter RETURN key):  
scratch directory:

Set scratch directory to working directory (Y/n) Y

Specify your program to read pdf files (default is okular)  
(on some Linux systems use xpdf, evince, pdfstudio, ...):evince

Set PDFREADER to evince (Y/n) Y

WIEN2k can use OpenMP parallelization on multicore computers.  
For details please read the "Parallelization section" of the Usersguide.  
Your present computer has 4 cores, but more than 4 (8) cores is useless.  
How many cores do you want to use by default (4):1

Set OMP\_NUM\_THREADS to 1 (Y/n) Y

!!! The following lines will be added to your .bashrc file if you continue !!!  
A copy of your current .bashrc will be saved under .bashrc.savelapw !

```
# added by WIEN2k: BEGIN
```

```
# -----
```

```
alias lsi="ls -aslp *.in*"
```

```

alias lso="ls -aslp *.output*"
alias lsd="ls -aslp *.def"
alias lsc="ls -aslp *.clm*"
alias lss="ls -aslp *.scf* */*scf"
alias lse="ls -aslp *.error"
alias LS="ls -alsp |grep /"
alias pslapw="ps -ef |grep "lapw""
alias cdw="cd /home/username/wiendata"
if [ "$OMP_NUM_THREADS" = "" ]; then export OMP_NUM_THREADS=1; fi
#export LD_LIBRARY_PATH=.....
export EDITOR="gedit"
export SCRATCH=./
if [ "$WIENROOT" = "" ]; then export WIENROOT=/home/username/WIEN2k; fi
export W2WEB_CASE_BASEDIR=/home/username/wiendata
export STRUCTEDIT_PATH=$WIENROOT/SRC_structeditor/bin
export PDFREADER=evince
export PATH=$WIENROOT:$STRUCTEDIT_PATH:$WIENROOT/SRC_IRelast/script-
elastic:$PATH:.
export OCTAVE_EXEC_PATH=${PATH}::
export OCTAVE_PATH=${STRUCTEDIT_PATH}::

ulimit -s unlimited
alias octave="octave -p $OCTAVE_PATH"
# -----
Do you want to continue (Y/n)? Y
...
Edit .rhosts file now? (y/N) N
...
username@computername:~/WIEN2k$ source ~/.bashrc

```

13. To setup or start w2web, enter in the terminal:

```

username@computername:~/WIEN2k$ w2web
#####
# w2web starter                                     #
# Copyright (C) 2001 luitz.at                       #
#####
w2web installer on host computername

#####
# w2web installer                                     #
# Copyright (C) 2001 luitz.at                       #
#####

Checking for Installation in /home/username/.w2web/computername

```

Creating /home/username/.w2web  
Creating /home/username/.w2web/computername  
conf directory does not exist - creating it.  
logs directory does not exist - creating it.  
sessions directory does not exist - creating it.  
tmp directory does not exist - creating it.

Installing w2web files ...  
Please answer these questions for proper installation.  
Just press enter for the default value of (in brackets).

Please enter the username: [admin] username  
Please enter the password: [password] password  
username:password  
Remember these. You will need them when you log in.

Select the port to run on: [7890]  
Running on port 7890

Please enter this system's hostname: [computername] localhost  
Using localhost

Is this your master node?: [y] y  
Installing... Attempting to start now...

Trying to start /home/username/WIEN2k/SRC\_w2web/bin/w2web  
w2web server started, now point your web browser to  
<http://localhost:7890>

done.

14. The WIEN2k 21.1 installation is now complete. To test if WIEN2k installed okay or not, run the TiC example. Additional details of the TiC example are given in the WIEN2k 21.1 usersguide (section “3 Quick Start” starting on page 13) [1].

[1] [http://susi.theochem.tuwien.ac.at/reg\\_user/textbooks/usersguide.pdf](http://susi.theochem.tuwien.ac.at/reg_user/textbooks/usersguide.pdf)