

PROGRAM 1:-

```
GNU nano 8.7.1
#include<stdio.h>
#include<stdlib.h>
#include<unistd.h>
#include<sys/wait.h>

int main(){
char cmd[100];
printf("Enter Linux Command: ");
scanf("%s",cmd);
pid_t pid = fork();
if(pid==0){
printf("Child PID: %d\n",getpid());
execlp(cmd,cmd,NULL);
perror("Execution failed");
}
else if(pid>0){
printf("Parent PID: %d\n",getpid());
wait(NULL);
printf("Child process completed. \n");
}
else{
printf("Fork Failed\n");
}
return 0;
}
```

```
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ gcc ques1.c -o ques1
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ ./ques1
Enter Linux Command: uname
Parent PID: 545
Child PID: 546
Linux
Child process completed.
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ |
```

PROGRAM 2:-

```
#include<stdio.h>
#include<fcntl.h>
#include<unistd.h>
int main(){
int src,dest;
char buffer[1024];
int bytes;
src = open("input.txt",O_RDONLY);
if(src < 0){
printf("Cannot open source file\n");
return 1;
}
dest = open("output.txt",O_WRONLY|O_CREAT|O_TRUNC , 0644);
while((bytes = read(src,buffer,sizeof(buffer)))>0){
write(dest,buffer,bytes);
}
close(src);
close(dest);
printf("File copied successfully.\n");
return 0;
}
```

OUTPUT:-

```
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ gcc ques2.c -o ques2
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ ./ques2
Cannot open source file
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ nano input.txt
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ gcc ques2.c -o ques2
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ ./ques2
File copied successfully.
sai_pavani@Sai-Pavani:~/OS_LAB/prac_1_2$ |
```