

```
GNU nano 8.7.1 file_create.c
#include<stdio.h>
#include<sys/types.h>
#include<sys/stat.h>

int main(){

    if(mkfifo("myfifo",0666)==-1){
        perror("mkfifo");
        return 1;
    }
    printf("FIFO created\n");
    return 0;
}
```

```
GNU nano 8.7.1 file_fifo_read.c
#include<stdio.h>
#include<fcntl.h>
#include<unistd.h>
int main()
{
    int fd;
    char buffer[100];
    fd = open("myfifo",O_RDONLY);
    read(fd,buffer,sizeof(buffer));
    printf("Received: %s\n",buffer);
    close(fd);
    return 0;
}
```

```
GNU nano 8.7.1 file_fifo_write.c
#include<stdio.h>
#include<fcntl.h>
#include<unistd.h>
#include<string.h>

int main(){
int fd;
char message[]="Hello from Writer";
fd = open("myfifo", O_WRONLY);
write(fd,message,strlen(message)+1);
close(fd);
printf("Message sent\n");
return 0;
}
```

```
sai_pavani@Sai-Pavani:~/OS_LAB$ gcc file_fifo_write.c -o file_fifo_write
sai_pavani@Sai-Pavani:~/OS_LAB$ ./file_fifo_write
Message sent
```

```
sai_pavani@Sai-Pavani:~/OS_LAB$ nano file_fifo_read.c
sai_pavani@Sai-Pavani:~/OS_LAB$ gcc file_fifo_read.c -o file_fifo_read
sai_pavani@Sai-Pavani:~/OS_LAB$ ./file_fifo_read
Received:
sai_pavani@Sai-Pavani:~/OS_LAB$
```