

```

GNU nano 8.7.1                                     global_address.c
#include <stdio.h>
#include <stdlib.h>

int global = 10;
int bss_variable;

int main() {

    int local = 20;

    int *heap = malloc(sizeof(int));
    *heap = 30;

    printf("Code address    : %p\n", (void *)main);
    printf("Data address     : %p\n", (void *)&global);
    printf("BSS address      : %p\n", (void *)&bss_variable);
    printf("Heap address      : %p\n", (void *)heap);
    printf("Stack address     : %p\n", (void *)&local);

    free(heap);

    return 0;
}

```

```

Virtual address of x = 0x7fffd271904
sai_pavani@Sai-Pavani:~/OS_LAB$ nano virtual_address.c
sai_pavani@Sai-Pavani:~/OS_LAB$ nano global_address.c
sai_pavani@Sai-Pavani:~/OS_LAB$ gcc global_address.c -o global_address
sai_pavani@Sai-Pavani:~/OS_LAB$ ./global_address
Code address    : 0x5c42f4f601a9
Data address     : 0x5c42f4f63010
BSS address      : 0x5c42f4f63018
Heap address     : 0x5c42fff01010
Stack address    : 0x7ffcdc4c63cc
sai_pavani@Sai-Pavani:~/OS_LAB$ |

```