

GNU nano 8.7.1

skill6.c *

```

#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <string.h>
#include <stdlib.h>

int main() {
    char command[100];

    printf("Enter command: ");
    fgets(command, sizeof(command), stdin);

    command[strcspn(command, "\n")] = '\0';

    pid_t pid = fork();

    if (pid < 0) {
        perror("fork");
        return 1;
    }

    if (pid == 0) {
        char *args[20];
        int i = 0;

        char *token = strtok(command, " ");

        while (token != NULL && i < 19) {
            args[i++] = token;
            token = strtok(NULL, " ");
        }

        args[i] = NULL;

        execvp(args[0], args);

        perror("execvp failed");
        exit(1);
    } else {
        wait(NULL);
        printf("Command execution completed.\n");
    }

    return 0;
}

```

```

sai_pavani@Sai-Pavani:~/OS_SKILL$ nano skill6.c
sai_pavani@Sai-Pavani:~/OS_SKILL$ gcc skill6.c -o skill6
sai_pavani@Sai-Pavani:~/OS_SKILL$ ./skill6
Enter command: ls
shellforge      skill13_input.txt  skill15_combined.txt  skill14      skill6      skill_11      skill_13      skill_15      skill_17      skill_19      skill_21      skill_23      skill_8      temp
shellforge.c    skill13_output.txt skill121_errors.log   skill14.c    skill6.c    skill_11.c.c  skill_13.c.c  skill_15.c.c  skill_17.c.c  skill_19.c.c  skill_21.c.c  skill_23.c.c  skill_8.c.c
simplecommandloop skill14_append.txt  skill13              skill15      skill_10    skill_12      skill_14      skill_16      skill_18      skill_20      skill_22      skill_24      skill_9
simplecommandloop.c skill14_error.txt   skill13.c            skill15.c    skill_10.c.c skill_12.c.c  skill_14.c.c  skill_16.c.c  skill_18.c.c  skill_20.c.c  skill_22.c.c  skill_24.c.c  skill_9.c.c
Command execution completed.
sai_pavani@Sai-Pavani:~/OS_SKILL$

```