

PRACTICAL 3 AND 4

Program 3:-

```
GNU nano 8.7.1 parentchildprocess.c *
#include<stdio.h>
#include<unistd.h>
#include<sys/wait.h>
int main(){

    pid_t pid=fork();
    if(pid==0){
        printf("Child Process\n");
        printf("PID : %d\n",getpid());
        printf("PPID :%d\n",getppid());
        sleep(10);
    }
    else{
        printf("Parent Process\n");
        printf("PID : %d\n",getpid());
        wait(NULL);
    }
    return 0;
}
```

output:-

```
sai_pavani@Sai-Pavani:~/OS_LAB/prac_3_4$ nano parentchildprocess.c
sai_pavani@Sai-Pavani:~/OS_LAB/prac_3_4$ gcc parentchildprocess.c -o parentchildprocess
sai_pavani@Sai-Pavani:~/OS_LAB/prac_3_4$ ./parentchildprocess
Parent Process
PID : 715
Child Process
PID : 716
PPID :715
```

```

#include<stdio.h>
#include<unistd.h>
#include<sys/wait.h>
int main(){
int i;
for(i=0;i<3;i++){
if(fork()==0){
printf("Child %d PID = %d\n",i+1,getpid());
return 0;
}
}
for(i=0;i<3;i++){
wait(NULL);
}
printf("All children completed.\n");
return 0;
}

```

```

sai_pavani@Sai-Pavani:~/OS_LAB/prac_3_4$ nano multiplechildproces
ss.c
sai_pavani@Sai-Pavani:~/OS_LAB/prac_3_4$ gcc multiplechildproces
s.c -o multiplechildprocess
sai_pavani@Sai-Pavani:~/OS_LAB/prac_3_4$ ./multiplechildprocess
Child 1 PID = 1097
Child 2 PID = 1098
Child 3 PID = 1099
All children completed.

```