



## Hyperparameter tuning, Batch Normalization, Programming Frameworks

Quiz, 10 questions

10/10 points  
(100%)

✓ **Congratulations! You passed!**

[Next Item](#)



1 / 1  
point

1. If searching among a large number of hyperparameters, you should try values in a grid rather than random values, so that you can carry out the search more systematically and not rely on chance. True or False?

☐ True

☒ False

Correct



1 / 1  
point

2. Every hyperparameter, if set poorly, can have a huge negative impact on training, and so all hyperparameters are about equally important to tune well. True or False?

☐ True

☒ False

Correct

Yes. We've seen in lecture that some hyperparameters, such as the learning rate, are more critical than others.



1 / 1  
point

3. During hyperparameter search, whether you try to babysit one model ("Panda" strategy) or train a lot of models in parallel ("Caviar") is largely determined by:

☐ Whether you use batch or mini-batch optimization

☐ The presence of local minima (and saddle points) in your neural network

☒ The amount of computational power you can access

Correct

☐ The number of hyperparameters you have to tune



1 / 1  
point

4. If you think  $\beta$  (hyperparameter for momentum) is between 0.9 and 0.99, which of the following is the recommended way to sample a value for beta?



```
1 r = np.random.rand()  
2 beta = r*0.09 + 0.9
```



```
1 r = np.random.rand()  
2 beta = 1-10**(-r - 1)
```

Correct



1 / 1  
point

5. Finding good hyperparameter values is very time-consuming. So typically you should do it once at the start of the project, and try to find very good hyperparameters so that you don't ever have to revisit tuning them again. True or false?



True



False

Correct



1 / 1  
point

6. In batch normalization as presented in the videos, if you apply it on the  $l$ th layer of your neural network, what are you normalizing?



$a^{[l]}$



$W^{[l]}$



$b^{[l]}$



$z^{[l]}$

Correct



7. In the normalization formula  $z_{norm}^{(i)} = \frac{z^{(i)} - \mu}{\sqrt{\sigma^2 + \epsilon}}$ , why do we use epsilon?

1 / 1  
point



To avoid division by zero

Correct



To speed up convergence



In case  $\mu$  is too small



To have a more accurate normalization



8. Which of the following statements about  $\gamma$  and  $\beta$  in Batch Norm are true?

1 / 1  
point



$\beta$  and  $\gamma$  are hyperparameters of the algorithm, which we tune via random sampling.

Un-selected is correct



The optimal values are  $\gamma = \sqrt{\sigma^2 + \epsilon}$ , and  $\beta = \mu$ .

Un-selected is correct



They set the mean and variance of the linear variable  $z^{[L]}$  of a given layer.

Correct



They can be learned using Adam, Gradient descent with momentum, or RMSprop, not just with gradient descent.

Correct



There is one global value of  $\gamma \in \mathfrak{R}$  and one global value of  $\beta \in \mathfrak{R}$  for each layer, and applies to all the hidden units in that layer.

Un-selected is correct



1 / 1  
point

9. After training a neural network with Batch Norm, at test time, to evaluate the neural network on a new example you should:

- ☐ Use the most recent mini-batch's value of  $\mu$  and  $\sigma^2$  to perform the needed normalizations.
- ☒ Perform the needed normalizations, use  $\mu$  and  $\sigma^2$  estimated using an exponentially weighted average across mini-batches seen during training.
- ☐ Skip the step where you normalize using  $\mu$  and  $\sigma^2$  since a single test example cannot be normalized.
- ☐ If you implemented Batch Norm on mini-batches of (say) 256 examples, then to evaluate on one test example, duplicate that example 256 times so that you're working with a mini-batch the same size as during training.

Correct



1 / 1  
point

10. Which of these statements about deep learning programming frameworks are true? (Check all that apply)

- ☐ Deep learning programming frameworks require cloud-based machines to run.
- ☒ Even if a project is currently open source, good governance of the project helps ensure that the it remains open even in the long term, rather than become closed or modified to benefit only one company.
- ☒ A programming framework allows you to code up deep learning algorithms with typically fewer lines of code than a lower-level language such as Python.

Un-selected is correct

Correct

Correct