Introduction to Programming with Scientific Applications

Gerth Stølting Brodal
Department of Computer Science
Aarhus University

Course evaluation

”The first lecture was intimidating and overwhelming”

Lecturer

Name	Gerth Stølting Brodal
Research	Algorithms and Data Structures (Computer Science)
Teaching	
2018 -	BSc course on Introduction to Programming with Scientific Applications
2003 -	BSc course on Introduction to Algorithms and Data Structures
1999 - 17	MSc courses on Computational Geometry, Algorithm Engineering, Advanced Data Structures, External Memory Algorithms and Data Structures
Python	Advanced Beginner

Command Prompt - python

```
Microsoft Windows [Version 10.0.26100.7171]
(c) Microsoft Corporation. All rights reserved.

C:\Users\au121>pip install pyfiglet
Collecting pyfiglet
  Using cached pyfiglet-1.0.4-py3-none-any.whl.metadata (7.4 kB)
Using cached pyfiglet-1.0.4-py3-none-any.whl (1.8 MB)
Installing collected packages: pyfiglet
Successfully installed pyfiglet-1.0.4

C:\Users\au121>python
Python 3.14.0 (tags/v3.14.0:ebf955d, Oct  7 2025, 10:15:03) [MSC v.1944 64 bit (AMD64)] on win32
Type "help", "copyright", "credits" or "license" for more information.
>>> import pyfiglet
>>> print(pyfiglet.figlet_format('Welcome to IPSA'))
__        __   _                            _          ___ ____  ____    _
\ \      / /__| | ___ ___  _ __ ___   ___  | |_ ___   |_ _|  _ \/ ___|  / \
 \ \ /\ / / _ \ |/ __/ _ \| '_ ` _ \ / _ \ | __/ _ \   | || |_) \___ \ / _ \
  \ V  V /  __/ | (_| (_) | | | | | |  __/ | || (_) |  | ||  __/ ___) / ___ \
   \_/\_/ \___|_|\___\___/|_| |_| |_|\___|  \__\___/  |___|_|   |____/_/   \_\


>>> |
```

Course description – kursuskatalog.au.dk/en/course/138411/

Introduction to Programming with Scientific Applications

Description of qualifications

After the course the participants will have knowledge of principles and techniques for systematic **construction** of **programs**.

At the end of the course, the participants will be able to:

- apply constructions of a common programming language,
- develop **well-structured** programs and perform **testing** and **debugging** of these,
- explain fundamental programming concepts and basic algorithmic techniques,
- apply standard **tools for scientific applications**,
- use the documentation for a programming language and available software packages.

Contents

The course gives an introduction to programming with scientific applications. Programming concepts and techniques are introduced using the **Python** programming language. The programming concepts are **illustrated in other programming languages**. The following content is included.

Basic programming constructs: Data types, operators, variables, flow of control, conditionals, loops, functions, recursion, scope, exceptions. *Object orientation*: Abstract data types, classes, inheritance, encapsulation. *Basic algorithmic techniques*: Sorting, binary search, dynamic programming. *Systematic development of programs*: Testing and debugging. File-based input/output, numerical analysis, functional programming. Scientific computing using standard packages for Python.

ECTS 10

Hours - weeks - periods

Lectures 2 x 2 hours/week
TA sessions 1 x 3 hours/week
Study café 3 x 1 hour/week

Language of instruction

Lectures: English. TA classes: Danish/English.

Instructor

Gerth Stølting Brodal

Academic prerequisites

(Some) Linear algebra

Exam

5 hour programming
Aid: Computer without Internet, no AI
7-point grading scale

Prerequisites for examination participation

Submission and approval of 10 mandatory assignments and submission of **1 implementation project**

Notes Grade reflects an overall assessment of implementation project and written examination. Project counts 20% and written exam counts 80%

Question – Primary education?

a) Mathematics
b) Mathematics-Economics
c) Data Science
d) Chemestry
e) Physics
f) Other Science-Technology
g) Other

Question – Programming languages you know?

+750 listed on en.wikipedia.org/wiki/List_of_programming_languages

Question – Programming experience?

For the programming language you know best (if any) please state you proficiency level within the language.

a) None
b) Fundamental awareness (basic knowledge)
c) Novice (limited experience)
d) Intermediate (practical application)
e) Advanced (applied theory)
f) Expert (recognized authority)

Some course practicalities

Primary lecture material = slides

Week	Monday	Tuesday	Wednesday	Thursday	Friday
5	F1	no TA class	F2		
6	F3	TØ1	TØ1 / F4	TØ1	TØ1
7	F5	TØ2	TØ2 / F6	TØ2	TØ2
8	F7	TØ3	TØ3 / F8	TØ3	TØ3
9	F9	TØ4	TØ4 / F10	TØ4	TØ4
10	F11	TØ5	TØ5 / F12	TØ5	TØ5
11	F13	TØ6	TØ6 / F14	TØ6	TØ6
12	F15	TØ7	TØ7 / F16	TØ7	TØ7
13	F17	TØ8	TØ8 / F18	TØ8	TØ8
14	Easter break				
15		-	-	TØ9	TØ9
16	F19	TØ9	TØ9 / F20	TØ10	TØ10
17	F21	TØ10	TØ10 / F22	TØ11	Kapsejlads
18	F23	TØ11	TØ11 / F24	TØ12	TØ11
19	F25	TØ12	TØ12 / F26	TØ13	TØ12
20	F27	TØ13	TØ13 / -	Kr HimFart	TØ13

	Monday	Tuesday	Wednesday	Thursday	Friday
8:15-9:00	Lecture	Hold 2			
9:15-10:00			Study cafe		
10:15-11:00	Study cafe		Lecture	MA1	MA2 DV(EN)
11:15-12:00					
12:15-13:00					
13:15-14:00				DV	
14:15-15:00		FY Hold 1	MØ1 MØ2	Study cafe	
15:15-16:00					
16:15-17:00					
17:15-18:00					

Course page on Brightspace and GitHub

gsbrodal.github.io/ipsa

Course text book – optional

John V. Guttag: **Introduction to Computation and Programming Using Python, Third Edition With Application to Computational Modeling and Understanding Data**. Third Edition. 664 pages. MIT Press, 2021.

- *[Guttag, 2nd Ed., page 8] "The reader should be forewarned that this book is by no means a comprehensive introduction to Python". 3rd Ed. added about 80 pages on introduction to Python.*
- *Covers all basic features of Python enabling you to deal with data in Chapters 1-10 (212 pages) - remaining chapters are applications*
- *Other resources: Google, stackoverflow, Python.org, YouTube, AIs...*

Comparison to a standard text book on the *programming language* Python by Cay Horstmann and Rance Necaise:

Topic **recursion** is covered by Guttag on page 123 (2nd edition on page 50), Horstmann and Necaise do it on page 611

Some other books on Python

O'Reilly, 2013
1684 pages

Wiley, 2016
752 pages

Addison-Wesley, 2015
794 pages

Wiley, 2013
580 pages

Franklin & Beedle, 2016
552 pages

... numerous online introduction texts/courses/videos on Python

Two Python programs

A Python program

Python shell

```
> x = 7
> print(x * x)
| 49
```

- `7` is an *integer literal* – in Python denoted an "`int`"
- `x` is the name of a *variable* that can hold some value
- `=` is assigning a value to a variable
- `*` denotes multiplication
- `print` is the name of a built-in *function*,
  here we call `print` to print the result of 7 * 7
- A program consists of a sequence of *statements*, executed sequentially

Question – What is the result of this program?

Python shell

```
> x = 3
> y = 5
> x = 2
> print(x * y)
```

x assigned new value

a) 10
b) 15
c) 25
d) [15, 10]
e) Error
f) Don’t know

Another Python program using lists

Python shell

```
> a = [13, 27, 7, 42]
> print(a)
| [13, 27, 7, 42]
> print(a[2])
| 7
```

- `[13, 27, 7, 42]` is a *list* containing four integers
- `a[2]` refers to the entry in the list with *index* 2
  (the first element has index 0, i.e. `a[2]` is the 3rd element of the list)
- Note that `print` can also print a list

Question – What is the result of this program?

Python shell

```
> a = [3, 5, 7]
> print(a[1] + a[2])
```

a) 8
b) 10
c) 12
d) 15
e) Don’t know

Why Python ?

⚠ the next slides will be technical

TIOBE Index January 2026

Python #1 Since November 2021

Jan 2026	Jan 2025	Change	Programming Language	Ratings	
1	1		Python	22.61%	-0.6[illegible]
2	4	^	C	10.99%	+2.13%
3	3		Java	8.71%	-1.44%
4	2	v	C++	8.67%	-1.62%
5	5		C#	7.39%	+2.94%
6	6		JavaScript	3.03%	-1.17%
7	9	^	Visual Basic	2.41%	+0.04%
8	8		SQL	2.27%	-0.14%
9	11	^	Delphi/Object Pascal	1.98%	+0.19%
10	18	^^	R	1.82%	+0.81%

The TIOBE Programming Community index is an indicator of the ***popularity of programming languages***. The index is updated once a month. The ratings are based on the number of skilled engineers world-wide, courses and third party vendors. Popular search engines such as Google, Bing, Yahoo!, Wikipedia, Amazon, YouTube and Baidu are used to calculate the ratings. It is important to note that the TIOBE index is not about the *best* programming language or the language in which *most lines of code* have been written. www.tiobe.com

Popularity of programming languages

Most Popular Programming Languages 1958 – 2025 (YouTube)

“Hello World”

- In Java, C, C++ a lot of “{“, “}” and “;” are needed
- Java tends to have a lot of “public…” details that need to be spelled out
- Python is concise

Java

```
public class HelloWorld {
    public static void main( String[] args ) {
        System.out.println( "Hello World!" );
        System.exit( 0 );
    }
}
```

C

```
#include <stdio.h>

int main(int argc, char **argv) {
    printf("Hello World");
    return 0;
}
```

C++

```
#include <iostream>
using namespace std;

int main(int argc, char** argv) {
    cout << "Hello, World!";
    return 0;
}
```

Python 2

```
print "Hello world"
```

Python 3

```
print("Hello world")
```

Why Python ?

- **Short concise code**

(C developed by Dennis Ritchie 1969-73)

C index out of bounds

Debugging is the process of finding and resolving defects or problems within a computer program that prevent correct operation of computer software or a system.

en.wikipedia.org/wiki/Debugging

indexing.c

```c
#include <stdio.h>
int main() {
  int x = 1;
  int A[2] = {2, 3}; // A[0] = 2, A[1] = 3
  printf("x = %d, A = {%d, %d}\n", x, A[0], A[1]);
  A[3] = 42; // index A[3] out of bounds
  printf("x = %d, A = {%d, %d}\n", x, A[0], A[1]);
  return 0;
}
```

Output

```
$ gcc indexing.c
$ ./a.exe
x = 1, A = {2, 3}
x = 42, A = {2, 3}
```

Skipping checking for invalid indexing makes programs faster, but also requires disciplined programming

(C++ was developed by Bjarne Stroustrup 1985)

… and C++ index out of bounds

indexing.cpp

```
#include <iostream>
int main() {
  int x = 1;
  int A[2] = {2, 3}; // A[0] = 2, A[1] = 3
  std::cout << "x = " << x << ", A = {"
            << A[0] << ", " << A[1] << "}" << std::endl;
  A[2] = 42; // index A[2] out of bounds
  std::cout << "x = " << x << ", A = {"
            << A[0] << ", " << A[1] << "}" << std::endl;
  return 0;
}
```

Output

```
$ g++ indexing.cpp
$ ./a.exe
x = 1, A = {2, 3}
x = 42, A = {2, 3}
```

… and C++ `vector` index out of bounds

indexing.cpp

```
#include <iostream>
#include <vector>
int main() {
  std::vector<int> A = {2, 3};  // A[0] = 2, A[1] = 3
  std::vector<int> B = {4, 5};  // B[0] = 4, B[1] = 5
  std::cout << "A={" << A[0] << ", " << A[1] << "}, ";
  std::cout << "B={" << B[0] << ", " << B[1] << "}" << std::endl;
  A[9]=42; // index A[9] out of bounds
  std::cout << "A={" << A[0] << ", " << A[1] << "}, ";
  std::cout << "B={" << B[0] << ", " << B[1] << "}" << std::endl;
  return 0;
}
```

Output

```
$ g++ -std=c++11 indexing-vector.cpp
$ ./a.exe
A={2, 3}, B={4, 5}
A={2, 3}, B={4, 42}
```

(Java was developed by James Gosling 1995)

… and Java index out of bounds exception

indexing.java

```
class IndexingTest{
    public static void main(String args[]){
        int a[] = {20, 21, 22};
        a[5] = 42; // index a[5] out of bounds
    }
}
```

Output

```
$ javac indexing.java
$ java IndexingTest
Exception in thread "main"
java.lang.ArrayIndexOutOfBoundsException: 5
        at IndexingTest.main(indexing.java:5)
```

Java provides error message when running the program

(Python first release by Guido van Rossum 1991)

… and Python index out of bounds exception

indexing.py

```
a = [20, 21, 22]
a[5] = 42  # index a[5] out of bounds
```

Output

```
$ python indexing.py
Traceback (most recent call last):
  File "indexing.py", line 3, in <module>
    a[5] = 42
IndexError: list assignment index out of range
```

Python provides error message when running the program

(Rust created by Graydon Hoare 2006)

Memory safety

The White House 2024 | Press Release: "*Future Software Should Be Memory Safe*" (www.whitehouse.gov)
National Security Agency 2022 | Cybersecurity Information Sheet: *Software Memory Safety* (media.defense.gov)

- C and C++ are flexible but **memory unsafe** programming languages
  - Unintended writes or reads to memory can be exploited by malicious cyber actors
- Python, Java, Rust are examples of memory safe languages
- Rust aims at achieving the efficiency of C by slightly restricting flexibility

indexing.rs

```
fn main() {
    let mut a = [3, 4];
    a[2] = 7;  // Compile error: this operation will panic at runtime
    for i in 2..3 { a[i] = 7 }  // Run-time panic: index out of bounds
    let b = &mut a;
    a[1] = 6;  // Compile error: cannot use `a` because it was mutably borrowed
    (*b)[0] = 5;
    for i in 0..2 { println!("a[{}] = {}", i, a[i]) }
}
```

www.rust-lang.org

Why Python ?

- Short concise code
- **Index out-of-range exceptions**

C++ different ways to print a vector

vector-iterator.cpp

```
#include <iostream>
#include <vector>
int main() {
  // Vector is part of STL (Standard Template Library)
  std::vector<int> A = {20, 23, 26};
  // "C" indexing - since C++98
  for (int i = 0; i < A.size(); i++)
    std::cout << A[i] << std::endl;
  // iterator - since C++98
  for (std::vector<int>::iterator it = A.begin(); it != A.end(); ++it)
    std::cout << *it << std:: endl;
  // "auto" iterator - since C++11
  for (auto it = A.begin(); it != A.end(); ++it)
    std::cout << *it << std:: endl;
  // Range-based for-loop - since C++11
  for (auto e : A)
    std::cout << e << std:: endl;
}
```

elegant

Java - different ways to print a vector

vector-iterator.java

```
import java.util.Vector;
import java.util.Iterator;

class IteratorTest{
   public static void main(String[] args) {
       Vector<Integer> a = new Vector<Integer>();
       a.add(7);
       a.add(42);
       // "C" for-loop & get method
       for (int i = 0; i < a.size(); i++)
          System.out.println(a.get(i));
       // iterator
       for (Iterator it = a.iterator(); it.hasNext(); )
          System.out.println(it.next());
       // for-each loop - since Java 5
       for (Integer e : a)
          System.out.println(e);
   }
}
```

elegant

The Python way to print a list

print-list.py

```
a = [20, 23, 26]

for e in a:
    print(e)
```

Output

```
$ python print-list.py
20
23
26
```

Why Python ?

- Short concise code
- Index out of range exceptions
- **Elegant for-each loop**

C++ how not to print a vector

```
$ g++ -std=c++11 print-vector.cpp
cpp-error-message.cpp: In function 'int main()':
cpp-error-message.cpp:7:13: error: no match for 'operator<<' (operand types are 'std::ostream {aka std::basic_ostream<char>}' and 'std::vector<int>')
   std::cout << A << std::endl;
             ^
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39:0,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:628:5: note: candidate: std::basic_ostream<_CharT, _Traits>& std::operator<<(std::basic_ostream<_CharT, _Traits>&&, const _Tp&) [with _CharT = char; _Traits = std::char_traits<char>; _Tp = std::vector<int>] <near match>
     operator<<(basic_ostream<_CharT, _Traits>&& __os, const _Tp& __x)
     ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:628:5: note:   conversion of argument 1 would be ill-formed:
cpp-error-message.cpp:7:16: error: cannot bind 'std::ostream {aka std::basic_ostream<char>}' lvalue to 'std::basic_ostream<char>&&'
   std::cout << A << std::endl;
                ^
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ios[illegible]
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:108:7: note: cand[illegible] std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(std::basic_ostream<_CharT, _Traits>::__ostream_type&)) [with _CharT = char; _Tra
std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basic_ostream<char>]
       operator<<(__ostream_type& (*__pf)(__ostream_type&))
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:108:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::basic_ostream<char>::__ostream_type& (*)(std::basic_ostream<char>::__ostream_type&) {aka std::basic_ostream<char>& (*)(std::basic_ostream<char>&)}'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:117:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(std::basic_ostream<_CharT, _Traits>::__ios_type& (*)(std::basic_ostream<_CharT, _Traits>::__ios_type&)) [with _CharT = char; _Traits = st
_Traits>::__ostream_type = std::basic_ostream<char>; std::basic_ostream<_CharT, _Traits>::__ios_type = std::basic_ios<char>]
       operator<<(__ios_type& (*__pf)(__ios_type&))
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:117:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::basic_ostream<char>::__ios_type& (*)(std::basic_ostream<char>::__ios_type&) {aka std::basic_ios<char>& (*)(std::basic_ios<char>&)}'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:127:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(std::ios_base& (*)(std::ios_base&)) [with _CharT = char; _Traits = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream
       operator<<(ios_base& (*__pf) (ios_base&))
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:127:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base&)'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:166:7: note: candidate: std::basic_ostream[illegible]s = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basic_ostream
       operator<<(long __n)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:166:7: note:   no known conversion for arg[illegible]
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:170:7: note: candidate: std::basic_ostream[illegible]ar; _Traits = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basi
       operator<<(unsigned long __n)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:170:7: note:   no known conversion for arg[illegible]
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:174:7: note: candidate: std::basic_ostream[illegible] std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basic_ostream<cha
       operator<<(bool __n)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:174:7: note:   no known conversion for arg[illegible]
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:638:0,
                 from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:91:5: note: candidate: std::basic[illegible]d::char_traits<char>]
     basic_ostream<_CharT, _Traits>::
     ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:91:5: note:   no known conversion[illegible]
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39:0,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:181:7: note: candidate: std::basic_ostream[illegible]har; _Traits = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::bas
       operator<<(unsigned short __n)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:181:7: note:   no known conversion for arg[illegible]
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:638:0,
                 from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:105:5: note: candidate: std::basi[illegible]ar_traits<char>]
     basic_ostream<_CharT, _Traits>::
     ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:105:5: note:   no known conversio[illegible]
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39:0,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:192:7: note: candidate: std::basic_ostream[illegible]ream<_CharT, _Traits>::__ostream_type = std::basic_ost
       operator<<(unsigned int __n)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:192:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'unsigned [illegible]
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:201:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic[illegible]tream<_CharT, _Traits>::__ostream_type = std::basic_os
       operator<<(long long __n)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:201:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'long long [illegible]
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:205:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic[illegible]:basic_ostream<_CharT, _Traits>::__ostream_type = std:
       operator<<(unsigned long long __n)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:205:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'long long unsigned int'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:220:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(double) [with _CharT = char; _Traits = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basic_ostream<c
       operator<<(double __f)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:220:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'double'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:224:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(float) [with _CharT = char; _Traits = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basic_ostream<ch
       operator<<(float __f)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:224:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'float'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:232:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(long double) [with _CharT = char; _Traits = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basic_ostr
       operator<<(long double __f)
       ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:232:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'long double'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:245:7: note: candidate: std::basic_ostream<_CharT, _Traits>::__ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(const void*) [with _CharT = char; _Traits = std::char_traits<char>; std::basic_ostream<_CharT, _Traits>::__ostream_type = std::basic_ostr
```

print-vector.cpp

```
#include <iostream>
#include <vector>

int main() {
  std::vector<int> A = {2, 3};
  std::cout << A << std::endl;
  return 0;
}
```

C++ vectors cannot be printed directly – mistake results in +200 lines of error messages

Why Python ?

- Short concise code
- Index out of range exceptions
- Elegant for-each loop
- **Python hopefully better error messages than C++**

Python and garbage collection

garbage.py

```
a = [2, 5, 3]
a = [7,4]
```

a gets new value

- Python and e.g. Java, C# and JavaScript have a **garbage collector** to automatically recycle garbage
- C and C++ garbage collection must be done explicitly by the program; forgetting to **free** memory again results in **memory leaks** – which can be really hard to find. **Have fun debugging!**
- Automatic garbage collection increases memory safety

Why Python ?

- Short concise code
- Index out of range exceptions
- Elegant for-each loop
- Python hopefully better error messages than C++
- **Garbage collection is done automatically**

Python performance vs C, C++ and Java

Compute sum $1 + 2 + 3 + \cdots + n = n^2/2 + n/2$

$1 + 2 + \cdots + n$

add.py

```python
import sys

n = int(sys.argv[1])
sum = 0
for i in range(1, n + 1):
    sum += i
print("Sum =", sum)
```

add.c

```c
#include <stdio.h>
#include <stdlib.h>

int main(int argc, char *argv[]) {
  int n = atoi(argv[1]);
  int sum = 0;
  for (int i = 1; i <= n; i++)
    sum += i;
  printf("Sum = %d\n", sum);
}
```

add.cpp

```cpp
#include <iostream>
#include <cstdlib>
using namespace std;

int main(int argc, char *argv[]) {
  int n = atoi(argv[1]);
  int sum = 0;
  for (int i = 1; i <= n; i++)
    sum += i;
  cout << "Sum = " << sum << endl;
}
```

add.java

```java
class Add{
    public static void main(String args[]){
        int n = Integer.parseInt(args[0]);
        int sum = 0;
        for (int i = 1; i <= n; i++)
            sum += i;
        System.out.println("Sum = " + sum);
    }
}
```

Timing results

n	C (gcc 9.2)	C++, int (g++ 9.2)	C++, long (g++ 9.2)	Java (12.0)	Python: CPython (3.8.1)	Python: PyPy (7.3.0)	Python: Numba, int64
10^7	0.001 sec*	0.001 sec*	0.003 sec	0.006 sec*	1.5 sec	0.27 sec	0.002 sec
10^9	0.10 sec**	0.10 sec**	0.30 sec	0.40 sec**	145 sec	27 sec	0.2 sec**

Wrong output (overflow)

* -2004260032 instead of 50000005000000

** -243309312 instead of 500000000500000000

- since C, C++, and Java only uses 32 bits to represent integers (and 64 bits for ”long” integers)

Have fun debugging!

```
Bit             66666666665555555555444444444433333333332222222222211111111110000000000
position        98765432109876543210987654321098765432109876543210987654321098765432 10

bin(10**9)                                                   111011100110101100101000000000

bin(50000005000000)                        1011010111100110001000100010010110101101000000
bin(-2004260032+2**32)                                     10001000100010010110101101000000

bin(500000000500000000)     1101111000001011011010110011111000101111111101100010100000000
bin(-243309312+2**32)                                      11110001011111110110010100000000
```

Try Google: civilization gandhi overflow

Timing results

n	C (gcc 9.2)	C++, int (g++ 9.2)	C++, long (g++ 9.2)	Java (12.0)	CPython (3.8.1)	PyPy (7.3.0)	Numba, int64
					Python		
10^7	0.001 sec*	0.001 sec*	0.003 sec	0.006 sec*	1.5 sec	0.27 sec	0.002 sec
10^9	0.10 sec**	0.10 sec**	0.30 sec	0.40 sec**	145 sec	27 sec	0.2 sec**

- Relative speed

C ≈ C++ > Java >> Python

- C, C++, Java need to care about integer overflows – select integer representation carefully with sufficient number of bits (8, 16, 32, 64, 128)
- Python natively works with arbitrary long integers (as memory on your machine allows). Also possible in Java using the class java.math.BigInteger
- Python programs can (sometimes) run faster using PyPy
- Number crunching in **Python** should be delegated to **specialized modules (e.g. Numpy, CPLEX, Numba)** – often written in C or C++ and requires selecting right integer representation

Interpreter vs Compiler

C / C++ program
(.c, .cpp)

Internally generates Assembly code

```
.L4:
        movl    -8(%rbp), %eax
        addl    %eax, -4(%rbp)
        addl    $1, -8(%rbp)
.L3:
        movl    -8(%rbp), %eax
        cmpl    -12(%rbp), %eax
        jle     .L4
        movl    -4(%rbp), %edx
        movl    -12(%rbp), %eax
        movl    %edx, %r8d
        movl    %eax, %edx
        leaq    .LC1(%rip), %rcx
        call    printf
        movl    $0, %eax
        addq    $48, %rsp
        popq    %rbp
```

Compiler
(gcc, g++)

Executable code
(.exe)

execution

Java program
(.java)

Java compiler
(javac)

Java bytecode
(.class)

Java Virtual Machine
(java)

execution

Python program
(.py)

Internally CPython generates bytecode

```
 0 LOAD_CONST       1 (0)
 2 STORE_FAST       1 (sum)
 4 SETUP_LOOP      30 (to 36)
 6 LOAD_GLOBAL      0 (range)
 8 LOAD_CONST       2 (1)
10 LOAD_FAST        0 (n)
12 LOAD_CONST       2 (1)
14 BINARY_ADD
16 CALL_FUNCTIO     2
18 GET_ITER
20 FOR_ITER        12 (to 34)
22 STORE_FAST       2 (i)
24 LOAD_FAST        1 (sum)
26 LOAD_FAST        2 (i)
28 INPLACE_ADD
30 STORE_FAST       1 (sum)
32 JUMP_ABSOLUT    20
34 POP_BLOCK
36 LOAD_FAST        1 (sum)
38 RETURN_VALUE
```

CPython interpreter
(python)

execution

Why Python ?

- Short concise code
- Index out of range exceptions
- Elegant for-each loop
- Python hopefully better error messages than C++
- Garbage collection is done automatically
- **Exact integer arithmetic (no overflows)**
- **Can delegate number crunching to C, C++, ...**

This course

Programming Languages
Rust
C
Java
JavaScript
C++
Haskell
R
MatLab
(Scientific) Applications
Machine learning
Visualization
GPS tracking
Optimization
Python
IPython
NumPy
matplotlib
Django
Jupyter
BeautifulSoup
SciPy
Programming modules/packages/libraries...
Algorithms and Data Structures
Computability and Logic
Programming Languages
Compilation
Computer Science Courses

Course overview

Basic programming
Advanced / specific python
Libraries & applications

1. Introduction to Python	10. Functions as objects	19. Linear programming
2. Python basics / if	11. Object oriented programming	20. Generators, iterators, with
3. Basic operations	12. Class hierarchies	21. Modules and packages
4. Lists / while / for	13. Exceptions and files	22. Working with text
5. Tuples / comprehensions	14. Doc, testing, debugging	23. Relational data
6. Dictionaries and sets	15. Decorators	24. Clustering
7. Functions	16. Dynamic programming	25. Graphical user interfaces (GUI)
8. Recursion	17. Visualization and optimization	26. Java vs Python
9. Recursion and Iteration	18. Multi-dimensional data	27. Final lecture

10 handins
1 final project (last 1 month)

History of Python development

- Python created by Guido van Rossum in 1989, first release 0.9.0 1991
- Python 2 → Python 3 (clean up of Python 2 language)
  - Python 2 – version 2.0 released 2000, final version 2.7 released mid-2010
  - Python 3 – released 2008, current release 3.14.2
- Python 3 is *not* backward compatible, libraries incompatible

Python 2	Python 3
print 42	print(42)
int = C long (32 bits)	int = arbitrary number of digits (= named “long” in Python 2)
7/3 → 2 returns “int”	7/3 → 2.333... returns “float”
range() returns list (memory intensive)	range() returns iterator (memory efficient; xrange in Python 2)

100th episode of Talk Python To Me: **Python past, present, and future with Guido van Rossum**

Python.org

Python
PSF
Docs
PyPI
Jobs
Community
python™
GO
Socialize
About
Downloads
Documentation
Community
Success Stories
News
Documentation
+700.000 Python packages
Download Python and IDLE
# Python 3: Fibonacci series up
>>> def fib(n):
>>> a, b = 0, 1
>>> while a < n:
>>> print(a, end=' ')
>>> a, b = b, a+b
>>> print()
>>> fib(1000)
0 1 1 2 3 5 8 13 21 34 55 89 144 233 377 610 987
Functions Defined
The core of extensible programming is defining functions. Python allows mandatory and optional arguments, keyword arguments, and even arbitrary argument lists. More about defining functions in Python 3
1 2 3 4 5
Python is a programming language that lets you work quickly and integrate systems more effectively. >>> Learn More
Get Started
Whether you're new to programming or an experienced developer, it's easy to learn and use Python.
Start with our Beginner's Guide
Download
Python source code and installers are available for download for all versions!
Latest: Python 3.14.2
Docs
Documentation for Python's standard library, along with tutorials and guides, are available online.
docs.python.org
Jobs
Looking for work or have a Python related position that you're trying to hire for? Our relaunched community-run job board is the place to go.
jobs.python.org

Installing Python from Python.org

IMPORTANT

Add commands directory to your PATH now? [y/N] y 4

Running the Python Interpreter from a terminal

- Open Command Prompt (Windows-key + cmd) or Windows PowerShell (Windows-key + powershell)
- Type “python” + return
- Start executing Python statements

- To exit shell: Ctrl-d *or* exit() + return

- Note: Sometimes “python” is installed as “python3”

Python package installer – pip

Try to install the Numpy package

- Open Command Prompt
- Execute one of the following:

```
py -m pip install numpy
python -m pip install numpy
python3 -m pip install numpy
pip install numpy
pip3 install numpy
```

Which works depends on your setup

Some other usefull packages

- Try installing some more Python packages:

`pip install numpy`	linear algebra support (N-dimensional arrays)
`pip install scipy`	numerical integration and optimization
`pip install matplotlib`	2D and 3D plotting library
`pip install pylint`	Python source code analyzer enforcing a coding standard

Creating a Python program the very basic way

my-first-python-program.py - Notepad

File Edit Format View Help

```
x = 3
y = 4
print(x * y)
```

Ln 1, Col 1

Command Prompt

```
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>cd Desktop

C:\Users\au121\Desktop>dir
 Volume in drive C is OSDisk
 Volume Serial Number is 3CDB-90D8

 Directory of C:\Users\au121\Desktop

30-01-2018  16:45    <DIR>          .
30-01-2018  16:45    <DIR>          ..
30-01-2018  16:40    <DIR>          ipsa18
30-01-2018  16:44                26 my-first-python-program.py
               1 File(s)             26 bytes
               3 Dir(s)  420.462.858.240 bytes free

C:\Users\au121\Desktop>python my-first-python-program.py
12

C:\Users\au121\Desktop>
```

- Open Notepad (or TextEdit on Mac)
  - write a simple Python program
  - save it
- Open a command prompt
  - go to folder (using cd)
  - run the program using

    `python <program name>.py`

… or open IDLE and run program with F5

enable
line numbers
under options

my-first-python-program.py - C:\Users\au121\Desktop\my-first-python-program.py (3.11.0)

File Edit Format Run Options Window Help

```
1 x = 3
2 y = 4
3 print(x *y)
4
```

Ln: 4 Col: 0

IDLE Shell 3.11.0

File Edit Shell Debug Options Window Help

```
Python 3.11.0 (main, Oct 24 2022, 18:26:48) [MSC v.1933 64 bit (AMD64)] on win32
Type "help", "copyright", "credits" or "license()" for more information.
>>>
========== RESTART: C:\Users\au121\Desktop\my-first-python-program.py ==========
12
>>>
```

Ln: 6 Col: 0

- IDLE ships with Python from python.org
- Good beginner IDE (Integrated Development Environment)

The Python Ecosystem

- **Interpreters/compiler**
  - CPython – reference C implementation from python.org
  - PyPy – written in RPython (a subset of Python) – faster than Cpython
  - Jython – written in Java and compiles to Java bytecode, runs on the JVM
  - IronPython – written in C#, compiles to Microsoft's Common Language Runtime (CLR) bytecode
  - Cython – project translating Python-ish code to C
- **Shells (IPython, IDLE, Jupyter)**
- **Libraries/modules/packages**
  - pypi.python.org/pypi (PyPI - the Python Package Index, +700.000 packages)
- **IDEs (Integrated development environment)**
  - IDLE comes with Python (docs.python.org/3/library/idle.html)
  - Anaconda w. Spyder, IPython (www.anaconda.com/download)
  - Canopy (enthought.com/product/canopy)
  - Visual Studio Code (code.visualstudio.com)
  - Python tools for Visual Studio (github.com/Microsoft/PTVS)
  - PyCharm (www.jetbrains.com/pycharm/)
  - Emacs (Python mode and ElPy mode)
  - Notepad++
- **Python Style guide (PEP8)**
  - pylint, pep8, flake8
- **Python online**
  - Google colab (colab.research.google.com), repl.it, sagemath.org, …
- **Pair programming plugins (share your editor with others)**
  - PyCharm : Code With Me
  - Visual Studio Code : Live Share

Good beginer Python IDE

Visual Studio Code is used by more than twice as many developers than its nearest alternative, Stack overflow survey 2025

Try to google "best ide python"

IDEs and AI assistants

- Some IDEs integrate AI assistants to support code suggestions, e.g. GitHub Copilot in VS Code
- AI assistants increase productivity *if* you understand their output
- Interacting with an AI assistant can be a great programming tutor
- AI assistants are not allowed at the exam

Guido van Rossum, inventor of Python, on GitHub Copilot

"I use it every day. It writes a lot of code for me… and usually it is slightly wrong but it still saves me typing."

Python and the Future of Programming, Guido van Rossum interviewed by Lex Fridman

9gag.com

Python basics

- Comments
- ”;”
- Variable names
- int, float, str
- type conversion
- assignment (=)
- print(), help(), type()

Python comments

A ‘#’ indicates the beginning of a comment.
From ‘#’ until of end of line is ignored by Python.

```
x = 42  # and here goes the comment
```

Comments useful to describe what a piece of code is supposed to do, what kind of input is expected, what is the output, side effects...

Comments are aimed at people (including yourself) reading the code

The “;” in Python

- Normally statements follow in consecutive lines with identical indentation

```
x = 1
y = 1
```

- but Python also allows multiple statements on one line, separated by “;”

```
x = 1; y = 1
```

Command Prompt

```
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>cd Desktop

C:\Users\au121\Desktop>pylint semicolon.py
No config file found, using default configuration
************* Module semicolon
C:  1, 0: Missing module docstring (missing-docstring)
C:  1, 0: Constant name "x" doesn't conform to UPPER_CASE naming style (invalid-name)
C:  1, 7: More than one statement on a single line (multiple-statements)
C:  1, 7: Constant name "y" doesn't conform to UPPER_CASE naming style (invalid-name)

------------------------------------
Your code has been rated at -10.00/10


C:\Users\au121\Desktop>flake8 semicolon.py
semicolon.py:1:6: E702 multiple statements on one line (semicolon)

C:\Users\au121\Desktop>
```

neither **pylint** or **flake8** like “;”

- General Python PEP 8 guideline: **avoid using “;”**
- Other languages like C, C++ and Java require “;” to end/separate statements

Variable names

- Variable name = sequence of **letters** ‘a’-’z’, ‘A’-’Z’, **digits** ‘0’-’9’, and **underscore** ‘_’

```
v, volume, height_of_box, WidthOfBox, x0, _v12_34B, _
```

(snake_case) (CamelCase)

  - a name cannot start with a digit
  - names are case sensitive (`AB`, `Ab`, `aB` and `ab` are different variables)

- Variable names are references to objects in memory
- **Use meaningful variables names**
- **Python 3 reserved keywords:**

```
and     class     elif     for     import  nonlocal  raise   with   None
as      continue  else     from    in      not       return  yield  False
assert  def       except   global  is      or        try            True
break   del       finally  if      lambda  pass      while
```

Question – Not a valid Pyton variable name?

a) `print`
b) `for` ← Python reserved keyword
c) `_100`
d) `x`
e) `_`
f) `python_for_ever`
g) Don’t know

Integer literals

- …. `-4, -3, -2, -1, 0, 1, 2, 3, 4` ….
- Python integers can have an arbitrary number of digits (only limited by machine memory)
- Can be preceded by a plus (`+`) or minus (−)
- Leading zeros are not allowed (e.g., 7 cannot be written as 007)
- For readability underscores (_) can be added between digits,

```
2_147_483_647
```

(for more, see PEP 515 - Underscores in Numeric Literals)

Question – What statement will not fail?

a) `x = _42`
b) `_10 = -1_1`
c) `x = 1__0`
d) `x = +1_0_`
e) Don’t know

Float literals

- Decimal numbers are represented using **float** – contain "." or "e"
- Examples
  - `3.1415`
  - `-.00134`
  - `124e3 = 124·10³`
  - `-2.345e2 = -234.5`
  - `12.3e-4 = 0.00123`
- ⚠ Floats are often only approximations, e.g. `0.1` is *not* 1/10
- Extreme values (CPython)
  - max = 1.7976931348623157e+308
  - min = 2.2250738585072014e-308
- NB: Use module `fractions` for exact fractions/rational numbers.

Python shell

```
> 0.1 + 0.2 + 0.3
| 0.6000000000000001
> (0.1 + 0.2) + 0.3
| 0.6000000000000001
> 0.1 + (0.2 + 0.3)
| 0.6
> type(0.1)
| <class 'float'>
> 1e200 * 1e300
| inf
> 0.1+(0.2+0.3) == (0.1+0.2)+0.3
| False
> x = 0.1 + 0.2
> y = 0.3
> x == y
| False
> print(f'{x:.30f}')  # 30 decimals
| 0.300000000000000444089209850062
> print(f'{y:.30f}')  # 30 decimals
| 0.299999999999999988897769753748
> import sys
> sys.float_info.min
| 2.2250738585072014e-308
> sys.float_info.max
| 1.7976931348623157e+308
```

Associativity rule does not apply to floats

Question – What addition order is ”best”?

a) `1e10 + 1e-10 + -5e-12 + -1e10`

b) `1e10 + -1e10 + 1e-10 + -5e-12`

c) `1e-10 + 1e10 + -1e10 + -5e-12`

d) `-5e-12 + -1e10 + 1e10 + 1e-10`

e) Any order is equally good

f) Don’t know

```
 1e10  =  10000000000
-1e10  = -10000000000
 1e-10 =            0.0000000001
-5e-12 =           -0.000000000005
```

Approximating π = 3.14159265359...

$$\frac{\pi^2}{6} = \sum_{k=1}^{+\infty} \frac{1}{k^2} = \frac{1}{1^2} + \frac{1}{2^2} + \frac{1}{3^2} + \cdots$$

$$= 1.6449340668...$$

Riemann zeta function ζ(2)

pi_approximation_riemann.py

```
apx = 0.0
k = 0.0
while True:
    k = k + 1.0
    apx = apx + 1.0 / (k * k)
    print(k, apx)
```

Output

```
...
94906261.0 1.6449340578345741
94906262.0 1.6449340578345744
94906263.0 1.6449340578345746
94906264.0 1.6449340578345748
94906265.0 1.644934057834575
94906266.0 1.644934057834575
94906267.0 1.644934057834575
94906268.0 1.644934057834575
94906269.0 1.644934057834575
94906270.0 1.644934057834575
...
```

This is not a course in numeric computations – but now you are warned....

Python float ≡ IEEE-754 double precision*

- A binary number is a number in base 2 with digits/bits from {0,1}

$$10110_2 = 1\cdot 2^4 + 0\cdot 2^3 + 1\cdot 2^2 + 1\cdot 2^1 + 0\cdot 2^0 = 16 + 4 + 2 = 22_{10}$$

- IEEE-754 64-bit double

sign s	exponent e	coefficient c
1 bit	11 bits	52 bits

$s = 0$ c

+1 0011101101011100111010101010101010101010101011101100 1001010101100.01000111100101011110011101010101111101011001101 01

e – 1023 bits

2^{-6}

Float value	Case
$(-1)^s \cdot (1 + c \cdot 2^{-52}) \cdot 2^{e-1023}$	$0 < e < 2047$
$(-1)^s \cdot c \cdot 2^{-1074}$	$e = 0, c \neq 0$
+0 and -0	$e = 0, c = 0$
+∞ and -∞	$e = 2047, c = 0$
NaN ("not a number")	$s = 0, e = 2047, c \neq 0$

Python shell

```
> 1e200 * 1e200
| inf
> -1e200 * 1e200
| -inf
> 1e-200 * 1e-200
| 0.0
> -1e-200 * 1e-200
| -0.0
> 1e200 * 1e200 * 0.0
| nan
```

(*most often, but there is no guarantee given in the Python language specification that floats are represented using IEEE-754)

String literals (type `str`)

- Sequence of characters enclosed by single (`'`) or double (`"`) quotes

  `"a 'quoted' word"` `"Hello World"` `'abc'`
  `'a "quoted" word'` `'_"_\'_"_'`

- Escape characters

`\n`	newline
`\t`	tab
`\\`	backslash
`\'`	single quote
`\"`	double quote
`\N{`*unicode name*`}`	

- A backslash (`\`) at the end of line, will continue line/string on next line
- Use triple single or double quotes (`'''` or `"""`) for enclosing strings spanning more lines

  (in particular for Python Doscrings, see PEP 257)

string-test.py

```
print("abc")
print('de\'f')
print("'ghi'")
print("'jk\nl'\"")
print("mn\
o")
print("p\\q\tr")
print("\N{SNOWMAN}")
```

Output

```
$ python string-test.py
abc
de'f
'ghi'
'jk
l'"
mno
p\q     r
```

Question – What does the following print ?

```
print("\\\"\\n\n'")
```

a) `\\\"\\n\n'`

b) `\"\nn'`

c) `\"\n`
`'`

d) `"nn'`

e) `\"`

`'`

f) Don’t know

Long string literals

- Long string literals often need to be split over multiple lines
- In Python two (or more) string literals following each other will be treated as a single string literal (they can use different quotes)
- Putting parenthesis around multiple literals allows line breaks
- Advantages:
  - avoids the backslash at the end of line
  - can use indentation to increase readability
  - allows comments between literals

long-string-literals.py

```
s1 = 'abc' "def"  # two string literals
print(s1)
s2 = '"' "'" '"'  # avoid escaping quotes
print(s2)
s3 = 'this is a really, really, really, \
really, really, long string'
print(s3)
s4 = ('this is a really, really, '
      'really, really, really, '
      'long string')
print(s4)
very_very_long_variable_name = (
    'this is a really, really, '  # line 1
    'really, really, really, '    # line 2
    "long string"                 # line 3
)
print(very_very_long_variable_name)
```

Python shell

```
| abcdef
| "'"
| this is a really, really, really, really,
  really, long string
| this is a really, really, really, really,
  really, long string
| this is a really, really, really, really,
  really, long string
```

Raw string literals

- By prefixing a string literal with an `r`, the string literal will be considered a raw string and backslashes become literal characters
- Useful in cases where you actually need backslashes in your strings, e.g. when working with Python's regular expression module `re`

Python shell

```
> print('\let\epsilon\varepsilon')      # \v = vertical tab
| \let\epsilon
  arepsilon
> print('\\let\\epsilon\\varepsilon')   # many backslashs
| \let\epsilon\varepsilon
> print(r'\let\epsilon\varepsilon')     # more readable
| \let\epsilon\varepsilon
```

- Strange exception: A raw string cannot end with an odd number of backslashes

print(...)

- `print` can print zero, one, or more values
- default behavior
  - print a space between values
  - print a line break after printing all values
- default behavior can be changed by **keyword arguments** "`sep`" and "`end`"

Python shell

```
> print()
|
> print(7)
| 7
> print(2, 'Hello')
| 2 Hello
> print(3, 'a', 4)
| 3 a 4
> print(3, 'a', 4, sep=':')
| 3:a:4
> print(5); print(6)
| 5
| 6
> print(5, end=', '); print(6)
| 5, 6
```

print(...) and help(...)

Python shell

```
> help(print)
| Help on built-in function print in module builtins:
|
| print(...)
|     print(value, ..., sep=' ', end='\n', file=sys.stdout, flush=False)
|
|     Prints the values to a stream, or to sys.stdout by default.
|     Optional keyword arguments:
|     file:  a file-like object (stream); defaults to the current sys.stdout.
|     sep:   string inserted between values, default a space.
|     end:   string appended after the last value, default a newline.
|     flush: whether to forcibly flush the stream.
```

Assignments

- *variable = expression*

```
x = 42
```

- Multiple assignments – right hand side evaluated before assignment

```
x, y, z = 2, 5, 7
```

- Useful for swapping

```
x, y = y, x
```

- Assigning multiple variables same value in left-to-right

```
x = y = z = 7
```

Warning

```
i = 1
i = v[i] = 3  # v[3] is assigned value 3
```

In languages like C and C++ instead v[1] is assigned 3

Python is dynamically typed, type(…)

- The current type of a value can be inspected using the **type()** function (that returns a type object)
- In Python the values contained in a variable over time can be of different type
- In languages like C, C++ and Java variables are declared with a given type, e.g.

```
int x = 42;
```

  and the different values stored in this variable must remain of this type

Python shell

```
> x = 1
> type(x)
| <class 'int'>
> x = 'Hello'
> type(x)
| <class 'str'>
> type(42)
| <class 'int'>
> type(type(42))
| <class 'type'>
```

x new type

Type conversion

- Convert a value to another type:

  new-type(*value*)

- Sometimes done automatically:

```
1.0+7=1.0+float(7)=8.0
```

Python shell

```
> float(42)
| 42.0
> int(7.8)
| 7
> x = 7
> print("x = " + x)
| Traceback (most recent call last):
|   File "<stdin>", line 1, in <module>
| TypeError: must be str, not int
> print("x = " + str(x))
| x = 7
> print("x = " + str(float(x)))
| x = 7.0
> int("7.3")
| Traceback (most recent call last):
|   File "<stdin>", line 1, in <module>
| ValueError: invalid literal for int() with base 10: '7.3'
> int(float("7.3"))
| 7
```

string concatenation

Questions – `str(float(int(float("7.5"))))` ?

a) 7
b) 7.0
c) 7.5
d) "7"
e) "7.0"
f) "7.5"
g) Don’t know

Control structures

- input()
- if-elif-else
- while-break-continue

input

- The builtin function `input(`*message*`)` prints *message*, and waits for the user provides a line of input and presses return. The line of input is returned as a `str`
- If you e.g. expect input to be an `int`, then remember to convert the input using `int()`

name-age.py

```
name = input('Name: ')
age = int(input('Age: '))
print(name, 'is', age, 'years old')
```

Python shell

```
> Name: Donald Duck
> Age: 84
| Donald Duck is 84 years old
```

Branching – do either this or that ?

Basic if-else

```
if boolean expression:
    code
    code
    code
else:
    code
    code
    code
```

identical indentation

identical indentation

if-else.py

```
if x % 2 == 0:
    print('even')
else:
    print('odd')
```

Identical indentation for a sequence of lines = the same spaces/tabs should precede code

pass

- `pass` is a Python statement doing nothing. Can be used where a statement is required but you want to skip (e.g. code will be writen later)

- Example (bad example, since `else` could just be omitted):

if-else.py

```
if x % 2 == 0:
    print('even')
else:
    pass
```

if-elif-else

```
if condition:
        code
elif condition :     # zero or more "elfi" ≡ "else if"
        code
else:    # optional
        code
```

```
if (condition) {
  code
} else if (condition) {
  code
} else {
  code
}
```

Java, C, C++ syntax

Other languages using indentation for blocking:
ABC (1976), occam (1983), Miranda (1985)

if.py

```
if x == 0:
    print('zero')
```

if-else.py

```
if x % 2 == 0:
    print('even')
else:
    print('odd')
```

elif.py

```
if x < 0:
    print('negative')
elif x == 0:
    print('zero')
elif x == 1:
    print('one')
else:
    print('>= 2')
```

elif can make code nicer (less identation)

elif.py

```
if x < 0:
    print('negative')
elif x == 0:
    print('zero')
elif x == 1:
    print('one')
else:
    print('>= 2')
```

ugly-if.py

```
if x < 0:
    print('negative')
else:
    if x == 0:
        print('zero')
    else:
        if x == 1:
            print('one')
        else:
            print('>= 2')
```

Questions – What value is printed?

```
x = 1
if x == 2:
    x = x + 1
else:
    x = x + 1
    x = x + 1
x = x + 1
print(x)
```

a) 1
b) 2
c) 3
d) 4
e) 5
f) Don’t know

Nested if-statements

nested-if.py

```
if x < 0:
    print('negative')
elif x % 2 == 0:
    if x == 0:
        print('zero')
    elif x == 2:
        print('even prime number')
    else:
        print('even composite number')
else:
    if x == 1:
        print('one')
    else:
        print('some odd number')
```

Common mistake

if-if.py

```
x = int(input())
if x == 0:
    print('zero')
if x % 2 == 0:
    print('even')
```

Python shell

```
> 0
| zero
| even
```

if-elif.py

```
x = int(input())
if x == 0:
    print('zero')
elif x % 2 == 0:
    print('even')
```

Python shell

```
> 0
| zero
```

if-else *expressions*

- A very common computation is

```
if test:
    x = true-expression
else:
    x = false-expression
```

- In Python there is a shorthand for this:

```
x = true-expression if test else false-expression
```

think of this as the "common case" and the "exceptional case"

(see What's New in Python 2.5 - **PEP 308: Conditional Expressions**)

- In C, C++, Java, Javascript the equivalent notation is (note the different order)

```
x = test ? true-expression : false-expression
```

Repeat until done

while-statement

```
while condition:
    code
    ...
    break # jump to code after while loop
    ...
    continue # jump to condition at the
    ...      # beginning of while loop
```

```
while (condition) {
  code
}
```

Java, C, C++ syntax

count.py

```
x = 1
while x <= 5:
    print(x, end=' ')
    x = x + 1
print('and', x)
```

Python shell

```
| 1 2 3 4 5 and 6
```

The function `randint(a, b)` from module `random` returns a random integer from {a, a + 1,..., b – 1, b}

random-pair.py

```
from random import randint
while True:
    x = randint(1, 10)
    y = randint(1, 10)
    if abs(x - y) >= 2:
        break
    print('too close', x, y)
print(x, y)
```

Python shell

```
| too close 4 4
| too close 10 9
| 8 5
```

Computing $\lfloor\sqrt{x}\rfloor$ using binary search

An exercise asks to simplify the code

int-sqrt.py

```
x = 20
low = 0
high = x + 1
while True:  # low <= sqrt(x) < high
    if low + 1 == high:
        break
    mid = (high + low) // 2
    if mid * mid <= x:
        low = mid
        continue
    high = mid
print(low)  # low = floor(sqrt(x))
```

Integer division

$$\left\lfloor\frac{\texttt{high}+\texttt{low}}{2}\right\rfloor$$

$$\texttt{mid} \le \sqrt{x}$$
$$\Updownarrow$$
$$\texttt{mid}^2 \le x$$

bisect

- **Note** Binary search on sorted lists is supported by the standard library module `bisect`
- `bisect_left` and `bisect_right` return the *insertion point* before and after, respectively, of existing occurrences of the value

binary_search_bisect.py

```
from bisect import bisect_left, bisect_right

L = [3, 4, 6, 7, 7, 7, 10, 11, 13, 16, 17]

print(bisect_left(L, 7))
print(bisect_right(L, 7))
print(bisect_left(L, 14))
print(bisect_right(L, 14))
```

Python shell

```
| 3   # bisect_left(L, 7)
| 6   # bisect_right(L, 7)
| 9   # bisect_left(L, 14)
| 9   # bisect_right(L, 14)
```

Division using the Newton-Raphson method

- **Goal:** Compute 1 / n only using +, -, and *
- $x = 1 / n \iff f(x) = n - 1 / x = 0$
- Problem reduces to finding root of f
- Newton-Raphson:

$$x := x - f(x)/f'(x) = x - (n - 1/x)/(1/x^2) = (2 - n \cdot x) \cdot x$$

since $f'(x) = 1 / x^2$ for $f(x) = n - 1 / x$

division.py

```
n = 0.75  # n in [0.5, 1.0]

x = 1.0
last = 0.0
while last < x:
    print(x)
    last = x
    x = (2 - n * x) * x

print('Apx of 1.0 /', n, '=', x)
print('Python 1.0 /', n, '=', 1.0 / n)
```

Python shell

```
| 1.0
| 1.25
| 1.328125
| 1.33331298828125
| 1.3333333330228925
| 1.3333333333333333
| Apx of 1.0 / 0.75 = 1.3333333333333333
| Python 1.0 / 0.75 = 1.3333333333333333
```

en.wikipedia.org/wiki/Newton's_method

Operations

- None, bool
- basic operations
- strings
- += and friends

NoneType

- The type None has only one value: `None`
- Used when context requires a value, but none is really available
- **Example**: All functions must return a value. The function `print` has the *side-effect* of printing something to the standard output, but returns `None`
- **Example**: Initialize a variable with no value, e.g. list entries `mylist = [None, None, None]`

Python shell

```
> x = print(42)
| 42
> print(x)
| None
```

Named after mathematician George Boole (1815-1864)

Type bool

- The type `bool` only has two values: `True` and `False`

- Logic truth tables:

x **or** *y*	True	False
True	True	True
False	True	False

x **and** *y*	True	False
True	True	False
False	False	False

x	**not** *x*
True	False
False	True

Scalar vs Non-scalar Types

- **Scalar types** (atomic/indivisible): `int`, `float`, `bool`, `None`
- **Non-scalar**: Examples `strings` and `lists`

```
"string"[3] = "i"
[2, 5, 6, 7][2] = 6
```

Questions – What is `[7,3,5][[1,2,3][1]]` ?

a) 1
b) 2
c) 3
d) 5
e) 7
f) Don’t know

Operations on int and float

Result is float if and only if at least one argument is float, except ** with negative exponent always gives a float

- `+`, –, `*` addition multiplication, e.g. `3.0*2` = `6.0`
- `**` and `pow(x, y)` power, e.g. `2**3` = `pow(2,3)` = 8, `2**-2` = `0.25`
- `//` integer division = ⌊x / y⌋
  e.g. `15.0//4` = `3.0`. Note: –`8//3` = –3
- `/` division returns float, `6/3` = `2.0`
- `abs(x)` absolute value
- `%` integer division remainder (modulo)
  `11 % 3` = 2
  `4.7%0.6` = `0.5000000000000003`

Python shell

```
> 0.4 // 0.1
| 4.0
> 0.4 / 0.1
| 4.0
> 0.3 // 0.1
| 2.0
> 0.3 / 0.1
| 2.9999999999999996
> 10**1000 / 2
| OverflowError: integer division
  result too large for a float
```

Running time for 3 ** x // 3 ** x

Working with larger integers takes slightly more than linear time in the number of digits

integer-division-timing.py

```
from time import time
import matplotlib.pyplot as plt

bits, compute_time = [], []

for i in range(42):
    x = 3 ** i // 2 ** i
    start = time()
    result = 3 ** x // 3 ** x      # the computation we time
    end = time()
    t = end - start
    print('i =', i, 'x =', x, 'Result =', result, 'time(sec) =', t)
    bits.append(x)
    compute_time.append(t)

plt.title('Computing 3**x // 3**x')
plt.xlabel('x')
plt.ylabel('computation time (seconds)')
plt.plot(bits, compute_time, 'g:')
plt.plot(bits, compute_time, 'ro')
plt.show()
```

module math

Many standard mathematical functions are available in the Python module "`math`", e.g.

sqrt, sin, cos, tan, asin, acos, atan, log(natural), log10, exp, ceil, floor, ...

- To use all the functions from the math module use `import math`
  Functions are now available as e.g. `math.sqrt(10)` and `math.ceil(7.2)`
- To import selected functions you instead write `from math import sqrt, ceil`
- The library also contains some constants, e.g.
  `math.pi` = 3.141592... and `math.e` = 2.718281...
- Note: `x ** 0.5` significantly faster than `sqrt(x)`

Python shell

```
> (0.1 + 0.2) * 10
| 3.0000000000000004
> math.ceil((0.1 + 0.2) * 10)
| 4
```

docs.python.org/3/library/math.html

module `statistics` contains basic functions like mean and variance, see docs.python.org/3/library/statistics.html

Python shell

```
> import math
> math.sqrt(8)
| 2.8284271247461903
> from math import pi, sqrt
> pi
| 3.141592653589793
> sqrt(5)
| 2.23606797749979
> from math import sqrt as kvadratrod
> kvadratrod(3)
| 1.7320508075688772

> import timeit
> timeit.timeit('1e10**0.5')
| 0.021124736888936863
> timeit.timeit('sqrt(1e10)', 'from math import sqrt')
| 0.1366314052865789
> timeit.timeit('math.sqrt(1e10)', 'import math')
| 0.1946660841634582
```

docs.python.org/3.12/library/timeit.html

Rounding up integer fractions

- Python: $\lceil x/y \rceil = -(-x//y)$

-(-13/3)		
Python	Java	C
-(-13//3) = 5	-(-13/3) = 4 ⚠	-(-13/3) = 4 ⚠

⚠ The intermediate result `x/y` in `math.ceil(x/y)` is a float with limited precision

- Alternative computation:

$\lceil x/y \rceil = (x+(y-1))//y$

Python shell

```
> from math import ceil
> from timeit import timeit
> 13 / 3
| 4.333333333333333
> 13 // 3
| 4
> -13 // 3
| -5
> -(-13 // 3)
| 5
> ceil(13 / 3)
| 5
> -(-2222222222222222223 // 2)
| 1111111111111111112
> ceil(2222222222222222223 / 2)
| 1111111111111110656
> timeit('ceil(13 / 3)', 'from math import ceil')
| 0.2774667127609973
> timeit('-(-13 // 3)')  # negation trick is fast
| 0.05231945830200857
```

⚠

floats : Overflow, inf, -inf, nan

- There exists special float values
  `inf, -inf, nan`
  representing “+infinity”, “-infinity” and “not a number”
- Can be created using e.g.
  `float('inf')`
  or imported from the `math` module
- Some overflow operations generate an `OverflowError`, other return `inf` and allow calculations to continue !
- Read the IEEE 754 standard if you want to know more details...

Python shell

```
> 1e250 ** 2
| OverflowError:
  (34, 'Result too large')
> 1e250 * 1e250
| inf
> -1e250 * 1e250
| -inf
> import math
> math.inf
| inf
> type(math.inf)
| <class 'float'>
> math.inf / math.inf
| nan
> type(math.nan)
| <class 'float'>
> math.nan == math.nan
| False
> float('inf') - float('inf')
| nan
```

Operations on bool

- The operations `and`, `or`, and `not` behave as expected when the arguments are `False`/`True`.
- The three operators also accept other types, where the following values are considered *false*:

```
False, None, 0, 0.0, "", []
```

(see The Python Standard Library > Built-in Types > True Value Testing for more *false* values)

- *Short-circuit evaluation*: The rightmost argument of `and` and `or` is only evaluated if the result cannot be determined from the leftmost argument alone. The result is either the leftmost or rightmost argument (see truth tables), i.e. the result is not necessarily `False`/`True`.

`True or 7/0` is completely valid since 7/0 will never be evaluated (which otherwise would throw a ZeroDivisionError exception)

x	x or y
false	y
otherwise	x

x	x and y
false	x
otherwise	y

x	not x
false	True
otherwise	False

Questions – What is `"abc" and 42` ?

a) `False`
b) `True`
c) `"abc"`
d) `42`
e) TypeError
f) Don’t know

Comparison operators (e.g. int, float, str)

==	test if two objects are equal, returns bool not to be confused with the assignment operator (=)
!=	not equal
>	
>=	
<	
<=	

Python shell

```
> 3 == 7
| False
> 3 == 3.0
| True
> "-1" != -1
| True
> "abc" == "ab" + "c"
| True
> 2 <= 5
| True
> -5 > 5
| False
> 1 == 1.0
| True
> 1 == 1.0000000000000001
| True
> 1 == 1.000000000000001
| False
```

Chained comparisons

- A recurring condition is often

```
x < y and y < z
```

- If `y` is a more complex expression, we would like to avoid computing `y` twice, i.e. we often would write

```
tmp = complex expression
x < tmp and tmp < z
```

- In Python this can be written as a chained comparisons (which is shorthand for the above)

```
x < y < z
```

- Note: Chained comparisons do not exist in C, C++, Java, ...

Questions – What is `1 < 0 < 6/0` ?

a) `True`
b) `False`
c) `0`
d) `1`
e) `6`
f) ZeroDivisionError
g) Don’t know

Binary numbers and operations

- Binary number = integer written in base 2: $101010_2 = 42_{10} = 2^1 + 2^3 + 2^5$

- Python constant prefix 0b: `0b101010` → `42`
- `bin(x)` converts integer to string: `bin(49)` → `"0b110001"`
- `int(x, 2)` converts binary string value to integer: `int("0b110001", 2)` → `49`
- Bitwise operations
  - | Bitwise OR
  - & Bitwise AND
  - ~ Bitwise NOT (`~ x` equals to `-x - 1`)
  - ^ Bitwise XOR
- Example: `bin(0b1010 | 0b1100)` → `"0b1110"`
- Hexadecimal = base 16, Python prefix 0x: `0x30` → `48`, `0xA0` → `160`, `0xFF` → `255`
- << and >> integer bit shifting left and right, e.g. `12 >> 2` → `3`, and `1 << 4` → `16`

Operations on strings

- `len(`*str*`)` returns length of *str*
- *str*`[`*index*`]` returns *index*+1'th symbol in *str*
- $str_1 + str_2$ returns concatenation of two strings
- *int* `*` *str* concatenates *str* with itself *int* times
- Formatting: % operator or .format() function
  old Python 2 way since Python 3.0
  or formatted string literals (f-strings) with prefix
  since Python 3.6
  letter `f` and Python expressions in `{ }`

  (see pyformat.info for an introduction)

From "What's New In Python 3.0", 2009: *A new system for built-in string formatting operations replaces the % string formatting operator. (However, the % operator is still supported; it will be deprecated in Python 3.1 and removed from the language at some later time.) Read PEP 3101 for the full scoop.*

Python shell

```
> len("abcde")
| 5
> "abcde"[2]
| 'c'
> x, y = 2, 3
> "x = %s, y = %s" % (x, y)
| 'x = 2, y = 3'
> "x = {}, y = {}".format(x, y)
| 'x = 2, y = 3'
> "x = {1}, y = {0}".format(y, x)
| 'x = 2, y = 3'
> f'x + y = {x + y}'
| 'x + y = 5'
> f'{x + y = }'  # >= Python 3.8
| 'x + y = 5'
> f'{x} / {y} = {x / y:.3}'
| '2 / 3 = 0.667'
> "abc" + "def"
| 'abcdef'
> 3 * "x--"
| 'x--x--x--'
> 0 * "abc"
| ''
```

% formatting (inherited from C's sprint() function) was supposed to be on the way out - but is still going strong in Python 3.13

Python does not automatic convert to string

- A `str` can not be concatenated with an `int`
- The `int` must first be converted to a `str` using `str(`*`int value`*`)`

works in Java and Javascript

Python shell

```
> 'abc' + 42
| TypeError: can only concatenate str (not "int") to str
> 'abc' + str(42)
| 'abc42'
```

- In some languages, like Java and Javascript, the conversion to string happens automatically (just a language design choice)

… more string functions

- *str*`[`−*i*`]` returns the symbol *i* positions from the right, the rightmost *str*`[-1]`
- *str*`[`*from*`:`*to*`]` substring starting at index *from* and ending at index *to*-1
- *str*`[`*from*`:-`*to*`]` substring starting at *from* and last at index `len(`*str*`)` − *to* `-1`
- *str*`[`*from*`:`*to*`:`*step*`]` only take every *step*'th symbol in *str*[*from*:*to*]
  - *from* or/and *to* can be omitted and defaults to the beginning/end of string
- `chr(`*x*`)` returns a string of length 1 containing the *x*'th Unicode character
- `ord(`*str*`)` for a string of length 1, returns the Unicode number of the symbol
- *str*`.lower()` returns string in lower case
- *str*`.split()` split string into list of words, e.g.

```
"we love python".split() = ['we', 'love', 'python']
```

docs.python.org/3/library/string.html

Python shell

```
> s = 'this is a string'
> s.capitalize()
| 'This is a string'
> s.title()
| 'This Is A String'
> s.upper()
| 'THIS IS A STRING'
> s.title().swapcase()
| 'tHIS iS a sTRING
> s.removeprefix('this is ')
| 'a string'
> s.removesuffix(' string')
| 'this is a'
> s.replace('is', 'IS')
| 'thIS IS a string'
> s.ljust(30)
| 'this is a string              '
> s.center(30)
| '       this is a string       '
> s.rjust(30, '.')
| '..............this is a string'
> s.count('i')
| 3
> '12345'.zfill(8)
| '00012345'
```

https://docs.python.org/3/library/stdtypes.html#text-sequence-type-str

Questions – What is `s[2:42:3]`?

```
s = 'abwwdexy___lwtopavghevt_xypxxyattx_hxwoadnxxx'
```

a) `'wwdexy___lwtopavghevt_xypxxyattx_hxwoadn'`
b) `'we_love_python'`
c) `'we_love_java'`
d) Don’t know

Strings are immutable

- Strings are non-scalar, i.e. for `s = "abcdef"`, `s[3]` will return `"d"`
- Strings are immutable and cannot be changed once created.
  I.e. the following natural update is not possible (but is e.g. allowed in C)

```
s[3] = "x"
```

- To replace the `"d"` with `"x"` in `s`, instead create the new string

```
s = s[:3] + "x" + s[4:]
```

Operators
Precedence rules & Associativity

Example: * has higher precedence than +

2 + 3 * 4 ≡ 2 + (3 * 4) → 14 and (2 + 3) * 4 → 20

All operators in same group are evaluated left-to-right

2 + 3 - 4 - 5 ≡ ((2 + 3) - 4) - 5 → -4

except for **, that is evaluated right-to-left

2**2**3 ≡ 2**(2**3) → 256

Rule: Use parenthesis whenever in doubt of precedence!

Precedence (low to high)
`or`
`and`
`not x`

`in` `not in`
`is` `is not`
`==` `<` `<=`
`!=` `>` `>=`

`|`
`^`
`&`
`<<` `>>`
`+` `-`
`*` `@` `/` `//` `%`
`+x` `-x` `~x`
`**`

docs.python.org/3/reference/expressions.html

Long expressions

- Long expressions can be broken over several lines by putting parenthesis around it
- The PEP8 guidelines recommend to limit **all** lines to a maximum of 79 characters

Python shell

```
> (1
    + 2 +
          3)
| 6
```

https://www.python.org/dev/peps/pep-0008/#maximum-line-length

+= and friends

- Recurring statement is

```
x = x + value
```

- In Python (and many other languages) this can be written as

```
x += value
```

- This also applies to other operators like

```
+=   -=   *=   /=   //=   **=
|=   &=   ^=   <<=   >>=
```

Python shell

```
> x = 5
> x *= 3
> x
| 15
> a = 'abc'
> a *= 3
> a
| 'abcabcabc'
```

:= assignment expressions (the "Walrus Operator")

- Syntax

  `name := expression`

- Evaluates to the value of `expression`, with the side effect of assigning result to `name`
- Useful for naming intermediate results/repeating subexpressions for later reusage
- See PEP 572 for further details and restrictions of usage

Python shell

```
> (x := 2 * 3) + 2 * x
| 18
> print(1 + (x := 2 * 3), 2 + x)
| 7 8
> x := 7
| SyntaxError
> (x := 7)  # valid, but not recommended
> while line := input():
      print(line.upper())
> abc
| ABC
```

- In some languages, e.g. Java, C and C++, "=" also plays the role of ":=", implying "`if (x=y)`" and "`if (x==y)`" mean quite different things (common typo)

Lists

- List syntax
- List operations
- copy.deepcopy
- range
- while-else
- for
- for-break-continue-else

`L[-index] == L[len(L)-index]`
Negative indexing from the right is Python specific, and is e.g. not supported in Java, C, C++

List operations

- List syntax `[`*value*$_0$`,` *value*$_1$`,` `...,` *value*$_{k-1}$`]`
- List indexing `L[`*index*`]`, `L[`−*index*`]`
- ★ List slices `L[`*from*`:`*to*`]`, `L[`*from*`:`*to*`:`*step*`]` or `L[slice(`*from*`,`*to*`,`*step*`)]`
- ★ Creating a copy of a list `L[:]` or `L.copy()`
- ★ List concatenation (creates new list) `X + Y`
- ★ List repetition (repeated concatenation with itself) `42 * L`
- Length of list `len(L)`
- Check if element is in list `e in L` (returns `True` or `False`)
- Check if element is not in list `e not in L` (same as `not e in L`)
- Index of first occurrence of element in list `L.index(e)`
- Number of occurrences of element in list `L.count(e)`
- `sum(L)` `min(L)` `max(L)`

★ = creates new list

docs.python.org/3/library/stdtypes.html#sequence-types-list-tuple-range

sum(...)

Python 3.12 change

Python shell

```
> 1 - 1/3 - 1 + 1/3  # mathematically should be zero
| 5.551115123125783e-17  # but floats are imprecise
> L = [1, -1/3, -1, 1/3]
> L
| [1, -0.3333333333333333, -1, 0.3333333333333333]  # mix of int and float
> sum(L)
| 5.551115123125783e-17
> sum([1.0, -1/3, -1.0, 1/3])  # all floats
| 5.551115123125783e-17  # Python 3.11
> sum([1.0, -1/3, -1.0, 1/3])
| 0.0  # Python 3.12 uses "Neumaier summation" to improve accuracy for floats
> sum([1, -1/3, -1, 1/3])
| 5.551115123125783e-17  # Python 3.12 looses accuracy when mixing int and float
> import math
> math.fsum([1, -1/3, -1, 1/3])  # math.fsum more accurate float sums
| 0.0
```

List modifiers (lists are mutable)

- Extend list with elements (`X` is modified) `X.extend(Y)`
- Append an element to a list (`L` is modified) `L.append(42)`
- Replace sublist by another list (length can differ) `X[i:j] = Y`
- Delete elements from list `del L[i:j:k]`
- Remove & return element at position `L.pop(i)`
- Remove first occurrence of element `L.remove(e)`
- Reverse list `L.reverse()`
- `L *= 42`
- `L.insert(i, x)` same as `L[i:i] = [x]`

Python shell

```
> x = [1, 2, 3, 4, 5]
> x[2:4] = [10, 11, 12]
> x
| [1, 2, 10, 11, 12, 5]
> x = [1, 2, 11, 5, 8]
> x[1:4:2] = ['a', 'b']
| [1, 'a', 11, 'b', 8]
```

docs.python.org/3/library/stdtypes.html#sequence-types-list-tuple-range

Questions – What is `x` ?

```
x = [1,2,3,4,5,6,7,8,9,10]
x[2:8:3] = ['a', 'b']
```

a) `[1,2,'a','b',5,6,7,8,9,10]`
b) `[1,'a',3,4,5,6,7,'b',9,10]`
c) `[1,2,3,4,5,6,7,'a','b']`
d) `[1,2,'a',4,5,'b',7,8,9,10]`
e) ValueError
f) Don’t know

Questions – What is `y` ?

```
y = [1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19]
y = y[3:15:3][1:4:2]
```

a) `[3,6,9,12,15]`
b) `[7,13]`
c) `[1,9]`
d) `[4,7,10,13,2,4]`
e) TypeError
f) Don’t know

Nested lists (multi-dimensional lists)

- Lists can contain lists as elements, that can contain lists as elements, that ...
- Can e.g. be used to store multi-dimensional data (list lengths can be non-uniform)

Note: For dealing with matrices the NumPy module is a better choice

multidimensional-lists.py

```
list1d = [1, 3, 5, 2]
list2d = [[1, 2, 3, 4],
          [5, 6, 7, 9],
          [0, 8, 2, 3]]
list3d = [[[5,6], [4,2], [1,7], [2,4]],
          [[1,2], [6,3], [2,5], [7,5]],
          [[3,8], [1,5], [4,3], [2,4]]]

print(list1d[2])
print(list2d[1][2])
print(list3d[2][0][1])
```

Python shell

```
| 5
| 7
| 8
```

aliasing

```
a = [13, 27, 7, 42]
b = a
a[2] = 12
```

y = x vs y = x[:]

```
a = [13, 27, 7, 42]
b = a
a[2] = 12
```

```
a = [13, 27, 7, 42]
b = a[:]
a[2] = 12
```

x[:] vs nested structures

```
a = [[3,5],[7,11]]
b = a
c = a[:]
a[0][1] = 4
c[1] = b[0]
```

Question – what is `c` ?

a) `[[3,5],[7,11]]`

b) `[[3,5],[3,5]]`

c) `[[3,4],[3,5]]`

d) `[[3,4],[3,4]]`

e) Don't know

```
a = [[3,5],[7,11]]
b = a
c = a[:]
a[0][1] = 4
c[1] = b[0]
```

Try pythontutor.com

copy.deepcopy

- To make a copy of all parts of a composite value use the function deepcopy from module copy

Python shell

```
> from copy import deepcopy
> a = [[3, 5], 7]
> b = deepcopy(a)
> a[0][0] = 4
> a
| [[4,5],7]
> b
| [[3,5],7]
```

Initializing a 2-dimensional list

Python shell

```
> x = [1] * 3
> x
| [1, 1, 1]
> y = [[1] * 3] * 4
> y
| [[1, 1, 1], [1, 1, 1], [1, 1, 1], [1, 1, 1]]
> y[0][0] = 0
> y
| [[0, 1, 1], [0, 1, 1], [0, 1, 1], [0, 1, 1]]
```

Python shell

```
> y = []
> for _ in range(4): y.append([1] * 3)
> y[0][0] = 0
> y
| [[0, 1, 1], [1, 1, 1], [1, 1, 1], [1, 1, 1]]
```

range(*from, to, step*)

In Python 2, `range` generates the explicit list, i.e. always use memory proportional to the length; `xrange` in Python 2 corresponds to `range` in Python 3; Python 3 is more memory friendly

- `range(`*from*`, `*to*`, `*else*`)` represents the sequence of numbers starting with *from*, with increments of *step*, and smaller/greater than *to* if *step* positive/negative

`range(5)`	: `0, 1, 2, 3, 4`	(default *from* = 0, *step* = 1)
`range(3, 8)`	: `3, 4, 5, 6, 7`	(default *step* = 1)
`range(-2, 7, 3)`	: `-2, 1, 4`	(*from* and *to* can be any integer)
`range(2, -5, -2)`	: `2, 0, -2, -4`	(decreasing sequence if *step* negative)

- Ranges are immutable, can be indexed like a list, sliced, and compared (i.e. generate the same numbers)
- `list(range(...))` generates the explicit list of numbers

Python shell

```
> range(1, 10000000, 3)[2]
| 7
> range(1, 10000000, 3)[100:120:4]
| range(301, 361, 12)
> range(1, 10000000, 3)[100:120:4][2:3]
| range(325, 337, 12)
> list(range(5, 14, 3))
| [5, 8, 11]
```

Question – What is `range(3,20,4)[2:4][1]` ?

a) 3
b) 7
c) 11
d) 15
e) 19
f) Don’t know

for - loop

- For every element in a sequence execute a block of code:

  `for` *var* `in` *sequence*`:`
  block

- Sequences can e.g. be lists, strings, ranges
- `break` and `continue` can be used like in a while-loop to break out of the for-loop or continue with the next element in the sequence

Python shell

```
> for x in [1, 'abc', [2, 3], 5.0]:
>     print(x)
| 1
| abc
| [2, 3]
| 5.0
> for x in 'abc':
>     print(x)
| a
| b
| c
> for x in range(5, 15, 3):
>     print(x)
| 5
| 8
| 11
| 14
```

Question – What is printed ?

Python shell

```
> for i in range(1, 4):
>     for j in range(i, 4):
>         print(i, j, sep=':', end=' ')
```

a) 1:1 1:2 1:3 2:1 2:2 2:3 3:1 3:2 3:3

b) 1:1 1:2 1:3 2:2 2:3 3:3

c) 1:1 2:1 3:1 1:2 2:2 3:2 1:3 2:3 3:3

d) 1:1 2:1 3:1 2:2 3:2 3:3

e) Don’t know

Question – `break`, what is printed ?

Python shell

```
> for i in range(1, 4):
>     for j in range(1, 4):
>         print(i, j, sep=':', end=' ')
>         if j >= i:
>             break
```

a) *nothing*

b) `1:1`

c) `1:1 2:1 2:2 3:1 3:2 3:3`

d) `1:1 2:2 3:3`

e) Don't know

In nested `for`- and `while`-loops, `break` only breaks the innermost loop

```
    **** COMMODORE 64 BASIC V2 ****

 64K RAM SYSTEM  38911 BASIC BYTES FREE

READY.
10 FOR I=1 TO 10
20 PRINT I
30 NEXT
RUN
 1
 2
 3
 4
 5
 6
 7
 8
 9
 10

READY.
```

```
    **** COMMODORE 64 BASIC V2 ****

 64K RAM SYSTEM  38911 BASIC BYTES FREE

READY.
10 FOR I=1 TO 3
20   FOR J=I TO 3
30     PRINT I,J
40   NEXT
50 NEXT
RUN
 1            1
 1            2
 1            3
 2            2
 2            3
 3            3

READY.
```

Palindromic substrings

- Find all palindromic substrings of length ≥ 2, i.e. substrings spelled identically forward and backwards:

```
abracadrabratrallalla
    i   j           i     j
```

- **Algorithm:** Test all possible substrings (brute force/exhaustive search)
- **Note**: the slice `t[::-1]` is `t` reversed

palindrom.py

```python
s = 'abracadrabratrallalla'

for i in range(len(s)):
    for j in range(i + 2, len(s) + 1):
        t = s[i:j]
        if t == t[::-1]:
            print(t)
```

Python shell

```
| aca
| alla
| allalla
| ll
| llall
| lal
| alla
| ll
```

Sieve of Eratosthenes

- Find all prime numbers ≤ n

- Algorithm:

2 3 4 5 6 7 8 9 10 11 12 13 14 ...
2 3 4 5 6 7 8 9 10 11 12 13 14 ...
2 3 4 5 6 7 8 9 10 11 12 13 14 ...
2 3 4 5 6 7 8 9 10 11 12 13 14 ...
2 3 4 5 6 7 8 9 10 11 12 13 14 ...
2 3 4 5 6 7 8 9 10 11 12 13 14 ...

eratosthenes.py

```
n = 100
prime = [True] * (n + 1)

for i in range(2, n):
    for j in range(2 * i, n + 1, i):
        prime[j] = False

for i in range(2, n + 1):
    if prime[i]:
        print(i, end=' ')
```

Python shell

```
2 3 5 7 11 13 17 19 23 29 31 37 41
43 47 53 59 61 67 71 73 79 83 89
97
```

en.wikipedia.org/wiki/Sieve_of_Eratosthenes

while-else and for-else loops

- Both for- and while-loops can have an optional “else”:

```
for var in sequence:
        block
else:
        block

while condition:
        block
else:
        block
```

- The “else” block is only executed if no `break` is performed in the loop
- The “else” construction for loops is specific to Python, and does not exist in e.g. C, C++ and Java

Linear search

linear-search-while.py

```
L = [7, 3, 6, 4, 12, 'a', 8, 13]
x = 4

i = 0
while i < len(L):
    if L[i] == x:
        print(x, 'at position', i, 'in', L)
        break
    i = i + 1

if i >= len(L):
    print(x, 'not in', L)
```

linear-search-while-else.py

```
i = 0
while i < len(L):
    if L[i] == x:
        print(x, 'at position', i, 'in', L)
        break
    i = i + 1
else:
    print(x, 'not in', L)
```

linear-search-for.py

```
found = False
for i in range(len(L)):
    if L[i] == x:
        print(x, 'at position', i, 'in', L)
        found = True
        break

if not found:
    print(x, 'not in', L)
```

linear-search-for-else.py

```
for i in range(len(L)):
    if L[i] == x:
        print(x, 'at position', i, 'in', L)
        break
else:
    print(x, 'not in', L)
```

linear-search-builtin.py

```
if x in L:
    print(x, 'at position', L.index(x), 'in', L)
else:
    print(x, 'not in', L)
```

Some performance considerations

String concatenation

- To concatenate two (or few) strings use

  str_1 + str_2
  var += *str*

- To concatenate several/many strings use

  ''.join([str_1, str_2, str_3, ... , str_n])

- Concatenating several strings by repeated use of + generates explicitly the longer-and-longer intermediate results; using `join` avoids this slowdown

Python shell

```
> s = 'A' + 'B' + 'C'
> s
| 'ABC'
> 'x'.join(['A', 'B', 'C'])
| 'AxBxC'
> s = ''
> s += 'A'
> s += 'B'
> s += 'C'
> s
| 'ABC'
> L = []
> L.append('A')
> L.append('B')
> L.append('C')
> L
| ['A', 'B', 'C']
> s = ''.join(L)
> s
| 'ABC'
```

string-concatenation.py

```
from time import time
from matplotlib import pyplot as plt

ns = range(10_000, 1_000_000, 10_000)
time_string = []
time_list = []
for n in ns:
    start = time()
    s = ''
    for _ in range(n):
        s += 'abcdefgh'   # slow
    end = time()
    time_string.append(end - start)

    start = time()
    substrings = []
    for _ in range(n):
        substrings.append('abcdefgh');
    s = ''.join(substrings);
    end = time()
    time_list.append(end - start)

plt.plot(ns, time_string, label='string +=')
plt.plot(ns, time_list, label="''.join(list)")
plt.xlabel('n')
plt.ylabel('time')
plt.legend()
plt.show()
```

The internal implementation of Python lists

- Accessing and updating list positions take the same time independently of position
- Creating new / deleting entries in a list depends on position,
  Python optimizes towards updates at the end
- Try to organize your usage of lists to insert / delete elements at the end
  `L.append(element)` and `L.pop()`
- Python lists internally have space for adding ≈ 12.5 % additional entries at the end; when the reserved extra space is exhausted the list is moved to a new chunk of memory with ≈ 12.5 % extra space

github.com/python/cpython/blob/master/Objects/listobject.c

List insertions at front vs end

list-insertions.py

```
from time import time
from matplotlib import pyplot as plt

ns = range(1000, 100_000, 1000)
time_end = []
time_append = []
time_front = []
for n in ns:
    start = time()
    L = []
    for i in range(n):
        L[i:i] = [i]   # insert after list
    end = time()
    time_end.append(end - start)

    start = time()
    L = []
    for i in range(n):
        L.append(i)   # append to list
    end = time()
    time_append.append(end - start)

    start = time()
    L = []
    for i in range(n):
        L[0:0] = [i]   # insert at front
    end = time()
    time_front.append(end - start)

plt.plot(ns, time_front, label='front')
plt.plot(ns, time_append, label='append')
plt.plot(ns, time_end, label='end')
plt.xlabel('n')
plt.ylabel('time')
plt.legend()
plt.show()
```

Updates (insertions + deletions) in the middle of a list

list-updates.py

```
from time import time
from matplotlib import pyplot as plt

ns = range(0, 1_000_001, 10_000)
time_pos = []
L = list(range(1_000_000))  # L = [0, ..., 999_999]
for i in ns:
    start = time()
    for _ in range(1000):
        L[i:i] = [42]  # insert element before L[i]
        del L[i]       # remove L[i] from L
    end = time()
    time_pos.append(end - start)

plt.plot(ns, time_pos)
plt.xlabel('position')
plt.ylabel('time')
plt.show()
```

Tuples and lists

- tuples
- lists
- mutability
- list comprehension
- for-if, for-for
- list()
- any(), all()
- enumerate(), zip()

Tuples

$$(\text{value}_0,\ \text{value}_1,\ \ldots\ ,\ \text{value}_{k-1})$$

- Tuples can contain a sequence of zero or more elements, enclosed by "(" and ")"
- Tuples are immutable
- Tuple of length 0: ()
- Tuple of length 1: (value,)

  Note the comma to make a tuple of length one distinctive from an expression in parenthesis
- In many contexts a tuple with ≥ 1 elements can be written without parenthesis
- Accessors to lists also apply to tuples, slices, ...

Python shell

```
> (1, 2, 3)
| (1, 2, 3)
> ()
| ()
> (42)
| 42
> (42,)
| (42,)
> 1, 2
| (1, 2)
> 42,
| (42,)
> x = (3, 7)
> x
| (3, 7)
> x = 4, 6
> x
| (4, 6)
> x[1] = 42
| TypeError: 'tuple' object does
  not support item assignment
```

Question – What value is `((42,))` ?

a) `42`
b) `(42)`
c) `(42,)`
d) `((42,),)`
e) Don’t know

Warning: Unintended tuples

Python shell

```
>x = 7,      # x = (7,)
>y = 5,      # y = (5,)
>x + y
|(7, 5)
```

Question – What is `x` ?

```
x = [1, [2, 3], (4, 5)]
x[2][0] = 42
```

a) `[1, [42, 3], (4, 5)]`
b) `[1, [2, 3], (42, 5)]`
c) `[1, [2, 3], 42]`
d) TypeError
e) Don’t know

Question – What tree is `('A',(('B','C'),'D'))` ?

```
          /\
         /  \
        /    \
       /      \
      /\      'D'
     /  \
    /    \
   /\    'C'
  /  \
'A'  'B'
```

a)

```
          /\
         /  \
        /    \
       /      \
      /        \
     /\        'D'
    /  \
   /    \
  /    \
'A'    /\
      /  \
    'B'  'C'
```

b)

```
          /\
         /  \
        /    \
       /      \
      /        \
     /\        /\
    /  \      /  \
  'A'  'B'  'C'  'D'
```

c)

```
          /\
         /  \
        /    \
       /      \
      /        \
    'A'        /\
              /  \
             /    \
            /\    'D'
           /  \
         'B'  'C'
```

d)

```
          /\
         /  \
        /    \
       /      \
    'A'      /\
            /  \
         'B'    /\
               /  \
             'C'  'D'
```

e)

f) Don’t know

Tuple assignment

Unpacking

```
Python shell
> point = (10, 25)
> x, y = point
> x
| 10
> y
| 25
```

- Parallel assignments

  `x, y, z = a, b, c`

  is a shorthand for a tuple assignment (right side is a single tuple)

  `(x, y, z) = (a, b, c)`

- First the right-hand side is evaluated completely, and then the individual values of the tuple are assigned to `x`, `y`, `z` left-to-right (length must be equal on both sides)

Nested tuple/lists assignments

- Let hand side can be nested (great for unpacking data)

```
(x, (y, (a[0], w)), a[1])
    = 1, (2, (3, 4)), 5
```

- [...] and (...) on left side matches both lists and tuples of equal length (but likely you would like to be consistent with type of parenthesis)

Python shell

```
> two_points = [(10, 25), (30, 40)]
> (x1, y1, x2, y2) = two_points
| ValueError: not enough values to
  unpack (expected 4, got 2)
> ((x1, y1), (x2, y2)) = two_points
> a = [None, None]
> v = ((2, (3, 4)), 5)
> ((y, (a[0], w)), a[1]) = v
> a
| [3, 5]
> [x, y, z] = (3, 5, 7)
> (x, y, z) = [3, 5, 7]
> [x, (y, z), w] = (1, [2, 3], 4)
> [x, (y, z), w] = (1, [2, (5, 6)], 4)
> z
| (5, 6)
```

Unpacking a sequence with one element

Python shell

```
> x = [42]  # simple assignment
> x
| [42]
> x, = [42]  # unpacking, implicit parenthesis
> x
| 42
> (x,) = [42]  # unpacking
> x
| 42
> x, = [1, 2, 3]
| ValueError: too many values to unpack (expected 1)
```

Tuples vs lists: `a += b`

- Lists
  Extends existing list, i.e., same as `a.extend(b)`

- Tuples
  Must create a new tuple `a + b` and assign to `a`
  (since tuples are immutable)

Python shell

```
> (1, 2) + (3, 4)
| (1, 2, 3, 4)
> x = [1, 2]
> y = x
> y += [3, 4]
> y
| [1, 2, 3, 4]
> x
| [1, 2, 3, 4]

> x = (1, 2)
> y = x
> y += (3, 4)
> y
| (1, 2, 3, 4)
> x
| (1, 2)
```

More on += on lists

- Since `a += b` is the same as `a.extend(b)` we can also do

Python shell

```
> x = [1, 2, 3]
> x += [4, 5, 6]
> x += (7, 8, 9)
> x += range(10, 13)   # 10, 11, 12
> x += 'abc'           # 'a', 'b', 'c'
> print(x)
| [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 'a', 'b', 'c']
> x = [1, 2, 3] + (4, 5, 6)
| TypeError: can only concatenate list (not "tuple") to list
```

- For tuples `+=` only accepts tuples

*variable assignment

- For a tuple of variable length a single **variable name* on the left side will be assigned a *list* of the remaining elements not matched by variables preceding/following *

- *Example*

```
a, *b, c = t
```

is equivalent to

```
a = t[0]
b = t[1:-1]
c = t[-1]
```

- There can be a single * in a left-hand-side tuple (but one new * in each nested tuple)

Python shell

```
> (a, *b, c, d) = (1, 2, 3, 4, 5, 6)
> b
| [2, 3, 4]
> (a, *b, c, d) = (1, 2, 3)
> b
| []
> (a, *b, c, d) = (1, 2)
| ValueError: not enough values to
  unpack (expected at least 3, got 2)
> v = ((1,2,3),4,5,6,(7,8,9,10))
> ((a, *b), *c, (d, *e)) = v
> b
| [2, 3]
> c
| [4, 5, 6]
> e
| [8, 9, 10]
> head, *tail = [1, 2, 3, 4]
> head
| 1
> tail
| [2, 3, 4]
```

Question – What is `b` ?

```
(*a,(b,),c) = ((1,2),((3,4)),((5,)),(6))
```

a) `(1,2)`

b) `(3,4)`

c) `5`

d) `(5,)`

e) `(6)`

f) Don’t know

* in list and tuple construction

- When constructing a list or tuple you can insert zero or more elements from another list/tuple/sequence by inserting **expression*
- There can be an arbitrary number of * expressions in a tuple or list construction

Python shell

```
> A = (1, 2, 3)
> B = ['B', 'C']
> L = [A, B, 4, 5]
> L
| [(1, 2, 3), ['B', 'C'], 4, 5]
> len(L)
| 4
> L = [*A, *B, 4, 5]
> L
| [1, 2, 3, 'B', 'C', 4, 5]
> len(L)
| 7
> (*A, *B, 4, 5)
| (1, 2, 3, 'B', 'C', 4, 5)
```

Python shell

```
> from timeit import timeit
> timeit('A + A + A + A + A + A + A + A', setup='A = [1,2,3,4,5,6,7,8,9,10]')
| 0.665172699955292  # repeated concatenation can be slow
> timeit('[*A, *A, *A, *A, *A, *A, *A, *A]', setup='A = [1,2,3,4,5,6,7,8,9,10]')
| 0.32599859999027103  # * notation can be faster for multiple concatenation
```

list_catenation.py

```
import matplotlib.pyplot as plt
from timeit import timeit

ns = range(2, 101)
P, S = [], []
for n in ns:
    setup = 'A = list(range(10))'
    plus = ' + '.join(['A'] * n)
    star = '[' + ', '.join(['*A'] * n) + ']'
    P.append(timeit(plus, setup=setup))
    S.append(timeit(star, setup=setup))

plt.plot(ns, P, '.-', label='A + ... + A')
plt.plot(ns, S, '.-', label='[*A, ..., *A]')
plt.legend()
plt.ylabel('time (sec $10^{-6}$)')
plt.xlabel('number of As')
plt.show()
```

List comprehension (cool stuff)

- Example:

  `[x*x for x in [1, 2, 3]]`

  returns

  `[1, 4, 9]`

- General

  [*expression* `for` *variable* `in` *sequence*]

  returns a list, where *expression* is computed for each element in *sequence* assigned to *variable*

Python shell

```
> [2*x for x in [1,2,3]]
| [2, 4, 6]
> [2*x for x in (1,2,3)]
| [2, 4, 6]
> [2*x for x in range(10,15)]
| [20, 22, 24, 26, 28]
> [2*x for x in 'abc']
| ['aa', 'bb', 'cc']
> [(None, None) for _ in range(2)]
| [(None, None), (None, None)]
```

List comprehension (it's just syntactic sugar…)

Python shell

```
> [x * 2 for x in [1, 2, 3]]
| [2, 4, 6]

> L = []
> for x in [1, 2, 3]:
>     L.append(x * 2)
> L
| [2, 4, 6]
```

List comprehension (more cool stuff)

- Similarly, to the left-hand-side in assignments, the variable part can be a (nested) tuple of variables for unpacking elements:

[*expression* `for` *tuple of variables* `in` *sequence*]

Python shell

```
> points = [(3, 4), (2, 5), (4, 7)]
> [(x, y, x*y) for (x, y) in points]
| [(3, 4, 12), (2, 5, 10), (4, 7, 28)]
> [(x, y, x*y) for x, y in points]
| [(3, 4, 12), (2, 5, 10), (4, 7, 28)]
> [x, y, x*y for (x, y) in points]
| SyntexError: invalid syntax
```

parenthesis required for the constructed tuples

List comprehension – for-if and multiple for

- List comprehensions can have nested for-loops

  [*expression* `for` v_1 `in` s_1 `for` v_2 `in` s_2 `for` v_3 `in` s_3]

- Can select a subset of the elements by adding an if-condition

  [*expression* `for` v_1 `in` s_1 `if` *condition*]

- and be combined...

Python shell

```
> [(x, y) for x in range(1, 3) for y in range(4, 6)]
| [(1, 4), (1, 5), (2, 4), (2, 5)]
> [x for x in (1, 2) for x in (4, 5)]
| [4, 5, 4, 5]
> [x for x in range(1, 101) if x % 7 == 1 and x % 5 == 2]
| [22, 57, 92]
> [(x, y, x*y) for x in range(1, 11) if 6 <= x <= 7 for y in range(x, 11) if 6 <= y <= 7 and not x == y]
| [(6, 7, 42)]
```

Question – What will print the same?

```
points = [(3,7), (4,10), (12,3), (9,11), (7,5)]
print([(x, y) for x, y in points if x < y])
```

a) `print([x, y for x, y in points if x < y])`
b) `print([(x, y) for p in points if p[0] < p[1]])`
c) `print([p for p in points if p[0] < p[1]])`
d) `print([[x, y] for x, y in points if x < y])`
e) Don’t know

List comprehension – space usage long lists ⚠

Bad: creates new tuples
(64 bytes per point)

Good: looks nice

list_comprehension_space_usage.py

3.7 MB
```
input('press enter')
points = [(x, x + 1) for x in range(10_000_000)]  # dummy points
```
1305.6 MB
```
input('press enter')
selected = [(x, y) for (x, y) in points if y == x + 1]
```
1997.3 MB
```
input('press enter')
selected = [point for point in points if point[1] == point[0] + 1]
```
1387.3 MB
```
input('press enter')
```

Good: refers to existing tuple
(8 bytes per point)

Bad: looks ugly (hard to read)

- Memory usage according to “Task Manager” in Windows
- Unpacking makes code more readable, but creating new tuples requires additional space…

Without comprehension (1 line becomes 5 lines)

Good: looks nice

3.8 MB

1305.6 MB

1383.0 MB

list_unpacking_space_usage.py

```
input('press enter')
points = [(x, x + 1) for x in range(10_000_000)]
input('press enter')
selected = []
for point in points:
    x, y = point  # unpack tuple
    if y == x + 1:
        selected.append(point)  # append original tuple
input('press enter')
```

Good: refers to existing tuple

any, all

- `any(L)` checks if at least one element in the sequence `L` is true (list, tuple, ranges, sequence, strings, ...)

  `any([False, True, False])`

- `all(L)` checks if all elements in the sequence `L` are true

  `all([False, False, True])`

- `any` and `all` return `True` or `False`

Python shell

```
> any((False, True, False))
| True
> any([False, False, False])
| False
> any([])
| False
> all([False, False, True])
| False
> all((True, True, True))
| True
> all(())
| True
> L = (7, 42, 13)
> any([x == 42 for x in L])
| True
> all([x == 42 for x in L])
| False
```

Example – computing primes

Python shell

```
> [x for x in range(2, 50) if all([x % f for f in range(2, x)])]
| [2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47]

> [10 % f for f in range(2, 10)]
| [0, 1, 2, 0, 4, 3, 2, 1]
> all([10 % f for f in range(2, 10)])  #  == 0 is considered False
| False
> [13 % f for f in range(2, 13)]
| [1, 1, 1, 3, 1, 6, 5, 4, 3, 2, 1]
> all([13 % f for f in range(2, 13)])
| True
```

enumerate

`list(enumerate(L))`

returns

`[(0, L[0]), (1, L[1]), ..., (len(L) - 1, L[-1])]`

Python shell

```
> points = [(1, 2), (3, 4), (5, 6)]
> [(idx, x * y) for idx, (x, y) in enumerate(points)]
| [(0, 2), (1, 12), (2,30)]
> L = ('a', 'b', 'c')
> list(enumerate(L))
| [(0, 'a'), (1, 'b'), (2, 'c')]
> L_ = []
> for idx in range(len(L)):
>       L_.append((idx, L[idx]))
> print(L_)
| [(0, 'a'), (1, 'b'), (2, 'c')]
> list(enumerate(['a', 'b', 'c'], start=7))
| [(7, 'a'), (8, 'b'), (9, 'c')]
```

zip

$$\texttt{list(zip(}L_1,L_2,\ldots,L_k\texttt{))} = [(L_1[0],L_2[0],\ldots,L_k[0]),\ldots,(L_1[n\text{-}1],L_2[n\text{-}1],\ldots,L_k[n\text{-}1])]$$

where $n = \min(\text{len}(L_1), \text{len}(L_2),\ldots, \text{len}(L_k))$

- Example ("matrix transpose"):

```
list(zip([1,2,3],
          [4,5,6],
          [7,8,9]))
```

returns

```
[(1, 4, 7),
 (2, 5, 8),
 (3, 6, 9)]
```

Python shell

```
> x = [1, 2, 3]
> y = [4, 5, 6]
| zip(x, y)
> <zip at 0xb02b530>
> points = list(zip(x, y))
> print(points)
| [(1, 4), (2, 5), (3, 6)]
```

Python shell

```
> first = ['Donald', 'Mickey', 'Scrooge']
> last = ['Duck', 'Mouse', 'McDuck']

> for i, (a, b) in enumerate(zip(first, last), start=1):
>     print(i, a, b)

| 1 Donald Duck
| 2 Mickey Mouse
| 3 Scrooge McDuck
```

(Simple) functions

- You can define your own functions using:

  `def` *function-name* `(`var_1, ..., var_k`):`

  body code

- If the body code executes

  `return` *expression*

  the result of *expression* will be returned by the function. If expression is omitted or the body code terminates without performing `return`, then `None` is returned

- When *calling* a function *name* `(`$value_1$,..., $value_k$`)` body code is executed with var_i=$value_i$

Python shell

```
> def sum3(x, y, z):
      return x + y + z

> sum3(1, 2, 3)
| 6
> sum3(5, 7, 9)
| 21

> def powers(L, power):
      P = [x**power for x in L]
      return P

> powers([2, 3, 4], 3)
| [8, 27, 64]
```

Question – What tuple is printed ?

```
def even(x):
    if x % 2 == 0:
        return True
    else:
        return False

print((even(7), even(6)))
```

a) (False, False)
b) (False, True)
c) (True, False)
d) (True, True)
e) Don’t know

Geometric orientation test

Purpose of example

- illustrate tuples
- list comprehension
- matplotlib.pyplot
- floats are strange

$$\det = \begin{vmatrix} 1 & q_x & q_y \\ 1 & r_x & r_y \\ 1 & p_x & p_y \end{vmatrix} = \underbrace{r_x p_y - p_x r_y - q_x p_y + p_x q_y + q_x r_y - r_x q_y}_{6\,! = 720 \text{ different orders to add}}$$

Kettner, Mehlhorn, Pion, Schirra, Yap:
Classroom Examples of Robustness Problems in Geometric Computations

sign-plot.py

```
import matplotlib.pyplot as plt

N = 256
delta = 1 / 2**54
q = (12, 12)
r = (24, 24)
P = []  # points (i, j, det)

for i in range(N):
    for j in range(N):
        p = (1/2 + i * delta, 1/2 + j * delta)
        det = (q[0]*r[1] + r[0]*p[1] + p[0]*q[1]
             - r[0]*q[1] - p[0]*r[1] - q[0]*p[1])
        P.append((i, j, det))

pos = [(i, j) for i, j, det in P if det > 0]
neg = [(i, j) for i, j, det in P if det < 0]
zero = [(i, j) for i, j, det in P if det == 0]

plt.subplot(facecolor='lightgrey', aspect='equal')
plt.xlabel('i')
plt.ylabel('j', rotation=0)

for points, color in [(pos, 'b'), (neg, 'r'), (zero, 'y')]:
    X = [i for i, j in points]
    Y = [j for i, j in points]
    plt.plot(X, Y, color + '. ')

plt.plot([-1, N], [-1, N], 'k-')
plt.show()
```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72

73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144

145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216

217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288

289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360

361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432

433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504

505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576

577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648

649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720

Dictionaries and Sets

- dict
- set
- frozenset
- set/dict comprehensions

Dictionaries (type dict)

$$\{\, key_1 : \; value_1 , \; \ldots , \; key_k : \; value_k \,\}$$

- Stores a mutable set of (key, value) pairs, denoted *items*, with distinct keys, i.e. *maps* keys to values
- Constructing empty dictionary: `dict()` or `{}`
- *dict* [*key*] lookup for key in dictionary, and returns associated value. Key must be present, otherwise a KeyError is raised
- *dict* [*key*] = *value* assigns value to *key*, overriding exising value if present

key	value
'a'	7
'foo'	'42nd'
5	29
'5'	44
5.5	False
False	True
(3, 4)	'abc'

distinct keys, i.e. not "=="

https://docs.python.org/3/tutorial/datastructures.html#dictionaries

Dictionaries (type dict)

Python shell

```
> d = {'a': 42, 'b': 57}
> d
| {'a': 42, 'b': 57}

> d.keys()
| dict_keys(['a', 'b'])

> list(d.keys())
| ['a', 'b']

> d.items()
| dict_items([('a', 42), ('b', 57)])

> list(d.items())
| [('a', 42), ('b', 57)]
```

```
> for key in d:
      print(key)
| a
| b

> for key, val in d.items():
      print('Key', key, 'has value', val)
| Key a has value 42
| Key b has value 57

> {5: 'a', 5.0: 'b'}
| {5: 'b'}
```

Python shell

```
> surname = dict(zip(['Donald', 'Mickey', 'Scrooge'], ['Duck', 'Mouse', 'McDuck']))
> surname['Mickey']
| 'Mouse'
```

Dictionaries (type dict)

Python shell

```
> gradings = [('A', 7), ('B', 4), ('A', 12), ('C', 10), ('A', 7)]
> grades = {}  # empty dictionary
> for student, grade in gradings:
      if student not in grades:  # is key in dictionary
          grades[student] = []
      grades[student].append(grade)
> grades
| {'A': [7, 12, 7], 'B': [4], 'C': [10]}
> print(grades['A'])
| [7, 12, 7]
> print(grades['E'])  # can only lookup keys in dictionary
| KeyError: 'E'
> print(grades.get('E'))  # .get returns None if key not in dictionary
| None
> print(grades.get('E', []))  # change default return value
| []
> print(grades.get('A', []))
| [7, 12, 7]
```

Dictionary initialization

```
Python shell
> d1 = {'A': 7, 'B': 42}
> d2 = dict([('A', 7), ('B', 42)])  # list of (key, value) pairs
> d3 = dict(A=7, B=42)              # keyword arguments to constructor
> d1 == d2 == d3
| True
```

- **Note**: *keyword initialization* only works if keys are strings which are valid keyword arguments to a function – but saves writing a lot of quotes

| and |=

new in Python 3.9
PEP 584

```
Python shell
> d1 = dict(A=1, B=2)
> d2 = dict(B=3, C=4)
> d1 | d2                          # merge dictionaries
| {'A': 1, 'B': 3, 'C': 4}         # rightmost value for 'B' wins
> {**d1, **d2, 'D': 5}             # ** inserts dictionary content
| {'A': 1, 'B': 3, 'C': 4, 'D': 5} # rightmost value for 'B' wins
> d1 |= d2                         # same as d1.update(d2)
> d1
| {'A': 1, 'B': 3, 'C': 4}
```

Dictionary operation	Description
len(d)	Items in dictionary
d[key]	Lookup key
d[key] = value	Update value of key
del d[key]	Delete an existing key
key in d	Key membership
key not in d	Key non-membership
clear()	Remove all items
copy()	Shallow copy
get(key), get(key, default)	d[key] if key in dictionary, otherwise `None` or default
items()	*View* of the dictionaries items
keys()	*View* of the dictionaries keys
values()	*View* of the dictionaries values
pop(key)	Remove key and return previous value
popitem()	Remove and return an arbitrary item
update()	Update key/value pairs from another dictionary

https://docs.python.org/3/library/stdtypes.html#mapping-types-dict

Tuples as dictionary keys

- A tuple can be used as a dictionary key, and parenthesis can be omitted

Python shell -

```
> d = {('a', 1): 7, ('b', 2): 42}
> d[('b', 2)]
| 42
> d['b', 2]  # same as above, parenthesis omitted
| 42
> T = [[None, None], [42, None]]  # 2D table as lists-of-lists
> T[1][0]
| 42
> T[1, 0]  # wrong, T is a list (of lists)
| TypeError: list indices must be integers or slices, not tuple
> T = {(1, 0): 42}  # 2D table as dictionary
> T[1, 0]  # dictionary lookup with tuple (1, 0) as key
| 42
> T[1][0]  # wrong, T has only one key = the tuple (1, 0)
| KeyError: 1
```

Order returned by `list(d.keys())` ?

The Python Standard Library
Mapping Types — dict

"Dictionaries preserve insertion order. Note that updating a key does not affect the order. Keys added after deletion are inserted at the end." (since Python 3.7)

docs.python.org/3/library/stdtypes.html

Python shell

```
> d = {'d': 1, 'c': 2, 'b': 3, 'a': 4}
> d['x'] = 5    # new key at end
> d['c'] = 6    # overwrite value
> del d['b']    # remove key 'b'
> d['b'] = 7    # reinsert key 'b' at end
> d
| {'d': 1, 'c': 6, 'a': 4, 'x': 5, 'b': 7}
```

Raymond Hettinger @ Twitter

See also Raymond's talk @ PyCon 2017

Modern Python Dictionaries
A confluence of a dozen great ideas

Dictionary comprehension

- Similarly to creating a list using list comprehension, one can create a set of key-value pairs:

{*key* : *value* for *variable* in *list*}

Python shell

```
> names = ['Mickey', 'Donald', 'Scrooge']
> list(enumerate(names, start=1))
| [(1, 'Mickey'), (2, 'Donald'), (3, 'Scrooge')]
> dict(enumerate(names, start=1))  # construct dict from pairs
| {1: 'Mickey', 2: 'Donald', 3: 'Scrooge'}
> {name: idx for idx, name in enumerate(names, start=1)}
| {'Mickey': 1, 'Donald': 2, 'Scrooge': 3}
```

Sets (set and frozenset)

$$\{\, value_1, \quad ..., \quad value_k \,\}$$

- Values of type `set` represent mutable sets, where "==" elements only appear once
- Do **not** support: indexing, slicing
- `frozenset` is an immutable version of `set`

Python shell

```
> S = {2, 5, 'a', 'c'}
> T = {3, 4, 5, 'c'}
> S | T
| {2, 3, 4, 5, 'a', 'c'}
> S & T
| {5, 'c'}
```

```
> S ^ T
| {2, 3, 4, 'a'}
> S - T
| {2, 'a'}
> {4, 5, 5.0, 5.1}
| {4, 5, 5.1}
```

Operation	Description
S | T	Set union
S & T	Set intersection
S – T	Set difference
S ^ T	Symmetric difference
set()	Empty set ({} = empty dictionary ⚠)
set(L)	Create set from sequence
x in S	Membership
x not in S	Non-membership
S.isdisjoint(T)	Disjoint sets
S <= T	Subset
S < T	Proper subset
S >= T	Superset
S > T	Proper superset
len(S)	Size of S
S.add(x)	Add x to S (not frozenset)

https://docs.python.org/3/tutorial/datastructures.html#sets
https://docs.python.org/3/library/stdtypes.html#set-types-set-frozenset

Question – What value has the expression ?

```
sorted( { 5, 5.5, 5.0, '5' } )
```

a) `{'5', 5, 5.0, 5.5}`
b) `{5, 5.5}`
c) `['5', 5.0, 5.5]`
d) `['5', 5, 5.5]`
e) TypeError
f) Don’t know

Sets of (frozen) sets

- Sets are mutable, i.e. cannot be used as dictionary keys or elements in sets
- Frozen sets can

Python shell

```
> S = {{'a'}, {'a', 'b'}, {'a', 'c'}}
| TypeError: unhashable type: 'set'
> S = {frozenset({'a'}), frozenset({'a', 'b'}), frozenset({'a', 'c'})}
> frozenset({'a', 'b'}) in S
| True
> {'a', 'b'} in S  # automatically converts unhashable set to frozenset
| True
> {'a', 'b'} == frozenset(['a', 'b'])  # frozenset from list
| True
> D = {frozenset({'a', 'b'}): 42}  # dictionary
> frozenset({'a', 'b'}) in D
| True
> {'a', 'b'} in D  # dictionaries are not that friendly as sets
| TypeError: unhashable type: 'set'
```

Set comprehension

- Similarly to creating a list using list comprehension, one can create a set of values (also using nested for- and if-statements):

{*value* `for` *variable* `in` *list*}

- A value occurring multiple times as *value* will only be included once

primes_set.py

```
n = 101
not_primes = {m for f in range(2, n) for m in range(2 * f, n, f)}
primes = set(range(2, n)) - not_primes
```

Python shell

```
> L = ['a', 'b', 'c']
> {(x,(y,z)) for x in L for y in L for z in L if x != y and y != z and z != x}
| {('a',('b','c')),('a',('c','b')),('b',('a','c')),...,('c',('b','a'))}
> L = {'a', 'b', 'c'}
> {(x,(y,z)) for x in L for y in L - {x} for z in L - {x, y}}
| {('c',('b','a')),('c',('a','b')),('a',('c','b')),...,('b',('a','c'))}
```

Hash, equality, and immutability

- Keys for dictionaries and sets must be *hashable*, i.e. have a __hash__() method returning an integer that does not change over their lifetime and an __eq__() method to check for equality with "=="

`'abc'.__hash__()` could e.g. return `624337162`

`(624337162).__hash__()` would also return `624337162`

- All built-in immutable types are hashable.
  In particular tuples of immutable values are hashable.
  I.e. nested tuples like `(('a'),'b'),('c',('d','e')))`
  representing trees can be used as dictionary keys or stored in a set

Sketch of internal set implementation

Raymond Hettinger,
Modern Python Dictionaries
- A confluence of a dozen great ideas

Membership queries `in`

in.py

```
from random import shuffle, choices
from time import time
import matplotlib.pyplot as plt

time_L = []
time_S = []
time_D = []

ns = [1, *range(100, 2001, 100)]

for n in ns:
    print(f'{n = }')
    L = list(range(n))
    shuffle(L)
    S = set(L)
    D = {value: 42 for value in L}

    queries = choices(L, k=1_000_000)
    for X, times in [(L, time_L), (S, time_S), (D, time_D)]:
        count = 0
        start = time()
        for q in queries:
            if q in X:
                count +=1
        end = time()
        times.append((end - start) / len(queries))

plt.plot(ns, time_L, '.-', label='list')
plt.plot(ns, time_S, '.-', label='set')
plt.plot(ns, time_D, '.-', label='dict')
plt.xlabel('Size of list/set/dict (n)')
plt.ylabel("Average query time for 'in' (seconds)")
plt.legend()
plt.show()
```

⚠ Avoid using **`in`** repeatedly on long lists

Module `collections` (container datatypes)

- Python builtin containers for data: `list`, `tuple`, `dict`, and `set`.
- The module **`collections`** provides further alternatives
  (but these are not part of the language like the builtin containers)

`deque`	double ended queue
`namedtuple`	tuples allowing access to fields by name
`Counter`	special dictionary to count occurrences of elements
…	

https://docs.python.org/3/library/collections.html

deque – double ended queues

- Extends lists with efficient updates at the front
- ⚠ Inserting at the front of a standard Python list takes linear time in the size of the list – very slow for long lists

Python shell

```
> L = list()
> L.append(1)
> L.append(2)
> L.insert(0, 0)   # insert at the front
> L.insert(0, -1)  # slow for long lists
> L.insert(0, -2)
> L
| [-2, -1, 0, 1, 2]
```

```
> from collections import deque
> d = deque()   # create empty deque
> d.append(1)
> d.append(2)
> d.appendleft(0)   # efficient
> d.appendleft(-1)
> d.appendleft(-2)
> d
| deque([-2, -1, 0, 1, 2])
> for e in d: print(e, end=', ')
| -2, -1, 0, 1, 2,
```

namedtuple – tuples with field names

Since Python 3.7 dataclass better choice

- Compromise between `tuple` and `dict`, can increase code readability

Python shell

```
> person = ('Donald Duck', 1934, '3 feet')  # as tuple
> person[1]  # not clear what is accessed
| 1934
> person = {'name': 'Donald Duck', 'appeared': 1934, 'height': '3 feet'}  # as dict
> person['appeared']  # more clear what is accessed, but ['...'] overhead
| 1934
> from collections import namedtuple
> Person = namedtuple('Person', ['name', 'appeared', 'height'])  # create new type
> person = Person('Donald Duck', 1934, '3 feet')  # as namedtuple
> person
| Person(name='Donald Duck', appeared=1934, height='3 feet')
> person.appeared  # short and clear
| 1934
> person[1]  # still possible
| 1934
```

Counter – dictionaries for counting

Python shell

```
> from collections import Counter
> fq = Counter('abracadabra')  # create new counter from a sequence
> fq
| Counter({'a': 5, 'b': 2, 'r': 2, 'c': 1, 'd': 1})  # frequencies of the letters
> fq['a']
| 5
> fq.most_common(3)
| [('a', 5), ('b', 2), ('r', 2)]
> fq['x'] += 5  # increase count of 'x', also valid if 'x' not in Counter yet
> Counter('aaabbbcc') - Counter('aabdd')  # counters can be subtracted
| Counter({'b': 2, 'c': 2, 'a': 1})
> Counter([1, 2, 1, 3, 4, 5]) + Counter([3, 3, 3])  # counters can be added
| Counter({3: 4, 1: 2, 2: 1, 4: 1, 5: 1})
> T = 'AfD adsf dsa f dsaf daf dsaf DSA fda f SA dsa f dsa fdsa f dsAf sAf f dsaf'
> Counter(T.lower().split()).most_common(3)
| [('f', 5), ('dsa', 4), ('dsaf', 4)]
```

Handin 3 & 4 – Triplet distance (Dobson, 1975)

```
(('A','F'),'B'),('D',('C','E')))
```

```
(a)

          /\
         /  \
        /    \
       /      \
      /        \
     /          \
    /\          /\
   /  \        /  \
  /    \      /    \
 /\    'B'  'D'    /\
/  \              /  \
'A'  'F'          'C'  'E'
```

How similar are the trees ?

```
((('D','A'),'B'),'F'),('C','E'))
```

```
(b)

          /\
         /  \
        /    \
       /      \
      /        \
     /          \
    /\          /\
   /  \        /  \
  /    \     'C'  'E'
 /      \
/\      'F'
/  \
/    \
/\    'B'
/  \
'D'  'A'
```

arxiv.org/abs/1706.10284

Handin 3 & 4 – Triplet distance (Dobson, 1975)

Consider all $\binom{n}{3}$ subsets of size three, and count how many do not have identical substructure (topology) in the two trees.

```
    /\
   /  \
  /    \
'D'    /\
      /  \
    'A'  'F'

('D',('A','F'))
```

canonical ordering

```
(a)

anchor *
      / \
     /   \
    /     \
   /       \
  /         \
 /\         /\
/  \       /  \
/   \     /   \
/\   'B' 'D'   /\
/  \          /  \
'A'  'F'     'C'  'E'
```

{'A','D','F'}

```
(b)

/\
/  \
/    \
/      \
/        \
/          \
anchor *     /\
/ \        /  \
/   \     'C'  'E'
/     \
/\     'F'
/  \
/    \
/\    'B'
/  \
'D'  'A'
```

```
    /\
   /  \
  /    \
'F'    /\
      /  \
    'A'  'D'

('F',('A','D'))
```

arxiv.org/abs/1706.10284

Functions

- functions
- return
- scoping
- arguments
- keyword arguments
- *, **
- global variables

(Simple) functions

- You can define your own functions using:

  def ***function-name*** **(*var*$_1$, ..., *var*$_k$):**
  body code

  var$_1$, ..., *var*$_k$ are the *formal parameters*

- If the body code executes

  `return` *expression*

  the result of *expression* will be returned by the function. If expression is omitted or the body code terminates without performing `return`, then `None` is returned

- When *calling* a function ***name*** **(*value*$_1$,..., *value*$_k$)** body code is executed with *var*$_i$=*value*$_i$

Python shell

```
> def sum3(x, y, z):
      return x + y + z

> sum3(1, 2, 3)
| 6
> sum3(5, 7, 9)
| 21

> def powers(L, power):
      P = [x**power for x in L]
      return P

> powers([2,3,4], 3)
| [8, 27, 64]
```

Questions – `poly(3, "10", '3')`?

```
def poly(z, x, y):
    return z * x + y
```

a) `33`
b) `1010103`
c) `'33'`
d) `'1010103'`
e) TypeError
f) Don’t know

Why functions ?

- Avoid writting the same code multiple times, *re-usability*
- Be able to *name a functionality*
- Clearly state the functionality of a piece of code, *abstraction*: *Input* = arguments, *output* = return value (and/or side effects)
- *Encapsulate* code with clear interface to the dependency to the outside world/code
- Share functionality in modules/libraries/packages with other users, *code sharing*
- Increase *readability* of code, smaller independent blocks of code
- Easier systematically *testing* of code
- ...

Some other Python language features helping structuring programs

- Object orientation
- Modules
- Decorators
- Context managers
- Exceptions
- Doc strings
- doctest

Local variables in functions

- The formal arguments and variables assigned to in the body of a function are created as temporary *local variables*

Global variables		Local variables	
sum3	<function>	x	4
a	3	y	5
y	42	z	6
		a	9
		b	15

state just before `return b`

Python shell

```
> def sum3(x, y, z):
      a = x + y
      b = a + z
      return b

> a = 3
> y = 42
> w = sum3(4, 5, 6)
> w
| 15
> a
| 3
> b
| NameError: name 'b' is not defined
> x
| NameError: name 'x' is not defined
> y
| 42
> sum3
| <function sum3 at 0x0356DA98>
```

Global variables

- Variables in function bodies that are only read, are considered access to *global variables*

Python shell

```
> prefix = 'The value is'

> def nice_print(x):
      print(prefix, x)

> nice_print(7)
| The value is 7
> prefix = 'Value ='
> nice_print(42)
| Value = 42
```

Global variables		Local variables	
`nice_print`	`<function>`	`x`	`42`
`prefix`	`'Value ='`		

state just before returning from 2nd `nice_print`

Global vs local variables

- If a function contains an assignment to a variable, the variable is local throughout the function – also before the first assignment

Python shell

```
> x = 42
> def f():
      print(x)   # refers to local variable
      x = 7      # x declared local variable
> f()
| UnboundLocalError: local variable 'x' referenced before assignment
```

global

- Global variables that should be updated in the function body must be declared global in the body:

  `global` *variable*, *variable*, ...

- Note: If you only need to read a global variable, it is not required to be declared global (but would be polite to the readers of your code)

Since `counter` assigned in body, `counter` will be considered to be a local variable

Python shell

```
> counter = 1

> def counted_print(x):
      global counter
      print(f'({counter}) {x}')
      counter += 1

> counted_print(7)
| (1) 7
> counted_print(42)
| (2) 42

> def counted_print(x):
      print(f'({counter}) {x}')
      counter += 1

> counted_print(7)
| UnboundLocalError: local variable
  'counter' referenced before
  assignment
```

Question – What value is printed ?

```
x = 1
def f(a):
    global x
    x = x + 1
    return a + x
print(f(2) + f(4))
```

a) 6
b) 7
c) 8
d) 9
e) 10
f) 11
g) 12
h) Don’t know

Arbitrary number of arguments

- If you would like your function to be able to take a variable number of additional arguments in addition to the required, add a **variable* as the *last* argument
- In a function call *variable* will be assigned a tuple with all the additional arguments

Python shell

```
> def my_print(x, y, *L):
      print('x =', x)
      print('y =', y)
      print('L =', L)

> my_print(2, 3, 4, 5, 6, 7)
| x = 2
| y = 3
| L = (4, 5, 6, 7)
> my_print(42)
| TypeError: my_print() missing 1
  required positional argument: 'y'
```

Unpacking a list of arguments in a function call

- If you have list `L` (or tuple) containing the arguments to a *function call*, you can unpack them in the function call using `*L`

```
L = [x, y, z]
f(*L)
```

is equivalent to calling

```
f(L[0], L[1], L[2])
```

i.e.

```
f(x, y, z)
```

- Note that `f(L)` would pass a single argument to `f`, namely a list
- In a function call several `*` expressions can appear, e.g. `f(*L1, x, *L2, *L3)`

Python shell

```
> import math
> def norm(x, y):
      return math.sqrt(x * x + y * y)
> norm(3, 5)
| 5.830951894845301
> point = (3, 4)
> print(*point, sep=':')
| 3:4
> norm(point)
| TypeError: norm() missing 1 required positional argument: 'y'
> norm(*point)
| 5.0
> def dist(x0, y0, x1, y1):
       return math.sqrt((x1 - x0) ** 2 + (y1 - y0) ** 2)
> p = 3, 7
> q = 7, 4
> dist(p, q)
| TypeError: dist() missing 2 required positional arguments: 'x1' and 'y1'
> dist(*p, *q)
| 5.0
```

Question – How many arguments should `f` take ?

```
a = [1, 2, 3]
b = [4, 5]
c = (6, 7, 8)
d = (9, 10)
f(*a, b, c, *d)
```

a) 4
b) 5
c) 6
d) 7
e) 8
f) 9
g) 10
h) Don’t know

Question – What is `list(zip(*zip(*L)))` ?

```
L = [[1, 2, 3], [4, 5], [6, 7, 8]]
```

a) `[(([1, 2, 3],),), (([4, 5],),), (([6, 7, 8],),)]`

b) `[((1, 4, 6),), ((2, 5, 7),)]`

c) `[(1, 2), (4, 5), (6, 7)]`

d) `[(1, 2, 3), (4, 5), (6, 7, 8)]`

e) `[([1, 2, 3], [4, 5], [6, 7, 8])]`

f) Don’t know

Python shell

```
> list(zip((1, 2, 3), (4, 5, 6)))
| [(1, 4), (2, 5), (3, 6)]
```

Keyword arguments

- Previously we have seen the following (strange) function calls

```
print(7, 14, 15, sep=':', end='')
enumerate(my_list, start=1)
```

- *name=* refers to one of the formal arguments, known as a keyword argument
- A *name* can appear at most once in a function call
- In function calls keyword arguments must follow positional arguments
- Improves readability when arguments have non-obvious order

```
complicated_function(
    name='Mickey',
    city='Duckburg',
    state='Calisota',
    occupation='Detective',
    gender='Male'
)
```

Python shell

```
> def sub(x, y):
      return x - y

> sub(9, 4)
| 5
> sub(y=9, x=4)
| -5
```

Keyword arguments, default values

```
Python shell
> def my_print(a, b, c=5, d=7):
      print(f'{a=} {b=} {c=} {d=}')

> my_print(2, d=3, b=4)
| a=2, b=4, c=5, d=3
```

- When calling a function arguments can be ommitted if the corresponding arguments in the function definition have default values *argument=value*
- Arguments with default values must be after those without
- Default arguments are e.g. also available in Javascript, C++ and C#, and keyword arguments in e.g. Javascript and C#s

Question – What is `f(6, z=2)` ?

```
def f(x, y=3, z=7):
    return x + y + z
```

a) `10`
b) `11`
c) `16`
d) `TypeError: f() missing 1 required positional argument: 'y'`
e) Don’t know

Keyword arguments, mutable default values

- Be carefull: Default value will be shared among calls (which can be usefull)

The Python Language Reference
8.7 Function definitions

"**Default parameter values are evaluated from left to right when the function definition is executed**. This means that the expression is evaluated once, when the function is defined, and that the same "pre-computed" value is used for each call. This is especially important to understand when a default parameter is a mutable object, such as a list or a dictionary: if the function modifies the object (e.g. by appending an item to a list), the default value is in effect modified. This is generally not what was intended. A way around this is to use None as the default"

Python shell

```
> def list_append(e, L=[]):
      L.append(e)
      return L
> list_append('x', ['y', 'z'])
| ['y', 'z', 'x']
> list_append('a')
| ['a']
> list_append('b')
| ['a', 'b']
> list_append('c')
| ['a', 'b', 'c']
```

Python shell

```
> def list_append(e, L=None):
      if L == None:
          L = []
      L.append(e)
      return L
> list_append('x', ['y', 'z'])
| ['y', 'z', 'x']
> list_append('a')
| ['a']
> list_append('b')
| ['b']
> list_append('c')
| ['c']
```

Function call, dictionary of keyword arguments

- If you happen to have a *dictionary* containing the keyword arguments you want to pass to function, you can give all dictionary items as arguments using the single argument ***dictionary*

Python shell

```
> print(3, 4, 5, sep=':', end='#\n')
| 3:4:5#
> print_kwarg = {'sep': ':', 'end': '#\n'}
> print(3, 4, 5, **print_kwarg)
| 3:4:5#
```

Function definition, arbitrary keyword arguments

- If you want a function to accept arbitrary keyword arguments, add an argument ***argument* to the function definition
- When the function is called *argument* will be assigned a dictionary containing the excess keyword arguments

Python shell

```
> def my_print(a, b=3, **c):
        print('a =', a)
        print('b =', b)
        print('c =', c)

> my_print(x=27, y=42, a=7)
| a = 7
| b = 3
| c = {'x': 27, 'y': 42}
```

Example

Python shell

```
> L1 = [1, 'a']
> L2 = ['b', 2, 3]
> D1 = {'y':4, 's':10}
> D2 = {'t':11, 'z':5.0}

> def f(a, b, c, d, e, *f, q=0, x=1, y=2, z=3, **kw):
      print(f'{a=}, {b=}, {c=}, {d=}, {e=}, {f=}\n'
            f'{q=}, {x=}, {y=}, {z=}, {kw=}')
> f(7, *L1, 9, *L2, x=7, **D1, w=42, **D2)
| a=7, b=1, c=a, d=9, e=b, f=(2, 3)
| q=0, x=7, y=4, z=5.0, kw={'w': 42, 's': 10, 't': 11}
```

non-keyword arguments must appear before keyword arguments

all arguments must have distinct names

A confusing example

Python shell

```
> def f(*a, **kw):
      print(f'{a=} {kw=}')

> f(a=42)  # no positional arguments
| a=() kw={'a': 42}
```

Forwarding function arguments

- * and ** can e.g. be used to forward (unknown) arguments to other function calls

Python shell

```
> def my_print(*positional_arguments, sep=':', **keyword_arguments):
      print(*positional_arguments, sep=sep, **keyword_arguments)
> my_print(7, 42)
| 7:42
> my_print('x', 'y', end='<')
| x:y<
> my_print('x', 'y', sep='_')
| x_y
```

Local function definitions and namespaces

- Function definitions can contain (nested) local function definitions, only accessable inside the function
- *static/lexical scoping*, i.e. can see from the code which variables are in scope

Python shell

```
> def a(x):
      def b(y):
          print(f'b: {y=} {x=}')
          c(y + 1)
      def c(z):
          print(f'c: {z=} {x=}')
      print(f'a: {x=}')
      b(x + 1)
> a(42)
| a: x=42
| b: y=43 x=42
| c: z=44 x=42
```

3 4 2 1

Example – nested function definitions

Python shell

```
> def a(x):
      def b(y):
          print(f'Enter b ({y=}, {x=})')
          c(y + 1)
          print('leaving b')
      def c(x):  # x hides argument of function a
          def d(z):
              print(f'Enter d ({z=}, {x=})')
              print('leaving d')
          print(f'Enter c ({x=})')
          d(x + 1)
          print('leaving c')
      print(f'Enter a ({x=})')
      b(x + 1)
      print('leaving a')
```

```
> a(5)
| Enter a (x=5)
| Enter b (y=6, x=5)
| Enter c (x=7)
| Enter d (z=8, x=7)
| leaving d
| leaving c
| leaving b
| leaving a
```

Functions must be defined before you can call them…

Python shell

```
> f()
| NameError: name 'f' is not defined
> def f():
      print('Hi')
> f()
| Hi
> def f():
      g()  # g not yet defined locally
      def g():
          print('Howdy')
> f()
| UnboundLocalError: cannot access local variable 'g' where it is not associated with a value
> def f():
      def g():
          print('Howdy')
      g()
> f()
| Howdy
```

Example – nested functions and default values

Python shell

```
> def init_none(var_name):
>     print('initializing', var_name)
>     return None  # redundant line

> def f(a=init_none('a')):
>     def g(b=init_none('b')):
>         print('b =', b)
>     print('a =', a)
>     g(a + 1)

| initializing a

> f(10)

| initializing b
| a = 10
| b = 11
```

nonlocal

- The keyword `nonlocal` makes local identifiers refer to previously bound variables in the nearest *enclosing scope excluding globals*

- `nonlocal` *variable, variable, …*

Python shell

```
> x = 0

> def f():
      y = 1
      def f_helper(z):
          global x
          nonlocal y
          print(f'({x}:{y}) {z}')
          y += 1
          x += 3
      f_helper(7)
      f_helper(42)

> f()
| (0:1) 7
| (3:2) 42
> f()
| (6:1) 7
| (9:2) 42
```

docs.python.org/3/reference/simple_stmts.html#the-nonlocal-statement

Positional and keyword only arguments

- A function definition can contain / and * as arguments
- Arguments before / must be provided as positional arguments in a call
- Arguments after * cannot be positional arguments

Python shell

```
> def f(a, /, b, *, c):
      print(a, b, c)

> f(a=1, b=2, c=3)
| TypeError: f() got some positional-only arguments passed as keyword arguments: 'a'
> f(1, b=2, c=3)
| 1 2 3
> f(1, 2, c=3)
| 1 2 3
> f(1, 2, 3)
| TypeError: f() takes 2 positional arguments but 3 were given
```

A note on Python and functions

- Similarities between Python and other languages:
  - functions are widely supported (sometimes called methods and procedures)
  - scoping rules is present in many languages (but details differ)
- Python specific (but nice):
  - how to handle global, local and nonlocal variables
  - keyword arguments
  - *, **

Recursion

- symbol table
- stack frames

Recursion

Recursive function
≡
”function that calls itself”

Python shell

```
> def recursive_function(x):
      if x > 0:
          print("start", x)
          recursive_function(x - 1)
          print("end", x)
      else:
          print("done")

> recursive_function(5)
| start 5
| start 4
| start 3
| start 2
| start 1
| done
| end 1
| end 2
| end 3
| end 4
| end 5
```

Recursion

x	0
x	1
x	2
x	3
x	4
x	5
recursive_function	<function>

stack frame

global variables

Recursion stack when x = 0 is reached

Python shell

```
> def recursive_function(x):
      if x > 0:
          print("start", x)
          recursive_function(x - 1)
          print("end", x)
      else:
          print("done")

> recursive_function(5)
| start 5
| start 4
| start 3
| start 2
| start 1
| done
| end 1
| end 2
| end 3
| end 4
| end 5
```

Python shell

```
> def rec(x):
      if x > 0:
          print("start", x)
          rec(x - 1)
          rec(x - 1)
          print("end", x)
      else:
          print("done")
```

Python shell

```
> rec(3)
| start 3
| start 2
| start 1
| done
| done
| end 1
| start 1
| done
| done
| end 1
| end 2
| start 2
| start 1
| done
| done
| end 1
| start 1
| done
| done
| end 1
| end 2
| end 3
```

Recursion tree

Question – How many times does `rec(5)` print "`done`"?

Python shell

```
> def rec(x):
      if x > 0:
          print("start", x)
          rec(x - 1)
          rec(x - 1)
          rec(x - 1)
          print("end", x)
      else:
          print("done")
```

a) 3
b) 5
c) 15
d) 81
e) 125
f) $243 = 3^5$
g) Don't know

Factorial

$$n\,! = n \cdot \underbrace{(n-1) \cdot (n-2) \cdots 3 \cdot 2 \cdot 1}_{(n-1)\,!}$$

Observation
(recursive definition)

$$1\,! = 1$$

$$n\,! = n \cdot (n-1)\,!$$

factorial.py

```
def factorial(n):
    if n <= 1:
        return 1
    return n * factorial(n - 1)
```

factorial.py

```
def factorial(n):
    return n * factorial(n - 1) if n > 1 else 1
```

factorial_iterative.py

```
def factorial(n):
    result = 1
    for i in range(2, n + 1):
        result *= i
    return result
```

Binomial coefficient $\binom{n}{k}$

- $\binom{n}{k}$ = number of ways to pick k elements from a set of size n

- $$\binom{n}{k} = \begin{cases} 1 & \text{if } k = 0 \text{ or } k = n \\ \binom{n-1}{k} + \binom{n-1}{k-1} & \text{otherwise} \end{cases}$$

binomial_recursive.py

```
def binomial(n, k):
    if k == 0 or k == n:
        return 1
    return binomial(n - 1, k) + binomial(n - 1, k - 1)
```

- Unfolding computation shows $\binom{n}{k}$ 1's are added → slow

Readable functions ? – return early / bail out fast

- Treat simple cases first and return
- Do not put `else` after `if` ending with `return`
- Avoid unnecessary nesting of code
- 1-liners are not always the most readable code

binomial_return_early.py

```
def binomial(n, k):  # Ugly, nested indentations and redundant else
    if k == 0:
        return 1
    else:
        if k == n:
            return 1
        else:
            return binomial(n - 1, k) + binomial(n - 1, k - 1)

def binomial(n, k):  # Treat each special case first and return
    if k == 0:
        return 1
    if k == n:
        return 1
    return binomial(n - 1, k) + binomial(n - 1, k - 1)

def binomial(n, k):   # Several cases simultaneously – is test obvious?
    if k == 0 or k == n:
        return 1
    return binomial(n - 1, k) + binomial(n - 1, k - 1)

def binomial(n, k):  # 1-liner, but is this the easiest to read?
    return binomial(n - 1, k) + binomial(n - 1, k - 1) if 0 < k < n else 1
```

See also *Clean Code - Handbook of Agile Software Craftsmanship*, by Robert C. Martin (2009)

Tracing the recursion

- At beginning of function call, print arguments
- Before returning, print return value
- Keep track of recursion depth in a argument to print indentation

binomial_trace.py

```
def binomial(n, k, indent=0):
    print('    ' * indent + f'binomial({n}, {k})')
    if k == 0 or k == n:
        result = 1
    else:
        result = binomial(n - 1, k, indent=indent + 1) + \
                 binomial(n - 1, k - 1, indent=indent + 1)
    print('    ' * indent + f'return {result}')
    return result
```

Python shell

```
> binomial(4, 2)
| binomial(4, 2)
|     binomial(3, 2)
|         binomial(2, 2)
|         return 1
|         binomial(2, 1)
|             binomial(1, 1)
|             return 1
|             binomial(1, 0)
|             return 1
|         return 2
|     return 3
|     binomial(3, 1)
|         binomial(2, 1)
|             binomial(1, 1)
|             return 1
|             binomial(1, 0)
|             return 1
|         return 2
|         binomial(2, 0)
|         return 1
|     return 3
| return 6
| 6
```

Binomial coefficient $\binom{n}{k}$

Observation $\binom{n}{k} = \frac{n\,!}{(n-k)\,!\cdot k\,!}$

binomial_factorial.py

```
def binomial(n, k):
    return factorial(n) // factorial(k) // factorial(n - k)
```

- Unfolding computation shows 2n - 2 multiplications and 2 divisions → fast
- Intermediate value n ! can have significantly more digits than result (bad)

Binomial coefficient $\binom{n}{k}$

Observation $$\binom{n}{k} = \frac{n \cdot (n-1) \cdot (n-2) \cdots (n-k+1)}{k \cdot (k-1) \cdot (k-2) \cdots 1} = \binom{n-1}{k-1} \cdot \frac{n}{k}$$

binomial_recursive_product.py

```
def binomial(n, k):
    if k == 0:
        return 1
    else:
        return binomial(n - 1, k - 1) * n // k
```

- Unfolding computation shows k multiplications and divisions → fast
- Multiplication with fractions ≥ 1 → intermediate numbers limited size

Questions – Which correctly computes $\binom{n}{k}$?

Observation $\binom{n}{k} = \dfrac{n \cdot (n-1) \cdot (n-2) \cdots (n-k+1)}{k \cdot (k-1) \cdot (k-2) \cdots 1}$

a) `binomial_A`
b) `binomial_B`
c) both
d) none
e) Don't know

binomial_iterative.py

```
def binomial_A(n, k):
    result = 1
    for i in range(k):
        result = result * (n - i) // (k - i)
    return result

def binomial_B(n, k):
    result = 1
    for i in range(k)[::-1]:
        result = result * (n - i) // (k - i)
    return result
```

Recursively print all leaves of a tree

- Assume a recursively nested tuple represents a tree with strings as leaves

Python shell

```
> def print_leaves(tree):
      if isinstance(tree, str):
          print('Leaf:', tree)
      else:
          for child in tree:
              print_leaves(child)

> print_leaves(('a',('b','c')))
| Leaf: a
| Leaf: b
| Leaf: c
```

```
    /\
   /  \
 'a'  /\
     /  \
   'b'  'c'
```

Question – How many times is `print_leaves` function called in the example?

```
   /\
  /  \
'a'  /\
    /  \
  'b'  'c'
```

Python shell

```
> def print_leaves(tree):
      if isinstance(tree, str):
          print('Leaf:', tree)
      else:
          for child in tree:
              print_leaves(child)

> print_leaves(('a',('b','c')))
| Leaf: a
| Leaf: b
| Leaf: c
```

a) 3
b) 4
c) 5
d) 6
e) Don’t know

Python shell

```
> def collect_leaves_wrong(tree, leaves = set()):
      if isinstance(tree, str):
          leaves.add(tree)
      else:
          for child in tree:
              collect_leaves_wrong(child, leaves)
      return leaves

> def collect_leaves_right(tree, leaves = None):
      if leaves == None:
          leaves = set()
      if isinstance(tree, str):
          leaves.add(tree)
      else:
          for child in tree:
              collect_leaves_right(child, leaves)
      return leaves
```

```
> collect_leaves_wrong(('a',('b','c')))
| {'a', 'c', 'b'}
> collect_leaves_wrong(('d',('e','f')))
| {'b', 'e', 'a', 'f', 'c', 'd'}

> collect_leaves_right(('a',('b','c')))
| {'b', 'a', 'c'}
> collect_leaves_right(('d',('e','f')))
| {'f', 'd', 'e'}
```

Python shell

```
> def collect_leaves(tree):
      leaves = set()

      def traverse(tree):
          nonlocal leaves  # can be omitted
          if isinstance(tree, str):
              leaves.add(tree)
          else:
              for child in tree:
                  traverse(child)

      traverse(tree)
      return leaves

> collect_leaves(('a', ('b', 'c')))
| {'b', 'a', 'c'}
> collect_leaves(('d', ('e', 'f')))
| {'f', 'd', 'e'}
```

Maximum recursion depth ?

- Pythons maximum allowed recursion depth can be increased by

```
import sys
sys.setrecursionlimit(1500)
```

Python shell

```
> def f(x):
      print("#", x)
      f(x + 1)

> f(1)
| # 1
| # 2
| # 3
| ...
| # 975
| # 976
| # 977
| # 978
| RecursionError: maximum
  recursion depth exceeded
  while pickling an object
```

Koch Curves

koch_curve.py

```
import matplotlib.pyplot as plt
from math import sqrt

def koch(p, q, depth=3):
    if depth == 0:
        return [p, q]

    (px, py), (qx, qy) = p, q
    dx, dy = qx - px, qy - py
    h = 1 / sqrt(12)
    p1 = px + dx / 3, py + dy / 3
    p2 = px + dx / 2 - h * dy, py + dy / 2 + h * dx
    p3 = px + dx * 2 / 3, py + dy * 2 / 3
    return (koch(p,  p1, depth - 1)[:-1]
            + koch(p1, p2, depth - 1)[:-1]
            + koch(p2, p3, depth - 1)[:-1]
            + koch(p3, q,  depth - 1))

points = koch((0, 0), (1, 0), depth=3)
X, Y = zip(*points)

plt.subplot(aspect='equal')
plt.plot(X, Y, 'r-')
plt.plot(X, Y, 'k.')
plt.show()
```

remove last point (equal to first point in next recursive call)

en.wikipedia.org/wiki/Koch_snowflake

Z-curves

z_curve.py

```python
import matplotlib.pyplot as plt

def z_curve(depth, x0=0, y0=0, x1=1, y1=1):
    x, y = (x0 + x1) / 2, (y0 + y1) / 2
    if depth == 0:
        return [(x, y)]
    return [
        *z_curve(depth - 1, x0, y0, x, y),
        *z_curve(depth - 1, x, y0, x1, y),
        *z_curve(depth - 1, x0, y, x, y1),
        *z_curve(depth - 1, x, y, x1, y1)
    ]

for depth in range(4):
    X, Y = zip(*z_curve(depth))
    plt.subplot(2, 2, 1 + depth, aspect='equal')
    plt.title(f'depth {depth}')
    plt.axis('off')
    plt.axis([0, 1, 0, 1])
    plt.plot(
        [0,1,1,0,0], [0,0,1,1,0], 'k:',  # dash box
        [0.5,0.5], [0,1], 'k:',  # dash vertical
        [0,1], [0.5,0.5], 'k:',  # dash horizontal
        X, Y, 'k-',  # Z-curve
        X, Y, 'r.',  # Z-curve points
    )
plt.show()
```

en.wikipedia.org/wiki/Z-order_curve

Recursion and iteration

- algorithm examples

Standard 52-card deck

	Ace	2	3	4	5	6	7	8	9	10	Jack	Queen	King
Clubs													
Diamonds													
Hearts													
Spades													

en.wikipedia.org/wiki/Standard_52-card_deck

Selection sort

selection_sort.py

```
def selection_sort(L):
    unsorted = L[:]
    result = []

    while unsorted:
        e = min(unsorted)
        unsorted.remove(e)
        result.append(e)

    return result
```

- `min` and `.remove` scan the remaining `unsorted` list for each element moved to `result`
- order $|L|^2$ comparisons

Sorting a pile of cards (Merge sort)

- If one card in pile, i.e. pile is sorted
- Otherwise

1) Split pile into two piles, **left** and **right**, of approximately same size
2) Sort **left** and **right** recursively (independently)
3) Merge **left** and **right** (which are sorted)

merge_sort.py

```python
def merge_sort(L):
    n = len(L)
    if n <= 1:
        return L[:]
    mid = n // 2
    left, right = L[:mid], L[mid:]
    return merge(merge_sort(left), merge_sort(right))

def merge(A, B):
    n = len(A) + len(B)
    C = n * [None]
    a, b = 0, 0
    for c in range(n):
        if a < len(A) and (b == len(B) or A[a] < B[b]):
            C[c] = A[a]
            a = a + 1
        else:
            C[c] = B[b]
            b = b + 1
    return C
```

Question – Depth of recursion for 52 elements

a) 1
b) 2
c) 3
d) 4
e) 5
f) 6
g) 7
h) 8
i) 9
j) 10
k) Don’t know

Question – Order of comparisons by Merge sort ?

a) ~ n

b) ~ $n\sqrt{n}$

c) ~ $n \log_2 n$

d) ~ n^2

e) ~ n^3

f) Don't know

merge_sort.py

```
def merge_sort(L):
    n = len(L)
    if n <= 1:
        return L[:]
    else:
        mid = n // 2
        left, right = L[:mid], L[mid:]
        return merge(merge_sort(left), merge_sort(right))

def merge(A, B):
    n = len(A) + len(B)
    C = n * [None]
    a, b = 0, 0
    for c in range(n):
        if a < len(A) and (b == len(B) or A[a] < B[b]):
            C[c] = A[a]
            a = a + 1
        else:
            C[c] = B[b]
            b = b + 1
    return C
```

Growth of some functions

Merge sort without recursion

- Start with piles of size one
- Repeatedly merge two smallest piles

merge_sort.py

```
def merge_sort_iterative(L):
    Q = [[x] for x in L]
    while len(Q) > 1:
        Q.insert(0, merge(Q.pop(), Q.pop()))
    return Q[0]

from collections import deque

def merge_sort_deque(L):
    Q = deque([[x] for x in L])
    while len(Q) > 1:
        Q.appendleft(merge(Q.pop(), Q.pop()))
    return Q[0]
```

insert at front of list inefficient

deques are a generalization of lists with efficient updates at both ends

```
merge_sort_iterative([7,1,9,3,-2,5])
```

Values of Q in while-loop

```
[[7], [1], [9], [3], [-2], [5]]
[[-2, 5], [7], [1], [9], [3]]
[[3, 9], [-2, 5], [7], [1]]
[[1, 7], [3, 9], [-2, 5]]
[[-2, 3, 5, 9], [1, 7]]
[[-2, 1, 3, 5, 7, 9]]
```

Note: Lists in Q appear in non-increasing length order, where longest ≤ 2· shortest

Question – Number of iterations of while-loop ?

```
merge_sort_iterative([7, 1, 9, 3, -2, 5])
```

a) 1
b) 2
c) 3
d) 4
e) 5
f) 6
g) 7
h) Don’t know

merge_sort.py

```
def merge_sort_iterative(L):
    Q = [[x] for x in L]
    while len(Q) > 1:
        Q.insert(0, merge(Q.pop(), Q.pop()))
    return Q[0]
```

Quicksort (randomized)

quicksort.py

```
import random

def quicksort(L):
    if len(L) <= 1:
        return L[:]

    idx = random.randrange(len(L))
    pivot = L[idx]
    other = L[:idx] + L[idx + 1:]

    small = [e for e in other if e < pivot]
    large = [e for e in other if e >= pivot]

    return quicksort(small) + [pivot] + quicksort(large)
```

order $|L| \cdot \log_2 |L|$ comparisons, expected

Sorting comparison (single run)

tuned merge-sort (Tim-sort) implementation in C

|L|	Selection sort	Merge sort Recursive	Merge sort Iterative	Merge sort Deque	Quicksort	sorted (Python builtin)
2^{10}	0.006	0.002	0.003	0.002	0.002	0.00004
2^{11}	0.02	0.004	0.006	0.000	0.003	0.0001
2^{12}	0.09	0.008	0.01	0.008	0.007	0.0003
2^{13}	0.37	0.02	0.04	0.03	0.02	0.0007
2^{14}	1.50	0.04	0.10	0.06	0.03	0.002
2^{15}	6.19	0.08	0.26	0.13	0.07	0.003
2^{16}	25.67	0.18	0.81	0.26	0.14	0.008
2^{17}	104.20 x 4	0.38	2.96	0.61	0.29	0.02
2^{18}		0.81	10.78	1.29	0.62	0.04
2^{19}		1.69	41.71	2.58	1.48	0.09
2^{20}		3.65	167.31 x 4	5.15	3.30	0.20
2^{21}		7.85		9.68	7.53	0.45
2^{22}		16.69 x 2		19.09 x 2	17.6 x 2	1.00 x 2

Sorting comparison

Find zero

- Given a list L of integers starting with a negative and ending with a positive integer, and where |L[i+1] - L[i]| ≤ 1, find the position of a zero in L.

L = [-5, -4, -3, -3, -4, -3, -2, -1, 0, 1, 2, 1, 0, -1, -2, -1, 0 , 1, 2, 3, 2]

find_zero.py

```python
def find_zero_loop(L):
    i = 0
    while L[i] != 0:
        i += 1
    return i

def find_zero_enumerate(L):
    for i, e in enumerate(L):
        if e == 0:
            return i

def find_zero_index(L):
    return L.index(0)
```

```python
def find_zero_binary_search(L):
    low = 0
    high = len(L) - 1
    while True:  # L[low] < 0 < L[high]
        mid = (low + high) // 2
        if L[mid] == 0:
            return mid
        elif L[mid] < 0:
            low = mid
        else:
            high = mid

def find_zero_recursive(L):
    def search(low, high):
        mid = (low + high) // 2
        if L[mid] == 0:
            return mid
        elif L[mid] < 0:
            return search(mid, high)
        else:
            return search(low, mid)

    return search(0, len(L) - 1)
```

find_zero.py

```python
def find_zero_loop(L):
    i = 0
    while L[i] != 0:
        i += 1
    return i

def find_zero_enumerate(L):
    for i, e in enumerate(L):
        if e == 0:
            return i

def find_zero_index(L):
    return L.index(0)
```

Function (|L| = 10^6)	Time, sec
find_zero_loop	0.13
find_zero_enumerate	0.10
find_zero_index	0.015
find_zero_binary_search	0.000015
find_zero_recursive	0.000088

```python
def find_zero_binary_search(L):
    low = 0
    high = len(L) - 1
    while True:  # L[low] < 0 < L[high]
        mid = (low + high) // 2
        if L[mid] == 0:
            return mid
        elif L[mid] < 0:
            low = mid
        else:
            high = mid

def find_zero_recursive(L):
    def search(low, high):
        mid = (low + high) // 2
        if L[mid] == 0:
            return mid
        elif L[mid] < 0:
            return search(mid, high)
        else:
            return search(low, mid)

    return search(0, len(L) - 1)
```

Greatest Common Divisor (GCD)

Notation $x \uparrow y$ denotes y is divisible by x, e.g. $3 \uparrow 12$
i.e. $y = a \cdot x$ for some integer a

Definition $\gcd(m, n) = \max \{ x \mid x \uparrow m \text{ and } x \uparrow n \}$

Fact if $x \uparrow y$ and $x \uparrow z$ then $x \uparrow (y + z)$ and $x \uparrow (y - z)$

Observation
(recursive definition)

$$\gcd(m, n) = \begin{cases} m & \text{if } m = n \\ \gcd(m, n - m) & \text{if } m < n \\ \gcd(m - n, n) & \text{if } m > n \end{cases}$$

gcd(90, 24)

m	n
90	24
66	24
42	24
18	24
18	6
12	6
6	6

Greatest Common Divisor (GCD)

gcd_slow.py

```
def gcd(m, n):
    while m != n:
        if n > m:
            n = n - m
        else
            m = m - n
    return m
```

gcd_slow_recursive.py

```
def gcd(m, n):
    if m == n:
        return m
    elif m > n:
        return gcd(m - n, n)
    else:
        return gcd(m, n - m)
```

gcd.py

```
def gcd(m, n):
    while n != 0:
        m, n = n, m % n
    return m
```

gcd_recursive.py

```
def gcd(m, n):
    if n == 0:
        return m
    else:
        return gcd(n, m % n)
```

gcd_recursive_one_line.py

```
def gcd(m, n):
    return m if n == 0 else gcd(n, m % n)
```

Permutations

- Generate a list L of all permutations of a tuple

Python shell

```
> permutations(('a', 'b', 'c'))
| [('a', 'b', 'c'), ('b', 'a', 'c'), ('b', 'c', 'a'),
   ('a', 'c', 'b'), ('c', 'a', 'b'), ('c', 'b', 'a')]
```

permutations.py

```
def permutations(L):
    if len(L) == 0:
        return [L[:]]  # empty tuple (ensures same type as L)
    else:
        P = permutations(L[1:])
        return [p[:i] + L[:1] + p[i:] for p in P for i in range(len(L))]
```

- An implementation of `permutations` exists in the itertools module

Maze solver

Input

- First line #rows and #columns
- Following #rows lines contain strings containing #column characters
- There are exactly one 'A' and one 'B'
- '.' are free cells and '#' are blocked cells

Output

- Print whether there is a path from 'A' to 'B' or not

maze input

```
11 19
#######A##########
#.......#.....#...#
#.###.###...#.#.#.#
#...#.....#.#...#.#
#.#.###.#.#.#.###.#
#.#.....#...#.#...#
#.##########.#.#.#
#.#.#.....#...#.#.#
#.#.#####.#####.#.#
#.........#.....#.#
##############B###
```

Maze solver (recursive)

maze_solver.py

```
def explore(i, j):
    global solution, visited

    if (0 <= i < n and 0 <= j < m and
        maze[i][j] != '#' and not visited[i][j]):

        visited[i][j] = True

        if maze[i][j] == 'B':
            solution = True

        explore(i - 1, j)
        explore(i + 1, j)
        explore(i, j - 1)
        explore(i, j + 1)
```

maze input

```
11 19
#######A###########
#.......#.....#...#
#.###.###...#.#.#.#
#...#.....#.#...#.#
#.#.###.#.#.#.###.#
#.#.....#...#.#...#
#.###########.#.#.#
#.#.#.....#...#.#.#
#.#.#####.#####.#.#
#.........#.....#.#
###############B###
```

```
def find(symbol):
    for i, row in enumerate(maze):
        j = row.find(symbol)
        if j >= 0:
            return (i, j)

n, m = [int(x) for x in input().split()]
maze = [input() for i in range(n)]

solution = False
visited = [m * [False] for i in range(n)]

explore(*find('A'))

if solution:
    print('path from A to B exists')
else:
    print('no path')
```

Maze solver (iterative)

maze_solver_iterative.py

```
def explore(i, j):
    global solution, visited

    Q = [(i, j)]  # cells to visit

    while Q:
        i, j = Q.pop()
        if (0 <= i < n and 0 <= j < m and
            maze[i][j] != '#' and not visited[i][j]):

            visited[i][j] = True

            if maze[i][j] == 'B':
                solution = True

            Q.append((i - 1, j))
            Q.append((i + 1, j))
            Q.append((i, j - 1))
            Q.append((i, j + 1))
```

```
def find(symbol):
    for i, row in enumerate(maze):
        j = row.find(symbol)
        if j >= 0:
            return (i, j)

n, m = [int(x) for x in input().split()]
maze = [input() for i in range(n)]

solution = False
visited = [m*[False] for i in range(n)]

explore(*find('A'))

if solution:
    print("path from A to B exists")
else:
    print("no path")
```

Question – How difficult is the triplet project on a scale 1 – 10 ?

a) 1 (I'm offended by how trivial the project was)
b) 2 (very easy)
c) 3 (a quite standard review exercise)
d) 4 (not too complicated, got some known concepts repeated)
e) 5 (good exercise to repeat standard programming techniques)
f) 6 (had to use more advanced techniques in a familiar way)
g) 7 (quite complicated, but manageable)
h) 8 (very abstract exercise, using complicated language constructs)
i) 9 (very complicated – barely manageable spending all my time)
j) 10 (this is a research project – could be an MSc thesis/PhD project)
k) 25 (this is wayyy too complicated for a university course)

Functions as objects

- lambda
- higher-order functions
- map, filter, reduce

Aliasing functions – both user defined and builtin

Python shell

```
> def square(x):
      return x * x
> square
| <function square at 0x0329A390>
> square(8)
| 64
> kvadrat = square
| kvadrat(5)
| 25
> kvadrat
| <function square at 0x0329A390>
> len
| <built-in function len>
> length = len
> length([1, 2, 3])
| 3
```

Functions as values

square_or_double.py

```
def square(x):
        return x * x

def double(x):
        return 2 * x

while True:
    answer = input('square or double ? ')
    if answer == 'square':
        f = square
        break
    if answer == 'double':
        f = double
        break

answer = input('numbers: ')
L_in = [int(x) for x in answer.split()]
L_out = [f(x) for x in L_in]
print(L_out)
```

Python shell

```
| square or double ? square
| numbers: 3 6 7 9
| [9, 36, 49, 81]

| square or double ? double
| numbers: 2 3 4 7 9
| [4, 6, 8, 14, 18]
```

`f` will refer to one of the functions `square` and `double` refer to

call the function `f` is referring to with argument `x`

Functions as values and namespaces

say.py

```
def what_says(name):
    def say(message):
        print(name, 'says:', message)
    return say

alice = what_says('Alice')
peter = what_says('Peter')

alice('Where is Peter?')
peter('I am here')
```

Python shell

```
| Alice says: Where is Peter?
| Peter says: I am here
```

- `what_says` is a function returning a function (`say`)
- Each call to `what_says` with a single string as its argument **creates a new `say`** function with the current `name` argument in its namespace
- In each call to a an instance of a `say` function, `name` refers to the string in the namespace when the function was created, and `message` is the string given as an argument in the call

Question – What list is printed ?

```
def f(x):
    def g(y):
        nonlocal x
        x = x + 1
        return x + y
    return g
a = f(3)
b = f(6)
print([a(3), b(2), a(4)])
```

a) [7, 7, 10]
b) [7, 9, 8]
c) [7, 9, 9]
d) [7, 9, 12]
e) [7, 10, 10]
f) Don't know

map

- `map(function, list)` applies the function to each element of the sequence `list`
- `map(function, list`$_1$`, …, list`$_k$`)` requires `function` to take k arguments, and creates a sequence with the i'th element being `function(list`$_1$`[i], …, list`$_k$`[i])`

Python shell

```
> def square(x):
      return x * x
> list(map(square, [1,2,3,4,5]))
| [1, 4, 9, 16, 25]
> def triple_sum(x, y, z):
      return x + y + z
> list(map(triple_sum, [1,2,3], [4,5,6], [7,8,9]))
| [12, 15, 18]
> list(map(triple_sum, *zip(*[(1,4,7), (2,5,8), (3,6,9)])))
| [12, 15, 18]
```

sorted

- A list `L` can be sorted using `sorted(L)`
- A user defined order on the elements can be defined by providing a function using the keyword argument `key`, that maps elements to values with some default ordering

Python shell

```
> def length_square(p):
      x, y = p
      return x**2 + y**2  # no sqrt

> L = [(5, 3), (2, 5), (1, 9), (2, 2), (3, 4)]
> list(map(length_square, L))
| [34, 29, 82, 8, 25]
> sorted(L)  # default lexicographical order
| [(1, 9), (2, 2), (2, 5), (3, 4), (5, 3)]
> sorted(L, key=length_square)  # order by length
| [(2, 2), (3, 4), (2, 5), (5, 3), (1, 9)]
```

https://docs.python.org/3/library/functions.html#sorted

Question – What list does sorted produce ?

```
sorted([2, 3, -1, 5, -4, 0, 8, -6], key=abs)
```

key 2 3 1 5 4 0 8 6

a) `[-6, -4, -1, 0, 2, 3, 5, 8]`

b) `[0, 2, 3, 5, 8, -1, -4, -6]`

c) `[0, -1, 2, 3, -4, 5, -6, 8]`

d) `[8, 5, 3, 2, 0, -1, -4, -6]`

e) `[0, 1, 2, 3, 4, 5, 6, 8]`

f) Don't know

Python shell

```
> abs(7)
| 7
> abs(-42)
| 42
```

filter

- `filter(function, list)` returns the subsequence of `list` where `function` evaluates to true
- Essentially the same as

```
[x for x in list if function(x)]
```

Python shell

```
> def odd(x):
      return x % 2 == 1

> filter(odd, range(10))
| <filter object at 0x03970FD0>
> list(filter(odd, range(10)))
| [1, 3, 5, 7, 9]
```

reduce (in module functools)

- Python's "reduce" function is in other languages often denoted "foldl"

$$\texttt{reduce(f, [}x_1\texttt{, }x_2\texttt{, }x_3\texttt{, ..., }x_k\texttt{]) = f(}\cdots\texttt{f(f(}x_1\texttt{, }x_2\texttt{), }x_3\texttt{)}\cdots\texttt{, }x_k\texttt{)}$$

Python shell

```
> from functools import reduce

> def power(x, y):
      return x ** y

> reduce(power, [2, 2, 2, 2, 2])
| 65536
```

lambda (anonymous functions)

- If you need to define a *short* function, that *returns a value*, and the function is only *used once* in your program, then a lambda function might be appropriate:

```
lambda arguments: expression
```

- Creates a function with no name that takes zero or more arguments, and returns the value of the single expression

Python shell

```
> f = lambda x, y: x + y  # discouraged by PEP 8, use def
> f(2, 3)
| 5
> list(filter(lambda x: x % 2, range(10)))
| [1, 3, 5, 7, 9]
```

History of lambda in programming languages

- Lambda calculus invented by Alonzo Church in 1930s
- At the heart of functional programming languages
  - LISP (1958)
  - ML (1973) and its derivatives, e.g. OCaml (1996) and F* (2011)
  - Haskell (1990), based on Miranda (1985)
- C++ got lambdas with C++11 in 2011 (26 years after 1st release)
- Java first got lambdas with Java 8 in 2014 (19 years after 1st release)
- Python has had lambdas since its inception in 1994

Examples: sorted using lambda

Python shell

```
> L = [ 'AHA', 'Oasis', 'ABBA', 'Beatles', 'AC/DC', 'B. B. King', 'Bangles', 'Alan Parsons']

> # Sort by length, secondary after input position (default, known as stable)
> sorted(L, key=len)
| ['AHA', 'ABBA', 'Oasis', 'AC/DC', 'Beatles', 'Bangles', 'B. B. King', 'Alan Parsons']

> # Sort by length, secondary alphabetically
> sorted(L, key=lambda s: (len(s), s))
| ['AHA', 'ABBA', 'AC/DC', 'Oasis', 'Bangles', 'Beatles', 'B. B. King', 'Alan Parsons']

> # Sort by most 'a's, if equal by number of 'b's, etc.
> sorted(L, key=lambda s: sorted([a.lower() for a in s if a.isalpha()] + ['~']))
| ['Alan Parsons', 'ABBA', 'AHA', 'Beatles', 'Bangles', 'AC/DC', 'Oasis', 'B. B. King']

> sorted([a.lower() for a in 'AC/DC' if a.isalpha()] + ['~'])
| ['a', 'c', 'c', 'd', '~']  # '~' is larger than all letters 'a'-'z'
```

min and max

- Similarly to `sorted`, the functions `min` and `max` take a keyword argument `key`, to map elements to values with some default ordering

Python shell

```
> max(['w', 'xyz', 'abcd', 'uv'])
| 'xyz'
> max(['w', 'xyz', 'abcd', 'uv'], key=len)
| 'abcd'
> sorted([210, 13, 1010, 30, 27, 103], key=lambda x: str(x)[::-1])
| [1010, 210, 30, 103, 13, 27]
> min([210, 13, 1010, 30, 27, 103], key=lambda x: str(x)[::-1])
| 1010
```

docs.python.org/3/library/functions.html#min

defaultdict (from module collections)

- An extension of the built-in dict that automatically initializes undefined items on access by calling a function (factory) to produce a default value to be inserted

`defaultdict(`*function to create default value*`,` *normal dict arguments*`)`

Python shell

```
> scores = {'Mickey': [2, 3, 1], 'Goofy': [1, 0, 2]}
> scores['Gladstone']  # access to undefined key in a standard dictionary
| KeyError: 'Gladstone'

> from collections import defaultdict
> scores = defaultdict(lambda : [], {'Mickey': [2, 3, 1], 'Goofy': [1, 0, 2]})
> scores
| defaultdict(<function <lambda> at 0x0000026460F0BBE0>, {'Mickey': [2, 3, 1], 'Goofy': [1, 0, 2]})
> scores['Gladstone']  # calls lambda without arguments to initialize scores['Gladstone']
| []
> scores
| defaultdict(<function <lambda> at ...>, {'Mickey': [2, 3, 1], 'Goofy': [1, 0, 2], 'Gladstone': []})
> scores = defaultdict(list, Mickey=[2, 3, 1], Goofy=[1, 0, 2])
> scores['daisy'].append(7)  # calls list() to initialize scores['daisy']
> scores
| defaultdict(<class 'list'>, {'Mickey': [2, 3, 1], 'Goofy': [1, 0, 2], 'daisy': [7]})
```

docs.python.org/3/library/collections.html#collections.defaultdict

polynomial.py

```python
def linear_function(a, b):
    return lambda x: a * x + b

def degree_two_polynomial(a, b, c):
    def evaluate(x):
        return a * x**2 + b * x + c

    return evaluate

def polynomial(coefficients):
    return lambda x: sum([c * x**p for p, c in enumerate(coefficients)])

def combine(f, g):
    def evaluate(*args, **kwargs):
        return f(g(*args, **kwargs))

    return evaluate

f = linear_function(2, 3)
for x in [0, 1, 2]:
    print(f'f({x}) = {f(x)}')

p = degree_two_polynomial(1, 2, 3)
for x in [0, 1, 2]:
    print(f'p({x}) = {p(x)}')

print(f'{polynomial([3, 2, 1])(2) = }')

h = combine(abs, lambda x, y: x - y)
print(f'{h(3, 5) = }')
```

Python shell

```
f(0) = 3
f(1) = 5
f(2) = 7
p(0) = 3
p(1) = 6
p(2) = 11
polynomial([3, 2, 1])(2) = 11
h(3, 5) = 2
```

Question – What value is h(1) ?

linear_combine.py

```
def combine(f, g):
    def evaluate(*args, **kwargs):
        return f(g(*args, **kwargs))

    return evaluate

def linear_function(a, b):
    return lambda x: a * x + b

f = linear_function(2, 3)
g = linear_function(4, 5)

h = combine(f, g)

print(h(1))
```

a) 5

b) 9

c) 16

d) 21

e) 25

f) Don’t know

Namespace example

linear_combine.py

```
def combine(f, g):
    def evaluate(*args, **kwargs):
        return f(g(*args, **kwargs))

    return evaluate

def linear_function(a, b):
    return lambda x: a * x + b

f = linear_function(2, 3)
g = linear_function(4, 5)

h = combine(f, g)

print(h(1))
```

partial (trace of computation)

partial_trace.py

```python
def partial(fn, *args):
    def new_f(*a):
        print(f'new_f: fn={fn.__name__}, args={args}, a={a})')
        answer = fn(*args, *a)
        print(f'answer={answer}')
        return answer

    return new_f

def f(x, y, z):
    print(f'f({x},{y},{z})')
    return x + 2 * y + 3 * z

g = partial(f, 7)
h = partial(f, 2, 1)
k = partial(g, 1, 2)

print(f'{g(2, 1)=}\n')   # 7 + 2 * 2 + 3 * 1 = 14
print(f'{h(3)=}\n')      # 2 + 2 * 1 + 3 * 3 = 13
print(f'{k()=}\n')       # 7 + 2 * 1 + 3 * 2 = 15
```

Python shell

```
| new_f: fn=f, args=(7,), a=(2, 1))
| f(7,2,1)
| answer=14
| g(2, 1)=14
|
| new_f: fn=f, args=(2, 1), a=(3,))
| f(2,1,3)
| answer=13
| h(3)=13
|
| new_f: fn=new_f, args=(1, 2), a=())
| new_f: fn=f, args=(7,), a=(1, 2))
| f(7,1,2)
| answer=15
| answer=15
| k()=15
```

Python shell

```
> def f(x): return x
> g = lambda x: x
> f.__name__
| 'f'
> g.__name__
| '<lambda>'
```

functools.partial

Object oriented programming

- classes, objects
- self
- construction
- encapsulation

Object Oriented Programming

- **Programming paradigm**, other paradigms are e.g.
  - *functional programming* where the focus is on functions, lambda's and higher order functions, and
  - *imperative programming* focusing on sequences of statements changing the state of the program
- Core concepts are **objects**, **methods** and **classes**,
  - allowing one to construct *abstract data types*, i.e. user *defined types*
  - objects have states
  - methods manipulate objects, defining the interface of the object to the rest of the program
- OO supported by many programming languages, including Python

Object Oriented Programming - History

(selected programming languages)

Mid 1960's **Simula 67**

(Ole-Johan Dahl and Kristen Nygaard, Norsk Regnesentral Oslo)
Introduced classes, objects, virtual procedures

1970's **Smalltalk** (Alan Kay, Dan Ingalls, Adele Goldberg, Xerox PARC)

Object-oriented programming, fully dynamic system
(opposed to the static nature of Simula 67)

1985 **Eiffel** (Bertrand Meyer, Eiffel Software)

Focus on software quality, capturing the full software cycle

1985 **C++** (Bjarne Stroustrup [MSc Aarhus 1975], AT&T Bell Labs)

1995 **Java** (James Gosling, Sun)

2000 **C#** (Anders Hejlsberg (studied at DTU) et al., Microsoft)

1991 **Python** (Guido van Rossum)

Multi-paradigm programming language, fully dynamic system

Byte Magazine, August 1981

Note: Java, C++, Python, C# are among Top 5 on TIOBE March 2024 index of popular languages (only non OO language among Top 5 was C)

Design Patterns (not part of this course)

reoccuring patterns in software design

The Classic book 1994
(C++ cookbook)

A very alternative book 2004
(Java, very visual)

Java cookbook 2003

Java textbook 2004

Java textbook 2010

...and many more books on the topic of Design Patterns, also with Python

Some known classes, objects, and methods

Type / class	Objects	Methods (examples)
int	0 -7 42 1234567	.__add__(x), .__eq__(x), .__str__()
str	"" 'abc' '12_ a'	.isdigit(), .lower(), .__len__()
list	[] [1,2,3] ['a', 'b', 'c']	.append(x), .clear(), .__mul__(x)
dict	{'foo' : 42, 'bar' : 5}	.keys(), .get(), .__getitem__(x)
NoneType	None	.__str__()

Example:

The function `str(obj)` calls the methods `obj.__str__()` or `obj.__repr__()`, if `obj.__str__` does not exist.

`print` calls `str`.

Python shell

```
> 5 + 7  # + calls .__add__(7)
| 12
> (5).__add__(7)  # eq. to 5 + 7
| 12
> (7).__eq__(7)  # eq. to 7 == 7
| True
> 'aBCd'.lower()
| 'abcd'
> 'abcde'.__len__()
  # .__len__() called by len(...)
| 5
> ['x', 'y'].__mul__(2)
| ['x', 'y', 'x', 'y']
> {'foo' : 42}.__getitem__('foo')
  # eq. to {'foo' : 42}['foo']
| 42
> None.__str__()  # used by str(...)
| 'None'
> 'abc'.__str__(), 'abc'.__repr__()
| ('abc', "'abc'")
```

Classes and Objects

class
(type)

```
class Student
```

class methods

```
set_name(name)
set_id(student_id)

get_name()
get_id()
```

creating **instances** of class `Student` using **constructor** `Student()`

objects
(instances)

```
student_DD
name = 'Donald Duck'
id = '107'
```

data attributes

```
student_MM
name = 'Mickey Mouse'
id = '243'
```

```
student_SM
name = 'Scrooge McDuck'
id = '777'
```

docs.python.org/3/tutorial/classes.html

Using the `Student` class

student.py

```
student_DD = Student()
student_MM = Student()
student_SM = Student()

student_DD.set_name('Donald Duck')
student_DD.set_id('107')

student_MM.set_name('Mickey Mouse')
student_MM.set_id('243')

student_SM.set_name('Scrooge McDuck')
student_SM.set_id('777')

students = [student_DD, student_MM, student_SM]

for student in students:
    print(student.get_name(),
          'has id',
          student.get_id())
```

Python shell

```
Donald Duck has id 107
Mickey Mouse has id 243
Scrooge McDuck has id 777
```

Call **constructor** for class `Student`. Each call returns a new `Student` object.

Call class methods to set data attributes

Call class methods to read data attributes

class Student

name of class

docstring containing documentation for class

class definitions start with the keyword `class`

student.py

```
class Student:
    '''Documentation of class'''

    def set_name(self, name):
        self.name = name

    def set_id(self, student_id):
        self.id = student_id

    def get_name(self):
        return self.name

    def get_id(self):
        return self.id
```

the first argument to all class methods is a reference to the object called upon, and by convention the first argument should be named `self`.

use `self.` to access an attribute of an object or class method (attribute reference)

often called **mutator methods**, since they change the state of an object

often called **accessor methods**, since they only read the state of an object

class method definitions start with keyword `def` (like normal function definitions)

Note In other OO programming languages the explicit reference to **self** is not required (in Java and C++ `self` is the keyword `this`)

When are object attributes initialized ?

```
Python shell
> x = Student()
> x.set_name("Gladstone Gander")
> x.get_name()
| 'Gladstone Gander'
> x.get_id()
| AttributeError: 'Student' object has no attribute 'id'
```

- Default behaviour of a class is that instances are created with no attributes defined, but has access to the attributes / methods of the class
- In the previous class `Student` both the `name` and `id` attributes were first created when set by `set_name` and `set_id`, respectively

Class construction and `__init__`

- When an object is created using *`class_name`*`()` it's initializer metod `__init__` is called.
- To initialize objects to contain default values, (re)define this function.

student.py

```
class Student:
    def __init__(self):
        self.name = None
        self.id = None

    ... previous method definitions ...
```

Question – What is printed ?

Python shell

```
> class C:
      def __init__(self):
            self.v = 0
      def f(self):
            self.v = self.v + 1
            return self.v
> x = C()
> print(x.f() + x.f())
```

a) 1
b) 2
c) 3
d) 4
e) 5
f) Don’t know

__init__ with arguments

- When creating objects using *class_name*(*args*) the initializer method is called as __init__(*args*)
- To initialize objects to contain default values, (re)define this function to do the appropriate initialization

student.py

```
class Student:
    def __init__(self, name=None, student_id=None):
        self.name = name
        self.id = student_id

    ... previous method definitions ...
```

Python shell

```
> p = Student('Pluto')
> print(p.get_name())
| Pluto
> print(p.get_id())
| None
```

Are accessor and mutator methods necessary ?

No - but good programming style

Python shell

```
> p = Pair(3, 5)
> p.sum()
| 8
> p.set_a(4)
> p.sum()
| 9
> p.a      # access object attribute
| 4
> p.b = 0 # update object attribute
> p.sum()
| 9        # the_sum not updated
```

pair.py

```
class Pair:
    """ invariant: the_sum = a + b """
    def __init__(self, a, b):
        self.a = a
        self.b = b
        self.the_sum = self.a + self.b
    def set_a(self, a):
        self.a = a
        self.the_sum = self.a + self.b
    def set_b(self, b):
        self.b = b
        self.the_sum = self.a + self.b
    def sum(self):
        return self.the_sum
```

constructor

mutator

accessor

Converting objects to `str`

- To be able to convert an object to a string using `str(object)`, define the method `__str__`
- `__str__` is e.g. used by `print`

Student_constructor.py

```
class Student:
    def __str__(self):
        return f"Student('{self.name}', '{self.id}')"
    ... previous method definitions ...
```

Python shell

```
> print(student_DD)  # without __str__
| <__main__.Student object at 0x03AB6B90>
> print(student_DD)  # with __str__
| Student('Donald Duck', '107')
```

Defining order on instances of a class (sorting)

- To define an order on objects, define the “<“ operator by defining `__lt__`
- When ”<” is defined a list `L` of students can be sorted using `sorted(L)` and `L.sort()`

student.py

```
class Student:
    def __lt__(self, other):
        return self.id < other.id

    ... previous method definitions ...
```

Python shell

```
> student_DD < student_MM
| True
> [x.id for x in students]
| ['243', '107', '777']
> [x.id for x in sorted(students)]
| ['107', '243', '777']
```

Nothing is private in Python

- Python does not support **hiding information** inside objects
- Recommendation is to start attributes with underscore, if these should be used only locally inside a class, i.e. be considered ”private”
- **PEP8:** “Use one leading underscore only for non-public methods and instance variables“

private_attributes.py

```
class My_Class:
    def set_xy(self, x, y):
        self._x = x
        self._y = y

    def get_sum(self):
        return self._x + self._y

obj = My_Class()
obj.set_xy(3, 5)

print('Sum =', obj.get_sum())
print('_x =', obj._x)
```

Python shell

```
| Sum = 8
| _x = 3
```

C++ private, public

C++ vs Python

1. argument types
2. return types
3. `void` = `NoneType`
4. `private` / `public` access specifier
5. types of data attributes
6. data attributes must be defined in class
7. object creation
8. no `self` in class methods

private_attributes.cpp

```
#include <iostream>

using namespace std;

class My_Class {
private: ④
 ⑤int x, y; ⑥
public: ④        ⑧①        ①
②③void set_xy(int a, int b) {
     x = a;
     y = b
   };            ⑧
② int get_sum() {
     return x + y;
   };
};

main() {
⑦ My_Class obj;
   obj.set_xy(3, 5);
   cout << "Sum = " << obj.get_sum() << endl;
   cout << "x = " << obj.x << endl;
}
```

invalid reference

Java private, public

Java vs Python

1. argument types
2. return types
3. `void` = `NoneType`
4. `private` / `public` access specifier
5. types of data attributes
6. data attributes must be defined in class
7. object creation
8. no `self` in class methods

private_attributes.java

```
class My_Class {
④ private int x, y; ⑥
④ public void set_xy(int a, int b) {
    x = a; y = b;
  }
④ public int get_sum() { return x + y; };
};
class private_attributes {
  public static void main(String args[]){
  ⑦ My_Class obj = new My_Class();
    obj.set_xy(3, 5);
    System.out.println("Sum = " + obj.get_sum());
    System.out.println("x = " + obj.x);
  }
}
```

invalid reference

Name mangling (partial privacy)

- Python handles references to class attributes inside a class definition with *at least two leading underscores and at most one trailing underscore* in a special way: `__attribute` is textually replaced by `_classname__attribute`

- Note that [Guttag, p. 200] states ”that attribute is not visible outside the class” – which only is partially correct (see example)

name_mangeling.py

```
class MySecretBox:
    def __init__(self, secret):
        self.__secret = secret
```

Python shell

```
> x = MySecretBox(42)
> print(x.__secret)
| AttributeError: 'MySecretBox'
  object has no attribute
  '__secret'
> print(x._MySecretBox__secret)
| 42
```

Class attributes

class

class attributes

```
class Student
next_id = 3

set_name(name)
set_id(student_id)

get_name()
get_id()
```

object

```
student_DD
name = 'Donald Duck'
id = '2'
```

data attributes

- *obj.attribute* first searches the objects attributes to find a match, if no match, continuous to search the attributes of the class
- Assignments to *obj.attribute* are always to the objects attribute (possibly creating the attribute)
- Class attributes can be accesed directly as *class.attribute* (or *obj.__class__.attribute*)

Class data attribute

- **next_id** is a class attribute
- Accessed using **Student.next_id**
- The lookup ① can be replaced with **self.next_id**, since only the class has this attribute, looking up in the object will be propagated to a lookup in the class attributes
- In the update ② it is crucial that we update the class attribute, since otherwise the incremented value will be assigned as an object attribute

  (What will the result be?)

student_auto_id.py

```
class Student:
    next_id = 1  # class attribute
    def __init__(self, name):
        self.name = name
        self.id = str(Student.next_id)  ①
      ② Student.next_id += 1
    def get_name(self):
        return self.name
    def get_id(self):
        return self.id

students = [Student('Scrooge McDuck'),
            Student('Donald Duck'),
            Student('Mickey Mouse')]
for student in students:
    print(student.get_name(),
          "has student id",
          student.get_id())
```

Python shell

```
| Scrooge McDuck has student id 1
| Donald Duck has student id 2
| Mickey Mouse has student id 3
```

Question – What does `obj.get()` return ?

Python shell

```
> class MyClass:
      x = 2

      def get(self):
          self.x = self.x + 1
          return MyClass.x + self.x

> obj = MyClass()
> print(obj.get())
| ?
```

a) 4

b) 5

c) 6

d) UnboundLocalError

e) Don’t know

Class data attribute example (in Python)

class_attributes.py

```
class My_Class:
    x = 1  # class attribute
    def inc(self):
        My_Class.x = self.x + 1
obj1 = My_Class()
obj2 = My_Class()
obj1.inc()
obj2.inc()
print(obj1.x, obj2.x)
```

Python shell

```
| 3 3
```

- Note that `My_Class.x` and `self.x` refer to the same class attribute (since `self.x` has never been assigned a value)

__dict__, __name__ and __class__

Python shell

```
> MM = Student('Mickey Mouse')
> MM.__dict__                                  # objects attributes
| {'name': 'Mickey Mouse', 'id': '1'}
> MM.__class__                                 # objects class (reference to object of type class)
| <class '__main__.Student'>
> Student.__name__                             # class name (string)
| 'Student'
> Student.__dict__                             # class attributes
| mappingproxy({
  '__module__': '__main__',                                          # module where class defined
  'next_id': 2,                                                      # class data attriute
  '__init__': <function Student.__init__ at 0x000002831344CD30>,     # class method
  'get_name': <function Student.get_name at 0x000002831344CE50>,     # class method
  'get_id': <function Student.get_id at 0x000002831344CEE0>,         # class method
  '__dict__': <attribute '__dict__' of 'Student' objects>,           # attributes of class
  '__weakref__': <attribute '__weakref__' of 'Student' objects>,     # (for garbage collecting)
  '__doc__': None                                                    # docstring
  })
```

Java `static`

- In Java *class attributes,* i.e. attribute values shared by all instances, are labeled **`static`**
- Python allows both class and instance attributes with the same name – in Java at most one of them can exist

static_attributes.java

```
class My_Class {
    public static int x = 1;
    public void inc() { x += 1; };
}

class static_attributes {
    public static void main(String args[]){
        My_Class obj1 = new My_Class();
        My_Class obj2 = new My_Class();
        obj1.inc();
        obj2.inc();
        System.out.println(obj1.x);
        System.out.println(obj2.x);
    }
}
```

Java output

```
3
3
```

C++ static

- In C++ *class attributes,* i.e. attribute values shared by all instances, are labeled **static**
- ISO C++ forbids in-class initialization of non-const static member
- Python allows both class and instance attributes with the same name – in C++ at most one of them can exist

static_attributes.cpp

```cpp
#include <iostream>
using namespace std;
class My_Class {
public:
  static int x; // "= 1" is not allowed
  void inc() { x += 1; };
};
int My_Class::x = 1; // class initialization
int main(){
  My_Class obj1;
  My_Class obj2;
  obj1.inc();
  obj2.inc();
  cout << obj1.x << endl;
  cout << obj2.x << endl;
}
```

C++ output

```
3
3
```

Constants

- A simple usage of class data attributes is to store a set of constants (but there is nothing preventing anyone to chance these values)

Python shell

```
> class Color:
      RED   = "ff0000"
      GREEN = "00ff00"
      BLUE  = "0000ff"
> Color.RED
| 'ff0000'
```

PEP8 Style Guide for Python Code (some quotes)

- Class names should normally use the CapWords convention.
- Always use self for the first argument to instance methods.
- Use one leading underscore only for non-public methods and instance variables.
- For simple public data attributes, it is best to expose just the attribute name, without complicated accessor/mutator methods.
- Always decide whether a class's methods and instance variables (collectively "attributes") should be public or non-public.
  If in doubt, choose non-public; it's easier to make it public later than to make a public attribute non-public.

www.python.org/dev/peps/pep-0008/

Some methods many classes have

Method	Description
`__eq__(self, other)`	Used to test if two elements are equal Two elements where __eq__ is true must have equal __hash__
`__str__(self)`	Used by `str` and `print`
`__repr__(self)`	Used by `repr`, e.g. for printing to the IDE shell (usually something that is a valid Python expression for `eval()`)
`__len__(self)`	Length (integer) of object, e.g. lists, strings, tuples, sets, dictionaries
`__doc__`	The docstring of the class
`__hash__(self)`	Returns hash value (integer) of object Dictionary keys and set values must have a __hash__ method
`__lt__(self, other)`	Comparison (less than, <) used by `sorted` and `sort()`
`__init__(self,...)`	Class initializer

Overloading operators: www.python-course.eu/python3_magic_methods.php

Class hierarcies

- inheritance
- method overriding
- super
- multiple inheritance

Calling methods of a class

- If an object *obj* of class *C* has a method `method`, then usually you call *obj*`.`*method*`()`

- It is possible to call the method in the class directly using *C*`.`*method*, where the object is the first argument

  C`.`*method*`(`*obj*`)`

X.py

```
class X:
    def set_x(self, x):
        self.x = x

    def get_x(self):
        return self.x

obj = X()

obj.set_x(42)

print(f'{obj.get_x() = }')
print(f'{obj.x = }')
print(f'{X.get_x(obj) = }')
```

Python shell

```
| obj.get_x() = 42
| obj.x = 42
| X.get_x(obj) = 42
```

Classes and Objects

Observation: students and employees are persons with additional attributes

```
class Person
set_name(name)
get_name()

set_address(address)
get_address()
```

instance →

```
Person object
name = 'Mickey Mouse'
address = 'Mouse Street 42, Duckburg'
```

```
class Student
set_name(name)
get_name()

set_address(address)
get_address()

set_id(student_id)
get_id()

set_grade(course, grade)
get_grades()
```

instance →

```
Student object
name = 'Donald Duck'
address = 'Duck Steet 13, Duckburg'
id = '1094'
grades = {'programming' : 'A' }
```

```
Employee object
name = 'Goofy'
address = 'Clumsy Road 7, Duckburg'
employer = 'Yarvard University'
```

Classes and Objects

```
class Person
set_name(name)
get_name()

set_address(address)
get_address()
```

```
class Student
set_name(name)
get_name()

set_address(address)
get_address()

set_id(student_id)
get_id()

set_grade(course, grade)
get_grades()
```

person attributes

Goal – avoid redefining the 4 methods below from `person` class again in `student` class

person.py

```
class Person:
    def set_name(self, name):
        self.name = name

    def get_name(self):
        return self.name

    def set_address(self, address):
        self.address = address

    def get_address(self):
        return self.address
```

Classes inheritance

```
class Person
set_name(name)
get_name()

set_address(address)
get_address()
```

```
class Student
set_name(name)
get_name()

set_address(address)
get_address()

set_id(student_id)
get_id()

set_grade(course, grade)
get_grades()
```

person attributes

class `Student` inherits from class `Person`
class `Person` is the base class of `Student`

person.py

```
class Student(Person):
    def set_id(self, student_id):
        self.id = student_id

    def get_id(self):
        return self.id

    def set_grade(self, course, grade):
        self.grades[course] = grade

    def get_grades(self):
        return self.grades
```

Classes constructors

```
class Person
set_name(name)
get_name()

set_address(address)
get_address()
```

```
class Student
set_name(name)
get_name()

set_address(address)
get_address()

set_id(student_id)
get_id()

set_grade(course, grade)
get_grades()
```

person attributes

person.py

```
class Person:
    def __init__(self):
        self.name = None
        self.address = None
    ...

class Student(Person):
    def __init__(self):
        self.id = None
        self.grades = {}
        Person.__init__(self)
    ...
```

constructor for `Person` class

constructor for `Student` class

Notes

1) If `Student.__init__` is not defined, then `Person.__init__` will be called
2) `Student.__init__` must call `Person.__init__` to initialize the `name` and `address` attributes

super()

class Person

```
set_name(name)
get_name()

set_address(address)
get_address()
```

class Student

```
set_name(name)
get_name()

set_address(address)
get_address()

set_id(student_id)
get_id()

set_grade(course, grade)
get_grades()
```

person attributes

person.py

```
class Person:
    def __init__(self):
        self.name = None
        self.address = None
    ...

class Student(Person):
    def __init__(self):
        self.id = None
        self.grades = {}
        Person.__init__(self)
        super().__init__()
    ...
```

alternative constructor

Notes

1) Function `super()` searches for attributes in base class
2) `super` is often a keyword in other OO languages, like Java and C++
3) Note `super().__init__()` does not need `self` as argument

Method search order

```
class Person
set_name(name)
get_name()

set_address(address)
get_address()
```

```
class Student(Person)
set_id(student_id)
get_id()

set_grade(course, grade)
get_grades()
```

```
Student object
name = 'Donald Duck'
address = 'Duck Steet 13, Duckburg'
id = '1094'
grades = {'programming' : 'A' }
```

Class hierarchy

Method overriding

overloading.py

```
class A:
    def say(self):
        print('A says hello')

class B(A):  # B is a subclass of A
    def say(self):
        print('B says hello')
        super().say()
```

Python shell

```
> B().say()
| B says hello
| A says hello
```

In Java one can use the keyword "`finally`" to prevent any subclass to override a method

Question – What does `b.f()` print ?

Python shell

```
> class A:
      def f(self):
          print("Af")
          self.g()
      def g(self):
          print("Ag")

> class B(A):
      def g(self):
          print("Bg")

> b = B()
> b.f()
| ?
```

a) `AttributeError`

b) `Af Ag`

c) `Af Bg`

d) Don’t know

Undefind methods in superclass ?

Python shell

```
> class A:
      def f(self):
          print("Af")
          self.g()
      def g(self):
          print("Ag")
> class B(A):
      def g(self):
          print("Bg")
> b = B()
> b.f()
| Af
| Bg
> a = A()
> a.f()
| Af
| Ag
```

Python shell

```
> class A:
      def f(self):
          print("Af")
          self.g()
> class B(A):
      def g(self):
          print("Bg")
> b = B()
> b.f()
| Af
| Bg
> a = A()
> a.f()
| Af
| AttributeError: 'A' object has no attribute 'g'
```

method `g` undefined in class `A`; subclasses must implement `g` to be able to call `f`

in Java, `A` would have been required to be declared an *abstract class*

can create instance of `A`

fails since `g` is not defined in class `A`

Name mangling and inheritance ⚠

```
Python shell
> class A:
      def f(self):
          print("Af")
          self.__g()
      def __g(self):
          print("Ag")
> class B(A):
      def __g(self):
          print("Bg")
> b = B()
> b.f()
| Af
| Ag
```

- The call to `A.__g` in `A.f` forces a call to `__g` to stay within `A`
- Recall that due to name mangling, `__g` is accessible as `A._A__g`

Multiple inheritance

- A class can inherit attributes from multiple classes (in example two)
- When calling a method defined in several ancestor classes, Python executes only one of the these (in the example `say_hello`)
- Which one is determined by the so called ”C3 Method Resolution Order” (originating from the Dylan language)

multiple_inheritance.py

```
class Alice:
    def say_hello(self):
        print("Alice says hello")
    def say_good_night(self):
        print("Alice says good night")
class Bob:
    def say_hello(self):
        print("Bob says hello")
    def say_good_morning(self):
        print("Bob says good morning")
class X(Alice, Bob):  # Multiple inheritance
    def say(self):
        self.say_good_morning()
        self.say_hello()        # C3 resolution
        Alice.say_hello(self)   # from Alice
        Bob.say_hello(self)     # from Bob
        self.say_good_night()
```

Python shell

```
> X().say()
| Bob says good morning
| Alice says hello
| Alice says hello
| Bob says hello
| Alice says good night
```

since `Alice` before `Bob` in list of super classes

Raymond Hettinger, *Super considered super!*
Conference talk at PyCon 2015

C3 Method resolution order

- Use `help(class)` to determine the resolution order for the class
- or access the `__mro__` attribute of the class

Python shell

```
> X.__mro__
| (<class '__main__.X'>, <class '__main__.Alice'>,
  <class '__main__.Bob'>, <class 'object'>)
> help(X)
| Help on class X in module __main__:
| class X(Alice, Bob)
|  |  Method resolution order:
|  |      X
|  |      Alice
|  |      Bob
|  |      builtins.object
|  |  Methods defined here:
|  |  say(self)
|  |  ----------------------------------
|  |  Methods inherited from Alice:
|  |  say_good_night(self)
|  |  say_hello(self)
|  |  ----------------------------------
|  |  ...
|  |  ----------------------------------
|  |  Methods inherited from Bob:
|  |  say_good_morning(self)
```

Question – Who says hello ? Bob says good morning

inheritance.py

```
class Alice:
    def say_hello(self):
        print("Alice says hello")
class Bob:
    def say_hello(self):
        print("Bob says hello")
    def say_good_morning(self):
        self.say_hello()
        print("Bob says good morning")
class X(Alice, Bob):  # Multiple inheritance
    pass

X().say_good_morning()
```

a) Alice
b) Bob
c) Dont’ know

…example of code injection using multiple inheritance and where body of new class is empty

Comparing objects and classes

- `id(obj)` returns a unique identifyer for an object (in CPython the memory address)
- `obj1 is obj2` tests if `id(obj1) == id(obj2)`
- `type(obj)` and `obj.__class__` return the class of an object
- `isinstance(object, class)` checks if an object is of a particular class, *or a derived subclass*
- `issubclass(class1, class2)` checks if `class1` is a subclass of `class2`

Note: PEP8 recommends to use `isinstance(x, int)` over `type(x) is int`

`is` is not for integers, strings, … and `is` is not ==

Python shell

```
> 500 + 500 is 1000
| True
> x = 500
> x + x is 1000
| False
> x + x == 1000  # int.__eq__(...)
| True
> for x in range(0, 1000):
      if x - 1 + 1 is not x:
          print(x)
          break
| 257
> for x in range(0, -1000, -1):
      if x + 1 - 1 is not x:
          print(x)
          break
| -6
```

Python shell

```
> "abc" is "abc"
| True
> "abc" is "xabc"[1:]
| False
> x, y = "abc", "xabc"[1:]
> x, y
| ('abc', 'abc')
> x is y
| False
> x == y  # x.__eq__(y)
| True
```

- Only use `is` on objects !
- Even though `isinstance(42, object)` and `isinstance("abc", object)` are true, do not use `is` on integers and strings !

Comparison of OO in Python, Java and C++

- private, public, ... – in Python everything in an object is public
- class inheritance – core concept in OO programming
  - Python and C++ support multiple inheritance
  - Java only allows single inheritance, but Java ”interfaces” allow for something like multiple inheritance
- Python and C++ allow overloading standard operators (+, *, ...). In Java it is not possible
- Overloading methods
  - Python extremely dynamic (hard to say anything about the behaviour of a program in general)
  - Java and C++’s type systems allow several methods with same name in a class, where they are distinguished by the type of the arguments, whereas Python allows only one method that can have * and ** arguments

Python is really dynamic…
(this is ugly – likely don't do this at home)

Python shell

```
> class Pair:
      def __init__(self, x, y):
          self._x = x
          self._y = y

> point = Pair(3, 5)
> print(point)  # class Pair has no __str__ method, uses object.__str__
| <__main__.Pair object at 0x0000027571904B50>

> Pair.__str__ = lambda self: f'Pair({self._x}, {self._y})'

> print(point)
| Pair(3, 5)
```

dynamically add a method to an existing class (and all existing instances),
e.g. technique used by the class decorator `@functools.total_ordering`

C++ example

- Multiple methods with identical name (`print`)
- The types distinguish the different methods

printing.py

```python
class MyClass:
    def print(self, value):
        if isinstance(value, int):
            print('An integer', value)
        elif isinstance(value, str):
            print('A string', value)

C = MyClass()
C.print(42)
C.print('abc')
```

printing.cpp

```cpp
#include <iostream>
using namespace std;

class MyClass {
public:
  void print(int x) {
    cout << "An integer " << x << endl;
  };

  void print(string s) {
    cout << "A string " << s << endl;
  };
};

main() {
  MyClass C;

  C.print(42);
  C.print("abc");
}
```

Shell

```shell
| An integer 42
| A string abc
```

Exceptions and file input/output

- try-raise-except-finally
- Exception
- control flow
- match - case
- file open/read/write
- sys.stdin, sys.stdout, sys.stderr
- context manager

Exceptions – Error handling and control flow

- Exceptions is a widespread technique to handle run-time **errors** / abnormal behaviour (e.g. in Python, Java, C++, JavaScript, C#)

- Exceptions can also be used as an **advanced control flow mechanism** (e.g. in Python, Java, JavaScript)

  - *Problem: How to perform a ”break” in a recursive function ?*

Built-in exceptions (class hierarchy)

```
BaseException
 +-- SystemExit
 +-- KeyboardInterrupt
 +-- GeneratorExit
 +-- Exception
      +-- StopIteration
      +-- StopAsyncIteration
      +-- ArithmeticError
      |    +-- FloatingPointError
      |    +-- OverflowError
      |    +-- ZeroDivisionError
      +-- AssertionError
      +-- AttributeError
      +-- BufferError
      +-- EOFError
      +-- ImportError
      |    +-- ModuleNotFoundError
      +-- LookupError
      |    +-- IndexError
      |    +-- KeyError
      +-- MemoryError
      +-- NameError
      |    +-- UnboundLocalError
      +-- TypeError
      +-- ValueError
      |    +-- UnicodeError
      |         +-- UnicodeDecodeError
      |         +-- UnicodeEncodeError
      |         +-- UnicodeTranslateError
      |
      +-- OSError
      |    +-- BlockingIOError
      |    +-- ChildProcessError
      |    +-- ConnectionError
      |    |    +-- BrokenPipeError
      |    |    +-- ConnectionAbortedError
      |    |    +-- ConnectionRefusedError
      |    |    +-- ConnectionResetError
      |    +-- FileExistsError
      |    +-- FileNotFoundError
      |    +-- InterruptedError
      |    +-- IsADirectoryError
      |    +-- NotADirectoryError
      |    +-- PermissionError
      |    +-- ProcessLookupError
      |    +-- TimeoutError
      +-- ReferenceError
      +-- RuntimeError
      |    +-- NotImplementedError
      |    +-- RecursionError
      +-- SyntaxError
      |    +-- IndentationError
      |         +-- TabError
      +-- SystemError
      +-- Warning
           +-- DeprecationWarning
           +-- PendingDeprecationWarning
           +-- RuntimeWarning
           +-- SyntaxWarning
           +-- UserWarning
           +-- FutureWarning
           +-- ImportWarning
           +-- UnicodeWarning
           +-- BytesWarning
           +-- ResourceWarning
```

docs.python.org/3/library/exceptions.html

Typical built-in exceptions

and unhandled behaviour

Python shell

```
> 7 / 0
| ZeroDivisionError: division by zero
> int('42x')
| ValueError: invalid literal for int() with base 10: '42x'
> x = y
| NameError: name 'y' is not defined
> L = [1] * 10_000_000_000
| MemoryError
> 2.5 ** 1000
| OverflowError: (34, 'Result too large')
> t = (3, 4)
> t[0] = 7
| TypeError: 'tuple' object does not support item assignment
> t[3]
| IndexError: tuple index out of range
> t.x
| AttributeError: 'tuple' object has no attribute 'x'
> x = {}
> x['foo']
| KeyError: 'foo'
> def f(x): f(x + 1)
> f(0)
| RecursionError: maximum recursion depth exceeded
> def f(): x = x + 1
> f()
| UnboundLocalError: local variable 'x' referenced before assignment
```

Catching exceptions – Fractions (I)

fraction1.py

```
while True:
    numerator = int(input('Numerator = '))
    denominator = int(input('Denominator = '))
    result = numerator / denominator
    print(f'{numerator} / {denominator} = {result}')
```

Python shell

```
| Numerator = 10
| Denominator = 3
| 10 / 3 = 3.3333333333333335
| Numerator = 20
| Denominator = 0
| ZeroDivisionError: division by zero
>
```

Catching exceptions – Fractions (II)

catch exception

fraction2.py

```
while True:
    numerator = int(input('Numerator = '))
    denominator = int(input('Denominator = '))
    try:
        result = numerator / denominator
    except ZeroDivisionError:
        print('cannot divide by zero')
        continue
    print(f'{numerator} / {denominator} = {result}')
```

Python shell

```
| Numerator = 10
| Denominator = 0
| cannot divide by zero
| Numerator = 20
| Denominator = 3
| 20 / 3 = 6.666666666666667
| Numerator = 42x
| ValueError: invalid literal for int() with base 10: '42x'
```

Catching exceptions – Fractions (III)

catch exception

catch exception

fraction3.py

```
while True:
    try:
        numerator = int(input('Numerator = '))
        denominator = int(input('Denominator = '))
    except ValueError:
        print('input not a valid integer')
        continue
    try:
        result = numerator / denominator
    except ZeroDivisionError:
        print('cannot divide by zero')
        continue
    print(f'{numerator} / {denominator} = {result}')
```

Python shell

```
| Numerator = 5
| Denominator = 2x
| input not a valid integer
| Numerator = 5
| Denominator = 2
| 5 / 2 = 2.5
```

fraction3.py

```
while True:
    try:
        numerator = int(input('Numerator = '))
        denominator = int(input('Denominator = '))
    except ValueError:
        print('input not a valid integer')
        continue
    try:
        result = numerator / denominator
        print(f'{numerator} / {denominator} = {result}')
    except ZeroDivisionError:
        print('cannot divide by zero')
```

Python shell

```
| Numerator = 1000000000000000000000000000000000000000000000000000000
  0000000000000000000000000000000000000000000000000000000000000000000
  0000000000000000000000000000000000000000000000000000000000000000000
  0000000000000000000000000000000000000000000000000000000000000000000
  0000000000000000000000000000000000000000000000000000000000000000000
  0000000000000000000000000000000000000000
| Denominator = 1
| OverflowError: integer division result too large for a float
```

exception not caught

Catching exceptions – Fractions (IV)

catch exceptions

fraction4.py

```
while True:
    try:
        numerator = int(input('Numerator = '))
        denominator = int(input('Denominator = '))
        result = numerator / denominator
        print(f'{numerator} / {denominator} = {result}')
    except ValueError:
        print('input not a valid integer')
    except ZeroDivisionError:
        print('cannot divide by zero')
```

Python shell

```
| Numerator = 3
| Denominator = 0
| cannot divide by zero
| Numerator = 3x
| input not a valid integer
| Numerator = 4
| Denominator = 2
| 4 / 2 = 2.0
```

Keyboard interrupt (*Ctrl-c*)

- throws **`KeyboardInterrupt`** exception

infinite-loop1.py

```
print('starting infinite loop')

x = 0
while True:
    x = x + 1

print(f'done ({x = })')
input('type enter to exit')
```

Python shell

```
| starting infinite loop
| Traceback (most recent call last):
|   File 'infinite-loop1.py', line 4, in <module>
|     x = x + 1
| KeyboardInterrupt
```

infinite-loop2.py

```
print('starting infinite loop')

try:
    x = 0
    while True:
        x = x + 1
except KeyboardInterrupt:
    pass

print(f'done ({x = })')
input('type enter to exit')
```

Python shell

```
| starting infinite loop
| done (x = 23890363)     Ctrl-c
| type enter to exit
```

Keyboard interrupt (*Ctrl-c*)

- Be aware that you likely would like to leave the *Ctrl-c* generated **`KeyboardInterrupt`** exception unhandled, except when stated explicitly

read-int1.py

```
while True:
    try:
        x = int(input('An integer: '))
        break
    except ValueError:  # only ValueError
        continue

print('The value is:', x)
```

Python shell

```
| An integer:                Ctrl-c
| KeyboardInterrupt
```

read-int2.py

```
while True:
    try:
        x = int(input('An integer: '))
        break
    except:  # all exceptions
        continue

print('The value is:', x)
```

catches KeyboardInterrupt

Python shell

```
| An integer:          Ctrl-c
| An integer:          Ctrl-c
| An integer:
```

- (left) `KeyboardInterrupt` is unhandled (right) it is handled (intentionally?)

Exception class hierarchy

except-twice1.py

```
try:
    L[4]
except IndexError:  # must be before Exception
    print('IndexError')
except Exception:
    print('Fall back exception handler')
```

except-twice2.py

```
try:
    L[4]
except Exception:  # and subclasses of Exception
    print('Fall back exception handler')
except IndexError:
    print('IndexError')  # unreachable
```

`try` statement syntax

arbitrary number of except cases

```
try:
    code
except ExceptionType1:
    code  # executed if raised exception instanceof
          # ExceptionType1 (or subclass of ExceptionType1)
except ExceptionType2:
    code  # executed if exception type matches and none of
          # the previous except statements matched
...
else:
    code  # only executed if no exception was raised
finally:
    code  # always executed independent of exceptions
          # typically used to clean up (like closing files)
```

`except` variations

```
except:                    # catch all exceptions

except ExceptionType:      # only catch exceptions of class ExceptionType
                           # or subclasses of ExceptionType

except (ExceptionType1, ExceptionType2, ..., ExceptionTypek):
                           # catch any of k classes (and subclasses)
                           # paranthesis cannot be omitted

except ExceptionType as e:
                           # catch exception and assign exception object to e
                           # e.args contains arguments to the raised exception
```

Raising exceptions

- An exception is raised (or trown) using one of the following (the first being an alias for the second):

```
raise ExceptionType
raise ExceptionType()
raise ExceptionType(args)
```

abstract.py

```
class A():
    def f(self):
        print('f')
        self.g()
    def g(self):
        raise NotImplementedError
class B(A):
    def g(self):
        print('g')
```

Python shell

```
> B().f()
| f
| g
> A().f()
| f
| NotImplementedError
```

User exceptions

- New exception types are created using class inheritance from an existing exception type (possibly defining __init__)

tree-search.py

```
class SolutionFound(Exception):  # new exception
    pass

def recursive_tree_search(x, tree):
    if isinstance(tree, tuple):
        for child in tree:
            recursive_tree_search(x, child)
    elif x == tree:
        raise SolutionFound  # found x in tree

def tree_search(x, tree):
    try:
        recursive_tree_search(x, tree)
    except SolutionFound:
        print('found', x)
    else:
        print('search for', x, 'unsuccessful')
```

Python shell

```
> tree_search(8, ((3,2),5,(7,(4,6))))
| search for 8 unsuccessful
> tree_search(7, ((3,2),5,(7,(4,6))))
| found 7
```

PEP8 on exceptions

- For all try/except clauses, limit the try clause to the absolute minimum amount of code necessary
- The class naming convention applies (CapWords)
- Use the suffix "Error" on your exception names (if the exception actually is an error)
- A bare `except:` clause will catch `SystemExit` and `KeyboardInterrupt` exceptions, making it harder to interrupt a program with Control-C, and can disguise other problems. If you want to catch all exceptions that signal program errors, use `except Exception:`

www.python.org/dev/peps/pep-0008/

3 ways to read lines from a file

Steps

1. Open file using `open`
2. Read lines from file using
   a) `for line in filehandler:`
   b) `filehandler.readlines`
   c) `filehandler.readline`
3. Close file using `close`

`open ('filename.txt')` assumes the file to be in the same folder as your Python program, but you can also provide a full path `open('c:/Users/gerth/Documents/filename.txt')`

try to open file for reading

filename

filehandle

iterate over lines in file

close file when done

reading-file1.py

```
f = open('reading-file1.py')
for line in f:
    print('> ', line, end='')
f.close()
```

read all lines into a list of strings

reading-file2.py

```
f = open('reading-file2.py')
lines = f.readlines()
f.close()
for line in lines:
    print('> ', line, end='')
```

read single line (terminated by '\n')

reading-file3.py

```
f = open('reading-file3.py')
line = f.readline()
while line != '':
    print('> ', line, end='')
    line = f.readline()
f.close()
```

3 ways to write lines to a file

try to open file for writing

write mode

write single string to file

write list of strings to file

append to existing file

write-file.py

```
f = open('output-file.txt', 'w')
f.write('Text 1\n')
f.writelines(['Text 2\n', 'Text 3 '])
f.close()

g = open('output-file.txt', 'a')
print('Text 4', file=g)
g.writelines(['Text 5 ', 'Text 6'])
g.close()
```

output-file.txt

```
Text 1
Text 2
Text 3 Text 4
Text 5 Text 6
```

- Opening file:
  `open(`*`filename, mode`*`)`
  where *`mode`* is a string, either `'w'` for opening a new (or truncating an existing file) and `'a'` for appending to an existing file
- Write single string:
  `filehandle``.write(`*`string`*`)`
  Returns the number of characters written
- Write list of strings strings:
  `filehandle``.writeline(`*`list`*`)`
- Newlines (`'\n'`) must be written explicitly
- `print` can take an optional `file` argument

Exceptions while dealing with files

- When dealing with files one should be prepared to handle errors / raised exceptions, e.g. `FileNotFoundError`

reading-file4.py

```
try:
    f = open('reading-file4.py')
except FileNotFoundError:
    print('Could not open file')
else:
    try:
        for line in f:
            print('> ', line, end='')
    finally:
        f.close()
```

Opening files using `with` (recommended way)

- The Python keyword `with` allows to create a *context manager* for handling files
- Filehandle will automatically be closed, also when exceptions occur
- Under the hood: filehandles returned by `open` support `__enter__` and `__exit__` methods

f = result of calling `__enter__()` on result of `open` expression, which is the file handle

reading-file5.py

```
with open('reading-file5.py') as f:
    for line in f:
        print('> ', line, end='')
```

docs.python.org/3/library/stdtypes.html#typecontextmanager

Does a file exist?

- Module `os.path` contains a method `isfile` to check if a file exists

checking-files.py

```
import os.path

filename = input('Filename: ')
if os.path.isfile(filename):
    print('file exists')
else:
    print('file does not exist')
```

docs.python.org/3/library/os.path.html

module sys

- Module `sys` contains the three standard file handles
  - `sys.stdin` (used by the `input` function)
  - `sys.stdout` (used by the `print` function)
  - `sys.stderr` (error output from the Python interpreter)

sys-test.py

```
import sys
sys.stdout.write('Input an integer: ')
x = int(sys.stdin.readline())
sys.stdout.write(f'{x} square is {x ** 2}')
```

Python shell

```
| Input an integer: 10
| 10 square is 100
```

docs.python.org/3/library/sys.html

print(..., file=*output file*)

sys-print-file.py

```
import sys

def complicated_function(file):
    print('Hello world', file=file)  # print to file or STDOUT

while True:
    file_name = input('Output file (empty for STDOUT): ')

    if file_name == '':
        file = sys.stdout
        break
    else:
        try:
            file = open(file_name, 'w')
            break
        except Exception:
            pass

complicated_function(file)

if file != sys.stdout:
    file.close()
```

Input performance

- Reading 10.000.000 short lines

`input()`	2.2 sec
`sys.stdin.readlines()`	0.65 sec
`sys.stdin.readline()`	0.65 sec
`readline()` alias	0.50 sec
`for line in sys.stdin:`	0.39 sec
`sys.stdin.read()`	0.18 sec
`sys.stdin.read().split('\n')`	0.53 sec

- Note: Time difference up to a factor 10

input_performance.py

```
from time import time
import sys
n = 10_000_000
data = 'numbers.txt'
def test_input():
    for i in range(n):
        line = input()
def test_stdin_readline():
    for i in range(n):
        line = sys.stdin.readline()
def test_stdin_readline():
    readline = sys.stdin.readline
    for i in range(n):
        line = readline()
def test_stdin_readlines():
    lines = sys.stdin.readlines()
def test_stdin_read():
    text = sys.stdin.read()
def test_for():
    for line in sys.stdin:
        pass
def create_test_input():
    with open(data, 'w') as file:
        for i in range(n):
            print(i, file=file)
create_test_input()
for _ in range(5):
    for name, value in list(vars().items()):
        if name.startswith('test_'):
            with open(data) as file:
                original_stdin = sys.stdin
                sys.stdin = file
                start = time()
                value()
                end = time()
                sys.stdin = original_stdin
            print(f'{name} {end - start:.2} sec')
```

Performance of scanning a file

- Python can efficiently scan through quite big files

File	Size	Time
Atom_chem_shift.csv	≈ 750 MB	≈ 8 sec
cano.txt	≈ 3.7 MB	≈ 0.1 sec

The first search finds all lines related to ThrB12-DKP-insulin (Entry ID 6203) in a chemical database available from www.bmrb.wisc.edu

The second search finds all occurrences of “Germany” in Conan Doyle's complete Sherlock Holmes available at sherlock-holm.es

file-scanning.py

```
from time import time

for filename, query in [
        ('Atom_chem_shift.csv', ',6203,'),
        ('cano.txt', 'Germany')
    ]:
    count = 0
    matches = []
    start = time()
    with open(filename) as f:
        for i, line in enumerate(f, start=1):
            count += 1
            if query in line:
                matches.append((i, line))
    end = time()

    for i, line in matches:
        print(i, ':', line, end='')
    print('Duration:', end - start)
    print(len(matches), 'of', count, 'lines match')
```

Python shell

```
...
3057752 : 195,,2,2,30,30,THR,HB,H,1,4.22,0.02,,1,,,,,,,,,,,,,,,,,,,,,,,,228896,6203,2
3057753 : 196,,2,2,30,30,THR,HG21,H,1,1.18,0.02,,1,,,,,,,,,,,,,,,,,,,,,,,,228896,6203,2
3057754 : 197,,2,2,30,30,THR,HG22,H,1,1.18,0.02,,1,,,,,,,,,,,,,,,,,,,,,,,,228896,6203,2
3057755 : 198,,2,2,30,30,THR,HG23,H,1,1.18,0.02,,1,,,,,,,,,,,,,,,,,,,,,,,,228896,6203,2
Duration: 7.760039329528809
329 of 9758361 lines match
57557 :      "Well, then, to the West, or to England, or to Germany, where father
66515 :      kind master. He wanted me to go with his wife to Germany yesterday,
66642 :      of business in Germany in the past and my name is probably familiar
73273 :      associates with Germany. This he placed in his instrument cupboard.
Duration: 0.07700657844543457
4 of 76764 lines match
```

sudoku.py

```python
class Sudoku:
  def __init__(self, puzzle):
    self.puzzle = puzzle

  def solve(self):
    def find_free():
      for i in range(9):
        for j in range(9):
          if self.puzzle[i][j] == 0:
            return (i, j)
      return None

    def unused(i, j):
      i_, j_ = i // 3 * 3, j // 3 * 3
      cells  = {(i, k) for k in range(9)}
      cells |= {(k, j) for k in range(9)}
      cells |= {(i, j) for i in range(i_, i_ + 3)
                       for j in range(j_, j_ + 3)}
      return set(range(1, 10)) - {self.puzzle[i][j] for i, j in cells}

    class SolutionFound(Exception):
      pass

    def recursive_solve():
      cell = find_free()
      if not cell:
        raise SolutionFound
      i, j = cell
      for value in unused(i, j):
        self.puzzle[i][j] = value
        recursive_solve()
      self.puzzle[i][j] = 0

    try:
      recursive_solve()
    except SolutionFound:
      pass
```

sudoku.py (*continued*)

```python
  def print(self):
    for i, row in enumerate(self.puzzle):
      cells = [f' {c} ' if c else ' . ' for c in row]
      print('|'.join([''.join(cells[j:j+3]) for j in (0,3,6)]))
      if i in (2, 5):
        print('---------+---------+---------')

with open('sudoku.txt') as f:
    A = Sudoku([[int(x) for x in line.strip()] for line in f])

A.solve()
A.print()
```

sudoku.txt

```
517600034
289004000
346205090
602000010
038006047
000000000
090000078
703400560
000000000
```

Python shell

```
|   5  1  7 | 6  9  8 | 2  3  4
|   2  8  9 | 1  3  4 | 7  5  6
|   3  4  6 | 2  7  5 | 8  9  1
|  ---------+---------+---------
|   6  7  2 | 8  4  9 | 3  1  5
|   1  3  8 | 5  2  6 | 9  4  7
|   9  5  4 | 7  1  3 | 6  8  2
|  ---------+---------+---------
|   4  9  5 | 3  6  2 | 1  7  8
|   7  2  3 | 4  8  1 | 5  6  9
|   8  6  1 | 9  5  7 | 4  2  3
```

`match – case` (since Python 3.10)

- Assume we want to do different things depending on the value of an expression (different *cases*)
- Can be done using `if`, but also using `match – case`, that is also evaluated top-down

match-case.py

```
x = 7

if x == 1:
    print('x is one')
elif x == 2:
    print('x is two')
elif x == 3 or x == 4 or x == 5:
    print('x is three, four or five')
else:
    print(x, 'is not in the range 1-5')
```

Python shell

```
| 7 is not in the range 1-5
```

match-case.py

```
x = 7

match x:  # match expression
    case 1:
        print('x is one')
    case 2:
        print('x is two')
    case 3 | 4 | 5:  # match any of the cases
        print('x is three, four or five')
    case value:  # else, value = variable name
        print(value, 'is not in the range 1-5')
```

Python shell

```
| 7 is not in the range 1-5
```

match – case

Can match…

- simple values
- named variable values
- guards (`if`)
- sequences of values
- dictionaries
- builtin types
- user defined classes
- nested structures of the above

match-case.py

```
class Color:
    RED   = 'ff0000'
    GREEN = '00ff00'
    BLUE  = '0000ff'

class Point:
    __match_args__ = ('x', 'y')

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def __repr__(self):
        return f'Point({self.x}, {self.y})'
```

match-case.py

```
def f(x):
  match x:
    case 42:
        return 'the integer 42'
    case 1 | 2 | 3 | 4 | 5:
        return 'integer in range(1, 6)'
    case (1, 2):
        return 'sequence containing the elements 1 and 2'
    case [x, 2]:
        return 'sequence of length 2, last=2, first=' + str(x)
    case (x, y) if x + y == 7:  # guard
        return 'sequence with two values with sum 7'
    case [0, 1, *x]:  # x is list of remaining elements in sequence
        return 'sequence starting with 0 and 1, and tail ' + str(x)
    case {'a': 7, 'b': x}:  # a dictionary containing at least two keys
        return 'dictionary "a" -> 7, "b" -> ' + str(x)
    case (('a' | 'b'), ('c' | 'd')):
        return 'tuple length 2, first "a" or "b", last "c" or "d"'
    case (('x' | 'y') as fst, ('x' | 'y') as snd):
        return '(fst, snd), where fst=' + str(fst) + ', snd=' + str(snd)
    case float(value):  # test on builtin type
        return 'a float ' + str(value)
    case Color.RED:  # class or object attribute
        return 'the color red'
    case Point(x=7, y=value):  # Point object with attributes x and y
        return 'a Point object with x=7, and y=' + str(value)
    case Point(x, y):  # requires __match_args__ in class Point
        return 'a point Point(' + str(x) + ', ' + str(y) + ')'
    case e:  # ⚠ using the wildcard _ would not bind to a variable
        return 'cannot match ' + repr(e)
```

Python shell (match-case.py *continued*)

```
> for x in [42, 1, [1, 2], [7, 2], range(3, 5), (3, (5, 7)), (0, 1, 2, 3, 4, 5), {'a':7, 'b':42, 'c':1},
            ('b', 'c'), ('y', 'x'), 3.14, 'ff0000', Point(7, 42), Point(3, 5), 'abc']:
      print('f(' + repr(x) + ') = ' + repr(f(x)))
| f(42) = 'the integer 42'
| f(1) = 'integer in range(1, 6)'
| f([1, 2]) = 'sequence containing the elements 1 and 2'
| f([7, 2]) = 'sequence of length 2, last=2, first=7'
| f(range(3, 5)) = 'sequence with two values with sum 7'
| f((3, (5, 7))) = 'a triplet (3, (5, 7))'
| f((0, 1, 2, 3, 4, 5)) = 'sequence starting with 0 and 1, and tail [2, 3, 4, 5]'
| f({'a': 7, 'b': 42, 'c': 1}) = 'dictionary "a" -> 7, "b" -> 42'
| f(('b', 'c')) = 'tuple length 2, first "a" or "b", last "c" or "d"'
| f(('y', 'x')) = '(fst, snd), where fst=y, snd=x'
| f(3.14) = 'a float 3.14'
| f('ff0000') = 'the color red'
| f(Point(7, 42)) = 'a Point object with x=7, and y=42'
| f(Point(3, 5)) = 'a point Point(3, 5)'
| f('abc') = "cannot match 'abc'"
```

Documentation, testing and debugging

- docstring
- defensive programming
- assert
- test driven developement
- assertions
- testing
- unittest
- debugger
- coverage
- static type checking (mypy, pyright)

- On average, a developer creates 70 bugs per 1000 lines of code
- 15 bugs per 1,000 lines of code find their way to the customers
- Fixing a bug takes 30 times longer than writing a line of code
- 75% of a developer’s time is spent on debugging

Ensuring good quality code ?

Goal

- Develop programs that work correctly
- Tools and techniques

What is good code ?

- Readability
  - well-structured
  - documentation
  - comments
  - follow some standard structure (easy to recognize, follow PEP8 Style Guide)
- Correctness
  - outputs the correct answer on valid input
  - eventually stops with an answer on valid input (should not go in infinite loop)
- Reusable...

Why ?

Documentation

- *specification of functionality*
- docstring
  - *for users of the code*
  - modules
  - methods
  - classes
- comments
  - *for readers of the code*

Testing

- Correct implementation ?
- Try to predict behavior on unknown input ?
- Performance guarantees ?

Debugging

- *Where is the #!¤$ bug ?*

”Program testing can be used to show the presence of bugs, but never to show their absence” – Edsger W. Dijkstra

Built-in exceptions (class hierarchy)

```
BaseException
 +-- SystemExit
 +-- KeyboardInterrupt
 +-- GeneratorExit
 +-- Exception
      +-- StopIteration
      +-- StopAsyncIteration
      +-- ArithmeticError
      |    +-- FloatingPointError
      |    +-- OverflowError
      |    +-- ZeroDivisionError
      +-- AssertionError
      +-- AttributeError
      +-- BufferError
      +-- EOFError
      +-- ImportError
      |    +-- ModuleNotFoundError
      +-- LookupError
      |    +-- IndexError
      |    +-- KeyError
      +-- MemoryError
      +-- NameError
      |    +-- UnboundLocalError
      +-- TypeError
      +-- ValueError
      |    +-- UnicodeError
      |         +-- UnicodeDecodeError
      |         +-- UnicodeEncodeError
      |         +-- UnicodeTranslateError
      |
      +-- OSError
      |    +-- BlockingIOError
      |    +-- ChildProcessError
      |    +-- ConnectionError
      |    |    +-- BrokenPipeError
      |    |    +-- ConnectionAbortedError
      |    |    +-- ConnectionRefusedError
      |    |    +-- ConnectionResetError
      |    +-- FileExistsError
      |    +-- FileNotFoundError
      |    +-- InterruptedError
      |    +-- IsADirectoryError
      |    +-- NotADirectoryError
      |    +-- PermissionError
      |    +-- ProcessLookupError
      |    +-- TimeoutError
      +-- ReferenceError
      +-- RuntimeError
      |    +-- NotImplementedError
      |    +-- RecursionError
      +-- SyntaxError
      |    +-- IndentationError
      |         +-- TabError
      +-- SystemError
      +-- Warning
           +-- DeprecationWarning
           +-- PendingDeprecationWarning
           +-- RuntimeWarning
           +-- SyntaxWarning
           +-- UserWarning
           +-- FutureWarning
           +-- ImportWarning
           +-- UnicodeWarning
           +-- BytesWarning
           +-- ResourceWarning
```

docs.python.org/3/library/exceptions.html

Testing for unexpected behaviour ?

infinite-recursion1.py

```
def f(depth):
    f(depth + 1)   # infinite recursion

f(0)
```

Python shell

```
| RecursionError: maximum recursion depth exceeded
```

infinite-recursion2.py

```
def f(depth):
    if depth > 100:
        print('runaway recursion???')
        raise SystemExit   # raise built-in exception
    f(depth + 1)

f(0)
```

Python shell

```
| runaway recursion???
```

infinite-recursion3.py

```
import sys

def f(depth):
    if depth > 100:
        print('runaway recursion???')
        sys.exit()   # system function
    f(depth + 1)

f(0)
```

raises SystemExit

Python shell

```
| runaway recursion???
```

- let the program eventually fail
- check and raise exceptions
- check and call `sys.exit`

Catching unexpected behaviour – `assert`

infinite-recursion4.py

```
def f(depth):
    assert depth <= 100   # raise exception if False
    f(depth + 1)

f(0)
```

Python shell

```
| File "...\infinite-recursion4.py", line 2, in f
|     assert depth <= 100
| AssertionError
```

infinite-recursion5.py

```
def f(depth):
    assert depth <= 100, 'runaway recursion???'
    f(depth + 1)

f(0)
```

Python shell

```
| File "...\infinite-recursion5.py", line 2, in f
|     assert depth <= 100, "runaway recursion???"
| AssertionError: runaway recursion???
```

- keyword `assert` checks if boolean expression is true, if not, raises exception AssertionError
- optional second parameter passed to the constructor of the exception
- try to fail fast to discover errors early – making debugging easier

infinite-recursion6.py

```
def f(depth):
    if not depth <= 100:
        raise AssertionError('runaway recursion???')
    f(depth + 1)

f(0)
```

Python shell

```
| File "...\infinite-recursion6.py", line 3, in f
|     raise AssertionError("runaway recursion???")
| AssertionError: runaway recursion???
```

Disabling `assert` statements

Command Prompt

```
C:\Users\au121\Desktop>python -O infinite-recursion5.py
Traceback (most recent call last):
  File "infinite-recursion5.py", line 5, in <module>
    f(0)
  File "infinite-recursion5.py", line 3, in f
    f(depth + 1)
  File "infinite-recursion5.py", line 3, in f
    f(depth + 1)
  File "infinite-recursion5.py", line 3, in f
    f(depth + 1)
  [Previous line repeated 995 more times]
RecursionError: maximum recursion depth exceeded

C:\Users\au121\Desktop>
```

- **`assert`** statements are good to help check correctness of program – but can slow down program
- invoking Python with option `-O` disables all assertions (by setting `__debug__` to `False`)

docs.python.org/3/reference/simple_stmts.html#assert

Example

$$\left\lfloor \sqrt{x} \right\rfloor$$

First try... (seriously, the bugs were not on purpose)

intsqrt_buggy.py

```
def int_sqrt(x):
    low = 0
    high = x
    while low < high - 1:
        mid = (low + high) / 2
        if mid ** 2 <= x:
            low = mid
        else:
            high = mid
    return low
```

Python shell

```
> int_sqrt(10)
| 3.125  # 3.125 ** 2 = 9.765625
> int_sqrt(-10)
| 0  # what should the answer be ?
```

Let us add a specification...

intsqrt.py

```
def int_sqrt(x):
    '''Compute the integer square root of an integer x.

    Requires x >= 0 is an integer.
    Returns the integer floor(sqrt(x)).'''

    ...
```

docstring

input requirements

output guarantees

Python shell

```
> help(int_sqrt)
| Help on function int_sqrt in module __main__:
|
| int_sqrt(x)
|     Compute the integer square root of an integer x.
|
|     Requires x >= 0 is an integer.
|     Returns the integer floor(sqrt(x)).
```

- all methods, classes, and modules can have a **`docstring`** (ideally have) as a **specification**
- for methods: summarize purpose in first line, followed by input requirements and ouput guarantees
- the docstring is assigned to the object's `__doc__` attribute

PEP 257 -- Docstring Conventions
www.python.org/dev/peps/pep-0257/

Let us check input requirements...

intsqrt.py

```
def int_sqrt(x):
    '''Compute the integer square root of an integer x.

    Requires x >= 0 is an integer.
    Returns the integer floor(sqrt(x)).'''

    assert isinstance(x, int)
    assert 0 <= x
    ...
```

check input requirements

Python shell

```
> int_sqrt(-10)
|  File "...\int_sqrt.py", line 7, in int_sqrt
|     assert 0 <= x
| AssertionError
```

- doing explicit checks for valid input arguments is part of **defensive programming** and helps spotting errors early

  (instead of continuing using likely wrong values... resulting in a final meaningless error)

Let us check if output correct…

intsqrt.py

```
def int_sqrt(x):
    '''Compute the integer square root of an integer x.

    Requires x >= 0 is an integer.
    Returns the integer floor(sqrt(x)).'''

    assert isinstance(x, int)
    assert 0 <= x
    ...
    assert isinstance(result, int)
    assert result ** 2 <= x < (result + 1) ** 2
    return result
```

check output

Python shell

```
> int_sqrt(10)
|   File "...\int_sqrt.py", line 20, in int_sqrt
|     assert isinstance(result, int)
| AssertionError
```

- output check identifies the error

  `mid = (low + high) / 2`

- should have been

  `mid = (low + high) // 2`

- The output check helps us to ensure that function specifications are satisfied in applications

Let us test some input values…

intsqrt.py

```
def int_sqrt(x):
    ...

assert int_sqrt(0) == 0
assert int_sqrt(1) == 1
assert int_sqrt(2) == 1
assert int_sqrt(3) == 1
assert int_sqrt(4) == 2
assert int_sqrt(5) == 2
assert int_sqrt(200) == 14
```

Python shell

```
| Traceback (most recent call last):
|   File "...\int_sqrt.py", line 28, in <module>
|     assert int_sqrt(1) == 1
|   File "...\int_sqrt.py", line 21, in int_sqrt
|     assert result ** 2 <= x < (result + 1) ** 2
| AssertionError
```

- test identifies wrong output for x = 1

Let us check progress of algorithm...

intsqrt.py

```
...
low, high = 0, x
while low < high - 1:   # low <= floor(sqrt(x)) < high
    assert low ** 2 <= x < high ** 2
    mid = (low + high) // 2
    if mid ** 2 <= x:
        low = mid
    else:
        high = mid
result = low
...
```

check invariant for loop

$\lfloor\sqrt{x}\rfloor \in [\mathtt{low}, \mathtt{high}[$

Python shell

```
Traceback (most recent call last):
  File "...\int_sqrt.py", line 28, in <module>
    assert int_sqrt(1) == 1
  File "...\int_sqrt.py", line 21, in int_sqrt
    assert result ** 2 <= x < (result + 1) ** 2
AssertionError
```

- test identifies wrong output for x = 1
- but invariant apparently correct ???
- problem

  `low == result == 0`
  `high == 1`

  implies loop never entered
- output check identifies the error

  `high = x`
- should have been

  `high = x + 1`

Final program

We have used assertions to:

- Test if input arguments / usage is valid (defensive programming)
- Test if computed result is correct
- Test if an internal invariant in the computation is satisfied
- Perform a final test for a set of test cases (should be run whenever we change anything in the implementation)

intsqrt.py

```
def int_sqrt(x):
    '''Compute the integer square root of an integer x.

    Requires x >= 0 is an integer.
    Returns the integer floor(sqrt(x)).'''

    assert isinstance(x, int)
    assert 0 <= x

    low, high = 0, x + 1
    while low < high - 1:  # low <= floor(sqrt(x)) < high
        assert low ** 2 <= x < high ** 2
        mid = (low + high) // 2
        if mid ** 2 <= x:
            low = mid
        else:
            high = mid
    result = low

    assert isinstance(result, int)
    assert result ** 2 <= x < (result + 1) ** 2

    return result

assert int_sqrt(0) == 0
assert int_sqrt(1) == 1
assert int_sqrt(2) == 1
assert int_sqrt(3) == 1
assert int_sqrt(4) == 2
assert int_sqrt(5) == 2
assert int_sqrt(200) == 14
```

Which checks would you add to the below code?

binary-search.py

```
def binary_search(x, L):
    '''Binary search for x in sorted list L.

    Assumes x is an integer, and L a non-decreasing list of integers.

    Returns index i, -1 <= i < len(L), where L[i] <= x < L[i+1],
    assuming L[-1] = -infty and L[len(L)] = +infty.'''

    low, high = -1, len(L)
    while low + 1 < high:
        mid = (low + high) // 2
        if x < L[mid]:
            high = mid
        else:
            low = mid
    result = low

    return result
```

binary-search-assertions.py

```python
def binary_search(x, L):
    '''Binary search for x in sorted list L.

    Assumes x is an integer, and L a non-decreasing list of integers.

    Returns index i, -1 <= i < len(L), where L[i] <= x < L[i+1],
    assuming L[-1] = -infty and L[len(L)] = +infty.'''

    assert isinstance(x, int)
    assert isinstance(L, list)
    assert all([isinstance(e, int) for e in L])
    assert all([L[i] <= L[i + 1] for i in range(len(L) - 1)])

    low, high = -1, len(L)
    while low + 1 < high:  # L[low] <= x < L[high]
        assert (low == -1 or L[low] <= x) and (high == len(L) or x < L[high])
        mid = (low + high) // 2
        assert isinstance(L[mid], int)
        assert (low == -1 or L[low] <= L[mid]) and (high == len(L) or L[mid] <= L[high])
        if x < L[mid]:
            high = mid
        else:
            low = mid
    result = low

    assert (isinstance(result, int) and -1 <= result < len(L) and
            ((result == -1 and (len(L) == 0 or x < L[0])) or
             (result == len(L) - 1 and x >= L[-1]) or
             (0 <= result < len(L) - 1 and L[result] <= x < L[result + 1])))
    return result

assert binary_search(42, []) == -1
assert binary_search(42, [7]) == 0
assert binary_search(7, [42]) == -1
assert binary_search(7, [42, 42, 42]) == -1
assert binary_search(42, [7, 7, 7]) == 2
assert binary_search(42, [7, 7, 7, 56, 81]) == 2
assert binary_search(8, [1, 3, 5, 7, 9]) == 3
```

input

input loop

output

① inefficient

②

test cases

① Verifying if L is a sorted list of integers can slow down the program significantly

② Alternative is to only verify if the part of L visited is a sorted subsequence

Test driven development / Stress tests / Random testing

- Test driven development
  Write the tests before functionality – only write code needed by tests
- The challenge – what tests to do?
  Can you manually find all relevant cases? In particular all edge cases?
- Automate the testing?
  - Write method that can verify the output (possibly slower than the method)
  - Systematically try *all* possible inputs (if range is small)
  - Try a large random subset of inputs (if many possible inputs)

intsqrt_automatic_testing.py

```
import random

def int_sqrt(x):
    return 42  # Dummy code - write test code first

def test_int_sqrt(x):
    print('.', end='', flush=True)  # Show progress
    assert x >= 0  # Verify input
    answer = int_sqrt(x)
    # Verify output
    assert answer ** 2 <= x < (answer + 1) ** 2

# Test small inputs
for x in range(0, 100):
    test_int_sqrt(x)

# Test increasing sized inputs
for d in range(3, 30):
    for _ in range(100):  # Repeat for each size
        test_int_sqrt(random.randint(1, 10 ** d))
```

Testing – how ?

- Run set of test cases
  - test all cases in input/output specification **(black box testing)**
  - test all special cases **(black box testing)**
  - set of tests should force all lines of code to be tested **(glass box testing)**
- Visual test
- Automatic testing
  - Systematically / randomly generate input instances
  - Create function to **validate** if output is correct
    (hopefully easier than finding the solution)
- Formal verification
  - Use computer programs to do formal proofs of correctness, like using Coq

Visual testing – Convex hull computation

Correct

Bug !
(not convex)

doctest

- Python module
- Test instances (pairs of input and corresponding output) are written in the doc strings, formatted as in an interactive Python session

binary-search-doctest.py

```
def binary_search(x, L):
    '''Binary search for x in sorted list L.

    Examples:
    >>> binary_search(42, [])
    -1
    >>> binary_search(42, [7])
    0
    >>> binary_search(42, [7,7,7,56,81])
    2
    >>> binary_search(8, [1,3,5,7,9])
    3
    '''

    low, high = -1, len(L)
    while low + 1 < high:
        mid = (low + high) // 2
        if x < L[mid]:
            high = mid
        else:
            low = mid
    return low

import doctest
doctest.testmod(verbose=True)
```

Python shell

```
Trying:
    binary_search(42, [])
Expecting:
    -1
ok
Trying:
    binary_search(42, [7])
Expecting:
    0
ok
Trying:
    binary_search(42, [7,7,7,56,81])
Expecting:
    2
ok
Trying:
    binary_search(8, [1,3,5,7,9])
Expecting:
    3
ok
1 items had no tests:
    __main__
1 items passed all tests:
   4 tests in __main__.binary_search
4 tests in 2 items.
4 passed and 0 failed.
Test passed.
```

docs.python.org/3/library/doctest.html

pytest

- Run all tests stored in functions prefixed by `test_` or `test_` prefixed test methods inside `Test` prefixed test classes
- `pip install pytest`
- Run the `pytest` program from a shell

pytest.org

binary-search-pytest.py

```python
import pytest

def binary_search(x, L):
    '''Binary search for x in sorted list L.'''

    low, high = -1, len(L)
    while low + 1 < high:
        mid = (low + high) // 2
        if x < L[mid]:
            high = mid
        else:
            low = mid
    return low

def test_binary_search():
    assert binary_search(42, []) == -1
    assert binary_search(42, [7]) == 0
    assert binary_search(42, [7,7,7,56,81]) == 2
    assert binary_search(8, [1,3,5,7,9]) == 3

def test_types():
    with pytest.raises(TypeError):
        _ = binary_search(5, ['a', 'b', 'c'])
```

Shell

```
> pytest binary-search-pytest.py
| ============= test session starts =============
| platform win32 -- Python 3.11.2, pytest-7.2.1, pluggy-1.0.0
| plugins: anyio-3.6.2
| collected 2 items
| binary-search-pytest.py .. [100%]
| ============== 2 passed in 0.05s ==============
```

unittest

- Python module
- A comprehensive object-oriented test framework, inspired by the corresponding JUnit test framework for Java

binary-search-unittest.py

```
def binary_search(x, L):
    '''Binary search for x in sorted list L.'''

    low, high = -1, len(L)
    while low + 1 < high:
        mid = (low + high) // 2
        if x < L[mid]:
            high = mid
        else:
            low = mid
    return low

import unittest

class TestBinarySearch(unittest.TestCase):
    def test_search(self):
        self.assertEqual(binary_search(42, []), -1)
        self.assertEqual(binary_search(42, [7]), 0)
        self.assertEqual(binary_search(42, [7,7,7,56,81]), 2)
        self.assertEqual(binary_search(8, [1,3,5,7,9]), 3)

    def test_types(self):
        self.assertRaises(TypeError, binary_search, 5, ['a', 'b', 'c'])

unittest.main(verbosity=2)
```

Python shell

```
| test_search (__main__.TestBinarySearch) ... ok
| test_types (__main__.TestBinarySearch) ... ok
| ----------------------------------------------------------------------
| Ran 2 tests in 0.051s
| OK
```

docs.python.org/3/library/unittest.html

Debugger (IDLE)

- When an exception has stopped the program, you can examine the state of the variables using **Debug > Stack Viewer** in the Python shell

Stepping through a program (IDLE debugger)

- **Debug > Debugger** in the Python shell opens Debug Control window
- **Right click** on a code line in editor to set a “breakpoint” in your code
- **Debug Control:** Go → run until next breakpoint is encountered; Step → execute one line of code; Over → run function call without details; Out → finish current function call; Quit → Stop program;

Coverage

- Ensure that your tests cover the whole code and all possible branches are taken
- The module `coverage` can monitor running your code and report which lines and branches were not executed
- `pip install coverage`
- **Note** 100% coverage does not guarantee that there are no errors… just fewer

goldbach.py

```
1  def odd(x):
2    return x % 2 == 1
3  def sum_of_three_primes(n):
4    assert odd(n) and n > 5
5    primes = (set(range(2, n + 1)) -
6              set(x for f in range(2, n + 1)
7                    for x in range(2 * f, n + 1, f)))
8    for x in primes:
9      for y in primes:
10       for z in primes:
11         if n == x + y + z:
12           print(n, 'is the sum of three primes', x, y, z)
13           return
14   print(n, 'is not the sum of three primes')
15 for n in range(7, 1000, 2):
16   sum_of_three_primes(n)
```

Shell

```
> coverage run --branch goldbach.py
| 7 is the sum of three primes 2 2 3
| 9 is the sum of three primes 2 2 5
| ...
| 999 is the sum of three primes 3 5 991
> coverage report -m goldbach.py
| Name          Stmts   Miss Branch BrPart  Cover   Missing
| ---------------------------------------------------------
| goldbach.py      14      1     12      1    92%   14
| ---------------------------------------------------------
| TOTAL            14      1     12      1    92%
```

pypi.org/project/coverage

en.wikipedia.org/wiki/Goldbach's_weak_conjecture

coverage html

Coverage for **goldbach.py**: 92%

14 statements | 13 run | 1 missing | 0 excluded | 1 partial

« prev ^ index » next coverage.py v6.5.0, created at 2022-10-05 17:23 +0200

```
1  def odd(x):
2      return x % 2 == 1
3  def sum_of_three_primes(n):
4      assert odd(n) and n > 5
5      primes = (set(range(2, n + 1)) -
6                set(x for f in range(2, n + 1)
7                      for x in range(2 * f, n + 1, f)))
8      for x in primes:                                    8 ↛ 14
9          for y in primes:
10             for z in primes:
11                 if n == x + y + z:
12                     print(n, 'is the sum of three primes', x, y, z)
13                     return
14     print(n, 'is not the sum of three primes')
15 for n in range(7, 1001, 2):
16     sum_of_three_primes(n)
```

line 8 didn't jump to line 14, because the loop on line 8 didn't complete

Concluding remarks

- Simple debugging: add print statements
- **Test driven development** → Strategy for code development, where tests are written before the code
- **Defensive programming** → add tests (assertions) to check if input/arguments are valid according to specification
- When designing tests, ensure **coverage**
  (the set of test cases should make sure all code lines get executed)
- **Python testing frameworks: doctest, unittest, pytest, ...**

Mypy – a static type checker for Python

Experimental ⚠

- **Static type checking** tries to analyze a program for potential type errors without executing the program
- Installing:

  `pip install mypy`

- Running Python will cause an error during execution, whereas using mypy the error will be found without executing the program
- Standard (and required) in statically typed languages like Java, C, C++

mypy-simple.py

```
print('start')
print(42 + 'abc')  # error
print('end')
```

Shell

```
> python mypy-simple.py
| start
| TypeError: unsupported operand type(s)
  for +: 'int' and 'str'
> mypy mypy-simple.py
| mypy-simple.py:2: error: Unsupported
  operand types for + ("int" and "str")
  [operator]
```

mypy-lang.org
PEP 484 - Type Hints

mypy does not spot all errors…

mypy-add.py

```
def add(x, y):
    return x + y  # bug: x int and y string
print(add(42, 'abc'))
```

Shell

```
> python add.py
| TypeError: unsupported operand type(s) for +: 'int' and 'str'
> mypy add.py
| Success: no issues found in 1 source file
```

Type hints (PEP 484)

- Python allows type hints in programs
- Type hints are ignored at run-time by Python, but useful for static type analysis (e.g. mypy)
- Syntax

  variable : *type*

  variable : *type* = value

mypy-basic-types.py

```
x : int  # type hint
x = 42
x = 'abc'  # type error
y : int = 42  # type hint
y = 'abc'  # type error
z = 42
z = 'abc'  # type changed from int to str
print(x, y, z)
```

Shell

```
> python mypy-basic-types.py
| abc abc abc
> mypy mypy-basic-types.py
| mypy-basic-types.py:3: error: Incompatible
  types in assignment (expression has type
  "str", variable has type "int")
| mypy-basic-types.py:5: error: ...
| mypy-basic-types.py:7: error: ...
```

Type hints – functions

```
def name(variable : type, ...) -> return type:
```

mypy-function.py

```python
def f(x: int, units: str) -> str:
    return str(x) + ' ' + units

def g(x, units: str) -> str:
    return str(x) + ' ' + units

print(f(3, 'cm'))
print(f('one', 'meter'))

print(g(3, 'cm'))
print(g('one', 'meter'))

print(f.__annotations__)
```

Shell

```
> python mypy-function.py
| 3 cm
| one meter
| 3 cm
| one meter
| {'x': <class 'int'>, 'units': <class 'str'>,
  'return': <class 'str'>}
> mypy mypy-function.py
| mypy-function.py:8: error: Argument 1 to "f"
  has incompatible type "str"; expected "int"
```

- For functions and methods `function.__annotations__` is a dictionary with the annotation
- The types become part of the documentation

More type hints in Python 3.9
...see PEP 484 for even more...

mypy-typing.py

```
from typing import Mapping, Set, List, Tuple, Union, Optional

S : Set = {}                                    # error {} dictionary
S2 : Set[int] = {1, 2, 'abc'}                   # error 'abc' is not int
D : Mapping[int, int] = {1: 42, 'a': 1}         # error 'a' is not int
T : Tuple[int, str] = (42, 7)                   # error 7 is not str
L : List[Union[int, str]] = [42, 'a', None]     # error list can only contain int and str
L2 : List[Optional[str]] = ['abc', None, 42]    # error list can only contain str og None
```

Shell

```
> mypy mypy-typing.py
| mypy-typing.py:3: error: Incompatible types in assignment (expression has type "Dict[<nothing>,
  <nothing>]", variable has type "Set[Any]")
| mypy-typing.py:4: error: Argument 3 to <set> has incompatible type "str"; expected "int"
| mypy-typing.py:5: error: Dict entry 1 has incompatible type "str": "int"; expected "int": "int"
| mypy-typing.py:6: error: Incompatible types in assignment (expression has type "Tuple[int, int]",
  variable has type "Tuple[int, str]")
| mypy-typing.py:7: error: List item 2 has incompatible type "None"; expected "Union[int, str]"
| mypy-typing.py:8: error: List item 2 has incompatible type "int"; expected "Optional[str]"
```

PEP 484 - Type Hints

… the same in Python 3.10

mypy-typing-new.py

```
# deprecated: from typing import Mapping, Set, List, Tuple, Union, Optional

S : set = {}                                    # error {} dictionary
S2 : set[int] = {1, 2, 'abc'}                   # error 'abc' is not int
D : dict[int, int] = {1: 42, 'a': 1}            # error 'a' is not int
T : tuple[int, str] = (42, 7)                   # error 7 is not str
L : list[int | str] = [42, 'a', None]           # error list can only contain int and str
L2 : list[str | None] = ['abc', None, 42]       # error list can only contain str og None
```

Shell

```
> mypy mypy-typing-new.py
| mypy-typing-new.py:3: error: Incompatible types in assignment (expression has type "Dict[<nothing>,
  <nothing>]", variable has type "Set[Any]")
| mypy-typing-new.py:4: error: Argument 3 to <set> has incompatible type "str"; expected "int"
| mypy-typing-new.py:5: error: Dict entry 1 has incompatible type "str": "int"; expected "int": "int"
| mypy-typing-new.py:6: error: Incompatible types in assignment (expression has type "Tuple[int, int]",
  variable has type "Tuple[int, str]")
| mypy-typing-new.py:7: error: List item 2 has incompatible type "None"; expected "Union[int, str]"
| mypy-typing-new.py:8: error: List item 2 has incompatible type "int"; expected "Optional[str]"
```

PEP 585 - Type Hinting Generics In Standard Collections (Python 3.9)
PEP 604 – Allow writing union types as X | Y (Python 3.10)

Specific values

mypy-literal.py

```python
from typing import Literal

def calc(cmd: Literal['add', 'sub'], x: int, y: int) -> int:
    match cmd:
        case 'add': return x + y
        case 'sub': return x - y
        case _: raise ValueError(f"Unknown command '{cmd}'")

print(f"{calc('add', 5, 8) = }")
print(f"{calc('sub', 5, 8) = }")
print(f"{calc('mul', 5, 8) = }")  # error
```

Shell

```
> python.exe mypy-literal.py
| calc('add', 5, 8) = 13
| calc('sub', 5, 8) = -3
| ValueError: Unknown command 'mul'
>  mypy.exe .\mypy-literal.py
| mypy-literal.py:11: error: Argument 1 to "calc" has incompatible type "Literal['mul']";
  expected "Literal['add', 'sub']"  [arg-type]
| Found 1 error in 1 file (checked 1 source file)
```

PEP 586 - Literal Types (since Python 3.8)

Type hints for methods with multiple signatures

printing1.py

```
class MyClass:
    def print(self, value: int | str) -> None:
        if isinstance(value, int):
            print('An integer', value)
        elif isinstance(value, str):
            print('A string', value)
```

printing2.py

```
from typing import overload

class MyClass:
    # type definition of usages
    @overload
    def print(self, value: int) -> None: ...

    @overload
    def print(self, value: str) -> None: ...

    # actual implementation
    def print(self, value):
        if isinstance(value, int):
            print('An integer', value)
        elif isinstance(value, str):
            print('A string', value)
```

- The right solution is useful for functions/methods with more complex overloaded type signatures
- `...` is the Python Ellipsis object
- `@overload` is a Python *decorator*

docs.python.org/3/library/typing.html

Type hints for class inheritance

abstract.py

```
from typing import override, final

class A():
    @final  # prevent subclasses to override f (since Python 3.8)
    def f(self):
        print('f')
        self.g()

    def g(self):
        raise NotImplementedError

class B(A):
    @override  # check if parent class contains g (since Python 3.12)
    def g(self):
        print('g')
```

- Use pyright (`pip install pyright`) to check the above, a static type checking tool from Microsoft
- mypy does not check it (mypy 1.8.0)

Decorators

- @

www.python.org/dev/peps/pep-0318/

Course overview

Basic programming
Advanced / specific python
Libraries & applications

1. Introduction to Python	10. Functions as objects	19. Linear programming
2. Python basics / if	11. Object oriented programming	20. Generators, iterators, with
3. Basic operations	12. Class hierarchies	21. Modules and packages
4. Lists / while / for	13. Exceptions and files	22. Working with text
5. Tuples / comprehensions	14. Doc, testing, debugging	23. Relational data
6. Dictionaries and sets	15. Decorators	24. Clustering
7. Functions	16. Dynamic programming	25. Graphical user interfaces (GUI)
8. Recursion	17. Visualization and optimization	26. Java vs Python
9. Recursion and Iteration	18. Multi-dimensional data	27. Final lecture

10 handins
1 final project (last 1 month)

Python decorators are just syntatic sugar

Python

```python
@dec2
@dec1
def func(arg1, arg2, ...):
    pass
```

≡

Python

```python
def func(arg1, arg2, ...):
    pass

func = dec2(dec1(func))
```

'pie-decorator' syntax

dec1, dec2, ... are functions (decorators) taking a *function as an argument* and *returning a new function*

Note: decorators are listed bottom up in order of execution

Recap functions

Contrived example : Plus one (I-II)

plus_one1.py

```
def plus_one(x):
    return x + 1

def square(x):
    return x ** 2

def cube(x):
    return x ** 3

print(plus_one(square(5)))
print(plus_one(cube(5)))
```

Python shell

```
| 26
| 126
```

Assume we *always* need to call `plus_one` on the result of `square` and `cube` (don't ask why!)

plus_one2.py

```
def plus_one(x):
    return x + 1

def square(x):
    return plus_one(x ** 2)

def cube(x):
    return plus_one(x ** 3)

print(square(5))
print(cube(5))
```

Python shell

```
| 26
| 126
```

We could call `plus_one` inside functions (but could be more `return` statements in functions)

Contrived example : Plus one (III-IV)

plus_one3.py

```
def plus_one(x):
    return x + 1

def square(x):
    return x ** 2

def cube(x):
    return x ** 3

square_original = square
cube_original = cube

square = lambda x: plus_one(square_original(x))
cube = lambda x: plus_one(cube_original(x))

print(square(5))
print(cube(5))
```

Python shell

```
| 26
| 126
```

Overwrite `square` and `cube` with decorated versions

plus_one4.py

```
def plus_one(x):
    return x + 1

def plus_one_decorator(f):
    return lambda x: plus_one(f(x))

def square(x):
    return x ** 2

def cube(x):
    return x ** 3

square = plus_one_decorator(square)
cube = plus_one_decorator(cube)

print(square(5))
print(cube(5))
```

Python shell

```
| 26
| 126
```

Create a decorator function `plus_one_decorator`

Contrived example : Plus one (V-VI)

plus_one5.py

```
def plus_one(x):
    return x + 1

def plus_one_decorator(f):
    return lambda x: plus_one(f(x))

@plus_one_decorator
def square(x):
    return x ** 2

@plus_one_decorator
def cube(x):
    return x ** 3

print(square(5))
print(cube(5))
```

Python shell

```
| 26
| 126
```

Use Python decorator syntax

plus_one6.py

```
def plus_one_decorator(f):
    def plus_one(x):
        return f(x) + 1

    return plus_one

@plus_one_decorator
def square(x):
    return x ** 2

@plus_one_decorator
def cube(x):
    return x ** 3

print(square(5))
print(cube(5))
```

Python shell

```
| 26
| 126
```

Create local function instead of using `lambda`

Contrived example : Plus one (VII)

plus_one7.py

```
def plus_one_decorator(f):
    def plus_one(x):
        return f(x) + 1
    return plus_one

@plus_one_decorator
@plus_one_decorator
def square(x):
    return x ** 2

@plus_one_decorator
@plus_one_decorator
@plus_one_decorator
def cube(x):
    return x ** 3

print(square(5))
print(cube(5))
```

Python shell

```
| 27
| 128
```

- A function can have an arbitrary number of decorators (also the same repeated)
- Decorators are listed bottom up in order of execution

Handling arguments

run_twice1.py

```
def run_twice(f):
    def wrapper():
        f()
        f()

    return wrapper

@run_twice
def hello_world():
    print('Hello world')

hello_world()
```

Python shell

```
| Hello world
| Hello world
```

"`wrapper`" is a common name for the function returned by a decorator

run_twice2.py

```
def run_twice(f):
    def wrapper(*args):
        f(*args)
        f(*args)

    return wrapper

@run_twice
def hello_world():
    print('Hello world')

@run_twice
def hello(txt):
    print('Hello', txt)

hello_world()
hello('Mars')
```

Python shell

```
| Hello world
| Hello world
| Hello Mars
| Hello Mars
```

`args` holds the arguments in a tuple given to the function to be decorated

Question – What does the decorated program print ?

decorator_quiz.py

```
def double(f):
    def wrapper(*args):
        return 2 * f(*args)
    return wrapper

def add_three(f):
    def wrapper(*args):
        return 3 + f(*args)
    return wrapper

@double
@add_three
def seven():
    return 7

print(seven())
```

- 7
- 10
- 14
- 17
- 20
- Don’t know

Example: Enforcing argument types

- Defining decorators can be (slightly) complicated
- Using decorators is easy

integer_sum1.py

```
def integer_sum(*args):
    assert all([isinstance(x, int) for x in args]),\
           'all arguments most be int'
    return sum(args)
```

Python shell

```
> integer_sum(1, 2, 3, 4)
| 10
> integer_sum(1, 2, 3.2, 4)
| AssertionError: all arguments most be int
```

integer_sum2.py

```
def enforce_integer(f):    # decorator function
    def wrapper(*args):
        assert all([isinstance(x, int) for x in args]),\
               'all arguments most be int'
        return f(*args)
    return wrapper

@enforce_integer
def integer_sum(*args):
    return sum(args)
```

Python shell

```
> integer_sum(1, 2, 3, 4)
| 10
> integer_sum(1, 2, 3.2, 4)
| AssertionError: all arguments most be int
```

Decorators can take arguments

```python
@dec(argA, argB, ...)
def func(arg1, arg2, ...):
    pass
```

≡

```python
def func(arg1, arg2, ...):
    pass
func = dec(argA, argB, ...)(func)
```

`dec` is a function (decorator) that takes a *list of arguments* and *returns a function* (to decorate `func`) that takes a *function as an argument* and *returns a new function*

Example: Generic type enforcing

print_repeated.py

```
def enforce_types(*decorator_args):
    def decorator(f):
        def wrapper(*args):
            assert len(args) == len(decorator_args), \
                   f'got {len(args)} arguments, expected {len(decorator_args)}'
            assert all([isinstance(x, t) for x, t in zip(args, decorator_args)]), \
                   'unexpected types'

            return f(*args)

        return wrapper

    return decorator

@enforce_types(str, int)  # decorator with arguments
def print_repeated(txt, n):
    print(txt * n)

print_repeated('Hello ', 3)
print_repeated('Hello ', 'world')
```

Python

```
@dec(argA, argB, ...)
def func(arg1, arg2, ...):
    pass
```

≡

Python

```
def func(arg1, arg2, ...):
    pass
func = dec(argA, argB, ...)(func)
```

Python shell

```
| Hello Hello Hello
| AssertionError: unexpected types
```

Example: A timer decorator

time_it.py

```
import time

def time_it(f):
    def wrapper(*args, **kwargs):
        t_start = time.time()
        result = f(*args, **kwargs)
        t_end = time.time()
        t = t_end - t_start
        print(f'{f.__name__} took {t:.2f} seconds')
        return result

    return wrapper

@time_it
def slow_function(n):
    sum_ = 0
    for x in range(n):
        sum_ += x
    print('The sum is:', sum_)

for i in range(6):
    slow_function(1_000_000 * 2 ** i)
```

Python shell

```
The sum is: 499999500000
slow_function took 0.27 sec
The sum is: 1999999000000
slow_function took 0.23 sec
The sum is: 7999998000000
slow_function took 0.41 sec
The sum is: 31999996000000
slow_function took 0.81 sec
The sum is: 127999992000000
slow_function took 1.52 sec
The sum is: 511999984000000
slow_function took 3.12 sec
```

Built-in `@property`

- decorator specific for class methods
- allows accessing `x.attribute()` as `x.attribute`, convenient if `attribute` does not take any arguments (also readonly)

rectangle1.py

```
class Rectangle:
    def __init__(self, width, height):
        self.width = width
        self.height = height

#   @property
    def area(self):
        return self.width * self.height
```

Python shell

```
> r = Rectangle(3, 4)
> print(r.area())
| 12
```

rectangle2.py

```
class Rectangle:
    def __init__(self, width, height):
        self.width = width
        self.height = height

    @property
    def area(self):
        return self.width * self.height
```

Python shell

```
> r = Rectangle(3, 4)
> print(r.area)
| 12
```

Class decorators

Python

```
@dec2
@dec1
class A:
  pass
```

≡

Python

```
class A:
  pass

A = dec2(dec1(A))
```

Module `dataclasses` (Since Python 3.7)

- New (and more configurable) alternative to `namedtuple`

Python shell

```
> from dataclasses import dataclass
> @dataclass  # uses a decorator to add methods to the class
  class Person:
      name: str  # uses type annotation to define fields
      appeared: int
      height: str = 'unknown height'  # field with default value
> person = Person('Donald Duck', 1934, '3 feet')
> person
| Person(name='Donald Duck', appeared=1934, height='3 feet')
> person.name
| 'Donald Duck'
> person.height = '3.5 feet'
> Person('Mickey Mouse', 1928)
| Person(name='Mickey Mouse', appeared=1928, height='unknown height')
```

docs.python.org/3/library/dataclasses.html#module-dataclasses

Raymond Hettinger - Dataclasses: The code generator to end all code generators - PyCon 2018

@functools.total_ordering (class decorator)

student.py

```
import functools

@functools.total_ordering
class Student():
    def __init__(self, name, student_id):
        self.name = name
        self.id = student_id

    def __eq__(self, other):
        return (self.name == other.name and self.id == other.id)

    def __lt__(self, other):
        my_name = ', '.join(reversed(self.name.split()))
        other_name = ', '.join(reversed(other.name.split()))
        return (my_name < other_name
                or (my_name == other_name and self.id < other.id))

donald = Student('Donald Duck', 7)
gladstone = Student('Gladstone Gander', 42)
grandma = Student('Grandma Duck', 1)
```

Automatically creates <, <=, >, >= if at least one of the functions is implemented and == is implemented

Python shell

```
> donald < grandma
| True
> grandma >= gladstone
| False
> grandma <= gladstone
| True
> donald > gladstone
| False
```

class_decorator.py

```python
def add_lessequal(cls):
    '''Class decorator to add __le__ given __eq__ and __lt__.'''
    cls.__le__ = lambda self, other : self == other or self < other
    return cls  # the original class cls with attribute __le__ added

def add_lessequal(cls):  # alternative
    class sub_cls(cls):
        def __le__(self, other):
            return self == other or self < other
    return sub_cls  # new subclass of class cls

@add_lessequal  # Vector = add_lessequal(Vector)
class Vector:
    def __init__(self, x, y):
        self.x = x
        self.y = y
    def _length_squared(self):
        return self.x ** 2 + self.y ** 2
    def __eq__(self, other):
        # Required, otherwise Vector(1, 2) == Vector(1, 2) is False
        return self._length_squared() == other._length_squared()
    def __lt__(self, other):
        return self._length_squared() < other._length_squared()
#    def __le__(self, other):
#        return self._length_squared() <= other._length_squared()
#    def __le__(self, other):
#        return self == other or self < other
```

Python shell

```python
> u = Vector(3, 4)
> v = Vector(2, 5)
> u.__eq__(v)
| False
> u.__ne__(v)
| True  # not u.__eq__(v)
> u.__lt__(v)
| True
> u.__gt__(v)
| NotImplemented  # special value
> u.__le__(v)
| True  # added by @add_lessequal
> u.__ge__(v)
| NotImplemented  # special value
> u == v
| False
> u != v
| True
> u < v
| True
> u > v  # v < u
| False
> u <= v
| True
> u >= v  # v <= u
| False
```

https://docs.python.org/3/reference/datamodel.html#basic-customization

Summary

- *@decorator_name*
- Pyton decorators are just syntatic sugar
- Adds functionality to a function without having to augment each call to the function or each return statement in the function
- There are decorators for functions, class methods, and classes
- There are many decorators in the Python Standard Library
- Decorators are easy to use
- ...and (slightly) harder to write

Dynamic programming

- memoization
- decorator memoized / functools.cache
- systematic subproblem computation

Binomial coefficient

```
--(7, 5)
  |--(6, 5)
  |   |--(5, 5)
  |    --(5, 4)
  |      |--(4, 4)
  |       --(4, 3)
  |         |--(3, 3)
  |          --(3, 2)
  |            |--(2, 2)
  |             --(2, 1)
  |               |--(1, 1)
  |                --(1, 0)
   --(6, 4)
     |--(5, 4)
     |   |--(4, 4)
     |    --(4, 3)
     |      |--(3, 3)
     |       --(3, 2)
     |         |--(2, 2)
     |          --(2, 1)
     |            |--(1, 1)
     |             --(1, 0)
      --(5, 3)
        |--(4, 3)
        |   |--(3, 3)
        |    --(3, 2)
        |      |--(2, 2)
        |       --(2, 1)
        |         |--(1, 1)
        |          --(1, 0)
         --(4, 2)
           |--(3, 2)
           |   |--(2, 2)
           |    --(2, 1)
           |      |--(1, 1)
           |       --(1, 0)
            --(3, 1)
              |--(2, 1)
              |   |--(1, 1)
              |    --(1, 0)
               --(2, 0)
```

identical computations

recursion tree for `binomial(7,5)`

$$\binom{n}{k} = \begin{cases} 1 & \text{if } k = 0 \text{ or } k = n \\ \binom{n-1}{k} + \binom{n-1}{k-1} & \text{otherwise} \end{cases}$$

binomial_recursive.py

```python
def binomial(n, k):
    if k == 0 or k == n:
        return 1
    return binomial(n - 1, k) + binomial(n - 1, k - 1)
```

Dynamic Programming
≡
Remember solutions already found (memoization)

- Technique sometimes applicable when running time otherwise becomes exponential
- Only applicable if stuff to be remembered is manageable

Binomial Coefficient
Dynamic programming using a dictionary

recursion tree for
`binomial(7,5)`

```
--(7, 5)
  |--(6, 5)
  |   |--(5, 5)
  |    --(5, 4)
  |      |--(4, 4)
  |       --(4, 3)
  |         |--(3, 3)
  |          --(3, 2)
  |            |--(2, 2)
  |             --(2, 1)
  |               |--(1, 1)
  |                --(1, 0)
   --(6, 4)
     |--(5, 4)
      --(5, 3)
        |--(4, 3)
         --(4, 2)
           |--(3, 2)
            --(3, 1)
              |--(2, 1)
               --(2, 0)
```

reuse value stored in dictionary `answers`

binomial_dictionary.py

```python
answers = {}  # answers[(n, k)] = binomial(n, k)

def binomial(n, k):
    if (n, k) not in answers:
        if k == 0 or k == n:
            answer = 1
        else:
            answer = binomial(n - 1, k) + binomial(n - 1, k - 1)
        answers[(n, k)] = answer
    return answers[(n, k)]
```

Python shell

```
> binomial(6, 3)
| 20
> answers
| {(3, 3): 1, (2, 2): 1, (1, 1): 1, (1, 0): 1, (2, 1): 2, (3, 2):
  3, (4, 3): 4, (2, 0): 1, (3, 1): 3, (4, 2): 6, (5, 3): 10, (3,
  0): 1, (4, 1): 4, (5, 2): 10, (6, 3): 20}
```

- Use a dictionary `answers` to store already computed values

Question – What is the order of the size of the dictionary **`answers`** after calling **`binomial(n, k)`** ?

binomial_dictionary.py

```
answers = {}  # answers[(n, k)] = binomial(n, k)

def binomial(n, k):
    if (n, k) not in answers:
        if k == 0 or k == n:
            answer = 1
        else:
            answer = binomial(n - 1, k) + binomial(n - 1, k - 1)
        answers[(n, k)] = answer
    return answers[(n, k)]
```

a) max(n, k)

b) n + k

c) n * k

d) n^k

e) k^n

f) Don't know

Binomial Coefficient
Dynamic programming using decorator

- Use a decorator (@memoize) that implements the functionality of remembering the results of previous function calls

binomial_decorator.py

```python
def memoize(f):
    # answers[args] = f(*args)
    answers = {}
    def wrapper(*args):
        if args not in answers:
            answers[args] = f(*args)
        return answers[args]
    return wrapper
```

```python
@memoize
def binomial(n, k):
    if k == 0 or k == n:
        return 1
    else:
        return binomial(n - 1, k) + binomial(n - 1, k - 1)
```

www.python-course.eu/python3_memoization.php

binomial_decorator_trace.py

```python
def trace(f):  # decorator to trace recursive calls
    indent = 0

    def wrapper(*args):
        nonlocal indent

        spaces = '|   ' * indent
        arg_str = ', '.join(map(repr, args))
        print(spaces + f'{f.__name__}({arg_str})')
        indent += 1
        result = f(*args)
        indent -= 1
        print(spaces + f'> {result}')
        return result

    return wrapper

def memoize(f):
    answers = {}

    def wrapper(*args):
        if args not in answers:
            answers[args] = f(*args)
        return answers[args]

    wrapper.__name__ = f.__name__ + '_memoize'

    return wrapper

@trace
@memoize
def binomial(n, k):
    if k == 0 or k == n:
        return 1
    return binomial(n - 1, k) + binomial(n-1, k-1)

print(binomial(5, 2))
```

Python shell (without @memoize)

```
binomial(5, 2)
|   binomial(4, 2)
|   |   binomial(3, 2)
|   |   |   binomial(2, 2)
|   |   |   > 1
|   |   |   binomial(2, 1)
|   |   |   |   binomial(1, 1)
|   |   |   |   > 1
|   |   |   |   binomial(1, 0)
|   |   |   |   > 1
|   |   |   > 2
|   |   > 3
|   |   binomial(3, 1)
|   |   |   binomial(2, 1)
|   |   |   |   binomial(1, 1)
|   |   |   |   > 1
|   |   |   |   binomial(1, 0)
|   |   |   |   > 1
|   |   |   > 2
|   |   |   binomial(2, 0)
|   |   |   > 1
|   |   > 3
|   > 6
|   binomial(4, 1)
|   |   binomial(3, 1)
|   |   |   binomial(2, 1)
|   |   |   |   binomial(1, 1)
|   |   |   |   > 1
|   |   |   |   binomial(1, 0)
|   |   |   |   > 1
|   |   |   > 2
|   |   |   binomial(2, 0)
|   |   |   > 1
|   |   > 3
|   |   binomial(3, 0)
|   |   > 1
|   > 4
> 10
10
```

Python shell (with @memoize)

```
binomial_memoize(5, 2)
|   binomial_memoize(4, 2)
|   |   binomial_memoize(3, 2)
|   |   |   binomial_memoize(2, 2)
|   |   |   > 1
|   |   |   binomial_memoize(2, 1)
|   |   |   |   binomial_memoize(1, 1)
|   |   |   |   > 1
|   |   |   |   binomial_memoize(1, 0)
|   |   |   |   > 1
|   |   |   > 2
|   |   > 3
|   |   binomial_memoize(3, 1)
|   |   |   binomial_memoize(2, 1)
|   |   |   > 2
|   |   |   binomial_memoize(2, 0)
|   |   |   > 1
|   |   > 3
|   > 6
|   binomial_memoize(4, 1)
|   |   binomial_memoize(3, 1)
|   |   > 3
|   |   binomial_memoize(3, 0)
|   |   > 1
|   > 4
> 10
10
```

without assigning `wrapper.__name__` the name shown would be `wrapper`

saved recursive calls when using memoization

Dynamic programming using cache decorator

bionomial_cache.py

```
from functools import cache

@cache
def binomial(n, k):
    if k == 0 or k == n:
        return 1
    else:
        return binomial(n - 1, k) + binomial(n - 1, k - 1)
```

- The decorators `@cache` (since Python 3.9) and `@lru_cache(maxsize=None)` in the standard library `functools` supports the same as the decorator `@memoize`
- By default `@lru_cache` at most remembers (caches) 128 previous function calls, always evicting **L**east **R**ecently **U**sed entries from its dictionary
- `functools.cache` can have problems when using `sys.setrecursionlimit` (e.g. with Python 3.13 on Windows)

docs.python.org/3/library/functools.html#functools.cache

Subset sum using dynamic programming

- In the subset sum problem (Exercise 13.4) we are given a number `x` and a list of numbers `L`, and want to determine if a subset of `L` has sum `x`

```
L = [3, 7, 2, 11, 13, 4, 8]    x = 22 = 7 + 11 + 4
```

- Let S(v, k) denote if it is possible to achieve value v with a subset of `L`[:k], i.e. S(v, k) = True if and only if a subset of the first k values in `L` has sum v
- S(v, k) can be computed from the recurrence

$$S(v, k) = \begin{cases} \text{True} & \text{if } k = 0 \text{ and } v = 0 \\ \text{False} & \text{if } k = 0 \text{ and } v \neq 0 \\ S(v, k-1) \text{ or } S(v - \texttt{L}[k-1], k-1) & \text{otherwise} \end{cases}$$

Subset sum using dynamic programming

subset_sum_dp.py

```
def subset_sum(x, L):
    @memoize
    def solve(value, k):
        if k == 0:
            return value == 0
        return solve(value, k - 1) or solve(value - L[k - 1], k - 1)

    return solve(x, len(L))
```

Python shell

```
> subset_sum(11, [2, 3, 8, 11, -1])
| True
> subset_sum(6, [2, 3, 8, 11, -1])
| False
```

$$S(v, k) = \begin{cases} \text{True} & \text{if } k = 0 \text{ and } v = 0 \\ \text{False} & \text{if } k = 0 \text{ and } v \neq 0 \\ S(v, k-1) \text{ or } S(v - \mathtt{L}[k-1], k-1) & \text{otherwise} \end{cases}$$

Question – What is a bound on the size order of the memoization table if all values are possitive integers?

subset_sum_dp.py

```
def subset_sum(x, L):
    @memoize
    def solve(value, k):
        if k == 0:
            return value == 0
        return solve(value, k-1) or solve(value - L[k-1], k-1)
    return solve(x, len(L))
```

Python shell

```
> subset_sum(11, [2, 3, 8, 11, -1])
| True
> subset_sum(6, [2, 3, 8, 11, -1])
| False
```

a) `len(L)`

b) `sum(L)`

c) `x`

d) $2^{\texttt{len(L)}}$

e) `len(L)`

f) `len(L)*sum(L)`

g) Don't know

Subset sum using dynamic programming

subset_sum_dp.py

```
def subset_sum_solution(x, L):
    @memoize
    def solve(value, k):
        if k == 0:
            if value == 0:
                return []
            else:
                return None
        solution = solve(value, k - 1)
        if solution != None:
            return solution
        solution = solve(value - L[k - 1], k - 1)
        if solution != None:
            return solution + [L[k - 1]]
        return None

    return solve(x, len(L))
```

Python shell

```
> subset_sum_solution(11, [2, 3, 8, 11, -1])
| [3, 8]
> subset_sum_solution(6, [2, 3, 8, 11, -1])
| None
```

Knapsack problem

	Volume	Value
0	3	6
1	3	7
2	2	8
3	5	9

- Given a **knapsack** with volume **capacity C**, and set of **objects** with different **volumes and value**
- **Objective**: Find a subset of the objects that fits in the knapsack (sum of volume ≤ capacity) and has maximal value
- **Example**: If C = 5 and the volume and weights are given by the table, then the maximal value 15 can be achieved by the 2nd and 3rd object
- Let V(c, k) denote the maximum value achievable by a subset of the first k objects within capacity c

$$V(c, k) = \begin{cases} 0 & \text{if } k = 0 \\ V(c, k-1) & \text{volume}[k-1] > c \\ \max\{V(c, k-1), \text{value}[k-1] + V(c - \text{volume}[k-1], k-1)\} & \text{otherwise} \end{cases}$$

Knapsack – maximum value

knapsack.py

```
def knapsack_value(volume, value, capacity):
    @memoize
    def solve(c, k):  # solve with capacity c and objects 0..k-1
        if k == 0:  # no objects to put in knapsack
            return 0
        v = solve(c, k - 1)  # try without object k-1
        if volume[k - 1] <= c:  # try also with object k-1 if space
            v = max(v, value[k - 1] + solve(c - volume[k - 1], k - 1))
        return v
    return solve(capacity, len(volume))
```

Python shell

```
> volumes = [3, 3, 2, 5]
> values = [6, 7, 8, 9]
> knapsack_value(volumes, values, 5)
| 15
```

Knapsack – maximum value and objects

knapsack.py

```
def knapsack(volume, value, capacity):
    @memoize
    def solve(c, k):  # solve with capacity c and objects 0..k-1
        if k == 0:  # no objects to put in knapsack
            return 0, []
        v, solution = solve(c, k - 1)  # try without object k-1
        if volume[k - 1] <= c:  # try also with object k-1 if space
            v2, sol2 = solve(c - volume[k - 1], k - 1)
            v2 = v2 + value[k - 1]
            if v2 > v:
                v = v2
                solution = sol2 + [k - 1]
        return v, solution

    return solve(capacity, len(volume))
```

Python shell

```
> volumes = [3, 3, 2, 5]
> values = [6, 7, 8, 9]
> knapsack(volumes, values, 5)
| (15, [1, 2])
```

Knapsack - Table

$$V(c, k) = \begin{cases} 0 & \text{if } k = 0 \\ V(c, k-1) & \text{value}[k-1] > c \\ \max\{V(c, k-1), \text{value}[k-1] + V(c - \text{volume}[k-1], k-1)\} & \text{otherwise} \end{cases}$$

- systematic fill out table
- only need to remember two rows

Knapsack – Systematic table fill out

knapsack_systematic.py

```
def knapsack(volume, value, capacity):
  ① solutions = [(0, [])] * (capacity + 1)
  ② for obj in range(len(volume)):
        for c in reversed(range(volume[obj], capacity + 1)):
            prev_v, prev_solution = solutions[c - volume[obj]]
            v = value[obj] + prev_v
            if solutions[c][0] < v:
              ③ solutions[c] = v, prev_solution + [obj]

    return solutions[capacity]
```

Python shell

```
> volumes = [3, 3, 2, 5]
> values = [6, 7, 8, 9]
> knapsack(volumes, values, 5)
| (15, [1, 2])
```

① base case k = 0

② consider each object

③ `solutions[c:]` current row
`solutions[:c]` previous row

④ compute next row right-to-left

⑤ `solutions[:volume[obj]]` unchanged from previous row

Summary

- Dynamic programming is a general approach for recursive problems where one tries to avoid recomputing the same expresions repeatedly

- **Solution 1: Memoization**
  - add dictionary to function to remember previous results
  - decorate with a @memoize decorator
- **Solution 2: Systematic table fill out**
  - can need to compute more values than when using memoization
  - can discard results not needed any longer (reduced memory usage)

Coding competitions and online judges

If you like to practice your coding skills, there are many online "judges" with numerous exercises and where you can upload and test your solutions.

- Project Euler
- Kattis
- CodeForces
- Topcoder

See cs.au.dk/~gerth/code/

Visualization and optimization

- Matplotlib
- Jupyter
- scipy.optimize.minimize

matplotlib

Matplotlib is a Python 2D plotting library which produces publication quality figures in a variety of hardcopy formats and interactive environments across platforms. Matplotlib can be used in Python scripts, the Python and IPython shells, the Jupyter notebook, web application servers, and four graphical user interface toolkits.

Matplotlib tries to make easy things easy and hard things possible. You can generate plots, histograms, power spectra, bar charts, errorcharts, scatterplots, etc., with just a few lines of code. For simple plotting the pyplot module provides a MATLAB-like interface, particularly when combined with IPython. For the power user, you have full control of line styles, font properties, axes properties, etc, via an object oriented interface or via a set of functions familiar to MATLAB users.

pip install matplotlib

matplotlib.org

Plot

pyplot module ≈ MATLAB-like plotting framework

matplotlib-simple.py

```
import matplotlib.pyplot as plt

plt.plot([1, 2, 3], [5, 2, 7], 'bo:')

plt.show()
```

add plot to figure

figure is first shown when show is called

x coordinates

y coordinates

format string

Colors	Line styles	Marker styles					
b	-	.		2		+	
g	--	,		3		x	
r	-.	o		4		D	
c	:	v		s		d	
m		^		p		|	
y		<		*		_	
k		>		h			
w		1		H			

save current view as picture

adjust margins

zoom rectangle

pan and zoom

navigate view history

reset view

Plot – some keyword arguments

matplotlib-plot.py

```
import matplotlib.pyplot as plt

X = range(-10, 11)
Y1 = [x ** 2 for x in X]
Y2 = [x ** 3 / 10 + x ** 2 / 2 for x in X]

plt.plot(X, Y1, color='red', label='$x^2$',
    linestyle='-', linewidth=2,
    marker='o', markersize=4,
    markeredgewidth=1,
    markeredgecolor='black',
    markerfacecolor='yellow')

plt.plot(X, Y2, '*', dashes=(2, 0.5, 2, 1.5),
    label=r'$\frac{1}{10}x^3+\frac{1}{2}x^2$')

plt.xlim(-15, 15)
plt.ylim(-75, 125)
plt.title('Some polynomials\n(degree 2 and 3)')

plt.xlabel('The x-axis')
plt.ylabel('The y-axis')
plt.legend(title='Curves')

plt.show()  # finally show figure
```

LaTeX

matplotlib.org/api/_as_gen/matplotlib.pyplot.plot.html

Colors: matplotlib.org/gallery/color/named_colors.html

Scatter (points with individual size and color)

colorbar
(of most recently used colormap)

matplotlib-scatter.py

```
import matplotlib.pyplot as plt

n = 13
X = range(n)
S = [x ** 2 for x in X]
E = [2 ** x for x in X]

plt.scatter(X, [4] * n, s=E, label='s = $2^x$', alpha=.2)
plt.scatter(X, [3] * n, s=S, label='s = $x^2$')
plt.scatter(X, [2] * n, s=X, label='s = $x$')
plt.scatter(X, [1] * n, s=S, c=X, cmap='plasma',
    label='s = $x^2$, c = $x$',
    edgecolors='gray', linewidth=0.5)
plt.colorbar()

plt.ylim(0.5, 5.5)
plt.xlim(0.5, 13.5)
plt.title('A scatter plot')
legend = plt.legend(loc='upper center', frameon=False,
    ncol=4, handletextpad=0)
for handle in legend.legend_handles:
    handle.set_sizes([100])  # fix marker size in legend

plt.show()
```

transparency

colormap (predefined)
color of each point
size ≈ area of each point
point boundary width
point boundary color

manual placement of legend box (default automatic); remove frame; place legends in 4 columns (default 1); reduce space between marks and label

matplotlib.org/api/_as_gen/matplotlib.pyplot.scatter.html
matplotlib.org/tutorials/colors/colormaps.html

Bars

matplotlib-bars.py

```
import matplotlib.pyplot as plt

x = [1, 2, 3]
y = [7, 5, 10]

plt.bar(x, y,
        color='lightblue',   # bar background color
        linewidth=1,         # bar boundary width
        edgecolor='gray',    # bar boundary color
        tick_label=x,        # ticks on x-axis
        width=0.7,           # width, default 0.8
        yerr=0.25,           # Error bar: y length
        xerr=0.5,            #   x length
        capsize=3,           #   capsize in points
        ecolor='darkblue',   #   error bar color
        log=True)            # y-axis log scale
plt.bar(x, [v**2 for v in x],
        color='pink',
        linewidth=1,
        edgecolor='gray')

plt.show()
```

matplotlib.org/api/_as_gen/matplotlib.pyplot.bar.html

Histogram

matplotlib-histogram.py

```
import matplotlib.pyplot as plt
from random import random

values1 = [random()**2 for _ in range(1000)]
values2 = [random()**3 for _ in range(100)]

bins = [0.0, 0.25, 0.5, 0.75, 1.0]

for i, ht in enumerate(
        ['bar', 'barstacked', 'step', 'stepfilled'],
        start=1):
    plt.subplot(2, 2, i)  # start new plot
    plt.hist([values1, values2],  # data sets
             bins,        # bucket boundaries
             histtype=ht, # default ht='bar'
             rwidth=0.7,  # fraction of bucket width
             label=['$x^2$', '$x^3$'],  # labels
             density=True)  # norm. prob. density
    plt.title(ht)         # plot title
    plt.xticks(bins)      # ticks on x-axis
    plt.legend()

plt.suptitle('Histogram') # figure title
plt.show()
```

matplotlib.org/api/_as_gen/matplotlib.pyplot.hist.html

Pie

matplotlib-pie.py

```
import matplotlib.pyplot as plt

plt.title('My Pie')
plt.pie([2, 3, 2, 7],          # relative wedge sizes
        labels=['A','B','C','D'],
        colors=['r', 'b', 'y', 'm'],
        explode=(0, 0.1, 0.3, 0),  # radius fraction
        startangle=5,          # angle above horizontal
        counterclock=True,     # default True
        rotatelabels=False,    # default False
        shadow=True,           # default False
        textprops=dict(        # text properties, dict
            color='black',     # text color
            style='italic'),   # text style
        wedgeprops=dict(       # wedge properties, dict
            width=0.8,         # width (missing center)
            linewidth=1,       # wedge boundary width
            edgecolor='black'),  # boundary color
        autopct='%1.1f %%')    # percent formatting

plt.show()
```

matplotlib.org/api/_as_gen/matplotlib.pyplot.pie.html

Customizing Pie shadows

- Need to do do it manually on each pie using matplotlib.patches.Shadow

matplotlib-pie-shadow.py

```
import matplotlib.pyplot as plt
from matplotlib.patches import Shadow

patches, texts, autotexts = plt.pie(
    [1, 2, 2],
    explode=(0.1, 0.1, 0.1),
    autopct='%1.0f %%'
)

for pie in patches:
    pie_shadow = Shadow(
        pie, 0.03, -0.03,  # patch, x-offset, y-offset
        alpha=0.3,         # shadow transparency
        edgecolor=None,    # shadow edge color
        facecolor=pie._facecolor  # shadow fill color
    )
    plt.gca().add_patch(pie_shadow)

plt.show()
```

https://matplotlib.org/stable/api/_as_gen/matplotlib.patches.Shadow.html

Stackplot

matplotlib-stackplot.py

```
import matplotlib.pyplot as plt

x = [1, 2, 3, 4]

y1 = [1, 2, 3, 4]
y2 = [2, 3, 1, 4]
y3 = [2, 4, 1, 3]

plt.style.use('dark_background')
for i, base in enumerate(
        ['zero', 'sym', 'wiggle','weighted_wiggle'],
        start=1):
    plt.subplot(4, 1, i)
    plt.stackplot(x, y1, y2, y3,
                  colors=['r', 'g', 'b'],
                  labels=['Red', 'Green', 'Blue'],
                  baseline=base)
    plt.grid(axis='both',  # 'x', 'y', or 'both'
        linewidth=0.5, linestyle='-', alpha=0.5)
    plt.legend(title=base, loc='upper left')
    plt.xticks(x)  # a tick for each value in x

plt.suptitle('Stackplot')
plt.show()
```

Stacked Graphs – Geometry & Aesthetics
Lee Byron & Martin Wattenberg, 2008

To list all available styles:
`print(plt.style.available)`

matplotlib.org/api/_as_gen/matplotlib.pyplot.stackplot.html

Subplot

(2 rows, 3 columns)

matplotlib-subplot.py

```
import matplotlib.pyplot as plt
from math import pi, sin

x_min, x_max, n = 0, 2 * pi, 100
x = [x_min + (x_max - x_min) * i / n for i in range(n + 1)]
y = [sin(v) for v in x]

ax1 = plt.subplot(2, 3, 1)  # 2 rows, 3 columns
ax1.label_outer()           # removes x-axis labels
plt.xlim(-pi, 3 * pi)       # increase x-axis range
plt.plot(x, y, 'r-')
plt.title('Plot A')

ax2 = plt.subplot(2, 3, 2)
ax2.label_outer()           # removes x- and y-axis labels
plt.xlim(-2 * pi, 4 * pi)   # increase x-axis range
plt.plot(x, y, 'g,')
plt.title('Plot B')

ax3 = plt.subplot(2, 3, 3, frameon=False)  # remove frame
ax3.set_xticks([])          # remove x-axis ticks & labels
ax3.set_yticks([])          # remove x-axis ticks & labels
plt.plot(x, y, 'b--')
plt.title('No frame')

ax4 = plt.subplot(2, 3, 4, sharex=ax1)  # share x-axis range
plt.ylim(-2, 2)             # increase y-axis range
plt.plot(x, y, 'm:')
plt.title('Plot C')

ax5 = plt.subplot(2, 3, 5, sharex=ax2, sharey=ax4) # share ranges
ax5.set_xticks(range(-5, 15, 5))  # specific x-ticks & x-labels
ax5.label_outer()           # removes y-axis labels
plt.plot(x, y, 'k-.')
plt.title('Plot D')

ax6 = plt.subplot(2, 3, 6, projection='polar')  # polar projection
ax6.set_yticks([-1, 0, 1])                      # y-labels
ax6.tick_params(axis='y', labelcolor='red')     # color of y-labels
plt.plot(x, y, 'r')
plt.title('Polar projection\n')  # \n to avoid overlap with 90°

plt.suptitle('2 x 3 subplots', fontsize=16)

plt.show()
```

- Subplots are numbered 1..6 row-by-row, starting top-left
- subplot returns an axes to access the plot in the figure

matplotlib.org/api/_as_gen/matplotlib.pyplot.subplot.html

Subplots

matplotlib-subplots.py

```
import matplotlib.pyplot as plt
from math import pi, sin, cos

times = [2 * pi * t / 1000 for t in range(1001)]

fig, ((ax1, ax2), (ax3, ax4), (ax5, ax6)) = \
    plt.subplots(3, 2, sharex=True, sharey=True)

for i, ax in enumerate([ax1, ax2, ax3, ax4, ax5, ax6],
                       start=1):
    x = [i * sin(i * t) for t in times]
    y = [i * cos(3 * t) for t in times]
    ax.plot(x, y, label=f'$i = {i}$')  # plot to axes
    ax.legend(loc='upper right')       # axes legend

fig.suptitle('subplots', fontsize=16)  # figure title

plt.show()
```

create 6 axes in 3 rows with 2 colums
share the x- and y-axis ranges (automatically applies label_outer to created axes)
returns a pair (figure, axes)

matplotlib.org/api/_as_gen/matplotlib.pyplot.subplots.html

subplot2grid (5 x 5)

matplotlib-subplot2grid.py

```
import matplotlib.pyplot as plt
import math

x_min, x_max, n = 0, 2 * math.pi, 20

x = [x_min + (x_max - x_min) * i / n
     for i in range(n + 1)]
y = [math.sin(v) for v in x]

plt.subplot2grid((5, 5), (0,0),
                 rowspan=3, colspan=3)
plt.fill_between(x, 0.0, y,
                 alpha=0.25, color='r')
plt.plot(x, y, 'r-')
plt.title('Plot A')

plt.subplot2grid((5, 5), (0,3),
                 rowspan=2, colspan=2)
plt.plot(x, y, 'g.')
plt.title('Plot B')

plt.subplot2grid((5, 5), (2,3),
                 rowspan=1, colspan=2)
plt.plot(x, y, 'b--')
plt.title('Plot C')

plt.subplot2grid((5, 5), (3,0),
                 rowspan=2, colspan=5)
plt.plot(x, y, 'mx:')
plt.title('Plot D')

plt.tight_layout()  # adjust padding
plt.show()
```

upper left corner (row, column)

matplotlib.org/api/_as_gen/matplotlib.pyplot.subplot2grid.html

log scales

matplotlib-log.py

```
import matplotlib.pyplot as plt

x = [i / 10 for i in range(1, 101)]

y1 = [i ** 2 for i in x]
y2 = [i ** 3 for i in x]
y3 = [3 ** i for i in x]

for i in range(1, 7):
    ax = plt.subplot(3, 2, i)
    plt.plot(x, y3, label='$3^x$')
    plt.plot(x, y2, label='$x^3$')
    plt.plot(x, y1, label='$x^2$')
    match i:
      case 1:
        plt.ylim(0, 2000)
        plt.xscale('linear')  # default
        plt.yscale('linear')  # default
        plt.legend()
        plt.title('linear')
      case 2:
        plt.yscale('log')
        plt.title('plt.yscale')
      case 3:
        ax.set_xscale('log')
        ax.set_yscale('log')
        plt.title('ax.set_xscale & ax.set_yscale')
      case 4:
        plt.loglog()
        plt.title('plt.loglog')
      case 5:
        plt.ylim(0, 2000)
        plt.semilogx()
        plt.title('plt.semilogx')
      case 6:
        plt.semilogy()
        plt.title('plt.semilogy')

plt.show()
```

- There are many ways to make the x- and/or y-axis logarithmic with pyplot

Saving figures

matplotlib-savefig.py

```
import matplotlib.pyplot as plt
from math import pi, sin, cos

n = 1000
points = [(cos(2 * pi * i / n),
           sin(4 * pi * i / n)) for i in range(n)]
x, y = zip(*points)
plt.plot(x, y, 'k-', linewidth=5)

plt.savefig('butterfly.png')  # save plot as PNG

plt.savefig('butterfly-grey.png',
    dpi=100,                  # dots per inch
    bbox_inches='tight',      # crop to bounding box
    pad_inches=0.1,           # space around figure
    facecolor='lightgrey',    # background color
    format='png')             # optional if file extension

plt.savefig('butterfly.pdf')  # save plot as PDF

plt.show()                    # interactive viewer
```

butterfly.png

butterfly-grey.png

facecolor

pad_inches

matplotlib.org/api/_as_gen/matplotlib.pyplot.savefig.html

Interactive mode

Python shell

```
> import matplotlib.pyplot as plt
> plt.ion()                                  # Enable interactive mode
> plt.plot([0, 1], [0, 1], label='up')       # Shows plot immediately
> plt.plot([0, 1], [1, 0], label='down')     # Adds visible line
> plt.legend(loc='upper right')              # Adds visible legend
> plt.ioff()                                 # Disable interactive mode
```

- Useful when developing plot from Python shell
- Automatically shows / updates plot

https://matplotlib.org/stable/api/_as_gen/matplotlib.pyplot.isinteractive.html

A crude animation

clock.py

```
import matplotlib.pyplot as plt
from math import pi, sin, cos
import datetime

def plot_clock(hour, minute, second):
    plt.axis('off')                 # hide x and y axes
    plt.gca().set_aspect('equal')   # don't squeeze circle
    for i in range(60):             # show second marks
        angle = 2 * pi * i / 60
        x, y = cos(angle), sin(angle)
        start = 0.98 if i % 5 else .94  # every 5'th mark should be longer
        plt.plot([start * x, x], [start * y, y], c='black')  # mark
    for angle, length, style in [
        (second / 60, 0.9, dict(c='red', lw=2)),
        (minute / 60, 0.85, dict(c='black', lw=3)),
        ((hour + minute / 60) / 12, 0.5, dict(c='black', lw=8))
    ]:
        angle = 2 * pi * (0.25 - angle)
        x, y = length * cos(angle), length * sin(angle)
        plt.plot([0, x], [0, y], **style, solid_capstyle='round')  # arm
    plt.plot(0, 0, 'o', ms=10, c='black')  # center dot

while True:
    now = datetime.datetime.now()  # local time
    plot_clock(now.hour, now.minute, now.second)
    plt.pause(1)  # show figure and pause 1 second
    plt.clf()     # clear figure
```

matplotlib.org/stable/api/_as_gen/matplotlib.pyplot.pause.html

matplotlib.animation.FuncAnimation

matplotlib-animation.py

```python
import matplotlib.pyplot as plt
from matplotlib.animation import FuncAnimation
from math import pi, cos, sin

n, tail_length = 200, 75
points = []                    # tail_length recent poins

def point(i):
    t = 2 * pi * i / n
    return (cos(3 * t), sin(2 * t))

fig = plt.figure()             # new figure
ax = plt.gca()                 # get current axes
ax.set_facecolor('black')      # set background color
plt.xlim(-1.1, 1.1)            # set x-axis range
plt.ylim(-1.1, 1.1)            # set y-axis range
plt.xticks([])                 # remove x-ticks & labels
plt.yticks([])                 # remove y-ticks & labels
plt.title('Moving point')      # plot title

x, y = point(0)
plt.plot(x, y, 'w.')           # start point
plt.text(x - 0.025, y, 'start', color='w', # text label
    ha='right', va='center')                # alignment
tail, = plt.plot([], [], 'w-', alpha=0.5)  # init. tail
head, = plt.plot([], [], 'ro')     # init. current point

def move(frame):       # frame = value from frames
    x, y = point(frame)
    points.append((x, y))
    del points[:-tail_length]      # limit tail
    tail.set_data(*zip(*points))   # update tail points
    head.set_data([x], [y])        # update head point

animation = FuncAnimation(fig,     # figure to animate
    func=move,         # function called for each frame
    frames=range(n),   # array like to iterate over
    interval=25,       # milliseconds between frames
    repeat=True,       # repeat frames when done
    repeat_delay=0)    # wait milliseconds before repeat

plt.show()
```

- **plot** returns "Line2D" objects representing the plotted data
- "Line2D" objects can be updated using **set_data**
- To make an animation you need to repeatedly update the "line2D" objects
- **FuncAnimation** repeatedly calls func in regular intervals interval, each time with the next value from frames (if frames is None, then the frame values provided to func will be the infinite sequence 0,1,2,3,...)

matplotlib.org/api/_as_gen/matplotlib.animation.FuncAnimation.html

The Jupyter Notebook

The Jupyter Notebook is an open-source web application that allows you to create and share documents that contain live code, equations, visualizations and narrative text. Uses include: data cleaning and transformation, numerical simulation, statistical modeling, data visualization, machine learning, and much more.

jupyter.org

python

IP[y]:
IPython

jupyter

Jupyter Server
(e.g. running on
local machine)

Prime Number Theorem - Jupy

localhost:8888/notebooks/Desktop/Prime Number Theorem.ipynb

jupyter Prime Number Theorem (autosaved)

Logout

File Edit View Insert Cell Kernel Widgets Help Trusted Python 3

Run Code

Prime Number Theorem

$\pi(n) =$ the number of prime numbers $\leq n$. The Prime Number Theorem states that $\pi(n) \approx \frac{n}{\ln(n)}$.
In the following we consider all primes $\leq 1.000.000$. First we computer a set 'composite' of all composite numbers in the range $2..n$.

In [1]:
```
n = 1_000_000
composite = {p for f in range(2, n + 1) for p in range(f * f, n + 1, f)}
```

We next compute select all the prime numbers in the range $2..n$, i.e. the non-composite numbers.

In [2]:
```
primes = [p for p in range(2, n + 1) if p not in composite]
```

In [3]:
```
primes[:10]
```

Out[3]:
```
[2, 3, 5, 7, 11, 13, 17, 19, 23, 29]
```

In [4]:
```
import matplotlib.pyplot as plt
import math

X = range(2, n + 1, 25000)
Y = [len([p for p in primes if p <= x]) for x in X] # slow
plt.plot(X, Y, '.g')
plt.plot(X, [x / math.log(x) for x,y in zip(X, Y)], 'r-')
plt.show()
```

Web Browser

User

cells

Prime Number Theorem - Jupy

localhost:8888/notebooks/Desktop/Prime Number Theorem.ipynb

jupyter Prime Number Theorem (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Trusted Python 3

Run Code

Prime Number Theorem

$\pi(n) =$ the number of prime numbers $\leq n$. The Prime Number Theorem states that $\pi(n) \approx \frac{n}{\ln(n)}$.
In the following we consider all primes $\leq 1.000.000$. First we computer a set 'composite' of all composite numbers in the range $2..n$.

In [1]:
```
n = 1_000_000
composite = {p for f in range(2, n + 1) for p in range(f * f, n + 1, f)}
```

We next compute select all the prime numbers in the range $2..n$, i.e. the non-composite numbers.

In [2]:
```
primes = [p for p in range(2, n + 1) if p not in composite]
```

In [3]:
```
primes[:10]
```

Out[3]:
```
[2, 3, 5, 7, 11, 13, 17, 19, 23, 29]
```

In [4]:
```
import matplotlib.pyplot as plt
import math

X = range(2, n + 1, 25000)
Y = [len([p for p in primes if p <= x]) for x in X] # slow
plt.plot(X, Y, '.g')
plt.plot(X, [x / math.log(x) for x,y in zip(X, Y)], 'r-')
plt.show()
```

formatted text: Markdown / LaTeX / HTML / ...

python code

python shell output

matplotlib / numpy / ... output

Jupyter - installing

- Open a windows shell and run: `pip install jupyter`

Jupyter – launching the jupyter server

- Open a windows shell and run: `jupyter notebook`

Command Prompt - jupyter notebook

```
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>jupyter notebook
[I 17:36:08.584 NotebookApp] Serving notebooks from local directory: C:\Users\au121
[I 17:36:08.584 NotebookApp] 0 active kernels
[I 17:36:08.584 NotebookApp] The Jupyter Notebook is running at:
[I 17:36:08.584 NotebookApp] http://localhost:8888/?token=18644cfeedab986bbdcc068f61c21b06b62
548a090169463
[I 17:36:08.584 NotebookApp] Use Control-C to stop this server and shut down all kernels (twi
ce to skip confirmation).
[C 17:36:08.584 NotebookApp]

    Copy/paste this URL into your browser when you connect for the first time,
    to login with a token:
        http://localhost:8888/?token=18644cfeedab986bbdcc068f61c21b06b62548a090169463
[I 17:36:09.154 NotebookApp] Accepting one-time-token-authenticated connection from ::1
```

url

- If this does not work, then try `python -m notebook`

Desktop/jupyter/

localhost:8888/tree/Desktop/jupyter

jupyter

Quit Logout

Files Running Clusters

Select items to perform actions on them.

Upload New

create new notebook

0 / Desktop / jupyter

Name

..

Prime Number Theorem.ipynb

Notebook:

Python 3

Other:

Text File

Folder

Terminals Unavailable

Untitled - Jupyter Notebook
localhost:8888/notebooks/Desktop/jupyter/Untitled.ipynb?kernel_name=py
title – double click to change
jupyter
Untitled (unsaved changes)
Logout
File
Edit
View
Insert
Cell
Kernel
Widgets
Help
Trusted
Python 3
type of active cell
Run
Code
In [ ]:
active cell

Try:

Help > User Interface Tour

Help > Markdown

after pressing
Ctrl + Enter (evaluates)
Alt + Enter (evaluates + new cell)

github.com/adam-p/markdown-here/wiki/Markdown-Cheatsheet

Command Mode

- Used to naviagte between cells
- Current cell is marked with blue bar
- Keyboard shortcuts

ctrl-shift-h	show keyboard shortcuts
enter	enter Edit Mode on current cell
escape	leave Edit Mode
shift-enter	run cell + select below
ctrl-enter	run selected cells
alt-enter	run cell and insert below
Y M R	change cell type (code, markdown, raw text)
1 2 3 4 5 6	change heading level
ctrl-A	select all cells
down up	move to next/previous cell
space shift-space	scroll down/up
shift-up shift-down	extend selected cells
A B	insert cell above/below
X C V shift-V Z DD	cut, copy, paste below/above, undo, delete cells
shift-L	toggle line numbers in cells
shift-M	merge selected cells (or with cell below)

Edit Mode

- Used to edit current cell
- Current cell is marked with green bar
- Keyboard shortcuts

esc	enter Command Mode
shift-enter	run cell + select below
ctrl-enter	run selected cells
alt-enter	run cell and insert below
ctrl-shift- -	split cell at cursor
tab	indent or code completion
shift-tab	show docstring
ctrl-a -x -c -v -z -y	select all, cut, copy, paste, undo, redo
ctrl-d	delete line

Evaluating cells

- To evaluate cell
  ctrl-enter, alt-enter, shift-enter
- Output from program shown below cell
- Result of last evaluated line
- Order of code cells evaluated
  Note ”x ** 2” computed after ”x = 4”
- [*] are cells being evaluated / waiting
- [ ] not yet evaluated
- Recompute all cells top-down
  ⏩ or Kernel > Restart & Run all

Magic lines

- Jupyter code cells support *magic commands* (actually it is IPython)
- % is a *line magic*
- %% is a *cell magic*

%lsmagic	list magic commands
%quickref	quick reference sheet to IPython
%pwd	print working directory (current folder)
%cd *directory*	change directory (absolut or relative)
%ls	list content of current directory
%pip *or* %conda	run pip or conda from jupyter
%load *script*	insert external script into cell
%run *program*	run external program and show output
%automagic	toggle if %-prefix is required
%matplotlib inline	no zoom & resize, allows multiple plots
%matplotlib widget	a single plot can be zoomed & resized
%%writefile *file*	write content of cell to a file
%%time	measure time for cell execution
%timeit *expression*	time for simple expression

Jupyter and matplotlib

- `%matplotlib inline`
  pyplot figures are shown *without* interactive zoom and pan (default)
- Consider changing default figure size
  `plt.rcParams['figure.figsize']`
- Start each figure with `plt.figure`
- Final call to `show` can be omitted

Jupyter and matplotlib

- `%matplotlib widget`
  pyplot figures are shown *with* interactive zoom and pan

  `pip install ipympl`

- Start each figure with `plt.figure` (also allows setting figure size)
- Final call to `show` can be omitted

- Widespread tool used for data science applications
- Documentation, code for data analysis, and resulting visualizations are stored in one common format
- Easy to update visualizations
- Works with about 100 different programming languages (not only Python 3), many special features, ...
- Easy to share data analysis
- IDEs with Notebook support: VS Code, Spyder, PyCharm
- Online Jupyter Notebook with no setup: colab.google

- *Many online tutorials and examples are available*

https://www.youtube.com/results?search_query=jupyter+python

JupyterLab: A Next-Generation Notebook Interface

File Edit View Run Kernel Tabs Settings Help

Filter files by name

/ notebooks /

Name	Last Modified
audio	2 days ago
images	2 days ago
Cpp.ipynb	2 days ago
Data.ipynb	2 days ago
Fasta.ipynb	2 days ago
Julia.ipynb	2 days ago
Lorenz.ipynb	5 minutes ago
lorenz.py	5 minutes ago
R.ipynb	2 days ago

Lorenz.ipynb | Terminal 1 | Console 1 | Data.ipynb | README.md

Markdown | Python 3 (ipykernel)

We explore the Lorenz system of differential equations:

$$\dot{x} = \sigma(y - x)$$
$$\dot{y} = \rho x - y - xz$$
$$\dot{z} = -\beta z + xy$$

Let's change (σ, β, ρ) with ipywidgets and examine the trajectories.

[2]:
```
from lorenz import solve_lorenz
interactive(solve_lorenz, sigma=(0.0,50.0), rho=(0.0,50.0))
```

Output View

sigma 10.00

beta 2.67

rho 28.00

lorenz.py

```
def solve_lorenz(sigma=10.0, beta=8./3, rho=28.0):
    """Plot a solution to the Lorenz differential equations."""
    fig = plt.figure()
    ax = fig.add_axes([0, 0, 1, 1], projection='3d')
    ax.axis('off')

    # prepare the axes limits
    ax.set_xlim((-25, 25))
    ax.set_ylim((-35, 35))
    ax.set_zlim((5, 55))

    def lorenz_deriv(x_y_z, t0, sigma=sigma, beta=beta, rho=rho):
        """Compute the time-derivative of a Lorenz system."""
        x, y, z = x_y_z
        return [sigma * (y - x), x * (rho - z) - y, x * y - beta * z]

    # Choose random starting points, uniformly distributed from -15 to 15
    np.random.seed(1)
    x0 = -15 + 30 * np.random.random((N, 3))

```

Simple 3 0 Python 3 (ipykernel) | Idle Mode: Command Ln 1, Col 1 Lorenz.ipynb

jupyter.org jupyterlab.readthedocs.io

Visualization libraries

- Altair - altair-viz.github.io
- Bokeh - bokeh.org
- Plotly - plotly.com/python
- Seaborn - seaborn.pydata.org

demo.bokeh.org/movies

scipy.optimize.minimize

- Find point p minimizing function f
- Supports 13 algorithms – but no guarantee that result is correct
- Knowledge about optimization will help you know what optimization algorithm to select and what parameters to provide for better results
- ⚠️ WARNING ⚠️
  Many solvers return the wrong value when used as a black box

pip install scipy

docs.scipy.org/doc/scipy/reference/generated/scipy.optimize.minimize.html

minimize.py

```python
from math import sin
import matplotlib.pyplot as plt
from scipy.optimize import minimize

trace = []  # remember calls to f

def f(x):
    value = x[0]**2 + 10*sin(x[0])
    trace.append((x[0], value))
    return value

X = [-8 + 18 * i / 9999 for i in range(1000)]
Y = [f([x]) for x in X]

plt.style.use('dark_background')
plt.plot(X, Y, 'w-')
for start, color in [(8, 'red'), (-6, 'yellow')]:
    trace = []

    solution = minimize(f, [start], method='nelder-mead')

    x, y = solution.x[0], solution.fun
    plt.plot(*zip(*trace), '.-', c=color, label=f'start {start:.1f}') # trace
    plt.plot(*trace[0], 'o', c=color)                                 # first trace point
    plt.text(x, -23, f'{x:.3f}', c=color, ha='center')                # show minimum x
    plt.plot([x, x], [-18, y], '--', c=color)                         # dash to minimum
plt.xticks(range(-5, 15, 5))
plt.yticks(range(-25, 100, 25))
plt.minorticks_on()
plt.legend()
plt.show()
```

Python shell

```
> print(solution)
| final_simplex: (array([[-1.3064209 ],
|   [-1.30649414]]), array([-7.94582337, -7.94582336]))
|           fun: -7.94582337348758
|       message: 'Optimization terminated successfully.'
|          nfev: 38
|           nit: 19
|        status: 0
|       success: True
|             x: array([-1.3064209])
```

minimize tries to find a local minimum for **f** by repeatedly evaluating **f** for different **x** values

Example: Minimum enclosing circle

- Find c such that $r = \max_p |p - c|$ is minimized
- A solution is characterized by either
  1) three points on circle, where the triangle contains the circle center
  2) two opposite points on diagonal
- Try a standard numeric minimization solver
- ⚠ Computation involves max and $\sqrt{x}$, which can be hard for numeric optimization solvers

Python/scipy vs MATLAB

Some basic differences

- "**end**" closes a MATLAB block
- "**;**" at end of command avoids command output
- a(i) instead a[i]
- 1st element of a list a(1)
- a(i:j) includes both a(i) and a(j)

like R, Mathematica, Julia, AWK, Smalltalk, ...

Minimum enclosing circle in MATLAB

enclosing_circle.m

```
% Minimum enclosing circle of a point set
% fminsearch uses the Nelder-Mead algorithm

global x y
x = [1.0, 3.0, 2.5, 4.0, 5.0, 6.0, 5.0];
y = [3.0, 1.0, 3.0, 6.0, 7.0, 7.0, 2.0];
c = fminsearch(@(x) max_distance(x), [0,0]);
plot(x, y, "o");
viscircles(c, max_distance(c));

function dist = max_distance(p)
    global x y
    dist = 0.0;
    for i=1:length(x)
        dist = max(dist, pdist([p; x(i), y(i)],
                                'euclidean'));
    end
end
```

Minimum enclosing circle in MATLAB (trace)

enclosing_circle_trace.m

```
global x y trace_x trace_y

x = [1.0, 3.0, 2.5, 4.0, 5.0, 6.0, 5.0];
y = [3.0, 1.0, 3.0, 6.0, 7.0, 7.0, 2.0];
trace_x = [];
trace_y = [];

c = fminsearch(@(x) max_distance(x), [0, 0]);

hold on
plot(x, y, "o", 'color', 'b', 'MarkerFaceColor', 'b');
plot(trace_x, trace_y, "*-", "color", "g");
plot(c(1), c(2), "o", 'color', 'r', 'MarkerFaceColor', 'r');
viscircles(c, max_distance(c), "color", "red");

function dist = max_distance(p)
    global x y trace_x trace_y
    trace_x = [trace_x, p(1)];
    trace_y = [trace_y, p(2)];

    dist = 0.0;
    for i=1:length(x)
        dist = max(dist, pdist([p; x(i), y(i)], 'euclidean' ));
    end
end
```

Minimum enclosing circle in Python

enclosing_circle.py

```
from scipy.optimize import minimize
import matplotlib.pyplot as plt

x = [1.0, 3.0, 2.5, 4.0, 5.0, 6.0, 5.0]
y = [3.0, 1.0, 3.0, 6.0, 7.0, 7.0, 2.0]

def dist(p, q):
    return ((p[0] - q[0]) ** 2 + (p[1] - q[1]) ** 2)) ** 0.5
def max_distance(c):
    return max([dist(p, c) for p in zip(x, y)])

c = minimize(max_distance, [0.0, 0.0], method='nelder-mead').x
ax = plt.gca()
ax.set_xlim((0, 8))
ax.set_ylim((0, 8))
ax.set_aspect('equal')
plt.plot(x, y, 'g.')
ax.add_artist(plt.Circle(c, max_distance(c),
                         color='r', fill=False))
plt.show()
```

import modules

optimization method

manually set axis (force circle inside plot)

Minimum enclosing circle in Python (trace)

enclosing_circle_trace.py

```
from scipy.optimize import minimize
import matplotlib.pyplot as plt

x = [1.0, 3.0, 2.5, 4.0, 5.0, 6.0, 5.0]
y = [3.0, 1.0, 3.0, 6.0, 7.0, 7.0, 2.0]
trace = []

def dist(p, q):
    return ((p[0] - q[0]) ** 2 + (p[1] - q[1]) ** 2) ** 0.5
def max_distance(c):
    trace.append(c)
    return max([dist(p, c) for p in zip(x, y)])

c = minimize(max_distance, [0.0, 0.0],
             method='nelder-mead').x
ax = plt.gca()
ax.set_xlim((0, 8))
ax.set_ylim((0, 8))
ax.set_aspect("equal")
plt.plot(x, y, "g.")
plt.plot(*zip(*trace), 'b.-')
ax.add_artist(plt.Circle(c, max_distance(c),
                         color='r', fill=False))
plt.show()
```

Minimum enclosing circle – search space

Maximum distance to an input point

enclosing_circle_search_space.py (previous slide)

```python
from scipy.optimize import minimize
import matplotlib.pyplot as plt
import numpy as np
from mpl_toolkits.mplot3d import Axes3D

points = [(1.0, 3.0), (3.0, 1.0), (2.5, 3.0),
  (4.0, 6.0), (5.0, 7.0), (6.0, 7.0), (5.0, 2.0)]

#  Minimum enclosing circle solver

trace = []

def distance(p, q):
    return ((p[0]-q[0])**2 + (p[1]-q[1])**2)**0.5

def distance_max(q):
    dist = max([distance(p, q) for p in points])
    trace.append((*q, dist))
    return dist

solution = minimize(distance_max, [0.0, 0.0],
                    method='nelder-mead')
center = solution.x
radius = solution.fun

#  unzip point coordinates

points_x, points_y = zip(*points)
trace_x, trace_y, trace_z = zip(*trace)

#  Bounding box [x_min, x_max] x [y_min, y_max]

xs, ys = points_x + trace_x, points_y + trace_y
x_min, x_max = min(xs), max(xs)
y_min, y_max = min(ys), max(ys)
# enforce apsect ratio
x_max = max(x_max, x_min + y_max - y_min)
y_max = max(y_max, y_min + x_max - x_min)
```

```python
#  Minimum enclosing circle - 3D surface plot
#  (plot_surface requires X, Y, Z are 2D numpy.arrays)

X, Y = np.meshgrid(np.linspace(x_min, x_max, 100),
                   np.linspace(y_min, y_max, 100))
Z = np.zeros(X.shape)
for px, py in points:
    Z = np.maximum(Z, (X - px)**2 + (Y - py)**2)
Z = np.sqrt(Z)

ax = plt.subplot(1, 2, 1, projection='3d')
ax.plot_surface(X, Y, Z, cmap='plasma', alpha=0.7)
ax.plot(trace_x, trace_y, trace_z, '.-', c='darkblue')
ax.scatter(*center, radius, 'o', c='red')
ax.set_xlabel('x')
ax.set_ylabel('y')
ax.set_zlabel('max distance')
ax.set_title('plot_surface')

#  Minimum enclosing circle - contour plot

plt.subplot(1, 2, 2)
plt.title('pyplot.contour')
plt.plot(trace_x, trace_y, '.-', color='darkblue')
plt.plot(points_x, points_y, 'o', color='darkgreen')
plt.plot(*center, 'o', c='red')
qcs = plt.contour(X, Y, Z, levels=30, cmap='plasma')
plt.clabel(qcs, inline=1, fontsize=8, fmt='%.1f')

plt.suptitle('Maximum distance to an input point')
plt.tight_layout()
plt.show()
```

numpy arrays

scipy.minimize $f(\boldsymbol{c}) = \max_{\boldsymbol{p}} |\boldsymbol{p} - \boldsymbol{c}|$

docs.scipy.org/doc/scipy/reference/generated/scipy.optimize.minimize.html

scipy.minimize $f(c) = \max_p |p - c|^2$

avoids $\sqrt{}$

Multi-dimensional data

- NumPy
- matrix multiplication, @
- numpy.linalg.solve, numpy.polyfit

Array programming with NumPy
Harris et al.
Nature, volume 585, pages 357–362, 2020
DOI 10.1038/s41586-020-2649-2

NumPy

- NumPy is a Python package for dealing with multi-dimensional data

www.numpy.org

docs.scipy.org/doc/numpy/user/quickstart.html

pylab ?

- Guttag [2nd edition] uses pylab in the examples, but...

> *"pylab is a convenience module that bulk imports matplotlib.pyplot (for plotting) and numpy (for mathematics and working with arrays) in a single name space. Although many examples use pylab, it is no longer recommended."*

matplotlib.org/faq/usage_faq.html

NumPy arrays (example)

Python shell

```
> range(0, 1, .3)
| TypeError: 'float' object cannot be
  interpreted as an integer
> [1 + i / 4 for i in range(5)]
| [1.0, 1.25, 1.5, 1.75, 2.0]
```

python only supports ranges of int

generate 5 uniform values in range [1,2]

Python shell

```
> import numpy as np
> np.arange(0, 1, 0.3)
| array([0. , 0.3, 0.6, 0.9])
> type(np.arange(0, 1, 0.3))
| <class 'numpy.ndarray'>
> help(numpy.ndarray)
| +2000 lines of text
> np.linspace(1, 2, 5)
| array([1.  , 1.25, 1.5 , 1.75, 2.  ])
```

numpy can generate ranges with float

returns a ”NumPy array” (not a list)

”arange” ≡ ”array range” and generates the array explicitly

generate n uniformly spaced values

Plotting a function (example)

sin.py

```
import matplotlib.pyplot as plt
import math
n = 25
x = [2 * math.pi * i / (n - 1) for i in range(n)]
y = [math.sin(v) for v in x]
plt.plot(x, y, '.')
plt.show()
```

sin_numpy.py

```
import matplotlib.pyplot as plt
import numpy as np
x = np.linspace(0, 2 * np.pi, 25)
y = np.sin(x)
plt.plot(x, y, '.')
plt.show()
```

- `np.sin` applies the `sin` function *to each* element of `x`
- `pyplot` accepts NumPy arrays
- `math.pi == np.pi` $\approx \frac{22}{7}$

A circle

circle.py

```
import matplotlib.pyplot as plt
import numpy as np

a = np.linspace(0, 2 * np.pi, 100)
x = np.sin(a)
y = np.cos(a)

plt.plot(x, y, 'r.-')
plt.plot(x[0], y[0], 'bo')
plt.show()
```

Two half circles

half_circles.py

```
import matplotlib.pyplot as plt
import numpy as np

x = np.linspace(-1, 1, 100)
plt.plot(x, np.sqrt(1 - x ** 2), 'r.-')
plt.plot(x, -np.sqrt(1 - x ** 2), 'b.-')
plt.show()
```

compact expression computing something quite comlicated

- `x` is a NumPy array
- `**` NumPy method `__pow__` squaring each element in `x`
- binary – NumPy method `__rsub__` that for each element e in `x` computes 1 - e
- `np.sqrt` NumPy method computing the square root of each element in `x`
- unary – NumPy method `__neg__` that negates each element in `x`

Creating one-dimensional NumPy arrays

Python shell

```
> np.array([1, 2, 3])
| array([1, 2, 3])
> np.array((1, 2, 3))
| array([1, 2, 3])
> np.array(range(1, 4))
| array([1, 2, 3])
> np.arange(1., 4., 1.)
| array([1., 2., 3.])
> np.linspace(1, 3, 3)
| array([1., 2., 3.])
> np.zeros(3)
| array([0., 0., 0.])
> np.ones(3)
| array([1., 1., 1.])
> np.full(3, 7)
| array([7, 7, 7])
> np.random.random(3)
| array([0.73761651,
  0.60607355, 0.3614118 ])
```

```
> np.array([1, 2, 3]).dtype    # type of all values
| dtype('int32')
> np.arange(3, dtype='float')
| array([0., 1., 2.])
> np.arange(3, dtype='int16')   # 16 bit integers
| array([0, 1, 2], dtype=int16)
> np.arange(3, dtype='int32')   # 32 bit integers
| array([0, 1, 2])
> 1000 ** np.arange(5)
| array([1, 1000, 1000000, 1000000000, -727379968],
  dtype=int32)    # OOPS.. overflow
> 1000 ** np.arange(5, dtype='O')
| array([1, 1000, 1000000, 1000000000,
  1000000000000], dtype=object)   # Python integer
> np.arange(3, dtype='complex')
| array([0.+0.j, 1.+0.j, 2.+0.j])
```

slow

Elements of a NumPy array are not arbitrary precision integers by default – you can select between +25 number representations

https://numpy.org/doc/stable/reference/arrays.scalars.html

Supported dtypes

- The supported dtypes is platform dependent

Python shell

```
> import numpy as np
> list(np.sctypeDict)
| ['bool', 'float16', 'float32', 'float64', 'longdouble', 'complex64',
  'complex128', 'clongdouble', 'bytes_', 'str_', 'void', 'object_',
  'datetime64', 'timedelta64', 'int8', 'byte', 'uint8', 'ubyte', 'int16',
  'short', 'uint16', 'ushort', 'intc', 'uintc', 'int32', 'long', 'uint32',
  'ulong', 'int64', 'longlong', 'uint64', 'ulonglong', 'intp', 'uintp',
  'double', 'cdouble', 'single', 'csingle', 'half', 'bool_', 'int_', 'uint',
  'float', 'complex', 'object', 'bytes', 'a', 'int', 'str', 'unicode']
```

https://numpy.org/doc/stable/reference/arrays.scalars.html

Mantissa size in various numpy floats

Python shell

```
> for data_type in ['half', 'float', 'single', 'double', 'longdouble', 'float32', 'float64']:
    x = np.array([1], dtype=data_type)
    for i in range(100):
      if x == x + (x / 2) ** i:
        break
    print(data_type, i - 1, 'bits mantissa')
| half 10 bits mantissa
| float 52 bits mantissa
| single 23 bits mantissa
| double 52 bits mantissa
| longdouble 52 bits mantissa
| float32 23 bits mantissa              # platform independent
| float64 52 bits mantissa              # platform independent
```

$$1.\overbrace{\underbrace{0000}_{i}100000}^{\text{mantissa}}{}_2$$

docs.scipy.org/doc/numpy-1.13.0/user/basics.types.html

Creating multi-dimensional NumPy arrays

Python shell

```
> np.array([[1, 2, 3], [4, 5, 6]])
| array([[1, 2, 3],
|        [4, 5, 6]])
> np.array([[1, 2], [4, 5, 6]])
| ValueError: inhomogeneous shape
> np.arange(1, 7).reshape(2, 3)
| array([[1, 2, 3],
|        [4, 5, 6]])
> x = np.arange(12).reshape(2, 2, 3)
> x
| array([[[ 0,  1,  2],
|         [ 3,  4,  5]],
|
|        [[ 6,  7,  8],
|         [ 9, 10, 11]]])
> numpy.zeros((2, 5), dtype='int32')
| array([[0, 0, 0, 0, 0],
|        [0, 0, 0, 0, 0]])
```

```
> x.size
| 12
> x.ndim
| 3
> x.shape
| (2, 2, 3)
> x.dtype
| dtype('int32')
> x.flatten()
| array([0,1,2,3,4,5,6,7,8,9,10,11])
> list(x.flat)  # flat is an iterator
| [0,1,2,3,4,5,6,7,8,9,10,11]
> np.eye(3)     # diagonal 2D array
| array([[1., 0., 0.],
|        [0., 1., 0.],
|        [0., 0., 1.]])
```

View vs Copy

- Numpy is optimized to handle big multi-dimensional arrays
- To *avoid copying* data, **views** allows one to look at the underlying data in different ways (data can be shared by multiple views)
- `reshape`, `ravel` and slicing are examples creating views
- `flatten` and `ravel` both turn multiple dimensional arrays into one dimensional arrays but `flatten` creates an explicit copy whereas `ravel` creates a space efficient view

Python shell

```
> x = np.arange(6)
> y = x.reshape(2, 3)   # view
> y[0][0] = 42          # updates x
> x
| array([42, 1, 2, 3, 4, 5])
> y
| array([[42, 1, 2],
|        [ 3, 4, 5]])
> z = y.flatten()       # copy
> z[5] = 0
> z
| array([42, 1, 2, 3, 4, 0])
> x
| array([42, 1, 2, 3, 4, 5])
> w = y.ravel()         # view
> w[5] = -1
> w
| array([42, 1, 2, 3, 4, -1])
> x
| array([42, 1, 2, 3, 4, -1])
```

NumPy operations

Python shell

```
> x = numpy.arange(3)
> x
| array([0, 1, 2])
> x + x  # elementwise addition
| array([0, 2, 4])
> 1 + x  # add integer to each element
| array([1, 2, 3])
> x * x  # elementwise multiplication
| array([0, 1, 4])
> np.dot(x, x)  # dot product
| 5
> np.cross([1, 2, 3], [3, 2, 1]) # cross product
| array([-4,  8, -4])
```

```
> a = np.arange(6).reshape(2,3)
> a
| array([[0, 1, 2],
|        [3, 4, 5]])
> a.T  # matrix transposition, view
| array([[0, 3],
|        [1, 4],
|        [2, 5]])
> a @ a.T  # matrix multiplication
| array([[ 5, 14],
|        [14, 50]])
> a += 1  # modifies view
> a
| array([[1, 2, 3],
|        [4, 5, 6]])
```

PEP 465 - A dedicated infix operator for matrix multiplication

Universal functions (apply to each entry)

Python shell

```
> x = np.array([[1, 2], [3, 4]])
> np.sin(x)  # also: cos, exp, sqrt, log, ceil, floor, abs
| array([[ 0.84147098,  0.90929743],
|        [ 0.14112001, -0.7568025 ]])
> np.sign(np.sin(x))
| array([[ 1.,  1.],
|        [ 1., -1.]])
> np.mod(np.arange(10), 3)  # same as: np.arange(10) % 3
| array([0, 1, 2, 0, 1, 2, 0, 1, 2, 0], dtype=int32)
```

Axis

Python shell

```
> x = np.arange(1, 7).reshape(2, 3)
> x
| array([[1, 2, 3],
|        [4, 5, 6]])
> x.sum()  # = x.sum(axis=(0, 1))
| 21
> x.sum(axis=0)
| array([5, 7, 9])
> x.sum(axis=1)
| array([6, 15])
> x.min()  # = x.min(axis=(0, 1))
| 1
```

Python shell

```
> x.min(axis=0)
| array([1, 2, 3])
> x.min(axis=1)
| array([1, 4])
> x.cumsum()
| array([ 1,  3,  6, 10, 15, 21], dtype=int32)
> x.cumsum(axis=0)
| array([[1, 2, 3],
|        [5, 7, 9]], dtype=int32)
> x.cumsum(axis=1)
| array([[ 1,  3,  6],
|        [ 4,  9, 15]], dtype=int32)
```

Slicing

Python shell

```
> x = numpy.arange(20).reshape(4, 5)
> x
| array([[ 0,  1,  2,  3,  4],
|        [ 5,  6,  7,  8,  9],
|        [10, 11, 12, 13, 14],
|        [15, 16, 17, 18, 19]])
> x[2, 3]  # =  x[(2, 3)]
| 13
> x[1:4:2, 2:4:1]  # rows 1 and 3, and columns 2 and 3, view
| array([[ 7,  8],
|        [17, 18]])
> x[:, 3]
| array([ 3,  8, 13, 18])
> x[..., 3]  # ... is placeholder for ':' for all missing dimensions
| array([ 3,  8, 13, 18])
> type(...)
| <class 'ellipsis'>
```

Broadcasting (stretching arrays to get same size)

- Numpy tries to apply *broadcasting*, if array shapes do not match, i.e. adds missing leading dimensions and repeats a dimension with only one element:

```
  [[1],[2]] + [10,20]        column + row vector
≡ [[1],[2]] + [[10,20]]      both ndim = 2
≡ [[1,1],[2,2]] + [[10,20]]
≡ [[1,1],[2,2]] + [[10,20],[10,20]]
≡ [[11,21],[12,22]]
```

- To prevent unexpected broadcasting, add an assertion to your program:

```
assert x.shape == y.shape
```

docs.scipy.org/doc/numpy/user/basics.broadcasting.html

Python shell

```
> x = np.array([[1, 2, 3], [4, 5, 6]])
> y = np.array([1, 2, 3])  # one row
> z = np.array([[1], [2]]) # one column
> x + 3  # add 3 to each entry
| array([[4, 5, 6],
|        [7, 8, 9]])
> x + y  # add y to each row
| array([[2, 4, 6],
|        [5, 7, 9]])
> x + z  # add z to each column
| array([[2, 3, 4],
|        [6, 7, 8]])
> y + z  # 2 rows with y + 3 columns with z
| array([[2, 3, 4],
|        [3, 4, 5]])
> z == z.T  # [[1,1],[2,2]] == [[1,2],[1,2]]
| array([[ True, False],
|        [False,  True]])
```

Masking

Python shell

```
> x = np.arange(1, 11).reshape(2, 5)
> x
| array([[ 1,  2,  3,  4,  5],
|        [ 6,  7,  8,  9, 10]])
> x % 3
| array([[1, 2, 0, 1, 2],
|        [0, 1, 2, 0, 1]], dtype=int32)
> x % 3 == 0
| array([[False, False,  True, False, False],
|        [ True, False, False,  True, False]])
> x[x % 3 == 0]  # use Boolean matrix to select entries
| array([3, 6, 9])
> x[:, x.sum(axis=0) % 3 == 0]  # columns with sum divisible by 3
| array([[ 2,  5],
|        [ 7, 10]])
```

Numpy is fast... but be aware of dtype ⚠

Python shell

```
> sum([x**2 for x in range(1000000)])
| 333332833333500000
> (np.arange(1000000)**2).sum()
| 584144992   # wrong since overflow when default dtype='int32'
> (np.arange(1000000, dtype='int64')**2).sum()
| 333332833333500000  # 64 bit integers do not overflow

> import timeit from timeit
> timeit('sum([x**2 for x in range(1000000)])', number=1)
| 0.5614346340007614
> timeit('(np.arange(1000000)**2).sum()', setup='import numpy as np', number=1)
| 0.014362967000124627  # ridiculous fast but also wrong result...
> timeit('(np.arange(1000000, dtype='int64')**2).sum()',
  setup='import numpy as np', number=1)
| 0.048017077999247704  # fast and correct

> np.iinfo(np.int32).min
| -2147483648
> np.iinfo(np.int32).max
| 2147483647
```

results using a 32-bit Python installation

numpy.int32 – 32 bit signed two's-complement integers

32 bits $b_{31}b_{30}b_{29}b_{28}\cdots b_2b_1b_0$
represent the value

$$-b_{31}\cdot 2^{31}+\sum_{i=0}^{30} b_i\cdot 2^i$$

10000000000000000000000000000000	-2147483648
10000000000000000000000000000001	-2147483647
⋮	
11111111111111111111111111111110	-2
11111111111111111111111111111111	-1
00000000000000000000000000000000	0
00000000000000000000000000000001	1
00000000000000000000000000000010	2
⋮	
01111111111111111111111111111110	2147483646
01111111111111111111111111111111	2147483647

Note: There is one more negative number than positive

Python shell

```
> np.int32(- 2 ** 31)
| -2147483648
> np.int32(- 2 ** 31) + 1
| -2147483647
> np.int32(- 2 ** 31) - 1
| 2147483647
> np.int32(2 ** 31)
| OverflowError: Python int too
  large to convert to C long
> np.int32(2 ** 31 - 1)
| 2147483647
> np.int32(2 ** 31 - 1) + 1
| -2147483648
> np.abs(np.int32(-2147483647))
| 2147483647
> np.abs(np.int32(-2147483648))
| -2147483648
```

numpy.org/doc/stable/user/basics.types.html
en.wikipedia.org/wiki/Two's_complement

docs.scipy.org/doc/numpy/reference/routines.linalg.html

Linear algebra

numpy.matrix

"It is no longer recommended to use this class, even for linear algebra. Instead use regular arrays. The class may be removed in the future."

Python shell

```
> x = np.arange(1, 5, dtype=float).reshape(2, 2)
> x
| array([[1., 2.],
|        [3., 4.]])
> x.T  # matrix transpose
| array([[1., 3.],
|        [2., 4.]])
> np.linalg.det(x)  # matrix determinant
| -2.0000000000000004
> np.linalg.inv(x)  # matrix inverse
| array([[-2. ,  1. ],
|        [ 1.5, -0.5]])
> np.linalg.eig(x)  # eigenvalues and eigenvectors
| (array([-0.37228132,  5.37228132]),
   array([[-0.82456484, -0.41597356], [0.56576746, -0.90937671]]))
> y = np.array([[5.], [7.]])
> np.linalg.solve(x, y)  # solve linear matrix equations
| array([[-3.],   # z1
|        [ 4.]])  # z2
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix} \begin{pmatrix} z_1 \\ z_2 \end{pmatrix} = \begin{pmatrix} 5 \\ 7 \end{pmatrix}$$

Singular value decomposition, `np.linalg.svd`

- U and V unitary matrix ($UU^T = I$)
- S diagonal matrix, decreasing singular values

np.ndarray shape=(520, 800) dtype=uint8 min=0 max=252

image-reconstruction.py

```
import numpy as np
import cv2  # Computer Vision, opencv.org
import matplotlib.pyplot as plt

color = cv2.imread('university.jpg')              # color image
gray = cv2.cvtColor(color, cv2.COLOR_BGR2GRAY)   # convert to gray

u, s, v = np.linalg.svd(gray)  # Calculating the SVD

for i, r in enumerate([1, 5, 10, 15, 20, 50, 100, 150], start=1):
    rank_r = u[:, :r] @ np.diag(s[:r]) @ v[:r, :]
    plt.subplot(3, 3, i)
    plt.imshow(rank_r, cmap='gray', vmin=0, vmax=255)
    plt.title(f'{r} components')
    plt.axis('off')
plt.subplot(3, 3, 9)
plt.imshow(gray, cmap='gray')
plt.title(f'Original image {gray.shape[0]} x {gray.shape[1]}')
plt.show()
```

… and in color

image-reconstruction-color.py

```
import numpy as np
import matplotlib.pyplot as plt
from matplotlib.image import imread

color = imread('university.jpg')
color = color / 255  # convert integers 0..255 to floats 0..1

plt.subplot(4, 2, 8)
plt.imshow(color)
plt.axis('off')
plt.title(f'Original')

height, width, colors = color.shape

u, s, v = np.linalg.svd(color.reshape((height, width * colors)),
                        full_matrices=False)

for i, r in enumerate([1, 2, 5, 10, 25, 50, 125], start=1):
    rank_r = u[:, :r] @ np.diag(s[:r]) @ v[:r, :]
    plt.subplot(4, 2, i)
    plt.imshow(rank_r.reshape((height, width, colors)))
    plt.title(f'{r} components')
    plt.axis('off')
plt.show()
```

shape=(520, 800, 3)
3 = (red, blue, green)

shape=(520, 2400)

shape=(520, 800, 3)

v shape=(520, 2400)
instead of (2400, 2400)

… and in color (stacked)

image-reconstruction-color-stacked.py

```
import numpy as np
import matplotlib.pyplot as plt
from matplotlib.image import imread

color = imread('university.jpg')
color = color / 255  # convert integers 0..255 to floats 0..1

plt.subplot(4, 2, 8)
plt.imshow(color)
plt.axis('off')
plt.title(f'Original')

u, s, v = np.linalg.svd(color.transpose(2, 0, 1), full_matrices=False)

print(f'{u.shape=} {s.shape=} {v.shape=}')

for i, r in enumerate([1, 2, 5, 10, 25, 50, 125], start=1):
    rank_r = (u[:, :, :r] * s[:, None, :r]) @ v[:, :r, :]
    plt.subplot(4, 2, i)
    plt.imshow(rank_r.transpose(1, 2, 0))
    plt.title(f'{r} components')
    plt.axis('off')
plt.show()
```

shape = (520, 800, 3)

shape = (3, 520, 800)

element-wise multiplication (*), broadcasting (None), stacked for each color (:)

shape = (520, 800, 3)

Python shell

```
| u.shape=(3, 520, 520) s.shape=(3, 520) v.shape=(3, 520, 800)
```

matplotlib.image.imread

cv2.imread

cv2.imread corrected

color-image.py

```
import matplotlib.pyplot as plt
import matplotlib.image
import cv2

img1 = matplotlib.image.imread('university.jpg')
img2 = cv2.imread('university.jpg')  # cv2 uses BGR instead of RGB
img3 = img2[:, :, ::-1]              # change color order BGR to RGB

Images = [(img1, 'matplotlib.image.imread'), (img2, 'cv2.imread'), (img3, 'cv2.imread corrected')]

for i, (img, title) in enumerate(images, start=1):
    plt.subplot(1, 3, i)
    plt.imshow(img)
    plt.axis('off')
    plt.title(title)

plt.show()
```

numpy.polyfit

- Given n points with $(x_0, y_0), \ldots, (x_{n-1}, y_{n-1})$
- Find polynomial p of degree d that minimizes

$$\sum_{i=0}^{n-1} (y_i - p(x_i))^2$$

- known as least squares fit / linear regression / polynomial regression

docs.scipy.org/doc/numpy/reference/generated/numpy.polyfit.html

fit.py

```
import matplotlib.pyplot as plt
import numpy as np

x = [0, 2, 3, 5, 6, 7, 8]
y = [-2, 4, 3, 2, 4, 9, 12]

coefficients = np.polyfit(x, y, 3)

fx = np.linspace(-1, 9, 100)
fy = np.polyval(coefficients, fx)

plt.plot(fx, fy, '-')
plt.plot(x, y, 'ro')

plt.show()
```

degree

Least squares polynomial fit
degree 1
degree 2
degree 5
degree 10
average
14
12
10
8
6
4
2
0
−2
−1
0
1
2
3
4

polyfit.py

```
import matplotlib.pyplot as plt
import numpy as np

x = 3 * np.random.random(25)
noise = np.random.random(x.size) ** 2
y = 5 * x ** 2 - 12 * x + 7 + 5 * noise

for degree in [1, 2, 5, 10]:
    coefficients = np.polyfit(x, y, degree)
    fx = np.linspace(-1, 4, 100)
    fy = np.polyval(coefficients, fx)
    plt.plot(fx, fy, '-', label=f'degree {degree}')

avg = np.average(y)
plt.plot(x, y, 'ro')
plt.plot([-1, 4], [avg, avg], 'k-', label='average')
plt.ylim(-3, 15)
plt.title('Least squares polynomial fit')
plt.legend()
plt.show()
```

Animating bouncing balls

- matplotlib figures can be animated using

  `matplotlib.animation.FuncAnimation`

  that as arguments takes the figure to be updated/ redrawn, a function to call for each update, and an interval in milliseconds between updates

balls.py

```
import matplotlib.pyplot as plt
from matplotlib.animation import FuncAnimation
from numpy import zeros, maximum, minimum
from numpy.random import random

g = 0.01
N = 10
x, y = 10.0 * random(N), 1.0 + 9.0 * random(N)
dx, dy = random(N) / 5, zeros(N)

fig = plt.figure()
plt.xlim(0, 10)
plt.ylim(0, 10)
balls, = plt.plot(x, y, 'o') # returns Line2D obj

def move(frame):
    global x, y, dx, dy

    x += dx
    bounce = (x > 10.0) | (x < 0.0) # numpy mask
    dx[bounce] = -dx[bounce]
    x = minimum(10.0, maximum(0.0, x))

    y += dy
    bounce = y < 0.0  # numpy mask
    y[bounce] -= dy[bounce]
    dy[bounce] = -dy[bounce]
    dy -= g

    balls.set_data(x, y)  # update positions

# removing 'ani =' causes program to fail...
ani = FuncAnimation(fig, move, interval=25)
plt.show()
```

0
50
100
150
200
250
300
350
0
50
100
150
200
250
300
350

mandelbrot.py

```
import numpy as np
import matplotlib.pyplot as plt

def mandelbrot(h, w, maxit=20):
    '''Returns an image of the Mandelbrot fractal of size (h, w).'''
    x = np.linspace(-2.0, 0.8, w).reshape(1, w)    # row vector
    y = np.linspace(-1.4, 1.4, h).reshape(h, 1)    # column vector
    c = x + y * 1j                                 # broadcast & complex
    z = c
    divtime = np.full(z.shape, maxit, dtype=int)   # all values = maxit

    for i in range(maxit):
        z = z * z + c                              # elementwise
        diverge = z * np.conj(z) > 4               # who is diverging
        div_now = diverge & (divtime == maxit)     # who is diverging now
        divtime[div_now] = i                       # note when
        z[diverge] = 0                             # limit divergence
    return divtime                                 #   (avoids overflows)

plt.imshow(mandelbrot(400, 400))
plt.show()
```

code from docs.scipy.org/doc/numpy/user/quickstart.html

Linear programming

- Example Numpy: PageRank
- scipy.optimize.linprog
- Example linear programming: Maximum flow

PageRank

PageRank - A NumPy / Jupyter / matplotlib example

- Google's original search engine ranked webpages using PageRank
- View the internet as a graph where nodes correspond to webpages and directed edges to links from one webpage to another webpage
- Google's PageRank algorithm was described in (infolab.stanford.edu/pub/papers/google.pdf, 1998)

The Anatomy of a Large-Scale Hypertextual Web Search Engine

Sergey Brin and Lawrence Page

Computer Science Department,
Stanford University, Stanford, CA 94305, USA
sergey@cs.stanford.edu and page@cs.stanford.edu

Five different ways to compute PageRank probabilities

1) Simulate random process manually by rolling dices
2) Simulate random process in Python
3) Computing probabilities using matrix multiplication
4) Repeated matrix squaring
5) Eigenvector for $\lambda = 1$

Random surfer model (simplified)

The PageRank of a node (web page) is the fraction of the time one visits a node by performing an *infinite random traversal* of the graph starting at node 1, and in each step

- with probability 1/6 jumps to a random page (probability 1/6 for each node)
- with probability 5/6 follows an outgoing edge to an adjacent node (selected uniformly)

The above can be simulated by using a dice: Roll a *dice*. If it shows 6, jump to a random page by rolling the dice again to figure out which node to jump to. If the dice shows 1-5, follow an outgoing edge - if two outgoing edges roll the dice again and go to the lower number neighbor if it is odd.

Adjacency matrix and degree vector

pagerank.ipynb

```
import numpy as np

# Adjacency matrix of the directed graph in the figure
# (note that the rows/colums are 0-indexed, whereas in the figure the nodes are 1-indexed)

G = np.array([[0, 1, 0, 0, 0, 0],
              [0, 0, 0, 1, 0, 0],
              [1, 1, 0, 0, 0, 0],
              [0, 1, 0, 0, 1, 0],
              [0, 1, 0, 0, 0, 1],
              [0, 1, 0, 0, 0, 0]])

n = G.shape[0]  # number of rows in G
degree = np.sum(G, axis=1, keepdims=True)  # column vector with row sums = out-degrees

# The below code handles sinks, i.e. nodes with outdegree zero (no effect on the graph above)

G = G + (degree == 0)  # add edges from sinks to all nodes (uses broadcasting)
degree = np.sum(G, axis=1, keepdims=True)
```

Simulate random walk (random surfer model)

pagerank.ipynb

```
from random import randint, choice

STEPS = 1000000

# adjacency_list[i] is a list of all j where (i, j) is an edge of the graph.
adjacency_list = [[j for j, e in enumerate(row) if e] for row in G]

count = np.zeros(n)          # histogram over number of node visits
state = 0                    # start at node with index 0
for _ in range(STEPS):
    count[state] += 1        # increment count for state
    if randint(1, 6) == 6:   # original paper uses 15% instead of 1/6
        state = randint(0, 5)
    else:
        state = choice(adjacency_list[state])

print(adjacency_list, count / STEPS, sep='\n')
```

Python shell

```
| [[1], [3], [0, 1], [1, 4], [1, 5], [1]]
  [0.039365 0.353211 0.02751  0.322593 0.1623   0.095021]
```

Simulate random walk (random surfer model)

pagerank.ipynb

```
import matplotlib.pyplot as plt
plt.bar(range(6), count)
plt.title('Random Walk')
plt.xlabel('node')
plt.ylabel('number of visits')
plt.show()
```

Transition matrix *A*

pagerank.ipynb

```
A = G / degree   # Normalize row sums to one. Note that 'degree'
                 # is an n x 1 matrix, whereas G is an n x n matrix.
                 # The elementwise division is repeated for each column of G
print(A)
```

Python shell

```
[[0.   1.   0.   0.   0.   0. ]
 [0.   0.   0.   1.   0.   0. ]
 [0.5  0.5  0.   0.   0.   0. ]
 [0.   0.5  0.   0.   0.5  0. ]
 [0.   0.5  0.   0.   0.   0.5]
 [0.   1.   0.   0.   0.   0. ]]
```

Repeated matrix multiplication

We now want to compute the probability $p^{(i)}_j$ to be in vertex j after i steps. Let $p^{(i)} = (p^{(i)}_0, \dots, p^{(i)}_{n-1})$.

Initially we have $p^{(0)} = (1, 0, \dots, 0)$.

We compute a matrix M, such that $p^{(i)} = M^i \cdot p^{(0)}$ (assuming $p^{(0)}$ is a column vector).

If we let $\mathbf{1}_n$ denote the $n \times n$ matrix with 1 in each entry, then M can be computed as:

$$p_j^{(i+1)} = \frac{1}{6} \cdot \frac{1}{n} + \frac{5}{6} \sum_k p_k^{(i)} \cdot A_{k,j}$$

$$p^{(i+1)} = \underbrace{\left(\frac{1}{6} \cdot \frac{1}{n} \mathbf{1}_n + \frac{5}{6} A^{\mathsf{T}} \right)}_{M} \cdot p^{(i)}$$

pagerank.ipynb

```
ITERATIONS = 20
p_0 = np.zeros((n, 1))
p_0[0, 0] = 1.0
M = 1 / (6 * n) + 5 / 6 * A.T
p = p_0
prob = p   # 'prob' will contain each
           # computed 'p' as a new column
for _ in range(ITERATIONS):
    p = M @ p
    prob = np.append(prob, p, axis=1)
print(p)
```

Python shell

```
[[0.03935185]
 [0.35326184]
 [0.02777778]
 [0.32230071]
 [0.16198059]
 [0.09532722]]
```

Rate of convergence

pagerank.ipynb

```
x = range(ITERATIONS + 1)
for node in range(n):
    plt.plot(x, prob[node], label=f'node {node}')
plt.xticks(x)
plt.title('Random Surfer Probabilities')
plt.xlabel('Iterations')
plt.ylabel('Probability')
plt.legend()
plt.show()
```

Repeated squaring

$$\underbrace{M\cdot(\cdots(M\cdot(M}_{k \text{ multiplications, } k \text{ power of 2}}\cdot p^{(0)}))\cdots) = M^k\cdot p^{(0)} = M^{2^{\log_2 k}}\cdot p^{(0)} = (\cdots((\overbrace{M^2)^2)^2\cdots)^2}^{\log_2 k}\cdot p^{(0)}$$

pagerank.ipynb

```
from math import log2
MP = M
for _ in range(1 + int(log2(ITERATIONS))):
    MP = MP @ MP
p = MP @ p_0
print(p)
```

Python shell

```
[[0.03935185]
 [0.35332637]
 [0.02777778]
 [0.32221711]
 [0.16203446]
 [0.09529243]]
```

PageRank : Computing eigenvector for λ = 1

- We want to find a vector p, with $|p| = 1$, where $Mp = p$, i.e. an *eigenvector* p for the eigenvalue $\lambda = 1$

pagerank.ipynb

```
eigenvalues, eigenvectors = np.linalg.eig(M)

idx = eigenvalues.argmax()              # find the largest eigenvalue (= 1)
p =  np.real(eigenvectors[:, idx])      # .real returns the real part of complex numbers
p /= p.sum()                            # normalize p to have sum 1

print(p)
```

Python shell

```
| [0.03935185 0.3533267  0.02777778 0.32221669 0.16203473 0.09529225]
```

PageRank : Note on practicality

- In practice an explicit matrix for billions of nodes is infeasible, since the number of entries would be order of 10^{18}

- Instead use sparse matrices (in Python modul `scipy.sparse`) and stay with repeated multiplication

Linear programming

scipy.optimize.linprog

- scipy.optimize.linprog can solve *linear programs* of the following form, where one wants to find an n x 1 vector x satisfying:

Minimize: $c^T \cdot x$

Subject to: $A_{ub} \cdot x \leq b_{ub}$
$A_{eq} \cdot x = b_{eq}$

dimension

$c : n \times 1$

$A_{ub} : m \times n$ $\quad b_{ub} : m \times 1$

$A_{eq} : k \times n$ $\quad b_{eq} : k \times 1$

Some other open-source optimization libraries PuLP and Pyomo

For industrial strength linear solvers, use solvers like Cplex or Gurobi (mixed-integer linear programs)

Linear programming example

Maximize

$3 \cdot x_1 + 2 \cdot x_2$

Subject to

$2 \cdot x_1 + 1 \cdot x_2 \leq 10$

$5 \cdot x_1 + 6 \cdot x_2 \geq 4$

$-3 \cdot x_1 + 7 \cdot x_2 = 8$

$\Updownarrow$

Minimize

$-(3 \cdot x_1 + 2 \cdot x_2)$

Subject to

$2 \cdot x_1 + 1 \cdot x_2 \leq 10$

$-5 \cdot x_1 + -6 \cdot x_2 \leq -4$

$-3 \cdot x_1 + 7 \cdot x_2 = 8$

linear_programming.py

```
import numpy as np
from scipy.optimize import linprog
c = np.array([3, 2])
A_ub = np.array([[ 2,  1],
                 [-5, -6]])  # multiplied by -1
b_ub = np.array([10, -4])
A_eq = np.array([[-3, 7]])
b_eq = np.array([8])
res = linprog(-c,  # maximize = minimize the negated
              A_ub=A_ub,
              b_ub=b_ub,
              A_eq=A_eq,
              b_eq=b_eq)
print(res)  # res.x is the optimal vector
```

Python shell

```
  fun: -16.35294117647059
  message: 'Optimization terminated successfully.'
      nit: 3
    slack: array([ 0.        , 30.47058824])
   status: 0
  success: True
        x: array([3.64705882, 2.70588235])
```

Maxmium flow

Solving maximum flow using linear programming

Maximize

$x_7 + x_8$ — flow value

Subject to

capacity constraints:

$x_0 \le 4$
$x_1 \le 3$
$x_2 \le 1$
$x_3 \le 1$
$x_4 \le 3$
$x_5 \le 1$
$x_6 \le 3$
$x_7 \le 1$
$x_8 \le 5$

flow conservation:

$x_1 = x_4 + x_5$
$x_0 = x_2 + x_3$
$x_3 + x_5 + x_6 = x_8$
$x_2 + x_4 = x_6 + x_7$

We will use the scipy.optimize.linprog function to solve the *maximum flow* problem on the above directed graph. We want to send as much *flow* from node A to node F. Edges are numbered 0..8 and each edge has a maximum *capacity*.

Note: solution not unique

Solving maximum flow using linear programming

- x is a vector describing the flow along each edge
- c is a vector to add the flow along the edges (7 and 8) to the sink (F), i.e. a function computing *the flow value*
- A_{ub} and b_{ub} is a set of *capacity constraints*, for each edge flow ≤ capacity
- A_{eq} and b_{eq} is a set of *flow conservation* constraints, for each non-source and non-sink node (B, C, D, E), requiring that the flow into equals the flow out of a node

Minimize

$\boxed{-x_7 - x_8}$ $c^T \cdot x$ flow value

Subject to

$$\left.\begin{array}{l} \boxed{\begin{array}{l} x_0 \le 4 \\ x_1 \le 3 \\ x_2 \le 1 \\ x_3 \le 1 \\ x_4 \le 3 \\ x_5 \le 1 \\ x_6 \le 3 \\ x_7 \le 1 \\ x_8 \le 5 \end{array}} \\ A_{ub} \cdot x \le b_{ub} \\ \Updownarrow \\ I \cdot x \le \text{capacity} \end{array}\right\} \text{capacity constraints}$$

$$A_{eq} \cdot x = b_{eq} = 0$$

$$\left.\boxed{\begin{array}{l} 0 = -x_1 + x_4 + x_5 \\ 0 = -x_0 + x_2 + x_3 \\ 0 = -x_3 - x_5 - x_6 + x_8 \\ 0 = -x_2 - x_4 + x_6 + x_7 \end{array}}\right\} \text{flow conservation}$$

maximum-flow.py

```python
import numpy as np
from scipy.optimize import linprog

#                              0  1  2  3  4  5  6  7  8
conservation = np.array([[ 0,-1, 0, 0, 1, 1, 0, 0, 0],  # B
                         [-1, 0, 1, 1, 0, 0, 0, 0, 0],  # C
                         [ 0, 0, 0,-1, 0,-1,-1, 0, 1],  # D
                         [ 0, 0,-1, 0,-1, 0, 1, 1, 0]]) # E

#                    0  1  2  3  4  5  6  7  8
sinks = np.array([0, 0, 0, 0, 0, 0, 0, 1, 1])

#                      0  1  2  3  4  5  6  7  8
capacity = np.array([4, 3, 1, 1, 3, 1, 3, 1, 5])

res = linprog(-sinks,
              A_eq=conservation,
              b_eq=np.zeros(conservation.shape[0]),
              A_ub=np.eye(capacity.size),
              b_ub=capacity)

print(res)
```

Python shell

```
|       fun: -5.0
   message: 'Optimization terminated successfully.'
       nit: 9
     slack: array([2., 0., 0., 0., 1., 0., 1., 0., 1.])
    status: 0
   success: True
         x: array([2., 3., 1., 1., 2., 1., 2., 1., 4.])
```

the solution found varies with the scipy version

Generators, iterators

- __iter__, __next__
- yield
- generator expression
- measuring memory usage

Iterable & Iterator

Python shell

```
> L = ['a', 'b', 'c']
> type(L)
| <class 'list'>
> it = L.__iter__()
> type(it)
| <class 'list_iterator'>
> it.__next__()
| 'a'
> it.__next__()
| 'b'
> it.__next__()
| 'c'
> it.__next__()
| StopIteration  # Exception
```

Python shell

```
> L = ['a', 'b', 'c']
> it = iter(L)   # calls L.__iter__()
> next(it)       # calls it.__next__()
| 'a'
> next(it)
| 'b'
> next(it)
| 'c'
> next(it)
| StopIteration
```

iterator ≈ pointer into list

↓

`['a', 'b', 'c']`

- Lists are iterable (must support `__iter__`)
- `iter` returns an iterator (must support `__next__`)

Some iterables in Python: string, list, set, tuple, dict, range, enumerate, zip, map, reversed

Iterator

- next(*iterator_object*) returns the next element from the iterator, by calling the *iterator_object*`.__next__()`. If no more elements to report, raises exception `StopIteration`
- next(*iterator_object*, *default*) returns *default* when no more elements are available (no exception is raised)
- for-loops and list comprehensions require iterable objects `for x in range(5):` and `[2**x for x in range(5)]`
- The iterator concept is also central to Java and C++

for loop

Python shell

```
> for x in ['a', 'b', 'c']:
      print(x)
| a
| b
| c
```

result of `next` on iterator

iterable object (can call `iter` on it to generate an iterator)

≡

Python shell

```
> L = ['a', 'b', 'c']
> it = iter(L)
> while True:
      try:
          x = next(it)
      except StopIteration:
          break
      print(x)
| a
| b
| c
```

8.3. The `for` statement

The `for` statement is used to iterate over the elements of a sequence (such as a string, tuple or list) or other iterable object:

```
for_stmt ::=  "for" target_list "in" expression_list ":" suite
              ["else" ":" suite]
```

The expression list is evaluated once; it should yield an iterable object. An iterator is created for the result of the `expression_list`. The suite is then executed once for each item provided by the iterator, in the order returned by the iterator. Each item in turn is assigned to the target list using the standard rules for assignments (see Assignment statements), and then the suite is executed. When the items are exhausted (which is immediately when the sequence is empty or an iterator raises a `StopIteration` exception), the suite in the `else` clause, if present, is executed, and the loop terminates.

docs.python.org/3/reference/compound_stmts.html#the-for-statement

`for` loop over changing iterable

Changing (extending) the list while scanning
The iterator over a list is just an index into the list

Python shell

```
> L = [1, 2]
> for x in L:
      print(x, L)
      L.append(x + 2)
| 1 [1, 2]
| 2 [1, 2, 3]
| 3 [1, 2, 3, 4]
| 4 [1, 2, 3, 4, 5]
| 5 [1, 2, 3, 4, 5, 6]
...
```

Python shell

```
> L = [1, 2]
> for x in L:
      print(x, L)
      L[:0] = [L[0] - 2, L[0] - 1]
| 1 [1,2]
| 0 [-1,0,1,2]
| -1 [-3,-2,-1,0,1,2]
| -2 [-5,-4,-3,-2,-1,0,1,2]
| -3 [-7,-6,-5,-4,-3,-2,-1,0,1,2]
...
```

range

Python shell

```
> r = range(1, 6)   # 1,2,3,4,5
> type(r)
| <class 'range'>
> it = iter(r)
> type(it)
| <class 'range_iterator'>
> next(it)
| 1
> next(it)
| 2
> for x in it:
      print(x)
| 3
| 4
| 5
> list(r)
| [1, 2, 3, 4, 5]
```

iterable expected but got iterator ?

create list from iterable

Python shell

```
> it
| <range_iterator object at 0x03E7FFC8>
> iter(it)
| <range_iterator object at 0x03E7FFC8>
> it is iter(it)
| True
```

Calling `iter` on a `range_iterator` just returns the iterator itself, i.e. can use the iterator wherever an iterable is expected

str

Python shell

```
> s = 'abcde'
> list(s)  # create list from iterable
| ['a', 'b', 'c', 'd', 'e']
> type(s)
| <class 'str'>
> it = iter(s)
> type(it)
| <class 'str_ascii_iterator'>
> next(it)
| 'a'
> next(it)
| 'b'
> list(it)  # iter(it) is it
| ['c', 'd', 'e']
```

Creating an interable class

names.py

```
class Names:
    def __init__(self, *arg):
        self.people = arg

    def __iter__(self):
        return Names_iterator(self)

class Names_iterator:
    def __init__(self, names):
        self.idx = 0
        self.names = names

    def __next__(self):
        if self.idx >= len(self.names.people):
            raise StopIteration
        self.idx += 1
        return self.names.people[self.idx - 1]

duckburg = Names('Donald', 'Goofy', 'Mickey', 'Minnie')

for name in duckburg:
    print(name)
```

Python shell

```
| Donald
| Goofy
| Mickey
| Minnie
```

An infinite iterable

infinite_range.py

```
class infinite_range:
    def __init__(self, start=0, step=1):
        self.start = start
        self.step = step

    def __iter__(self):
        return infinite_range_iterator(self)

class infinite_range_iterator:
    def __init__(self, inf_range):
        self.range = inf_range
        self.current = self.range.start

    def __next__(self):
        value = self.current
        self.current += self.range.step
        return value

    def __iter__(self):  # make iterator iterable
        return self
```

Python shell

```
> r = infinite_range(42, -3)
> it = iter(r)
> for idx, value in zip(range(5), it):
      print(idx, value)
| 0 42
| 1 39
| 2 36
| 3 33
| 4 30
> for idx, value in zip(range(5), it):
      print(idx, value)
| 0 27
| 1 24
| 2 21
| 3 18
| 4 15
> print(sum(r))  # don't do this
| (runs forever)
```

`sum` and `zip` take iterables

(`zip` stops when shortest iterable is exhausted)

Creating an iterable class (iterable = iterator)

my_range.py

```
class my_range:
    def __init__(self, start, end, step):
        self.start = start
        self.end = end
        self.step = step
        self.x = start

    def __iter__(self):
        return self  # self also iterator

    def __next__(self):
        if self.x >= self.end:
            raise StopIteration
        answer = self.x
        self.x += self.step
        return answer

r = my_range(1.5, 2.0, 0.1)
```

Python shell

```
> list(r)
| [1.5, 1.6,
  1.7000000000000002,
  1.8000000000000003,
  1.9000000000000004]
> list(r)
| []
```

- Note that object acts both as an iterable and an iterator
- This e.g. also applies to `zip` objects
- Can only iterate over a `my_range` once

The old sequence iteration protocol

This is a reminiscence from Python 1 – now rarely used

odds.__contains__ does not exist

Python shell

```
> class Odd_numbers:
      def __getitem__(self, idx):
          print('getting item', idx)
          if not 0 <= idx < 10:
              raise IndexError
          return 2 * idx + 1
> odds = Odd_numbers()
> odds[3]
> getting item 3
| 7
> it = iter(odds)
> it
| <iterator object at ...>
> print(next(it), next(it), next(it))
| getting item 0
| getting item 1
| getting item 2
| 1 3 5
```

```
> 5 in odds
| getting item 0
| getting item 1
| getting item 2
| True
> 6 in odds
| getting item 0
| getting item 1
| getting item 2
| getting item 3
| getting item 4
| getting item 5
| getting item 6
| getting item 7
| getting item 8
| getting item 9
| getting item 10
| False
```

- Class with no `__iter__` method but supporting index lookup with `__getitem__`
- Python automatically creates iterator looking up *obj*[0], *obj*[1], *obj*[2], … until IndexError raised
- Keyword `in` falls back to iteration if no method `__contains__`

https://docs.python.org/3/reference/datamodel.html#object.__contains__

itertools

Function	Description
`count(start, step)`	Inifinite sequence: `start`, `stat + step`, …
`cycle(seq)`	Infinite repeats of the elements from `seq`
`repeat(value[, times])`	Infinite repeats of `value` or `times` repeats
`chain(seq0,...,seqk)`	Concatenate sequences
`starmap(func, seq)`	`func(*seq[0]), func(*seq[1]), …`
`permutations(seq)`	Genereate all possible permutations of `seq`
`islice(seq, start, stop, step)`	Create a slice of `seq`
…	…

https://docs.python.org/3/library/itertools.html

Example : Java iterators

vector-iterator.java

```
import java.util.Vector;
import java.util.Iterator;

class IteratorTest {
   public static void main(String[] args) {
       Vector<Integer> a = new Vector<Integer>();
       a.add(7);
       a.add(42);
       // "C" for-loop & get method
       for (int i=0; i<a.size(); i++)
          System.out.println(a.get(i));
       // iterator
       for (Iterator it = a.iterator(); it.hasNext(); )
          System.out.println(it.next());
       // for-each loop - syntax sugar since Java 5
       for (Integer e : a)
          System.out.println(e);
   }
}
```

In Java iteration does not stop using exceptions, but instead the iterator can be tested if it is at the end of the iterable

Example : C++ iterators

vector-iterator.cpp

```
#include <iostream>
#include <vector>
int main() {
  // Vector is part of STL (Standard Template Library)
  std::vector<int> A = {20, 23, 26};
  // "C" indexing - since C++98
  for (int i = 0; i < A.size(); i++)
    std::cout << A[i] << std::endl;
  // iterator - since C++98
  for (std::vector<int>::iterator it = A.begin(); it != A.end(); ++it)
    std::cout << *it << std:: endl;
  // "auto" iterator - since C++11
  for (auto it = A.begin(); it != A.end(); ++it)
    std::cout << *it << std:: endl;
  // Range-based for-loop - since C++11
  for (auto e : A)
    std::cout << e << std:: endl;
}
```

In C++ iterators can be tested if they reach the end of the iterable

move iterator to next element

Generators

Generator expressions

Python shell

```
> [x ** 2 for x in range(5)]  # list comprehension
| [0, 1, 4, 9, 16]  # list
> (x ** 2 for x in range(3))  # generator expression
| <generator object <genexpr> at 0x03D9F8A0>
> o = (x ** 2 for x in range(3))
> next(o)  # use generator expression as iterator
| 0
> next(o)
| 1
> next(o)
| 4
> next(o)
| StopIteration
```

- A generator expression `(... for x in ...)` looks like a list comprehension, except square brackets are replaced by parenthesis
- Is an iterable and iterator, that uses less memory than a list comprehension
- computation is done *lazily*, i.e. first when needed

https://docs.python.org/3/reference/expressions.html#generator-expressions

Nested generator expressions

```
Python shell
> squares = (x ** 2 for x in range(1, 6))  # generator expression
> ratios = (1 / y for y in squares)  # generator expression
> ratios
| <generator object <genexpr> at 0x031FC230>
> next(ratios)
| 1.0
> next(ratios)
| 0.25
> list(ratios)
| [0.1111111111111111, 0.0625, 0.04]  # remaining 3
```

- Each fraction is first computed when requested by `next(ratios)` (implicitly called repeatedly in `list(ratios)`)
- The next value of `squares` is first computed when needed by `ratios`

Generator expressions as function arguments

Python shell

```
> doubles = (x * 2 for x in range(1, 6))
> sum(doubles)  # sum takes an iterable
| 30
> sum((x * 2 for x in range(1, 6)))
| 30
> sum(x * 2 for x in range(1, 6))  # one pair of parenthesis omitted
| 30
```

- Python allows to omit a pair of parenthesis when a generator expression is the only argument to a function

```
f(... for x in ...)   ≡   f((... for x in ...))
```

PEP 289 – Generator Expressions

Generator functions

two.py

```
def two():
    yield 1
    yield 2
```

Python shell

```
> two()
| <generator object two at 0x03629510>
> t = two()
> next(t)
| 1
> next(t)
| 2
> next(t)
| StopIteration
```

- A *generator function* contains one or more `yield` statements
- Python automatically makes a call to a generator function into an iterable and iterator (provides `__iter__` and `__next__`)
- Calling a generator function returns a *generator object*
- Whenever `next` is called on a generator object, the excuting of the function continues until the next `yield` *exp* and the value of *exp* is returned as a result of `next`
- Reaching the end of the function or a return statement, will raise `StopIteration`
- Once consumed, can't be reused

https://docs.python.org/3/reference/expressions.html#yield-expressions

Generator functions (II)

my_generator.py

```
def my_generator(n):
    yield 'Start'
    for i in range(n):
        yield chr(ord('A') + i)
    yield 'Done'
```

Python shell

```
> g = my_generator(3)
> print(g)
| <generator object my_generator at 0x03E2F6F0>
> print(list(g))
| ['Start', 'A', 'B', 'C', 'Done']
> print(list(g))  # generator object g exhausted
| []
> print(*my_generator(5))  # * takes an iterable (PEP 448)
| Start A B C D E Done
```

PEP 448 – Additional Unpacking Generalizations

Generator functions (III)

my_range_generator.py

```
def my_range(start, end, step):
    x = start
    while x < end:
        yield x
        x += step
```

Python shell

```
> list(my_range(1.5, 2.0, 0.1))
| [1.5, 1.6, 1.7000000000000002, 1.8000000000000003, 1.9000000000000004]
```

- Generator functions are often easier to write than creating an iterable class and the accompanying iterator class

Pipelining generators

Python shell

```
> def squares(seq):       # seq should be an iterable object
      for x in seq:       # use iterator to run through seq
          yield x ** 2    # generator
> list(squares(range(5)))
| [0, 1, 4, 9, 16]
> list(squares(squares(range(5))))  # pipelining generators
| [0, 1, 16, 81, 256]
> sum(squares(squares(range(100000000))))  # pipelining generators
| 19999999500000003333333333333330000000
> sum((x ** 2) ** 2 for x in range(100000000))  # generator expression
| 19999999500000003333333333333330000000
> sum([(x ** 2) ** 2 for x in range(100000000)])  # list comprehension
| MemoryError  # when using a 32-bit version of Python, limited to 2 GB
```

yield vs yield from

Python shell

```
> def g():
      yield 1
      yield [2, 3, 4]
      yield 5
> list(g())
| [1, [2, 3, 4], 5]
```

Python shell

```
> def g():
      yield 1
      yield from [2, 3, 4]
      yield 5
> list(g())
| [1, 2, 3, 4, 5]
```

- `yield from` available since Python 3.3
- `yield from` *`exp`* ≈ `for x in` *`exp`*`: yield x`

Recursive `yield from`

without **yield from**

```
for value in traverse(child):
    yield value
```

Python shell

```
> def traverse(T):  # recursive generator
      if isinstance(T, tuple):
          for child in T:
              yield from traverse(child)
      else:
          yield T
> T = (((1, 2), 3, (4, 5)), (6, (7, 9)))
> traverse(T)
| <generator object traverse at 0x03279F30>
> list(traverse(T))
| [1, 2, 3, 4, 5, 6, 7, 9]
```

docs.python.org/3/reference/expressions.html#generator.close

Generator `.close()`

random_integers.py

```
def random_integers(n):
    seen = set()  # integers generated so far
    while len(seen) < n:
        value = random.randint(1, n)
        if value in seen:
            continue  # skip dublicates
        seen.add(value)
        yield value
```

- A generator can be forced to terminate by calling `.close()`
- Technically, the generator continues with a **`GeneratorExit`** exception raised, so that it can clean up before returning
- Useful to release resources from generators, e.g., infinite generators

Python shell

```
> r = random_integers(10)
> next(r)
| 9
> next(r)
| 3
> next(r)
| 5
> r.close()
> next(r)
| StopIteration

> r = random_integers(1_000_000_000)
> next(r)
| 191907382          # memory usage ~ 10 MB
> sum(next(r) for _ in range(10_000_000))
| 4998986626629771   # memory usage ~ 550 MB
> r.close()          # memory usage ~ 10 MB
> next(r)
| StopIteration
```

releases the **`seen`** set containing 10.000.001 elements for garbage collection

Making objects iterable using `yield`

vector2D.py

```
class vector2D:
    def __init__(self, x_value, y_value):
        self.x = x_value
        self.y = y_value

    def __iter__(self):  # generator
        yield self.x
        yield self.y

    def __iter__(self):  # alternative generator
        yield from (self.x, self.y)

v = vector2D(5, 7)

print(list(v))
print(tuple(v))
print(set(v))
```

Python shell

```
| [5, 7]
| (5, 7)
| {5, 7}
```

Generators vs iterables

- Iterables can often be reused (like lists, tuples, strings)
- Generators cannot be reused (only if a new generator object is created, starting over again)

- David Beazley's tutorial on
  "*Generators: The Final Frontier*", PyCon 2014 (3:50:54)
  Throughout advanced discussion of generators, e.g. how to use `.send` method to implement coroutines
  https://www.youtube.com/watch?v=D1twn9kLmYg

Measuring memory usage

Measuring memory usage (memory profiling)

- Macro level:

  Task Manager (Windows)
  Activity Monitor (Mac)
  top (Linux)

- Variable level:

  `getsizeof` from `sys` module

- Detailed overview:

  Module `memory_profiler`

  Allows detailed space usage of the code line-by-line (using @profile function decorator) or a plot of total space usage over time

  pip install memory-profiler

Python shell

```
> import sys
> sys.getsizeof(42)
| 28  # size of the integer 42 is 28 bytes
> sys.getsizeof(42 ** 42)
| 56  # the size increases with value
> sys.getsizeof('42')
| 51  # size of a string
> import numpy as np
> sys.getsizeof(np.array(range(100), dtype='int32'))
| 512  # also works on Numpy arrays
> squares = [x ** 2 for x in range(1000000)]
> sys.getsizeof(squares)
| 8448728
> g = (x ** 2 for x in range(1000000))
> sys.getsizeof(g)
| 208
```

size values depend on the Python version, e.g., 32 vs 64 bit

Module memory-profiler

pypi.org/project/memory-profiler/

memory_usage.py

```
from memory_profiler import profile

@profile  # prints new statistics for each call
def use_memory():
    s = 0
    x = list(range(20_000_000))
    s += sum(x)
    y = list(range(10_000_000))
    s += sum(x)

use_memory()
```

Python Shell

```
| Filename: C:/.../memory_usage.py
|
| Line #   Mem usage   Increment   Line Contents
| ================================================
|      3    32.0 MiB    32.0 MiB   @profile
|      4                           def use_memory():
|      5    32.0 MiB     0.0 MiB       s = 0
|      6   415.9 MiB   383.9 MiB       x = list(range(20_000_000))
|      7   415.9 MiB     0.0 MiB       s += sum(x)
|      8   607.8 MiB   191.9 MiB       y = list(range(10_000_000))
|      9   607.8 MiB     0.0 MiB       s += sum(x)
```

memory_sin_usage.py

```
from math import sin, pi

for a in range(1000):
    x = list(range(int(1000000 * sin(pi * a / 250))))
```

Windows Shell

```
> pip install memory-profiler
> mprof run memory_sin_usage.py
| mprof: Sampling memory every 0.1s
| running as a Python program...
> mprof plot
```

xkcd.com/353

Modules and packages

- import – from – as
- __name__, '__main__'
- heapq

docs.python.org/3/tutorial/modules.html

Python modules and packages

- A Python module is a *module_name*.py file containing Python code
- A Python package is a collection of modules

Why do you need modules ?

- A way to structure code into smaller logical units
- Encapsulation of functionality
- Reuse of code in different programs

- Your can write your own modules and packages or use any of the +600.000 existing packages from pypi.org
- The Python Standard Library consists of the modules listed on docs.python.org/3/library

Defining and importing a module

mymodule.py

```
'''This is a 'print something' module.'''

from random import choice

print('Running my module')

def print_something(n):
    W = ['Eat', 'Sleep', 'Rave', 'Repeat']
    print(' '.join(choice(W) for _ in range(n)))

def the_name():
    print(f'{__name__ = }')
```

using_mymodule.py

```
import mymodule

mymodule.the_name()
mymodule.print_something(5)

from mymodule import print_something

print_something(5)
```

Python shell

```
| Running my module
| __name__ = "mymodule"
| Eat Sleep Sleep Sleep Rave
| Eat Sleep Rave Repeat Sleep
```

- A module is only run once when imported several times

Some modules mentioned in the course

Module (example functions)	Description
math (pi sqrt ceil log sin)	*basic math*
random (random randint)	*random number generator*
numpy (array shape)	*multi-dimensional data*
pandas	*data tables*
SQLlite	*SQL database*
scipy scipy.optimize (minimize linprog) scipy.spatial (ConvexHull)	*mathematical optimization*
matplotlib matplotlib.pyplot (plot show style) matplotlib.backends.backend_pdf (PdfPages) mpl_toolkits.mplot3d (Axes3D)	 *plotting data* *print plots to PDF* *3D plot tools*
doctest (testmod) unittest (assertEqual assertTrue)	*testing using doc strings* *unit testing*
time (time) datetime (date.today)	*current time, coversion of time values*
timeit (timeit)	*time execution of simple code*
heapq	*use a list as a heap*

Module (example functions)	Description
functools (cache lru_cache total_ordering)	*higher order functions and decorators*
itertools (islice permutations)	*Iterator tools*
collections (Counter deque)	*datat structures for collections*
builtins	*module containing the Python builtins*
os (path)	*operating system interface*
sys (argv path)	*system specific functions*
Tkinter PyQt	*graphic user interface*
xml	*xml files (eXtensible Markup Language)*
json	*JSON (JavaScript Object Notation) files*
csv	*comma separated files*
openpyxl	*EXCEL files*
re	*regular expression, string searching*
string (split join lower ascii_letters digits)	*string functions*

Ways of importing modules

import.py

```
# Import a module name in the current namespace
# All definitions in the module are available as <module>.<name>

import math
print(math.sqrt(2))

# Import only one or more specific definitions into current namespace

from math import sqrt, log, ceil
print(ceil(log(sqrt(100), 2)))

# Import specific modules/definitions from a module into current namespace under new names

from math import sqrt as kvadratrod, \
                 log as logaritme  # long import line broken onto multiple lines
import matplotlib.pyplot as plt
print(logaritme(kvadratrod(100)))

# Import all definitions form a module in current namespace
# Deprecated, since unclear what happens to the namespace

from math import *
print(pi)  # where did 'pi' come from?
```

Python shell

```
| 1.4142135623730951
| 4
| 2.302585092994046
| 3.141592653589793
```

__all__ vs import *

- A module can control what is imported by `import *` by defining `__all__`

Python shell

```
> min
| <built-in function min>
> sum
| <built-in function sum>
> import numpy
> numpy.min
| <function min at 0x0000024E5DAC71F0>
> numpy.sum
| <function sum at 0x0000024E5DAC5D70>
> from numpy import *
> min
| <function min at 0x0000024E5DAC71F0>
> sum
| <function sum at 0x0000024E5DAC5D70>
> numpy.__all__
| [..., 'min', ..., 'sum', ...]    # len(numpy.__all__) == 500
```

all.py

```
__all__ = ['f']
def f():
    print('this is f')
def g():
    print('this is g')
```

Python shell

```
> import all
> all.f()
| this is f
> all.g()
| this is g
> from all import *
> f()
| this is f
> g()
| NameError: name 'g' is not defined
```

Performance of different ways of importing

`from math import sqrt`

appears to be faster than

`math.sqrt`

sqrt_performance.py

```
from time import time

import math
start = time()
x = sum(math.sqrt(x) for x in range(10000000))
end = time()
print('math.sqrt', end - start)

from math import sqrt
start = time()
x = sum(sqrt(x) for x in range(10000000))
end = time()
print('from math import sqrt', end - start)

def test(sqrt=math.sqrt):  # abuse of keyword argument
    start = time()
    x = sum(sqrt(x) for x in range(10000000))
    end = time()
    print('bind sqrt to keyword argument', end - start)

test()
```

Python shell

```
| math.sqrt 4.05187726020813
| from math import sqrt 3.5011463165283203
| bind sqrt to keyword argument 3.261594772338867
```

Listing definitions in a module: dir(*module*)

Python shell

```
> import math
> import matplotlib.pyplot as plt
> dir(math)
| ['__doc__', '__loader__', '__name__', '__package__', '__spec__', 'acos',
  'acosh', 'asin', 'asinh', 'atan', 'atan2', 'atanh', 'ceil', 'copysign',
  'cos', 'cosh', 'degrees', 'e', 'erf', 'erfc', 'exp', 'expm1', 'fabs',
  'factorial', 'floor', 'fmod', 'frexp', 'fsum', 'gamma', 'gcd', 'hypot',
  'inf', 'isclose', 'isfinite', 'isinf', 'isnan', 'ldexp', 'lgamma', 'log',
  'log10', 'log1p', 'log2', 'modf', 'nan', 'pi', 'pow', 'radians', 'sin',
  'sinh', 'sqrt', 'tan', 'tanh', 'tau', 'trunc']
> help(math)
| Help on built-in module math:
| NAME
|     math
| DESCRIPTION
| ...
```

https://docs.python.org/3/library/functions.html#dir

__name__

double.py

```
'''Module double.'''

def f(x):
    '''
    Some doc test code:

    >>> f(21)
    42
    >>> f(7)
    14
    '''

    return 2 * x

print(f'{__name__ = }')

if __name__ == '__main__':
    import doctest
    doctest.testmod(verbose=True)
```

Python shell

```
| __name__ = __main__
  ...
  2 passed and 0 failed.
  Test passed.
```

using_double.py

```
import double

print(f'{__name__ = }')
print(double.f(5))
```

Python shell

```
| __name__ = 'double'
  __name__ = '__main__'
  10
```

- The variable `__name__` contains the name of the module, or `'__main__'` if the file is run as the main file by the interpreter
- Can e.g. be used to test a module if the module is run independently

module `importlib`

- Implements the `import` statement (Python internal implementation details)
- `importlib.reload(`*module*`)`
  - Reloads a previously imported *module*. Relevant if you have edited the code for the module and want to load the new version in the Python interpreter, without restarting the full program from scratch.

a_constant.py

```
the_constant = 7
```

Python shell

```
> import a_constant  # import module
> a_constant.the_constant
| 7
> from a_constant import the_constant
> the_constant
| 7
# Update 7 to 42 in a_constant.py
> a_constant.the_constant  # new value not reflected
| 7
> import a_constant  # void, module already loaded
> a_constant.the_constant
| 7  # unchanged
> import importlib
> importlib.reload(a_constant)
| <module 'a_constant' from 'C:\\...\\a_constant.py'>
> a_constant.the_constant
| 42
> the_constant
| 7  # imported attributes are not updated by reload
> from a_constant import the_constant  # force update
> the_constant
| 42  # the new value
```

Packages

- A package is a collection of modules (and subpackages) in a folder = package name
- Only folders having an `__init__.py` file are considered packages
- The `__init__.py` can be empty, or contain code that will be loaded when the package is imported, e.g. importing specific modules

mypackage/__init__.py

```
```

mypackage/a.py

```
print('Loading mypackage.a')
def f():
    print('mypackage.a.f')
```

using_mypackage.py

```
import mypackage.a
mypackage.a.f()
```

Python shell

```
| Loading mypackage.a
| mypackage.a.f
```

A package with a subpackage

mypackage/__init__.py

```
print('loading mypackage')
```

mypackage/a.py

```
print('Loading mypackage.a')
def f():
    print('mypackage.a.f')
```

mypackage/mysubpackage/__init__.py

```
print('loading mypackage.mysubpackage')
import mypackage.mysubpackage.b
```

mypackage/mysubpackage/b.py

```
print('Loading mypackage.mysubpackage.b')
def g():
    print('mypackage.mysubpackage.b.g')
```

using_mysubpackage.py

```
import mypackage.a
mypackage.a.f()
import mypackage.mysubpackage
mypackage.mysubpackage.b.g()
from mypackage.mysubpackage.b import g
g()
```

Python shell

```
| loading mypackage
| Loading mypackage.a
| mypackage.a.f
| loading mypackage.mysubpackage
| Loading mypackage.mysubpackage.b
| mypackage.mysubpackage.b.g
| mypackage.mysubpackage.b.g
```

`__pycache__` folder

- When Python loads a module the first time it is *compiled* to some intermediate code, and stored as a .pyc file in the `__pycache__` folder.
- If a .pyc file exists for a module, and the .pyc file is newer than the .py file, then `import` loads .pyc – saving time to load the module (but does not make the program itself faster)
- It is safe to delete the `__pycache__` folder – but it will be created again next time a module is loaded

Path to modules

Python searches the following folders for a module in the following order:

1) The directory containing the input script / current directory
2) *Environment* variable `PYTHONPATH`
3) Installation defaults

The function `path` in the modul `sys` returns a list of the paths

Setting PYTHONPATH from windows shell

- set PYTHONPATH=*paths separated by semicolon*
  (only valid until shell is closed)

Select Command Prompt - python

```
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>set PYTHONPATH=C:\Users\au121\Desktop\PYLIB

C:\Users\au121>python
Python 3.6.4 (v3.6.4:d48eceb, Dec 19 2017, 06:04:45) [MSC v.1900 32 bit (Intel)] on win32
Type "help", "copyright", "credits" or "license" for more information.
>>> import sys
>>> sys.path
['', 'C:\\Users\\au121\\Desktop\\PYLIB', 'C:\\Program Files (x86)\\Python3\\python36.zip',
'C:\\Program Files (x86)\\Python3\\DLLs', 'C:\\Program Files (x86)\\Python3\\lib', 'C:\\Pro
gram Files (x86)\\Python3', 'C:\\Program Files (x86)\\Python3\\lib\\site-packages']
>>>
```

Setting PYTHONPATH from control panel

- Control panel > System > Advanced system settings > Environment Variables > User variables > Edit or New PYTHONPATH

Python shell www.python.org/dev/peps/pep-0020/

```
> import this
| The Zen of Python, by Tim Peters
|
| Beautiful is better than ugly.
| Explicit is better than implicit.
| Simple is better than complex.
| Complex is better than complicated.
| Flat is better than nested.
| Sparse is better than dense.
| Readability counts.
| Special cases aren't special enough to break the rules.
| Although practicality beats purity.
| Errors should never pass silently.
| Unless explicitly silenced.
| In the face of ambiguity, refuse the temptation to guess.
| There should be one-- and preferably only one --obvious way to do it.
| Although that way may not be obvious at first unless you're Dutch.
| Now is better than never.
| Although never is often better than *right* now.
| If the implementation is hard to explain, it's a bad idea.
| If the implementation is easy to explain, it may be a good idea.
| Namespaces are one honking great idea -- let's do more of those!
```

module **heapq** (Priority Queue)

- Implements a binary **heap** (Williams 1964).
- Stores a set of elements in a standard list, where arbitrary elements can be inserted efficiently and the *smallest element* can be extracted efficiently

heapq.heappush
heapq.heappop

docs.python.org/3/library/heapq.html

J. W. J. Williams. *Algorithm 232: Heapsort*. Communications of the ACM (1964)

heap.py

```
import heapq
from random import random

H = []  # a heap is just a list

for _ in range(10):
    heapq.heappush(H, random())

while True:
    x = heapq.heappop(H)
    print(x)
    heapq.heappush(H, x + random())
```

Python shell

```
0.20569933892764458
0.27057819339616174
0.31115615362876237
0.4841062272152259
0.5054280956005357
0.509387117524076
0.598647195480462
0.7035150735555027
0.7073929685826221
0.7091224012815325
0.714213496127318
0.727868481291271
0.8051275413759873
0.8279523767282903
0.8626022363202895
0.9376631236263869
```

Valid heap

- A *valid heap* satisfies for all i:

  $L[i] \leq L[2 \cdot i + 1]$ and $L[i] \leq L[2 \cdot i + 2]$

- **`heapify(L)`** rearranges the elements in a list to make the list a valid heap

Python shell

```
> from random import randint
> L = [randint(1, 20) for _ in range(10)]
> L  # just random numbers
| [18, 1, 15, 17, 4, 14, 11, 3, 4, 9]
> import heapq
> heapq.heapify(L)  # make L a valid heap
> L
| [1, 3, 11, 4, 4, 14, 15, 17, 18, 9]
> print(heapq.heappop(L))
| 1
> L
| [3, 4, 11, 4, 9, 14, 15, 17, 18]
> heapq.heappush(L, 7)
> L
| [3, 4, 11, 4, 7, 14, 15, 17, 18, 9]
```

J. W. J. Williams. *Algorithm 232: Heapsort*. Communications of the ACM (1964)

Why `heapq` ?

- `min` and `remove` on a list take *linear time* (runs through the whole list)
- heapq supports `heappush` and `heappop` in *logarithmic time*
- For lists of length 30.000.000 the performance gain is a factor 200.000

J. W. J. Williams. *Algorithm 232: Heapsort*. Communications of the ACM (1964)

heap_performance.py (generating plot on previous slide)

```
import heapq
from random import random
import matplotlib.pyplot as plt
from time import time
import gc  # garbage collection

size = []
time_heap = []
time_list = []

for i in range(26):
    n = 2 ** i
    size.append(n)

    L = [random() for _ in range(n)]
    R = max(1, 2 ** 23 // n)
 B  gc.collect()
    start = time()
    for _ in range(R):
        L.append(random())
        x = min(L)
        L.remove(x)
    end = time()
    time_list.append((end - start) / R)
 A  L = None  # avoid MemoryError
    L = [random() for _ in range(n)]
    heapq.heapify(L)  # make L a legal heap
 B  gc.collect()
    start = time()
    for _ in range(100000):
        heapq.heappush(L, random())
        x = heapq.heappop(L)
    end = time()
    time_heap.append((end - start) / 100000)

plt.title('Average time for insert + delete min')
plt.xlabel('list size')
plt.ylabel('time (seconds)')
plt.plot(size, time_list, 'b.-',
         label='list (append, min, remove)')
plt.plot(size, time_heap, 'r.-',
         label='heapq (heappush, heappop)')
plt.xscale('log')
plt.yscale('log')
plt.legend()
plt.show()
```

A Avoid out of memory error for largest experiment, by allowing old **L** to be garbage collected

B Reduce noise in experiments by forcing Python garbage collection before measurement

Working with text

- file formats
- CSV, JSON, XML, Excel
- regular expressions
- module re, finditer

Some file formats

File extension	Content
.html	HyperText Markup Language
.mp3	Audio File
.png .jpeg .jpg	Image files
.svg	Scalable Vector Graphics file
.json	JavaScript Object Notation
.csv	Comma separated values
.xml	eXtensible Markup Language
.xlmx	Micosoft Excel 2010/2007 Workbook

File extension	Description
.exe	Windows executable file
.app	Max OS X Application
.py	Python program
.pyc	Python compiled file
.java	Java program
.cpp	C++ program
.c	C program
.txt	Raw text file

PIL – the Python Imaging Library

- pip install Pillow

```
rotate_image.py
from PIL import Image
img = Image.open('Python-Logo.png')
img_out = img.rotate(45, expand=True)
img_out.save('Python-rotated.png')
```

- For many file types there exist Python packages handling such files, e.g. for images Pillow supports 40+ different file formats
- For more advanced computer vision tasks you should consider OpenCV

Python-Logo.png

Python-rotated.png

python-pillow.org

CSV files - Comma Separated Values

- Simple 2D tables are stored as rows in a file, with values separated by comma
- Strings stored are quoted if necessary
- Values read are strings
- The deliminator (default comma) can be changed by keyword argument `delimiter`.
  Other typical deliminators are tabs '`\t`', and semicolon '`;`'

csv-example.py

```
import csv
FILE = 'csv-data.csv'
data = [[1, 2, 3],
        ['a', '"b"'],
        [1.0, ['x',"y"], 'd']]

with open(FILE, 'w', newline='') as outfile:
    csv_out = csv.writer(outfile)
    for row in data:
        csv_out.writerow(row)

with open(FILE, 'r', newline='') as infile:
    for row in csv.reader(infile):
        print(row)
```

Python shell

```
['1', '2', '3']
['a', '"b"']
['1.0', "['x', 'y']", 'd']
```

csv-data.csv

```
1,2,3
a,""b""
1.0,"['x', 'y']",d
```

docs.python.org/3/library/csv.html

CSV files - Tab Separated Values

csv-tab-separated.py

```
import csv

FILE = 'tab-separated.csv'

with open(FILE) as infile:
    for row in csv.reader(infile, delimiter='\t'):
        print(row)
```

Python shell

```
['1', '2', '3']
['4', '5', '6']
['7', '8', '9']
```

tab-separated.csv

1	2	3
4	5	6
7	8	9

Reading an Excel generated CSV file

average.py

```
import csv

with open('grades.csv') as file:
    data = csv.reader(file, delimiter=';')  # data = iterator over the rows
    header = next(data)                     # ['Name', 'Course', 'Grade']
    count = {}
    total = {}
    for row in data:                        # iterate over data rows
        course = row[header.index('Course')]
        grade  = int(row[header.index('Grade')])
        count[course] = count.get(course, 0) + 1
        total[course] = total.get(course, 0) + grade
print('Average grades:')
width = max(map(len, count))  # maximum course name length
for course in count:
    print(f'{course:>{width}s} : {total[course] / count[course]:.2f}')
```

Python shell

```
Average grades:
    Analysis : 1.67
Programming : 1.50
 Statistics : 2.50
```

grades.csv - Excel

	A	B	C
1	Name	Course	Grade
2	Alice	Analysis	1
3	Alice	Programming	1
4	Bob	Statistics	2
5	Alice	Analysis	1
6	Charlie	Analysis	3
7	Charlie	Statistics	3
8	Bob	Programming	2
9			

Saving a file in Excel as
CSV (Comma delimited) (*.csv)
Sometimes use ';' as default separator,
determined by Windows Regional settings

grades.csv - Notepad

File Edit Format View Help

```
Name;Course;Grade
Alice;Analysis;1
Alice;Programming;1
Bob;Statistics;2
Alice;Analysis;1
Charlie;Analysis;3
Charlie;Statistics;3
Bob;Programming;2
```

Ln 1, Co

CSV files - Quoting

- The amount of quoting is controlled with keyword argument **`quoting`**
- `csv.QUOTE_MINIMAL` etc. can be used to select the quoting level
- Depending on choice of quoting, numeric values and strings cannot be distinguished in CSV file (`csv.reader` will read all as strings anyway)

csv-quoting.py

```
import csv
import sys

data = [[1, 1.0, '1.0'], ['abc', '"', '\t"', ','']]

quoting_options = [(csv.QUOTE_MINIMAL,     'QUOTE_MINIMAL'),
                   (csv.QUOTE_ALL,          'QUOTE_ALL'),
                   (csv.QUOTE_NONNUMERIC,   'QUOTE_NONNUMERIC'),
                   (csv.QUOTE_NONE,         'QUOTE_NONE')]

for quoting, name in quoting_options:
    print(name)
    csv_out = csv.writer(sys.stdout, quoting=quoting, escapechar='\\')
    for row in data:
        csv_out.writerow(row)
```

Python shell

```
| QUOTE_MINIMAL  # cannot distinguish 1.0 and "1.0"
| 1,1.0,1.0
| abc,"""","     """","
| QUOTE_ALL  # cannot distinguish 1.0 and "1.0"
| "1","1.0","1.0"
| "abc","""","   """","
| QUOTE_NONNUMERIC
| 1,1.0,"1.0"
| "abc","""","   """","
| QUOTE_NONE  # cannot distinguish 1.0 and "1.0"
| 1,1.0,1.0
| abc,\",        \",\,
```

File encodings...

```
river-utf8.py   (size 17 bytes, encoding UTF-8)
Æ Æ U I Æ Å
```

```
river-windows1252.py   (size 13 bytes, encoding Windows-1252)
Æ Æ U I Æ Å
```

- Text files can be *encoded* using many different encodings (UTF-8, UTF-16, UTF-32, Windows-1252, ANSI, ASCII, ISO-8859-1, ...)
- Different encodings can result in different file sizes, in particular when containing non-ASCII symbols
- Programs often try to predict the encoding of text files (often with success, but not always)
- Opening files assuming wrong encoding can give strange results....

Opening UTF-8 encoded file but trying to decode using Windows-1252

Opening Windows-1252 encoded file but trying to decode using UTF-8

en.wikipedia.org/wiki/Character_encoding

encoding.py

```
for filename in ['river-utf8.txt', 'river-windows1252.txt']:
    print(filename)
    f = open(filename, 'rb')  # open input in binary mode, default = text mode = 't'
    line = f.readline()       # type(line) = bytes = immutable list of integers in 0..255
    print(line)                                # byte literals look like strings, prefixed 'b'
    print(list(line))                          # print bytes as list of integers
    f = open(filename, 'r', encoding='utf-8')  # try to open file as UTF-8
    line = f.readline()                        # fails if input line is not utf-8
    print(line)
```

river-utf8.py

```
Æ Æ U I Æ Å
```

Python shell

```
| river-utf8.txt
| b'\xc3\x86 \xc3\x86 U I \xc3\x86 \xc3\x85\r\n'  # \x = hexadecimal value follows
| [195, 134, 32, 195, 134, 32, 85, 32, 73, 32, 195, 134, 32, 195, 133, 13, 10]
| Æ Æ U I Æ Å

| river-windows1252.txt
| b'\xc6 \xc6 U I \xc6 \xc5\r\n'
| [198, 32, 198, 32, 85, 32, 73, 32, 198, 32, 197, 13, 10]
| UnicodeDecodeError: 'utf-8' codec can't decode byte 0xc6 in position 0: invalid continuation
  byte

> 'Æ Æ U I Æ Å'.encode('utf8')  # convert string to (an immutable array of) bytes
| b'\xc3\x86 \xc3\x86 U I \xc3\x86 \xc3\x85'
> 'Æ Æ U I Æ Å'.encode('utf8').decode('Windows-1252')  # decode bytes to string
| 'Ã† Ã† U I Ã† Ã…'
```

Reading CSV files with specific encoding

read_shopping.py

```
import csv

with open('shopping.csv', encoding='Windows-1252') as file:
    for article, amount in csv.reader(file):
        print('Buy', amount, article)
```

Python shell

```
| Buy 2 æbler
| Buy 4 pærer
| Buy 3 jordbær
| Buy 10 gulerødder
```

shopping.csv

```
æbler,2
pærer,4
jordbær,3
gulerødder,10
```

CSV file saved with Windows-1252 encoding

JSON

*"**JSON** (**J**ava**S**cript **O**bject **N**otation) is a lightweight data-interchange format. It is easy for humans to read and write. It is easy for machines to parse and generate. It is based on a subset of the JavaScript Programming Language, Standard ECMA-262 3rd Edition - December 1999. JSON is an ideal data-interchange language."*

www.json.org

- Human readable file format
- Easy way to save a Python expression to a file
- Does *not* support all Python types, e.g. sets are not supported, and tuples are saved (and later loaded) as lists

JSON example

json-example.py

```
import json
FILE = 'json-data.json'
data = ((None, True), (42.7, (42,)), [3, 2, 4], (5, 6, 7),
        {'b':'banana', 'a':'apple', 'c': 'coconut'})

with open(FILE, 'w') as outfile:
    json.dump(data, outfile, indent=2, sort_keys=True)

with open(FILE) as infile:
    indata = json.load(infile)

print(indata)
```

Python shell

```
| [[None, True], [42.7, [42]], [3, 2, 4], [5, 6, 7], {'a':
  'apple', 'b': 'banana', 'c': 'coconut'}]
```

json-data.json

```
[
  [
    null,
    true
  ],
  [
    42.7,
    [
      42
    ]
  ],
  [
    3,
    2,
    4
  ],
  [
    5,
    6,
    7
  ],
  {
    "a": "apple",
    "b": "banana",
    "c": "coconut"
  }
]
```

XML - eXtensible Markup Language

- XML is a widespread used data format to store hierarchical data with tags and attributes

cities.xml

```xml
<?xml version="1.0"?>
<world>
  <country name="Denmark">
    <city name="Aarhus" pop="264716"/>
    <city name="Copenhagen" pop="1295686"/>
  </country>
  <country name="USA">
    <city name="New York" pop="8622698"/>
    <city name="San Francisco" pop="884363"/>
  </country>
</world>
```

docs.python.org/3/library/xml.html

xml-example.py

```python
import xml.etree.ElementTree as ET
FILE = 'cities.xml'
tree = ET.parse(FILE)  # parse XML file to internal representation
root = tree.getroot()  # get root element
for country in root:
    for city in country:
        print(city.attrib['name'],  # get value of attribute for an element
              'in',
              country.attrib['name'],
              'has a population of',
              city.attrib['pop'])
print(root.tag, root[0][1].attrib)  # the tag & indexing the children of an element
print([city.attrib['name'] for city in root.iter('city')])  # .iter finds elements
```

Python shell

```
Aarhus in Denmark has a population of 264716
Copenhagen in Denmark has a population of 1295686
New York in USA has a population of 8622698
San Francisco in USA has a population of 884363
world {'name': 'Copenhagen', 'pop': '1295686'}
['Aarhus', 'Copenhagen', 'New York', 'San Francisco']
```

cities.xml

```xml
<?xml version="1.0"?>
<world>
  <country name="Denmark">
    <city name="Aarhus" pop="264716"/>
    <city name="Copenhagen" pop="1295686"/>
  </country>
  <country name="USA">
    <city name="New York" pop="8622698"/>
    <city name="San Francisco" pop="884363"/>
  </country>
</world>
```

XML tags with text

city-descriptions.txt

```
<?xml version="1.0"?>
<world>
  <country name="Denmark">
    <city name="Aarhus" pop="264716">The capital of Jutland</city>
    <city name="Copenhagen" pop="1295686">The capital of Denmark</city>
  </country>
  <country name="USA">
    <city name="New York" pop="8622698">Known as Big Apple</city>
    <city name="San Francisco" pop="884363">Home of the Golden Gate Bridge</city>
  </country>
</world>
```

xml-descriptions.py

```
import xml.etree.ElementTree as ET
FILE = 'city-descriptions.xml'
tree = ET.parse(FILE)
root = tree.getroot()

for city in root.iter('city'):
    print(city.get('name'), '-', city.text)
```

Python shell

```
Aarhus - The capital of Jutland
Copenhagen - The capital of Denmark
New York - Known as Big Apple
San Francisco - Home of the Golden Gate Bridge
```

Openpyxl - Microsoft Excel 2010 manipulation

openpyxl-example.py

```
from openpyxl import Workbook
from openpyxl.styles import Font, PatternFill

wb = Workbook()   # create workbook
ws = wb.active    # active worksheet

ws['A1'] = 42
ws['B3'] = 7
ws['C2'] = ws['A1'].value + ws['B3'].value
ws['D3'] = '=A1+B3+C2'

ws.title = 'My test sheet'

ws['A1'].fill = PatternFill('solid', fgColor='ffff00')
ws['C2'].font = Font(bold=True)

wb.save('openpyxl-example.xlsx')
```

openpyxl.readthedocs.io/en/stable/tutorial.html

String searching using `find`

- Search for first occurence of *`substring`* in *`str[start, end]`*

  `str``.find(`*`substring`*`[, `*`start`*`[, `*`end`*`]])`
- Returns -1 if no occurence found.
- `.index` similar as `.find`, except raises ValueError exception if substring not found

string-search.py

```
text = 'this is a string - a list of characters'
pattern = 'is'

idx = text.find(pattern)
while idx >= 0:
    print(idx, end=' ')
    idx = text.find(pattern, idx + 1)
```

Python shell

```
| 2 5 22
```

docs.python.org/3/library/stdtypes.html#textseq

Is *str*.find fast?

- Typically linear
- Until Python 3.9 in some cases quadractic

  $\texttt{"A}^{2n}\texttt{BA}^{n}\texttt{".find("A}^{n}\texttt{BA}^{n}\texttt{")}$

- docs.python.org/3/whatsnew/3.10.html

  "Substring search functions such as str1 in str2 and str2.find(str1) now sometimes use Crochemore & Perrin's "Two-Way" string searching algorithm to avoid quadratic behavior on long strings."

Regular expression
– A powerful language to describe sets of strings

- **Examples**
  - `abc` denotes a string of letters
  - `ab*c` any string starting with `a`, followed by an arbitrary number of `b`s and terminated by `c`, i.e. {`ac`, `abc`, `abbc`, `abbbc`, `abbbbc`, ...}
  - `ab+c` equivalent to `abb*c`, i.e. there must be at least one `b`
  - `a\wc` any three letter string, starting with `a` and ending with `c`, where second character is any character in `[a-zA-Z0-9_]`
  - `a[xyz]c` any three letter string, starting with `a` and ending with `c`, where second character is either `x`, `y` or `z`
  - `a[^xyz]c` any three letter string, starting with `a` and ending with `c`, where second character is *none* of `x`, `y` or `z`
  - `^xyz` match at start of string (prefix)
  - `xyz$` match at end of string (suffix)
  - ...
- See docs.python.org/3/library/re.html for more

String searching using regular expressions

- `re.search(pattern, text)`
  - find the first occurence of *`pattern`* in *`text`* – returns `None` or a *match object*
- `re.findall(pattern, text)`
  - returns a list of non-overlapping occurence of *`pattern`* in *`text`* – returns a list of substrings
- `re.finditer(pattern, text)`
  - iterator returning a match object for each non-overlapping occurence of *`pattern`* in *`text`*

Python shell

```
> import re
> text = 'this is a string - a list of characters'
> re.findall(r'i\w*', text)  # prefix with 'r' for raw string literal
| ['is', 'is', 'ing', 'ist']
> for m in re.finditer(r'a[^at]*t', text):  # m is a match object
      print(f'text[{m.start()}, {m.end()}] = {m.group()}')
| text[8, 12] = a st
  text[19, 25] = a list
  text[33, 36] = act
```

docs.python.org/3/library/re.html

Substitution and splitting using regular expressions

- `re.sub(pattern, replacement, text)`
  - replace any occurence of the *pattern* in *text* by *replacement*
- `re.split(pattern, text)`
  - split *text* at all occurences of *patern*

Python shell

```
> text = 'this is a string - a list of characters'
> re.sub(r'\w*i\w*', 'X', text)  # replace all words containing i by 'X'
| 'X X a X - a X of characters'
> re.sub(r'\w*i\w*', lambda m: m.group()[::-1], text)  # reverse words containing i
| 'siht si a gnirts - a tsil of characters'
> re.split(r'[^\w]+a[^\w]+', text)  # split around word 'a'
| ['this is', 'string', 'list of characters']
```

docs.python.org/3/library/re.html

Regular expression substitution: \b \w \1 \2 …

- Assume we want to replace ”a” with ”an” in front of words starting with the vowels a, e, i, o and u.

Python shell

```
> txt = 'A elephant, a zebra and a ape'   # two places to correct
> re.sub('a', 'an', txt)                  # same as txt.replace('a', 'an')
| 'A elephannt, an zebran annd an anpe'   # replaces all letters 'a' with 'an'
> re.sub(r'\ba\b', 'an', txt)             # raw string + \b boundary of word
| 'A elephant, an zebra and an ape'       # all lower 'a' replaced
> re.sub(r'\b[aA]\b', 'an', txt)
| 'an elephant, an zebra and an ape'      # both 'a' and 'A' replaced by 'an'
> re.sub(r'\b([aA])\b', r'\1n', txt)      # use () and \1 to reinsert match
| 'An elephant, an zebra and an ape'      # kept 'a' and 'A'
> re.sub(r'\b([aA])\s+[aeiou]', r'\1n', txt)      # \s+ = one or more whitespace
| 'Anlephant, a zebra and anpe'           # missing original whitespace + vowel
> re.sub(r'\b([aA])(\s+[aeiou])', r'\1n\2', txt)  # reinsert both () using \1 \2
| 'An elephant, a zebra and an ape'
```

Fun with strings: Lindenmayer systems (L-systems)

Axiom A

(1) AB
(2) ABA
(3) ABAAB
(4) ABAABABA

Rules
A → AB
B → A

First four iterations of parallel rewriting

"L-systems were introduced and developed in 1968 by Aristid Lindenmayer, a Hungarian theoretical biologist and botanist at the University of Utrecht. Lindenmayer used L-systems to describe the behaviour of plant cells and to model the growth processes of plant development."

- Wikipedia

L_system.py

```
S = 'A'  # axiom
rules = {'A': 'AB', 'B': 'A'}
for i in range(8):
    S = ''.join(rules.get(c, c) for c in S)
    print(S)
```

Python shell

```
| AB
| ABA
| ABAAB
| ABAABABA
| ABAABABAABAAB
| ABAABABAABAABABAABABA
| ABAABABAABAABABAABABAABAABABAABAAB
```

en.wikipedia.org/wiki/L-system

Heighway Dragon

dragon.py

```
import matplotlib.pyplot as plt
from math import sin, cos, radians

axiom = 'FX'
rules = {'X': 'X+YF+', 'Y': '-FX-Y'}

def apply_rules(axiom, rules, repeat):
    for _ in range(repeat):
        axiom = ''.join(rules.get(symbol, symbol) for symbol in axiom)
    return axiom

def walk(commands, position=(0, 0), angle=0, turn=90):
    path = [position]
    for move in commands:
        match move:
            case 'F':
                position = (position[0] + cos(radians(angle)),
                            position[1] + sin(radians(angle)))
                path.append(position)
            case '-': angle -= turn
            case '+': angle += turn
    return path

path = walk(apply_rules(axiom, rules, 13))
plt.plot(*zip(*path), '-')
plt.title('Heighway dragon')
plt.show()
```

Interprete the symbols of the resulting string as a walk where 'F' = draw line forward, and '+' and '-' are turn left and right 90° (X and Y are skipped)

FX+YF++-FX-YF++-FX+YF+--FX-YF++-FX+YF++-FX-YF+--FX+YF+--FX-YF++-FX+YF++-FX-YF++-FX+YF+--FX-YF+--FX+YF++-FX-YF+--FX+YF+--FX-YF++-FX+YF++-FX-YF++-FX+YF+--FX-YF++-FX+YF++-FX-YF+--FX+Y

More space filling curves…

Sierpinski triangle

Axiom F-G-G
F → F-G+F+G-F
G→ GG

Forward F and G
Turns 120°

Sierpinski arrowhead curve

Axiom A
A → B-A-B
B → A+B+A

Forward A and B
Turns 60°

Peano curve

Axiom L
L → LFRFL-F-RFLFR+F+LFRFL
R→ RFLFR+F+LFRFL-F-RFLFR

Heighway dragon

Axiom FX
X → X+YF+
Y → -FX-Y

Koch curve

Axiom F
F → F+F-F-F+F

Hilbert curve

Axiom L
L → +RF-LFL-FR+
R → -LF+RFR+FL-

McWorter Pentigree curve

Axiom F-F-F-F-F
F → F-F-F++F+F-F

Turns 72°

Tree

Axiom F
F → F[+FF][-FF]F[-F][+F]F

Turns 36°
[and] return to start point when done

Cesero fractal

Axiom F
F → F+F--F+F

Turns 80°

More space filling curves… (source code)

space-filling-L_systems.py

```python
import matplotlib.pyplot as plt
from math import sin, cos, radians

def walk(commands,
         pos=(0, 0),
         forward=frozenset('F'),
         angle=0,
         turn=90):
  paths = [[pos]]
  stack = []
  for move in commands:
    if move in forward:
      pos = (pos[0]+cos(radians(angle)),
             pos[1]+sin(radians(angle)))
      paths[-1].append(pos)
    elif move == '-': angle -= turn
    elif move == '+': angle += turn
    elif move == '[':
      stack.append((pos, angle))
    elif move == ']':
      pos, angle = stack.pop()
      paths.append([pos])
  return paths
```

```python
def apply_rules(axiom, rules, repeat=1):
    for _ in range(repeat):
        axiom = ''.join(rules.get(symbol, symbol) for symbol in axiom)
    return axiom

curves = [  # Lindenmayer systems (L-systems)
  ('Sierpinski triangle', 'F-G-G', {'F': 'F-G+F+G-F', 'G': 'GG'}, 5, {'turn': 120, 'forward': {'F','G'}}),
  ('Sierpinski arrowhead curve', 'A', {'A': 'B-A-B', 'B': 'A+B+A'}, 5, {'turn': 60, 'forward': {'A','B'}}),
  ('Peano curve', 'L', {'L': 'LFRFL-F-RFLFR+F+LFRFL', 'R': 'RFLFR+F+LFRFL-F-RFLFR'}, 3, {}),
  ('Heighway dragon','FX', {'X': 'X+YF+', 'Y': '-FX-Y'}, 10, {}),
  ('Koch curve', 'F', {'F': 'F+F-F-F+F'}, 3, {}),
  ('Hilbert curve', 'L', {'L': '+RF-LFL-FR+', 'R': '-LF+RFR+FL-'}, 4, {}),
  ('McWorter Pentigree curve', 'F-F-F-F-F', {'F': 'F-F-F++F+F-F'}, 3, {'turn': 72}),
  ('Tree', 'F', {'F': 'F[+FF][-FF]F[-F][+F]F'}, 3, {'turn': 36}),
  ('Cesero fractal', 'F', {'F': 'F+F--F+F'}, 5, {'turn': 80})
]

for idx, (title, axiom, rules, repeat, walk_arg) in enumerate(curves, start=1):
    paths = walk(apply_rules(axiom, rules, repeat), **walk_arg)
    ax = plt.subplot(3, 3, idx, aspect='equal')
    ax.set_title(title)
    for path in paths:
        plt.plot(*zip(*path), '-')
plt.axis('off')
plt.show()
```

Relational data

- SQLite
- pandas

Two tables

Table: country

name	population	area	capital
'Denmark'	5748769	42931	'Copenhagen'
'Germany'	82800000	357168	'Berlin'
'USA'	325719178	9833520	'Washington, D.C.'
'Iceland'	334252	102775	'Reykjavik'

Table: city

name	country	population	established
'Copenhagen'	'Denmark'	775033	800
'Aarhus'	'Denmark'	273077	750
'Berlin'	'Germany'	3711930	1237
'Munich'	'Germany'	1464301	1158
'Reykjavik'	'Iceland'	126100	874
'Washington D.C.'	'USA'	693972	1790
'New Orleans'	'USA'	343829	1718
'San Francisco'	'USA'	884363	1776

SQL

pronounced ˌɛsˌkjuːˈɛl or ˈsiːkwəl

Table: country			
name	population	area	capital
'Denmark'	5748769	42931	'Copenhagen'
'Germany'	82800000	357168	'Berlin'
'USA'	325719178	9833520	'Washington, D.C.'
'Iceland'	334252	102775	'Reykjavik'

- SQL = Structured Query **Language**
- **Database = collection of tables** stored persistently on disk
- ANSI and ISO standards since 1986 and 1987, respectively; origin early 70s
- Widespread used SQL databases (can handle many tables/rows/users): Oracle, MySQL, Microsoft SQL Server, PostgreSQL and IBM DB2
- **SQLite** is a very lightweight version storing a database in a **single file**, without a separate database server; first release in 2000
- SQLite is included in both iOS and Android mobil phones and operating systemes like Mac OS, Windows, and Fedora Linux

The Course "Databases" gives a more in-depth introduction to SQL (MySQL)

Examples : SQL statements

Table: country			
name	population	area	capital
'Denmark'	5748769	42931	'Copenhagen'
'Germany'	82800000	357168	'Berlin'
'USA'	325719178	9833520	'Washington, D.C.'
'Iceland'	334252	102775	'Reykjavik'

- CREATE TABLE country (name, population, area, capital)
- INSERT INTO country VALUES ('Denmark', 5748769, 42931, 'Copenhagen')
- UPDATE country SET population=5748770 WHERE name='Denmark'
- SELECT name, capital FROM country WHERE population >= 1000000
  > [('Denmark', 'Copenhagen'), ('Germany', 'Berlin'), ('USA', 'Washington, D.C.')]
- SELECT * FROM country WHERE capital = 'Berlin'
  > [('Germany', 82800000, 357168, 'Berlin')]
- SELECT country.name, city.name, city.established FROM city, country WHERE city.name=country.capital AND city.population < 700000
  > [('Iceland', 'Reykjavik', 874), ('USA', 'Washington, D.C.', 1790)]
- DELETE FROM country WHERE name = 'Germany'
- DROP TABLE country

www.w3schools.com/sql/

sqlite-example.py

```python
import sqlite3

connection = sqlite3.connect('example.sqlite')  # creates file if necessary

c = connection.cursor()

c.executescript('''DROP TABLE IF EXISTS country;  -- multiple SQL statements
                   DROP TABLE IF EXISTS city''')

countries = [('Denmark', 5748769, 42931, 'Copenhagen'),
             ('Germany', 82800000, 357168, 'Berlin'),
             ('USA', 325719178, 9833520, 'Washington, D.C.'),
             ('Iceland', 334252, 102775, 'Reykjavik')]

cities = [('Copenhagen', 'Denmark', 775033, 800),
          ('Aarhus', 'Denmark', 273077, 750),
          ('Berlin', 'Germany', 3711930, 1237),
          ('Munich', 'Germany', 1464301, 1158),
          ('Reykjavik', 'Iceland', 126100, 874),
          ('Washington, D.C.', 'USA', 693972, 1790),
          ('New Orleans', 'USA', 343829, 1718),
          ('San Francisco', 'USA', 884363, 1776)]

c.execute('CREATE TABLE country (name, population, area, capital)')
c.execute('CREATE TABLE city (name, country, population, established)')
c.executemany('INSERT INTO country VALUES (?,?,?,?)', countries)
c.executemany('INSERT INTO city VALUES (?,?,?,?)', cities)

connection.commit()  # save data to database before closing
connection.close()
```

SQLite

docs.python.org/3/library/sqlite3.html

SQLite query examples

try to avoid using the asterisk (*) as a good habit

www.sqlitetutorial.net/sqlite-select

sqlite-example.py

```
for row in c.execute('SELECT * FROM country'):  # * = all columns, execute returns iterator
    print(row)                                  # row is by default a Python tuple

for row in c.execute('''SELECT * FROM city, country    -- all pairs of rows from city × country
                        WHERE city.name = country.capital AND city.population < 700000'''):
    print(row)

print(*c.execute('''SELECT country.name,
                           COUNT(city.name) AS cities,
                           100 * SUM(city.population) / country.population
                    FROM city JOIN country ON city.country = country.name  -- SQL join 2 tables
                    WHERE city.population > 500000                  -- only consider big cities
                    GROUP BY city.country                -- output has one row per group of rows
                    ORDER BY cities DESC, SUM(city.population) DESC'''))   # ordering of output
```

Python shell

```
| ('Denmark', 5748769, 42931, 'Copenhagen')
| ('Germany', 82800000, 357168, 'Berlin')
| ('USA', 325719178, 9833520, 'Washington, D.C.')
| ('Iceland', 334252, 102775, 'Reykjavik')

| ('Reykjavik', 'Iceland', 126100, 874, 'Iceland', 334252, 102775, 'Reykjavik')
| ('Washington, D.C.', 'USA', 693972, 1790, 'USA', 325719178, 9833520, 'Washington, D.C.')

| ('Germany', 2, 6) ('USA', 2, 0) ('Denmark', 1, 13)
```

SQL injection

Right way

```
c.execute('INSERT INTO users VALUES (?)', (user,))
```

unsafe-example.py

```
import sqlite3
connection = sqlite3.connect('users.sqlite')
c = connection.cursor()
c.execute('CREATE TABLE users (name)')
while True:
    user = input('New user: ')
    c.executescript(f'INSERT INTO users VALUES ("{user}")')
    connection.commit()
    print(list(c.execute('SELECT * FROM users')))
```

can execute a string containing several SQL statements

Insecure
NEVER use f-string with user input

Python shell

```
> New user: gerth
| [('gerth',)]
> New user: guido
| [('gerth',), ('guido',)]
> New user: evil"); DROP TABLE users; --
| sqlite3.OperationalError: no such table: users
```

```
INSERT INTO users VALUES ("evil"); DROP TABLE users; --")
```

HI, THIS IS YOUR SON'S SCHOOL. WE'RE HAVING SOME COMPUTER TROUBLE.
OH, DEAR – DID HE BREAK SOMETHING?
IN A WAY–
DID YOU REALLY NAME YOUR SON Robert'); DROP TABLE Students;-- ?
OH. YES. LITTLE BOBBY TABLES, WE CALL HIM.
WELL, WE'VE LOST THIS YEAR'S STUDENT RECORDS. I HOPE YOU'RE HAPPY.
AND I HOPE YOU'VE LEARNED TO SANITIZE YOUR DATABASE INPUTS.

xkcd.com/327/

Pandas

- Comprehensive Python library for data manipulation and analysis, in particular tables and time series
- Pandas **data frames** = tables
- Supports interaction with SQL, CSV, JSON, ...
- Integrates with Jupyter, numpy, matplotlib, ...

pandas

$y_{it} = \beta' x_{it} + \mu_i + \epsilon_{it}$

pandas.pydata.org

Pandas integration with Jupyter

- Tables (Pandas data frames) are rendered nicely in Jupyter

In [1]:

```
import pandas as pd
students = pd.read_csv('students.csv')
students
```

Out[1]:

	Name	City
0	Donald Duck	Copenhagen
1	Goofy	Aarhus
2	Mickey Mouse	Aarhus

students.csv

```
Name,City
"Donald Duck","Copenhagen"
"Goofy","Aarhus"
"Mickey Mouse","Aarhus”
```

Reading tables (data frames)

- Pandas provides functions for reading and writting pandas.DataFrames as files in different data formats, e.g. SQLite, csv and EXCEL files

pandas-example.py

```
import pandas as pd

import sqlite3
connection = sqlite3.connect('example.sqlite')
countries = pd.read_sql_query('SELECT * FROM country', connection)
cities = pd.read_sql_query('SELECT * FROM city', connection)

students = pd.read_csv('students.csv')
students.to_sql('students', connection, if_exists='replace')
students.to_excel('students.xlsx', sheet_name='students')
print(students)
```

Python shell

```
|              Name         City
| 0    Donald Duck   Copenhagen
| 1          Goofy       Aarhus
| 2   Mickey Mouse       Aarhus
```

Selecting columns and rows

Table: country

name	population	area	capital
'Denmark'	5748769	42931	'Copenhagen'
'Germany'	82800000	357168	'Berlin'
'USA'	325719178	9833520	'Washington, D.C.'
'Iceland'	334252	102775	'Reykjavik'

Python shell

```
> countries['name']                    # select column
> countries.name                       # same as above
> countries[['name', 'capital']]       # select multiple columns, note double-[]
> countries.head(2)                    # first 2 rows
> countries[1:3]                       # slicing rows, rows 1 and 2
> countries[::2]                       # slicing rows, rows 0 and 2
> countries.at[1, 'area']              # indexing cell by (row label, column name)
> cities[(cities['name'] == 'Berlin') | (cities['name'] == 'Munich')]  # select rows
|      name   country   population   established
| 2   Berlin   Germany     3711930          1237   # note original row labels
| 3   Munich   Germany     1464301          1158
> pd.DataFrame([[1, 2], [3, 4], [5, 6]], columns=['x', 'y'])  # create DF from list
> pd.DataFrame(np.random.random((3, 2)), columns=['x', 'y'])  # from numpy
```

pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html

Row labels

Python shell

```
> df = pd.DataFrame(np.arange(1, 13).reshape(3, 4),
                    index=['q', 'w', 'e'],          # row labels
                    columns=['c', 'a', 'd', 'e'])   # column names
> df
|    c   a   d   e
| q  1   2   3   4   # row labels can be strings
| w  5   6   7   8
| e  9  10  11  12
> df.loc['w':'e', ['e', 'a']]  # slice of labeled rows
|     e   a
| w   8   6
| e  12  10
> df.loc['w']  # single row (a one-dimensional pd.Series)
| c    5
| a    6
| d    7
| e    8
| Name: w, dtype: int32
> df.iloc[:2,:2]  # use iloc to work with integer indexes
|    c  a
| q  1  2
| w  5  6
```

Merging tables and creating a new column

pandas-example.py

```
M = pd.merge(countries, cities, left_on='capital', right_on='name')
# both data frames had a 'name' and 'population' column
M1 = M.rename(columns={
    'population_x': 'country_population',
    'population_y': 'capital_population'
})
M2 = M1.drop(columns=['name_x', 'name_y'])
M2['%pop in capital'] = M2.capital_population / M2.country_population  # add column
M2.sort_values('%pop in capital', ascending=False, inplace=True)
print(M2[['country', '%pop in capital']])
```

Python shell

```
|     country  %pop in capital
| 3  Iceland         0.377260  # note row labels are permuted
| 0  Denmark         0.134817
| 1  Germany         0.044830
| 2      USA         0.002131
```

Pandas datareader and Matplotlib

- pandas_datareader provides access to many data sources
- dataframes have a .plot method (using matplotlib.pyplot)
- `pip install pandas-datareader` and `pip install setuptools`

pandas-datareader.py

```
import matplotlib.pyplot as plt
import pandas_datareader
#df = pandas_datareader.data.DataReader(['AAPL', 'GOOGL', 'MSFT', 'ZM'], 'stooq')  # ignores start=...
df = pandas_datareader.stooq.StooqDailyReader(['AAPL', 'GOOGL', 'MSFT', 'ZM'], start='2000-01-01').read()
df['Close'].plot()
plt.legend()
plt.show()
```

pandas-datareader.readthedocs.io

pandas-datareader.readthedocs.io/en/latest/readers/stooq.html

Hierarchical / Multi-level indexing (MultiIndex)

Python shell

```
> df.tail(2)
| Attributes    Close                        ...      Volume
| Symbols        AAPL     GOOGL     MSFT      ...       GOOGL         MSFT           ZM
| Date                                        ...
| 2020-04-29   287.73   1342.18   177.43     ...   5417888.0   51286559.0   22033320.0
| 2020-04-30   293.80   1346.70   179.21     ...   2788644.0   53627543.0   16648922.0
> df['Close'].tail(2)
| Symbols        AAPL     GOOGL     MSFT       ZM
| Date
| 2020-04-29   287.73   1342.18   177.43   146.48
| 2020-04-30   293.80   1346.70   179.21   135.17
> df['Close']['GOOGL'].tail(2)
| Date
| 2020-04-29    1342.18
| 2020-04-30    1346.70
| Name: GOOGL, dtype: float64
> df.loc[:, pd.IndexSlice[:,'GOOGL']].tail(2)
| Attributes    Close      High       Low      Open      Volume
| Symbols       GOOGL     GOOGL     GOOGL     GOOGL       GOOGL
| Date
| 2020-04-29   1342.18   1360.15   1326.73   1345.00   5417888.0
| 2020-04-30   1346.70   1350.00   1321.50   1331.36   2788644.0
```

Both rows and columns can have multi-level indexing

Python shell

```
> df.columns
| MultiIndex([( 'Close',  'AAPL'),
|             ( 'Close', 'GOOGL'),
|             ( 'Close',  'MSFT'),
|             ( 'Close',    'ZM'),
|             (  'High',  'AAPL'),
|             (  'High', 'GOOGL'),
|             (  'High',  'MSFT'),
|             (  'High',    'ZM'),
|             (   'Low',  'AAPL'),
|             (   'Low', 'GOOGL'),
|             (   'Low',  'MSFT'),
|             (   'Low',    'ZM'),
|             (  'Open',  'AAPL'),
|             (  'Open', 'GOOGL'),
|             (  'Open',  'MSFT'),
|             (  'Open',    'ZM'),
|             ('Volume',  'AAPL'),
|             ('Volume', 'GOOGL'),
|             ('Volume',  'MSFT'),
|             ('Volume',    'ZM')],
|   names=['Attributes', 'Symbols'])
```

pandas.pydata.org/pandas-docs/stable/user_guide/advanced.html

xkcd.com/1838/

Clustering

- k-means
- scipy.cluster.vq.kmeans
- DBSCAN*
- neural networks

3 clusters / groups of points

Clustering = Optimization problem

Example: *k*-means

- Given *n* input points and an integer *k*, find *k* *centroid* points
- Assign each input point to nearest centroid → *k* clusters $\mathcal{C}$
- distortion = $\sum_{C \in \mathcal{C}} \sum_{p \in C} |p - \text{centroid}(C)|^2$
- Goal : Find *k* centroids that minimize distortion

k-means for $k = 1$

- Let the centroid point c for a point set C be the point minimizing the

$$\text{distortion} = \sum_{p \in C} |p - c|^2$$

- Theorem $c = \text{average}(C)$

k-means - Lloyd's method (pseudo code)

```
centroids = k distinct random input points
while centroids change:
    create clusters C by assigning points to the nearest centroid
    centroids = average of each cluster
```

k-means is a heuristic

output can be far from optimal

Generating random points (just one random approach)

k_means.py

```
from random import random
from math import pi, cos, sin

def random_point(x, y, radius):
    angle = 2 * pi * random()
    r = radius * random() ** 2
    return x + r * cos(angle), y + r * sin(angle)

def random_points(n, x, y, radius):
    for _ in range(n):
        yield random_point(x, y, radius)
```

k-means

k_means.py

```
from random import sample
from numpy import argmin, mean

def dist(p, q):
    return sum((a - b)**2 for a, b in zip(p, q))

def k_means(points, k):
    centroid = sample(points, k)
    centroids = [ centroid ]  # history for visualization
    while True:
        clusters = [[] for _ in centroid]
        for p in points:
            i = argmin([dist(p, c) for c in centroid])
            clusters[i].append(p)
        centroid = [tuple(map(mean, zip(*c))) for c in clusters]
        if centroid == centroids[-1]:
            break
        centroids.append(centroid)
        if any(len(c) == 0 for c in clusters):
            print('Not good - empty cluster')
            break
    return clusters
```

k-mean limitations

- Can easily converge to a solution far from a global minimum
  - Solution – try several times and take the best
    (possibly since we can measure the quality (= distortion) of a solution)
- Clusters can become empty
  - Solution – discard and restart / take a random point out as a new centroid / take point furthest away from existing centroids / ....
- Sensitive to the scales of the different dimensions
  - Solution – apply some kind of initial normalization of coordinates

k-means - better bounds

- The k-means++ algorithm achieves an expected guarantee to be at most a factor $8(2 + \ln k)$ from the optimal [Vassilvitskii & Arthur]

- There exist polynomial time approximation schemes that find a solution that is guaranteed $1 + \varepsilon$ of the optimal (but running time exponential in k and dimension of points) [Har-Peled et al.]

- **In practice: A heuristic is most often the algorithm of choice**

scipy.cluster.vq.kmeans

k_means.py

```
from scipy.cluster.vq import kmeans, whiten
import matplotlib.pyplot as plt

points = whiten(points)  # normalize variance of points
centroids, distortion = kmeans(points, K)

plt.plot(*zip(*points), 'r.')
plt.plot(*zip(*centroids), 'bo')
plt.title('scipy.cluster.vq.kmeans')
plt.show()
```

Note: According to the documentation "`whiten` must be called prior to passing an observation matrix to `kmeans`"

docs.scipy.org/doc/scipy/reference/generated/scipy.cluster.vq.kmeans.html

scipy.cluster.vq.whiten

- Normalizes / scales each dimension to have unit variance 1.0

$$\mathrm{Var}(X) = \frac{1}{n}\sum_{i=1}^{n}(x_i - \mu)^2 \qquad \mu = \frac{1}{n}\sum_{i=1}^{n} x_i$$

https://docs.scipy.org/doc/scipy/reference/generated/scipy.cluster.vq.kmeans.html

Other Python clustering methods - `sklearn.cluster`

http://scikit-learn.org/stable/modules/clustering.html

DBSCAN*

dbscan.py

```
def dbscan(points, epsilon, m):
    def dist(p, q):
        return sum((pi - qi) ** 2 for pi, qi in zip(p, q))

    def close(p, q):
        return dist(p, q) <= epsilon ** 2

    core, noise, clusters = [], [], []
    for p in points:
        if sum(close(p, q) for q in points) >= m:
            core.append(p)
        else:
            noise.append(p)

    while core:
        cluster = [core.pop()]
        for p in cluster:
            for q in list(core):
                if close(p, q):
                    cluster.append(q)
                    core.remove(q)
        clusters.append(cluster)
    return clusters, noise
```

- Parameters ε and m
- p is a core point when
  $$|\{q \mid |p - q| \le \varepsilon\}| \ge m$$
- Remaining points are noise
- Core points p and q are in the same cluster if $|p - q| \le \varepsilon$

Data Mining Algorithms

- k-means, DBSCAN*, and more generally clustering, is just one field in the area of *Data Mining*

- For more information see the webpage
  Top 10 Data Mining Algorithms, Explained
  a follow up to the below paper

- X. Wu et al., *Top 10 algorithms in data mining*,
  Knowledge and Information Systems, 14(1):1–37, 2008.
  DOI 10.1007/s10115-007-0114-2

www.kdnuggets.com/2015/05/top-10-data-mining-algorithms-explained.html

Neural networks (one slide introduction)

MNIST, 784 input pixels scaled to [0.0, 1.0]

activation $a_i^{(l)} = f^{(l)}\left(\sum_j a_j^{(l-1)} \cdot W_{ji}^{(l)} + b_i^{(l)} \right)$

activation function (nonlinear) — weight — bias

Classification, like MNIST, prediction = index of node with maximum output

MNIST : 28 x 28 pixel values from [0, 255]

Common activation functions

e.g. mean squared error

$$\frac{1}{n}\sum_{(x,y)} |\mathrm{out}(x) - y|^2$$

Learning

Find *W*s and *b*s performing well (minimize a cost function) on a set of *n* training inputs *x* with known output *y* using *backpropagation / stochastic gradient descend*

Applying a linear classifier using Numpy: $x \cdot W + b$

Python shell

```
| import matplotlib.pyplot as plt
| import numpy as np
| from tensorflow import keras
| (train_images, train_labels), (test_images, test_labels) = keras.datasets.mnist.load_data()
| type(test_images)
> <class 'numpy.ndarray'>
| test_images.shape
> (10000, 28, 28)  # 10_000 images 28 x 28
| test_labels.shape
> (10000,)         # 10_000 labels
| test_labels[:3]
> array([7, 2, 1], dtype=uint8)
| for i, image in zip(range(3), test_images):
|       plt.subplot(1, 3, i + 1)
|       plt.imshow(image)
| plt.show()
| W, b = map(np.array, eval(open('mnist_linear.weights').read()))  # read W and b from file
| print(W.shape, W.dtype, b.shape, b.dtype)
> (784, 10) float64 (10,) float64
| print([np.argmax(image.reshape(28 * 28) @ W + b) for image in test_images[:3]])
> [7, 2, 1]  # correct on 9_142 of the 10_000 images for the above file, ie accuracy 91%
```

manually generated labels

network prediction

Graphical user interfaces (GUI)

- Tkinter

primitive_calculator.py

```python
accumulator = 0

while True:
    print('Accumulator:', accumulator)
    print('Select:')
    print('  1: clear')
    print('  2: add')
    print('  3: subtract')
    print('  4: multiply')
    print('  5: quit')

    choice = int(input('Choice: '))

    match choice:
        case 1: accumulator = 0
        case 2: accumulator += int(input('add: '))
        case 3: accumulator -= int(input('subtract: '))
        case 4: accumulator *= int(input('multiply by: '))
        case 5: break
```

Python shell

```
Accumulator: 0
Select:
  1: clear
  2: add
  3: subtract
  4: multiply
  5: quit
Choice: 2
add: 10
Accumulator: 10
Select:
  1: clear
  2: add
  3: subtract
  4: multiply
  5: quit
Choice: 2
add: 15
Accumulator: 25
Select:
...
```

Homepage - Introduktion til pr

https://brightspace.au.dk/d2l/home/539

Introduktion til programmering me

Course Home Content Course Tools Classlist

```
def memoize(f):
    # answers[args] = f(*args)
    answers = {}
    def wrapper(*args):
        return answers[args]
```

Introduction to Programmi
Applications (2022)

This course is **open** for stude

AutoSave On gui.p... - Sa... Gerth Stølting Brodal GS

File Home AU Insert Design Transitions Animations Slide Show Review View Help Acrobat

Templafy Paste Slides Font Paragraph Drawing Editing Create and Share Adobe PDF Dictate Design Ideas

Templafy Clipboard Adobe Acrobat Voice Designer

1 2 3 4 5 6 7 8 9

Graphical user interfaces (GUI)

- Tkinter

Click to add notes

Slide 1 of 19 Danish Notes Display Settings 48 %

ENG 07:15

BackSlash Linux GUI
www.backslashlinux.com

Python GUI's (Graphical Users Interfaces)

- There is a long list of GUI frameworks and toolkits, designer tools
  - we will only briefly look at Tkinter
- GUI are, opposed to a text terminal, easier to use, more intuitive and flexible
- Windows, icons, menus, buttons, scrollbars mouse / touch / keyboard interaction etc.
- Operating system (e.g. Windows, maxOS, iOS, Linux, Android) provides basic functionality in particular a window manager
- Writing GUI applications from scratch can be painful – frameworks try to provide all standard functionality

en.wikipedia.org/wiki/Colossal_Cave_Adventure

wiki.python.org/moin/GuiProgramming

Tkinter

- “Tkinter is Python's de-facto standard GUI (Graphical User Interface) package. It is a thin object-oriented layer on top of Tcl/Tk.”
- “Tcl is a high-level, general-purpose, interpreted, dynamic programming language.”
- “Tk is a free and open-source, cross-platform widget toolkit that provides a library of basic elements of GUI widgets for building a graphical user interface (GUI) in many programming languages.”
- “The popular combination of Tcl with the Tk extension is referred to as Tcl/Tk, and enables building a graphical user interface (GUI) natively in Tcl. Tcl/Tk is included in the standard Python installation in the form of Tkinter.”

en.wikipedia.org

Terminology

- widgets (e.g. buttons, editable text fields, labels, scrollbars, menus, radio buttons, check buttons, canvas for drawing, frames...)
- events (e.g. key press, mouse click, mouse entering/leaving, resizing windows, redraw requests, ...)
- listening (application waits for events to be fired)
- event handler (a function whose purpose is to handle an event, many triggered by user or OS/Window manager)
- geometry managers (how to organize widgets in a window: Tkinter *pack*, *grid*, *place*)

docs.python.org/3/library/tk.html

“tkinter is also famous for having an outdated look and feel”

- Comes with Python
- Alternatives PySide, PyQt, Kivy, …

Welcome example

welcome.py

```
import tkinter
root = tkinter.Tk()  # root window
def do_quit():  # event handler for 'Close' button
    root.destroy()
root.title('Tkinter Welcome GUI')
label = tkinter.Label(root, text='Welcome to Tkinter', background='yellow',
                      anchor=tkinter.SE, font=('Helvetica', '24', 'bold italic'),
                      padx=10, pady=10)
label.pack(side=tkinter.LEFT, fill=tkinter.BOTH, expand=True)
                                          # parent window
close_button = tkinter.Button(root, text='Close', command=do_quit)
close_button.pack(side=tkinter.RIGHT)
tkinter.mainloop()  # loop until all windows are closed/destroyed
```

Welcome example (class)

welcome_class.py

```
import tkinter

class Welcome:
    def do_quit(self):  # event handler for 'Close'
        self.root.destroy()

    def __init__(self, window_title):
        self.root = tkinter.Tk()
        self.root.title(window_title)

        self.label = tkinter.Label(self.root, text='Welcome')
        self.label.pack(side=tkinter.LEFT)

        self.close_button = tkinter.Button(self.root, text='Close', command=self.do_quit)
        self.close_button.pack(side=tkinter.RIGHT)

Welcome('My Window')

tkinter.mainloop()
```

increment.py (part I)

```
import tkinter

class Counter:
    def do_quit(self):
        self.root.destroy()

    def add(self, x):
        self.counter += x
        self.count.set(self.counter)

    def __init__(self, message):
        self.counter = 0

        self.root = tkinter.Toplevel()  # new window
        self.root.title('Counter')

        self.label = tkinter.Label(self.root, text=message)
        self.label.grid(row=0, columnspan=3)

        self.minus_button = tkinter.Button(self.root, text='-', command=lambda: self.add(-1))
        self.minus_button.grid(row=1, column=0)

        self.count = tkinter.IntVar()
        self.count_label = tkinter.Label(self.root, textvariable=self.count)
        self.count_label.grid(row=1, column=1)

        self.plus_button = tkinter.Button(self.root, text='+', command=lambda: self.add(+1))
        self.plus_button.grid(row=1, column=2)
```

increment.py (part II)

```
class Counter_app:
    def __init__(self):
        self.counters = 0

        self.root = tkinter.Tk()

        self.create = tkinter.Button(self.root, text='Create counter', command=self.new_counter)
        self.create.pack()

    def new_counter(self):
        Counter('Counter ' + chr(ord('A') + self.counters))
        self.counters += 1

Counter_app()

tkinter.mainloop()
```

Canvas

canvas.py

```
import tkinter

root = tkinter.Tk()

canvas = tkinter.Canvas(root, width=100, height=100)
canvas.pack()
canvas.create_line(0, 0, 100, 100)
canvas.create_oval(20, 20, 80, 80, fill='blue')

close = tkinter.Button(root, text='Close', command=root.destroy)
close.pack()

tkinter.mainloop()
```

Calculator
42
7
8
9
*
C
4
5
6
/
%
1
2
3
-
=
0
.
+

calculator.py (Part I)

```
import tkinter
from tkinter import messagebox

class Calculator:
    def __init__(self, root):
        self.root = root

        self.display = tkinter.Entry(self.root, font=('Helvetica', 16), justify=tkinter.RIGHT)
        self.display.insert(0, '0')
        self.display.grid(row=0, column=0, columnspan=5)  # grid = geometry manager

        self.button(1, 0, '7')
        self.button(1, 1, '8')
        self.button(1, 2, '9')
        self.button(1, 3, '*')
        self.button(1, 4, 'C', command=self.clearText)  # 'C' button
        self.button(2, 0, '4')
        self.button(2, 1, '5')
        self.button(2, 2, '6')
        self.button(2, 3, '/')
        self.button(2, 4, '%')
        self.button(3, 0, '1')
        self.button(3, 1, '2')
        self.button(3, 2, '3')
        self.button(3, 3, '-')
        self.button(3, 4, '=', rowspan=2, command=self.calculateExpression)  # '=' button
        self.button(4, 0, '0', columnspan=2)
        self.button(4, 2, '.')
        self.button(4, 3, '+')
```

calculator.py (Part II)

```
    def button(self, row, column, text, command=None, columnspan=1, rowspan=1):
        if command == None:
            command = lambda: self.appendToDisplay(text)
        B = tkinter.Button(self.root, font=('Helvetica', 11), text=text, command=command)
        B.grid(row=row, column=column, rowspan=rowspan, columnspan=columnspan, sticky='NWNESWSE')

    def clearText(self):
        self.replaceText('0')

    def replaceText(self, text):
        self.display.delete(0, tkinter.END)
        self.display.insert(0, text)

    def appendToDisplay(self, text):
        if self.display.get() == '0':
            self.replaceText(text)
        else:
            self.display.insert(tkinter.END, text)

    def calculateExpression(self):
        expression = self.display.get().replace('%', '/ 100')
        try:
            result = eval(expression)  # DON'T DO THIS !!!
            self.replaceText(result)
        except:
            messagebox.showwarning('Message', 'Invalid expression')

root = tkinter.Tk()
root.title('Calculator')
root.resizable(0, 0)  # disallow resizing and maximizing the window

Calculator(root)

tkinter.mainloop()
```

Creating a menu

rectangles.py

```
class Rectangles:
    Colors = ['black', 'red', 'blue', 'green', 'yellow']

    def create_menu(self):
        menubar = tkinter.Menu(self.root)
        menubar.add_command(label='Quit! (Ctrl-q)', command=self.do_quit)

        editmenu = tkinter.Menu(menubar, tearoff=0)
        editmenu.add_command(label='Clear', command=self.clear_all)
        editmenu.add_command(label='Delete last (Ctrl-z)', command=self.delete_last_rectangle)

        colormenu = tkinter.Menu(menubar, tearoff=0)
        for color in self.Colors:  # list of color names
            colormenu.add_command(label=color,
                                  foreground=color,
                                  command=self.get_color_handler(color))

        menubar.add_cascade(label='Edit', menu=editmenu)
        menubar.add_cascade(label='Color', menu=colormenu)
        self.root.config(menu=menubar)  # Show menubar

    def get_color_handler(self, color):
        return lambda : self.set_color(color)

    def set_color(self, color):
        self.current_color = color
...
```

Binding key and mouse events

- Whenever a key is pressed, mouse button is pressed/released, mouse is moved, mouse enters/leaves objects etc. events are triggered that can be bound to call a user defined event handler

rectangles.py (continued)

```
...
  self.root = tkinter.Tk()
  self.root.bind('<Control-q>', self.do_quit)
  self.root.bind('<Control-z>', self.delete_last_rectangle)
...
  self.canvas = tkinter.Canvas(self.root, width=300, height=200,
                               background='white')
  self.canvas.bind('<Button-1>', self.create_rectangle_start)
  self.canvas.bind('<B1-Motion>', self.create_rectangle_mouse_move)
  self.canvas.bind('<ButtonRelease-1>', self.create_rectangle_end)
...
```

Handling mouse events

rectangles.py (continued)

```
def create_rectangle_start(self, event):
    radius = 3
    x, y = event.x, event.y
    self.top_pos = (x, y)
    self.bottom_pos = (x, y)
    self.rectangle = self.canvas.create_rectangle(x, y, x, y,  # top-left = bottom-right
                                                  fill=self.current_color, width=1, outline='grey', dash=(3, 5))
    self.corner = self.canvas.create_oval(x - radius, y - radius, x + radius, y + radius, fill='white')

def create_rectangle_mouse_move(self, event):
    if self.corner:
        x, y = event.x, event.y
        x_, y_ = self.bottom_pos
        self.bottom_pos = (x, y)
        self.canvas.coords(self.rectangle, *self.top_pos, *self.bottom_pos)
        self.canvas.move(self.corner, x - x_, y - y_)

def create_rectangle_end(self, event):
    if self.corner:
        self.canvas.delete(self.corner)
        self.corner = None
        if self.bottom_pos != self.top_pos:
            self.rectangles.append(self.rectangle)
            self.canvas.itemconfig(self.rectangle, width=0)
        else:  # empty rectangle, skip
            self.canvas.delete(self.rectangle)
        self.rectangle = None
```

Exercise 25.1 (convex hull GUI)

Java vs Python

runestone.academy/ns/books/published/java4python/

Why should you know something about Java?

- Java is an example of a **statically typed object oriented** language (like C and C++) opposed to Python's being dynamically typed
- One of the most widespread used programming languages
- Used in other courses at the Department of Computer Science

Java history

- Java 1.0 released 1995 by Sun Microsystems (acquired by Oracle 2010)
- ”Write Once, Run Anywhere”
- 1999 improved performance by the **Java HotSpot Performance Engine**
- Current version Java 24 (released March 2025)
- Java compiler generates **Java bytecode** that is executed on a **Java virtual machine** (**JVM**) that contains a garbage collector

PyPy is adopting the same ideas to Python (Just-in-Time compilation)

Installing Java

- To compile Java programs into **bytecode** you need a compiler, e.g. from Java SE Development Kit (**JDK**):

  www.oracle.com/java/technologies/downloads/

  (you might need to add the JDK directory to your PATH, e.g. C:\Program Files\Java\jdk-18.0.1.1\bin)

- To only run compiled Java programs:

  java.com/download

  (If you use JDK, you should not download this)

Java IDE

- Many available, some popular: Visual Studie Code, IntelliJ IDEA, Eclipse, and NetBeans
- An IDE for beginners: BlueJ

Compiling and running a Java program

HelloWorld.java

```
public class HelloWorld {
    public static void main( String[] args ) {
        System.out.println( "Hello World!" );
    }
}
```

Command Prompt

```
C:\Users\au121\Desktop>javac HelloWorld.java

C:\Users\au121\Desktop>dir HelloWorld*
 Volume in drive C is OSDisk
 Volume Serial Number is 3CDB-90D8

 Directory of C:\Users\au121\Desktop

04-05-2020  17:40               426 HelloWorld.class
09-05-2019  21:18               132 HelloWorld.java
               2 File(s)            558 bytes
               0 Dir(s)  372.191.944.704 bytes free

C:\Users\au121\Desktop>java HelloWorld
Hello World!

C:\Users\au121\Desktop>
```

Java : `main`

- *name* `.java` must be equal to the `public class` *name*
- A class can only be excuted using `java` *name* (without `.class`) if the class has a class method `main` with signature

  `public static void main(String[] args)`

- (`main` is inherited from C and C++ sharing a lot of syntax with Java)
- Java convention is that class names should use CamelCase

PrintArguments.java

```
public class PrintArguments {
    public static void main( String[] args ) {
        for (int i=0; i<args.length; i++)
            System.out.println( args[i] );
    }
}
```

shell

```
> java PrintArguments x y z
| x
| y
| z
```

a `static` method in
a class is a class method
(exists without creating objects)

method name

there can be several classes
in a file – but only one class
should be `public` and have
same name as file

type of return value
(`void` = no return value)

class name containing `main`
must have same name as file

type of argument,
array of `String` values

PrintArguments.java

```
public class PrintArguments {
    public static void main( String[] args ) {
        for (int i=0; i<args.length; i++)
            System.out.println( args[i] );
    }
}
```

the `main` method must
be `public` to be visible
outside class

name of argument

For-loop equivalent to

```
int i = 0;
while (i < args.length) {
    code
    i++;
}
```

i += 1

declare new `int` variable
locally inside for-loop

the print statement is found
in the `System` class

java arrays are indexed from
`0` to `args.length - 1`
and the length of an array
object is fixed once created

Argument list also exists in Python…

PrintArguments.py

```
import sys
print(sys.argv)
```

shell

```
> python PrintArguments.py a b 42
| ['PrintArguments.py', 'a', 'b', '42']
```

Primitive.java

```java
/**
 * A Java docstring to be processed using 'javadoc'
 */
// comment until end-of-line
public class Primitive {
    public static void main( String[] args ) {
        int x;  // type of variable must be declared before used
        x = 1;  // remember ';' after each statement
           int y=2;  // indentation does not matter
    int a=3, b=4;  // multiple declarations and initialization
        System.out.println(x + y + a + b);
        int[] v={1, 2, 42, 3};  // array of four int
        System.out.println(v[2]);  // prints 42, arrays 0-indexed
/* multi-line comment
       that continues until here */
        v = new int[3];  // new array of size three, containing zeros
        System.out.println(v[2]);  // prints 0
        if (x == y) {  // if-syntax '(' and ')' mandatory
             a = 1;
             b = 2;
        } else {  // use '{' and '}' to create block of statements
             a = 4; b = 3;  // two statements on one line
        }
}}
```

Why state types – Python works without…

- Just enforcing a different programming style (also C and C++)
- Helps users to avoid mixing up values of different types
- (Some) type errors can be caught at compile time
- More efficient code execution

type_error.py

```
x = 3
y = 'abc'
print('program running...')
print(x / y)
```

Python shell

```
| program running...
...
| ----> 4 print(x / y)
| TypeError: unsupported operand type(s) for
  /: 'int' and 'str'
```

TypeError.java

```
public class TypeError {
    public static void main( String[] args ) {
        int x = 3;
        String y = "abc";
        System.out.println(x / y);
    }
}
```

shell

```
> javac TypeError.java
| javac TypeError.java
| TypeError.java:5: error: bad operand types for
  binary operator '/'
|         System.out.println(x / y);
|                            ^
|   first type:  int
|   second type: String
| 1 error
```

Basic Java types

Type	Values
`boolean`	`true` or `false`
`byte`	8 bit integer
`char`	character (16-bit UTF)
`short`	16 bit integer
`int`	32 bit integer
`long`	64 bit integer
`float`	32 bit floating bout
`double`	64 bit floating point
`class BigInteger`	arbitrary precision integers
`class String`	strings

BigIntegerTest.java

```java
import java.math.*;  // import everything
// import java.math.BigInteger;  // alternativ

public class BigIntegerTest {
    public static void main( String[] args ) {
        BigInteger x = new BigInteger("2");
        while (true) {
            // BigIntegers are immutable
            x = x.multiply(x);
            // java.math.BigInteger.toString()
            System.out.println(x);
        }
    }
}
```

shell

```
| 4
| 16
| 256
| 65536
| 4294967296
| 18446744073709551616
| 340282366920938463463374607431768211456
| ...
```

Java arrays

- The size of a builtin Java array can not be modified when first created.
  If you need a bigger array you have to instantiate a new array.
- Or better use a standard collection class like **ArrayList**
- **ArrayList** is a generic class (type of content is given by <*element type*>; generics available since Java 5, 2004)
- The for-each loop was introduced in Java 5

ConcatenateArrayLists.java

```java
import java.util.*;  // java.util contains ArrayList

public class ConcatenateArrayList {
    public static void main( String[] args ) {
        // ArrayList is a generic container
        ArrayList<String> a = new ArrayList<String>();
        ArrayList<String> b = new ArrayList<String>();
        ArrayList<String> c = new ArrayList<String>();

        a.add("A1");  // in Python .append
        a.add("A2");
        b.add("B1");

        c.addAll(a);  // in Python .extend
        c.addAll(b);

        for (String e : c) {  // foreach over iterator
            System.out.println(e);
        }
    }
}
```

shell

```
| A1
| A2
| B1
```

Tired of writing all these types…

- In Java 7 (2011) the "diamond operator" **<>** was introduced for type inference for generic instance creation to reduce verbosity
- In Java 10 (2018) the **`var`** keyword was introduced to type infer variables

ArrayListTest.java

```
import java.util.*;  // java.util contains ArrayList

public class ArrayListTest {
    public static void main( String[] args ) {
        // ArrayList is a generic container
        ArrayList<String> a = new ArrayList<String>(); // Full types
        List<String> b = new ArrayList<String>();      // ArrayList is subclass of class List
        ArrayList<String> c = new ArrayList<>();       // <> uses type inference
        List<String> d = new ArrayList<>();            // <> and ArrayList subclass of List
        var e = new ArrayList<String>();               // use var to infer type of variable
    ⚠   var v = Math.floor(1.5);                       // not obvious what type v is (double)
}}
```

Function arguments

- Must declare the number of arguments and their types, and the return type
- The argument types are part of the *signature* of the function
- Several functions can have the same name, but different type signatures
- Python keyword arguments, * and ** do not exist in Java

Functions.java

```java
public class Functions {
    private static int f(int x) {
        return x * x;
    }
    private static int f(int x, int y) {
        return x * y;
    }
    private static String f(String a, String b) {
        return a + b; // string concatenation
    }

    public static void main( String[] args ) {
        System.out.println(f(7));
        System.out.println(f(3, 4));
        System.out.println(f("abc", "def"));
    }
}
```

shell

```
49
12
abcdef
```

functions.py

```python
def f(x, y=None):
    if y == None:
        y = x
    if type(x) is int:
        return x * y
    else:
        return x + y
print(f(7), f(3, 4), f('abc', 'def'))
```

Class

- Constructor = method with name equal to class name (no return type)
- `this` = referes to current object (Python "self")
- Use `private` / `public` on attributes / methods to give access outside class
- Use `new` *name*(arguments) to create new objects

- There can be multiple constructors, but with distinct type signatures

AClass.java

```java
class Rectangle {
    private int width, height;  // declare attributes
    // constructor, class name, no return type
    public Rectangle(int width, int height) {
        this.width = width;
        this.height = height;
    }
    public Rectangle(int side) {
        width = side;  // same as this.width = side
        height = side;
    }
    public int area() {
        return width * height;
    }
}
public class AClass {
    public static void main( String[] args ) {
        Rectangle r = new Rectangle(6, 7);
        System.out.println(r.area());
    }
}
```

shell

```
| 42
```

Inheritance

- Java supports single inheritance using `extends`
- Attributes and methods that should be accessible in a subclass must be declared protected (or public)
- Constructors are not inherited but can be called using `super`

Inheritance.java

```java
class BasicRectangle {
    // protected allows subclass to access attributes
    protected int width, height;
    public BasicRectangle(int width, int height) {
        this.width = width; this.height = height;
    }
}
class Rectangle extends BasicRectangle {
    public Rectangle(int width, int height) {
        // call constructor of super class
        super(width, height);
    }
    public int area() {
        return width * height;
    }
}
public class Inheritance {
    public static void main( String[] args ) {
        Rectangle r = new Rectangle(6, 7);
        System.out.println(r.area());
    }
}
```

shell

```
| 42
```

Generic class

- Class that is parameterized by one or more types (comma separated)
- Primitive types cannot be type parameters
- Instead use *wrappers*, like Integer for int

GenericPair.java

```
class Pair<element> {
    private element x, y;
    public Pair(element x, element y) {
        this.x = x; this.y = y;
    }
    element first() { return x; }
    element second() { return y; }
}
public class GenericPair {
    public static void main( String[] args ) {
        var p = new Pair<Integer>(6, 7);
        System.out.println(p.first() * p.second());
    }
}
```

shell

```
| 42
```

Interface

- Java does not support multiple inheritance like Python
- But a class can implement an arbitrary number of interfaces
- An interface specifices a set of attributes and methods a class must have
- The type of a variable can be an interface, and the variable can hold any object where the class is stated to implement the interface

RectangleInterface.java

```
interface Shape {
    public int area(); // method declaration
}
class Rectangle implements Shape {
    private int width, height;
    // constructor, class name, no return type
    public Rectangle(int width, int height) {
        this.width = width; this.height = height;
    }
    public int area() {
        return width * height;
    }
}
public class RectangleInterface {
    public static void main( String[] args ) {
        Shape r = new Rectangle(6, 7);
        System.out.println(r.area());
    }
}
```

Abstract classes

- Abstract class = class that cannot be instantiated, labeled `abstract`
- Abstract method = method declared without definition, labeled `abstract`, must be in abstract class
- An abstract class can be extended to a non-abstract class by providing the missing method definitions

AbstractRectangle.java

```
abstract class Shape {
    abstract public int circumference();
    abstract public int area();
    public double fatness() {
        // convert int from area() to double before /
        return (double)area() / circumference();
    }
}
class Rectangle extends Shape {
    private int width, height;
    // constructor, class name, no return type
    public Rectangle(int width, int height) {
        this.width = width; this.height = height;
    }
    public int area() {
        return width * height;
    }
    public int circumference() {
        return 2 * (width + height);
    }
}
public class AbstractRectangle {
    public static void main( String[] args ) {
        Shape r = new Rectangle(6, 7);
        System.out.println(r.fatness());
    }
}
```

Default methods in interfaces

- Before Java 8 all methods in an interface were abstract (no definition)
- Since Java 8 interfaces can have **`default`** methods with definition
- The distinction between abstract classes and interfaces gets blurred
  - a class can only extend one abstract class
  - a class can implement more interfaces

  ⇒ multiple "inheritance" is possible in Java

DefaultInterface.java

```
interface Shape {
    public int circumference();
    public int area();
    default public double fatness() {
        // convert int from area() to double before /
        return (double)area() / circumference();
    }
}
class Rectangle implements Shape {
    private int width, height;
    // constructor, class name, no return type
    public Rectangle(int width, int height) {
        this.width = width; this.height = height;
    }
    public int area() {
        return width * height;
    }
    public int circumference() {
        return 2 * (width + height);
    }
}
public class DefaultRectangle {
    public static void main( String[] args ) {
        Shape r = new Rectangle(6, 7);
        System.out.println(r.fatness());
    }
}
```

Multiple Inheritance

- Class `C` implements both interfaces `A` and `B`
- Inherits default methods `sayA` and `sayB`
- Cannot inherit `sayHi`, since in both `A` and `B`. Must be overriden in `C`
- Can use `@override` to enforce compiler to check if method exists in super class
- `new A(){}` creates an instance of an *anonymous class* (extending or implementing A)

MultipleInheritance.java

```
interface A {
    default public void sayA() { System.out.println("say A"); }
    default public void sayHi() { System.out.println("A say's Hi"); }
}

interface B {
    default public void sayB() { System.out.println("say B"); }
    default public void sayHi() { System.out.println("B say's Hi"); }
}

class C implements A, B {
    @Override // (optional) requests compiler to
              // check if sayHi exists in supertype
    public void sayHi() {
        System.out.println("C say's Hi");
        (new A(){}).sayHi();  // instantiate an anonymous class
    }

    public void test() {
        sayA();
        sayB();
        sayHi();
    }
}

public class MultipleInheritance {
    public static void main( String[] args ) {
        new C().test();
    }
}
```

Shell output

```
say A
say B
C say's Hi
A say's Hi
```

Lambda expression

- Lambda expressions are possible since Java 8
- Syntax : *argument –> expression*

LambdaPrinting.java

```
import java.util.*;  // ArrayList

public class LambdaPrinting {
    public static void main(String[] args) {
        var elements = new ArrayList<Integer>();

        for (int i = 1; i <= 3; i++)
            elements.add(i);

        elements.forEach(e -> System.out.println(e));
    };
}
```

LambdaPrinting.java

```
1
2
3
```

Welcome to Java for Python Pro

https://runestone.academy/ns/books/published/java4python/index.html

java4python

Saving and Logging are Disabled

Welcome to Java for Python Programmers

Contents:

- 1. Java for Python Programmers
  - 1.1. Preface
  - 1.2. Introduction
  - 1.3. Why Learn another programming Language?
    - 1.3.1. Why Learn Java? Why not C or C++?
  - 1.4. Lets look at a Java Program
  - 1.5. Java Data Types
    - 1.5.1. Numeric
      - 1.5.1.1. Import
      - 1.5.1.2. Declaring Variables
      - 1.5.1.3. Input / Output / Scanner
    - 1.5.2. String
    - 1.5.3. List
    - 1.5.4. Arrays

Introduction to Programming with Scientific Applications

- Missing handins, deadline 15 May 2026
- Final project, deadline 31 May 2026
- Course evaluation
- Exam, 20 June 2026
- AOB

Exam

- **5 hours, written exam, with aids, including PC but without internet**
- **Communication with others about the exam is not permitted during the exam**
- **WISEflow Device Monitor must be enabled**
- **AI assistants are not allowed**
- Reexam in August
- Grade is an *overall assessment* of the implementation project and the exam
  - The result of the final exam must meet the minimum requirements for acceptance to be able to pass the course
  - The final exam contributes 80% to the final grade
- wiseflow.au.dk
  - Download .zip + add missing code + upload .zip
- Questions? – post them on Brightspace

Content of .zip file

A.py - C:\Users\au121\Desktop\ipsa22\ipsa22exam\A.py (3.11.3)

File Edit Format Run Options Window Help

```python
'''
    INTERVAL SUM

    Your task is to write a function interval_sum(i, j), that returns
    the sum i + (i + 1) + ... + j. Eg. for i = 10 and j = 13 the sum
    returned should be 10 + 11 + 12 + 13 = 46.

    Input:  Two lines, containing integers i and j, respectively.
            It is guaranteed that 1 <= i <= j <= 100.

    Output: The sum i + (i + 1) + ... + j.

    Example:

      Input:  10
              13

      Output: 46

    Note: The below code already handles the input and ouput.
'''


def interval_sum(i, j):
    # insert code
    pass


i = int(input())
j = int(input())
print(interval_sum(i, j))
```

Ln: 1 Col: 0

Exam questions

- tests
  - A
    - A.in1
    - A.in2
    - A.in3
    - A.in4
    - A.in5
    - A.out1
    - A.out2
    - A.out3
    - A.out4
    - A.out5
  - B
  - C
  - D
  - E
  - F
  - G
  - H
  - I
  - J
  - K
  - L
- __README__.txt
- A.py
- B.py
- C.py
- D.py
- E.py
- F.py
- G.py
- H.py
- I.py
- J.py
- K.py
- L.py
- run_tests.py

A.in1

Fil Rediger Vis

```
10
13
```

Ln 1, Col 1 100% Windows (CRLF) UTF-8

test input

A.out1

Fil Rediger Vis

```
46
```

Ln 1, Col 1 100% Windows (CRLF) UTF-8

test output

Command Prompt

```
(c) Microsoft Corporation. All rights reserved.

C:\Users\au121>cd Desktop\ipsa22\ipsa22exam

C:\Users\au121\Desktop\ipsa22\ipsa22exam>python run_tests.py A --verbose=-1

Tests passed:

  A       0/5
  -----------
  Total   0/5
  ===========

C:\Users\au121\Desktop\ipsa22\ipsa22exam>python run_tests.py A --verbose=3 --abort
A.py tests/A\A.in1 [failed]
  Input
  > 10
  > 13
  Correct output
  > 46
  Received output
*> None

C:\Users\au121\Desktop\ipsa22\ipsa22exam>
```

run_tests.py arguments

- A B C …
  exercises to evaluate
  default are all
- --abort
  stop on first error
- --verbose=*value*
  amount of output

* = line with wrong output

Evaluation of code

Don’t expect partial scores for this solution

```
def interval_sum(i, j):
    if i == 10 and j == 13:
        return 46
```

- Each problem will be assigned a **weight**
- There will be problems of **varying difficulty**
- Code will be evaluated on **known test cases** and **unknown test cases**
- In general, **automatic scoring**, in some exceptional cases manual

- Put a **comment if you copied code from exercises/slides/documentation** to avoid plagiarism

AOB ?