

# Introduction to Programming with Scientific Applications

Gerth Stølting Brodal  
Department of Computer Science  
Aarhus University



**Course evaluation**  
*“The first lecture was intimidating  
and overwhelming”*



# Lecturer

|           |   |
|-----------|---|
| Name      | Gerth Stølting Brodal   |
| Research  | Algorithms and Data Structures (Computer Science)   |
| Teaching  |   |
| 2018 -    | BSc course on Introduction to Programming with Scientific Applications  |
| 2003 -    | BSc course on Introduction to Algorithms and Data Structures  |
| 1999 - 17 | MSc courses on Computational Geometry, Algorithm Engineering,<br>Advanced Data Structures, External Memory Algorithms and Data Structures |
| Python    | Advanced Beginner   |

# Course description – [kursuskatalog.au.dk/en/course/138411/](https://kursuskatalog.au.dk/en/course/138411/)

## Introduction to Programming with Scientific Applications

### Description of qualifications

After the course the participants will have knowledge of principles and techniques for systematic **construction of programs**.

At the end of the course, the participants will be able to:

- apply constructions of a common programming language,
- develop **well-structured** programs and perform **testing** and **debugging** of these,
- explain fundamental programming concepts and basic algorithmic techniques,
- apply standard **tools for scientific applications**,
- use the documentation for a programming language and available software packages.

### Contents

The course gives an introduction to programming with scientific applications.

Programming concepts and techniques are introduced using the **Python** programming language.

The programming concepts are **illustrated in other programming languages**. The following content is included.

*Basic programming constructs:* Data types, operators, variables, flow of control, conditionals, loops, functions, recursion, scope, exceptions. *Object orientation:* Abstract data types, classes, inheritance, encapsulation. *Basic algorithmic techniques:* Sorting, binary search, dynamic programming. *Systematic development of programs:* Testing and debugging. File-based input/output, numerical analysis, functional programming. Scientific computing using standard packages for Python.

**ECTS** 10

### Hours - weeks - periods

Lectures 2 x 2 hours/week

TA sessions 1 x 3 hours/week

Study café 3 x 1 hour/week

### Language of instruction

Danish

### Instructor

Gerth Stølting Brodal

### Academic prerequisites

(Some) Linear algebra

### Exam

#### **5 hour programming**

Aid: Computer without Internet, no AI

7-point grading scale

### Prerequisites for examination participation

Submission and approval of 10 mandatory assignments and submission of

#### **1 implementation project**

**Notes** Grade reflects an overall assessment of implementation project and written examination. Project counts 20% and written exam counts 80%

# Question – Primary Education?

- a) Mathematics
- b) Mathematics-Economics
- c) Data Science
- d) Chemistry
- e) Physics
- f) Other Science-Technology
- g) Other

# Question – Programming languages you know?

+750 listed on [en.wikipedia.org/wiki/List\\_of\\_programming\\_languages](https://en.wikipedia.org/wiki/List_of_programming_languages)

# Question – Programming experience?

For the programming language you know best (if any) please state your proficiency level within the language.

- a) None
- b) Fundamental awareness (basic knowledge)
- c) Novice (limited experience)
- d) Intermediate (practical application)
- e) Advanced (applied theory)
- f) Expert (recognized authority)

# Some course practicalities

Primary lecture material = slides



|             | Monday     | Tuesday      | Wednesday  | Thursday | Friday |
|-------------|------------|--------------|------------|----------|--------|
| 8:15-9:00   | Lecture    |              |            |          |        |
| 9:15-10:00  |            | Hold 2       |            |          |        |
| 10:15-11:00 | Study cafe |              | Study cafe |          |        |
| 11:15-12:00 |            |              | Lecture    | MA1      |        |
| 12:15-13:00 |            |              |            |          |        |
| 13:15-14:00 |            |              |            |          |        |
| 14:15-15:00 |            |              | DV         |          |        |
| 15:15-16:00 |            |              |            |          |        |
| 16:15-17:00 |            | FY<br>Hold 1 | MØ1<br>MØ2 |          |        |
| 17:15-18:00 |            |              |            |          |        |




| Week | Monday | Tuesday     | Wednesday  | Thursday     | Friday     |
|------|--------|-------------|------------|--------------|------------|
| 5    | F1     | no TA class | F2         |              |            |
| 6    | F3     | TØ1         | TØ1 / F4   | TØ1          | TØ1        |
| 7    | F5     | TØ2         | TØ2 / F6   | TØ2          | TØ2        |
| 8    | F7     | TØ3         | TØ3 / F8   | TØ3          | TØ3        |
| 9    | F9     | TØ4         | TØ4 / F10  | TØ4          | TØ4        |
| 10   | F11    | TØ5         | TØ5 / F12  | TØ5          | TØ5        |
| 11   | F13    | TØ6         | TØ6 / F14  | TØ6          | TØ6        |
| 12   | F15    | TØ7         | TØ7 / F16  | TØ7          | TØ7        |
| 13   | F17    | TØ8         | TØ8 / F18  | TØ8          | TØ8        |
| 14   |        |             |            | Easter break |            |
| 15   |        | -           | -          |              | TØ9 TØ9    |
| 16   | F19    | TØ9         | TØ9 / F20  | TØ10         | TØ10       |
| 17   | F21    | TØ10        | TØ10 / F22 | TØ11         | Kapsejlads |
| 18   | F23    | TØ11        | TØ11 / F24 | TØ12         | TØ11       |
| 19   | F25    | TØ12        | TØ12 / F26 | TØ13         | TØ12       |
| 20   | F27    | TØ13        | TØ13 / -   | Kr HimFart   | TØ13       |

# Course page on Brightspace and GitHub



gsbrodal.github.io/ipsa




The screenshot shows a comparison between a Brightspace course page and a corresponding GitHub page for the same course. The GitHub page is a static website for the course "Introduction to Programming with Scientific Applications" offered by Aarhus University's Department of Computer Science. It includes:

- A header with the course title and a Python code snippet.
- A "Welcome" section with a brief introduction and the lecturer's name, Gerth Stølting Brodal.
- A "Course content" section with a detailed outline of topics covered in the course.
- A portrait photo of the lecturer, Gerth Stølting Brodal.


The Brightspace course page on the left shows the same content structure but lacks the GitHub-specific features like the code snippet and the portrait photo.

# Course text book – optional



John V. Guttag: **Introduction to Computation and Programming Using Python, Third Edition With Application to Computational Modeling and Understanding Data.** Third Edition. 664 pages. MIT Press, 2021.


- *[Guttag, 2<sup>nd</sup> Ed., page 8] "The reader should be forewarned that this book is by no means a comprehensive introduction to Python". 3<sup>rd</sup> Ed. added about 80 pages on introduction to Python.*
- *Covers all basic features of Python enabling you to deal with data in Chapters 1-10 (212 pages) - remaining chapters are applications*
- *Other resources: Google, stackoverflow, Python.org, YouTube, Als...*




Comparison to a standard text book on the *programming language* Python by Cay Horstmann and Rance Necaise:

Topic **recursion** is covered by Guttag on page 123 (2<sup>nd</sup> edition on page 50), Horstmann and Necaise do it on page 611


# Some other books on Python




O'Reilly, 2013  
1684 pages




Wiley, 2016  
752 pages



Addison-Wesley, 2015  
794 pages



Wiley, 2013  
580 pages



FRANKLIN, BEEDLE  
INDEPENDENT PUBLISHERS SINCE 1985

Franklin & Beedle, 2016  
552 pages

... numerous online introduction texts/courses/videos on Python


# Two Python programs

# A Python program

Python shell

```
> x = 7
> print(x * x)
| 49
```

Memory



- 7 is an *integer literal* – in Python denoted an “int”
- x is the name of a *variable* that can hold some value
- = is assigning a value to a variable
- \* denotes multiplication
- print is the name of a built-in *function*,  
here we call print to print the result of  $7 * 7$
- A program consists of a sequence of *statements*, executed sequentially

# Question – What is the result of this program?

```
Python shell
> x = 3
> y = 5
> x = 2
> print(x * y)
```



x assigned new value


- a) 10
- b) 15
- c) 25
- d) [15, 10]
- e) Error
- f) Don't know

# Another Python program using lists

## Python shell

```
> a = [13, 27, 7, 42]
> print(a)
| [13, 27, 7, 42]
> print(a[2])
| 7
```

## Memory



- `[13, 27, 7, 42]` is a *list* containing four integers
- `a[2]` refers to the entry in the list with *index 2*  
(the first element has index 0, i.e. `a[2]` is the 3<sup>rd</sup> element of the list)
- Note that `print` also can print a list

# Question – What is the result of this program?

Python shell

```
> a = [3, 5, 7]
> print(a[1] + a[2])
```

- a) 8
- b) 10
- c) 12
- d) 15
- e) Don't know

# Why Python ?



the next slides will be technical

# TIOBE Index January 2026




| Jan 2026 | Jan 2025 | Change | Programming Language | Ratings |        |
|----------|----------|--------|----------------------|---------|--------|
| 1        | 1        |        | Python               | 22.61%  | -0.61% |
| 2        | 4        |        | C                    | 10.99%  | +2.13% |
| 3        | 3        |        | Java                 | 8.71%   | -1.44% |
| 4        | 2        |        | C++                  | 8.67%   | -1.62% |
| 5        | 5        |        | C#                   | 7.39%   | +2.94% |
| 6        | 6        |        | JavaScript           | 3.03%   | -1.17% |
| 7        | 9        |        | Visual Basic         | 2.41%   | +0.04% |
| 8        | 8        |        | SQL                  | 2.27%   | -0.14% |
| 9        | 11       |        | Delphi/Object Pascal | 1.98%   | +0.19% |
| 10       | 18       |        | R                    | 1.82%   | +0.81% |

The TIOBE Programming Community index is an indicator of the **popularity of programming languages**. The index is updated once a month. The ratings are based on the number of skilled engineers world-wide, courses and third party vendors. Popular search engines such as Google, Bing, Yahoo!, Wikipedia, Amazon, YouTube and Baidu are used to calculate the ratings. It is important to note that the TIOBE index is not about the *best* programming language or the language in which *most lines of code* have been written.

# Popularity of programming languages

TIOBE Programming Community Index

Source: [www.tiobe.com](http://www.tiobe.com)



# “Hello World”

- In Java, C, C++ a lot of “{”, “}” and “;” are needed
- Java tends to have a lot of “public...” details that need to be spelled out
- Python is concise

## Java

```
public class HelloWorld {  
    public static void main( String[] args ) {  
        System.out.println( "Hello World!" );  
        System.exit( 0 );  
    }  
}
```

## C

```
#include <stdio.h>  
  
int main(int argc, char **argv) {  
    printf("Hello World");  
    return 0;  
}
```

## C++

```
#include <iostream>  
using namespace std;  
  
int main(int argc, char** argv) {  
    cout << "Hello, World!";  
    return 0;  
}
```

## Python 2

```
print "Hello world"
```

## Python 3

```
print("Hello world")
```

# Why Python ?

- Short concise code


(C developed by Dennis Ritchie 1969-73)

# C index out of bounds

**Debugging** is the process of finding and resolving defects or problems within a computer program that prevent correct operation of computer software or a system.

[en.wikipedia.org/wiki/Debugging](https://en.wikipedia.org/wiki/Debugging)

Memory



"A" only has size 2, but tries to update the 4<sup>th</sup> entry.  
No warning is giving.  
Something unexpected is overridden in memory.  
**Have fun debugging!**

indexing.c


```
#include <stdio.h>
int main() {
    int x = 1;
    int A[2] = {2, 3}; // A[0] = 2, A[1] = 3
    printf("x = %d, A = {%d, %d}\n", x, A[0], A[1]);
    A[3] = 42; // index A[3] out of bounds
    printf("x = %d, A = {%d, %d}\n", x, A[0], A[1]);
    return 0;
}
```

Output

```
$ gcc indexing.c
$ ./a.exe
x = 1, A = {2, 3}
x = 42, A = {2, 3}
```

Skipping checking for invalid indexing makes programs faster,  
but also requires disciplined programming

# ... and C++ index out of bounds




## indexing.cpp

```
#include <iostream>
int main() {
    int x = 1;
    int A[2] = {2, 3}; // A[0] = 2, A[1] = 3
    std::cout << "x = " << x << ", A = {" 
                  << A[0] << ", " << A[1] << "}" << std::endl;
    A[2] = 42; // index A[2] out of bounds
    std::cout << "x = " << x << ", A = {" 
                  << A[0] << ", " << A[1] << "}" << std::endl;
    return 0;
}
```

## Output

```
$ g++ indexing.cpp
$ ./a.exe
x = 1, A = {2, 3}
x = 42, A = {2, 3}
```

# ... and C++ vector index out of bounds



## indexing.cpp

```
#include <iostream>
#include <vector>


int main() {
    std::vector<int> A = {2, 3}; // A[0] = 2, A[1] = 3
    std::vector<int> B = {4, 5}; // B[0] = 4, B[1] = 5
    std::cout << "A={" << A[0] << ", " << A[1] << "}, ";
    std::cout << "B={" << B[0] << ", " << B[1] << "}" << std::endl;
    A[9]=42; // index A[9] out of bounds
    std::cout << "A={" << A[0] << ", " << A[1] << "}, ";
    std::cout << "B={" << B[0] << ", " << B[1] << "}" << std::endl;
    return 0;
}
```

## Output

```
$ g++ -std=c++11 indexing-vector.cpp
$ ./a.exe
A={2, 3}, B={4, 5}
A={2, 3}, B={4, 42}
```

# ... and Java index out of bounds exception

Memory



## indexing.java

```
class IndexingTest{
    public static void main(String args[]) {
        int a[] = {20, 21, 22};
        a[5] = 42; // index a[5] out of bounds
    }
}
```


## Output

```
$ javac indexing.java
$ java IndexingTest
Exception in thread "main"
java.lang.ArrayIndexOutOfBoundsException: 5
        at IndexingTest.main(indexing.java:5)
```

Java provides error message when running the program

# ... and Python index out of bounds exception

Memory



## indexing.py

```
a = [20, 21, 22]
a[5] = 42 # index a[5] out of bounds
```

## Output

```
$ python indexing.py
Traceback (most recent call last):
  File "indexing.py", line 3, in <module>
    a[5] = 42
IndexError: list assignment index out of range
```

Python provides error message when running the program

# Memory safety

The White House 2024 | Press Release: “Future Software Should Be Memory Safe” ([www.whitehouse.gov](http://www.whitehouse.gov))


National Security Agency 2022 | Cybersecurity Information Sheet: *Software Memory Safety* ([media.defense.gov](http://media.defense.gov))

- C and C++ are flexible but **memory unsafe** programming languages
  - Unintended writes or reads to memory can be exploited by malicious cyber actors 
- Python, Java, Rust are examples of memory safe languages
- Rust aims at achieving the efficiency of C by slightly restricting flexibility

`indexing.rs`

```
fn main() {
    let mut a = [3, 4];
    a[2] = 7; // Compile error: this operation will panic at runtime
    for i in 2..3 { a[i] = 7 } // Run-time panic: index out of bounds
    let b = &mut a;
    a[1] = 6; // Compile error: cannot use `a` because it was mutably borrowed
    (*b)[0] = 5;
    for i in 0..2 { println!("a[{}] = {}", i, a[i]) }
}
```

[www.rust-lang.org](http://www.rust-lang.org)



# Why Python ?

- Short concise code
- **Index out-of-range exceptions**

# C++ different ways to print a vector

**vector-iterator.cpp**

```
#include <iostream>
#include <vector>
int main() {
    // Vector is part of STL (Standard Template Library)
    std::vector<int> A = {20, 23, 26};
    // "C" indexing - since C++98
    for (int i = 0; i < A.size(); i++)
        std::cout << A[i] << std::endl;
    // iterator - since C++98
    for (std::vector<int>::iterator it = A.begin(); it != A.end(); ++it)
        std::cout << *it << std::endl;
    // "auto" iterator - since C++11
    for (auto it = A.begin(); it != A.end(); ++it)
        std::cout << *it << std::endl;
    // Range-based for-loop - since C++11
    for (auto e : A)
        std::cout << e << std::endl;
}
```

elegant

# Java - different ways to print a vector

**vector-iterator.java**

```
import java.util.Vector;
import java.util.Iterator;

class IteratorTest{
    public static void main(String[] args) {
        Vector<Integer> a = new Vector<Integer>();
        a.add(7);
        a.add(42);
        // "C" for-loop & get method
        for (int i = 0; i < a.size(); i++)
            System.out.println(a.get(i));
        // iterator
        for (Iterator it = a.iterator(); it.hasNext(); )
            System.out.println(it.next());
        // for-each loop - since Java 5
        for (Integer e : a)
            System.out.println(e);
    }
}
```

elegant

# The Python way to print a list

**print-list.py**

```
a = [20, 23, 26]

for e in a:
    print(e)
```

**Output**

```
$ python print-list.py
20
23
26
```

# Why Python ?

- Short concise code
- Index out of range exceptions
- **Elegant for-each loop**

```
$ g++ -std=c++11 print-vector.cpp
cpp-error-message.cpp: In function 'int main()':
cpp-error-message.cpp:7:13: error: no match for 'operator<<' (operand types are 'std::ostream [aka std::basic_ostream<char>]' and 'std::vector<int>')
    std::cout << A << std::endl;
                                         ^
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39:0,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:628:5: note: candidate: std::basic_ostream<_CharT, _Traits>& std::operator<<(std::basic_ostream<_CharT, _Traits>&, const _Tp&) [with _CharT = char; _Traits = std::char_traits<char>; _Tp = std::vector<int>] <near match>
        operator<<(basic_ostream<_CharT, _Traits>&, _os, const _Tp& __x)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:628:5: note:   conversion of argument 1 would be ill-formed:
cpp-error-message.cpp:7:16: error: cannot bind 'std::ostream [aka std::basic_ostream<char>]' lvalue to 'std::basic_ostream<char>&'
    std::cout << A << std::endl;
                                         ^
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ios:39:0,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:108:7: note: candidate: std::basic_ostream<_CharT, _Traits>& std::operator<<(std::basic_ostream<_CharT, _Traits>&, std::ostream_type& __os) [with _CharT = char; _Traits = std::basic_ostream<_CharT, _Traits>; _ostream_type = std::basic_ostream<char>]
        operator<<(_ostream_type& (*__pf) (_ostream_type))
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:108:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::basic_ostream<char>::_ostream_type& (*)(std::basic_ostream<char>::_ostream_type&) (aka std::basic_ostream<char>& (*) (std::basic_ostream<char>))'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:117:7: note: candidate: std::basic_ostream<_CharT, _Traits>:: ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(std::basic_ostream<_CharT, _Traits>::_ios_type& (*)(std::basic_ostream<_CharT, _Traits>::_ios_types)) [with _CharT = char; _Traits = std::basic_ostream<_CharT, _Traits>::_ios_type = std::basic_ios<char>]
        operator<<(_ios_type& (*__pf) (_ios_type))
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:117:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::basic_ostream<char>::_ios_type& (*)(std::basic_ostream<char>::_ios_type) (aka std::basic_ios<char>& (*) (std::basic_ios<char>))'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:127:7: note: candidate: std::basic_ostream<_CharT, _Traits>:: ostream_type& std::basic_ostream<_CharT, _Traits>::operator<<(std::ios_base& (*)(std::ios_base)) [with _CharT = char; _Traits = std::basic_ostream<char>::_ios_type = std::ios_base]
        operator<<(_ios_base& (*__pf) (_ios_base))
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:127:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:166:7: note: candidate: std::basic_ostream<_CharT, _Traits>:: operator<<(long _n)
        operator<<(_long _n)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:166:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:170:7: note: candidate: std::basic_ostream<_CharT, _Traits>:: operator<<(_unsigned long _n)
        operator<<(_unsigned long _n)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:170:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:174:7: note: candidate: std::basic_ostream<_CharT, _Traits>:: operator<<(_bool _n)
        operator<<(_bool _n)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:174:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:638:0,
                 from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:91:5: note: candidate: std::basic_ostream<_CharT, _Traits>:: operator<<(_unsigned short _n)
        operator<<(_unsigned short _n)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:91:5: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39:0,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:181:7: note: candidate: std::basic_ostream<_CharT, _Traits>:: operator<<(_unsigned short _n)
        operator<<(_unsigned short _n)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:181:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:638:0,
                 from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:105:5: note: candidate: std::basic_ostream<_CharT, _Traits>:: operator<<(_long long _n)
        operator<<(_long long _n)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/bits/ostream.tcc:105:5: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
In file included from /usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/iostream:39:0,
                 from cpp-error-message.cpp:1:
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:192:7: note: candidate: std::basic_ostream<_CharT, _Traits>:: operator<<(_long long _n)
        operator<<(_long long _n)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:192:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:192:7: note: candidate: std::basic_ostream<_CharT, _Traits>::operator<<(double) [with _CharT = char; _Traits = std::basic_ostream<char>::_traits<char>]
        operator<<(double _f)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:220:7: note: candidate: std::basic_ostream<_CharT, _Traits>::operator<<(float) [with _CharT = char; _Traits = std::basic_ostream<char>::_traits<char>]
        operator<<(float _f)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:224:7: note: candidate: std::basic_ostream<_CharT, _Traits>::operator<<(long double) [with _CharT = char; _Traits = std::basic_ostream<char>::_traits<char>]
        operator<<(long double _f)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:224:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:232:7: note: candidate: std::basic_ostream<_CharT, _Traits>::operator<<(const void*) [with _CharT = char; _Traits = std::basic_ostream<char>::_traits<char>]
        operator<<(const void* _v)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:245:7: note: candidate: std::basic_ostream<_CharT, _Traits>::operator<<(long double)
        operator<<(long double _f)
                           ^
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:232:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
/usr/lib/gcc/x86_64-pc-cygwin/5.4.0/include/c++/ostream:245:7: note:   no known conversion for argument 1 from 'std::vector<int>' to 'std::ios_base& (*)(std::ios_base)'
```

# C++ how not to print a vector

## print-vector.cpp

```
#include <iostream>
#include <vector>


int main() {
    std::vector<int> A = {2, 3};
    std::cout << A << std::endl;
    return 0;
}
```

C++ vectors cannot be printed directly –  
mistake results in +200 lines of error messages

# Why Python ?

- Short concise code
- Index out of range exceptions
- Elegant for-each loop
- **Python hopefully better error messages than C++**

# Python and garbage collection




# Why Python ?

- Short concise code
- Index out of range exceptions
- Elegant for-each loop
- Python hopefully better error messages than C++
- **Garbage collection is done automatically**

# Python performance vs C, C++ and Java

Compute sum  $1 + 2 + 3 + \dots + n = \frac{n^2}{2} + \frac{n}{2}$



$$1 + 2 + \cdots + n$$

### add.py

```
import sys

n = int(sys.argv[1])
sum = 0
for i in range(1, n + 1):
    sum += i
print("Sum =", sum)
```

### add.c

```
#include <stdio.h>
#include <stdlib.h>

int main(int argc, char *argv[]) {
    int n = atoi(argv[1]);
    int sum = 0;
    for (int i = 1; i <= n; i++)
        sum += i;
    printf("Sum = %d\n", sum);
}
```

### add.cpp

```
#include <iostream>
#include <cstdlib>
using namespace std;

int main(int argc, char *argv[]) {
    int n = atoi(argv[1]);
    int sum = 0;
    for (int i = 1; i <= n; i++)
        sum += i;
    cout << "Sum = " << sum << endl;
}
```

### add.java

```
class Add{
    public static void main(String args[]){
        int n = Integer.parseInt(args[0]);
        int sum = 0;
        for (int i = 1; i <= n; i++)
            sum += i;
        System.out.println("Sum = " + sum);
    }
}
```

# Timing results

| n      | C (gcc 9.2) | C++, int (g++ 9.2 ) | C++, long (g++ 9.2 ) | Java (12.0) | CPython (3.8.1) | PyPy (7.3.0) | Numba, int64 |
|--------|-------------|---------------------|----------------------|-------------|-----------------|--------------|--------------|
| $10^7$ | 0.001 sec*  | 0.001 sec*          | 0.003 sec            | 0.006 sec*  | 1.5 sec         | 0.27 sec     | 0.002 sec    |
| $10^9$ | 0.10 sec**  | 0.10 sec**          | 0.30 sec             | 0.40 sec**  | 145 sec         | 27 sec       | 0.2 sec      |

## Wrong output (overflow)

\* -2004260032 instead of 50000005000000

**\*\*** -243309312 instead of 500000000500000000

- since C, C++, and Java only uses 32 bits to represent integers (and 64 bits for "long" integers)

Have fun  
debugging!

|                        |   |
|------------------------|---|
| Bit position           | 66666666655555554444444433333333222222221111111110000000000<br>9876543210987654321098765432109876543210987654321098765432109876543210 |
| bin(10**9)             | 111011100110101100101000000000  |
| bin(500000500000)      | 101101011100110001000100010010110101101000000   |
| bin(-2004260032+2**32) | 10001000100010010110101101000000  |
| bin(5000000050000000)  | 110111100000101101101011001111000101111110110010100000000   |
| bin(-243309312+2**32)  | 11110001011111101100101000000000  |

# Timing results


| n      | C (gcc 9.2) | C++, int (g++ 9.2 ) | C++, long (g++ 9.2 ) | Java (12.0) | Python (3.8.1) | PyPy (7.3.0) | Python<br>Numba, int64 |
|--------|-------------|---------------------|----------------------|-------------|----------------|--------------|------------------------|
| $10^7$ | 0.001 sec*  | 0.001 sec*          | 0.003 sec            | 0.006 sec*  | 1.5 sec        | 0.27 sec     | 0.002 sec              |
| $10^9$ | 0.10 sec**  | 0.10 sec**          | 0.30 sec             | 0.40 sec**  | 145 sec        | 27 sec       | 0.2 sec                |

- Relative speed

**C ≈ C++ > Java >> Python**


- C, C++, Java need to care about integer overflows – select integer representation carefully with sufficient number of bits (8, 16, 32, 64, 128)
- Python natively works with arbitrary long integers (as memory on your machine allows). Also possible in Java using the class `java.math.BigInteger`
- Python programs can (sometimes) run faster using PyPy
- Number crunching in **Python** should be delegated to **specialized modules (e.g. Numpy, CPLEX, Numba)** – often written in C or C++ and requires selecting right integer representation

# Interpreter vs Compiler




# Why Python ?

- Short concise code
- Index out of range exceptions
- Elegant for-each loop
- Python hopefully better error messages than C++
- Garbage collection is done automatically
- **Exact integer arithmetic (no overflows)**
- **Can delegate number crunching to C, C++, ...**



# This course



# Course overview

Basic programming  
Advanced / specific python  
Libraries & applications

|                            |                                    |                                     |
|----------------------------|------------------------------------|-------------------------------------|
| 1. Introduction to Python  | 10. Functions as objects           | 19. Linear programming              |
| 2. Python basics / if      | 11. Object oriented programming    | 20. Generators, iterators, with     |
| 3. Basic operations        | 12. Class hierarchies              | 21. Modules and packages            |
| 4. Lists / while / for     | 13. Exceptions and files           | 22. Working with text               |
| 5. Tuples / comprehensions | 14. Doc, testing, debugging        | 23. Relational data                 |
| 6. Dictionaries and sets   | 15. Decorators                     | 24. Clustering                      |
| 7. Functions               | 16. Dynamic programming            | 25. Graphical user interfaces (GUI) |
| 8. Recursion               | 17. Visualization and optimization | 26. Java vs Python                  |
| 9. Recursion and Iteration | 18. Multi-dimensional data         | 27. Final lecture                   |

10 handins  
1 final project (last 1 month)

# History of Python development

- Python created by Guido van Rossum in 1989, first release 0.9.0 1991
- Python 2 → Python 3 (clean up of Python 2 language)
  - Python 2 – version 2.0 released 2000, final version 2.7 released mid-2010
  - Python 3 – released 2008, current release 3.13.1
- Python 3 is *not* backward compatible, libraries incompatible

| Python 2                                | Python 3  |
|---|---|
| print 42                                | print(42)   |
| int = C long (32 bits)                  | int = arbitrary number of digits (= named “long” in Python 2)   |
| 7/3 → 2 returns “int”                   | 7/3 → 2.333... returns “float”                                  |
| range() returns list (memory intensive) | range() returns iterator (memory efficient; xrange in Python 2) |

# Python.org

The screenshot shows the Python.org homepage with several red arrows highlighting different features:

- A red arrow points from the top right towards the search bar and the "Documentation" button.
- A red arrow points from the middle right towards the "Download Python and IDLE" button.
- A red arrow points from the bottom left towards the "Get Started" section.

**Top Navigation Bar:**

- Python
- PSF
- Docs
- PyPI
- Jobs
- Community

**Header Area:**

- python™ logo
- Donate button
- Search bar with placeholder "+500,000 Python packages"
- GO button
- Socialize link

**Main Navigation Bar:**

- About
- Downloads
- Documentation
- Community
- Success Stories
- News
- Events

**Content Sections:**

- Documentation:** A code snippet demonstrating a for loop:

```
# For loop on a list
>>> numbers = [2, 4, 6, 8]
>>> product = 1
>>> for number in numbers:
...     product = product * number
...
>>> print('The product is:', product)
The product is: 384
```
- All the Flow You'd Expect:** Text explaining Python's control flow statements: `if`, `for`, `while`, and `range`.
- Download Python and IDLE:** A yellow button for downloading Python.
- Footer Call-to-Action:** Text: "Python is a programming language that lets you work quickly and integrate systems more effectively." followed by a "» Learn More" link.
- Footer Links:**
  - Get Started:** Text: "Whether you're new to programming or an experienced developer, it's easy to learn and use Python." Link: "Start with our Beginner's Guide".
  - Download:** Text: "Python source code and installers are available for download for all versions!" Link: "Latest: Python 3.11.1".
  - Docs:** Text: "Documentation for Python's standard library, along with tutorials and guides, are available online." Link: "docs.python.org".
  - Jobs:** Text: "Looking for work or have a Python related position that you're trying to hire for? Our **relaunched community-run job board** is the place to go." Link: "jobs.python.org".

# Installing Python

The image shows a screenshot of the Python website and a Windows installer window side-by-side.

**Python Website (Left):**


- The top navigation bar includes links for Python, PSF, Docs, PyPI, Jobs, and Community.
- The main header features the Python logo and the word "python" in lowercase.
- A red circle labeled "1" highlights the "Downloads" tab in the main menu.
- A secondary red circle labeled "2" highlights the "Python 3.11.1" button under the "Download for Windows" section.

**Windows Installer Window (Right):**

- The title bar says "Python 3.11.1 (64-bit) Setup".
- The main area is titled "Install Python 3.11.1 (64-bit)" with the sub-instruction "Select Install Now to install Python with default settings, or choose Customize to enable or disable features."
- A red circle labeled "4" highlights the "Install Now" button.
- Below the "Install Now" button, it says "Includes IDLE, pip and documentation" and "Creates shortcuts and file associations".
- At the bottom, there's a "Customize installation" section with the sub-instruction "Choose location and features".
- Checkboxes at the bottom include "Use admin privileges when installing py.exe" (unchecked) and "Add python.exe to PATH" (checked).
- A large red arrow points from the "IMPORTANT" text below the website screenshot towards the "Add python.exe to PATH" checkbox in the installer window.

# Running the Python Interpreter from a terminal

- Open Command Prompt  
(Windows-key + cmd)
- Type “python” + return
- Start executing  
Python statements
- To exit shell:  
Ctrl-Z + return or  
`exit()` + return
- Note: Sometimes “python”  
is installed as “python3”



```
C:\ Command Prompt
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>

C:\ Command Prompt - python
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>python
Python 3.6.4 (v3.6.4:d48eceb, Dec 19 2017, 06:04:45) [MSC v.1900 32 bit (Intel)] on win32
Type "help", "copyright", "credits" or "license" for more information.
>>> -
```

```
C:\ Command Prompt - python
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.


C:\Users\au121>python
Python 3.6.4 (v3.6.4:d48eceb, Dec 19 2017, 06:04:45) [MSC v.1900 32 bit (Intel)] on win32
Type "help", "copyright", "credits" or "license" for more information.
>>> print(6*5+3*4)
42
>>>
```

# Installing IPython – A more powerful interactive Python shell

- Open Command Prompt
  - Execute:  

```
pip install ipython
```
  - Start IPython  

```
ipython
```
- 
- pip = the Python package manager
  - Note: Sometimes “pip” is installed as “pip3”



The image shows two side-by-side screenshots of a Microsoft Windows Command Prompt window. The top screenshot shows the command `pip install ipython` being typed at the prompt. The bottom screenshot shows the IPython shell running, displaying its version information and a green "In [1]:" prompt.

**Top Screenshot (Command Prompt):**

```
C:\ Command Prompt
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>pip install ipython
```

**Bottom Screenshot (IPython Shell):**

```
c:\ IPython: C:\Users\au121
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>ipython
Python 3.6.4 (v3.6.4:d48eceb, Dec 19 2017, 06:04:45) [MSC v.1900 32 bit (Intel)]
Type 'copyright', 'credits' or 'license' for more information
IPython 6.2.1 -- An enhanced Interactive Python. Type '?' for help.

In [1]:
```

# Some other usefull packages

- Try installing some more Python packages:

pip install numpy

linear algebra support (N-dimensional arrays)

pip install scipy

numerical integration and optimization


pip install matplotlib

2D and 3D plotting library

pip install pylint

Python source code analyzer enforcing a coding standard


# Creating a Python program the very basic way



A screenshot of a Windows Notepad window titled "my-first-python-program.py - Notepad". The window contains the following Python code:

```
x = 3
y = 4
print(x * y)
```

The status bar at the bottom right shows "Ln 1, Col 1".



A screenshot of a Windows Command Prompt window titled "Command Prompt". The window shows the following terminal session:

```
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Users\au121>cd Desktop

C:\Users\au121\Desktop>dir
Volume in drive C is OSDisk
Volume Serial Number is 3CDB-90D8

Directory of C:\Users\au121\Desktop

30-01-2018  16:45    <DIR>      .
30-01-2018  16:45    <DIR>      ..
30-01-2018  16:40    <DIR>      ipsa18
30-01-2018  16:44            26 my-first-python-program.py
                           1 File(s)   26 bytes
                           3 Dir(s)  420.462.858.240 bytes free

C:\Users\au121\Desktop>python my-first-python-program.py
12

C:\Users\au121\Desktop>
```

- Open Notepad (orTextEdit on Mac)
  - write a simple Python program
  - save it
- Open a command prompt
  - go to folder (using cd)
  - run the program using

python <program name>.py

# ... or open IDLE and run program with F5

enable  
line numbers  
under options



```
my-first-python-program.py - C:\Users\au121\Desktop\my-first-python-program.py (3.11.0)
File Edit Format Run Options Window Help
1 x = 3
2 y = 4
3 print(x *y)
4
Ln: 4 Col: 0
```

```
IDLE Shell 3.11.0
File Edit Shell Debug Options Window Help
Python 3.11.0 (main, Oct 24 2022, 18:26:48) [MSC v.1933 64 bit (AMD64)] on win32
Type "help", "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\au121\Desktop\my-first-python-program.py =====
12
>>>
Ln: 6 Col: 0
```

- IDLE ships with Python from [python.org](https://www.python.org)
- Good beginner IDE (Integrated Development Environment)

# The Python Ecosystem

- **Interpreters/compiler**
  - CPython – reference C implementation from [python.org](http://python.org)
  - PyPy – written in RPython (a subset of Python) – faster than CPython
  - Jython – written in Java and compiles to Java bytecode, runs on the JVM
  - IronPython – written in C#, compiles to Microsoft's Common Language Runtime (CLR) bytecode
  - Cython – project translating Python-ish code to C
- **Shells (IPython, IDLE, Jupyter)**
- **Libraries/modules/packages**
  - [pypi.python.org/pypi](http://pypi.python.org/pypi) (PyPI - the Python Package Index, +500.000 packages)
- **IDEs (Integrated development environment)**
  - IDLE comes with Python ([docs.python.org/3/library/idle.html](http://docs.python.org/3/library/idle.html))
  - Anaconda w. Spyder, IPython ([www.anaconda.com/download](http://www.anaconda.com/download))
  - Canopy ([enthought.com/product/canopy](http://enthought.com/product/canopy))
  - Visual Studio Code ([code.visualstudio.com](http://code.visualstudio.com))
  - Python tools for Visual Studio ([github.com/Microsoft/PTVS](http://github.com/Microsoft/PTVS))
  - PyCharm ([www.jetbrains.com/pycharm/](http://www.jetbrains.com/pycharm/))
  - Emacs (Python mode and ElPy mode)
  - Notepad++

Good beginner Python IDE


Visual Studio Code is used by more than twice as many developers than its nearest alternative, [Stack overflow survey 2025](#)
- **Python Style guide (PEP8)**
  - pylint, pep8, flake8
- **Python online**
  - Google colab ([colab.research.google.com](http://colab.research.google.com)), repl.it, sagemath.org, ...
- **Pair programming plugins (share your editor with others)**
  - PyCharm : [Code With Me](#)
  - Visual Studio Code : [Live Share](#)

Try to google "[best ide python](#)"



# IDEs and AI assistants

- Some IDEs integrate AI assistants to support code suggestions, e.g. [GitHub Copilot](#) in [VS Code](#)
- AI assistants increase productivity if you understand their output
- Interacting with an AI assistant can be a great programming tutor
-  ■ AI assistants are not allowed at the exam



A screenshot of the Visual Studio Code interface. The title bar shows "binomial.py - Visual Studio Code". The left sidebar has a file icon with a blue dot (1) and a search icon. The main editor area contains Python code for calculating binomial coefficients:

```
C: > Users > au121 > Desktop > binomial.py > binomial
1 # Compute binomial coefficients
2
3 def binomial(n, k):
    if k > n:
        return 0
    if k == 0 or k == n:
        return 1
    return binomial(n-1, k-1) + binomial(n-1, k)
```

A red arrow points from the word "suggestion" to the code completion placeholder "def binomial(n, k):". The status bar at the bottom shows "Ln 3, Col 20" and "Python 3.11.2 64-bit".

Guido van Rossum, inventor of Python, on GitHub Copilot  
*"I use it every day. It writes a lot of code for me... and usually it is slightly wrong but it still saves me typing."*  
[Python and the Future of Programming](#), Guido van Rossum interviewed by Lex Fridman

# PROGRAMMER'S PROBLEM

