## clock.xbe

## **Attributes**

```
xbe name=clock evaluate=yes limit_tstep=yes
# clock source
Jacobian: constant
input_vars:
output_vars: y
aux_vars:
iparms:
sparms:
# Note: L1 is the level in the first interval, L2 in the second.
rparms:
+ T1=1
+ T2=1
+ L1=1
+ L2=-1
+ t0=0
+ delta1=0.01
  delta2=0.01
+ T=0
+ L0=0
+ tk1=0
+ tk2=0
+ tk3=0
+ tk4=0
+ tk5=0
+ slope1=0
+ slope2=0
+ epsl=0
stparms:
igparms:
outparms: y
```

## **Description**

clock.xbe is a square wave source with y as its output. The parameters have the following meaning:

- T1: The first part of one period. y is equal to L1 in this interval.
- T2: The second part of one period. y is equal to L2 in this interval.
- to: An "offset" time interval by which the waveform is shifted (to the right).
- delta1: Width of the transition from the T2 phase to the T1 phase.
- delta2: Width of the transition from the T1 phase to the T2 phase.

The effect of the various paramters of clock.xbe on y(t) is shown in the following figures.




Figure 1: y(t) obtained with T1 = 3, T2 = 5, L1 = 1, L2 = 0, delta1 = 1, delta2 = 1, t0 = 0.




Figure 2: y(t) obtained with T1 = 3, T2 = 5, L1 = 0, L2 = 1, delta1 = 1, delta2 = 2, t0 = 0.




Figure 3: y(t) obtained with T1 = 3, T2 = 5, L1 = -1, L2 = 1, delta1 = 0.1, delta2 = 0.1, t0 = 6.