DABC user manual

Titel: DABC: User Manual

Document	Date	Editor	Revision	Comment
DABC-user	2009-01-05	Hans G.Essel	1.0.0	First scetch

Contents

D	ABC us	ser manual	1
2	DABO	C User Manual: Overview	5
	2.1 U	Jser manual overview	5
3	DABO	C User Manual: Plugins	7
	3.1 I	DABC plug-in mechanism	7
4	DABO	C User Manual: Parameter	9
4	4.1 <i>I</i>	DABC parameters	9
5	DABO	C User Manual: Commands	11
	5.1 <i>I</i>	DABC commands	11
6	DABO	C User Manual: Setup	13
•	6.1 S	etting up system	13
7	DABO	C User Manual: GUI	15
,	7.1	GUI Guide lines	15
,	7.2	GUI Panels	15
	7.2.1	DABC launch panel	15
	7.2.2	MBS launch panel	15
	7.2.3	Combined DABC and MBS launch panel	15
	7.2.4	Command panel	15
	7.2.5	Parameter selection panel	15
	7.2.6	Monitoring panels	15
	7.2.7	Parameter table	15
	7.2.8	Logging window	15
,	7.3	GUI save/restore setups	15
8	DABO	C User Manual: Example MBS	17
	8.1 E	Example MBS event building	17
	8.1.1	MBS upgrade for DABC	17
	8.1.2	New LMD file format	17

9 DA	ABC User Manual: Example Bnet	19		
9.1	Example network event building	19		
10 DABC User Manual: Example ROC				
10.1	Example ROC event building	21		
Refere	ences	23		

2 DABC User Manual: Overview

[user/user-overview.tex]

2.1 User manual overview

3 DABC User Manual: Plugins

[user/user-plugin.tex]

3.1 DABC plug-in mechanism

4 DABC User Manual: Parameter

[user/user-parameter.tex]

4.1 DABC parameters

5 DABC User Manual: Commands

[user/user-command.tex]

5.1 DABC commands

6 DABC User Manual: Setup

[user/user-setup.tex]

6.1 Setting up system

7 DABC User Manual: GUI

[user/user-gui.tex]

7.1 GUI Guide lines

- 7.2 GUI Panels
- **7.2.1** *DABC* launch panel
- 7.2.2 MBS launch panel
- 7.2.3 Combined DABC and MBS launch panel
- 7.2.4 Command panel
- 7.2.5 Parameter selection panel
- 7.2.6 Monitoring panels
- **7.2.6.1** Rate meters
- 7.2.6.2 Histograms
- 7.2.6.3 States
- 7.2.6.4 Information
- 7.2.7 Parameter table
- 7.2.8 Logging window
- 7.3 GUI save/restore setups

8 DABC User Manual: Example MBS

[user/user-exa-mbs.tex]

8.1 Example MBS event building

8.1.1 *MBS* **upgrade for** *DABC*

To have minimal changes, we use standard collector and transport. Two changes:

8.1.1.1 Increased buffer size support

This is done in a completely compatible way. The only problem is the 16 bit i_used field in the buffer header keeping the number of 16 bit data words (behind buffer header). With a new rule we store this number in 32 bit field l_free[2]. Only if dlen is less equal MAX__DLEN defined as (16K-sizeof(bufhe))/2 this number is also stored in i_used as before. Modifications have to be made in all MBS modules accessing i_used. Modules outside MBS can be modified on demand to support large buffers. Current buffers still can be handled without change.

When MBS writes large buffer files only the used part of the file header is written. Number of 16 bit words behind buffer header structure is stored in filhe_used. Event API f_evt is updated to handle large buffers on input. Note: By setup the number of buffers per stream can be set to one. This suppresses event spanning. Large buffers can be used by standard MBS.

8.1.1.2 Variable sized buffers

As a second step variable sized buffers are implemented. They get a new type 100. The allocated buffers are still fixed length as before. However, the *MBS* transport would write only the used part of the buffers to clients. Processing these buffers a module must first read the header, then get the used size from iUsedWords (free[2]) and read the rest. Modules outside *MBS* must be modified to process such buffers. In *MBS*, after stream buffers are created, buffer types are set to 100 by a new command enable dabc in transport. This command also sets the transport synchronous mode. In this mode transport processes streams only if a client is connected.

8.1.2 New LMD file format

With *DABC* as event builder for *MBS* there is no need to write files in *MBS*. This gives more freedom to design a new file format. This format will be written by *DABC* and read by flmd functions (get event). The format is quite simpler than the old one, because it has no buffer structure causing so much complications by event spanning.

A file has a file header as before, but with a fixed size and a variable part (size iUsedWords). Behind the header follow data elements with sMbsHeader headers (length, type, subtype) allowing to identify and process or skip them. Besides event data, time stamps may be inserted from the original MBS formatted buffers to preserve this time information. Writing/reading such a file is very straight forward. The file header contains the number of data elements and the maximum size of elements. This information is collected throughout the file writing and written on close into the file header. The file header is an

sMbsFileHeader structure. iMaxWords is the maximum size of elements, iElements is the number of data elements.

The file size is no longer restricted to 2GB. Optionally an element index is written at the end of the file. This allows for random access of elements in the file through this index table. The table itself has 32-bit values for the element offsets (in 32-bit). It can therefore address offsets up to 16GB in the file. If larger files are needed, the table can be created with 64-bit values giving unlimited addressing.

Note: This file format needs the rewind file function because the file header must be rewritten to store iMaxWords, iElements, and optionally the offset of the index table. This function is currently not implemented in the RFIO package, but will be done.

9 DABC User Manual: Example Bnet

[user/user-exa-bnet.tex]

9.1 Example network event building

10 DABC User Manual: Example ROC

[user/user-exa-roc.tex]

10.1 Example ROC event building

References

- [1] CBM collaboration, "CBM Experiment: Technical Status Report", Januar 2005
- [2] CMS collaboration, http://cmsinfo.cern.ch/outreach/, "CMS Outreach", CERN 2006
- [3] The Experimental Physics and Industrial Control System website, http://www.aps.anl.gov/epics/index.php, Argonne National Laboratory 2006
- [4] C. Gaspar et al., "DIM Distributed Information Management System" http://dim.web.cern.ch/dim/, CERN May 2006
- [5] Y. Liu and P. Sinha, "A Survey Of Generic Architectures For Dependable Systems", IEEE Canadian Review, Spring 2003
- [6] The National Instruments Labview web site, http://www.ni.com/labview/, National Instruments Corporation 2006
- [7] L. Orsini and J. Gutleber, "The XDAQ Wiki Main Page" http://xdaqwiki.cern.ch/index.php, CERN 2006
- [8] L. Orsini and J. Gutleber, "I2O Messaging" http://xdaqwiki.cern.ch/index.php/I2O_Messaging, CERN 2006
- [9] L. Orsini and J. Gutleber, "XDAQ Monitor application" http://xdaqwiki.cern.ch/index.php/Monitor_CGI_interface, CERN 2005
- [10] L. Orsini and J. Gutleber, http://xdaqwiki.cern.ch/index.php/Configuration_schema "XDAQ XML configuration schema", CERN 2006
- [11] D. Stenberg et al., The curl and libcurl web site, http://curl.haxx.se/, HAXX HB 2006
- [12] SystemC website, http://www.systemc.org/
- [13] The W3C Consortium, "SOAP Version 1.2 Part 1: Messaging Framework", http://www.w3.org/TR/soap12-part1, W3C Recommendation, 24 June 2003
- [14] K. Whisnant, R.K. Iyer, Z. Kalbarczyk, and P. Jones, "The Effects of an ARMOR-based SIFT Environment on the Performance and Dependability of User Applications", University of Illinois, 2006
- [15] The Wikipedia, "Finite State Machine", http://en.wikipedia.org/wiki/State_machine, Wikipedia 2006