

# ESXi Network Internals

*Overview of the Tcpi network stack*

*Arun Ramanathan*

Confidential

vmware®

© 2009 VMware Inc. All rights reserved

# Agenda

---

## Network stack

### 1. [freebsd stack](#)

- TCP/IP
- ARP, Ethernet

### 2. [Tx/Rx dispatch layer](#)

- vmk glue code
- Tx/Rx dispatch queues

### 3. [Switching layer](#)

- VSS, DVS, port groups

### 4. [Net Sched - IO control layer](#)


- Manages the uplink queue

### 5. [vmk Linux layer](#)

- Linux networking, NAPI – networking APIs
- Drivers – Eg. bnx2net

# Net Stack

---



Software

---

Hardware



# Net Stack

User world

vmkernel

vMotion

freebsd Layer

Tx/Rx dispatch layer

Switching Layer

Net Sched Layer

vmk linux layer

Device driver

Mbuf

vmk\_PktHandle

vmk\_PktHandle

sk\_buff


vmkernel

Hardware



# Net Stack Layers

# 1. FreeBSD Layer




# 1. FreeBSD Layer

---


- Inherited from freebsd
- Consists of tcp/udp, ip and ethernet layers
- Responsible for constructing the ethernet frame
- Uses message buffer i.e Mbuf
  
- vMotion uses Net\_ API to interact with freebsd layer
  - Net\_SendTo, Net\_SendMbufTo etc
  
- Virtualized: Supports multiple netstack instances
  - Now vMotion has its own instance
  
- Possible queuing in the ethernet layer if ARP is not found

# 1. FreeBSD Layer






## 2. Tx/Rx Dispatch Layer




### 3. Switching Layer


#### vSphere standard switch



### 3. Switching Layer



## 4. Net Sched Layer



## 5. Vmk Linux layer

