

7.2. Format the containers for different screen sizes

In this tutorial, you'll **learn how to make your Oracle JET app work well on all screen sizes** (like mobile, tablet, desktop).

Key Concepts:

- **JET helper classes** help you **adjust layout based on screen size**.
- Layout uses a **12-column grid**.
- You can control how many columns an element takes on:
 - **Small (sm)**
 - **Medium (md)**
 - **Large (lg)**
 - **Extra-Large (xl)**
- If you set a size (like `oj-sm-6`), it applies to **small and bigger** unless you override it for larger screens.
- You can also:
 - Set **padding**
 - Align **text/elements**
 - Hide/show things on certain screen sizes

Small Screen (sm)											
1	2	3	4	5	6	7	8	9	10	11	12
Medium Screen (md)											
1	2	3	4	5	6	7	8	9	10	11	12
Large Screen (lg)											
1	2	3	4	5	6	7	8	9	10	11	12
Extra Large Screen (xl)											
1	2	3	4	5	6	7	8	9	10	11	12

Objectives

In this practice, you will add helper classes to your Oracle JET web app to specify text alignment, add padding to panels, and set columns for different screen sizes.

Prerequisites

- A development environment set up to create Oracle JET web apps that includes an installation of Node.js
- Access to the [Oracle JET Developer Cookbook](#)

- Completion of the previous practice, 2.1.

Task 1: Add Helper Classes for Content Alignment

Modify the alignment of content in the Oracle JET web app's layout by specifying helper classes for different screen sizes in the `div` element.

1. Navigate to the `JET_Web_Application/src/ts/views` directory and open the `dashboard.html` file in an editor.
2. Find the `div` element where `id="activitiesContainer"`, before the Activities heading, and then add the `oj-sm-only-text-align-end` Oracle JET responsive helper style class.

```
<!-- The responsive helper style class aligns the Activities container text to the end of the screen when the screen size is small -->
<div
  id="activitiesContainer"
  class="oj-flex-item oj-bg-info-30 oj-sm-only-text-align-end"
>
  <h3 id="activitiesHeader">Activities</h3>
</div>
```

1. The `oj-sm-only-text-align-end` style class aligns the contents in the container to the end of the screen width only if the screen size is small.
2. Save the `dashboard.html` file.

Your code should look similar to the below code

```
<div class="oj-hybrid-padding">
  <h1>Product Information</h1>
  <div id="parentContainer1" class="oj-flex oj-flex-init oj-panel oj-bg-warning-20">
    <!-- The responsive helper style class aligns the Activities container text to the end of the screen when the screen size is small -->
    <div id="activitiesContainer" class="oj-flex-item oj-bg-info-30 oj-sm-only-text-align-end">
      <h3 id="activitiesHeader">Activities</h3>
      <oj-list-view id="activitiesList" aria-labelledby="activitiesHeader" data="[[activityDataProvider]]"
        gridlines.item="visible">
        <template slot="itemTemplate">
          <div>
            <strong>
              <oj-bind-text value="[[ $current.data.name ]]"></oj-bind-text>
            </strong>
          </div>
        </template>
      </oj-list-view>
    </div>
    <div id="parentContainer2" class="oj-flex oj-flex-item oj-panel oj-bg-danger-30">
      <div id="activityItemsContainer" class="oj-flex-item"></div>
```

```

        <div id="itemDetailsContainer" class="oj-flex-item oj-panel oj-bg-
neutral-30">
            <h3>Item Details</h3>
            <oj-label for="basicSelect">Select Chart:</oj-label>
            <oj-select-single id="basicSelect" class="selectSingleStyle"
data="[[chartTypesDP]]" value="{{val}}">
            </oj-select-single>
            <oj-chart id="barChart" type="[[val]]" data="[[chartDataProvider]]"
animation-on-display="auto"
            animation-on-data-change="auto" hover-behavior="dim"
class="chartStyle">
                <template slot="itemTemplate" data-aj-as="item">
                    <oj-chart-item value="[[item.data.value]]" group-id="[[
item.data.group] ]]"
                    series-id="[[item.data.series]]">
                    </oj-chart-item>
                </template>
            </oj-chart>
        </div>
    </div>
</div>
</div>

```

Task 2: Add Helper Classes for Padding

Add padding to the content by using the Oracle JET responsive spacing style classes. When you specify the responsive spacing class on the parent div element, the padding is applied to all child div elements of that parent.

1. Find the div element where id="parentContainer2" and add the oj-lg-padding-pad-6x Oracle JET responsive spacing style class.

```

<!-- The style class is specified in the parent div element --
>
<div
    id="parentContainer2"
    class="oj-flex oj-flex-item oj-panel oj-bg-danger-30 oj-lg-
padding-6x"
></div>

```

Task 3: Set Columns for Different Screen Sizes

In the Oracle JET web app, specify the sizing style classes in the div element. These Oracle JET style classes allow you to set the minimum column width that is allocated for the specified screen size.

1. Find the div element where id="activitiesContainer", before the Activities heading, and add the style classes that specify the minimum number of columns for different screen sizes.

```

<!-- The oj-md-4 and oj-sm-12 style classes specify the column
width for small and medium screen sizes -->
<div

```

```

        id="activitiesContainer"
        class="oj-flex-item oj-bg-info-30 oj-sm-only-text-align-end
oj-md-4 oj-sm-12"
    >
        <h3 id="activitiesHeader">Activities</h3>
    </div>

```

The style class `oj-sm-12` makes the div container 12 columns wide in a small screen, and `oj-md-4` makes the div container four columns wide when in medium or above screen sizes.

2. Find the `div` elements surrounding the Item Details heading, which have `id` attributes with the values `parentContainer2`, `activityItemsContainer`, and `itemDetailsContainer`. Then add the following style classes to them to specify their minimum column width for different screen sizes.

```

<!-- The style class in the div elements specifies the column
width for different screen sizes -->
<div
    id="parentContainer2"
    class="oj-flex oj-flex-item oj-panel oj-bg-danger-30 oj-lg-
padding-6x oj-md-8 oj-sm-12"
>
    <div
        id="activityItemsContainer"
        class="oj-flex-item oj-md-6 oj-sm-12"
    ></div>
    <div
        id="itemDetailsContainer"
        class="oj-flex-item oj-panel oj-bg-neutral-30 oj-md-6 oj-
sm-12"
    ></div>
</div>

```

3. Save the `dashboard.html` file. Your code should look similar to below code

```

<div class="oj-hybrid-padding">
    <h1>Product Information</h1>
    <!-- The border and color for Parent Container 1 -->
    <div id="parentContainer1" class="oj-flex oj-flex-init oj-panel oj-bg-
warning-20">
        <!-- The oj-md-4 and oj-sm-12 style classes specify the column width
for small and medium screen sizes -->
        <div id="activitiesContainer" class="oj-flex-item oj-bg-info-30 oj-
sm-only-text-align-end oj-md-4 oj-sm-12">
            <h3 id="activitiesHeader">Activities</h3>
            <oj-list-view id="activitiesList" aria-
labelledby="activitiesHeader" data="[activityDataProvider]"
            gridlines.item="visible">
                <template slot="itemTemplate">
                    <div>
                        <strong>

```

```

text>
        <oj-bind-text value="[[ $current.data.name]]"></oj-bind-
text>
        </strong>
    </div>
</template>
</oj-list-view>
</div>
<!-- The style class in the div elements specifies the column width
for different screen sizes -->
<div id="parentContainer2" class="oj-flex oj-flex-item oj-panel oj-
bg-danger-30 oj-lg-padding-6x oj-md-8 oj-sm-12">
    <div id="activityItemsContainer" class="oj-flex-item oj-md-6 oj-
sm-12"></div>
    <div id="itemDetailsContainer" class="oj-flex-item oj-panel oj-bg-
neutral-30 oj-md-6 oj-sm-12">
        <h3>Item Details</h3>
        <oj-label for="basicSelect">Select Chart:</oj-label>
        <oj-select-single id="basicSelect" class="selectSingleStyle"
data="[[chartTypesDP]]" value="{{val}}">
            </oj-select-single>
            <oj-chart id="barChart" type="[[val]]"
data="[[chartDataProvider]]" animation-on-display="auto"
            animation-on-data-change="auto" hover-behavior="dim"
class="chartStyle">
                <template slot="itemTemplate" data-obj-as="item">
                    <oj-chart-item value="[[item.data.value]]" group-id="[[
[item.data.group] ]]"
                        series-id="[[item.data.series]]">
                    </oj-chart-item>
                </template>
            </oj-chart>
        </div>
    </div>
</div>
</div>

```

Task 4: Run the Web App

Ojet serve

Oracle JET runs your app in the browser. To test responsiveness, right-click → Inspect → choose a small device (e.g., Pixel 7) from the Dimensions dropdown and check how the Activities list layout adjusts.

Information

Activities

Baseball

Bicycling

Skiing

Soccer

Item Details

Select Chart:

Bar

