

SAFETY DATA SHEET PACKET

Product Identifier

SRM Number: 2497

SRM Name: Bingham Concrete Mixture for Rheological Measurements

SRM Description:

This Standard Reference Material (SRM) is intended for use in calibrating rheometers for measuring the rheological properties of concrete. A unit of SRM 2497 consists of two 18.9 L containers labeled P and A, respectively. Container P includes Limestone (12 kg) and 4 L of corn syrup. Container A includes one bottle each of 1 mm beads (6 kg) and 10 mm beads (20 kg).

SRM 2497 Parts:

Container A:

Part A: Glass Beads (10 mm diameter) Part B: Glass Beads (1 mm diameter)

Container P:

Part C: Corn Syrup
Part D: Limestone Powder

Company Information

National Institute of Standards and Technology Standard Reference Materials Program 100 Bureau Drive, Stop 2300 Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200 Emergency Telephone ChemTrec: FAX: 301-948-3730 1-800-424-9300 (North America) E-mail: SRMMSDS@nist.gov +1-703-527-3887 (International) Website: https://www.nist.gov/srm

DATE: 10 May 2019

Product Identifier

SRM Number: 2497

SRM Name: Bingham Concrete Mixture for Rheological Measurements

SRM Part: Part A: Glass Beads (10 mm diameter)

Part B: Glass Beads (1 mm diameter)

Under the U.S. Department of Labor, Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1200, this Standard Reference Material (SRM) is NOT classified as a physical hazard or a health hazard, a simple asphyxiant, combustible dust, pyrophoric gas, or hazard not otherwise classified. There are no hazard pictograms, hazard statements or signal word associated with it. Safety Data Sheet information is not required. This document may be used in conjunction with your hazard communication program.

Description: This SRM is intended for use in calibrating rheometers for measuring the rheological properties of concrete. A unit of SRM 2497 consists of two 18.9L containers labeled P and A, respectively. Container P includes Limestone (12 kg) and 4 L of corn syrup. Container A includes one bottle each of 1 mm beads (6 kg) and 10 mm beads (20 kg).

Disposal: Dispose of SRM 2497 Part A: Glass Beads (10 mm diameter) and Part B: Glass Beads (1 mm diameter) in accordance with local, state, and federal regulations.

Transport Information: This material is not regulated by the U.S. Department of Transportation (DOT) and/or International Air Transport Association (IATA).

Disclaimer: This document was prepared carefully, using current references. Users of this SRM should ensure that this document and the corresponding Certificate of Analysis in their possession are current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at https://www.nist.gov/srm.

DATE: 10 May 2019

Product Identifier

SRM Number: 2497

SRM Name: Bingham Concrete Mixture for Rheological Measurements

SRM Part: Part C: Corn Syrup

Under the U.S. Department of Labor, Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1200, this Standard Reference Material (SRM) is NOT classified as a physical hazard or a health hazard, a simple asphyxiant, combustible dust, pyrophoric gas, or hazard not otherwise classified. There are no hazard pictograms, hazard statements or signal word associated with it. Safety Data Sheet information is not required. This document may be used in conjunction with your hazard communication program.

Description: This SRM is intended for use in calibrating rheometers for measuring the rheological properties of concrete A unit of SRM 2497 consists of two 18.9 L containers labeled P and A, respectively. Container P includes Limestone (12 kg) and 4 L of corn syrup. Container A includes one bottle each of 1 mm beads (6 kg) and 10 mm beads (20 kg).

Disposal: Dispose of SRM 2497 Part C: Corn Syrup in accordance with local, state, and federal regulations.

Transport Information: This material is not regulated by the U.S. Department of Transportation (DOT) and/or International Air Transport Association (IATA).

Disclaimer: This document was prepared carefully, using current references. Users of this SRM should ensure that this document and the corresponding Certificate of Analysis in their possession are current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at https://www.nist.gov/srm.

SRM 2497 Part C: Corn Syrup Page 1 of 1



SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 2497

SRM Name: Bingham Concrete Mixture for Rheological Measurements

SRM Part: Part D: Limestone

Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is intended for use in calibrating rheometers for measuring the rheological properties of concrete. A unit of SRM 2497 consists of two 18.9 L containers labeled P and A, respectively. Container P includes Limestone (12 kg) and 4 L of corn syrup. Container A includes one bottle each of 1 mm beads (6 kg) and 10 mm beads (20 kg).

Company Information

National Institute of Standards and Technology Standard Reference Materials Program 100 Bureau Drive, Stop 2300 Gaithersburg, Maryland 20899-2300

 Telephone:
 301-975-2200
 Emergency Telephone ChemTrec:

 FAX:
 301-948-3730
 1-800-424-9300 (North America)

 E-mail:
 SRMMSDS@nist.gov
 +1-703-527-3887 (International)

Website: https://www.nist.gov/srm

2. HAZARDS IDENTIFICATION

Classification

Physical Hazard: Not classified.

Health Hazard: Carcinogenicity Category 1

STOT, Repeated Exposure Category 1

Label Elements Symbol



Signal Word DANGER

Hazard Statement(s):

H350 May cause lung cancer.

H372 Causes damage to lungs through prolonged or repeated inhalation.

Precautionary Statement(s):

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, and eye protection.

P308 + P313 If exposed or concerned: Get medical attention.

P405 Store locked up.

P501 Dispose of contents and container according to local regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients(s) with Unknown Acute Toxicity: Not applicable.

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Limestone

Other Designations: Calcium carbonate, natural; agricultural limestone; agstone; solnhofen stone; lithographic stone.

Components are listed in compliance with OSHA's 29 CFR 1910.1200; for the actual values see the NIST Certificate of Analysis.

Hazardous Component(s)	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)			
Limestone ^(a)			100%			
Individual Ingredient						
Quartz	14808-60-7	238-878-4	>0.1			

⁽a) Quartz is a component of limestone.

4. FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

Skin Contact: Wash skin with soap and water for at least 15 minutes. Thoroughly clean and dry contaminated clothing before reuse.

Eye Contact: Flush eyes with water for at least 15 minutes. If necessary, seek medical attention.

Ingestion: If adverse effects occur after ingestion, seek medical treatment.

Most Important Symptoms/Effects, Acute and Delayed: May cause irritation, lung damage, silicosis, and cancer.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek medical attention if needed.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Negligible fire hazard. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media:

Suitable: Use extinguishing agents appropriate for surrounding fire.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: None listed.

Special Protective Equipment and Precautions for Fire-Fighters: Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 1 Fire = 0 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection".

Methods and Materials for Containment and Clean up: Collect spilled material in appropriate container for disposal. Keep out of water supplies and sewers. Keep unnecessary people away, isolate hazard area and deny entry.

7. HANDLING AND STORAGE

Safe Handling Precautions: Minimize dust generation. See Section 8, "Exposure Controls and Personal Protection".

Storage: Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances (See Section 10, "Stability and Reactivity").

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits for Quartz:

ACGIH (TLV): 0.025 mg/m³ (TWA) [respirable fraction]

OSHA (PEL): $(30)/(\% SiO2 + 2) \text{ mg/m}^3 \text{ (TWA) [total dust]}$

(250)/(% SiO2 + 5) mppcf (TWA) [respirable fraction] (10)/(% SiO2 + 2) mg/m³ (TWA) [respirable fraction]

NIOSH (REL): 0.05 mg/m³ (TWA) [respirable dust]

50 mg/m³ (IDLH) [respirable dust]

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye/Face Protection: Wear splash resistant safety goggles with a face shield. An eyewash station should be readily available near areas of use.

Skin and Body Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant gloves should be worn at all times when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Descriptive Properties: Limestone

Appearance (physical state, color, etc.): white to brown powder

Molecular Formula: varies Molar Mass (g/mol): varies Odor: odorless **Odor threshold:** not available pH: not applicable **Evaporation rate:** not applicable Melting point/freezing point (°C): not available Density (g/mL): 2.71 to 2.95 Vapor Pressure (mmHg): not applicable Vapor Density (air = 1): not applicable Viscosity (cP): not applicable

Solubility(ies): 0.0014 % (water); dilute acids

Partition coefficient (n-octanol/water): not available
Particle Size: not available

Thermal Stability Properties:

Autoignition Temperature (°C):

Thermal Decomposition (°C):

898 (1648.4 °F)

Initial boiling point and boiling range (°C):

Explosive Limits, LEL (Volume %):

not applicable

not applicable

plash Point (°C):

not applicable

not applicable

not applicable

not applicable

not applicable

rot applicable

not applicable

10. STABILITY AND REACTIVITY					
Reactivity: Stable at normal temperatures and pressure.					
Stability: X Stable Unstable					
Possible Hazardous Reactions: None listed.					
Conditions to Avoid: Avoid generating dust.					
Incompatible Materials: Bases, halogens, acids, metal salts, metal, oxidizing materials, combustible materials.					
Fire/Explosion Information: See Section 5, "Fire Fighting Measures".					
Hazardous Decomposition: Thermal decomposition will produce miscellaneous decomposition products.					
Hazardous Polymerization: Will Occur X Will Not Occur					
11. TOXICOLOGICAL INFORMATION					
Route of Exposure: X Inhalation Skin Ingestion					
Symptoms Related to the Physical, Chemical and Toxicological Characteristics: May cause irritation, lung damage, silicosis, and cancer.					
Potential Health Effects (Acute, Chronic and Delayed):					
Inhalation: Inhalation of nuisance dust has little adverse effect on the lungs. Acute exposure to fine particles containing respirable quartz may result irritation; chronic exposure may result in irritation, chest pain, weight loss, difficulty breathing, digestive disorders, bluish skin color, lung damage, cancer, and death.					
Skin Contact: May cause irritation due to mechanical abrasion.					
Eye Contact: May cause irritation due to mechanical abrasion.					
Ingestion: No data available.					
Numerical Measures of Toxicity:					
Acute Toxicity: Not classified.					
Skin Corrosion/Irritation: Not classified; no data available.					
Serious Eye Damage/Irritation: Not classified; no data available.					
Respiratory Sensitization: Not classified; no data available.					
Skin Sensitization: Not classified; no data available.					
Germ Cell Mutagenicity: Not classified; no data available.					
Carcinogenicity: Category 1					
Listed as a Carcinogen/Potential Carcinogen X Yes No Silica dust, crystalline, in the form of quartz or cristobalite is listed by IARC, <i>Group 1</i> , <i>carcinogenic to humans</i> . Quartz is listed by NTP as a <i>known human carcinogen (respirable size)</i> . Quartz is not listed by OSHA as a designated carcinogen.					
Reproductive Toxicity: Not classified.					
Specific Target Organ Toxicity (STOT), Single Exposure: Not classified; no data available.					
Specific Target Organ Toxicity (STOT), Repeated Exposure: Category 1 Cumulative exposure may result in reduced lung capacity and silicosis.					
Aspiration Hazard: Not classified.					
12. ECOLOGICAL INFORMATION					
Ecotoxicity Data: No data available.					
Persistence and Degradability: No data available.					

Mobility in Soil: No data available.

Other Adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of waste in accordance with all applicable federal, state, and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA: Not regulated by DOT or IATA.

15. REGULATORY INFORMATION

U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): Not regulated.

SARA Title III Section 302 (40 CFR 355.30): Not regulated.

SARA Title III Section 304 (40 CFR 355.40): Not regulated.

SARA Title III Section 313 (40 CFR 372.65): Not regulated.

OSHA Process Safety (29 CFR 1910.119): Not regulated.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH: No. CHRONIC HEALTH: Yes. FIRE: No. REACTIVE: No. PRESSURE: No.

State Regulations:

California Proposition 65: WARNING! This product contains a chemical [quartz (airborne particles of respirable size)] known to the state of California to cause cancer.

U.S. TSCA Inventory: Limestone and quartz are listed.

TSCA 12(b), Export Notification: Not listed.

Canadian Regulations:

WHMIS Information: Not provided for this material.

16. OTHER INFORMATION

Issue Date: 10 May 2019

Sources: ChemAdvisor, Inc., SDS *Quartz*, 09 December 2015.

ChemAdvisor, Inc., SDS Limestone, 09 December 2015.

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial	NIST	National Institute of Standards and Technology
	Hygienists		
ALI	Annual Limit on Intake	NRC	Nuclear Regulatory Commission
CAS	Chemical Abstracts Service	NTP	National Toxicology Program
CEN	European Committee for Standardization	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response,	PEL	Permissible Exposure Limit
	Compensation, and Liability Act		
CFR	Code of Federal Regulations	RCRA	Resource Conservation and Recovery Act
CPSU	Coal Mine Dust Personal Sample Unit	REL	Recommended Exposure Limit
DOT	Department of Transportation	RM	Reference Material
EC50	Effective Concentration, 50 %	RQ	Reportable Quantity
EINECS	European Inventory of Existing Commercial Chemical	RTECS	Registry of Toxic Effects of Chemical Substances
	Substances		
EPCRA	Emergency Planning and Community Right-to-Know	SARA	Superfund Amendments and Reauthorization Act
	Act		
IARC	International Agency for Research on Cancer	SCBA	Self-Contained Breathing Apparatus
IATA	International Air Transport Association	SRM	Standard Reference Material
IDLH	Immediately Dangerous to Life and Health	STEL	Short Term Exposure Limit
ISO	International Organization for Standardization	STOT	Specific Target Organ Toxicity
LC50	Lethal Concentration, 50 %	TDLo	Toxic Dose Low
LD50	Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
NIOSH	National Institute for Occupational Safety and Health	WHMIS	Workplace Hazardous Materials Information System

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The certified values for this material are given in the NIST Certificate of Analysis.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at https://www.nist.gov/srm.