

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 2628a

SRM Name: Nitric Oxide in Nitrogen (Nominal Amount-of-Substance Fraction 10 µmol/mol)

Other Means of Identification: Not Applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is a primary gas mixture of nitric oxide in nitrogen supplied in a DOT 3AL-specification aluminum (6061 alloy) cylinder with a water volume of 6 L. Mixtures are shipped with a nominal pressure exceeding 11.0 MPa (1600 psig), which provides the user with 0.73 m³ (25.8 ft³) of useable mixture. The cylinder is the property of the purchaser and is equipped with a CGA-660 stainless steel valve, which is the recommended outlet for this nitric oxide mixture.

Company Information

National Institute of Standards and Technology Standard Reference Materials Program 100 Bureau Drive, Stop 2300 Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200 FAX: 301-948-3730 E-mail: SRMMSDS@nist.gov Website: http://www.nist.gov/srm Emergency Telephone ChemTrec: 1-800-424-9300 (North America) +1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Classification

Physical Hazard: Compressed Gas **Health Hazard:** Simple Asphyxiant

Label Elements Symbol



Signal Word WARNING

Hazard Statement(s)

H280 Contains gas under pressure; may explode if heated.

----- May displace oxygen and cause rapid suffocation.

Precautionary Statement(s)

P410+P403 Protect from sunlight. Store in a well-ventilated place.

Hazards Not Otherwise Classified: Not applicable.

Ingredients(s) with Unknown Acute Toxicity: Not applicable.

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Nitric oxide in nitrogen, compressed gas

Other Designations:

Nitric oxide: Nitrogen oxide; nitrogen monoxide; nitric oxide trimer; NO.

Nitrogen: Dinitrogen; nitrogen compressed.

SRM 2628a Page 1 of 6

Components are listed in compliance with OSHA's 29 CFR 1910.1200; for the actual values see the Certificate of Analysis.

Hazardous Components	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)
Nitrogen	7727-37-9	231-783-9	>99.99
Nitric oxide	10102-43-9	233-271-0	< 0.002

4. FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

Skin Contact: Not applicable.

Eye Contact: Immediately flush eyes, including under the eyelids with copious amounts of water for at least 15 minutes. Seek immediate medical attention.

Ingestion: Ingestion of a gas is unlikely.

Most Important Symptoms/Effects, Acute and Delayed: Harmful if inhaled, blood damage, difficulty breathing, and suffocation.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Negligible fire hazard applicable to the identified NIST cylinder. Cylinders may rupture or explode if exposed to heat. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media:

Suitable: Use extinguishing media appropriate to the surrounding fire.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: Oxides of nitrogen.

Special Protective Equipment and Precautions for Fire-Fighters: Move cylinder from fire area if it can be done without personal risk. Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 1 Fire = 0 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection". Shut off gas supply if this can be done safely. Isolate area until gas has dispersed.

Methods and Materials for Containment and Clean up: Stop leak if possible without personal risk. Isolate hazard area and deny entry. Ventilate closed spaces before entering.

7. HANDLING AND STORAGE

Safe Handling Precautions: Secure cylinder to prevent physical damage. Close valve after each use and when empty. Keep value protection cap on cylinder when not in use.

Storage: Store and handling in accordance with all current regulations and standards. Keep separated from incompatible substances. Store in well-ventilated area. Subject to storage regulations, OSHA 29 CFR 1910.101.

SRM 2628a Page 2 of 6

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits:

Nitric oxide

NIOSH (REL): 25 ppm (30 mg/m³) TWA NIOSH (REL): 100 ppm (123 mg/m³) IDLH ACGIH (TLV): 25 ppm (30 mg/m³) TWA OSHA (PEL): 25 ppm (30 mg/m³) TWA

Nitrogen

ACGIH (TLV): Simple asphyxiant.

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection Measures: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye/Face Protection: Wear splash resistant safety goggles with a face shield. An eye wash station should be readily available near areas of use.

Skin and Body Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant gloves should be worn at all times when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Containers may rupture or explode if exposed to heat.

Descriptive Properties:	Nitrogen			
•	(>99 %)			
Appearance (physical state, color, etc.)	Colorless compressed gas			
Molecular Formula	N_2			
Molar Mass (g/mol)	28			
Odor	Odorless			
Odor threshold	Not available			
pН	Not applicable			
Evaporation rate	Not applicable			
Melting point/freezing point (°C)	–210 (–346 °F)			
Relative Density (g/L)	1.2506			
Vapor Pressure (mmHg)	760 at −196 °C			
Vapor Density (air = 1)	0.967			
Viscosity (cP)	0.01787 at 27 °C			
Solubility(ies)	Water, 1.6 % at 20 °C; liquid ammonia			
Partition coefficient (n-octanol/water)	Not available			
Thermal Stability Properties				
Autoignition Temperature	Not applicable			
Thermal Decomposition	Not applicable			
Initial boiling point and boiling range (°C)	–196 (–321 °F)			
Explosive Limits, LEL	Not applicable			
Explosive Limits, UEL	Not applicable			
Flash Point	Not applicable			
Flammability (solid, gas)	Not applicable			
10. STABILITY AND REACTIVITY				
Reactivity: Stable at normal temperature and pressure.				
Stability: X Stable	Unstable			
Possible Hazardous Reactions: None listed.				

SRM 2628a Page 3 of 6

Conditions to Avoid: Avoid heat, flames, sparks, and other sources of ignition. Minimize contact with material.

Incompatible Materials: Oxidizing materials, halogens, metal oxides, metals, combustible materials, metal salts, halocarbons.				
Fire/Explosion Information: See Section 5, "Fire Fighting Measures".				
Hazardous Decomposition: Miscellaneous decomposition products.				
Hazardous Polymerization: Will Occur X Will Not Occur				
11. TOXICOLOGICAL INFORMATION				
Route of Exposure: X Inhalation Skin Ingestion				
Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Nausea, headache, weakness, drowsiness.				
Potential Health Effects (Acute, Chronic and Delayed):				
Inhalation: Nitric oxide: Acute exposure to nitric oxide at low concentrations in a one-time exposure may cause mild coughing, respiratory tract irritation, fatigue, headache, nausea and vomiting choking abdominal pain, and dyspnea. Exposure to 25 ppm for 60 minutes may cause irritation and minor chest pain; 50 ppm may lead to pulmonary edema with possible recovery; 100 ppm may cause pulmonary edema and death.				
Nitrogen: Nitrogen compressed gas is a simple asphyxiant. Release in an enclosed space may result in asphyxiation. The symptoms of asphyxia depend on the rapidity with which the oxygen deficiency develops and how long it continues. In sudden acute asphyxia, unconsciousness may be immediate. With slow development, there may be rapid respiration and pulse, air hunger, dizziness, reduced awareness, tightness in the head, tingling sensations, incoordination, faulty judgment, emotional instability, and rapid fatigue. As the asphyxia progresses, nausea, vomiting, collapse, unconsciousness, convulsions, deep coma, and death are possible.				
Skin Contact: Nitric oxide at low concentrations may cause skin irritation.				
Eye Contact: Nitric oxide at low concentrations in air may cause a stinging sensation of the eyes. Not applicable for exposure to nitrogen.				
Ingestion: Ingestion of a gas is unlikely under normal conditions of use.				
Numerical Measures of Toxicity:				
Acute Toxicity: Not classified. Nitric oxide: Rat, Inhalation LC50: 1068 mg/m ³ (4 h) Nitrogen: Simple asphyxiant				
Skin Corrosion/Irritation: Not applicable.				
Serious Eye Damage/ Eye Irritation: Not applicable.				
Respiratory Sensitization: No data available.				
Skin Sensitization: No data available.				
Germ Cell Mutagenicity: No data available.				
Carcinogenicity: Not classified. Listed as a Carcinogen/Potential Carcinogen Yes X No				
Nitrogen and nitric oxide are not listed by NTP, IARC or OSHA as carcinogens.				
Reproductive Toxicity: Not classified.				
Specific Target Organ Toxicity, Single Exposure: Not classified.				
Specific Target Organ Toxicity, Repeated Exposure: Not classified.				

SRM 2628a Page 4 of 6

Aspiration Hazard: Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity Data: No data available.

Persistence and Degradability: No data available. **Bioaccumulative Potential:** No data available.

Mobility in Soil: No data available.

Other Adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of waste in accordance with all applicable federal, state, and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA: UN1956, compressed gas, n.o.s. (nitric oxide in nitrogen), Hazard Class 2.2.

15. REGULATORY INFORMATION

U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): Identified cylinder not regulated.

SARA Title III Section 302 (40 CFR 355.30): Identified cylinder not regulated.

SARA Title III Section 304 (40 CFR 355.40): Identified cylinder not regulated.

SARA Title III Section 313 (40 CFR 372.65): Identified cylinder not regulated.

OSHA Process Safety (29 CFR 1910.119): Identified cylinder not regulated.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH: Yes
CHRONIC HEALTH: No
FIRE: No
REACTIVE: No
PRESSURE: Yes

State Regulations:

California Proposition 65: Not listed.

U.S. TSCA Inventory: Nitric oxide and nitrogen are listed.

TSCA 12(b), Export Notification: No components are listed.

Canadian Regulations: WHMIS Information is not provided for this material.

SRM 2628a Page 5 of 6

16. OTHER INFORMATION

Issue Date: 03 January 2014

Sources: ChemADVISOR, Inc., MSDS, Nitrogen, Compressed Gas, 11 September 2013.

ChemADVISOR, Inc., MSDS, Nitric Oxide, 11 September 2013.

NIOSH RTECS, Nitrogen Monoxide, No QX0525000, CAS No. 10102-43-9; May 2009; available at

http://www.cdc.gov/niosh-rtecs/QX802C8.html (accessed Jan 2014).

National Library of Medicine, Hazardous Subtances Databank, Nitric Oxide, available at

http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB (accessed Jan 2014).

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial	NRC	Nuclear Regulatory Commission
	Hygienists		
ALI	Annual Limit on Intake	NTP	National Toxicology Program
CAS	Chemical Abstracts Service	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response,	PEL	Permissible Exposure Limit
	Compensation, and Liability Act		•
CFR	Code of Federal Regulations	RCRA	Resource Conservation and Recovery Act
DOT	Department of Transportation	REL	Recommended Exposure Limit
EINECS	European Inventory of Existing Commercial	RQ	Reportable Quantity
	Chemical Substances	-	
EPCRA	Emergency Planning and Community Right-to-Know	RTECS	Registry of Toxic Effects of Chemical Substances
	Act		
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
IATA	International Air Transportation Agency	SCBA	Self-Contained Breathing Apparatus
IDLH	Immediately Dangerous to Life and Health	SRM	Standard Reference Material
LC50	Lethal Concentration	STEL	Short Term Exposure Limit
LD50	Median Lethal Dose or Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
NIOSH	National Institute for Occupational Safety and Health	UEL	Upper Explosive Limit
NIST	National Institute of Standards and Technology	WHMIS	Workplace Hazardous Materials Information System
			•

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The certified values for this material are given in the NIST Certificate of Analysis.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at http://www.nist.gov/srm.

SRM 2628a Page 6 of 6