

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 4415H

SRM Name: Xenon-133 Radioactivity Standard **Other Means of Identification:** Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) consists of a standardized and certified quantity of radioactive xenon-133 and non-radioactive xenon gas, unpressurized, in a stable and homogeneous mixture. It is intended primarily for the calibration of instruments that are used to measure radioactivity. A unit of SRM 4415H consists of approximately 5 mL of gas, contained in a flame-sealed borosilicate-glass ampoule.

Company Information

National Institute of Standards and Technology Standard Reference Materials Program 100 Bureau Drive, Stop 2300 Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200 FAX: 301-948-3730 E-mail: SRMMSDS@nist.gov Website: http://www.nist.gov/srm Emergency Telephone ChemTrec: 1-800-424-9300 (North America) +1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Radiological Hazard

Warning: THIS MATERIAL SHOULD ONLY BE USED BY PERSONS QUALIFIED TO HANDLE RADIOACTIVE MATERIAL!

This product contains licensed radioactive material and is therefore subject to the requirements of 10 CFR Part 20 (e.g., public and occupational exposure limits, waste disposal). At a minimum, the basic radiation safety principles of time, distance, and shielding, and appropriate radiation contamination control should be practiced to avoid/minimize any external and/or internal exposure. Consult with your Radiation Safety office for your facility's radiation safety requirements/precautions specific to the radionuclide(s) (including its activity and chemical/physical form) in this Radioactive SRM.

SRM 4415H is a radioactive material, Xenon-133, with a massic activity of approximately 12 GBq in non-radioactive xenon gas. Xenon-133 decays by beta-particle emission to excited levels of Cs-133. During the decay process, x-rays and gamma rays with energies from 3.8 keV to 384 keV are also emitted.

Classification

Physical Hazard: There are no known physical hazards associated with this material.

Health Hazard: Not classified.

Label Elements

Symbol: No symbol/No pictogram. **Signal Word:** No signal word.

Hazard Statement(s): Not applicable.

Precautionary Statement(s): Not applicable.

Hazards Not Otherwise Classified: None.

Ingredients(s) with Unknown Acute Toxicity: None.

SRM 4415H Page 1 of 6

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Xenon-133 in non-radioactive xenon gas.

Other Designations: Not applicable.

Components are listed in compliance with OSHA's 29 CFR 1910.1200; for the actual values see the NIST

Certificate.

Components	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)
Xenon Gas	7440-63-3	231-172-7	>99.9
Xenon-133	Not applicable	Not applicable	0.00005

4. FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

Skin Contact: N/A **Eye Contact:** N/A

Ingestion: Ingestion of a gas is unlikely. As this product is a gas, refer to the inhalation section.

Most Important Symptoms/Effects, Acute and Delayed: Not applicable.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Negligible fire hazard. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media:

Suitable: Use extinguishing media appropriate to the surrounding fire.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: No information available.

Special Protective Equipment and Precautions for Fire-Fighters: Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

NFPA Ratings: (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 1 Fire = 0 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

This material is radioactive. Immediately notify safety personnel of a leak.

Personal Precautions, Protective Equipment, Methods and Materials for Containment and Clean up:

Radiological Emergency Procedures:

The following is a guide for first responders. The following actions, including remediation, should be carried out by qualified individuals. In cases where a life-threatening injury occurs concurrent with personal contamination, treat the injury **first**.

Do not touch damaged packages. Handle as a radioactive material leak. In addition to those actions described below, the guidelines in the Emergency Response Guidebook (ERG) provide more specific measures that should be followed.

In case of a breakage, evacuate the room closing the door behind you and contact safety personnel

SRM 4415H Page 2 of 6

7. HANDLING AND STORAGE

Safe Handling Precautions and Storage: This material is radioactive. Use only with adequate ventilation. Do not puncture or incinerate container. Store and handle in accordance with all current regulations and standards. See NRC 10 CFR 20 or state regulations. See Section 8, "Exposure Controls and Personal Protection".

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits:

Xe-133

 $DAC = 1 \times 10^{-4} \,\mu\text{Ci/mL}$

OSHA: See OSHA 29 CFR and NRC 10 CFR 20.

ACGIH: See International Commission on Radiological Protection guidelines

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye/Face Protection: Wear splash resistant safety goggles. An eye wash station should be readily available near areas of use.

Skin and Body Protection: Wear protective clothing and appropriate gloves.

Appearance (physical state, color, etc.): Molecular Formula: Molar Mass (g/mol): Odor: Odor: Odor threshold: pH: Evaporation rate: Melting point/freezing point (°C): Relative Density (g/L) as specific gravity (water = 1): Vapor Pressure (mmHg): Vapor Pressure (mmHg): Vapor Density (air = 1): Viscosity (cP): Solubility(les): Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Rotavailable not available Flash Point (°C): not available Not avail	Descriptive Properties:	Xenon (>99 % of this SRM)		
Molar Mass (g/mol): Odor: Odor threshold: pH: not available Evaporation rate: Melting point/freezing point (°C): Relative Density (g/L) as specific gravity (water = 1): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, LEL (Volume %): Flammability (solid, gas): 131.3 odorless odorles odorles odorles odorles odorles odorles odorlable odorles odorlable odorles odorlable odorles odorlable odor	Appearance (physical state, color, etc.):	colorless gas		
Odor: Odor threshold: pH: Differential point (°C): Relative Density (g/L) as specific gravity (water = 1): Vapor Pressure (mmHg): Vapor Pressure (mmHg): Vapor Density (air = 1): Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Autoignition Temperature (°C): Thermal Decomposition (°C): Differential boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Plant Not available Flammability (solid, gas): Odorless not available Flammability (solid, gas):	Molecular Formula:	Xe		
Odor threshold: pH: not available not available Melting point/freezing point (°C): Relative Density (g/L) as specific gravity (water = 1): Sears Vapor Pressure (mmHg): Vapor Density (air = 1): Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): not available Initial boiling point and boiling range (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): not available Flash Point (°C): Flammability (solid, gas):	Molar Mass (g/mol):	131.3		
pH: Evaporation rate: Melting point/freezing point (°C): Relative Density (g/L) as specific gravity (water = 1): Sa878 Vapor Pressure (mmHg): Vapor Density (air = 1): Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Inot available Inot available Flash Point (°C): Inot available Flash Point (°C): Inot available Inot available Flash Point (°C): Inot available Inot available Inot available Flammability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	Odor:	odorless		
Evaporation rate: Melting point/freezing point (°C): Relative Density (g/L) as specific gravity (water = 1): S.8878 Vapor Pressure (mmHg): Vapor Density (air = 1): Vapor Density (air = 1): Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Flash Point (°C): Flash Point (°C): Flash Point (°C): Flammability (solid, gas): not available not available not available Flash Point (°C): not available not available not available Thermability (solid, gas): not available not available not available not available	Odor threshold:	not available		
Melting point/freezing point (°C): Relative Density (g/L) as specific gravity (water = 1): Solubility (air = 1): Solubility (ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Autoignition Temperature (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Inot available Thermability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	pH:	not available		
Relative Density (g/L) as specific gravity (water = 1): Vapor Pressure (mmHg): Vapor Density (air = 1): Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Flash Point (°C): Flammability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	Evaporation rate:	not available		
Vapor Pressure (mmHg): Vapor Density (air = 1): Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Inot available not available Flash Point (°C): Flammability (solid, gas): not available not available Not available not available not available Thermal Decomposition (°C): not available not available not available Not available	Melting point/freezing point (°C):	-112 (-170 °F)		
Vapor Density (air = 1): Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Flash Point (°C): Flammability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	Relative Density (g/L) as specific gravity (water = 1):	5.8878		
Viscosity (cP): Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): not available Thermal Decomposition (°C): not available Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): not available Flash Point (°C): not available Flash Point (°C): not available Thermal Decomposition (°C): not available not available Thermal Stability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	Vapor Pressure (mmHg):	760 at -108 °C		
Solubility(ies): Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Inot available Flash Point (°C): Inot available Flash Point (°C): Inot available Inot available Flammability (solid, gas): Thermal Stability AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	Vapor Density (air = 1):	4.561		
Partition coefficient (n-octanol/water): Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Thermal Decomposition (°C): Inot available Explosive Limits, UEL (Volume %): Inot available Flash Point (°C): Inot available Flammability (solid, gas): This material is stable at normal temperatures and pressure.	Viscosity (cP):	not available		
Thermal Stability Properties: Xenon (>99 % of this SRM) Autoignition Temperature (°C): not available Thermal Decomposition (°C): not available Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): not available Explosive Limits, UEL (Volume %): not available Flash Point (°C): not available Flammability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	Solubility(ies):	not available		
(>99 % of this SRM) Autoignition Temperature (°C): Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Inot available Explosive Limits, UEL (Volume %): Flash Point (°C): Flash Point (°C): Inot available Inot available Flammability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.	Partition coefficient (n-octanol/water):	not available		
Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Inot available Explosive Limits, UEL (Volume %): Inot available Flash Point (°C): Inot available Flammability (solid, gas): Inot available To available The material is stable at normal temperatures and pressure.	Thermal Stability Properties:			
Thermal Decomposition (°C): Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Inot available Explosive Limits, UEL (Volume %): Inot available Flash Point (°C): Inot available Flammability (solid, gas): Inot available Total available Inot ava	Autoignition Temperature (°C):	not available		
Initial boiling point and boiling range (°C): Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Flammability (solid, gas): not available not available not available To STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.				
Explosive Limits, LEL (Volume %): Explosive Limits, UEL (Volume %): Flash Point (°C): Flammability (solid, gas): not available not available not available To Stability And Reactivity Reactivity: This material is stable at normal temperatures and pressure.				
Explosive Limits, UEL (Volume %): Flash Point (°C): Flammability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.		` '		
Flash Point (°C):				
Flammability (solid, gas): 10. STABILITY AND REACTIVITY Reactivity: This material is stable at normal temperatures and pressure.				
Reactivity: This material is stable at normal temperatures and pressure.		not available		
	10. STABILITY AND REACTIVITY			
Stability: X Stable Unstable	Reactivity: This material is stable at normal temperatures and	d pressure.		

SRM 4415H Page 3 of 6

Conditions to Avoid: Avoid heat.					
Incompatible Materials: Halogens.					
Fire/Explosion Information: See Section 5, "Fire Fighting Measures".					
Hazardous Decomposition: No data available.					
Hazardous Polymerization: Will Occur X Will Not Occur					
11. TOXICOLOGICAL INFORMATION					
Route of Exposure: X Inhalation Skin Ingestion					
Symptoms Related to the Physical, Chemical and Toxicological Characteristics: No adverse effects reported.					
Potential Health Effects (Acute, Chronic and Delayed):					
Inhalation: No adverse effects reported.					
Skin Contact: No adverse effects reported.					
Eye Contact: No adverse effects reported.					
Ingestion: No adverse effects reported.					
Numerical Measures of Toxicity:					
Acute Toxicity: No data available.					
Skin Corrosion/Irritation: No data available.					
Serious Eye Damage/Eye Irritation: No data available.					
Respiratory Sensitization: No data available.					
Skin Sensitization: No data available.					
Germ Cell Mutagenicity: No data available.					
Carcinogenicity: No data available.					
Listed as a Carcinogen/Potential Carcinogen Yes X No Xenon is not listed by NTP, IARC or OSHA as a carcinogen.					
Radiological Hazard: Xe-133 Ionizing radiation is a known carcinogen.					
Reproductive Toxicity: No data available.					
Specific Target Organ Toxicity, Single Exposure: No data available.					
Specific Target Organ Toxicity, Repeated Exposure: No data available.					
Aspiration Hazard: No data available.					
12. ECOLOGICAL INFORMATION					
Ecotoxicity Data: No ecotoxicity data listed.					
Persistence and Degradability: No data available.					
Bioaccumulative Potential: No data available.					
Mobility in Soil: No data available.					
Other Adverse Effects: No data available.					

13. DISPOSAL CONSIDERATIONS

Waste Disposal: This material is radioactive. Dispose in accordance with all applicable federal, state, and local regulations for **RADIOACTIVE** materials. See NRC 10 CFR 20 subpart K.

SRM 4415H Page 4 of 6

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA:

Primary Risk: UN2915, Hazard Class 7, Radioactive material, Type A Package.

Subsidiary Risk: Not applicable.

15. REGULATORY INFORMATION

U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): Not regulated.
SARA Title III Section 302 (40 CFR 355.30): Not regulated.
SARA Title III Section 304 (40 CFR 355.40): Not regulated.
SARA Title III Section 313 (40 CFR 372.65): Not regulated.
OSHA Process Safety (29 CFR 1910.119): Not regulated.
SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):
ACUTE HEALTH: No.
CHRONIC HEALTH: No.
FIRE: No.
REACTIVE: No.

No.

State Regulations:

PRESSURE:

California Proposition 65: No components are regulated.

U.S. TSCA Inventory: Xenon is listed on inventory.

TSCA 12(b), Export Notification: No components are listed.

Canadian Regulations: WHMIS Information is not provided for this material.

SRM 4415H Page 5 of 6

16. OTHER INFORMATION

Issue Date: 20 May 2015

Sources: ChemAdvisor, Inc., MSDS Xenon, 20 March 2015.

OSHA 29 CFR, Subpart Z, Ionizing radiation, 1910.1096.

NRC 10 CFR 20, Standards for Protection Against Radiation.

DOT 49 CFR 173, Shippers General Requirements for Shipments and Packages.

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial Hygienists	NIOSH	National Institute for Occupational Safety and Health
ALI	Annual Limit on Intake	NIST	National Institute of Standards and Technology
CAS	Chemical Abstracts Service	NRC	Nuclear Regulatory Commission
CEN	European Committee for Standardization	NTP	National Toxicology Program
CERCLA	Comprehensive Environmental Response,	OSHA	Occupational Safety and Health Administration
CLRCLA	Compensation, and Liability Act	OSHA	Occupational Safety and Health Administration
CFR	Code of Federal Regulations	PEL	Permissible Exposure Limit
CPSU	<u>e</u>	RCRA	*
	Coal Mine Dust Personal Sample Unit		Resource Conservation and Recovery Act
DOT	Department of Transportation	REL	Recommended Exposure Limit
EC50	Effective Concentration, 50 %	RM	Reference Material
EINECS	European Inventory of Existing Commercial	RQ	Reportable Quantity
	Chemical Substances		
EPCRA	Emergency Planning and Community Right-to-Know	RTECS	Registry of Toxic Effects of Chemical Substances
	Act		
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
IATA	International Air Transportation Agency	SCBA	Self-Contained Breathing Apparatus
IDLH	Immediately Dangerous to Life and Health	SRM	Standard Reference Material
ISO	International Organization for Standardization	STEL	Short Term Exposure Limit
LC50	Lethal Concentration, 50 %	TDLo	Toxic Dose Low
LD50	Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPO	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
	Time Salety and Treater Training action	WHMIS	Workplace Hazardous Materials Information System
		** 111*1110	" orkpiace Hazardous Materials Information System

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of this material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The certified values for this material are given in the NIST Certificate.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at http://www.nist.gov/srm.

SRM 4415H Page 6 of 6