

Introduction to Dependent Types

Eagan Technology Unconference

Joseph Ching

September 22, 2015

Table of Contents

1 Preface

Table of Contents

1 Preface

2 Review of Basics

- Test
- Values and Types
- Functions

Table of Contents

1 Preface

2 Review of Basics

- Test
- Values and Types
- Functions

3 Questions

Quick Question

How many are familiar with this topic?

A Joke

This is not a $\mathsf{m-}$ tutorial.

A Joke

This is not a `m-` tutorial.
Nor is it a `lens` tutorial

A Joke

This is not a `m-` tutorial.

Nor is it a `lens` tutorial (aka the new new `m-` tutorial...)

A Joke

This is not a `m-` tutorial.

Nor is it a `lens` tutorial (aka the new new `m-` tutorial...

...because arrows *were* the new `m-` tutorials).

About This Talk

Agda, Idris, Coq and co^* have full support for dependent types.

About This Talk

Agda, Idris, Coq and co^* have full support for dependent types. Because of that, it's harder to see the build up, so we won't be directly using them in this talk.

About This Talk

Agda, Idris, Coq and co* have full support for dependent types. Because of that, it's harder to see the build up, so we won't be directly using them in this talk.

Honestly though, it's because they're way over my head :(

() There was another mini joke here...*

About This Talk

But we will be using Haskell though :)

About This Talk

But we will be using Haskell though :)

It's not truly dependent, but we can do more and more with each language extension that comes along.

For the examples, there also will be loose translation to imperative/OOP; though please keep in mind that they are not the same thing at all.

Test

Syntax highlighting test reference, to be removed later.

```
-- Comment
data Maybe a = Nothing | Just a
               deriving (Show, Eq)

fmap :: Functor f => (a -> b) -> f a -> f b
map _ []          = []
map f (x:xs) = f x : map f xs

type family TF a :: *
type instance TF Int = Bool
```

Test

Couldn't quite yet get listing to work with overlay yet.

```
{- block comment -}  
foo :: Bool -> Int -> String  
foo False 0 = "Bad"  
foo True 0 = "Questionable"  
foo False n = "Fake"  
foo True n = "Read"
```


Test

Pausing within listing is ok?

```
{-# LANGUAGE KitchenSink #-}  
zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]
```

Test

Pausing within listing is ok?

```
{-# LANGUAGE KitchenSink #-}  
zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]  
zipWith _ [] _ = []
```

Test

Pausing within listing is ok?

```
{-# LANGUAGE KitchenSink #-}  
zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]  
zipWith _ [] _ = []  
zipWith _ _ [] = []
```

Test

Pausing within listing is ok?

```
{-# LANGUAGE KitchenSink #-}
zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]
zipWith - [] - = []
zipWith - - [] = []
zipWith f (x:xs) (y:ys) = f x y : zipWith f xs ys
```

better yet

```
{-# LANGUAGE KitchenSink #-}
zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]
zipWith f (x:xs) (y:ys) = f x y : zipWith f xs ys
zipWith - - - = []
```

Values and Types

Values has Types, or **Values** are classified by **Types**.

```
..., -1, 0, 1, 2, 3, ... :: Int
```

Values and Types

Values has Types, or **Values** are classified by **Types**.

```
..., -1, 0, 1, 2, 3, ... :: Int  
True, False :: Bool
```

Values and Types

Values has Types, or **Values** are classified by **Types**.

```
..., -1, 0, 1, 2, 3, ... :: Int
True, False :: Bool
'a', 'b', 'c' :: Char
```

Values and Types

Values has Types, or **Values** are classified by **Types**.

```
..., -1, 0, 1, 2, 3, ... :: Int
True, False :: Bool
'a', 'b', 'c' :: Char
"abc" :: String ~ [Char]
```

Values are also called **Terms**

About Types

How are the types defined?

- Some are built in magic: `Int`, `Char`, functions

About Types

How are the types defined?

- Some are built in magic: `Int`, `Char`, functions
- Some are built in sugar: `list`, `tuples`
 - We can still define these ourselves without the sugar

About Types

How are the types defined?

- Some are built in magic: `Int`, `Char`, functions
- Some are built in sugar: list, tuples
 - We can still define these ourselves without the sugar
- Rest can be user defined: `Bool`, `String`, `Maybe`

Empty and Unit Types

Define new data type with `data`.

Empty and Unit Types

Define new data type with `data`.

- Left hand side (LHS) - `Type` constructor

Empty and Unit Types

Define new data type with `data`.

- Left hand side (LHS) - `Type` constructor
- Right hand side (RHS) - `Value` constructor

Empty and Unit Types

Define new data type with `data`.

- Left hand side (LHS) - `Type` constructor
- Right hand side (RHS) - `Value` constructor

```
data Bool = False | True
```

Here, `Bool` is the `Type` constructor, `True` and `False` are `Value` constructors.

Does this remind you of anything?

Empty and Unit Types

Define new data type with `data`.

- Left hand side (LHS) - `Type` constructor
- Right hand side (RHS) - `Value` constructor

```
data Bool = False | True
```

A loose translation:

```
enum Bool { False, True }
```


Sum Types

Simply, **Types** with more than one constructors.

Sum Types

Simply, **Types** with more than one constructors.

```
data Bool = False | True
data Weekdays = Sunday | Monday | Tuesday | Wednesday
               | Thursday | Friday | Saturday
```

Sum Types

Simply, **Types** with more than one constructors.

```
data Bool = False | True
data Weekdays = Sunday | Monday | Tuesday | Wednesday
               | Thursday | Friday | Saturday
```

Can parametrize over another type:

Sum Types

Simply, **Types** with more than one constructors.

```
data Bool = False | True
data Weekdays = Sunday | Monday | Tuesday | Wednesday
               | Thursday | Friday | Saturday
```

Can parametrize over another type:

```
data Identity a = Identity a
```

Sum Types

Simply, **Types** with more than one constructors.

```
data Bool = False | True
data Weekdays = Sunday | Monday | Tuesday | Wednesday
               | Thursday | Friday | Saturday
```

Can parametrize over another type:

```
data Identity a = Identity a
```

A very loose translation (assuming capitalization implies constructor):

```
enum Identity<T> {
  Identity(T t)
}
```

Sum Types

Simply, **Types** with more than one constructors.

```
data Bool = False | True
data Weekdays = Sunday | Monday | Tuesday | Wednesday
               | Thursday | Friday | Saturday
```

Can parametrize over another type:

```
data Identity a = Identity a
```

And its **Type**:

```
Identity :: a -> Identity t
```

Sum Types

Another example:

```
data Maybe a = Nothing | Just a
```

Sum Types

Another example:

```
data Maybe a = Nothing | Just a
```

The very loose translation:

```
enum Maybe<T> {  
  Nothing,  
  Just(T t)  
}
```


Sum Types

Another example:

```
data Maybe a = Nothing | Just a
```

The very loose translation:

```
enum Maybe<T> {  
  Nothing,  
  Just(T t)  
}
```

The Types of the two Value constructors:

```
Nothing  :: Maybe a  
Just     :: a -> Maybe a
```

Sum Types

A more involved example with `Either`:

```
data Either a b = Left a | Right b
```

Sum Types

A more involved example with `Either`:

```
data Either a b = Left a | Right b
```

Another very loose translation:

```
enum Either<T1, T2> {  
  Left(T1 t1),  
  Right(T2 t2)  
}
```

Sum Types

A more involved example with `Either`:

```
data Either a b = Left a | Right b
```

Another very loose translation:

```
enum Either<T1, T2> {  
  Left(T1 t1),  
  Right(T2 t2)  
}
```

The two `Value` constructors have `Types`:

```
Left  :: a -> Either a b  
Right :: b -> Either a b
```

Product Types

Types with Recursion

Phantom Types

Language Extension - GADTs

Type Synonyms

Functions

Higher-order Functions

Questions?