

THE UNIVERSITY
WISCONSIN
MADISON

Grant Roberts, Kevin Johnson, Carson Hoffman, Laura Eisenmenger, and Oliver Wieben


4D Flow MRI Poster #30

- Motion encoding using bipolar gradients

Background phase

- Non-linear gradients
- Concomitant fields
- Eddy currents

Velocity in Background Tissue








Grant Roberts, Kevin Johnson, Carson Hoffman, Laura Eisenmenger, and Oliver Wieben

Manual background phase correction (BPC)

- Subtract Polynomial fit from velocity data
 - $\phi(x, y, z) = a_1 x^3 + a_2 y^3 + a_3 z^3 + a_4 x^2 z + a_5 y^2 x + \cdots$








Grant Roberts, Kevin Johnson, Carson Hoffman, Laura Eisenmenger, and Oliver Wieben

Cranial 4D Flow Analysis Tool

- Condenses 6G 4D flow data to 1G .mat file
 - Can be loaded efficiently
- Requires manual BPC
 - MATLAB GUI

Can we eliminate <u>manual</u> BPC and create preprocessed file in reconstruction?










Grant Roberts, Kevin Johnson, Carson Hoffman, Laura Eisenmenger, and Oliver Wieben




- Manual and automatic BPC tested on 10 subjects.
- Absolute error in background tissue was similar for manual & automatic BPC.












THE UNIVERSITY
WISCONSIN

Grant Roberts, Kevin Johnson, Carson Hoffman, Laura Eisenmenger, and Oliver Wieben



Raw Velocity (x)




Automatic BPC



Manual BPC



Automatic+Manual BPC





THE UNIVERSITY
WISCONSIN
MADISON

Grant Roberts, Kevin Johnson, Carson Hoffman, Laura Eisenmenger, and Oliver Wieben

Conclusions

Poster #30

- Automatic BPC was sufficient in reducing phase offsets.
- Data loading time was reduced 6 minutes to 20 seconds and file sizes were reduced from 6G to 1G.

