

OSSP Practical 8

Code

```
#include <stdio.h>
#include <unistd.h>
#include <string.h>
#include <sys/wait.h>

int main() {

    int fd[2];
    pid_t pid;

    char message[] = "Hello from Parent";
    char buffer[100];

    if (pipe(fd) == -1) {
        printf("Pipe creation failed\n");
        return 1;
    }

    pid = fork();

    if (pid < 0) {
        printf("Fork failed\n");
        return 1;
    }
```

```
}

if (pid > 0) {
    // Parent
    close(fd[0]);

    write(fd[1], message, strlen(message) + 1);

    printf("Parent sent: %s\n", message);

    close(fd[1]);

    wait(NULL);
}
else {
    // Child
    close(fd[1]);

    read(fd[0], buffer, sizeof(buffer));

    printf("Child received: %s\n", buffer);

    close(fd[0]);
}

return 0;
}
```

Output

```
gssggy@Gyanadeep:~/os_practicals$ gedit practical8.c
** (gedit:4328): WARNING **: 06:59:47.759: Could not load Peas repository: Typelib file for namespace 'Peas', version '1.0' not found
** (gedit:4328): WARNING **: 06:59:47.760: Could not load PeasGtk repository: Typelib file for namespace 'PeasGtk', version '1.0' not found
gssggy@Gyanadeep:~/os_practicals$ gcc practical8.c -o practical8
gssggy@Gyanadeep:~/os_practicals$ ./practical8
Parent sent: Hello from Parent
Child received: Hello from Parent
gssggy@Gyanadeep:~/os_practicals$ |
```