European Journal of Operational Research

The waste collection routing problem with time-varying stochastic demand: A machine learning based approach

--Manuscript Draft--

Manuscript Number:	
Article Type:	Theory and Methodology Paper
Section/Category:	(O) Routing
Keywords:	Vehicle Routing; Urban Logistics; Waste Collection; Stochastic Programming; Machine Learning
Corresponding Author:	Francesca Vocaturo Università della Calabria Arcavacata di Rende, ITALY
First Author:	Simona Mancini
Order of Authors:	Simona Mancini
	Alessio Sclafani
	Giuseppe Stecca
	Francesca Vocaturo
Abstract:	We introduce the Waste Collection Routing Problem with Time-Varying Stochastic Demand (WCRP-TVSD), in which a homogeneous fleet of vehicles must visit a set of collection points under capacity constraints. We divide the planning horizon (or day) into not-overlapping time slots. Each collection point is associated with a known initial demand. For each collection point and for each time slot, additional demand may appear. The demand increments are revealed upon arrival at the collection points, but an estimate of such additional demand is known in advance and depends on the nature of the collection point and the time of day in which collection takes place. The WCRP-TVSD consists of designing vehicle routes that visit each collection point exactly once during the planning horizon. The aim is to minimize the expected total cost given by net routing costs and penalties associated with uncollected waste at the end of the planning horizon. The WCRP-TVSD can be formulated as a multi-period two-stage stochastic program and solved through a traditional methodology employing scenarios. For the problem we also propose a machine learning based approach that encompasses several deterministic policies. In order to empirically prove the effectiveness of this approach, we present extensive computational results.
Opposed Reviewers:	

Powered by Editorial Manager® and ProduXion Manager® from Aries Systems Corporation

UNIVERSITÀ DELLA CALABRIA
DIPARTIMENTO DI ECONOMIA, STATISTICA E FINANZA
"Giovanni Anania" - DESF

January 26, 2026

Dear Editor,

I would like to submit the article

"The waste collection routing problem with time-varying stochastic demand: A machine learning based approach" by Simona Mancini, Alessio Sclafani, Giuseppe Stecca, and myself

for possible publication in *European Journal of Operational Research*.

Thank you for taking care of our work.

Best regards,

Francesca Vocaturo

Dipartimento di Economia, Statistica e Finanza
"Giovanni Anania" - DESF
Università della Calabria
Via P. Bucci, Cubo 0C - 1C
87036 Rende (CS) - ITALIA

Amministrazione:
Tel. (+39) 0984.492434 - **Fax** (+39) 0984.492421
Didattica:
Tel. (+39) 0984.492438 - **Fax** (+39) 0984.492435
Posta certificata:
dipartimento.desf@pec.unical.it

www.desf.unical.it

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Manuscript (With Author Details)

Click here to view linked References

The waste collection routing problem with time-varying stochastic demand: A machine learning based approach

Simona Mancini[a,b], Alessio Sclafani[a], Giuseppe Stecca[c], Francesca Vocaturo[d]

[a] *Dipartimento di Ingegneria, Università degli Studi di Palermo, Viale delle Scienze 7, 90128, Palermo, Italy*
[b] *Department of Operations, Energy, and Environmental Management, University of Klagenfurt, Universitätsstraße 65-67, 9020, Klagenfurt, Austria*
[c] *Istituto di Analisi dei Sistemi ed Informatica "Antonio Ruberti", Consiglio Nazionale delle Ricerche, Via dei Taurini 19, 00185, Roma, Italy*
[d] *Dipartimento di Economia, Statistica e Finanza "Giovanni Anania", Università della Calabria, via Pietro Bucci, Cubo 0/C, 87036, Arcavacata di Rende (CS), Italy*

Abstract

We introduce the Waste Collection Routing Problem with Time-Varying Stochastic Demand (WCRP-TVSD), in which a homogeneous fleet of vehicles must visit a set of collection points under capacity constraints. We divide the planning horizon (or day) into not-overlapping time slots. Each collection point is associated with a known initial demand. For each collection point and for each time slot, additional demand may appear. The demand increments are revealed upon arrival at the collection points, but an estimate of such additional demand is known in advance and depends on the nature of the collection point and the time of day in which collection takes place. The WCRP-TVSD consists of designing vehicle routes that visit each collection point exactly once during the planning horizon. The aim is to minimize the expected total cost given by net routing costs and penalties associated with uncollected waste at the end of the planning horizon. The WCRP-TVSD can be formulated as a multi-period two-stage stochastic program and solved through a traditional methodology employing scenarios. For the problem we also propose a machine learning based approach that encompasses several deterministic policies. In order to empirically prove the effectiveness of this approach, we present extensive computational results.

Keywords: Vehicle Routing, Urban Logistics, Waste Collection, Stochastic Programming, Machine Learning

Email addresses: simona.mancini@unipa.it, simona.mancini@aau.at (Simona Mancini), alessio.sclafani@unipa.it (Alessio Sclafani), giuseppe.stecca@iasi.cnr.it (Giuseppe Stecca), vocaturo@unical.it (Francesca Vocaturo)

1. Introduction

Waste collection is an increasingly relevant issue for local administrators, as it has a significant impact on public health, fouls up the environment, and affects the appearance of urban areas. Worldwide, huge amounts of waste must be handled every day, implying considerable collection truck coverage and significant production of greenhouse gas emissions. As an example, 511 kg of municipal waste per capita were generated in Europe in 2023 (Eurostat, 2025). Planning specific systems and handling tailored activities represent complex processes that involve uncertainty and require expertise in a variety of disciplines. These processes can be adequately addressed only by closely examining the environment surrounding the decisions that must be made and focusing on the key elements. More specifically, waste management involves a number of strategic, tactical, and operational decisions, such as selection of waste manipulation technologies, location of treatment sites and landfills, future capacity expansion strategies of the sites, waste flow allocation to processing facilities and landfills, service territory partitioning into districts, fleet and crew composition determination (Ghiani et al., 2014). In addition, decisions concerning waste collection and transportation must be made. These decisions heavily rely on solving a vehicle routing problem (VRP) and their effectiveness is based on the successful estimation of quantities to be picked up over time (Hess et al., 2024). In practical cases, waste collection and transportation are often inefficient due to the high uncertainty associated with bin fill levels, resulting in routes that visit empty bins or in bins overflowing due to lack of routes. An example of inefficient usage of resources is provided by Ramos et al. (2018). These authors refer to a case study in which real data collected from a Portuguese company over a 6-month period show that only 40% of the bins were collected with a fill level exceeding 75% of the volume.

Technologies such as geographic information system (GIS) and smart sensors can provide information on bin fill levels and improve pickup activities when integrated with methods in the field of Operations Research and Management Science. This type of information could be used, e.g., by municipal decision makers and planners in combination with dynamic optimization approaches to effectively design smart collection routes. In addition, the sensors installed in the bins could be used to collect historical data and design appropriate probability distributions for waste levels within different optimization tools or discrete-event simulation frameworks. For instance, given a history of observations from bins equipped with sensors, Markov et al. (2020) use a statistical model to estimate the expected demand and a forecasting error representing the

level of uncertainty. Then, they propose a stochastic approach for a real-world waste collection problem which includes a range of practical and policy-related constraints. The reader is referred to the articles of Johansson (2006), Rovetta et al. (2009), and de Morais et al. (2024) for other interesting contributions on the topic.

Our study points in this direction by adding some novel elements to the scientific discussion. It comes from the observation that the bin fill levels depend not only on the type of *collection point* (CP) but also on the time of day in which collection takes place. More specifically, we address the Waste Collection Routing Problem with Time-Varying Stochastic Demand (WCRP-TVSD). In our problem a set of CPs must be visited by a set of homogeneous capacitated vehicles located at a common depot. We divide the planning horizon (or day) in not-overlapping time slots (or periods). Each CP is associated with a known initial demand. For each CP and for each time slot, additional (uncertain) demand may arise. We represent this increment as a random variable with a known probability distribution. It is worth noting that the use of smart technologies may provide an accurate estimate of the demand increments in advance (e.g., historical data and forecasting techniques may be utilized to design adequate probability distributions). In addition, we point out that these increments depend on the nature of the CP, as well as the time slot. For example, a restaurant is more likely to produce a higher amount of waste in the afternoon than in the early morning, whereas a school probably shows the opposite pattern.

The WCRP-TVSD consists of designing vehicle routes for service purposes that visit each CP exactly once during the day. The set of planned routes must be consistent with the number of vehicles available for service. The aim is to minimize the expected total cost given by net routing costs and penalties associated with uncollected waste at the end of the day. We assume that a vehicle visiting a CP loads all the waste if its residual capacity is sufficient; otherwise, it partially loads the waste or totally skips the CP. However, the amount of waste left over for the next day in a specific CP is not due only to events of "capacity saturation". Since a CP is visited exactly once during the day, there is a natural accumulation of waste after the planned visit. Note that large amounts of waste left over for the next day represent an undesirable event, especially in terms of urban blight. Therefore, it is fundamental to select the most appropriate period to visit each CP.

In order to solve the WCRP-TVSD, we rely on two-stage stochastic programming with recourse (Ruszczynski and Shapiro, 2003). In particular, we propose for the WCRP-TVSD a scenario-based approach. In addition, we describe a faster machine learning procedure that

encompasses several deterministic policies. Integrating machine learning and optimization represents a promising way to boost decision making. A recent example of integration is given by Bibak and Karaesmen (2025) for a data-driven lot sizing problem with random yield. Bengio et al. (2021) survey different uses of machine learning to help solve combinatorial optimization problems. Furthermore, an overview on integration of machine learning as a component of a metaheuristic framework can be found in Karimi-Mamaghan et al. (2022). Most papers integrate machine learning in optimization approaches to find promising initial solution or to decide which search neighborhood to apply, while in our case machine learning is used to predict which policy must be selected among a pool of strategies, based on the instance features.

This paper makes the following contributions to the scientific literature. First, we deal with a new problem in the area of waste collection routing which warrants further investigation in uncertain environments. Second, we focus on time-varying stochastic demands; to the best of our knowledge, the way to treat this aspect represents a novelty in the field. Finally, we propose a tailored machine learning based approach that combines the speed of deterministic optimization with the quality of stochastic programming in uncertain environments.

The remainder of the article is organized as follows. Review articles and relevant works in the scientific literature are discussed in Section 2. A formal description of the problem is given in Section 3. Section 4 describes the solution methodology and Section 5 presents the computational experiments. Finally, Section 6 concludes the article and presents some future research directions.

2. Related Literature

With transitions in their economies, many countries have also witnessed an explosion of waste quantities. In this context, waste has not remained an issue to be addressed by local urban administrators alone. Waste management has become a subject of importance for engineers as well as medical operators, psychologists, economists, climate scientists, and many others practitioners. This topic is also largely discussed by academics, resulting in a huge amount of books on the subject. An example is given by the volume of Chandrappa and Das (2012) that: (*i*) includes history, psychology, economics of solid waste, (*ii*) investigates variation in approaches to tackle waste over time and region as well as safety issues, (*iii*) deals with biomedical waste, hazardous waste, disaster waste, waste from electrical and electronic material, radioactive waste, etc. The scientific literature also presents many surveys on waste

management, some of which are briefly described in Section 2.1. In addition to review articles dealing mainly with academic literature, there are manuscripts with a more practical focus on waste management. In particular, in Section 2.2, we discuss articles in which transportation problems correlated with waste collection operations in uncertain environments are modeled and solved.

2.1. Surveys on Waste Collection

Dealing with waste management systems leads to solving several optimization problems and, therefore, to taking advantage of Operations Research and Management Science. In the following, we only cite review articles referring to models and methods developed within the scopes of these disciplines.

Malladi and Sowlati (2018) present a literature review based on content analysis where sustainability aspects are central. Although their aim is to illustrate studies on sustainable inventory routing problems, waste management represents a consistent part of the review. In particular, studies with single-objective models cover largely areas including waste management (in reverse logistics models) and waste prevention or reduction (in models with perishable products). Instead, multi-objective models have received much less attention. In particular, the authors emphasize that in this context few studies consider a multi-criteria measure for handling hazardous materials (De Maio et al., 2025) and infectious medical waste (Wang et al., 2023). It is worth noting that two large (partly overlapping) areas regarding the environmental and economical attractive removal of waste coexist: reverse logistics and waste management. In both areas, most studies refer to the flows of discarded products leaving the end consumer. The article by Van Engeland et al. (2020) takes a synergistic point of view on reverse logistics and waste management and aims at a better integration. In particular, it gives an overview of the efforts already performed in network design (that is a strategic decision) in waste reverse supply chains by means of combinatorial optimization models.

Ghiani et al. (2014) provide an extensive bibliographic coverage of Operations Research in solid waste management up to 2013, while Alshaikh and Abdelfatah (2024) review the scientific literature from 2010 to 2023 by dividing the optimization techniques used in solid waste management into three key areas: waste collection and transportation, waste treatment and disposal, and resource recovery. Decisions concerning waste collection and transportation are the most debated in the Operations Research and Management Science fields, especially because waste collection and transportation may account for more than 70% of the total waste management

budget, most of which is for fuel costs (Tavares et al., 2009). With this in mind, Beliën et al. (2014) provide an excellent review of waste management problems with a special focus on VRPs. These authors state that the interest in waste collection routing problems has increased from 1995 on. They classify the literature on the basis of different perspectives such as type of waste, type of resource, scope, solution method, objectives, and type of constraints. Hess et al. (2024) also aim to review the state-of-the-art overlap in waste collection and routing literature. The most notable papers are categorized according to their underlying problem type, examined and brought into relation based on their common problem characteristics. The problem types comprise general, node and arc routing problems, with node routing problems being the most common, followed by arc and location routing problems. The authors point out interesting characteristics found in the literature and in practical problems, such as features related to uncertainty, risk, and sustainability. In addition, they remark that the use of intermediate facilities is very common in waste collection literature. The importance of intermediate facilities for replenishment or disposal is also stressed by Schiffer et al. (2019) that review the literature on VRPs and location routing problems with intermediate stops and discuss application areas and popular variants.

Sulemana et al. (2018) review the effect of applying optimization methods to the solid waste collection process, with particular interest in mathematical programming and GIS approaches in developing countries. The large use of GIS in solid waste collection is also remarked by Hannan et al. (2020) and Liang et al. (2022). In particular, Hannan et al. (2020) summarize studies that include different models, constraints, optimization topics, and technologies such as GIS. Future research gaps are identified by the authors through the investigation of various key issues and challenges of existing methods. In addition, significant contributions to solid waste collection in relation to the sustainable development goals (`https://sdgs.un.org/goals`) are thoroughly explained. Liang et al. (2022) describe studies in which either heuristics or a combination of heuristics with GIS are used to solve waste collection routing problems.

2.2. Waste Collection and Transportation under Uncertainty

Beltrami and Bodin (1974) provide one of the seminal applications of the VRP to waste collection by solving a practical problem in New York City. Since then, the optimization literature on waste collection and transportation has grown dramatically through theoretical and applicative contributions. Most studies are carried out in static settings using deterministic approaches. Here, we discuss only studies related to uncertain environments in which stochastic,

robust, and fuzzy optimization techniques are used, as well as dynamic, simulation-optimization and machine learning approaches.

Laporte et al. (2010) solve an uncertain version of the capacitated arc routing problem, with a focus on waste collection. Uncertainty refers to waste levels represented by random variables. Their problem is formulated within a stochastic framework in which a first-stage solution is computed, the realizations of the random variables are revealed, and a recourse action is applied in the case of failure. More specifically, their first-stage solution is a set of vehicle routes. Whenever vehicle capacity is reached along its route, failure is said to occur. The vehicle then drives to a dump site to unload and returns to the point of failure to resume its route. The authors construct a first-stage solution by means of adaptive large neighborhood search, a local search approach in which simple heuristics compete to modify the current solution. This approach is also used by Nolz et al. (2014). More specifically, these authors deal with a stochastic inventory routing problem for infectious medical waste collection, in which waste materials are produced by patients in self-treatment, stored at pharmacies, and picked up by local authorities for disposal. Two types of decisions must be taken: (*i*) when to visit each pharmacy, (*ii*) how to sequence vehicle routes. The authors consider social objectives, specifically the satisfaction of pharmacists and local authorities, as well as the minimization of public health risks. A stochastic inventory routing problem for collecting waste over a predefined planning horizon is also studied by Spinelli et al. (2025). Their problem is formulated as a multi-stage model where decisions are related to the selection of the bins to be visited and the corresponding routing plan. Uncertainty in waste accumulation is modeled by the authors through scenario trees generated via conditional density estimation and dynamic stochastic approximation techniques. The model proposed by the authors is solved using a rolling horizon approach.

Tirkolaee et al. (2018) deal with a robust periodic capacitated arc routing problem considering multiple trips and drivers and crew's working time to study the uncertain nature of the demands in an urban waste collection system. Zhang et al. (2022) propose a robust optimization model for a multi-trip collection problem with uncertain amounts of waste output and incorporate the consideration of resident satisfaction into their model. The authors control the degree of conservatism of the solutions without increasing computational complexity in the experimental phase, where real data from a case study in China are used. A practical case from China is also analyzed by Shi et al. (2024). These authors propose a robust optimization model to manage kitchen waste transportation and resource treatment under uncertainty. Battery

electric vehicles are used in the collection process.

A fuzzy optimization approach is proposed by Aliahmadi et al. (2020) to deal with an uncertain capacitated node routing problem for municipal solid waste collection. Multiple depots, multiple intermediate facilities, and multiple trips are incorporated into the system under study and real data from a practical case in Iran are considered in the computational phase. Tirkolaee et al. (2020) focus on a fuzzy multi-trip capacitated arc routing problem with the aim of minimizing the total traversing cost and the total number of vehicles within uncertain solid waste collection systems. These authors consider a real case study in Iran to assess the applicability of their methodology.

Gruler et al. (2017) present a simulation–optimization method in order to support waste collection operations under scenarios characterized by the existence of multiple depots and stochastic waste levels. More precisely, they propose a hybrid algorithm that combines metaheuristics with simulation (named *simheuristic*) and study the effects of cooperation between different depots, thus quantifying the potential savings that this cooperation could provide to city governments and waste collection companies. A simheuristic algorithm is also used by Gruler et al. (2020) to tackle a time-dependent waste collection problem with stochastic travel times and by Rabbani et al. (2019) to address a stochastic multi-period industrial waste location-routing problem. Machine learning techniques are used in waste collection especially for forecasting demand. For instance, Pasa et al. (2025) propose machine learning to forecast door-to-door waste collection by exploiting data from a northeastern Italian municipality. In particular, they predict daily waste exposure likelihood for each citizen and forecast the amount of fulfilled pickups within designated time frames, evaluating the effectiveness of their approach on monthly and weekly scales. Other applications of machine learning techniques to waste collection problems are described by Xia et al. (2022).

Among the studies most related to the one described in this manuscript we mention the following two that also deal with waste collection in stochastic environments.

- Markov et al. (2020) focus on a stochastic inventory routing problem to collect recyclable waste on a predefined planning horizon by using a heterogeneous fleet of vehicles. These authors also consider time-varying stochastic demands. However, their planning horizon is a multi-day set and the stochastic demand can vary from period to period but it is daily stationary. On the contrary, we consider a single-day planning horizon and deal with non-stationary stochastic demands while performing a same route.

- As mentioned in Section 1, the integration of machine learning with optimization represents a promising way to boost decision making. Nguyen et al. (2025) propose this integration for a waste collection problem with stochastic travel times into the electrical and electronic equipment industry. For this problem, the authors present a method that combine deep reinforcement learning with local search. More specifically, their search procedure is modeled as a Markov decision process where the deep reinforcement learning agent can adapt its strategies by taking actions based on instance-dependent heuristics derived from the search state. Here, we use machine learning in the form of classification approach not within an iterative scheme but as a single-policy selector.

3. Problem Description and Mathematical Formulation

In our problem a set of CPs must be visited by a set of homogeneous vehicles located at a common depot. All the vehicles must return to the depot before a time-limit T_{max} which is imposed by the drivers' contracts. For each CP is known an initial non-negative quantity of waste to be collected, which may increase along the day. We divide the time-horizon (or day) in non-overlapping time slots. For each CP j and each time slot t, the uncertain (non-negative) demand increment is represented as a random variable δ_{jt}, taking values within a finite interval. Since the increment depends on the time slot, time-varying demands arise and our problem is indicated by the acronym WCRP-TVSD, where TVSD stands for time-varying stochastic demand. The expected value of the demand increment and the variation range are known in advance. We assume that each CP belongs to a category (e.g., school, restaurant, private home), and different categories are associated with different demand patterns. The waste collection company has to define a routing and scheduling plan at the beginning of the time horizon, when only the initial demand is known. This plan is executed and the actual demand to collect is revealed only at the arrival of the vehicle at the various CPs. If the available capacity of the vehicle is not sufficient to load all the demand at a specific CP, or if the demand fully saturates this capacity, the vehicle returns to the depot and skips the following CPs on the route. This action represents our recourse (skipping is common in the scientific literature; see, e.g., the article of Beraldi et al., 2010). Consequently, the residual demand remains unfilled. The CP where the capacity is saturated is denoted as *skipping point*. We assume, for operational reasons, that each CP is visited exactly once during the day. The demand accumulated in each CP after the visit is left unfilled and becomes the initial demand

for the next day. At the end of the day a penalty proportional to the unfilled demand is paid since high quantities of waste left over for the next day represent an undesirable event; in fact, they cause inconvenience to the citizens, in addition to yielding to a larger workload for the company in the following day. The goal is to minimize the expected total cost given by routing costs and penalties associated with unfilled demand. The net routing cost corresponds to the cost of the actual traveled routes, which may differ from the initial routing plan cost, if one or more CPs are skipped. In fact, each time a skip occurs, we have to subtract from the original route cost the cost of the remaining arcs that are no longer traveled (*skipped arcs*) and add the cost for transit from the skipping point back to the depot. It is worth noting that two identical routing plans associated to two different schedules (i.e., plans in which the routes are the same but they are executed in different parts of the day), may yield to completely different final solutions with different associated costs. In fact, the same route could require no recourse if executed in the early morning when the demand to collect is small, but could yield to a large quantity of uncollected demand (waste cumulated after the visit of the vehicle), or could require skipping if executed in the afternoon, when the cumulated demand is larger than the vehicle capacity. The resulting decision problem can be modeled as a multi-period two-stage stochastic program. Even if the actual demand increment is revealed at different times (i.e., when the vehicle arrives at a CP), we assume a single moment at which it is possible to make new decisions and implement the recourse action against the full knowledge of the problem data. This allows us to be conservative enough with respect to the possible future scenarios, despite the actual dynamism of the recourse action (Gobbi et al., 2026).

To practically solve the WCRP-TVSD, the multi-period two-stage stochastic program can be approximated by a (deterministic) Scenario-based Model (SM) in which each scenario is associated with a realization of the random variables representing the demand increments. These increments are uniformly distributed. Formal notation to describe the scenario-based model is given in the following. Let m be the number of available vehicles and G a direct graph. Nodes $1, ..., n$ of G represent the CPs, whereas node 0 and nodes $n+1, ..., n+m$ represent the central depot (same location). In practice, there exist copies of a same depot; 0 represents the starting point of all routes and $n+h$ ($h = 1, ..., m$) represents the final node of route h. In G there are only outgoing arcs from node 0 towards all other nodes and only entering arcs in nodes $n+1, ..., n+m$ from all other nodes. A CP $j \in \{1, ..., n\}$ has outgoing arcs towards and entering arcs from all other nodes. Table 1 reports further notation in terms of sets, parameters, and decision variables. Note that, since node 0 physically coincides with nodes $n+1, ..., n+m$,

both travel costs and travel times associated with arcs from 0 to $j \in \{n+1, ..., n+m\}$ are equal to zero.

Sets and parameters	
$V = \{0, 1, ..., n, n+1, ...n+m\}$	set of all nodes
$V' = \{0, 1, ..., n\} = V \setminus \{n+1, ..., n+m\}$	set of nodes with outgoing arcs
$V'' = \{1, ..., n, n+1, ...n+m\} = V \setminus \{0\}$	set of nodes with entering arcs
S	set of scenarios
T	set of periods
M, Q_{max}	large constants
c_{ij}	travel cost for arc (i,j), $i \in V'$, $j \in V''$ $(j \neq i)$
t_{ij}	travel time for arc (i,j), $i \in V'$, $j \in V''$ $(j \neq i)$
C	vehicle capacity
e^t	starting time of period $t \in T$
ℓ^t	ending time of period $t \in T$
p	unit penalty cost associated with uncollected waste at the end of the planning horizon
d_j	initial demand for CP $j \in \{1, ..., n\}$
δ^s_{jt}	demand increment for CP $j \in \{1, ..., n\}$ at the beginning of period $t \in T$ in scenario $s \in S$
Decision variables	
x_{ij}	1 if a vehicle travels from node $i \in V'$ to node $j \in V''$ $(j \neq i)$, 0 otherwise
U_{jt}	1 if node $j \in V''$ is visited in period $t \in T$, 0 otherwise
$\bar{T}_j$	arrival time at node $j \in V$
y^s_{ij}	1 if a vehicle skips arc (i,j), $i \in V'$, $j \in V''$ $(j \neq i)$ in scenario $s \in S$, 0 otherwise
Q^s_j	theoretical cumulative load at node $j \in V$ in scenario $s \in S$ (it can exceed C)
R^s_j	quantity of waste exceeding C at node $j \in \{n+1, ..., n+m\}$ in scenario $s \in S$
L^s_j	quantity of waste accumulated at CP $j \in \{1, ..., n\}$ in scenario $s \in S$ after its visit
ρ^s_j	1 if CP $j \in \{1, ..., n\}$ is associated with event "saturation" in scenario $s \in S$, 0 otherwise
α^s_j	1 if CP $j \in \{1, ..., n\}$ is the skipping point in scenario $s \in S$, 0 otherwise

Table 1: Overview of main notation

The SM can be formulated in the following way:

$$\min \sum_{i \in V'} \sum_{j \in V''(j \neq i)} c_{ij} x_{ij} - \frac{1}{|S|} \sum_{s \in S} \sum_{i=1}^{n} \sum_{j \in V''(j \neq i)} c_{ij} y^s_{ij} + \frac{1}{|S|} \sum_{s \in S} \sum_{j=1}^{n} c_{j0} \alpha^s_j +$$

$$+\frac{1}{|S|}\sum_{s\in S}\sum_{j=n+1}^{n+m} pR_j^s + \frac{1}{|S|}\sum_{s\in S}\sum_{j=1}^{n} pL_j^s \tag{1}$$

subject to

$$\sum_{j\in V''\setminus\{i\}} x_{ij} = \sum_{j\in V'\setminus\{i\}} x_{ji} = \sum_{t\in T} U_{it}, \quad i = 1, ..., n \tag{2}$$

$$\sum_{j\in V''} x_{0j} = m \tag{3}$$

$$\sum_{j\in V'} x_{ji} = 1, \quad i = n+1, ..., n+m \tag{4}$$

$$\sum_{t\in T} U_{jt} = 1, \quad j \in V'' \tag{5}$$

$$\bar{T}_0 = 0 \tag{6}$$

$$\bar{T}_j \geq \bar{T}_i + t_{ij} - M(1 - x_{ij}), \quad i \in V', j \in V''(j \neq i) \tag{7}$$

$$e^t - T_{max}(1 - U_{jt}) \leq \bar{T}_j \leq \ell^t + T_{max}(1 - U_{jt}), \quad j \in V'', t \in T \tag{8}$$

$$Q_0^s = 0, \quad s \in S \tag{9}$$

$$Q_j^s \geq Q_i^s - M(1 - x_{ij}) + d_j + \sum_{t\in T}\sum_{\tau=1}^{t} \delta_{j\tau}^s U_{jt}, \quad s \in S, i \in V', j = 1, ..., n(j \neq i) \tag{10}$$

$$Q_j^s \leq Q_i^s + M(1 - x_{ij}) + d_j + \sum_{t\in T}\sum_{\tau=1}^{t} \delta_{j\tau}^s U_{jt}, \quad s \in S, i \in V', j = 1, ..., n(j \neq i) \tag{11}$$

$$Q_j^s \geq Q_i^s - M(1 - x_{ij}), \quad s \in S, i \in V', j = n+1, ..., n+m \tag{12}$$

$$Q_j^s \leq Q_i^s + M(1 - x_{ij}), \quad s \in S, i \in V', j = n+1, ..., n+m \tag{13}$$

$$R_j^s \geq Q_j^s - C, \quad s \in S, j = n+1, ..., n+m \tag{14}$$

$$R_j^s \geq 0, \quad s \in S, j = n+1, ..., n+m \tag{15}$$

$$L_j^s = \sum_{t\in T}\sum_{\tau=t+1}^{|T|} \delta_{j\tau}^s U_{jt}, \quad s \in S, j = 1, ..., n \tag{16}$$

$$\rho_j^s \geq \frac{Q_j^s - C}{Q_{max}}, \quad s \in S, j = 1, \ldots, n \tag{17}$$

$$\rho_j^s \leq 1 - \frac{C - Q_j^s}{Q_{max}}, \quad s \in S, j = 1, \ldots, n \tag{18}$$

$$y_{ij}^s \leq \frac{1}{2}(x_{ij} + \rho_i^s), \quad s \in S, i = 1, ..., n, j \in V''(j \neq i) \tag{19}$$

$$y_{0j}^s = 0, \quad s \in S, \quad j \in V'' \tag{20}$$

$$\alpha_j^s = \sum_{i \in V''} y_{ji}^s - \sum_{i \in V'} y_{ij}^s, \quad s \in S, j = 1, \ldots, n \tag{21}$$

$$x_{ij} \in \{0, 1\}, \quad i \in V', j \in V''(j \neq i) \tag{22}$$

$$U_{jt} \in \{0, 1\}, \quad j \in V'', t \in T \tag{23}$$

$$y_{ij}^s \in \{0, 1\}, \quad s \in S, i \in V', j \in V''(j \neq i) \tag{24}$$

$$\rho_j^s, \alpha_j^s \in \{0, 1\}, \quad s \in S, j = 1, ..., n \tag{25}$$

The objective function (1) consists in first stage travel costs minus average cost savings due to partial routes skipping. In addition, it considers penalty cost due to uncollected waste. Equations (2) represent flow conservation constraints and ensure that each CP is visited exactly once. The number of routes starting from depot, which coincides with the number of available vehicles, is fixed by equation (3). Equations (4) ensure that routes end at the depot. Note that $x_{0j} = 1$ for some $j = n+1, ..., n+m$ denotes an empty route. Each node in V'' must be visited in exactly one period as stated by constraints (5). Note that visiting nodes $n+1, ..., n+m$ within the planning horizon indirectly means fixing a maximum temporal length for the routes. Arrival times at node 0 and at the other nodes are tracked by constraints (6) and (7), respectively. These constraints also eliminate subtours. Constraints (8) allow to identify in which period the nodes in V'' are visited. Each vehicle starts empty from the depot as stated by constraints (9). The theoretical cumulative load at the other nodes in every scenario, obtained by ignoring the vehicle capacity, is defined by means of constraints (10)-(13). In particular, constraints (12)-(13) establish the theoretical cumulative load at the end of each route. Note that the arrival times and the theoretical cumulative loads are non-negative without imposing other constraints. The quantity of waste exceeding the capacity in each route and in each scenario is defined by constraints (14); it cannot be negative according to constraints (15). The demand left over

at each CP after its visit is computed through constraints (16). It is non-negative without imposing other constraints. Constraints (17)-(18) allow to identify CPs associated with event "saturation". If a vehicle is fully saturated at a node, the remaining ones are skipped as implied by constraints (19). More specifically, these constraints individuate skipped arcs according to the various scenarios. Since the "initial" depot cannot be a node associated with event "saturation", constraints (20) avoid that the vehicles skip arcs outgoing from 0. Constraints (21) check whether a CP is the skipping point of the route. Finally, constraints (22)-(25) state the nature of binary variables.

4. Solution Methodology

Solving the SM (1)-(25) is effective but very time-consuming (especially when the number of scenarios is high). An alternative solution methodology is based on the development of a set of policies and of a policy selection strategy. The policies are designed in order to be faster to run compared to the SM while maintaining a good performance. By design, a policy is tailored to exploit some specific characteristics of the instances, such as customer distribution, rate of demand (with respect to the vehicle capacity) and so on. Our solution methodology leverages machine learning to predict performance of policies from instance-specific features, enabling the selection of the policy with the lowest predicted objective value. In essence, it works as a policy selector that adapts its decisions to the characteristics of the instance, ensuring that the chosen policy is either optimal or as close as possible to the optimal one. In the following, we detail the policies and the machine learning framework.

4.1. Policies

The designed policies solve either a VRP (policies P1-P6, P9, P10) or a simplified version of the SM (policies P7, P8, P11, P12). For the VRP, in order to ensure a feasible solution, it is allowed to load a demand greater than the capacity if needed, weighted with a penalty. Instead, the simplified version of the SM consists of considering a single scenario, i.e., the scenario with the expected value of the demand increments. In practice, we solve model (1)-(25) by setting $|S| = 1$ and $\delta^s_{jt} = \bar{\delta}_{jt}$ and refer to this model as the Expected-value Model (EM).

With respect to the VRP, while P1 does not consider future demands and represents a sort of benchmark, other policies consider the expected demand increments for all the time slots or for a subset of them (P2, P3). Some policies exploit the reduction of vehicles capacity

in order to provide more robust solutions (P4, P7, P9, P11). Another set of polices try to leverage solutions with non homogeneous routes (P5, P8, P10, P12), eventually with more or less aggressive levels of capacity reduction. Finally, one policy (i.e., P6) considers a different objective function, in order to differently take into account distant CPs. In the following, all the designed policies are briefly described.

- P1: we solve a VRP with demands equal to the initial demands d_j (completely neglecting future demand increments).
- P2: we solve a VRP with demands equal to the initial demands d_j plus the sum over time of the expected values of the additional demands $\bar{\delta}_{jt}$. This is a more conservative policy.
- P3: we solve a VRP with demands equal to the initial demands d_j plus the sum over time of the expected values of the additional demands $\bar{\delta}_{jt}$ up to the central time slot; in particular, we sum up the first $\lceil |T|/2 \rceil$ periods. This policy is less conservative than P2, since it considers that we are unlikely to visit all the CPs in the last time slots.
- P4: we solve a VRP with demands equal to the initial demands plus the sum over time of the expected values of the additional demands (like in P2) but with vehicle capacity reduced by x% (this allows us to better distribute the load over the vehicles and to have a cushion to be used for unexpected extra demand). In this case x% = 10%.
- P5: we solve a VRP with demands equal to the initial demands plus the sum over time of the expected values of the additional demands (like in P2) in which half of the vehicle has increased capacity and the other half has reduced capacity by 15%.
- P6: we solve a VRP with demands equal to the initial demands plus the sum over time of the expected values of the additional demands (like in P2) but with the following modified objective function:

$$f_{P6} = \min \quad \sum_{j \in V' \setminus \{0\}} \frac{1}{c_{0j}} \cdot u_j,$$

where u_j is the position of the node $j \in V'$ in the route. This position can be defined through the following additional constraints:

$$u_j \geq u_i + 1 - (|V'| - 1)(1 - x_{ij}) \quad \forall j \in V' \setminus \{0\} \quad \forall i \in V',$$
$$u_0 = 0.$$

The aim of this policy is to place farther nodes at the end of the routes such that, in the case in which the final part of the route needs to be skipped due to overflow of the vehicle, this part contains the longest (and therefore more expensive) arcs.

- P7: we apply the policy P4, but solving the EM instead of the VRP.
- P8: we apply the policy P5, but solving the EM instead of the VRP.
- P9: we apply the policy P4 (solving the VRP) but with reduced vehicle capacity of 20%.
- P10: we apply the policy P5 (solving the VRP) but with reductions and increments for the vehicle capacity of 30%.
- P11: we apply the policy P9, but solving the EM instead of the VRP.
- P12: we apply the policy P10, but solving the EM instead of the VRP.

4.2. A Machine Learning based Approach

None of the policies presented in Section 4.1 strictly dominates the other ones over all scenarios, and the best choice often depends on the characteristics of the instance. For this reason, we propose a machine learning based framework that automatically identifies the best policy for each instance of the optimization problem, given its characteristics. Each policy achieves a specific objective function value when applied to an instance. Our goal is to leverage machine learning to predict these performance values from the features of the instance, and then to select the policy with the lowest predicted objective value. In practice, our framework acts as a policy-selector that adapts its decision to each situation, ensuring that the selected policy is the best one or as close as possible to the best one. In the remainder of the paper, any policy selection model employing this methodology will be also referred to as an *ML-policy*. In Table 2 we define the features used to characterize each problem instance.

We investigate three distinct ML-policies, each leveraging different aspects of machine learning.

- *Multiclass Classification*: In this approach, in the following also referred to as MultiClass, each instance is associated with a single label indicating the policy with the lowest objective value. This method casts the problem as a multiclass classification task with a number of classes equal to the number of policies. Although straightforward, this method

Feature	Description
$n_{customers}$	Total number of CPs to be served (i.e., n)
$n_{vehicles}$	Number of vehicles in the fleet (i.e., m)
$depot_dispersion$	Indicator of how far CPs are from the depot
$depot_location$	Position of the depot (central or corner)
$customers_dispersion$	Indicator of how far the CPs are among each other
$perc_{pattern_1}$	Percentage of CPs with demand pattern of type 1
$perc_{pattern_2}$	Percentage of CPs with demand pattern of type 2
$perc_{pattern_3}$	Percentage of CPs with demand pattern of type 3
$expected_demand_on_tot_capacity$	Expected demand over total fleet capacity
$initial_demand_on_tot_capacity$	Initial demand over total fleet capacity
$time_slot_size$	Length of each time slot

Table 2: Instance features

does not capture how close the other policies are to the optimal, as it only provides the best option. Thus, we loose information on the performance of each policy on all the instances.

- *Multilabel Classification*: Instead of a single label, each instance is represented by a binary vector of length equal to the number of policies. Each component is set to 1 if the corresponding policy objective value is within a specified tolerance (e.g., within 10% of the best value) and 0 otherwise. This method acknowledges situations where multiple policies are nearly optimal and thus offers a more flexible decision set. It is also referred to as MultiLabel in the following.

- *Multioutput Regression:* Here, we directly predict the continuous objective values using a regressor for each policy. The final decision is made by selecting the policy with the minimum predicted value. This method, in the following also referred to as MultiRegression, not only provides a ranking but also quantifies the expected performance difference between policies.

5. Computational Results

In this section, we illustrate the results provided by the computational study on the instances presented in Section 5.1. This study consists of three parts. The first part aims to demonstrate that uncertainty is significant in this type of problem and, consequently, to justify the complexity of stochastic programming. In the second part, we test the effectiveness of the

deterministic policies proposed for the WCRP-TVSD. Finally, the third part focuses on the machine learning based approach.

The computational study is based on the following software/hardware equipment: GUROBI 12 solver on a windows PC equipped with 12th Gen Intel© Core(TM) i7-1260P 2.10 GHz with 32 GB RAM.

5.1. Instances

Different artificial instances have been generated for a total of 720. First, the position of the CPs has been generated using a uniform random variable distributed on a square of ten units of length. The depot position has been set in two different points in the square: central or located on the lower left. Second, we have fixed the various parameters according to the values given in Table 3.

Parameter	Value
n	[5,6,7,8]
m	[3,4]
C	[150, 200, 250]
$\|T\|$	3
T_{max}	[15, 30, 45]

Table 3: Basic parameters for the instances

The baseline for defining the demands is $uniform[10, 30]$. First, initial demands d_j for each CP j and demand increments δ^s_{jt} for each CP j, for each time slot t, and for each scenario s have been generated by assigning to each CP a type (e.g., school, restaurant, home). Second, different types have been associated with different patterns of initial demand and increments over the time slots. In particular, demand patterns present the following characteristics:

- CP j of type 1: d_j low; δ^s_{j1} high; δ^s_{j2} low; δ^s_{j3} low;
- CP j of type 2: d_j average; δ^s_{j1} average; δ^s_{j2} high; δ^s_{j3} low;
- CP j of type 3: d_j high; δ^s_{j1} low; δ^s_{j2} low; δ^s_{j3} average.

In particular, when an initial demand (or a demand increment) is high, the realization is multiplied by a factor of 1.5. Conversely, for a low initial demand (or a demand increment) the multiplication factor is 0.5. Average initial demands and demand increments are unchanged with respect to the realizations.

5.2. Impact of Uncertainty

In order to solve the SM, we set $|S| = 5$ and imposed a time limit of 3600 seconds. As expected, solving this model was very challenging even for instances with a few CPs. In the following, we refer to the instances for which GUROBI was not able to provide a primal bound within the time limit as "not solved"; otherwise, the instances are referred to as "solved".

Our computational experiments on SM provided many not solved instances and a certain number of solved instances involving eight CPs associated with a large gap. We refer to the GUROBI gap that measures the (relative) difference between the value of the best feasible solution (primal bound) and the best-known objective bound (dual bound). In order to evaluate the difference between a solution obtained by considering uncertainty (i.e., the solution of the SM) and a solution obtained by ignoring it and involving an expected scenario (i.e., the solution of the EM), we use an index which is similar to the one known in the scientific literature as the *Value of the Stochastic Solution* (VSS). In our context this index, expressed as a percentage, can be computed as:

$$\text{VSS} = 100 \cdot \left(\frac{\text{EM}_{obj} - \text{SM}_{obj}}{\text{SM}_{obj}} \right), \tag{26}$$

where SM_{obj} represents the objective function value for the SM and EM_{obj} is the expectation of the solution value over all scenarios when routes are fixed to the ones provided by EM.

In detail, Tables 4 shows the computational results for groups of instances aggregated on the basis of the number n of CPs and the vehicle capacity C. More specifically, for each group of instances, Table 4 reports:

- the number of solved instances out of the total number of instances (solved);
- the average percentage value for VSS (VSS_a);
- the maximum percentage value for VSS (VSS_M);
- the average computational time in seconds required to compute SM_{obj} or EM_{obj} (time_a);
- the maximum computational time in seconds required to compute SM_{obj} or EM_{obj} (time_M);
- the average gap obtained in computing SM_{obj} or EM_{obj} (gap_a);
- the maximum gap obtained in computing SM_{obj} or EM_{obj} (gap_M).

					SM_{obj}				EM_{obj}			
n	C	solved	VSS_a	VSS_M	$time_a$	$time_M$	gap_a	gap_M	$time_a$	$time_M$	gap_a	gap_M
5	150	50/60	4.02	20.04	1.66	3.58	0.00	0.00	0.49	1.12	0.00	0.00
5	200	50/60	74.32	581.79	1.01	2.56	0.00	0.00	0.28	0.70	0.00	0.00
5	250	50/60	106.12	538.26	0.53	1.00	0.00	0.00	0.18	0.40	0.00	0.00
6	150	49/60	0.66	7.36	16.73	63.55	0.00	0.00	3.71	10.11	0.00	0.00
6	200	49/60	5.03	23.34	6.36	22.71	0.00	0.00	1.09	3.40	0.00	0.00
6	250	49/60	69.64	198.09	0.91	2.97	0.00	0.00	0.30	0.82	0.00	0.00
7	150	50/60	0.79	3.01	317.16	1022.41	0.00	0.00	63.04	144.67	0.00	0.00
7	200	50/60	4.51	24.77	197.73	520.44	0.00	0.00	26.57	85.40	0.00	0.00
7	250	50/60	41.48	351.36	55.41	236.39	0.00	0.00	3.41	13.08	0.00	0.00
8	150	50/60	0.22	2.35	2507.71	3600.39	0.68	0.98	1631.95	3600.13	0.31	0.76
8	200	50/60	2.71	12.99	1777.46	3600.26	0.49	0.97	455.52	1956.51	0.00	0.00
8	250	50/60	14.64	131.13	652.68	3600.15	0.40	0.91	106.84	1175.79	0.00	0.00

Table 4: Results for groups of instances with the same number of customers and vehicle capacity

Note that all the gaps and the computational times reported in Table 4 are recorded considering only the solved instances. For the not solved instances we are not able to get any gap and the computational time coincides with the time limit. There exist instances with eight CPs for which we are not able to solve to optimality even the SM with fixed decisions (i.e., the model that provides EM_{obj}). We do not report results for a greater number of CPs, as the optimal solution is very hard to be found for most instances.

Our computational experiments clearly show the significant impact of uncertainty and the value of VSS even reaches 581.79%. In addition, we observe that the value VSS_a increases as capacity increases. Finally, we report that, on all 597 solved instances, the value of the average percentage VSS is 21.33.

5.3. Deterministic Policies

To test the policies, we selected a subset of solved instances, with the aim of finding challenging instances where there is a remarkable difference between EM_{obj} and SM_{obj}. In particular, we first considered the instances solved to optimality or near to optimality, i.e., the instances with a gap less than or equal to 0.001 (548 instances out of 597 solved instances). Among them, we selected the instances with VSS $\geq 4\%$. The resulting subset includes 178 instances for which the average percentage VSS is equal to 64.8%.

A formula similar to (26) can be applied to each policy Pi ($i = 1, ..., 12$). In particular, we

can define the following index:

$$\mathrm{VSS}(i) = 100 \cdot \left(\frac{\mathrm{P}_{obj}(i) - \mathrm{SM}_{obj}}{\mathrm{SM}_{obj}} \right),$$

where $\mathrm{P}_{obj}(i)$ is the expectation of the solution value over all scenarios when routes and visit times are fixed to the ones provided by policy Pi.

Additional computational results on these 178 instances are aggregated for policy and summarized in Table 5. In detail, for each policy Pi ($i = 1, ..., 12$), Table 5 reports:

- the number of times the policy is recorded as the best (nbest);
- the average percentage value for $\mathrm{VSS}(i)$, indicated as $\mathrm{VSS}(i)_a$;
- the minimum computational time in seconds required to compute $\mathrm{P}_{obj}(i)$, indicated as time_m);
- the average computational time in seconds required to compute $\mathrm{P}_{obj}(i)$, indicated as time_a);
- the maximum computational time in seconds required to compute $\mathrm{P}_{obj}(i)$, indicated as time_M.

In the final line of Table 5, we also report time_m, time_a, and time_M when EM is used in place of a policy P(i) (in this case, we refer to the times required to compute EM_{obj} over the 178 instances). Analogously, VSS(i) is recomputed for EM through formula (26) and reported as average value on the 178 instances in column $\mathrm{VSS}(i)_a$.

policy	nbest	$\mathrm{VSS}(i)_a$	time_m	time_a	time_M
P1	0	4188.36	0.02	0.11	1.03
P2	24	104.77	0.02	0.34	4.79
P3	26	480.15	0.02	0.17	1.37
P4	61	68.65	0.02	0.71	17.74
P5	26	244.08	0.01	0.25	3.34
P6	13	212.77	0.01	0.10	1.20
P7	97	20.08	0.05	32.58	1284.39
P8	40	64.74	0.05	9.42	502.24
P9	47	95.30	0.02	1.16	22.98
P10	7	555.10	0.01	0.19	2.83
P11	66	37.00	0.05	84.09	1600.31
P12	41	64.89	0.05	8.84	481.70
EM		64.81	0.03	11.50	326.99

Table 5: Aggregated results for policy

Table 5 shows that, on average, policies P7 and P11 perform significantly better than EM within similar computational times. Especially P7 presents a distance from SM equal to 20.08% against the 64.81% associated with EM. Other policies are associated with a lower quality but, in general, are very fast. However, no policy (except P1) is dominated by the other policies, since the number of times each policy is recorded as best is greater than 0. The very weak performance of policy P1 is not only due to by the fact that we neglect stochasticity, but also by the fact that we neglect the increments of demand during the day. In conclusion, the policy that presents the highest performance is P7, but it is not advisable to choose it over all instances. The experiments described in Section 5.3 clearly show that there is room for improvement, as shown in Section 5.4.

5.4. Machine Learning for Policy Selection

We evaluate the ML-policies by comparing the corresponding results with the performance of an *Oracle-policy*. More specifically, for each instance the Oracle-policy selects the deterministic policy with the lowest objective value. This represents the ideal outcome with perfect information. Consequently, the Oracle-policy provides a lower bound on the cost. From a practical perspective, the Oracle-policy solves each instance by applying all the deterministic policies; then, it keeps the best solution obtained so far. Note that, given an instance, the computational times required by the Oracle-policy are much larger than those required by a single deterministic policy or by an ML-policy. In fact, the ML-policies use the features of the instance to select a single deterministic policy to be applied, after the training phase.

The dataset of the 178 instances selected for the experiments described in Section 5.3 was split into a training set, denoted as TRAIN (65%), and a TEST set (35%). For each subset, as well as for the OVERALL dataset of 178 instances, we computed the mean real objective values for the best deterministic policy (i.e., P7), for the Oracle-policy, and for the ML-policies. Table 6 summarizes the results of our experiments. In particular, it reports for the ML-policies and for the best deterministic policy the average objective value (Absolute) and the percentage difference from the Oracle-policy (Relative) for TRAIN, TEST, and OVERALL sets. In both columns, lower values indicate better performance.

Table 6 reveals that MultiRegression consistently achieves an average objective value that is much closer to the Oracle-policy performance than the best deterministic policy or alternative ML-policies based on classification. This confirms that MultiRegression is effective in dynamically selecting a near-optimal policy for each instance, and offering a significant performance

Policy	TRAIN (0.65)		TEST (0.35)		OVERALL	
	Absolute	Relative	Absolute	Relative	Absolute	Relative
MultiClass	357.35	0%	542.40	17%	422.84	7%
MultiLabel	366.41	3%	491.29	6%	410.61	4%
MultiRegression	366.03	2%	479.73	3%	406.27	3%
P7	387.28	8%	499.95	8%	427.15	8%
Oracle-policy	357.35	–	464.53	–	395.28	–

Table 6: Absolute performance and relative distance from the Oracle-policy.

gain over a fixed policy choice. More in detail, MultiRegression achieves results close the ones provided by the Oracle-policy, thus validating the advantage of a selector based on machine learning.

It is worth noting that, while on the TRAIN set MultiClass obtains the best performance and it is able to exactly replicate Oracle-policy decisions, its performance is relatively poor on the TEST set. This means that this ML-policy suffers from overfitting, and does not generalize well on new data. On the contrary, MultiRegression performs slightly worse on the TRAIN set but generalized much better, obtaining an excellent performance on the TEST set. This result demonstrates that MultiRegression is a reliable and powerful tool to select the right policy to apply based on the instance's features.




Figure 1: Scatter plots comparing the real objective values of each ML-policy (on the x-axis) with the corresponding values provided by the Oracle-policy (on the y-axis).

In Figure 1, we present a graphical visualization of the actual performance of each candidate ML-Policy against the Oracle-policy on the TEST set. The results reported in this figure

confirm that MultiRegression outperforms both the classification methods, i.e., MultiClass and MultiLabel. The x-axis represents the real objective value obtained by a ML-policy for each instance. The y-axis represents the real objective value of the Oracle-policy for the same instances, which serves as a theoretical lower bound (i.e., the best possible outcome). The dotted diagonal line $y = x$ highlights the region where a ML-policy's performance would match the lower bound exactly. Points lying below this line indicate that the ML-policy under study performed worse than the Oracle-policy for those instances, whereas points on or very close to the line indicate optimal or near-optimal performance. Each subplot also includes a fitted linear regression line (shown in blue), which models the relationship $y = \alpha + \beta\, x$ between the ML-policy's performance x and the Oracle-policy's performance y. The slope coefficient β is particularly informative: a β value close to 1 indicates that the policy under study tracks the Oracle-policy very closely.

6. Conclusions

In this paper we have introduced and formalized a new realistic vehicle routing problem arising in waste collection, referred to as the Waste Collection Routing Problem with Time-Varying Stochastic Demand (WCRP-TVSD). In this problem, the waste amount may increase over time and the demand increments are stochastic with a distribution which depends on the day time and on the typology of the collection point. This aspect represents a realistic feature that has not been addressed in the literature to the best of our knowledge. The WCRP-TVSD has been modeled as a two-stage stochastic model in which vehicle routing and scheduling are planned a priori. In case in which, during the route execution, vehicle capacity is exceeded, the vehicle skips the remaining part of the route and comes back straight to the depot. A penalty is paid for uncollected waste. The waste may remain uncollected for two reasons: (i) an additional amount of waste accumulated after the vehicle's visit to the node (ii) a violation of the vehicle's capacity. Our two-stage stochastic program has been approximated by a (deterministic) scenario-based model and solved for small-sized instances.

For the WCRP-TVSD, we have also presented several deterministic policies corresponding to mathematical models that can be solved more quickly. They allow us to generate the a priori routes. Then, the actual cost (comprehensive of routing costs and penalties for uncollected waste) has been computed over all scenarios. The computational results have shown that no policy clearly dominates the others in all instances. However, there exist policies that perform

better than the expected-value model, i.e., a scenario-based model which uses a single scenario and replies stochastic parameters with their expected values. Finally, we have presented a machine learning based policy selector, which uses classification algorithms to predict the policy to apply on a given instance, based on its features. The computational results have shown the excellent performance of a policy selector based on multioutput regression.

Future works could address the design of metaheuristics for solving the models representing the deterministic policies in the case of large-scale instances. Moreover, different recourse policies could be designed, including: returning to the depot for unloading waste and to gain capacity to fulfill the remaining part of the route, to use proactive visits to the depot for waste unloading, once passing nearby it, in order to avoid exceeding the capacity and to be obliged to make long detours, or the exploitation of compaction mechanisms, which can be used to reduce the volume of collected waste and, therefore, to generate extra-capacity. From an application point of view, we identify two promising directions. The first one deals with the integration of sensors to obtain real-time information on the filling level of the bins which can be used to reschedule and re-route vehicles in order to avoid exceeding capacity. The second one consists in the possibility of paying workers for handily compacting waste at the bins in order to decrease their volume.

References

Aliahmadi S.Z., Barzinpour F., Pishvaee M.S. (2020). A fuzzy optimization approach to the capacitated node-routing problem for municipal solid waste collection with multiple tours: A case study, *Waste Management & Research*, 38(3): 279–290.

Alshaikh R., Abdelfatah A. (2024). Optimization techniques in municipal solid waste management: A systematic review, *Sustainability*, 16(15): 6585.

Beliën J., De Boeck L., Van Ackere J. (2014). Municipal solid waste collection and management problems: A literature review, *Transportation Science*, 48(1): 78–102.

Beltrami E.J., Bodin L.D. (1974). Networks and vehicle routing for municipal waste collection. *Networks*, 4(1): 65–94.

Bengio Y., Lodi A., Prouvost A. (2021). Machine learning for combinatorial optimization: A methodological tour d'horizon, *European Journal of Operational Research*, 290(2): 405–421.

Beraldi P., Ghiani G., Musmanno R., Vocaturo F. (2010). Efficient neighborhood search for the probabilistic multi-vehicle pickup and delivery problem, *Asia-Pacific Journal of Operational Research*, 27(3): 301-314.

Bibak B., Karaesmen F. (2025). Integration of machine learning and optimization models for a data-driven lot sizing problem with random yield, *International Journal of Production Economics*, 282: 109529.

Chandrappa R., Das D.B. (2012). Solid Waste Management (Principles and Practice). Springer Berlin, Heidelberg.

De Maio A., Laporte G., Musmanno R., Vocaturo F. (2025). Sustainable risk mitigation in hazardous material transportation, *Computers & Operations Research*, 184: 107228.

de Morais C.S., Ramos T.R.P., Lopes M., Barbosa-Póvoa A.P. (2024). A data–driven optimization approach to plan smart waste collection operations, *International Transactions in Operational Research*, 31(4): 2178–2208.

Eurostat – official website of the European Union (2025). Municipal waste statistics, `https://ec.europa.eu/eurostat/statistics-explained/index.php?title=Municipal_waste_statistics`. Last access: May 22, 2025.

Ghiani G., Laganà D., Manni E., Musmanno R., Vigo D. (2014). Operations research in solid waste management: A survey of strategic and tactical issues, *Computers & Operations Research*, 44: 22–32.

Gobbi A., Manerba D., Vocaturo F. (2026). Incorporating stochastic optional pickup demand in routing operations with divisible services for hub-and-spoke e-commerce returns management systems, *Omega*, 141: 103510.

Gruler A., Juan A.A., Hirsch P., Contreras-Bolton C. (2017). Supporting multi-depot and stochastic waste collection management in clustered urban areas via simulation–optimization, *Journal of Simulation*, 11(1): 11–19.

Gruler A., Pérez-Navarro A., Calvet L., Juan A.A. (2020). A simheuristic algorithm for time-dependent waste collection management with stochastic travel times, *SORT – Statistics and Operations Research Transactions*, 44(2): 285–310.

Hannan M.A., Hossain Lipu M.S., Akhtar M., Begum R.A., Abdullah Al Mamun M., Hussain A., Mia M.S., Basri H. (2020). Solid waste collection optimization objectives, constraints, modeling approaches, and their challenges toward achieving sustainable development goals, *Journal of Cleaner Production*, 277: 123557.

Hess C., Dragomir A.G., Doerner K.F., Vigo D. (2024). Waste collection routing: a survey on problems and methods, *Central European Journal of Operations Research*, 32(2): 399–434.

Johansson O.M. (2006). The effect of dynamic scheduling and routing in a solid waste management system, *Waste Management*, 26(8): 875–885.

Karimi-Mamaghan, M., Mohammadi, M., Meyer, P., Karimi-Mamaghan, A.M. , El-Ghazali, T. (2022) Machine learning at the service of meta-heuristics for solving combinatorial optimization problems: A state-of-the-art, *European Journal of Operational Research*, 296(2): 393-422.

Laporte G., Musmanno R., Vocaturo F. (2010). An adaptive large neighbourhood search heuristic for the capacitated arc-routing problem with stochastic demands, *Transportation Science*, 44(1): 125–135.

Liang Y.-C., Minanda V., Gunawan A. (2022). Waste collection routing problem: A mini-review of recent heuristic approaches and applications, *Waste Management & Research*, 40(5): 519–537.

Malladi K.T., Sowlati T. (2018). Sustainability aspects in inventory routing problem: A review of new trends in the literature, *Journal of Cleaner Production*, 197(1): 804–814.

Markov I., Bierlaire M., Cordeau J.-F., Maknoon Y., Varone S. (2020). Waste collection inventory routing with non-stationary stochastic demands, *Computers & Operations Research*, 113: 104798.

Nguyen D.V.A., Gunawan A., Misir M., Hui L.K., Vansteenwegen P. (2025). Deep reinforcement learning for solving the stochastic e-waste collection problem, *European Journal of Operational Research*, 327(1): 309–325.

Nolz P.C., Absi N., Feillet D. (2014). A stochastic inventory routing problem for infectious medical waste collection, *Networks*, 63(1): 82–95.

Pasa L., Angelini G., Ballarin M., Fedrizzi P., Sperduti A. (2025). Enhancing door-to-door waste collection forecasting through ML, *Waste Management*, 194: 36–44.

Rabbani M., Heidari R., Yazdanparast R. (2019). A stochastic multi-period industrial hazardous waste location-routing problem: Integrating NSGA-II and Monte Carlo simulation, *European Journal of Operational Research*, 272(3): 945–961.

Ramos T.R.P., de Morais C.S., Barbosa-Póvoa A.P. (2018). The smart waste collection routing problem: alternative operational management approaches, *Expert Systems With Applications*, 103: 146–158.

Rovetta A., Xiumin F., Vicentini F., Minghua Z., Giusti A., Qichang H. (2009). Early detection and evaluation of waste through sensorized containers for a collection monitoring application, *Waste Management*, 29: 2939–2949.

Ruszczynski A., Shapiro A., Eds (2003). Stochastic Programming (Handbooks in Operations Research and Management Science, Volume 10), Elsevier Science.

Schiffer M., Schneider M., Walther G., Laporte G. (2019). Vehicle routing and location routing with intermediate stops: A review. *Transportation Science*, 53(2): 319–343.

Shi Y., Vanhaverbeke L., Xu J. (2024). Electric vehicle routing optimization for sustainable kitchen waste reverse logistics network using robust mixed-integer programming. *Omega*, 128: 103128.

Spinelli A., Maggioni F., Ramos T.R.P., Barbosa-Póvoa A.P., Vigo D. (2025). A rolling horizon heuristic approach for a multi-stage stochastic waste collection problem. *European Journal of Operational Research*, 323(1): 276–296.

Sulemana A., Donkor E.A., Forkuo E.K., Oduro-Kwarteng S. (2018). Optimal routing of solid waste collection trucks: A review of methods, *Journal of Engineering*, 4586376.

Tavares G., Zsigraiova Z., Semiao V., Carvalho M. (2009). Optimisation of MSW collection routes for minimum fuel consumption using 3D GIS modelling, *Waste Management*, 29(3): 1176–1185.

Tirkolaee E.B., Mahdavi I., Seyyed Esfahani M.M. (2018). A robust periodic capacitated arc routing problem for urban waste collection considering drivers and crew's working time, *Waste Management*, 76: 138–146.

Tirkolaee E.B., Mahdavi I., Seyyed Esfahani M.M., Weber G.-W. (2020). A hybrid augmented ant colony optimization for the multi-trip capacitated arc routing problem under fuzzy demands for urban solid waste management, *Waste Management & Research*, 38(2): 156–172.

Van Engeland J., Beliën J., De Boeck L., De Jaeger S. (2020). Literature review: Strategic network optimization models in waste reverse supply chains, *Omega*, 91: 102012.

Wang N., Cui W., Zhang M., Jiang Q. (2023). Routing optimization for medical waste collection considering infectious risk and multiple disposal centers, *Expert Systems with Applications*, 234: 121035.

Xia W., Jiang Y., Chen X., Zhao R. (2022). Application of machine learning algorithms in municipal solid waste management: A mini review, *Waste Management & Research*, 40(6): 609–624.

Zhang S., Zhang J., Zhao Z., Xin C. (2022). Robust optimization of municipal solid waste collection and transportation with uncertain waste output: A case study, *Journal of Systems Science and Systems Engineering*, 31: 204–225.