



We will show an example about how to do the Development

Client need mark one line text in a rectangle, which is shown as following, and the content of text must be achieved from a network server.



Common step of Development as follows:

Step 1. Create a template file as test.ezd, then create a new text object and named it to "name". Adjust the size, position and parameters to reach the machining effect. Then save file and exit EzCad2.



Step 2. Program software for calling markez.dll.

a) First step : Dynamic Load MarkEzd.dll

```
HINSTANCE hEzdDLL = LoadLibrary(_T("MarkEzd.dll"));
```

b) Second step: get the pointer of the function to be called

```
lmc1_Initial=(LMC1_INITIAL)GetProcAddress(hEzdDLL,  
_T("lmc1_Initial"));  
lmc1_Close=(LMC1_CLOSE)GetProcAddress(hEzdDLL,  
_T("lmc1_Close"));  
lmc1_LoadEzdFile=(LMC1_LOADEZDFILE)GetProcAddress(hEzdDLL,  
_T("lmc1_LoadEzdFile"));  
lmc1_Mark=(LMC1_MARK)GetProcAddress(hEzdDLL,_T("lmc1_Mark")  
);
```

```
lmc1_ChangeTextByName=(LMC1_CHANGETEXTBYNAME)GetProcAddress(hEzdDLL,  
_T("lmc1_ChangeTextByName"));
```

c) Third step: Call the function

1) Initialization lmc1 board: **lmc1_Initial()**

2) Open test.ezd: **lmc1_LoadEzdFile(_T("test.ezd"))**.

3) Get the text content from network server. User must write this segment program oneself.

4) Change the content of the named text object.

```
lmc1_ChangeTextByName (_T( "name" ), szTextAchievedFromNetwork);
```

5) Call **lmc1_Mark()** for machining

- 6) If go on, return to 3).
 - 7) Close lmc1 board: **lmc1_Close()**.
- d) Fourth step, Release markezd.dll: **FreeLibrary(hEzdDLL)**