

Swagger Codegen Reference - v2

Contents

Swagger Codegen CLI — general options	1
Java client generator — configuration options	2
python generator config options	3
.swagger-codegen-ignore	4
Using a JSON config file (-c)	5

Swagger Codegen CLI — general options

Swagger Codegen 2.x is distributed under the Maven group id io.swagger.

Get the CLI jar:

```
wget https://repo1.maven.org/maven2/io/swagger/swagger-codegen-cli/2.4.46/\
swagger-codegen-cli-2.4.46.jar -O swagger-codegen-cli.jar
```

Run the generator:

```
java -jar swagger-codegen-cli.jar generate \
-i https://petstore.swagger.io/v2/swagger.json \
-l php \
-o /tmp/php_api_client
```

General flags:

Flag	Description
-i	Location of the OpenAPI spec, as URL or file.
-l	Client language to generate.
-o	Output directory.
-c	Path to a JSON configuration file.
-DhideGenerationTimestamp=true	Suppresses the generation timestamp comment in output files.

To list general options available, run `java -jar swagger-codegen-cli.jar help generate`.

Java client generator — configuration options

Config options for the java client generator in Swagger Codegen 2.x, settable via `-c config.json`.

- **sortParamsByRequiredFlag** — Sort method arguments to place required parameters before optional parameters. (Default: true)
- **ensureUniqueParams** — Whether to ensure parameter names are unique in an operation. (Default: true)
- **allowUnicodeIdentifiers** — Toggles whether unicode identifiers are allowed in names. (Default: false)
- **modelPackage** — Package for generated models.
- **apiPackage** — Package for generated api classes.
- **library** — Library template to use: jersey1, jersey2, feign, okhttp-gson, retrofit, retrofit2, resttemplate, resteasy. (Default: okhttp-gson)

Run `config-help -l java` to see the full, current list for your installed version.

python generator config options

packageName, type string — python package name, default swagger_client.

projectName, type string — python project name in setup.py, default derived from package-Name.

packageVersion, type string — python package version, default 1.0.0.

sortParamsByRequiredFlag, type boolean — default true, sort method arguments to place required parameters before optional ones.

Example config.json:

```
{  
  "packageName": "petstore_api",  
  "packageVersion": "1.0.1"  
}
```

Pass it with -c config.json on the generate command.

.swagger-codegen-ignore

Swagger Codegen 2.x supports a .swagger-codegen-ignore file, similar in syntax to .gitignore, placed in the output directory before generation.

```
# Ignore this specific file
docs/some-doc.md
```

```
# Ignore all files ending in .foo
*.foo
```

```
# Ignore everything under a folder
build/**/*
```

Rules are read once, at the start of generation, and are not re-read if regenerating in the same output directory in a single CLI invocation with multiple -I targets.

Using a JSON config file (-c)

Any codegen option that has a corresponding command-line flag can also be set via a JSON file supplied with `-c path/to/config.json`, and this is generally the recommended approach once you have more than two or three options to set, since command lines with many `-D` flags become difficult to read, difficult to keep consistent across a team's CI pipeline definitions, and difficult to diff meaningfully in a pull request compared to a small, self-contained JSON file that can be reviewed on its own and reused verbatim across multiple invocations of the generator for different languages if the option names happen to be shared across those language generators, which many of the common ones are.

Key	Type	Description
modelPackage	string	Package for generated models.
apiPackage	string	Package for generated API classes.
invokerPackage	string	Root package for the generated client.
groupId	string	Maven groupId, for languages that produce a Maven project.
artifactId	string	Maven artifactId.
artifactVersion	string	Maven artifact version.

```
java -jar swagger-codegen-cli.jar generate -i spec.json -l java -c config.json
```