

Developing Quantum Computing Algorithms for Modeling Heat Transfer with Phase Change



Georgia Tech College of Computing
Center for Research into
Novel Computing Hierarchies

Christopher Jawetz, Fatima Chrit, Spencer Bryngelson, Alexander Alexeev
Mechanical Engineering, Georgia Tech

Goal

CFD is historically the most compute-heavy field. Despite all the resources allocated to it, simulations still require compromises in fidelity to run in a reasonable amount of time. Quantum computing promises to accelerate these algorithms exponentially, by creating superpositions of states and solving them simultaneously.



- LBM works well on quantum computers because of its locality
- Cooling processes that lead to grain formation are not well understood
- Quantum spin states affect grain boundaries
- Quantum mechanics are well-suited for simulation on QC

Conclusions

Our algorithm promises to greatly speed up transport simulations and allow us to simulate these systems at a higher fidelity. This promises insights into grain formation and properties.


Acknowledgements

CRNCH Fellowship



Quantum LBM

Traditional LBM

- The lattice Boltzmann method (LBM) solves the Boltzmann transport equation at the mesoscale
- Heat equation: $\frac{\partial T}{\partial t} = \alpha \nabla^2 T - \varphi$
- Simulates the fluid density with streaming and collision processes
- In the streaming step, fluid flows in each direction to adjacent nodes
- In the collision step, arriving fluid from each direction is averaged towards the equilibrium distribution
- This method is localized and therefore highly parallelizable
- $f_\alpha(\mathbf{r} + \mathbf{c}_\alpha \Delta t, t + \Delta t) = f_\alpha(\mathbf{r}, t) + \Omega_\alpha[f_\alpha(\mathbf{r}, t)]$



Quantum Algorithm




- 1 qubit per direction per node
- Initialization by $Ry(\theta_\alpha)$ gate
 - $\theta_\alpha = 2 \arccos \sqrt{1 - f_\alpha(x_i, t)}$
- Collision applied by entangling the qubits at each lattice point

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & e^{i\varphi} e^{i\xi} \cos \theta & e^{i\varphi} e^{i\xi} \sin \theta & 0 \\ 0 & -e^{i\varphi} e^{-i\xi} \sin \theta & e^{i\varphi} e^{-i\xi} \cos \theta & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$
- Φ, ξ, ζ, θ , determined by LBM collision operator
- Example is 1D heat transfer with fixed T_w on left + phase change
- Benchmarked against classical LBM and analytic solutions

Quantum Monte Carlo

- Monte Carlo (MC) methods use randomness to estimate complicated systems using repeated sampling
- Can improve runtime quadratically using amplitude estimation
 - Generalization of Grover's algorithm
- Nature of quantum computing allows for easy incorporation of these methods



$$P(x_1, x_2, x_3) = 0.5 * x_1 + 0.25 * x_2 + 0.25 * x_3$$

- Unitary operation $W|x\rangle|0\rangle = |x\rangle (\sqrt{1 - \phi(x)}|0\rangle + \sqrt{\phi(x)}|1\rangle)$ to assign target qubits
- Repeated for successive target qubits
- Use amplitude estimation to increase accuracy
- Qubits are fully integrated into the larger circuit and are initialized and measured at the same time

