

PLpgSQL (iii)

- PLpgSQL Functions (recap)
- Query results in PLpgSQL
- Dynamically Generated Queries
- Functions vs Views

❖ PLpgSQL Functions (recap)

Defining PLpgSQL functions:

```
CREATE OR REPLACE
    funcName(param1, param2, ....)
    RETURNS rettype
AS $$
DECLARE
    variable declarations
BEGIN
    code for function
END;
$$ LANGUAGE plpgsql;
```

❖ Query results in PLpgSQL

Can evaluate a query and iterate through its results

- one tuple at a time, using a **for ... loop**

```
declare
    tup Type;
begin
    for tup in Query
    loop
        Statements;
    end loop;
end;
```

Type of **tup** variable must match type of *Query* results

If declared as **record**, will automatically match *Query* results type

❖ Query results in PLpgSQL (cont)

Example: count the number of Employees earning more than min.salary

```
create or replace function
    well_paid(_minsal integer) returns integer
as $$
declare
    nemps integer := 0;
    tuple record; -- could also be tuple Employees;
begin
    for tuple in
        select * from Employees where salary > _minsal
    loop
        nemps := nemps + 1;
    end loop;
    return nemps;
end;
$$ language plpgsql;
```

❖ Query results in PLpgSQL (cont)

Alternative to the above (but less efficient):

```
create or replace function
  well_paid(_minsal integer) returns integer
as $$
declare
  nemps integer := 0;
  tuple record;
begin
  for tuple in
    select name,salary from Employees
  loop
    if (tuple.salary > _minsal) then
      nemps := nemps + 1;
    end if;
  end loop;
  return nemps;
end;
$$ language plpgsql;
```

❖ Query results in PLpgSQL (cont)

And the example could be done more simply (and efficiently) as:

```
create or replace function
    well_paid(_minsal integer) returns integer
as $$
declare
    nemps integer;
begin
    select count(*) into nemps
    from Employees where salary > _minsal
    return nemps;
end;
$$ language plpgsql;
```

❖ Dynamically Generated Queries

EXECUTE takes a string and executes it as an SQL query.

Examples:

```
-- constant string
execute 'select * from Employees';
-- concatenation of constant strings
execute 'select * from ' || 'Employees';
-- using a name of e.g. table or attribute
execute 'select * from ' || quote_ident($1);
-- using a value generated in the program
execute 'delete from Accounts' ||
       ' where holder=' || quote_literal($1);
```

Can be used in any context where an SQL query is expected

This mechanism allows us to **construct** queries "on the fly".

❖ Dynamically Generated Queries (cont)

Example: a wrapper for updating a single text field

```
create or replace function
    set(_table text, _attr text, _val text) returns void
as $$
declare
    query text;
begin
    query := 'update ' || quote_ident(_table);
    query := query || ' SET ' || quote_ident(_attr);
    query := query || ' = ' || quote_literal(_val);
    execute query;
end; $$ language plpgsql;
```

which could be used as e.g.

```
select set('branches','assets','0.00');
```


❖ Dynamically Generated Queries (cont)

One limitation of **EXECUTE**:

- cannot use **select into** inside dynamic queries

Needs to be expressed instead as:

```
declare tuple R%rowtype; n int;
execute 'select * from R where id=' || n into tuple;
-- or
declare x int; y int; z text;
execute 'select a,b,c from R where id=' || n into x,y,z;
```

Notes:

- if query returns multiple tuples, first one is stored
- if query returns zero tuples, all nulls are stored

❖ Functions vs Views

A difference between views and functions returning a **SETOF**:

- **CREATE VIEW** produces a "virtual" table definition
- **SETOF** functions require an existing tuple type

In examples above, we used existing **Employees** tuple type.

In general, you need to define the tuple return type via

```
create type TupleType as ( attr1 type1, ... attrn typen );
```

Other major differences between **setof** functions and views ...

- functions have parameters; views don't (although **where** might help)
- functions are "run-time" objects; views are interpolated into queries

❖ Functions vs Views (cont)

Another example of function returning **setof** tuples ...

```
create type EmpInfo as (name text, pay integer);

create or replace function
    richEmps(_minsal integer) returns setof EmpInfo
as $$
declare
    emp record;    info EmpInfo;
begin
    for emp in
        select * from Employees where salary > _minsal
    loop
        info.name := emp.name;
        info.pay := emp.salary;
        return next info;
    end loop;
end; $$ language plpgsql;
```

❖ Functions vs Views (cont)

Using the function ...

```
select * from richEmps(100000);
```

versus a view

```
create or replace view richEmps(name,pay) as
select name, salary from Employees where salary > 100000;

select * from richEmps; -- but no scope for different salary
```

versus an SQL function

```
create or replace function
    richEmps(_minsal integer) returns setof EmpInfo
as $$
select name, salary from Employees where salary > _minsal;
$$ language sql;
```

Produced: 10 Oct 2020