

# Aggregates

---

- Aggregates
- User-defined Aggregates

## ◆ Aggregates

Aggregates reduce a collection of values into a single result.

Examples: `count(Tuples)`, `sum(Numbers)`, `max(AnyOrderedType)`

The action of an aggregate function can be viewed as:

```
State = initial state
for each item T {
    # update State to include T
    State = updateState(State, T)
}
return makeFinal(State)
```

## ◆ Aggregates (cont)

Aggregates are commonly used with **GROUP BY**.

In that context, they "summarise" each group.

Example:

<p>R</p> <table border="1"> <thead> <tr> <th>a</th> <th>b</th> <th>c</th> </tr> </thead> <tbody> <tr><td>1</td><td>2</td><td>x</td></tr> <tr><td>1</td><td>3</td><td>y</td></tr> <tr><td>2</td><td>2</td><td>z</td></tr> <tr><td>2</td><td>1</td><td>a</td></tr> <tr><td>2</td><td>3</td><td>b</td></tr> </tbody> </table>	a	b	c	1	2	x	1	3	y	2	2	z	2	1	a	2	3	b	<pre>select a,sum(b),count(*) from R group by a</pre> <table border="1"> <thead> <tr> <th>a</th> <th>sum</th> <th>count</th> </tr> </thead> <tbody> <tr><td>1</td><td>5</td><td>2</td></tr> <tr><td>2</td><td>6</td><td>3</td></tr> </tbody> </table>	a	sum	count	1	5	2	2	6	3
a	b	c																										
1	2	x																										
1	3	y																										
2	2	z																										
2	1	a																										
2	3	b																										
a	sum	count																										
1	5	2																										
2	6	3																										

## ❖ User-defined Aggregates

---

SQL standard does not specify user-defined aggregates.

But PostgreSQL provides a mechanism for defining them.

To define a new aggregate, first need to supply:

- *BaseType* ... type of input values
- *StateType* ... type of intermediate states
- state mapping function:  $sfunc(state, value) \rightarrow newState$
- [optionally] an initial state value (defaults to null)
- [optionally] final function:  $ffunc(state) \rightarrow result$

## ❖ User-defined Aggregates (cont)

New aggregates defined using **CREATE AGGREGATE** statement:

```
CREATE AGGREGATE AggName(BaseType) (  
    sfunc      = UpdateStateFunction,  
    stype     = StateType,  
    initcond  = InitialValue,  
    finalfunc = MakeFinalFunction,  
    sortop   = OrderingOperator  
);
```

- **initcond** (type *StateType*) is optional; defaults to **NULL**
- **finalfunc** is optional; defaults to identity function
- **sortop** is optional; needed for min/max-type aggregates

## ❖ User-defined Aggregates (cont)

Example: defining the **count** aggregate (roughly)

```
create aggregate myCount(anyelement) (  
    stype      = int,      -- the accumulator type  
    initcond   = 0,        -- initial accumulator value  
    sfunc      = oneMore   -- increment function  
);  
  
create function  
    oneMore(sum int, x anyelement) returns int  
as $$  
begin return sum + 1; end;  
$$ language plpgsql;
```

## ❖ User-defined Aggregates (cont)

Example: **sum2** sums two columns of integers

```
create type IntPair as (x int, y int);

create function
    addPair(sum int, p IntPair) returns int
as $$
begin return sum + p.x + p.y; end;
$$ language plpgsql;

create aggregate sum2(IntPair) (
    stype      = int,
    initcond   = 0,
    sfunc      = addPair
);
```

## ❖ User-defined Aggregates (cont)

---

PostgreSQL has many aggregates (e.g. **sum**, **count**, ...)

But it doesn't have a product aggregate.

Implement a **prod** aggregate that

- computes the product of values in a column of numeric data

Usage:

```
select prod(*) from iota(5);
 prod
-----
 120
```



## ❖ User-defined Aggregates (cont)

---

### Example: product aggregate

```
create function
  mult(soFar numeric, next numeric) returns numeric
as $$
begin return soFar * next; end;
$$ language plpgsql;

create aggregate prod(numeric) (
  stype      = numeric,
  initcond   = 1,
  sfunc      = mult
);
```

## ❖ User-defined Aggregates (cont)

Define a **concat** aggregate that

- takes a column of string values
- returns a comma-separated string of values

Example:

```
select count(*), concat(name) from Employee;
```

```
-- returns e.g.
```

count	concat
4	John,Jane,David,Phil

## ❖ User-defined Aggregates (cont)

### Example: string concatenation aggregate

```
create function
    join(s1 text, s2 text) returns text
as $$
begin
    if (s1 = '') then
        return s2;
    else
        return s1||','||s2;
    end if;
end;
$$ language plpgsql;

create aggregate concat(text) (
    stype      = text,
    initcond   = '',
    sfunc      = join
);
```

Produced: 15 Oct 2020