

Prepared by :- Benjamin Jomy

<https://tryhackme.com/p/Cronus.Myth>

TryHackMe

Dashboard Learn Compete Other

Access Machines Go Premium 0 XP

Learn > Nmap

Nmap

An in depth look at scanning with Nmap, a powerful network scanning tool.

Easy 50 min

Share your achievement Start AttackBox Help Save Room 19640 Options

Room completed (100%)

- Task 1 Deploy
- Task 2 Introduction
- Task 3 Nmap Switches
- Task 4 Scan Types Overview
- Task 5 Scan Types TCP Connect Scans
- Task 6 Scan Types SYN Scans
- Task 7 Scan Types UDP Scans
- Task 8 Scan Types NULL, FIN and Xmas
- Task 9 Scan Types ICMP Network Scanning
- Task 10 NSE Scripts Overview
- Task 11 NSE Scripts Working with the NSE
- Task 12 NSE Scripts Searching for Scripts
- Task 13 Firewall Evasion
- Task 14 Practical
- Task 15 Conclusion

How likely are you to recommend this room to others?

Room Walkthrough Summary

Each task in the room covers an advanced aspect of Nmap scanning.

Here's a summary of what was covered:

Task 1: TCP Connect vs SYN Scans Learned

the difference between:

- sT (TCP Connect) — a full handshake, more detectable.
- sS (SYN Stealth) — half-open scan, stealthier and faster.

Task 2: UDP Scanning

Task 2: UDP Scanning

Used:

```
nmap -sU <IP>
```

Observed how much slower UDP scanning is and how some services (like DNS or SNMP) may only be discovered through UDP ports.

Task 3: Service Versioning

Used:

```
nmap -sV <IP>
```

Learned how Nmap uses probes and matches for banner grabbing and version detection.

Task 4: Aggressive Scan

Command:

```
nmap -A <IP>
```

This bundled OS detection, version detection, traceroute, and script scanning. Great for quick recon but noisy.

Task 5: Default Scripts

Command:

```
nmap -sC <IP>
```

Learned that -sC runs the default NSE (Nmap Scripting Engine) scripts.

These can identify things like:

- HTTP titles
- SSL cert info
- FTP anonymous access
- SMB versions

Task 6: OS Detection

Used:

```
nmap -O <IP>
```

Nmap compares network behavior to an internal database to guess the target OS — though not always 100% accurate.

Task 7: NSE Scripts

Used:

```
nmap --script <script-name> <IP>
```

Learned how to use custom and category-based scripts, e.g.:

```
nmap --script vuln <IP>
```

```
nmap --script http-title <IP>
```