

Package ‘fastfurious’

March 23, 2016

Type Package

Title fastfurious

Version 0.1-1

Date 2015-08-03

Author Gino Tesei <gtesei@yahoo.com>

Maintainer Gino Tesei <gtesei@yahoo.com>

Description fast-furiuos gathers code, models and meta-models I needed in my
Machine Learning Lab but I didn't found on the shelf.

License MIT + file LICENSE

URL <https://github.com/gteseifast-furious>

BugReports <https://github.com/gteseifast-furious/issues>

VignetteBuilder knitr

Suggests knitr, lattice (>= 0.20), ggplot2 (>= 1.0.0), testthat,
Cubist, arm, MASS, kknn, kernlab, ipred, randomForest, pROC

Depends R (>= 2.10), caret

Imports parallel, subselect, plyr, xgboost, magrittr, stringr, e1071,
glmnet, verification

RoxygenNote 5.0.1

R topics documented:

ff.bindPath	2
ff.blend	3
ff.corrFilter	4
ff.createEnsemble	5
ff.encodeCategoricalFeature	7
ff.extractDateFeature	9
ff.featureFilter	9
ff.getBestBlenderPerformance	10
ff.getBestBlenderTune	11
ff.getMaxCuncurrentThreads	11
ff.getPath	12
ff.getPathBindings	12
ff.kmeans	13

ff.makeFeatureSet	14
ff.pca	15
ff.plotPerformance.reg	16
ff.poly	17
ff.setBasePath	17
ff.setMaxCuncurrentThreads	18
ff.summaryBlender	18
ff.trainAndPredict.class	19
ff.trainAndPredict.reg	20
ff.verifyBlender	22
RMSE.xgb	23
RMSLE.xgb	23
RMSPE	24

Index	25
--------------	-----------

ff.bindPath	<i>Bind an absolute path for a kind of resources.</i>
-------------	---

Description

Bind an absolute path for a kind of resources.

Usage

```
ff.bindPath(type, sub_path, createDir = FALSE)
```

Arguments

type	the type of resource.
sub_path	the suffix to concatenate to the absolute path to get the absolute path of the kind of resource.
createDir	set to 'TRUE' to create the directory if it does not exist

Examples

```
ff.setBasePath(getwd())
if(! dir.exists("mydata") ) dir.create('mydata')
ff.bindPath(type = "data",sub_path = "mydata")
```

ff.blend	<i>Given a tuned regression model, finds more performant tuning configurations using Nelder/Mead, quasi-Newton and conjugate-gradient algorithms.</i>
----------	---

Description

Given a tuned regression model, finds more performant tuning configurations using Nelder/Mead, quasi-Newton and conjugate-gradient algorithms.

Usage

```
ff.blend(bestTune, caretModelName, Xtrain, y, controlObject, max_secs = 10 *
  60, seed = NULL, method = c("Nelder-Mead", "BFGS", "CG", "L-BFGS-B",
    "SANN"), useInteger = TRUE, parallelize = TRUE, verbose = TRUE)
```

Arguments

bestTune	a data.frame with best tuned parameters of specified model.
caretModelName	a string specifying which model to use. Possible values are 'lm', 'bayesglm', 'glm', 'glmStepAIC', 'rlm', 'knn', 'pls', 'ridge', 'enet', 'svmRadial', 'treebag', 'gbm', 'rf', 'cubist', 'avNNet', 'xgbTreeGJTJ', 'xgbTree'
Xtrain	the encoded data.frame of train data. Must be a data.frame of numeric
y	the output variable as numeric vector
controlObject	a list of values that define how this function acts. Must be a caret trainControl object
max_secs	the max number of seconds as time constraint
seed	a user specified seed. Useful for replicable execution (e.g. passing the same seed to the ff.verifyBlender function) if the control object involves random steps for creating resamples.
method	the method to use. Possible values are c('Nelder-Mead', 'BFGS', 'CG', 'L-BFGS-B', 'SANN').
useInteger	TRUE if the tuning grid is composed of integers and not of continuous numbers.
parallelize	TRUE to enable parallelization (require parallel).
verbose	TRUE to enable verbose mode.

Value

a list of lists (one for each specified optimization method) with components par (best set of parameters found), value (the value of fn corresponding to par), counts (a two-element integer vector giving the number of calls to fn and gr respectively; this excludes those calls needed to compute the Hessian, if requested, and any calls to fn to compute a finite-difference approximation to the gradient), convergence (an integer code. 0 indicates successful completion which is always the case for SANN and Brent), message (a character string giving any additional information returned by the optimizer, or NULL), seed (the used seed). For further details see [optim](#).

References

<https://stat.ethz.ch/pipermail/r-devel/2010-August/058081.html>

Examples

```
## suppress warnings raised because there few obs
warn_def = getOption('warn')
options(warn=-1)

## data
Xtrain <- data.frame( a = rep(1:5 , each = 2), b = 10:1,
  c = rep(as.Date(c("2007-06-22", "2004-02-13")),5) )
Xtest <- data.frame( a = rep(2:6 , each = 2), b = 1:10,
  c = rep(as.Date(c("2007-03-01", "2004-05-23")),5) )
Ytrain = 1:10 + runif(nrow(Xtrain))

## encode datasets
l = ff.makeFeatureSet(Xtrain,Xtest,c("C","N","D"))
Xtrain = l$traindata
Xtest = l$testdata

## make a caret control object
controlObject <- trainControl(method = "repeatedcv",
  repeats = 1, number = 2)

## train and predict
tp = ff.trainAndPredict.reg(Ytrain=Ytrain ,
  Xtrain=Xtrain ,
  Xtest=Xtest ,
  model.label = "cubist" ,
  controlObject=controlObject)

pred_test = tp$pred
model = tp$model
secs = tp$secs

## blender
gBlender = ff.blend(bestTune = tp$model$bestTune,
  caretModelName = "cubist" ,
  Xtrain = Xtrain ,
  y = Ytrain, controlObject = tp$model$control,
  max_secs = 3,
  seed = 123,
  method = c("Nelder-Mead", "BFGS", "CG", "L-BFGS-B", "SANN"),
  useInteger = TRUE,
  parallelize = TRUE,
  verbose = FALSE)

ff.summaryBlender(gBlender)
ff.getBestBlenderPerformance(gBlender)
bestTune = ff.getBestBlenderTune(gBlender)
ff.verifyBlender (gBlender,Xtrain=Xtrain,y=Ytrain,seed=123,
  controlObject=tp$model$control,caretModelName = "cubist")

## restore warnings
options(warn=warn_def)
```

ff.corrFilter

Filter a data.frame of numeric according to a given threshold of correlation

Description

Filter a data.frame of numeric according to a given threshold of correlation

Usage

```
ff.corrFilter(Xtrain, Xtest, y, abs_th = NULL, rel_th = 1,
             method = "pearson")
```

Arguments

Xtrain	a train set data.frame of numeric
Xtest	a test set data.frame of numeric
y	the output variable (as numeric vector)
abs_th	an absolute threshold (= number of data frame columns)
rel_th	a relative threshold (= percentage of data frame columns)
method	a character string indicating which correlation method is to be used for the test. One of "pearson", "kendall", or "spearman".

Value

a list of filtered train set and test set with correlation test results

Examples

```
Xtrain <- data.frame( a = rep(1:3 , each = 2), b = c(4:1,6,6), c = rep(1,6))
Xtest <- Xtrain + runif(nrow(Xtrain))
y = 1:6
l = ff.corrFilter(Xtrain=Xtrain,Xtest=Xtest,y=y,rel_th=0.5)
Xtrain.filtered = l$Xtrain
Xtest.filtered = l$Xtest
```

ff.createEnsemble	<i>Create an ensemble of a tuned model</i>
-------------------	--

Description

Create an ensemble of a tuned model

Usage

```
ff.createEnsemble(Xtrain, Xtest, y, caretModelName, bestTune, predTest = NULL,
                 removePredictorsMakingIllConditionedSquareMatrix_forLinearModels = TRUE,
                 controlObject, parallelize = TRUE, verbose = TRUE, regression = TRUE,
                 ...)
```

Arguments

Xtrain	the encoded data.frame of train data. Must be a data.frame of numeric
Xtest	the encoded data.frame of test data. Must be a data.frame of numeric
y	the output variable as numeric vector
caretModelName	a string specifying which model to use. Possible values for regression are 'lm', 'bayesglm', 'glm', 'glmStepAIC', 'rlm', 'knn', 'pls', 'ridge', 'enet', 'svmRadial', 'treebag', 'gbm', 'rf', 'cubist', 'avNNet', 'xgbTreeGTJ', 'xgbTree'.
bestTune	a data.frame with best tuned parameters of specified model.
predTest	test set prediction (numeric vector). If available, passing it through this paramter the function doesn't compute it again for creating the esemble.
removePredictors	MakingIllConditionedSquareMatrix_forLinearModels TRUE for removing predictors making ill-conditioned square matrices in case of fragile linear models, i.e. c('rlm', 'pls', 'ridge', 'enet') for regression.
controlObject	a list of values that define how this function acts. Must be a caret trainControl object
parallelize	TRUE to enable parallelization (require parallel).
verbose	TRUE to enable verbose mode.
regression	TRUE to create an ensemble of a tuned regression model and FALSE to create an ensemble of a tuned classification model.
...	arguments passed to the regression routine.

Value

a list of train and test predictions.

Examples

```
## suppress warnings raised because there few obs
warn_def = getOption('warn')
options(warn=-1)

## data
Xtrain <- data.frame( a = rep(1:10 , each = 2), b = 20:1,
c = rep(as.Date(c("2007-06-22", "2004-02-13")),10) )
Xtest <- data.frame( a = rep(2:11 , each = 2), b = 1:20,
c = rep(as.Date(c("2007-03-01", "2004-05-23")),10) )
Ytrain = 1:20 + runif(nrow(Xtrain))

## encode datasets
l = ff.makeFeatureSet(Xtrain,Xtest,c("C","N","D"))
Xtrain = l$traindata
Xtest = l$testdata

## make a caret control object
controlObject <- trainControl(method = "repeatedcv", repeats = 1, number = 2)

tp = ff.trainAndPredict.reg(Ytrain=Ytrain ,
                           Xtrain=Xtrain ,
                           Xtest=Xtest ,
```

```

        model.label = "cubist" ,
        controlObject=controlObject)

pred_test = tp$pred
model = tp$model
secs = tp$secs

## create ensemble
en = ff.createEnsemble(Xtrain = Xtrain,
                      Xtest = Xtest,
                      y = Ytrain,
                      bestTune = tp$model$bestTune ,
                      caretModelName = "cubist" ,
                      parallelize = TRUE,
                      removePredictorsMakingIllConditionedSquareMatrix_forLinearModels = TRUE,
                      controlObject = tp$model$control)
predTrain = en$predTrain
predTest = en$predTest

## restore warnings
options(warn=warn_def)

```

ff.encodeCategoricalFeature

Encode a generic predictor as a categorical features using both observations of train set and test for levels. It's anyway possible to adopt more levels by using the parameter levels. Notice that modeling a generic vector, e.g. c(1,2,3,4,5,2,3) as a categorical predictor xor a numeric predictor is a modeling choice (eventually to be assessed by cross-validation).

Description

Encode a generic predictor as a categorical features using both observations of train set and test for levels. It's anyway possible to adopt more levels by using the parameter levels. Notice that modeling a generic vector, e.g. c(1,2,3,4,5,2,3) as a categorical predictor xor a numeric predictor is a modeling choice (eventually to be assessed by cross-validation).

Usage

```

ff.encodeCategoricalFeature(data.train, data.test, colname.prefix,
                           asNumericSequence = F, replaceWhiteSpaceInLevelsWith = NULL,
                           levels = NULL, remove1DummyVar = FALSE)

```

Arguments

data.train	the observations of the predictor in train set.
data.test	the observations of the predictor in test set.
colname.prefix	the prefix of output data frame.
asNumericSequence	set T if the predictor is a numeric sequence filling any possible hole between min and max in observations that could occur both in train set and test set.

replaceWhiteSpaceInLevelsWith

replace possible spaces in the train/test name of feature.

levels

the levels of the categorical feature. Must be NULL if asNumericSequence is T.

remove1DummyVar

T to remove one dummy variable. Why? First, if you know the values of the first $C - 1$ dummy variables, you know the last one too and it is more economical to use $C - 1$. Secondly, if the model has slopes and intercepts (e.g. linear regression), the sum of all of the dummy variables will add up to the intercept (usually encoded as a "1") and that is bad for the math involved. On the other hand, there are models like penalized methods (such as ridge regression) that seldom penalize the intercept, so a $C-1$ encoded variable could cause the other category effects to be penalized towards the reference category effect.

Value

the list of trainset and testset after applying the specified filters

References

<http://appliedpredictivemodeling.com/blog/2013/10/23/the-basics-of-encoding-categorical-data-fo>

Examples

```
Xtrain <- data.frame( a = rep(1:3 , each = 2), b = 6:1, c = letters[1:6])
Xtest <- data.frame( a = rep(2:4 , each = 2), b = 1:6, c = letters[6:1])
print(Xtrain)
#   a b c
# 1 1 6 a
# 2 1 5 b
# 3 2 4 c
# 4 2 3 d
# 5 3 2 e
# 6 3 1 f

l = ff.encodeCategoricalFeature (Xtrain$c , Xtest$c , "c")
l$traindata
#      c_1 c_2 c_3 c_4 c_5 c_6
# 7      1  0  0  0  0  0
# 8      0  1  0  0  0  0
# 9      0  0  1  0  0  0
# 10     0  0  0  1  0  0
# 11     0  0  0  0  1  0
# 12     0  0  0  0  0  1

Xtrain[, 'c'] = NULL
Xtest[, 'c'] = NULL
Xtrain = cbind(Xtrain, l$traindata)
Xtest = cbind(Xtest, l$testdata)
```

`ff.extractDateFeature` *Extracts a numerical feature from a date predictor. The feature is built as the difference in days from the oldest date in both the train set and test set and any given observation.*

Description

Extracts a numerical feature from a date predictor. The feature is built as the difference in days from the oldest date in both the train set and test set and any given observation.

Usage

```
ff.extractDateFeature(data.train, data.test)
```

Arguments

`data.train` the observations of the predictor in train set.
`data.test` the observations of the predictor in test set.

Value

the list of trainset and testset after applying the specified encoding and the related date range

Examples

```
Xtrain <- data.frame( a = rep(1:3 , each = 2), b = 6:1,
  c = rep(as.Date(c("2007-06-22", "2004-02-13")),3) )
Xtest <- data.frame( a = rep(2:4 , each = 2), b = 1:6,
  c = rep(as.Date(c("2007-03-01", "2004-05-23")),3) )
l = ff.extractDateFeature(Xtrain$c,Xtest$c)
Xtrain[, 'c'] = NULL
Xtest[, 'c'] = NULL
Xtrain = cbind(Xtrain,c=l$traindata)
Xtest = cbind(Xtest,c=l$testdata)
```

`ff.featureFilter` *Filter predictors according to specified criteria.*

Description

Filter predictors according to specified criteria.

Usage

```
ff.featureFilter(traindata, testdata, y = NULL,
  removeOnlyZeroVariancePredictors = FALSE,
  performVarianceAnalysisOnTrainSetOnly = TRUE, correlationThreshold = NULL,
  removePredictorsMakingIllConditionedSquareMatrix = TRUE,
  removeIdenticalPredictors = TRUE, removeHighCorrelatedPredictors = TRUE,
  featureScaling = TRUE, verbose = TRUE)
```

Arguments

traindata	the train set
testdata	the test set
y	the response variable. Must be not NULL if correlationThreshold is not NULL.
removeOnlyZeroVariancePredictors	TRUE to remove only zero variance predictors
performVarianceAnalysisOnTrainSetOnly	TRUE to perform the variance analysis on the train set only
correlationThreshold	a correlation threshold above which keeping predictors (considered only if removeOnlyZeroVariancePredictors is FALSE).
removePredictorsMakingIllConditionedSquareMatrix	TRUE to predictors making ill conditioned square matrices
removeIdenticalPredictors	TRUE to remove identical predictors (using base::identical function)
removeHighCorrelatedPredictors	TRUE to remove high correlated predictors
featureScaling	TRUE to perform feature scaling
verbose	TRUE to set verbose mode

Value

the list of trainset and testset after applying the specified filters

Examples

```
Xtrain <- data.frame( a = rep(1:3 , each = 2), b = c(4:1,6,6), c = rep(1,6))
Xtest <- Xtrain + runif(nrow(Xtrain))
l = ff.featureFilter (traindata = Xtrain,
                    testdata = Xtest,
                    removeOnlyZeroVariancePredictors=TRUE)
Xtrain = l$traindata
Xtest = l$testdata
```

ff.getBestBlenderPerformance

Helper function that given a blender object returns the best optimization method.

Description

Helper function that given a blender object returns the best optimization method.

Usage

```
ff.getBestBlenderPerformance(blender)
```

Arguments

blender	a blender object
---------	------------------

Value

a numeric of best score and as object name the best performant method name.

See Also

[ff.blend](#) for examples.

`ff.getBestBlenderTune` *Helper function that given a blender object returns the best tuning parameters found by the blender.*

Description

Helper function that given a blender object returns the best tuning parameters found by the blender.

Usage

```
ff.getBestBlenderTune(blender, truncate = TRUE)
```

Arguments

<code>blender</code>	a blender object
<code>truncate</code>	TRUE to cut at the first tuning best configuration in case there are more than one optimal tuning configurations.

Value

a data.frame of the best tuning parameters.

See Also

[ff.blend](#) for examples.

`ff.getMaxCuncurrentThreads`
Get the max number of cuncurrent threads.

Description

Get the max number of cuncurrent threads.

Usage

```
ff.getMaxCuncurrentThreads()
```

Examples

```
ff.getMaxCuncurrentThreads()
```

ff.getPath	<i>Get the absolute path for a kind of resources.</i>
------------	---

Description

Get the absolute path for a kind of resources.

Usage

```
ff.getPath(type = "base")
```

Arguments

type the type of resource.

Value

the absolute path for a kind of resources (as character)

Examples

```
ff.setBasePath('.')
ff.getPath() ## equivalent to ff.getPath(type="base")
```

ff.getPathBindings	<i>Get the list of bindings, i.e. (type resource,absolute path) pairs as a list</i>
--------------------	---

Description

Get the list of bindings, i.e. (type resource,absolute path) pairs as a list

Usage

```
ff.getPathBindings()
```

Value

the list of bindings

Examples

```
ff.setBasePath(getwd())
if(! dir.exists("mydata") ) dir.create('mydata')
ff.bindPath(type = "data",sub_path = "mydata")
ff.getPathBindings()
```

ff.kmeans	<i>An useful wrapper of kmeans performing k-means clustering on the given trainset / testset (Xtrain / Xtest) and assuming a number of cluster from 1:max_centers. The best number of cluster is computed so that the variation in the within group sum of squares between two subsequent number of clusters is maximized in absolute value.</i>
-----------	--

Description

An useful wrapper of [kmeans](#) performing k-means clustering on the given trainset / testset (Xtrain / Xtest) and assuming a number of cluster from 1:max_centers. The best number of cluster is computed so that the variation in the within group sum of squares between two subsequent number of clusters is maximized in absolute value.

Usage

```
ff.kmeans(Xtrain, Xtest, max_centers = 10, nstart = 5, iter.max = 10,
          doPlot = FALSE, verbose = FALSE)
```

Arguments

Xtrain	the encoded data.frame of train data. Must be a data.frame of numeric
Xtest	the encoded data.frame of train data. Must be a data.frame of numeric
max_centers	the max number of clusters to be evaluated
nstart	how many random sets should be chosen? Such a parameter is passed to kmeans .
iter.max	the maximum number of iterations allowed. Such a parameter is passed to kmeans .
doPlot	a logical value indicating whether plotting.
verbose	a logical value indicating whether verbose mode should be enabled.
varThreshold	a threshold indicating the proportion of variance that should be explained. Must be a numeric between 0 and 1.

Value

a list whose components are the max number of clusters evaluated (max_centers), the best number of clusters (best_n_clusters), the sequence of within groups sum of squares across number of clusters (wss), assuming best_n_clusters as number of clusters a vector of integers (from 1:best_n_clusters) indicating the cluster to which each point is allocated in the train set (K.train) and test set (K.test).

Examples

```
## data
Xtrain <- data.frame(a = rep(1:10 , each = 2), b = 20:1,
                    c = rep(as.Date(c("2007-06-22", "2004-02-13")),10) , d = 20:1)
Xtest <- data.frame(a = rep(2:11 , each = 2), b = 1:20,
                   c = rep(as.Date(c("2007-03-01", "2004-05-23")),10) , d = 1:20)

## encode data sets
l = ff.makeFeatureSet(Xtrain,Xtest,c("C","N","D","N"))
```

```

Xtrain = l$traindata
Xtest = l$testdata

ffKmeans = ff.kmeans(Xtrain = Xtrain , Xtest = Xtest ,
                     max_centers = 10 , verbose = TRUE)

best_n_clusters = ffKmeans$best_n_clusters

K.train = ffKmeans$K.train
K.test = ffKmeans$K.test

```

ff.makeFeatureSet	<i>Encode the feature set according to meta data passed as input.</i>
-------------------	---

Description

Encode the feature set according to meta data passed as input.

Usage

```
ff.makeFeatureSet(data.train, data.test, meta, scaleNumericFeatures = FALSE,
                  parallelize = FALSE, remove1DummyVarInCatPreds = FALSE)
```

Arguments

data.train	the observations of the predictor in train set.
data.test	the observations of the predictor in test set.
meta	the meata data. It should be a vector of the character 'C' , 'N' , 'D' , e.g. c('N','C','D') of the same length of the train set / test set columns
scaleNumericFeatures	seto to 'TRUE' to center and scale numeric features
parallelize	set to 'TRUE' to enable parallelization (require parallel package)
remove1DummyVarInCatPreds	T to remove one dummy variable in encoding categorical predictors. For further details see ff.encodeCategoricalFeature .

Value

the list of trainset and testset after applying the specified encodings

Examples

```

Xtrain <- data.frame( a = rep(1:3 , each = 2), b = 6:1,
                     c = rep(as.Date(c("2007-06-22", "2004-02-13")),3) )
Xtest <- data.frame( a = rep(2:4 , each = 2), b = 1:6,
                    c = rep(as.Date(c("2007-03-01", "2004-05-23")),3) )
l = ff.makeFeatureSet(Xtrain,Xtest,c('C','N','D'))
Xtrain = l$traindata
Xtest = l$testdata

```

ff.pca	<i>An useful wrapper of prcomp performing a principal components analysis on the given trainset / testset (Xtrain / Xtest).</i>
--------	---

Description

An useful wrapper of [prcomp](#) performing a principal components analysis on the given trainset / testset (Xtrain / Xtest).

Usage

```
ff.pca(Xtrain, Xtest, center = TRUE, scale. = FALSE,
       removeZeroVarPredictors = TRUE, varThreshold = 0.95, doPlot = TRUE,
       verbose = FALSE)
```

Arguments

Xtrain	the encoded data.frame of train data. Must be a data.frame of numeric
Xtest	the encoded data.frame of train data. Must be a data.frame of numeric
center	a logical value indicating whether the variables should be shifted to be zero centered. Alternately, a vector of length equal the number of columns of data can be supplied. The value is passed to scale.
scale.	a logical value indicating whether the variables should be scaled to have unit variance before the analysis takes place. The default is FALSE for consistency with S, but in general scaling is advisable. Alternatively, a vector of length equal the number of columns of data can be supplied. The value is passed to scale.
removeZeroVarPredictors	a logical value indicating whether removing zero variance predictors before calling prcomp preventing errors due to the fact that the latter cannot rescale a constant/zero column to unit variance.
varThreshold	a threshold indicating the proportion of variance that should be explained. Must be a numeric between 0 and 1.
doPlot	a logical value indicating whether plotting the proportion of variance explained vs. principal components.
verbose	a logical value indicating whether verbose mode should be enabled.

Value

a list whose components are the number of principal components (numComp), the number of principal components to hold so that the proportion of variance explained by each subsequent principal component drops off as an elbow in the screen plot (numComp.elbow), the number of principal components explaining a given (specified by the varThreshold input parameter) proportion of variance (numComp.threshold), the threshold indicating the proportion of variance that should be explained (varThreshold), the cumulative sum of proportion of variance explained by each principal component (cumVar), the proportion of variance explained by each principal component (var), the principal components for train and test set (PC.train and PC.test)

Examples

```
## data
Xtrain <- data.frame(a = rep(1:10 , each = 2), b = 20:1,
                    c = rep(as.Date(c("2007-06-22", "2004-02-13")),10) , d = 20:1)
Xtest <- data.frame(a = rep(2:11 , each = 2), b = 1:20,
                   c = rep(as.Date(c("2007-03-01", "2004-05-23")),10) , d = 1:20)

## encode data sets
l = ff.makeFeatureSet(Xtrain,Xtest,c("C","N","D","N"))
Xtrain = l$traindata
Xtest = l$testdata

ffPCA = ff.pca(Xtrain = Xtrain , Xtest = Xtest , center = TRUE , scale. = TRUE ,
               removeZeroVarPredictors = TRUE ,
               varThreshold = 0.95 , doPlot = FALSE , verbose = TRUE)

numComp <- ffPCA$numComp
numComp.elbow <- ffPCA$numComp.elbow
numComp.threshold <- ffPCA$numComp.threshold

PC_Xtrain_95Var = ffPCA$PC.train[1:numComp.threshold,,drop=FALSE]
PC_Xtest_95Var = ffPCA$PC.test[1:numComp.threshold,,drop=FALSE]
```

ff.plotPerformance.reg

Plot predicted values vs. observed / residual values.

Description

Plot predicted values vs. observed / residual values.

Usage

```
ff.plotPerformance.reg(observed, predicted, main = NULL)
```

Arguments

observed	the observed output variables (numeric vector).
predicted	the predicted values (numeric vector).
main	a string as a title for the plot

Examples

```
obs = 1:10
preds = obs + runif(length(obs))
ff.plotPerformance.reg(observed = obs , predicted = preds, main="Predicted vs. observed/residual")
```

ff.poly	<i>Make polynomial terms of a data.frame</i>
---------	--

Description

Make polynomial terms of a data.frame

Usage

```
ff.poly(x, n, direction = 0)
```

Arguments

x	a data.frame of numeric
n	the polynomial degree
direction	if set to 0 returns the terms $x^{(1/n)}, x^{(1/(n-1))}, \dots, x, x^2, \dots, x^n$. If set to -1 returns the terms $x^{(1/n)}, x^{(1/(n-1))}, \dots, x$. If set to 1 returns the terms x, x^2, \dots, x^n .

Value

the data.frame with the specified polynomial terms

Examples

```
Xtrain <- data.frame( a = rep(1:3 , each = 2), b = c(4:1,6,6), c = rep(1,6))
Xtest <- Xtrain + runif(nrow(Xtrain))
data = rbind(Xtrain,Xtest)
data.poly = ff.poly(x=data,n=3)
Xtrain.poly = data.poly[1:nrow(Xtrain),]
Xtest.poly = data.poly[(nrow(Xtrain)+1):nrow(data),]
```

ff.setBasePath	<i>Set base path</i>
----------------	----------------------

Description

Set base path

Usage

```
ff.setBasePath(path)
```

Arguments

path	the absolute path.
------	--------------------

Examples

```
ff.setBasePath('./')
```

```
ff.setMaxCuncurrentThreads
```

Set the max number of cuncurrent threads.

Description

Set the max number of cuncurrent threads.

Usage

```
ff.setMaxCuncurrentThreads(nThreads = 2)
```

Arguments

nThreads max number of cuncurrent threads.

Examples

```
ff.setMaxCuncurrentThreads(4)
```

```
ff.summaryBlender
```

Helper function that given a blender object returns a numeric vector of performances (one for each optimization method).

Description

Helper function that given a blender object returns a numeric vector of performances (one for each optimization method).

Usage

```
ff.summaryBlender(blender)
```

Arguments

blender a blender object

Value

a numeric vector of performances (one for each optimization method)

See Also

[ff.blend](#) for examples.

ff.trainAndPredict.class

Trains a specified classification model on the given train set and predicts on the given test set.

Description

Trains a specified classification model on the given train set and predicts on the given test set.

Usage

```
ff.trainAndPredict.class(Ytrain, Xtrain, Xtest, model.label, controlObject,
  best.tuning = FALSE, verbose = FALSE,
  removePredictorsMakingIllConditionedSquareMatrix_forLinearModels = TRUE,
  metric.label = "auc", xgb.metric.fun = NULL, xgb.maximize = FALSE,
  xgb.foldList = NULL, xgb.eta = NULL, xgb.max_depth = NULL,
  xgb.cv.default = TRUE, xgb.param = NULL, ...)
```

Arguments

Ytrain	the output variable as numeric vector
Xtrain	the encoded data.frame of train data. Must be a data.frame of numeric
Xtest	the encoded data.frame of test data. Must be a data.frame of numeric
model.label	a string specifying which model to use.
controlObject	a list of values that define how this function acts. Must be a caret trainControl object for all models except that for 'xgbTreeGTJ'.
best.tuning	TRUE to use more dense tuning grid or custom routine/tuning grid if available
verbose	TRUE to enable verbose mode.
removePredictorsMakingIllConditionedSquareMatrix_forLinearModels	TRUE for removing predictors making ill-conditioned square matrices in case of fragile linear models.
metric.label	the label of function to optimize/minimize.
xgb.metric.fun	custom function to optimize/minimize for 'xgbTreeGTJ'.
xgb.maximize	TRUE to maximize the specified xgb.metric.fun.
xgb.foldList	custom resampling folds list for 'xgbTreeGTJ'.
xgb.eta	custom eta parameter for 'xgbTreeGTJ'.
xgb.max_depth	custom max_depth parameter for 'xgbTreeGTJ'.
xgb.cv.default	TRUE for using xgboost::xgb.cv function (mandatory in case of fix nrounds), FALSE for using the internal ff.xgb.cv function. The main advantage of the latter is that it doesn't need to restart nrounds in case for the specified nrounds cross validation error is still decreasing.
xgb.param	custom parameters for XGBoost.
...	arguments passed to the regression routine.

Value

a list of test predictions, model and number of executing seconds.

Examples

```
## suppress warnings raised because of few obs
warn_def = getOption('warn')
options(warn=-1)

## data
Xtrain <- data.frame( a = rep(1:10 , each = 2), b = 20:1,
                     c = rep(as.Date(c("2007-06-22", "2004-02-13")),10) , d = 20:1)
Xtest <- data.frame( a = rep(2:11 , each = 2), b = 1:20,
                    c = rep(as.Date(c("2007-03-01", "2004-05-23")),10) , d = 1:20)
Ytrain = c(rep(1,10),rep(0,10))

## encode datasets
l = ff.makeFeatureSet(Xtrain,Xtest,c("C","N","D","N"))
Xtrain = l$traindata
Xtest = l$testdata

## make a caret control object
controlObject <- trainControl(method = "repeatedcv", repeats = 2, number = 3 ,
                             summaryFunction = twoClassSummary , classProbs = TRUE)
tp = ff.trainAndPredict.class(Ytrain=Ytrain ,
                              Xtrain=Xtrain ,
                              Xtest=Xtest,
                              model.label = "svmRadial" ,
                              controlObject=controlObject,
                              verbose=TRUE ,
                              best.tuning=TRUE)

pred_test = tp$pred
model = tp$model
elapsed.secs = tp$secs

bestTune = l$model$bestTune
best_ROC = max(tp$model$results$ROC)

## restore warnings
options(warn=warn_def)
```

```
ff.trainAndPredict.reg
```

Trains a specified model on the given train set and predicts on the given test set.

Description

Trains a specified model on the given train set and predicts on the given test set.

Usage

```
ff.trainAndPredict.reg(Ytrain, Xtrain, Xtest, model.label, controlObject,
                       best.tuning = FALSE, verbose = FALSE,
                       removePredictorsMakingIllConditionedSquareMatrix_forLinearModels = TRUE,
                       xgb.metric.fun = RMSLE.xgb, xgb.maximize = FALSE,
                       xgb.metric.label = "RMSLE", xgb.foldList = NULL, xgb.eta = NULL,
                       xgb.max_depth = NULL, xgb.cv.default = TRUE, xgb.param = NULL, ...)
```

Arguments

<code>Ytrain</code>	the output variable as numeric vector
<code>Xtrain</code>	the encoded data.frame of train data. Must be a data.frame of numeric
<code>Xtest</code>	the encoded data.frame of test data. Must be a data.frame of numeric
<code>model.label</code>	a string specifying which model to use. Possible values are 'lm', 'bayesglm', 'glm', 'glmStepAIC', 'rlm', 'knn', 'pls', 'ridge', 'enet', 'svmRadial', 'treebag', 'gbm', 'rf', 'cubist', 'avNNet', 'xgbTreeGTJ', 'xgbTree'
<code>controlObject</code>	a list of values that define how this function acts. Must be a caret trainControl object for all models except that for 'xgbTreeGTJ' and 'xgbTree'. In the latter case only if <code>best.tuning</code> is TRUE.
<code>best.tuning</code>	TRUE to use more dense tuning grid or custom routine if available
<code>verbose</code>	TRUE to enable verbose mode.
<code>removePredictors</code>	<code>MakingIllConditionedSquareMatrix_forLinearModels</code> TRUE for removing predictors making ill-conditioned square matrices in case of fragile linear models, i.e. <code>c('rlm', 'pls', 'ridge', 'enet')</code> .
<code>xgb.metric.fun</code>	custom function to optimize/minimize for 'xgbTreeGTJ' and 'xgbTree'. In the latter case only if <code>best.tuning</code> is TRUE.
<code>xgb.maximize</code>	TRUE to maximize the specified <code>xgb.metric.fun</code> . Only for 'xgbTreeGTJ' and 'xgbTree'. In the latter case only if <code>best.tuning</code> is TRUE.
<code>xgb.metric.label</code>	custom label of function to optimize/minimize for 'xgbTreeGTJ' and 'xgbTree'. In the latter case only if <code>best.tuning</code> is TRUE.
<code>xgb.foldList</code>	custom resampling folds list for 'xgbTreeGTJ' and 'xgbTree'. In the latter case only if <code>best.tuning</code> is TRUE.
<code>xgb.eta</code>	custom eta parameter for 'xgbTreeGTJ' and 'xgbTree'. In the latter case only if <code>best.tuning</code> is TRUE.
<code>xgb.max_depth</code>	custom <code>max_depth</code> parameter for 'xgbTreeGTJ' and 'xgbTree'. In the latter case only if <code>best.tuning</code> is TRUE.
<code>xgb.cv.default</code>	TRUE for using <code>xgboost::xgb.cv</code> function (mandatory in case of fix rounds), FALSE for using the internal <code>ff.xgb.cv</code> function. The main advantage of the latter is that it doesn't need to restart rounds in case for the specified rounds cross validation error is still decreasing.
<code>xgb.param</code>	custom parameters for XGBoost.
<code>...</code>	arguments passed to the regression routine.

Value

a list of test predictions, model and number of executing seconds.

Examples

```
## suppress warnings raised because of few obs
warn_def = getOption('warn')
options(warn=-1)

## data
Xtrain <- data.frame( a = rep(1:10 , each = 2), b = 20:1,
  c = rep(as.Date(c("2007-06-22", "2004-02-13")),10) )
```

```

Xtest <- data.frame( a = rep(2:11 , each = 2), b = 1:20,
c = rep(as.Date(c("2007-03-01", "2004-05-23")),10) )
Ytrain = 1:20 + runif(nrow(Xtrain))

## encode datasets
l = ff.makeFeatureSet(Xtrain,Xtest,c("C","N","D"))
Xtrain = l$traindata
Xtest = l$testdata

## make a caret control object
controlObject <- trainControl(method = "repeatedcv", repeats = 1, number = 2)

tp = ff.trainAndPredict.reg(Ytrain=Ytrain ,
                           Xtrain=Xtrain ,
                           Xtest=Xtest ,
                           model.label = "cubist" ,
                           controlObject=controlObject)

pred_test = tp$pred
model = tp$model
elapsed.secs = tp$secs

## restore warnings
options(warn=warn_def)

```

ff.verifyBlender

Helper function that given a blender object replicates the execution in order to verify performances.

Description

Helper function that given a blender object replicates the execution in order to verify performances.

Usage

```
ff.verifyBlender(blender, Xtrain, y, seed = NULL, controlObject,
  caretModelname)
```

Arguments

blender	a blender object
Xtrain	the train set
y	the output variable as numeric vector
seed	the seed used by the blender, if applicable. If the blender used one, it is necessary for replicating blender performances.
controlObject	a list of values that define how this function acts. Must be a caret trainControl object. It must be the same used by the blender.
caretModelname	a string specifying which model to use. Possible values are 'lm', 'bayesglm', 'glm', 'glmStepAIC', 'rlm', 'knn', 'pls', 'ridge', 'enet', 'svmRadial', 'treebag', 'gbm', 'rf', 'cubist', 'avNNet', 'xgbTreeGJTJ', 'xgbTree'. It must be the same model name used by the blender.

Value

a numeric as difference in performance between blender and replicated execution.

See Also

[ff.blend](#) for examples.

RMSE.xgb	<i>Root mean square error</i>
----------	-------------------------------

Description

Root mean square error

Usage

```
RMSE.xgb(preds, dtrain)
```

Arguments

preds	the predicted values (numeric vector).
dtrain	the xgboost train set object.

Value

a list of metric label / values

RMSLE.xgb	<i>Root mean square logistic error</i>
-----------	--

Description

Root mean square logistic error

Usage

```
RMSLE.xgb(preds, dtrain, th_err = 1.5)
```

Arguments

preds	the predicted values (numeric vector).
dtrain	the xgboost train set object.
th_err	a threshold in case predictions are negative.

Value

a list of metric label / values

RMSPE	<i>Root mean square percentage error</i>
-------	--

Description

Root mean square percentage error

Usage

```
RMSPE(preds, dtrain)
```

Arguments

<code>preds</code>	the predicted values (numeric vector).
<code>dtrain</code>	the xgboost train set object.

Value

a list of metric label / values

Index

`ff.bindPath`, [2](#)
`ff.blend`, [3](#), [11](#), [18](#), [23](#)
`ff.corrFilter`, [4](#)
`ff.createEnsemble`, [5](#)
`ff.encodeCategoricalFeature`, [7](#), [14](#)
`ff.extractDateFeature`, [9](#)
`ff.featureFilter`, [9](#)
`ff.getBestBlenderPerformance`, [10](#)
`ff.getBestBlenderTune`, [11](#)
`ff.getMaxCuncurrentThreads`, [11](#)
`ff.getPath`, [12](#)
`ff.getPathBindings`, [12](#)
`ff.kmeans`, [13](#)
`ff.makeFeatureSet`, [14](#)
`ff.pca`, [15](#)
`ff.plotPerformance.reg`, [16](#)
`ff.poly`, [17](#)
`ff.setBasePath`, [17](#)
`ff.setMaxCuncurrentThreads`, [18](#)
`ff.summaryBlender`, [18](#)
`ff.trainAndPredict.class`, [19](#)
`ff.trainAndPredict.reg`, [20](#)
`ff.verifyBlender`, [3](#), [22](#)

`kmeans`, [13](#)

`optim`, [3](#)

`prcomp`, [15](#)

`RMSE.xgb`, [23](#)
`RMSLE.xgb`, [23](#)
`RMSPE`, [24](#)