


○○ programming

May 2018

Hadley Wickham
[@hadleywickham](#)
Chief Scientist, RStudio

Motivation

Why should you care about **S3**?



You're already using S3 objects in your analyses

Important S3 objects in base R


`data.frame()`

`factor()`

`Sys.Date()`

`Sys.time()`

`table()`



Complex functions need to return multiple things

This is obviously important for linear models

```
mod <- lm(mpg ~ wt, data = mtcars)
str(mod)
```

```
# But also their summaries
sum <- summary(mod)
str(sum)
```

Form follows function



One example is linear models

```
sum
#> Call:
#> lm(formula = mpg ~ wt, data = mtcars)
#>
#> Residuals:
#>      Min       1Q   Median       3Q      Max
#> -4.5432 -2.3647 -0.1252  1.4096  6.8727
#>
#> Coefficients:
#>              Estimate Std. Error t value Pr(>|t|)
#> (Intercept)  37.2851      1.8776  19.858  < 2e-16 ***
#> wt          -5.3445      0.5591  -9.559 1.29e-10 ***
#> ---
#> Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
#>
#> Residual standard error: 3.046 on 30 degrees of freedom
#> Multiple R-squared:  0.7528, Adjusted R-squared:  0.7446
#> F-statistic: 91.38 on 1 and 30 DF, p-value: 1.294e-10
```


Another example is tibbles

Total size

A tibble: 53,940 x 10

	carat	cut	color	clarity	depth	table	price	x	y	z
	<dbl>	<ord>	<ord>	<ord>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>
1	0.230	Ideal	E	SI2	61.5	55.0	326	3.95	3.98	2.43
2	0.210	Premium	E	SI1	59.8	61.0	326	3.8		
3	0.230	Good	E	VS1	56.9	65.0	327	4.05	4.07	2.51
4	0.290	Premium	I	VS2	62.4	58.0	334	4.20	4.23	2.63
5	0.310	Good	J	SI2	63.3	58.0	335	4.34	4.35	2.75
6	0.240	"Very Good"	J	VVS2	62.8	57.0	336	3.94	3.96	2.48
7	0.240	"Very Good"	I	VVS1	62.3	57.0	336	3.95	3.98	2.47
8	0.260	"Very Good"	H	SI1	61.9	55.0	337	4.07	4.11	2.53
9	0.220	Fair	E	VS2	65.1	61.0	337	3.87	3.78	2.49
10	0.230	"Very Good"	H	VS1	59.4	61.0	338	4.00	4.05	2.39

... with 53,930 more rows

Variable type

Only shows first 10 rows

S3 makes packages extensible

New methods

Lets you extend other packages

New generics

Write packages in way that others can easily extend.

You could use a nested if statement

```
mean <- function(x, ...) {  
  if (is.Date(x)) {  
    ...  
  } else if (is.difftime(x)) {  
    ...  
  } else if (is.POSIXct(x)) {  
  
  } else if (is.POSIXlt(x)) {  
    ...  
  } else {  
    ...  
  }  
}
```

But a generic function lets anyone extend

```
mean <- function(x, ...) {  
  UseMethod("mean")  
}
```

```
mean.Date <- function(x, ...) ...  
mean.diffftime <- function(x, ...) ...  
mean.POSIXct <- function(x, ...) ...  
mean.POSIXlt <- function(x, ...) ...  
  
mean.default <- function(x, ...) ...
```


Vector classes

<https://adv-r.hadley.nz/S3.html>

Your turn

What is an **attribute**? What types of objects can have attributes?

How do you *get* the value of an attribute?

How do you *set* the value an attribute?

What's *the* most important attribute?

Attributes add arbitrary metadata to any object

```
x <- 1:6  
attr(x, "max") <- 5  
attr(x, "max")  
attributes(x)
```

```
# structure returns a modified object  
structure(1:10, min = 1, max = 10)
```

```
# Most important attribute is names()
```

Your turn

Every S3 class is built on a base type (e.g. a vector). The two most important S3 classes are factor and data frame.

What are **factors** built on top of?

What attributes do they use?

What are **data frames** built on top of?

What attributes do they use?


```
f <- factor(c("a", "b", "c"))
typeof(f)      # Built on top of integer
attributes(f)  # Use levels and class attributes

d <- data.frame(f)
typeof(d)      # Built on top of list
attributes(d)  # names, row.names and class
```

“Scalar” classes

Back at 11:05am

Principle:

Provide consistent structure
and print method for
complex return values

Change working directory/project to:

[safely]

Challenge: how can improve the output of safely?

```
library(purrr)
safe_log <- safely(log)
```

```
safe_log("a")
#> $result
#> NULL
#>
#> $error
#> <simpleError in log(...):
#>   non-numeric argument to
#>   mathematical function>
```

```
safe_log(10)
#> $result
#> [1] 2.302585
#>
#> $error
#> NULL
```

1. Figure out name
2. Define properties of the class
3. Write the constructor
4. Write methods

Your turn

What are the invariants of the results of safely?

```
safe_log <- purrr::safely(log)
# what do we know to be always true
# about the result of safe_log?
```

Invariants

Return a list

- two components: result and error
- result should always come first
- one is always NULL

Now, write the constructor

```
new_safely <- function(result = NULL, error = NULL) {  
  if (!(is.null(result) || is.null(error))) {  
    stop(  
      "One of `result` and `error` must be NULL",  
      call. = FALSE  
    )  
  }  
  
  structure(  
    list(  
      result = result,  
      error = error  
    ),  
    class = "safely"  
  )  
}
```

Most S3 classes will
have this form

Definition of safely

```
safely <- function(.f) {  
  stopifnot(is.function(.f))  
  
  function(...) {  
    tryCatch({  
      list(result = .f(...), error = NULL)  
    }, error = function(e) {  
      list(result = NULL, error = e)  
    })  
  }  
}
```

Then use the constructor

```
safely <- function(.f) {  
  stopifnot(is.function(.f))  
  
  function(...) {  
    tryCatch({  
      new_safely(result = .f(...))  
    }, error = function(e) {  
      new_safely(error = e)  
    })  
  }  
}
```

How could we test the constructor?

Abbreviation	Test
<code>expect_null()</code>	Checks if a literal NULL
<code>expect_type()</code> <code>expect_s3_class()</code> <code>expect_s4_class()</code>	Check that inherits from a given base type, S3 class, or S4 class.
<code>expect_true()</code> <code>expect_false()</code>	Catch all expectations for anything not otherwise covered

Your turn

Write tests to ensure that our new `safely()` function returns the correct type of output regardless of whether or not an error occurs. (i.e. express the invariants as unit tests)


There is a bug in your version (think about what happens if the function returns `NULL`)!

Now we can improve the output with a print method

```
safe_log(10)
```

```
#> <safely: ok>
```

```
#> [1] 2.302585
```



I think it's good practice
to include type in <>

```
safe_log("a")
```

```
#> <safely: error>
```

```
#> Error: non-numeric argument to
```

```
#> mathematical function
```

S3 methods all have the same basic structure

generic.class

Same arguments as generic

```
print.safely <- function(x, ...) {
```

```
}
```

Methods belong to
generics, not classes

	Date	POSIXct	integer
print			
mean			
sum			

Date

POSIXct

integer

print

mean

sum

Your turn: fill in the blanks

```
print.safely <- function(x, ...) {
```

```
}
```

```
# Useful helper found in utils.R
```

```
cat_line <- function(...) {
```

```
  cat(..., "\n", sep = "")
```

```
}
```

```
# See https://github.com/r-lib/cli for
```

```
# many more helpers.
```

```
f <- function() NULL  
safe_f <- safely(f)  
safe_f()
```

```
# What has gone wrong?
```

```
# And how can you fix it?
```

My print method

```
print.safely <- function(x, ...) {  
  if (!is.null(x$error)) {  
    cat_line("<safely: error>")  
    cat_line("Error: ", x$error$message)  
  } else {  
    cat_line("<safely: ok>")  
    print(x$result)  
  }  
}
```

```
invisible(x)  Called primarily for side-effects  
}
```

How do we test printing code?

```
expect_output(  
  new_safely(result = 1:10),  
  "<safely: ok>"  
)
```

How do we test printing code?

```
expect_output(  
  print(new_safely(result = 1:10)),  
  "<safely: ok>"  
)
```


But this is tedious & error prone

```
# It's hard to define precisely what the output
# should be (but we know it when we see it)

# So instead we can use a regression test.
# This is a weaker guarantee than a unit test:
# we'll just get alerted when it changes

expect_known_output(
    new_safely(result = 1:10),
    test_path("safely-ok.txt"),
    print = TRUE
)
```

A little colour can be transformative

```
print.safely <- function(x, ...) {  
  if (is.null(x$result)) {  
    cat_line("<safely: ", crayon::bold(crayon::red("error")), ">")  
    cat_line(crayon::red("Error: "), x$error$message)  
  } else {  
    cat_line("<safely: ", crayon::green("ok"), ">")  
    print(x$result)  
  }  
  
  invisible(x)  
}
```

New generic

Change working directory/project to:

[bizarro]

Goal: create a bizarro function

```
bizarro("abc")
```

```
#> [1] "cba"
```

```
bizarro(1)
```

```
#> [1] -1
```

```
bizarro(c(TRUE, FALSE))
```

```
#> [1] FALSE TRUE
```

We could eliminate using if + else

```
str_reverse <- function(x) {  
  purrr::map_chr(stringr::str_split(x, ""),  
    ~ stringr::str_flatten(rev(.x))  
  )  
}
```

```
bizarro <- function(x) {  
  if (is.character(x)) {  
    str_reverse(x)  
  } else if (is.numeric(x)) {  
    -x  
  } else if (is.logical(x)) {  
    !x  
  } else {  
    stop(  
      "Don't know how to make bizzaro <", class(x)[[1]], ">",  
      call. = FALSE)  
    }  
}
```


But instead we'll create a new S3 generic

Magically passes all
arguments to correct method

```
bizarro <- function(x) {  
  UseMethod("bizarro")  
}
```

}
method = generic.class

```
bizarro.character <- function(x) {  
  str_reverse(x)  
}
```

```
bizarro("abc")
```

```
#> [1] cba
```

Your turn

Implement numeric and logical methods

Implement a data frame method that bizzarros the column names, as well as each column.

(i.e. get tests parsing)

```
bizarro.integer <- function(x) {  
  -x  
}
```

```
bizarro.logical <- function(x) {  
  !x  
}
```

```
bizarro.data.frame <- function(x) {  
  names(x) <- bizarro(names(x))  
  x[] <- purrr::map(x, bizarro)  
  x  
}
```

What happens when a method isn't available?

```
bizarro(factor(letters))
```

```
#> Error in UseMethod("bizarro") :
```

```
#> no applicable method for 'bizarro'
```

```
#> applied to an object of class "factor"
```

```
# How can we do better?
```

```
# We need to provide a catch-all default method
```

```
bizarro.default <- function(x) {  
  stop(  
    "Don't know how to make bizzaro <",  
    class(x)[[1]], ">",  
    call. = FALSE  
  )  
}
```

```
bizarro(factor(letters))  
#> Error: Don't know how to make  
#> bizzaro <factor>
```

Your turn

What should `bizzaro(factor("abc"))` return?

Decide, encode your decisions in tests, then implement `bizarro.factor()`.

Learning more

Advanced R (2nd ed) has four chapters

S3: <https://adv-r.hadley.nz/s3.html>

S4: <https://adv-r.hadley.nz/s4.html>

R6: <https://adv-r.hadley.nz/r6.html>

Trade-offs: <https://adv-r.hadley.nz/oo-tradeoffs.html>

This work is licensed under the
Creative Commons Attribution-Noncommercial 3.0
United States License.

To view a copy of this license, visit
<http://creativecommons.org/licenses/by-nc/3.0/us/>