# White noise sensor calibration processing results

Processed by dbcalbrt:glenn:swarm at 2008302:00:17:12.811

| Channel: | Time: | Sequence: | |
|---|---|---|---|
| **PS_PS01_BHE** | **2008299:21:40:12.000** | **PS_PS01-2008299:21:40:12** | |
| Dlmodel: | Dlserial: | Snmodel: | Snserial: |
| **q330** | **0100000B6970C263** | **-** | **-** |
| Ref Channel: | Ref Time: | Ref Sequence: | |
| **PS_PS01_BHE** | **2008299:16:40:12.000** | **PS_PS01-2008299:16:40:12** | |
| Ref Dlmodel: | Ref Dlserial: | Ref Snmodel: | Ref Snserial: |
| **q330** | **0100000B6970C263** | **-** | **-** |

| Cal mode: | Cal Waveform: | Cal Duration: | Samplerate: | Cal Amplitude: |
|---|---|---|---|---|
| **cmp** | **white** | **1:00 hours** | **50** | **0.625 V** |
| Cal processing: | Cal Settle Time: | Cal Trailer Time: | | |
| **ratio** | **10:00 minutes** | **10:00 minutes** | | |

| Amp Ratio: | Norm Freq: |
|---|---|
| **0.259450** | **1.000 Hz** |

Processing Parameters:

| | |
|---|---|
| {bands}[0]{fmax} = 0.02 | {bands}[2]{nwindows} = 0 |
| {bands}[0]{fmin} = 0.000001 | {bands}[2]{overlap_percent} = 50.0 |
| {bands}[0]{nwindows} = 1 | {bands}[2]{taper_percent} = 50.0 |
| {bands}[0]{overlap_percent} = 0.0 | {bands}[3]{fmax} = 200.0 |
| {bands}[0]{taper_percent} = 0.0 | {bands}[3]{fmin} = 1.00 |
| {bands}[1]{fmax} = 1.0 | {bands}[3]{nwindows} = 0 |
| {bands}[1]{fmin} = 0.0025 | {bands}[3]{overlap_percent} = 50.0 |
| {bands}[1]{nwindows} = 0 | {bands}[3]{taper_percent} = 50.0 |
| {bands}[1]{overlap_percent} = 50.0 | {tlag} = 1000.0 |
| {bands}[1]{taper_percent} = 25.0 | {tlead} = 30.0 |
| {bands}[2]{fmax} = 10.0 | |
| {bands}[2]{fmin} = 0.05 | |