White noise sensor calibration processing results

Processed by dbcalbrt:glenn:swarm at 2008302:00:17:20.786

Channel:	Time:	Sequence:	
PS_PS01_BHZ	**2008299:21:40:12.000**	**PS_PS01-2008299:21:40:12**	
Dlmodel:	Dlserial:	Snmodel:	Snserial:
q330	**0100000B6970C263**	**-**	**-**
Ref Channel:	Ref Time:	Ref Sequence:	
PS_PS01_BHZ	**2008299:16:40:12.000**	**PS_PS01-2008299:16:40:12**	
Ref Dlmodel:	Ref Dlserial:	Ref Snmodel:	Ref Snserial:
q330	**0100000B6970C263**	**-**	**-**

Cal mode:	Cal Waveform:	Cal Duration:	Samplerate:	Cal Amplitude:
cmp	**white**	**1:00 hours**	**50**	**0.625 V**
Cal processing:	Cal Settle Time:	Cal Trailer Time:		
ratio	**10:00 minutes**	**10:00 minutes**		

Amp Ratio:	Norm Freq:
0.158260	**1.000 Hz**

Processing Parameters:

{bands}[0]{fmax} = 0.02	{bands}[2]{nwindows} = 0
{bands}[0]{fmin} = 0.000001	{bands}[2]{overlap_percent} = 50.0
{bands}[0]{nwindows} = 1	{bands}[2]{taper_percent} = 50.0
{bands}[0]{overlap_percent} = 0.0	{bands}[3]{fmax} = 200.0
{bands}[0]{taper_percent} = 0.0	{bands}[3]{fmin} = 1.00
{bands}[1]{fmax} = 1.0	{bands}[3]{nwindows} = 0
{bands}[1]{fmin} = 0.0025	{bands}[3]{overlap_percent} = 50.0
{bands}[1]{nwindows} = 0	{bands}[3]{taper_percent} = 50.0
{bands}[1]{overlap_percent} = 50.0	{tlag} = 1000.0
{bands}[1]{taper_percent} = 25.0	{tlead} = 30.0
{bands}[2]{fmax} = 10.0	
{bands}[2]{fmin} = 0.05	