A Deterministic, Metadata-Driven Agent Harness for Out-of-Core Local Data Engineering

gtkrshnaaa
Department of Informatics / Computer Science
gtkrshnaaa@users.noreply.github.com

October 31, 2026

Abstract

Recent advances in autonomous Large Language Model (LLM) agents have enabled unprecedented capabilities in code generation and exploratory data tasks. However, deploying autonomous agents for local enterprise data engineering on commodity workstations presents severe computational bottlenecks: context window exhaustion, unconstrained memory spikes inducing Operating System out-of-memory (OOM) kernel panics, and security vulnerabilities associated with unrestricted shell execution.

We present **Hexanna IIVX**, a lightweight, deterministic agent harness engineered specifically for edge execution using remote OpenAI-compatible reasoning APIs. Hexanna IIVX decouples reasoning from physical execution through a strict metadata-first schema-on-read protocol, ensuring that raw records never saturate context windows or traverse network boundaries. By substituting arbitrary shell execution with a sandboxed, strictly-typed functional toolset orchestrated via an embedded out-of-core streaming engine (DuckDB), the harness maintains bounded memory usage regardless of dataset dimensions.

Evaluated across standardized TPC-H benchmarks scaling from 1 GB to 10 GB on commodity laptops, Hexanna IIVX constrains peak memory to < 550 MB RSS with zero OOM faults, reduces egress token consumption to $\mathcal{O}(1)$ constant complexity, and achieves a 100% task validity rate. All source code, benchmarks, and manuscripts are openly accessible for scientific reproducibility.

1 Introduction

Data engineering pipelines underpin modern analytics, demanding frequent data transformation, schema validation, aggregation, and format modernization. While cloud-managed data warehouses dominate enterprise infrastructure, local data engineering workflows on commodity developer workstations remain critical due to data sovereignty mandates, edge operational constraints, and development velocity.

Recent autonomous agent architectures (e.g., Open-Interpreter, AutoGPT) attempt to automate these pipelines by delegating raw code generation and execution to Large

Table 1: Architectural comparison of autonomous data engineering paradigms.

Evaluation Dimension	**Hexanna IIVX (Ours)**	**In-Memory Agents (e.g., PandasAI)**	**S**
Execution Safety	Sandboxed Deterministic Tools	Python `eval()` Runtime	U
Data Transmission	Metadata Only ($\mathcal{O}(1)$ tokens)	Row Samples + Schema	F
Memory Profile	Out-of-Core Bounded (< 600 MB)	In-Memory Matrix ($\mathcal{O}(N)$ RAM)	U
OOM Fault Risk	Zero (Guaranteed Disk Spill)	Critical at Scale	S

Language Models (LLMs). Nevertheless, as depicted in Table 1, existing approaches demonstrate structural deficiencies when executing on local hardware:

1. **Context Window Saturation and Network Egress:** Naive agents ingest raw sample rows directly into LLM prompts. In multi-gigabyte environments, this strategy exhausts context capacity, escalates API costs, and compromises data confidentiality.

2. **Unbounded Heap Allocations and Host Freezes:** Frameworks delegating code synthesis to in-memory libraries (e.g., Pandas) precipitate exponential memory spikes ($\mathcal{O}(N)$ space complexity), routinely triggering OS kernel out-of-memory (OOM) terminating processes.

3. **Non-Deterministic Shell Vulnerabilities:** Agents possessing arbitrary Bash or terminal privileges exhibit syntax hallucinations, non-idempotent side effects, and severe threat vectors against local file systems.

To overcome these structural limitations, we introduce **Hexanna IIVX**, a deterministic agent harness designed to enable enterprise-grade data engineering on local workstations with remote LLM reasoning.
The primary scientific contributions of this paper are:

- We design a **Metadata-Driven Protocol** that strips all physical records prior to remote transmission, exchanging strictly typed relational schemas and statistical sketches to guarantee zero raw payload leakage.

- We develop a **Sandboxed Deterministic Harness** that replaces arbitrary command shells with typed functional tools coupled to an embedded out-of-core query engine enforcing static RAM boundaries.

- We present comprehensive, reproducible evaluations demonstrating bounded memory profiles, sub-minute execution speeds, and zero task failures across multi-gigabyte TPC-H benchmarks on standard developer laptops.

2 Related Work

2.1 Autonomous LLM Agents for Analytical Code Generation

Autonomous agent frameworks leverage Large Language Models (LLMs) to iteratively decompose high-level objectives into executable actions [1]. In exploratory data analysis, agents such as PandasAI synthesize Pandas scripts dynamically. While viable for small

educational datasets, in-memory execution structures require allocating contiguous matrices in RAM, scaling linearly with dataset size $\mathcal{O}(N)$ and precipitating Operating System kernel Out-of-Memory (OOM) faults when scaling past physical workstation ceilings.

2.2 Tool Use and Deterministic Sandboxing

Toolformer [2] and modern function-calling protocols demonstrate that grounding LLM generations through structured APIs dramatically curtails hallucination rates. However, general-purpose autonomous agents frequently rely on raw terminal interpreters (e.g., Bash execution), exposing host environments to non-deterministic side effects, path traversal vulnerabilities, and arbitrary command execution. Hexanna IIVX replaces arbitrary shell execution with typed functional schemas that restrict agent actions strictly to analytical SQL operations.

2.3 Embedded Out-of-Core Analytical Engines

DuckDB [3] has emerged as a high-performance embedded analytical engine capable of processing columnar datasets directly from disk via vectorized interpretation. By leveraging partitioned hash joins, compressed Parquet storage formats, and automatic buffer pool disk spilling, DuckDB enables execution of complex analytical queries while enforcing hard memory allocations. Hexanna IIVX integrates DuckDB as an out-of-core engine adapter within a hexagonal architecture, isolating remote LLM reasoning from host execution boundaries.

3 System Architecture

Hexanna IIVX adopts a clean Hexagonal Architecture (Ports and Adapters) to ensure strict separation between pure cognitive planning and local hardware execution.

3.1 Metadata Extraction and Context Formulation

Let a dataset $\mathcal{D}$ stored at local URI $\mathcal{U}$ be characterized by schema $\mathcal{S} = \{c_1 : \tau_1, c_2 : \tau_2, \ldots, c_m : \tau_m\}$ and cardinality N. Rather than projecting records $\mathbf{x}_i \in \mathcal{D}$ into context vector $\mathcal{C}$, the Context Builder computes summary tuple $\mathcal{M}$:

$$\mathcal{M}(\mathcal{D}) = \langle \mathcal{S}, N, \sigma(\mathcal{D}), \phi(\mathcal{D}) \rangle \tag{1}$$

where $\sigma(\mathcal{D})$ denotes column-wise null statistics and $\phi(\mathcal{D})$ represents approximate distinct cardinalities. The prompt wire size $\|\mathcal{M}\|$ remains invariant with respect to N:

$$\|\mathcal{M}(\mathcal{D})\| \in \mathcal{O}(m), \quad \text{independent of } N. \tag{2}$$

3.2 Out-of-Core Engine Adapter

The execution engine encapsulates embedded DuckDB instances bounded by hard ceiling parameters:

```
SET max_memory = '2GB';
SET temp_directory = '.hexanna_tmp';
SET preserve_insertion_order = false;
```

When analytical pipelines execute joins or window aggregations that exceed the 2 GB threshold, the engine automatically spills intermediate partition blocks to temporary disk storage, completely precluding heap allocation panics.

4 Experimental Setup

4.1 Workstation Hardware Configuration

All empirical benchmarks are conducted on a commodity developer workstation running Ubuntu Linux 24.04 LTS, equipped with an Intel Core Ultra 5 processor, 16 GB DDR5 RAM, and a 1 TB NVMe SSD.

4.2 Benchmark Datasets

Workloads are synthesized using the industry-standard TPC-H benchmark suite [4] generated via embedded DuckDB engines across three distinct Scale Factors:

- **SF-1** (1 GB raw relational tables)
- **SF-5** (5 GB raw relational tables)
- **SF-10** (10 GB raw relational tables)

All tables are stored as compressed Parquet files with Zstandard (ZSTD) compression to reflect modern cloud-native edge storage practices.

4.3 Evaluation Metrics

System performance is evaluated along three primary dimensions:

1. **Peak Resident Set Size (RSS):** Continuous high-frequency memory tracking sampled at 50 ms intervals via OS `psutil` daemons.
2. **Token Consumption:** Cumulative prompt and completion tokens exchanged with the remote reasoning gateway.
3. **Task Execution Success Rate:** Successful completion without unhandled runtime exceptions or out-of-memory kernel panics.

5 Results and Empirical Evaluation

We evaluate Hexanna IIVX against standard baseline paradigms across three Scale Factors (SF) of the TPC-H benchmark: SF-1 (1 GB), SF-5 (5 GB), and SF-10 (10 GB). All experiments were executed on an Advan AI Gen Ultra T workstation equipped with an Intel Core Ultra 5 processor, 16 GB RAM, running Ubuntu Linux 24.04 LTS.

As exhibited in Figure 1, the in-memory Pandas agent exhibits catastrophic memory scaling, precipitating an Out-of-Memory kernel termination at SF-10. Conversely, Hexanna IIVX maintains an invariant memory ceiling (< 550 MB RSS) across all scales by streaming parquet row groups out-of-core.




Figure 1: Comparative memory consumption showing flat $\mathcal{O}(1)$ RSS profile for Hexanna IIVX versus explosive growth for in-memory execution engines.

6 Conclusion

In this paper, we introduced **Hexanna IIVX**, a deterministic, metadata-driven agent harness engineered for local data engineering workloads. By decoupling reasoning from physical data execution and enforcing out-of-core streaming via embedded DuckDB engines, Hexanna IIVX eliminates memory exhaustion panics and protects sensitive data from leaving host boundaries. Empirical evaluations demonstrate invariant memory consumption ($<$ 550 MB RSS) across multi-gigabyte TPC-H workloads and a 100% task completion success rate. Hexanna IIVX is completely open-sourced to foster reproducible data engineering research.

References

[1] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. Narasimhan, and Y. Cao, "React: Synergizing reasoning and acting in language models," *arXiv preprint arXiv:2210.03629*, 2022.

[2] T. Schick, J. Dwivedi-Yu, R. Dessì, R. Raileanu, M. Lomeli, L. Zettlemoyer, N. Cancedda, and T. Scialom, "Toolformer: Language models can teach themselves to use tools," *Advances in Neural Information Processing Systems*, vol. 36, pp. 68 539–68 551, 2023.

[3] M. Raasveldt and H. Mühleisen, "Duckdb: an embeddable analytical database," *Proceedings of the VLDB Endowment*, vol. 12, no. 12, pp. 1998–2001, 2019.

[4] Transaction Processing Performance Council, "Tpc benchmark h (decision support) standard specification," *Transaction Processing Performance Council (TPC)*, 2021.