

# Big Data Computing

Master's Degree in Computer Science  
2025-2026



SAPIENZA  
UNIVERSITÀ DI ROMA

Gabriele Tolomei

Department of Computer Science

Sapienza Università di Roma

[tolomei@di.uniroma1.it](mailto:tolomei@di.uniroma1.it)

# Information Overload

- With the explosion of content and services available on the Web, consumers are inundated with choices

# Information Overload

- With the explosion of content and services available on the Web, consumers are inundated with choices
- This phenomenon is usually referred to as **information overload**

# Information Overload

- With the explosion of content and services available on the Web, consumers are inundated with choices
- This phenomenon is usually referred to as **information overload**
- To actually take advantage of such a huge pile of information we need techniques that narrow down it to **human-manageable** figures:

# Information Overload

- With the explosion of content and services available on the Web, consumers are inundated with choices
- This phenomenon is usually referred to as **information overload**
- To actually take advantage of such a huge pile of information we need techniques that narrow down it to **human-manageable** figures:
  - **Searching/Filtering**

# Information Overload


- With the explosion of content and services available on the Web, consumers are inundated with choices
- This phenomenon is usually referred to as **information overload**
- To actually take advantage of such a huge pile of information we need techniques that narrow down it to **human-manageable** figures:
  - Searching/Filtering
  - Recommending

# Why Do We Need Recommendation?

We are constantly moving from scarcity to abundance

# Why Do We Need Recommendation?



We are constantly moving from scarcity to abundance







# Why Do We Need Recommendation?

We are constantly moving from scarcity to abundance



# Why Do We Need Recommendation?


We are constantly moving from scarcity to abundance



The number of relevant "items" of interest is huge

# Why Do We Need Recommendation?

We are constantly moving from scarcity to abundance



The number of relevant "items" of interest is huge

How could we even think of **exhaustively explore** all of them?

# Why Do We Need Recommendation?

Compared to physical stores, online catalogs of product/services are almost unlimited

# Why Do We Need Recommendation?

Compared to physical stores, online catalogs of product/services are almost unlimited

Matching consumers with the most appropriate products/services is key to enhancing **user satisfaction** and loyalty

# Why Do We Need Recommendation?

Compared to physical stores, online catalogs of product/services are almost unlimited

Matching consumers with the most appropriate products/services is key to enhancing **user satisfaction** and loyalty

More choices need **better filters!**

# Why Do We Need Recommendation?

Compared to physical stores, online catalogs of product/services are almost unlimited


Matching consumers with the most appropriate products/services is key to enhancing **user satisfaction** and loyalty

More choices need **better filters!**




**Recommender Systems**

# The Economics of Abundance: The Long Tail






# The Economics of Abundance: The Long Tail




Items can be anything


# The Economics of Abundance: The Long Tail



# The Economics of Abundance: The Long Tail



# The Economics of Abundance: The Long Tail



# Recommender Systems: Formalism

$\mathcal{U} = \{u_1, \dots, u_m\}$  Set of users

# Recommender Systems: Formalism

$\mathcal{U} = \{u_1, \dots, u_m\}$  Set of users

$\mathcal{I} = \{i_1, \dots, i_n\}$  Set of items

# Recommender Systems: Formalism

$\mathcal{U} = \{u_1, \dots, u_m\}$  Set of users

$\mathcal{I} = \{i_1, \dots, i_n\}$  Set of items

$r : \mathcal{U} \times \mathcal{I} \mapsto \mathcal{R}$  utility function (user-item matrix)

# Recommender Systems: Formalism

$\mathcal{U} = \{u_1, \dots, u_m\}$  Set of **users**

$\mathcal{I} = \{i_1, \dots, i_n\}$  Set of **items**

$r : \mathcal{U} \times \mathcal{I} \mapsto \mathcal{R}$  **utility function** (**user-item matrix**)

$\mathcal{R} \subseteq \mathbb{R}$  Set of **ratings** (totally ordered)



# Recommender Systems: Formalism

$\mathcal{U} = \{u_1, \dots, u_m\}$  Set of **users**

$\mathcal{I} = \{i_1, \dots, i_n\}$  Set of **items**


$r : \mathcal{U} \times \mathcal{I} \mapsto \mathcal{R}$  **utility function** (**user-item matrix**)

$\mathcal{R} \subseteq \mathbb{R}$  Set of **ratings** (totally ordered)

$\mathcal{R} = \{0, 1, \dots, v - 1\}$  Discrete ratings (e.g., 0-5 stars)












$\mathcal{R} = [0, 1]$  Continuous ratings

# The Utility Function (User-Item Matrix)

USERS		Alice
		Bob
		Carl
	...	
		Zoe

11/27/2025

# The Utility Function (User-Item Matrix)

		MOVIES							
									
USERS		Alice							
		Bob							
		Carl							
	...								
		Zoe							

# The Utility Function (User-Item Matrix)

		MOVIES							
									
USERS	 Alice	2		5	4	5	4		4
	 Bob	4					3		3
	 Carl	5	5	3	4	5	4		5
	...	...	...	...	...	...	...	...	...
	 Zoe		1	3				5	4

# The Utility Function (User-Item Matrix)

3 key problems for a recommender system

# The Utility Function (User-Item Matrix)

3 key problems for a recommender system

Data  
Collection  
Gathering known  
ratings to populate  
the utility matrix

# The Utility Function (User-Item Matrix)

3 key problems for a recommender system

## Data Collection

Gathering known  
ratings to populate  
the utility matrix

## Rating Prediction

Extrapolate unknown  
ratings from the  
known ones

# The Utility Function (User-Item Matrix)

3 key problems for a recommender system

## Data Collection

Gathering known ratings to populate the utility matrix

## Rating Prediction

Extrapolate unknown ratings from the known ones

## Recommendation Evaluation

Measure the performance of recommender methods



# Data Collection

Data

Collection

Gathering known  
ratings to populate  
the utility matrix

# Data Collection

## Data

## Collection

Gathering known ratings to populate the utility matrix

## Explicit

Ask people to rate items

Doesn't scale: only few users leave ratings

# Data Collection

Data  
Collection  
Gathering known  
ratings to populate  
the utility matrix

## Explicit

Ask people to rate items

Doesn't scale: only few users  
leave ratings

## Implicit

Learn ratings from user actions

Click/purchases implies positive feedback  
What about negative ones?

# Rating Prediction

## Rating Prediction

Extrapolate unknown  
ratings from the  
known ones

# Rating Prediction

## Rating Prediction

Extrapolate unknown  
ratings from the  
known ones

The utility matrix  $R$  is sparse!

Most people have not rated most items

# Rating Prediction

## Rating Prediction

Extrapolate unknown  
ratings from the  
known ones

The utility matrix  $R$  is sparse!

Most people have not rated most items

Cold Start

New users/items have no history

# Recommendation Evaluation

## Recommendation Evaluation

Measure the  
performance of  
recommender  
methods

# Recommendation Evaluation

## Recommendation Evaluation

Measure the  
performance of  
recommender  
methods

RMSE

Serendipity

Personalization

Mean Average Precision/Recall at K  
(MAP@K/MAR@K)



# Recommendation Strategies

3 approaches to recommender systems

# Recommendation Strategies

3 approaches to recommender systems

Content-based  
filtering

# Recommendation Strategies


3 approaches to recommender systems

Content-based  
filtering

Collaborative  
filtering


# Recommendation Strategies

3 approaches to recommender systems




# Recommendation Strategies

3 approaches to recommender systems




# Recommendation Strategies

3 approaches to recommender systems



# Recommendation Strategies

3 approaches to recommender systems



# CONTENT-BASED FILTERING



# Content-based Filtering

## Idea

Recommend items to user  $u$  similar to previous items rated highly by  $u$

# Content-based Filtering

## Idea

Recommend items to user  $u$  similar to previous items rated highly by  $u$

Core concept: Item/User Profiles

# Content-based Filtering

## Idea

Recommend items to user  $u$  similar to previous items rated highly by  $u$

Core concept: Item/User Profiles

## Steps

1. Build *item profiles* (i.e., a description of items using metadata)

# Content-based Filtering

## Idea

Recommend items to user  $u$  similar to previous items rated highly by  $u$

Core concept: Item/User Profiles

## Steps

1. Build **item profiles** (i.e., a description of items using metadata)
2. Based on the item profiles, build **user profiles**: what the user likes

# Content-based Filtering

## Idea

Recommend items to user  $u$  similar to previous items rated highly by  $u$

Core concept: Item/User Profiles

## Steps

1. Build **item profiles** (i.e., a description of items using metadata)
2. Based on the item profiles, build **user profiles**: what the user likes
3. Match the user profile with the item catalog

# Building Item Profiles

## Goal

For each item  $i$  create a **profile**, i.e., a set of features

# Building Item Profiles

## Goal

For each item  $i$  create a **profile**, i.e., a set of features

### Movies

- Author
- Title
- Director
- Genre
- ...

### Images/Videos

- Width
- Height
- Framerate
- Tags
- ...

...

### People

- Age
- Sex
- Job
- Friends
- ...

# Building Item Profiles

## Goal

For each item  $i$  create a **profile**, i.e., a set of features

### Movies

- Author
- Title
- Director
- Genre
- ...

### Images/Videos

- Width
- Height
- Framerate
- Tags
- ...

...

### People

- Age
- Sex
- Job
- Friends
- ...

Think of each profile as a vector of numerical/categorical features



# Item Profile: Example

- Suppose we want to build a news recommender system

# Item Profile: Example

- Suppose we want to build a news recommender system
- Items are news article (i.e., text documents)


# Item Profile: Example

- Suppose we want to build a news recommender system
- Items are news article (i.e., text documents)
- Possible profile of the  $j$ -th item:



# Item Profile: Example

- Suppose we want to build a news recommender system
- Items are news article (i.e., text documents)
- Possible profile of the  $j$ -th item:



# Building User Profiles

## Goal

For each user  $u$  create a **profile**, from the profiles of the items she rated

# Building User Profiles

## Goal

For each user  $u$  create a **profile**, from the profiles of the items she rated

$\mathcal{I}_u \subseteq \mathcal{I}$  The set of items rated by user  $u$

# Building User Profiles

## Goal

For each user  $u$  create a **profile**, from the profiles of the items she rated

$\mathcal{I}_u \subseteq \mathcal{I}$  The set of items rated by user  $u$

$\mathbf{i}_j$  The vector profile of item  $j$

# Building User Profiles

## Goal

For each user  $u$  create a **profile**, from the profiles of the items she rated

$\mathcal{I}_u \subseteq \mathcal{I}$  The set of items rated by user  $u$

$\mathbf{i}_j$  The vector profile of item  $j$

The simplest solution to build the user profile is to take the average of item profiles rated

$$\mathbf{u}_i = \frac{1}{|\mathcal{I}_u|} \sum_{\mathbf{i}_j \in \mathcal{I}_u} \mathbf{i}_j$$



# Building User Profiles

## Goal

For each user  $u$  create a **profile**, from the profiles of the items she rated

$\mathcal{I}_u \subseteq \mathcal{I}$  The set of items rated by user  $u$

$\mathbf{i}_j$  The vector profile of item  $j$

The simplest solution to build the user profile is to take the average of item profiles rated

$$\mathbf{u}_i = \frac{1}{|\mathcal{I}_u|} \sum_{\mathbf{i}_j \in \mathcal{I}_u} \mathbf{i}_j$$

All the items are treated equally, independently of the rating

# Simple User Profile: Example

Items = Movies

# Simple User Profile: Example


Items = Movies

Movie Profile = List of Actors

# Simple User Profile: Example

Items = Movies


Movie Profile = List of Actors



# Simple User Profile: Example

Items = Movies

Movie Profile = List of Actors



Binary feature indicating if  $actor_i$  appears in movie<sub>j</sub>

# Simple User Profile: Example

Suppose user  $u$  has watched 5 movies, each movie represented by 2 actors

1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

# Simple User Profile: Example

Suppose user  $u$  has watched 5 movies, each movie represented by 2 actors

1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

2 movies feature actor 1

# Simple User Profile: Example

Suppose user u has watched 5 movies, each movie represented by 2 actors

1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

3 movies feature actor 2



# Simple User Profile: Example

Suppose user  $u$  has watched 5 movies, each movie represented by 2 actors

1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

User profile is the **mean** of item profiles

# Simple User Profile: Example

Suppose user u has watched 5 movies, each movie represented by 2 actors

1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

User profile is the **mean** of item profiles


$(1+1)/5$		0.4	
		actor <sub>1</sub>	actor <sub>2</sub>

# Simple User Profile: Example

Suppose user u has watched 5 movies, each movie represented by 2 actors

1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

User profile is the **mean** of item profiles



# Simple User Profile: Example With Ratings

Suppose user  $u$  has watched (and rated) 5 movies



Normalize ratings by subtracting user's mean rating before

# Simple User Profile: Example With Ratings

Suppose user u has watched (and rated) 5 movies

★	★	★		★		★	★	★	★	★	★	★	★	★
1	0	0	1	0	1	1	0	0	1	0	1			
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>			

Normalize ratings by subtracting user's mean rating before

$$\text{Avg. User Rating} = (3 + 1 + 2 + 5 + 4)/5 = 3$$

# Simple User Profile: Example With Ratings

Suppose user u has watched (and rated) 5 movies

3-3 = 0		1-3 = -2		2-3 = -1		5-3 = 2		4-3 = 1	
1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

Normalize ratings by subtracting user's mean rating before


$$\text{Avg. User Rating} = (3 + 1 + 2 + 5 + 4)/5 = 3$$

# Simple User Profile: Example With Ratings

Suppose user u has watched (and rated) 5 movies

	0		-2		-1		2		1
1	0	0	1	0	1	1	0	0	1
actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>	actor <sub>1</sub>	actor <sub>2</sub>

Normalize ratings by subtracting user's mean rating before



# Building Predictions (from Item/User Profiles)

		MOVIES							
									
USERS	 Alice	2		5	4	5	4		4
	 Bob	4	?	?	?	?	3	?	3
	 Carl	5	5	3	4	5	4		5
	...	...	...	...	...	...	...	...	...
	 Zoe		1	3				5	4



# Building Predictions (from Item/User Profiles)

How to fill the  
"?"?

		MOVIES							
									
USERS	 Alice	2		5	4	5	4		4
	 Bob	4	?	?	?	?	3	?	3
	 Carl	5	5	3	4	5	4		5
	...	...	...	...	...	...	...	...	...
	 Zoe		1	3				5	4

# Building Predictions (from Item/User Profiles)

- Given user profile  $u$  we can **estimate** the missing entries of the utility matrix for  $u$  (i.e., the ratings  $u$  would give to unrated items)

# Building Predictions (from Item/User Profiles)

- Given user profile  $u$  we can **estimate** the missing entries of the utility matrix for  $u$  (i.e., the ratings  $u$  would give to unrated items)
- For each item unrated by  $u$ , compute the cosine similarity (or Pearson's correlation) between  $u$  and the corresponding item profile vectors

# Building Predictions (from Item/User Profiles)

- Given user profile  $u$  we can **estimate** the missing entries of the utility matrix for  $u$  (i.e., the ratings  $u$  would give to unrated items)
- For each item unrated by  $u$ , compute the cosine similarity (or Pearson's correlation) between  $u$  and the corresponding item profile vectors
- Finally, we pick the top- $k$  items with the **highest** similarity score, and we recommend those to  $u$

# Building Predictions (from Item/User Profiles)

$$A^0 = \emptyset$$

# Building Predictions (from Item/User Profiles)

$$A^0 = \emptyset$$

$$A^1 = \operatorname{argmax}_i \{\operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0\}$$

# Building Predictions (from Item/User Profiles)

$$A^0 = \emptyset$$

$$A^1 = \operatorname{argmax}_i \{\operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0\}$$

$$A^2 = \operatorname{argmax}_i \{\operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0 - A^1\}$$

# Building Predictions (from Item/User Profiles)

$$A^0 = \emptyset$$

$$A^1 = \operatorname{argmax}_i \{\operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0\}$$

$$A^2 = \operatorname{argmax}_i \{\operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0 - A^1\}$$

...

$$A^k = \operatorname{argmax}_i \{\operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0 - A^1 - \dots - A^{k-1}\}$$



# Building Predictions (from Item/User Profiles)

$$A^0 = \emptyset$$

$$A^1 = \operatorname{argmax}_i \{ \operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0 \}$$

$$A^2 = \operatorname{argmax}_i \{ \operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0 - A^1 \}$$

...

$$A^k = \operatorname{argmax}_i \{ \operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - A^0 - A^1 - \dots - A^{k-1} \}$$

$$R_{u,k} = \bigcup_{j=1}^k A^j = \bigcup_{j=1}^k \operatorname{argmax}_i \left\{ \operatorname{sim}(\mathbf{u}, \mathbf{i}) : i \in \mathcal{I} - \mathcal{I}_u - \left\{ \bigcup_{l=0}^{j-1} A^l \right\} \right\}$$

# Content-based Filtering: PROs

- No need for data on other users: only the user and the items rated by her/him are needed

# Content-based Filtering: PROs

- No need for data on other users: only the user and the items rated by her/him are needed
- No item cold start problem: when the item is new or unpopular (i.e., no one has rated yet) it can still be recommended to users with highest profile similarity

# Content-based Filtering: PROs

- No need for data on other users: only the user and the items rated by her/him are needed
- No item cold start problem: when the item is new or unpopular (i.e., no one has rated yet) it can still be recommended to users with highest profile similarity
- Explainable recommendations using content features that caused an item to be recommended

# Content-based Filtering: CONs

- Finding the appropriate item features is hard

# Content-based Filtering: CONs

- Finding the appropriate item features is hard
- Overspecialization: never recommends items outside user's profile

# Content-based Filtering: CONs

- Finding the appropriate item features is hard
- Overspecialization: never recommends items outside user's profile
- Unable to exploit quality judgments of other users

## Content-based Filtering: CONs

- Finding the appropriate item features is hard
- Overspecialization: never recommends items outside user's profile
- Unable to exploit quality judgments of other users
- Cold start problem for new users: If the user hasn't rated any items, then there's no user profile



# Content-based Filtering: CONs

- Finding the appropriate item features is hard
- Overspecialization: never recommends items outside user's profile
- Unable to exploit quality judgments of other users
- Cold start problem for new users: If the user hasn't rated any items, then there's no user profile
- May need to create average profiles and gradually improve them overtime

# Take-Home Message of Today

- Recommender systems as tools to handle information overload

# Take-Home Message of Today

- Recommender systems as tools to handle information overload
- The main goal of recommender systems is to select items that are likely of interest to users

# Take-Home Message of Today

- Recommender systems as tools to handle information overload
- The main goal of recommender systems is to select items that are likely of interest to users
- They make use of either explicit (e.g., ratings) or implicit (e.g., clicks) feedback to build a user-item utility matrix

# Take-Home Message of Today

- Recommender systems as tools to handle information overload
- The main goal of recommender systems is to select items that are likely of interest to users
- They make use of either explicit (e.g., ratings) or implicit (e.g., clicks) feedback to build a user-item utility matrix
- Content-based recommender systems make use of item and user profiles (built in the item space) to come up with top- $k$  suggestions