

Big Data Computing

Master's Degree in Computer Science
2025-2026



SAPIENZA
UNIVERSITÀ DI ROMA

Gabriele Tolomei

Department of Computer Science

Sapienza Università di Roma

tolomei@di.uniroma1.it

Goal: The "Importance" of a Node

- We want to find an effective way to measure the **trustworthiness** of a page within the Web graph

Goal: The "Importance" of a Node

- We want to find an effective way to measure the **trustworthiness** of a page within the Web graph
- More generally, we want to assign a score which indicates the **importance** of a node in a graph

Goal: The "Importance" of a Node

- We want to find an effective way to measure the **trustworthiness** of a page within the Web graph
- More generally, we want to assign a score which indicates the **importance** of a node in a graph
- Derive such a score from the structural properties of the graph only (i.e., via **link analysis**)

Goal: The "Importance" of a Node

- We want to find an effective way to measure the **trustworthiness** of a page within the Web graph
- More generally, we want to assign a score which indicates the **importance** of a node in a graph
- Derive such a score from the structural properties of the graph only (i.e., via **link analysis**)
- Exploit the fact that the Web is an example of a **scale-free network**

12/11/2025

Computing Node Importance

Several link analysis approaches to compute web page importance

PageRank

Hubs and Authorities
(HITS)

Personalized PageRank

Web Spam Detection

PageRank

One Slide PageRank

- A link analysis approach to the definition of web page importance

One Slide PageRank

- A link analysis approach to the definition of web page importance
- Introduced in 1998 by Sergey Brin and Larry Page*

*[The Anatomy of a Large-Scale Hypertextual Web Search Engine](#). In Computer Networks, vol. 30, n. 1-7, pp. 107-117, 1998.
12/11/2025

One Slide PageRank

- A link analysis approach to the definition of web page importance
- Introduced in 1998 by Sergey Brin and Larry Page*
- The core of Google search engine

*[The Anatomy of a Large-Scale Hypertextual Web Search Engine](#). In Computer Networks, vol. 30, n. 1-7, pp. 107-117, 1998.
12/11/2025

One Slide PageRank

- A link analysis approach to the definition of web page importance
- Introduced in 1998 by Sergey Brin and Larry Page^{*}
- The core of Google search engine
- Assigns a numerical score to each web page with the purpose of indicating its relative importance within the whole collection


^{*}[The Anatomy of a Large-Scale Hypertextual Web Search Engine](#). In Computer Networks, vol. 30, n. 1-7, pp. 107-117, 1998.
12/11/2025

PageRank's Intuition: Links as Votes

Based on 2 intuitions

PageRank's Intuition: Links as Votes

Based on 2 intuitions



The more incoming links a web page has the more important it is


PageRank's Intuition: Links as Votes

Based on 2 intuitions

The more incoming links a web page has the more important it is

Each link from a web page w to a web page v is interpreted as a

vote by w to v



PageRank's Intuition: Links as Votes


Based on 2 intuitions

The more incoming links a web page has the more important it is

Links (i.e., votes) from important web pages should count more!

Each link from a web page w to a web page v is interpreted as a

vote by w to v




PageRank's Intuition: Links as Votes

Based on 2 intuitions

The more incoming links a web page has the more important it is

Each link from a web page w to a web page v is interpreted as a

vote by w to v



Links (i.e., votes) from important web pages should count more!

Different web pages have different

in-degree (scale-free network)

www.stanford.edu has more than 23K in-links

www.uniroma1.it/~tolomei has one or two in-links!


PageRank's Intuition: Links as Votes

Based on 2 intuitions

The more incoming links a web page has the more important it is

Each link from a web page w to a web page v is interpreted as a

vote by w to v



Links (i.e., votes) from important web pages should count more!

Different web pages have different in-degree (scale-free network)


www.stanford.edu has more than 23K in-links

www.uniroma1.it/~tolomei has one or two in-links!


Recursive definition

PageRank Scores: Example

Circle size proportional to the node importance




PageRank Scores: Example



Circle size proportional to the node importance

B has a high score since many nodes point to it

PageRank Scores: Example




Circle size proportional to the node importance

B has a high score since many nodes point to it

C also has a high score even though it has only one incoming link but from an important node **B**

PageRank Scores: Example



Circle size proportional to the node importance

B has a high score since many nodes point to it

C also has a high score even though it has only one incoming link but from an important node **B**

Many other less important nodes

PageRank: Preliminaries


$G = (V, E)$ The Web Graph $|V| = N$ Number of Nodes (pages)

PageRank: Preliminaries

$G = (V, E)$ The Web Graph $|V| = N$ Number of Nodes (pages)

$O_v = \{w \in V : (v, w) \in E\}$ Set of pages linked by v

$|O_v| = o_v$ Out-degree of node v



PageRank: Preliminaries


$G = (V, E)$ The Web Graph $|V| = N$ Number of Nodes (pages)

$O_v = \{w \in V : (v, w) \in E\}$ Set of pages linked by v

$|O_v| = o_v$ Out-degree of node v

$I_v = \{w \in V : (w, v) \in E\}$ Set of pages linked to v

$|I_v| = i_v$ In-degree of node v



PageRank: First Simple Recursive Formulation

Each link's vote to a page v is proportional to the importance of the source page w , which the link comes from

PageRank: First Simple Recursive Formulation

Each link's vote to a page v is proportional to the importance of the source page w , which the link comes from

If a page w has importance r_w and out-degree o_w , each out-link will get an equal proportion of the importance, i.e., r_w/o_w


PageRank: First Simple Recursive Formulation

Each link's vote to a page v is proportional to the importance of the source page w , which the link comes from


If a page w has importance r_w and out-degree o_w , each out-link will get an equal proportion of the importance, i.e., r_w/o_w

Each page v 's importance can be computed just as the sum of votes of all its incoming links (i.e., in-degree)

PageRank: First Simple Recursive Formulation




PageRank: First Simple Recursive Formulation




What is r_v ?

PageRank: First Simple Recursive Formulation




Suppose **v** has only **2** in-links coming from **w** and **x**

PageRank: First Simple Recursive Formulation




We must
compute the
in-link's **vote**
from **w** and
from **x**

PageRank: First Simple Recursive Formulation




The importance of page **w** (r_w) is distributed across each of its **2** outgoing links

PageRank: First Simple Recursive Formulation




The importance of page x (r_x) is distributed across each of its 4 outgoing links

PageRank: First Simple Recursive Formulation



The importance of page **v** (r_v) is just the **sum** of its incoming links' votes


PageRank: First Simple Recursive Formulation



The importance of page **v** (r_v) is just the **sum** of its incoming links' votes

$$r_v = r_w/2 + r_x/4$$

PageRank: First Simple Recursive Formulation




The importance of page **v** (r_v) is just the **sum** of its incoming links' votes

$$r_v = r_w/2 + r_x/4$$

$$r_v = \sum_{u \in I_v} \frac{r_u}{o_u}$$

PageRank: First Simple Recursive Formulation



Similarly, page v uniformly distributes its importance r_v to its outgoing links


PageRank's Interpretations

2 main perspectives

PageRank's Interpretations

2 main perspectives


Linear Algebra



PageRank's Interpretations

2 main perspectives

Linear Algebra




Probabilistic



PageRank's Interpretations

2 main perspectives


Linear Algebra




Probabilistic




PageRank: The "Flow" Model




PageRank: The "Flow" Model



PageRank: The "Flow" Model




PageRank: The "Flow" Model




$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \end{cases}$$

PageRank: The "Flow" Model



$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

PageRank: The "Flow" Model



$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

"Flow" Equations

Solving the System of "Flow" Equations

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases} \quad \text{3 equations with 3 unknowns: } r_v, r_w, \text{ and } r_x$$

Solving the System of "Flow" Equations

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases} \quad \begin{array}{l} \text{3 equations with 3 unknowns: } r_v, r_w, \text{ and } r_x \\ \text{But the first 2 equations are} \\ \text{exactly the same if we substitute } r_x \end{array}$$

Solving the System of "Flow" Equations

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

3 equations with 3 unknowns: r_v , r_w , and r_x

But the first 2 equations are exactly the same if we substitute r_x



No unique solution!
Infinitely many apart from a constant
scale factor

Solving the System of "Flow" Equations

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \\ r_v + r_w + r_x = 1 \end{cases}$$

Additional constraint (equation)
enforces the uniqueness of the
solution

Solving the System of "Flow" Equations

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \\ r_v + r_w + r_x = 1 \end{cases}$$

Additional constraint (equation)
enforces the uniqueness of the
solution

$$r_v = r_w = \frac{2}{5} \quad r_x = \frac{1}{5}$$

Solving the System of "Flow" Equations

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \\ r_v + r_w + r_x = 1 \end{cases}$$

Additional constraint (equation)
enforces the uniqueness of the
solution

$$r_v = r_w = \frac{2}{5} \quad r_x = \frac{1}{5}$$

This may work for very small systems of
linear equations
(e.g., using Gaussian elimination)

Solving the System of "Flow" Equations

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \\ r_v + r_w + r_x = 1 \end{cases}$$

Additional constraint (equation) enforces the uniqueness of the solution

$$r_v = r_w = \frac{2}{5} \quad r_x = \frac{1}{5}$$

In the case of web pages we might have **100s of billions** of equations!



We need a new formulation

PageRank: The Matrix Formulation

Represent the Web graph of documents $G=(V, E)$ s.t. $|V|=N$
as a column stochastic matrix M of size $N \times N$

PageRank: The Matrix Formulation


Represent the Web graph of documents $G=(V, E)$ s.t. $|V|=N$
as a column stochastic matrix M of size $N \times N$



One of those O_w
links points to
page v


PageRank: The Matrix Formulation

Represent the Web graph of documents $G=(V, E)$ s.t. $|V|=N$
as a **column stochastic matrix** M of size $N \times N$




PageRank: The Matrix Formulation


Represent the Web graph of documents $G=(V, E)$ s.t. $|V|=N$
as a column stochastic matrix M of size $N \times N$



For any other page u
which w is not
pointing to $M[u, w] = 0$




PageRank: The Matrix Formulation




M is column stochastic because,
by design, each of its column
sums up to 1

PageRank: The Matrix Formulation




M is column stochastic because, by design, each of its column sums up to 1




The w -th column will contain $o_w \leq N$ non-zero entries, each evaluating to $1/o_w$

$$\sum_{v=1}^N m_{v,w} = o_w \times \frac{1}{o_w} = 1$$

PageRank: The Matrix Formulation



M is column stochastic because, by design, each of its column sums up to 1



Note:

We are implicitly assuming there exists at least one outgoing link from each node

A Formal View of the Matrix M

$$\mathbf{A}_{N \times N} \quad a_{v,w} = \begin{cases} 1 & \text{if } w \in O_v \\ 0 & \text{otherwise} \end{cases} \quad \text{Traditional adjacency matrix}$$

A Formal View of the Matrix \mathbf{M}

$$\mathbf{A}_{N \times N} \quad a_{v,w} = \begin{cases} 1 & \text{if } w \in O_v \\ 0 & \text{otherwise} \end{cases} \quad \text{Traditional adjacency matrix}$$

$$\mathbf{L}_{N \times N} \quad l_{v,w} = \begin{cases} o_v & \text{if } v = w \\ 0 & \text{otherwise} \end{cases} \quad \text{Diagonal matrix of out-degrees}$$

A Formal View of the Matrix \mathbf{M}

$$\mathbf{A}_{N \times N} \quad a_{v,w} = \begin{cases} 1 & \text{if } w \in O_v \\ 0 & \text{otherwise} \end{cases} \quad \text{Traditional adjacency matrix}$$

$$\mathbf{L}_{N \times N} \quad l_{v,w} = \begin{cases} o_v & \text{if } v = w \\ 0 & \text{otherwise} \end{cases} \quad \text{Diagonal matrix of out-degrees}$$

$$\mathbf{M}_{N \times N} \quad m_{v,w} = \begin{cases} \frac{1}{o_w} & \text{if } v \in O_w \\ 0 & \text{otherwise} \end{cases} \quad \text{Column stochastic matrix}$$


$\mathbf{M} = (\mathbf{L}^{-1} \mathbf{A})^T$

PageRank: The Matrix Formulation

\mathbf{r} $N \times 1$ rank vector with an entry for each page


PageRank: The Matrix Formulation

\mathbf{r} $N \times 1$ rank vector with an entry for each page

r_v  Rank score of page v

PageRank: The Matrix Formulation

\mathbf{r} $N \times 1$ rank vector with an entry for each page



r_v


Rank score of page v

$$\sum_{v=1}^N r_v = 1$$

All the rank scores
must sum up to 1

PageRank: The Matrix Formulation


\mathbf{r} $N \times 1$ rank vector with an entry for each page

r_v  Rank score of page v $\sum_{v=1}^N r_v = 1$ All the rank scores must sum up to 1


$$r_v = \sum_{w \in I_v} \frac{r_w}{o_w} \quad \Longrightarrow \quad \mathbf{r} = \mathbf{M}\mathbf{r}$$

Flow equations in matrix form

PageRank: The Matrix Formulation




PageRank: The Matrix Formulation



$$r_v = \mathbf{m}_v^T \cdot \mathbf{r} = \sum_{w=1}^N m_{v,w} \times r_w = \sum_{w=1}^N \frac{1}{o_w} \times r_w = \sum_{w=1}^N \frac{r_w}{o_w} = \sum_{w \in I_v} \frac{r_w}{o_w}$$

12/11/2025 70

PageRank: The Matrix Formulation



PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

Doesn't it look familiar?

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

Doesn't it look familiar?

$$\mathbf{A}\mathbf{x} = \lambda\mathbf{x}$$

\mathbf{x} is an eigenvector

λ is an
eigenvalue

PageRank: The Eigenvector Formulation

$$\mathbf{Mr} = \mathbf{r}$$

Doesn't it look familiar?

$$\mathbf{Ax} = \lambda \mathbf{x}$$

\mathbf{x} is an eigenvector

λ is an eigenvalue

So, the rank vector \mathbf{r} is an **eigenvector** of the matrix \mathbf{M}

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

Doesn't it look familiar?

$$\mathbf{A}\mathbf{x} = \lambda\mathbf{x}$$

\mathbf{x} is an eigenvector

λ is an eigenvalue

So, the rank vector \mathbf{r} is an **eigenvector** of the matrix \mathbf{M}

In fact, \mathbf{r} is the eigenvector corresponding to the **eigenvalue** $\lambda = 1$

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

For a fixed eigenvalue, eigenvectors are just scalar multiples of each other

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

For a fixed eigenvalue, eigenvectors are just scalar multiples of each other

We can choose **any** of them to be our PageRank vector \mathbf{r}

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

For a fixed eigenvalue, eigenvectors are just scalar multiples of each other

We can choose **any** of them to be our PageRank vector \mathbf{r}

Since PageRank should reflect only the relative importance of the nodes, choose $\mathbf{r} = \mathbf{r}^*$ as the eigenvector whose entries sum up to 1

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

For a fixed eigenvalue, eigenvectors are just scalar multiples of each other

We can choose **any** of them to be our PageRank vector \mathbf{r}

Since PageRank should reflect only the relative importance of the nodes, choose $\mathbf{r} = \mathbf{r}^*$ as the eigenvector whose entries sum up to 1

This may be referred to as the **probabilistic eigenvector** corresponding to the eigenvalue $\lambda = 1$

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

We know from linear algebra theory that for any stochastic matrix \mathbf{M} its largest eigenvalue is $\lambda = 1$

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

We know from linear algebra theory that for any stochastic matrix \mathbf{M} its largest eigenvalue is $\lambda = 1$

Therefore, $\mathbf{r} = \mathbf{r}^*$ is the principal eigenvector of \mathbf{M} (i.e., the eigenvector associated with the largest eigenvalue)

PageRank: The Eigenvector Formulation

$$\mathbf{M}\mathbf{r} = \mathbf{r}$$

We know from linear algebra theory that for any stochastic matrix \mathbf{M} its largest eigenvalue is $\lambda = 1$

Therefore, $\mathbf{r} = \mathbf{r}^*$ is the principal eigenvector of \mathbf{M} (i.e., the eigenvector associated with the largest eigenvalue)

Note:

So far, we have assumed that \mathbf{M} is (column) stochastic yet this may not be the case for the general Web graph...

PageRank: Quick Recap

We start from "flow" equations

PageRank: Quick Recap

We start from "flow" equations

We reformulate the system of linear equations using
linear algebra
(i.e., stochastic matrix M and rank vector r)

PageRank: Quick Recap

We start from "flow" equations

We reformulate the system of linear equations using
linear algebra

(i.e., stochastic matrix M and rank vector r)

We reduce to finding the **eigenvector** of the matrix M

PageRank: Quick Recap

We start from "flow" equations

We reformulate the system of linear equations using
linear algebra


(i.e., stochastic matrix M and rank vector r)

We reduce to finding the **eigenvector** of the matrix M




We know how to solve this efficiently using
power iteration method

PageRank: The "Flow" Model



$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

PageRank: The "Flow" Model



$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

$$\mathbf{r} = \mathbf{M} \mathbf{r}$$

0	1/2	1
1/2	1/2	0
1/2	0	0

PageRank: Power Iteration Method

At the beginning, we assume all pages have the same rank score, **uniformly distributed** across the N pages

init: $t = 0; \mathbf{r}(t) = (1/N, 1/N, \dots, 1/N)^T$

PageRank: Power Iteration Method

Keep updating the rank vector \mathbf{r} until convergence

init: $t = 0; \mathbf{r}(t) = (1/N, 1/N, \dots, 1/N)^T$

repeat:

$$\mathbf{r}(t + 1) = \mathbf{M}\mathbf{r}(t)$$

until $\delta(\mathbf{r}(t + 1), \mathbf{r}(t)) < \epsilon$

$$\epsilon > 0$$

PageRank: Power Iteration Method

init: $t = 0; \mathbf{r}(t) = (1/N, 1/N, \dots, 1/N)^T$

repeat:

$$\mathbf{r}(t+1) = \mathbf{M}\mathbf{r}(t)$$


until $\delta(\mathbf{r}(t+1), \mathbf{r}(t)) < \epsilon$

$$\epsilon > 0$$

$$\left\{ \begin{array}{l} \delta(\mathbf{r}(t+1), \mathbf{r}(t)) = |\mathbf{r}(t+1) - \mathbf{r}(t)| \\ \text{or} \\ \delta(\mathbf{r}(t+1), \mathbf{r}(t)) = \|\mathbf{r}(t+1) - \mathbf{r}(t)\| \end{array} \right.$$

Power Iteration Method: Example

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$



0	1/2	1
1/2	1/2	0
1/2	0	0

r = **M** **r**

Power Iteration Method: Example

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

$$\mathbf{r} = \mathbf{M} \mathbf{r}$$

0	1/2	1
1/2	1/2	0
1/2	0	0

$$\mathbf{r}(0) = \begin{bmatrix} 1/3 \\ 1/3 \\ 1/3 \end{bmatrix}$$

Power Iteration Method: Example

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

$$\mathbf{r} = \mathbf{M} \mathbf{r}$$

0	1/2	1
1/2	1/2	0
1/2	0	0

$$\mathbf{r}(0) \quad \mathbf{r}(1) = \mathbf{M} \mathbf{r}(0)$$

1/3
1/3
1/3

3/6
1/3
1/6

Power Iteration Method: Example

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

$$\mathbf{r} = \mathbf{M} \mathbf{r}$$

0	1/2	1
1/2	1/2	0
1/2	0	0

1/3
1/3
1/3

$\mathbf{r}(0)$

3/6
1/3
1/6

$\mathbf{r}(1) = \mathbf{M}\mathbf{r}(0)$

1/3
5/12
3/12

$\mathbf{r}(2) = \mathbf{M}\mathbf{r}(1)$

Power Iteration Method: Example

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

$$\mathbf{r} = \mathbf{M} \mathbf{r}$$

0	1/2	1
1/2	1/2	0
1/2	0	0

<table border="1" style="margin: 0 auto; text-align: center;"> <tr><td>1/3</td></tr> <tr><td>1/3</td></tr> <tr><td>1/3</td></tr> </table>	1/3	1/3	1/3	<table border="1" style="margin: 0 auto; text-align: center;"> <tr><td>3/6</td></tr> <tr><td>1/3</td></tr> <tr><td>1/6</td></tr> </table>	3/6	1/3	1/6	<table border="1" style="margin: 0 auto; text-align: center;"> <tr><td>1/3</td></tr> <tr><td>5/12</td></tr> <tr><td>3/12</td></tr> </table>	1/3	5/12	3/12	<table border="1" style="margin: 0 auto; text-align: center;"> <tr><td>6/15</td></tr> <tr><td>6/15</td></tr> <tr><td>3/15</td></tr> </table>	6/15	6/15	3/15	<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;">2/5</div> <div style="margin-right: 10px;">2/5</div> <div style="margin-right: 10px;">1/5</div> </div>
1/3																
1/3																
1/3																
3/6																
1/3																
1/6																
1/3																
5/12																
3/12																
6/15																
6/15																
3/15																
$\mathbf{r}(0)$	$\mathbf{r}(1) = \mathbf{M}\mathbf{r}(0)$	$\mathbf{r}(2) = \mathbf{M}\mathbf{r}(1)$	\dots	$\mathbf{r}(t+1) = \mathbf{M}\mathbf{r}(t)$												

Power Iteration Method: Example

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

$$\mathbf{r} = \mathbf{M} \mathbf{r}$$

0	1/2	1
1/2	1/2	0
1/2	0	0

<table border="1" style="background-color: red; color: white;"> <tr><td>1/3</td></tr> <tr><td>1/3</td></tr> <tr><td>1/3</td></tr> </table>	1/3	1/3	1/3	<table border="1" style="background-color: red; color: white;"> <tr><td>3/6</td></tr> <tr><td>1/3</td></tr> <tr><td>1/6</td></tr> </table>	3/6	1/3	1/6	<table border="1" style="background-color: red; color: white;"> <tr><td>1/3</td></tr> <tr><td>5/12</td></tr> <tr><td>3/12</td></tr> </table>	1/3	5/12	3/12	...	<table border="1" style="background-color: red; color: white;"> <tr><td>6/15</td></tr> <tr><td>6/15</td></tr> <tr><td>3/15</td></tr> </table>	6/15	6/15	3/15	<div style="color: red;">2/5</div> <div style="color: green;">2/5</div> <div style="color: blue;">1/5</div>
1/3																	
1/3																	
1/3																	
3/6																	
1/3																	
1/6																	
1/3																	
5/12																	
3/12																	
6/15																	
6/15																	
3/15																	
$\mathbf{r}(0)$	$\mathbf{r}(1) = \mathbf{M}\mathbf{r}(0)$	$\mathbf{r}(2) = \mathbf{M}\mathbf{r}(1)$...	$\mathbf{r}(t+1) = \mathbf{M}\mathbf{r}(t)$													

We came up with the same set of solutions for r_v , r_w , and r_x without explicitly solving the system of equations

Take-Home Message of Today

- We present an example of **link analysis** algorithm:
PageRank

Take-Home Message of Today

- We present an example of **link analysis** algorithm:
PageRank
- Goal: Find an **importance score** for each web page

Take-Home Message of Today

- We present an example of **link analysis** algorithm:
PageRank
- Goal: Find an **importance score** for each web page
- Represent the Web graph as a matrix **M**, where a link from page **w** to **v** is a **vote** from **w** to **v**

Take-Home Message of Today

- We present an example of **link analysis** algorithm:
PageRank
- Goal: Find an **importance score** for each web page
- Represent the Web graph as a matrix **M**, where a link from page **w** to **v** is a **vote** from **w** to **v**
- **2** different yet equivalent approaches:
 - **Linear Algebra** → Matrix eigenvector
 - **Probabilistic** → ? (More on this next time...)