# Systems and Networking I

Applied Computer Science and Artificial Intelligence 2023–2024



#### Gabriele Tolomei

Dipartimento di Informatica Sapienza Università di Roma tolomei@di.uniroma1.it

• So far, we have assumed each process is allocated into a contiguous space of physical memory

- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions


- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions
  - Assign each process to a segment

- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions
  - Assign each process to a segment
  - Implicitly restricts the grade of multiprogramming (i.e., the number of simultaneous processes) and their size


- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions
  - Assign each process to a segment
  - Implicitly restricts the grade of multiprogramming (i.e., the number of simultaneous processes) and their size
  - No longer used!

An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate


An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate



An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate





An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate





10


An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate











 Linearly scan the list of holes until one is found that is big enough to satisfy the request

- Linearly scan the list of holes until one is found that is big enough to satisfy the request
- Subsequent requests may either start from the beginning of the list or from the end of previous search

- Linearly scan the list of holes until one is found that is big enough to satisfy the request
- Subsequent requests may either start from the beginning of the list or from the end of previous search
- Complexity: O(n), where n is the number of holes

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using first-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:




Which segment will be picked by the OS using first-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:




Which segment will be picked by the OS using first-fit?



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using first-fit?




What if afterwards process Y requires 350B?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using first-fit?



What if afterwards process Y requires 350B?

We will not be able to satisfy this request even if theoretically we could

 Allocate the smallest hole that is big enough to satisfy the request

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted
- Complexity: still O(n) but can be O(log n) if the list of holes is kept sorted


- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted
- Complexity: still O(n) but can be O(log n) if the list of holes is kept sorted

Do you know how which data structure can be used to achieve this?

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted
- Complexity: still O(n) but can be O(log n) if the list of holes is kept sorted

Do you know how which data structure can be used to achieve this?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using best-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:




Which segment will be picked by the OS using best-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:




Which segment will be picked by the OS using best-fit?



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using best-fit?




What if afterwards process Y requires 350B?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using best-fit?



What if afterwards process Y requires 350B?

We can now assign it the second available hole segment (400B)

Allocate the largest hole available

- Allocate the largest hole available
- Might sound counterintuitive but this increases the likelihood that the remaining portion will be usable for satisfying future requests

- Allocate the largest hole available
- Might sound counterintuitive but this increases the likelihood that the remaining portion will be usable for satisfying future requests
- Simulations show that First-Fit and Best-Fit usually work best

- Allocate the largest hole available
- Might sound counterintuitive but this increases the likelihood that the remaining portion will be usable for satisfying future requests
- Simulations show that First-Fit and Best-Fit usually work best
- First-Fit is also generally faster than Best-Fit

### Fragmentation

#### Problem

Individual holes may be too small to serve a process request but they can be large enough if combined together

### Fragmentation

#### Problem

Individual holes may be too small to serve a process request but they can be large enough if combined together

External Fragmentation

### Fragmentation

#### Problem

Individual holes may be too small to serve a process request but they can be large enough if combined together


External Fragmentation

Internal Fragmentation

• Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks

- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous


- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous 3999



- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous 3999

Simulations show that for every 2N allocated blocks, N are lost due to external fragmentation

1/3 of memory space is wasted on average




- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous 3999

Simulations show that for every 2N allocated blocks, N are lost due to external fragmentation

1/3 of memory space is wasted on average

Goal: Allocation policy that minimizes wasted space!



OS


• It happens when memory internal to a segment is wasted


- It happens when memory internal to a segment is wasted
- For example, consider a process whose size is 8,846B and a hole of size 8,848B


- It happens when memory internal to a segment is wasted
- For example, consider a process whose size is 8,846B and a hole of size 8,848B
- It may be much more efficient to allocate the process the whole block (and waste 2B) rather than keep track of a tiny 2B hole


11/30/23


51



















Only one hole is left but two processes need to be moved (C and D)

















Still some holes left but only one process is moved (D) rather than two

• So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)

- So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)
- Remember: A process needs to sit physically in main memory only if the CPU executes its instructions and accesses its data

- So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)
- Remember: A process needs to sit physically in main memory only if the CPU executes its instructions and accesses its data
- If a process blocks (e.g., due to an I/O call) it doesn't need to be in memory while I/O is running

- So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)
- Remember: A process needs to sit physically in main memory only if the CPU executes its instructions and accesses its data
- If a process blocks (e.g., due to an I/O call) it doesn't need to be in memory while I/O is running
- That process can be "swapped out" from memory to disk to make room for other processes

• Once process becomes ready again, the OS must reload it in memory

- Once process becomes ready again, the OS must reload it in memory
- Swap in depends on the address binding used:
  - compile- or load-time: must be swapped back into the same memory location from which they were swapped out

- Once process becomes ready again, the OS must reload it in memory
- Swap in depends on the address binding used:
  - compile- or load-time: must be swapped back into the same memory location from which they were swapped out
  - execution-time: can be swapped back into any available location (updating base and limit registers)


- Once process becomes ready again, the OS must reload it in memory
- Swap in depends on the address binding used:
  - compile- or load-time: must be swapped back into the same memory location from which they were swapped out
  - execution-time: can be swapped back into any available location (updating base and limit registers)
- Using swapping, fragmentation can be tackled easily
  - Just run compaction before swapping-in a process

• Swapping is a very slow process compared to other operations due to the interaction with hard disk

- Swapping is a very slow process compared to other operations due to the interaction with hard disk
- Example:
  - 10 MB user process
  - disk transfer rate = 40 MB/sec (250 msec just to do the data transfer)

- Swapping is a very slow process compared to other operations due to the interaction with hard disk
- Example:
  - 10 MB user process
  - disk transfer rate = 40 MB/sec (250 msec just to do the data transfer)
- Since swap-in may involve swapping-out another process, the overall time required will be ~500 msec

- Swapping is a very slow process compared to other operations due to the interaction with hard disk
- Example:
  - 10 MB user process
  - disk transfer rate = 40 MB/sec (250 msec just to do the data transfer)
- Since swap-in may involve swapping-out another process, the overall time required will be ~500 msec
- Time slice is usually way smaller than that!



Most modern OSs no longer use swapping, because it is too slow and there are faster alternatives available (e.g., paging)

#### Problems Seen So Far

- Contiguous allocation
  - Hard to grow or shrink process memory

#### Problems Seen So Far

- Contiguous allocation
  - Hard to grow or shrink process memory
- Fragmentation
  - Frequent compaction needed

#### Problems Seen So Far

- Contiguous allocation
  - Hard to grow or shrink process memory
- Fragmentation
  - Frequent compaction needed
- Process entirely loaded
  - Swapping helps but it may be too inefficient

• A memory management scheme that addresses the problems above

11/30/23 76

- A memory management scheme that addresses the problems above
- The logical address space of a process is still **contiguous** but it is divided into **fixed-size blocks**, called **pages**

- A memory management scheme that addresses the problems above
- The logical address space of a process is still contiguous but it is divided into fixed-size blocks, called pages
- Contiguous allocation is no longer required as logical pages can be mapped to non-contiguous physical frames

11/30/23 78

- A memory management scheme that addresses the problems above
- The logical address space of a process is still contiguous but it is divided into fixed-size blocks, called pages
- Contiguous allocation is no longer required as logical pages can be mapped to non-contiguous physical frames
- External fragmentation is eliminated because pages have fixed size
  - Internal fragmentation may still occur though


11/30/23 79

- A memory management scheme that addresses the problems above
- The logical address space of a process is still **contiguous** but it is divided into **fixed-size blocks**, called **pages**
- Contiguous allocation is no longer required as logical pages can be mapped to non-contiguous physical frames
- External fragmentation is eliminated because pages have fixed size
  - Internal fragmentation may still occur though

#### 90/10 Rule

Processes spend 90% of their time accessing only 10% of their allocated memory space

### Paging: The Big Picture



Logical/Virtual Address Space of process A

#### Physical Memory Paging: The Big Picture OS frame 0 OS frame 1 page 0 $A_{O}$ frame 2 $A_4$ page 1 $A_1$ frame 3 page 2 $A_2$ frame 4 page 3 $A_3$ $A_1$ frame 5 page 4 $A_4$ frame 6 page 5 $A_5$ $A_2$ frame 7 Logical/Virtual Address Space $A_{O}$ frame 8 of process A $A_3$ frame 9

11/30/23

frame 10

 $A_5$ 

# Basic OS Responsibilities for Paging

- The OS has 2 main responsibilities:
  - mapping between logical pages and physical frames
  - translating logical addresses to physical addresses


# Basic OS Responsibilities for Paging


- The OS has 2 main responsibilities:
  - mapping between logical pages and physical frames
  - translating logical addresses to physical addresses
- All of this must be done efficiently!
  - Remember, memory addresses are referenced all the time

# Basic OS Responsibilities for Paging

- The OS has 2 main responsibilities:
  - mapping between logical pages and physical frames
  - translating logical addresses to physical addresses
- All of this must be done efficiently!
  - Remember, memory addresses are referenced all the time
- OS needs dedicated support for doing it → Page
  Table

## Page Table: Mapping Pages to Frames





### Page Table: Mapping Pages to Frames

Lookup table to retrieve what frame a page is stored in


0	Ao
1	$A_1$
2	$A_2$
3	$A_3$
4	A <sub>4</sub>
5	A <sub>5</sub>

Page	Frame
0	8
1	5
2	7
3	9
4	2
5	10


OS	0
OS	1
$A_4$	1 2 3
	3
	4 5
$A_1$	5
	6
A <sub>2</sub>	7
Ao	8
$A_3$	9
A <sub>5</sub>	10
	1

## Page Table: Mapping Pages to Frames

Lookup table to retrieve what frame a page is stored in



Page	Frame
0	8
1	5
2	7
3	9
4	2
5	10



We have assumed all pages of a process are mapped to physical frames, but this is not always the case

- Contiguous memory allocation may cause fragmentation
  - External vs. Internal Fragmentation

- Contiguous memory allocation may cause fragmentation
  - External vs. Internal Fragmentation
- Existing countermeasures (compaction) exist but they are costly

- Contiguous memory allocation may cause fragmentation
  - External vs. Internal Fragmentation
- Existing countermeasures (compaction) exist but they are costly
- We may want to relax the constraint on having an entire process loaded in main memory

- Contiguous memory allocation may cause fragmentation
  - External vs. Internal Fragmentation
- Existing countermeasures (compaction) exist but they are costly
- We may want to relax the constraint on having an entire process loaded in main memory
- Paging solves all these issues!