

# Systems and Networking I

Applied Computer Science and Artificial Intelligence  
2024-2025



**SAPIENZA**  
UNIVERSITÀ DI ROMA

Gabriele Tolomei

Dipartimento di Informatica  
Sapienza Università di Roma

[tolomei@di.uniroma1.it](mailto:tolomei@di.uniroma1.it)

# Recap from Last Lecture

- Synchronization primitives:
  - Locks
  - Semaphores
  - Monitors

# Recap from Last Lecture

- Synchronization primitives:
  - Locks
  - Semaphores
  - Monitors
- 2 fundamental synchronization problems:
  - Producers-Consumers
  - Readers-Writers

# Our Journey

- What is deadlock?
- Conditions for deadlock to happen
- Deadlock detection
- Deadlock prevention
- Deadlock avoidance

# Our Journey

- What is deadlock?
- Conditions for deadlock to happen
- Deadlock detection
- Deadlock prevention
- Deadlock avoidance

# What is Deadlock?

“When two trains approach each other at a crossing, both shall come to a full stop and neither shall start up again until the other has gone.”

Kansas legislation early 1900's

# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

Thread A

```
printer.wait();  
disk.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```


Thread B

```
disk.wait();  
printer.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```



# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads



# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

Thread A

```
printer.wait(); Acquires printer and context switch  
disk.wait();
```



```
// copy from disk to printer
```

```
printer.signal();  
disk.signal();
```

Thread B

```
disk.wait();  
printer.wait();
```

```
// copy from disk to printer
```

```
printer.signal();  
disk.signal();
```

# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

Thread A

```
printer.wait();  
disk.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```

B takes over

Thread B

```
disk.wait();  
printer.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```

# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

Thread A

```
printer.wait();  
disk.wait();
```

```
// copy from disk to printer
```

```
printer.signal();  
disk.signal();
```

Thread B

```
disk.wait();  
printer.wait();
```


← Acquires disk and context switch

```
// copy from disk to printer
```

```
printer.signal();  
disk.signal();
```

# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads



# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

Thread A

```
printer.wait();  
disk.wait();
```

```
// copy from disk to printer
```

```
printer.signal();  
disk.signal();
```

Thread B

```
disk.wait();  
printer.wait();
```

B executes again and blocks

```
// copy from disk to printer
```

```
printer.signal();  
disk.signal();
```

# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

Thread A

```
printer.wait();  
disk.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```

Thread B

```
disk.wait();  
printer.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```

A waits B to release the disk

# What is Deadlock?

Intuitively, a condition where two or more threads are waiting for an event that can only be generated by the very same threads

Thread A

```
printer.wait();  
disk.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```

Thread B

```
disk.wait();  
printer.wait();  
  
// copy from disk to printer  
  
printer.signal();  
disk.signal();
```

B waits A to release the printer



# Deadlock: Terminology

- **Deadlock:** it can occur when multiple threads compete for a finite number of resources

# Deadlock: Terminology

- **Deadlock:** it can occur when multiple threads compete for a finite number of resources
- **Deadlock detection:** finds instances of deadlocks and tries to recover

# Deadlock: Terminology

- **Deadlock**: it can occur when multiple threads compete for a finite number of resources
- **Deadlock detection**: finds instances of deadlocks and tries to recover
- **Deadlock prevention (offline)**: imposes restrictions/rules on how to write deadlock-free programs

# Deadlock: Terminology

- **Deadlock:** it can occur when multiple threads compete for a finite number of resources
- **Deadlock detection:** finds instances of deadlocks and tries to recover
- **Deadlock prevention (offline):** imposes restrictions/rules on how to write deadlock-free programs
- **Deadlock avoidance (online):** runtime support checks resource requests made by threads to avoid deadlocks

# Deadlock vs. Starvation

- Not to be confused with each other!

# Deadlock vs. Starvation

- Not to be confused with each other!
- Related terms but each one refers to a specific situation

# Deadlock vs. Starvation

- Not to be confused with each other!
- Related terms but each one refers to a specific situation
- Starvation occurs when a thread waits indefinitely for some resource but other threads are actually making progress using that resource

# Deadlock vs. Starvation

- Not to be confused with each other!
- Related terms but each one refers to a specific situation
- Starvation occurs when a thread waits indefinitely for some resource but other threads are actually making progress using that resource
- The main difference with deadlock is that the system is not completely stuck!



# Our Journey

- What is deadlock?
- Conditions for deadlock to happen
- Deadlock detection
- Deadlock prevention
- Deadlock avoidance

# Necessary Conditions for Deadlock

- Deadlock can happen if all the 4 conditions below hold

# Necessary Conditions for Deadlock

- Deadlock can happen if all the 4 conditions below hold
  - Mutual Exclusion → at least one thread must hold a non-sharable resource (only one thread holds the resource)

# Necessary Conditions for Deadlock

- Deadlock can happen if all the 4 conditions below hold
  - **Mutual Exclusion** → at least one thread must hold a non-sharable resource (only one thread holds the resource)
  - **Hold and Wait** → at least one thread is holding a non-sharable resource and is waiting for other resource(s) to become available (another thread holds the resource(s))

# Necessary Conditions for Deadlock

- Deadlock can happen if all the 4 conditions below hold
  - **Mutual Exclusion** → at least one thread must hold a non-sharable resource (only one thread holds the resource)
  - **Hold and Wait** → at least one thread is holding a non-sharable resource and is waiting for other resource(s) to become available (another thread holds the resource(s))
  - **No Preemption** → a thread can only release a resource voluntarily; neither another thread nor the OS can force it to release the resource

# Necessary Conditions for Deadlock

- Deadlock can happen if all the 4 conditions below hold
  - **Mutual Exclusion** → at least one thread must hold a non-sharable resource (only one thread holds the resource)
  - **Hold and Wait** → at least one thread is holding a non-sharable resource and is waiting for other resource(s) to become available (another thread holds the resource(s))
  - **No Preemption** → a thread can only release a resource voluntarily; neither another thread nor the OS can force it to release the resource
  - **Circular Wait** → a set of waiting threads  $t_1, \dots, t_n$  where  $t_i$  is waiting on  $t_{(i+1)\%n}$

# Our Journey

- What is deadlock?
- Conditions for deadlock to happen
- **Deadlock detection**
- Deadlock prevention
- Deadlock avoidance

# Deadlock Detection: Resource Allocation Graph

- We define a **directed graph**  $G=(V, E)$  where:



# Deadlock Detection: Resource Allocation Graph

- We define a **directed graph**  $G=(V, E)$  where:
  - $V$  is the set of vertices representing both **resources**  $\{r_1, \dots, r_m\}$  and **threads**  $\{t_1, \dots, t_n\}$

# Deadlock Detection: Resource Allocation Graph

- We define a **directed graph**  $G=(V, E)$  where:
  - $V$  is the set of vertices representing both **resources**  $\{r_1, \dots, r_m\}$  and **threads**  $\{t_1, \dots, t_n\}$
  - $E$  is the set of edges between resources and threads

# Deadlock Detection: Resource Allocation Graph

- We define a **directed graph**  $G=(V, E)$  where:
  - $V$  is the set of vertices representing both **resources**  $\{r_1, \dots, r_m\}$  and **threads**  $\{t_1, \dots, t_n\}$
  - $E$  is the set of edges between resources and threads
- Edges can be of **2 types**:


# Deadlock Detection: Resource Allocation Graph

- We define a **directed graph**  $G=(V, E)$  where:
  - $V$  is the set of vertices representing both **resources**  $\{r_1, \dots, r_m\}$  and **threads**  $\{t_1, \dots, t_n\}$
  - $E$  is the set of edges between resources and threads
- Edges can be of **2 types**:
  - **Request Edge**  $\rightarrow$  a directed edge  $(t_i, r_j)$  indicates that  $t_i$  has requested  $r_j$ , but not yet acquired


# Deadlock Detection: Resource Allocation Graph

- We define a **directed graph**  $G=(V, E)$  where:
  - $V$  is the set of vertices representing both **resources**  $\{r_1, \dots, r_m\}$  and **threads**  $\{t_1, \dots, t_n\}$
  - $E$  is the set of edges between resources and threads
- Edges can be of **2 types**:
  - **Request Edge**  $\rightarrow$  a directed edge  $(t_i, r_j)$  indicates that  $t_i$  has requested  $r_j$ , but not yet acquired
  - **Assignment Edge**  $\rightarrow$  a directed edge  $(r_j, t_i)$  indicates that the OS has allocated  $r_j$  to  $t_i$

# Deadlock Detection: Resource Allocation Graph




# Deadlock Detection: Resource Allocation Graph



If the graph has no cycles, no deadlock will ever exist

# Deadlock Detection: Resource Allocation Graph




If the graph has no cycles, no deadlock will ever exist

Why?




# Deadlock Detection: Resource Allocation Graph



Suppose we remove the edge  $(t_4, r_3)$  so as to remove the cycle


# Deadlock Detection: Resource Allocation Graph



Suppose we remove the edge  $(t_4, r_3)$  so as to remove the cycle

No deadlock can occur as  $t_4$  is not waiting on anything...

# Deadlock Detection: Resource Allocation Graph




Suppose we remove the edge  $(t_4, r_3)$  so as to remove the cycle

No deadlock can occur as  $t_4$  is not waiting on anything...

Therefore,  $t_4$  can run and eventually will release  $r_2$ , which wakes up  $t_3$

# Deadlock Detection: Resource Allocation Graph




Suppose we remove the edge  $(t_4, r_3)$  so as to remove the cycle

No deadlock can occur as  $t_4$  is not waiting on anything...

Therefore,  $t_4$  can run and eventually will release  $r_2$ , which wakes up  $t_3$


And so on and so forth...

# Deadlock Detection: Resource Allocation Graph



If the graph has cycles, deadlock **might** exist


# Deadlock Detection: Resource Allocation Graph



If the graph has cycles, deadlock **might** exist

Why?


# Deadlock Detection: Resource Allocation Graph



If the graph has cycles, deadlock **might** exist

We are assuming the **multiplicity** of each resource is **1** (i.e., one  $r_1$ , one  $r_2$ , etc.)


# Deadlock Detection: Resource Allocation Graph




What if there are **multiple** instances of the same resource?



# Deadlock Detection: Resource Allocation Graph



# Deadlock Detection: Resource Allocation Graph



This works!  
If **any** resource involved in the cycle is held by a thread which is not in the cycle ( $t_1$ ) then we can make progress

# Deadlock: Detect and Correct It!

- Scan the Resource Allocation Graph (RAG) for cycles, and then break those!

# Deadlock: Detect and Correct It!

- Scan the Resource Allocation Graph (RAG) for cycles, and then break those!
- How? Several ways of doing it:

# Deadlock: Detect and Correct It!

- Scan the Resource Allocation Graph (RAG) for cycles, and then break those!
- How? Several ways of doing it:
  - Kill all the threads in the cycle (quite harsh, ugh?)

# Deadlock: Detect and Correct It!

- Scan the Resource Allocation Graph (RAG) for cycles, and then break those!
- How? Several ways of doing it:
  - Kill all the threads in the cycle (quite harsh, ugh?)
  - Kill all the threads one at a time, forcing each one of them to release resource(s)

# Deadlock: Detect and Correct It!

- Scan the Resource Allocation Graph (RAG) for cycles, and then break those!
- How? Several ways of doing it:
  - Kill all the threads in the cycle (quite harsh, ugh?)
  - Kill all the threads one at a time, forcing each one of them to release resource(s)
  - Preempt resources one at a time rolling back to a consistent status (e.g., common in database transactions)

# Deadlock: Detect and Correct It!

- Scan the Resource Allocation Graph (RAG) for cycles, and then break those!
- How? Several ways of doing it:
  - Kill all the threads in the cycle (quite harsh, ugh?)
  - Kill all the threads one at a time, forcing each one of them to release resource(s)
  - Preempt resources one at a time rolling back to a consistent status (e.g., common in database transactions)
- We would like to be more precise than that...



# Deadlock: Detect and Correct It!

- Detecting cycles on a directed graph  $G=(V, E)$  is a quite costly operation

# Deadlock: Detect and Correct It!

- Detecting cycles on a directed graph  $G=(V, E)$  is a quite costly operation
- Known algorithms based on **depth-first search (DFS)** take  $O(|V|+|E|)$  time

# Deadlock: Detect and Correct It!

- Detecting cycles on a directed graph  $G=(V, E)$  is a quite costly operation
- Known algorithms based on **depth-first search (DFS)** take  $O(|V|+|E|)$  time
- $O(|V|+|E|) \sim O(|V|^2)$  as  $|E| = O(|V|^2)$  for dense graphs, and  $|V| = \text{\#threads} + \text{\#resources}$

# Deadlock: Detect and Correct It!

- When to run such a detection algorithm?

# Deadlock: Detect and Correct It!

- When to run such a detection algorithm?
  - Before granting a resource → each granted request will take  $O(|V|^2)$

# Deadlock: Detect and Correct It!

- When to run such a detection algorithm?
  - Before granting a resource → each granted request will take  $O(|V|^2)$
  - When a request cannot be fulfilled → each failed request will take  $O(|V|^2)$

# Deadlock: Detect and Correct It!

- When to run such a detection algorithm?
  - Before granting a resource → each granted request will take  $O(|V|^2)$
  - When a request cannot be fulfilled → each failed request will take  $O(|V|^2)$
  - On a regular schedule or when the CPU is under-utilized

# Our Journey

- What is deadlock?
- Conditions for deadlock to happen
- Deadlock detection
- **Deadlock prevention**
- Deadlock avoidance



# Deadlock Prevention

- Ensure that at least one of the 4 necessary conditions doesn't hold
  - Mutual Exclusion → make all resources sharable
    - Not all can be shared
    - E.g., disks, printers, etc.

# Deadlock Prevention

- Ensure that at least one of the 4 necessary conditions doesn't hold
  - Hold and Wait → a thread cannot hold one resource when it requests another
    - Enforce requests to be made all at once
    - Hard to predict all the resources a thread will need

# Deadlock Prevention

- Ensure that **at least one** of the **4** necessary conditions doesn't hold
  - **No Preemption** → if a thread requests a resource that cannot be allocated to it, the OS preempts (releases) all the resources that the thread is already holding
    - Not all resources can be easily preempted (e.g., printers)

# Deadlock Prevention

- Ensure that at least one of the 4 necessary conditions doesn't hold
  - Circular Wait → impose an ordering (i.e., numbering) on resources and enforce to request them in such order
    - Hard to establish such an order

# Our Journey

- What is deadlock?
- Conditions for deadlock to happen
- Deadlock detection
- Deadlock prevention
- **Deadlock avoidance**

# Deadlock Avoidance: Resource Reservation

Each thread provides information about the **maximum** number of resources it **might** need during execution

# Deadlock Avoidance: Resource Reservation

Each thread provides information about the **maximum** number of resources it **might** need during execution

$m_i$  = *maximum* number of resources that thread  $i$  *might* request

$c_i$  = *current* number of resources that thread  $i$  is holding

$C = \sum_{i=1}^n c_i$  = *total* number of resources currently allocated

$R$  = *maximum* number of resources overall available

# Deadlock Avoidance: Resource Reservation

Each thread provides information about the **maximum** number of resources it **might** need during execution

$m_i$  = *maximum* number of resources that thread  $i$  *might* request

$c_i$  = *current* number of resources that thread  $i$  is holding

$C = \sum_{i=1}^n c_i$  = *total* number of resources currently allocated

$R$  = *maximum* number of resources overall available

Any thread sequence is **safe** if for each thread it holds that:

$$\underbrace{m_i - c_i}_{\text{resources } t_i \text{ might still request}} \leq \underbrace{R - C}_{\text{resources currently available}} + \underbrace{\sum_{j=1}^{i-1} c_j}_{\text{resources currently allocated up to } t_j, j < i}$$



# Deadlock Avoidance: Safe State

- A state in which there is a safe sequence for the threads

# Deadlock Avoidance: Safe State

- A state in which there is a safe sequence for the threads
- An unsafe state does not necessarily mean deadlock (i.e., some threads may not request the maximum number of resources as declared)

# Deadlock Avoidance: Safe State

- A state in which there is a safe sequence for the threads
- An unsafe state does not necessarily mean deadlock (i.e., some threads may not request the maximum number of resources as declared)
- Grant a resource to a thread if the new state is safe, otherwise make it wait even if the resource is available

# Deadlock Avoidance: Safe State

- A state in which there is a safe sequence for the threads
- An unsafe state does not necessarily mean deadlock (i.e., some threads may not request the maximum number of resources as declared)
- Grant a resource to a thread if the new state is safe, otherwise make it wait even if the resource is available
- This policy ensures no circular-wait condition exists

# Deadlock Avoidance: Example

- 3 threads:  $t_1$ ,  $t_2$ , and  $t_3$  are competing for 12 tape drives (resources)

# Deadlock Avoidance: Example

- 3 threads:  $t_1$ ,  $t_2$ , and  $t_3$  are competing for 12 tape drives (resources)
- Currently, 11 drives are allocated to the threads, leaving 1 available

# Deadlock Avoidance: Example

- 3 threads:  $t_1$ ,  $t_2$ , and  $t_3$  are competing for 12 tape drives (resources)
- Currently, 11 drives are allocated to the threads, leaving 1 available

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	4	8

# Deadlock Avoidance: Example

- 3 threads:  $t_1$ ,  $t_2$ , and  $t_3$  are competing for 12 tape drives (resources)
- Currently, 11 drives are allocated to the threads, leaving 1 available

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	4	8

Is the current state safe?



# Deadlock Avoidance: Example

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	4	8

The current state is safe: there exists a sequence of threads ( $t_1, t_2, t_3$ ) where each one gets the maximum number of resources without waiting

# Deadlock Avoidance: Example

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	4	8

The current state is safe: there exists a sequence of threads ( $t_1, t_2, t_3$ ) where each one gets the maximum number of resources without waiting

$t_1$  can complete using the current allocation and the 1 drive left

# Deadlock Avoidance: Example

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	4	8

The current state is safe: there exists a sequence of threads ( $t_1, t_2, t_3$ ) where each one gets the maximum number of resources without waiting

$t_1$  can complete using the current allocation and the 1 drive left

$t_2$  can use the current allocation, plus  $t_1$ 's resources and 1 drive left (4 drives)

# Deadlock Avoidance: Example

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	4	8

The current state is safe: there exists a sequence of threads ( $t_1, t_2, t_3$ ) where each one gets the maximum number of resources without waiting

$t_1$  can complete using the current allocation and the 1 drive left

$t_2$  can use the current allocation, plus  $t_1$ 's resources and 1 drive left (4 drives)

$t_3$  can use the current allocation, plus  $t_1$ 's &  $t_2$ 's resources and 1 drive left (8 drives)

# Deadlock Avoidance: Example

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	5	7

Suppose  $t_3$  requests one more drive, then now there are **no more available drives**

# Deadlock Avoidance: Example

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	5	7

Suppose  $t_3$  requests one more drive, then now there are **no more available drives**

Theoretically, **everything might still work** (e.g.,  $t_1$  may never request another drive)

# Deadlock Avoidance: Example

Thread	$m_i$	$c_i$	$m_i - c_i$
$t_1$	4	3	1
$t_2$	8	4	4
$t_3$	12	5	7

Suppose  $t_3$  requests one more drive, then now there are **no more available drives**

Theoretically, **everything might still work** (e.g.,  $t_1$  may never request another drive)

However,  $t_3$  must wait because allocating that extra drive would lead to an unsafe state, which in turn might lead to deadlock

# Deadlock Avoidance: Resource Allocation Graph

- An extension of the original resource allocation graph



# Deadlock Avoidance: Resource Allocation Graph

- An extension of the original resource allocation graph
- Edges can now be of 3 types:
  - Request Edge  $\rightarrow$  a directed edge  $(t_i, r_j)$  indicates that  $t_i$  has requested  $r_j$ , but not yet acquired
  - Claim (dotted) Edge  $\rightarrow$  a directed edge  $(t_i, r_j)$  indicates that  $t_i$  might request  $r_j$  in the future
  - Assignment Edge  $\rightarrow$  a directed edge  $(r_j, t_i)$  indicates that the OS has allocated  $r_j$  to  $t_i$

# Deadlock Avoidance: Resource Allocation Graph

- An extension of the original resource allocation graph
- Edges can now be of 3 types:
  - Request Edge  $\rightarrow$  a directed edge  $(t_i, r_j)$  indicates that  $t_i$  has requested  $r_j$ , but not yet acquired
  - Claim (dotted) Edge  $\rightarrow$  a directed edge  $(t_i, r_j)$  indicates that  $t_i$  might request  $r_j$  in the future
  - Assignment Edge  $\rightarrow$  a directed edge  $(r_j, t_i)$  indicates that the OS has allocated  $r_j$  to  $t_i$
- Satisfying a request means converting a claim into an assignment edge

# Deadlock Avoidance: Resource Allocation Graph

- A cycle in this extended RAG indicates an unsafe state

# Deadlock Avoidance: Resource Allocation Graph

- A cycle in this extended RAG indicates an unsafe state
- If the allocation results in an unsafe state, this will be denied even if the resource is actually available


# Deadlock Avoidance: Resource Allocation Graph

- A cycle in this extended RAG indicates an unsafe state
- If the allocation results in an unsafe state, this will be denied even if the resource is actually available
- In other words, the claim edge is converted into a request edge and the thread will wait


# Deadlock Avoidance: Resource Allocation Graph

- A cycle in this extended RAG indicates an unsafe state
- If the allocation results in an unsafe state, this will be denied even if the resource is actually available
- In other words, the claim edge is converted into a request edge and the thread will wait
- NOTE: This solution does not work when there are multiple instances of the **same** resource

# Deadlock Avoidance: Resource Allocation Graph




# Deadlock Avoidance: Resource Allocation Graph






# Deadlock Avoidance: Resource Allocation Graph




We are introducing a potential cycle ( $t_3$  requests  $r_2$ ), which in turn might cause deadlock

unsafe state

# Deadlock Avoidance: Resource Allocation Graph




# Deadlock Avoidance: Resource Allocation Graph



We are **not** introducing any potential cycle ( $t_4$  requests  $r_2$ )

**safe state**

# Deadlock Avoidance: Resource Allocation Graph



Start from a safe state

## Invariant

Accept a request iff  
we move from a safe  
state to another

# Banker's Algorithm

- Handles multiple instances of the same resource
- Forces threads to provide information on what resource they might need, in advance
- The resources requested must not exceed the total available in the system
- The algorithm allocates resources to a requesting thread if the allocation leaves the system in a safe state, otherwise the thread waits

# Banker's Algorithm: Data Structures

- $n$  = number of threads;  $m$  = number of resource types
- $available[1..m]$ :  $m$ -dimensional vector
  - $available[j] = k$  means there are  $k$  resources of type  $j$  available
- $max[1..n, 1..m]$ :  $n \times m$  matrix
  - $max[i, j] = k$  means thread  $i$  may require at most  $k$  resources of type  $j$
- $allocation[1..n, 1..m]$ :  $n \times m$  matrix
  - $allocation[i, j] = k$  means thread  $i$  has allocated  $k$  resources of type  $j$
- $need[1..n, 1..m]$ :  $n \times m$  matrix
  - $need[i, j] = max[i, j] - allocation[i, j] = k$  means thread  $i$  may need  $k$  more resources of type  $j$  to complete its task

# Banker's Algorithm: Idea

- The algorithm is divided in 2 tasks:
  - `isSafeState` → given the current status of allocation of resources, tests if this is a safe state
  - `resourceRequest` → given a thread and its resource request decides if such a request can be satisfied

# Banker's Algorithm: Idea

- The algorithm is divided in 2 tasks:
  - `isSafeState` → given the current status of allocation of resources, tests if this is a safe state
  - `resourceRequest` → given a thread and its resource request decides if such a request can be satisfied
- A request can be satisfied iff this leads to a safe state!



# Banker's Algorithm: Idea

- The algorithm is divided in 2 tasks:
  - `isSafeState` → given the current status of allocation of resources, tests if this is a safe state
  - `resourceRequest` → given a thread and its resource request decides if such a request can be satisfied
- A request can be satisfied iff this leads to a safe state!
- In other words, the second task uses the output of the first one in order to make a decision

# Banker's Algorithm: isSafeState

1. Let work and finish be vectors of length m and n, respectively

Initialize:  $work = available$ ;  $finish[i] = false$ ; for all i

2. Find an i such that:

$finish[i] = false \ \&\& \ need[i] \leq work$

If no such i exists, go to step 4.

3. Assume thread i executes:

$work = work + allocation[i]$ ;  $finish[i] = true$ ; go to step 2.

4. If  $finish[i] == true$  for all i, the system is in a safe state

# Banker's Algorithm: requestResource

Input:  $i$  (thread) and request an  $m$ -dimensional vector of requests

1. If  $\text{request} > \text{need}[i]$  raise an error as thread  $i$  is attempting to request more resources than it claimed, otherwise go to step 2.
2. If  $\text{request} > \text{available}$  thread  $i$  must wait since resources are not available, otherwise go to step 3.
3. Even if resources are available, test if this allocation will lead to a safe state by simulating it  
 $\text{available} -= \text{request}; \text{allocation}[i] += \text{request}; \text{need}[i] -= \text{request};$   
 $\text{isSafeState()} ? \text{OK} : \text{rollback()} \text{ and } \text{wait}()$

# Banker's Algorithm: Example

A snapshot of the current state of the system

		RESOURCES								
		MAX			ALLOCATION			AVAILABLE		
		A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1			
	T <sub>1</sub>	1	7	5	1	0	0			
	T <sub>2</sub>	2	3	5	1	3	5			
	T <sub>3</sub>	0	6	5	0	6	3			
	Total				2	9	9	1	5	2

# Banker's Algorithm: Example

**Q1:** How many resources of type A, B, and C are there overall?

		RESOURCES								
		MAX			ALLOCATION			AVAILABLE		
		A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1			
	T <sub>1</sub>	1	7	5	1	0	0			
	T <sub>2</sub>	2	3	5	1	3	5			
	T <sub>3</sub>	0	6	5	0	6	3			
Total					2	9	9	1	5	2

# Banker's Algorithm: Example

**Q1:** How many resources of type A, B, and C are there overall?

		RESOURCES								
		MAX			ALLOCATION			AVAILABLE		
		A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1			
	T <sub>1</sub>	1	7	5	1	0	0			
	T <sub>2</sub>	2	3	5	1	3	5			
	T <sub>3</sub>	0	6	5	0	6	3			
	Total				2	9	9	1	5	2

$$A = 2 + 1 = 3$$

$$B = 9 + 5 = 14$$

$$C = 9 + 2 = 11$$

# Banker's Algorithm: Example

**Q2:** What is the content of the NEED matrix?

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1						
	T <sub>1</sub>	1	7	5	1	0	0						
	T <sub>2</sub>	2	3	5	1	3	5						
	T <sub>3</sub>	0	6	5	0	6	3						
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

**Q2:** What is the content of the NEED matrix?

$$NEED[i, j] = MAX[i, j] - ALLOCATION[i, j]$$

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1						
	T <sub>1</sub>	1	7	5	1	0	0						
	T <sub>2</sub>	2	3	5	1	3	5						
	T <sub>3</sub>	0	6	5	0	6	3						
	Total				2	9	9	1	5	2			



# Banker's Algorithm: Example

**Q2:** What is the content of the NEED matrix?

$$NEED[i, j] = MAX[i, j] - ALLOCATION[i, j]$$

		RESOURCES									NEED		
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0-0 = 0		
	T <sub>1</sub>	1	7	5	1	0	0						
	T <sub>2</sub>	2	3	5	1	3	5						
	T <sub>3</sub>	0	6	5	0	6	3						
Total					2	9	9	1	5	2			

# Banker's Algorithm: Example

**Q2:** What is the content of the NEED matrix?

$$NEED[i, j] = MAX[i, j] - ALLOCATION[i, j]$$

		RESOURCES									NEED		
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0-0=0	
	T <sub>1</sub>	1	7	5	1	0	0						
	T <sub>2</sub>	2	3	5	1	3	5						
	T <sub>3</sub>	0	6	5	0	6	3						
Total					2	9	9	1	5	2			

# Banker's Algorithm: Example

**Q2:** What is the content of the NEED matrix?

$$NEED[i, j] = MAX[i, j] - ALLOCATION[i, j]$$

		RESOURCES									NEED		
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	1-1 = 0
	T <sub>1</sub>	1	7	5	1	0	0						
	T <sub>2</sub>	2	3	5	1	3	5						
	T <sub>3</sub>	0	6	5	0	6	3						
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

**Q2:** What is the content of the NEED matrix?

$$NEED[i, j] = MAX[i, j] - ALLOCATION[i, j]$$

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

Q3: Is the system in a safe state? Why?

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

Let's start with  $T_0$

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

Eventually,  $T_0$  finishes and releases all its resources

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

$T_1$  can't execute as it still might NEED (0, 7, 5) and AVAILABLE = (1, 5, 3)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	8	1	5	3			



# Banker's Algorithm: Example

$T_2$  can execute as it still might NEED (1, 0, 0) and **AVAILABLE** = (1, 5, 3)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	8	1	5	3			

# Banker's Algorithm: Example

$T_2$  can execute as it still might NEED (1, 0, 0) and  $AVAILABLE = (1, 5, 3)$

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	2	3	5				0	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				3	9	8	0	5	3			

# Banker's Algorithm: Example

$T_2$  eventually finishes and releases all its resources

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				1	6	3	2			8	8	

# Banker's Algorithm: Example

$T_3$  can execute as it still might NEED (0, 0, 2) and **AVAILABLE** = (2, 8, 8)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				1	6	3	2	8	8			

# Banker's Algorithm: Example

$T_3$  can execute as it still might NEED (0, 0, 2) and **AVAILABLE** = (2, 3, 6)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	0	6	5				0	0	0
	Total				1	6	5	2	8	6			

# Banker's Algorithm: Example

$T_3$  eventually finishes and releases all its resources

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	-	-	-				-	-	-
	Total				1	0	0	2	14	11			

# Banker's Algorithm: Example

$T_1$  can now execute since NEED (0, 7, 5) and AVAILABLE = (2, 14, 11)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	7	5				0	0	0
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	-	-	-				-	-	-
	Total				1	7	5	2					

# Banker's Algorithm: Example

We have found a sequence of execution  $T_0, T_2, T_3, T_1$  which leads to safe state!

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	-	-	-				-	-	-
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	-	-	-				-	-	-
	Total				-	-	-	3	14	11			



# Banker's Algorithm: Example

Q4: If  $T_1$  issues a REQUEST (0, 5, 2), can this be granted immediately?

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

We have to ask ourselves: 1. if the request can be satisfied;  
2. if it will lead to a safe state

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

To answer 1. check if: a. REQUEST  $\leq$  NEED and b. REQUEST  $\leq$  AVAILABLE

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

1.a. REQUEST ≤ NEED?

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

1.a. REQUEST  $\leq$  NEED? YES!  $(0, 5, 2) \leq (0, 7, 5)$

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

1.b. REQUEST  $\leq$  AVAILABLE?

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

1.b. REQUEST  $\leq$  AVAILABLE? YES!  $(0, 5, 2) \leq (1, 5, 2)$

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			

# Banker's Algorithm: Example

To answer **2.** we simulate the request is granted and see if we are still in a safe state

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	0	0				0	7	5
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	9	9	1	5	2			



# Banker's Algorithm: Example

To answer **2.** we simulate the request is granted and see if we are still in a safe state

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	14	11	1	0	0			

# Banker's Algorithm: Example

Let's start with  $T_0$

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	0	0	1				0	0	0
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	14	11	1	0	0			

# Banker's Algorithm: Example

Eventually,  $T_0$  finishes and releases all its resources

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	14	10	1	0	1			

# Banker's Algorithm: Example

$T_1$  can't execute as it still might NEED (0, 2, 3) and AVAILABLE = (1, 0, 1)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	14	10	1	0	1			

# Banker's Algorithm: Example

$T_2$  can execute as it still might NEED (1, 0, 0) and **AVAILABLE** = (1, 0, 1)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	1	3	5				1	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				2	14	10	1	0	1			

# Banker's Algorithm: Example

$T_2$  can execute as it still might NEED (1, 0, 0) and **AVAILABLE** = (1, 0, 1)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	2	3	5				0	0	0
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				3	14	10	0	0	1			

# Banker's Algorithm: Example

$T_2$  eventually finishes and releases all its resources

		RESOURCES												
		MAX			ALLOCATION			AVAILABLE						
		A	B	C	A	B	C	A	B	C	A	B	C	
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-	
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3	
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-	
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2	
	Total				1	11	5	2			3	6		

# Banker's Algorithm: Example

$T_3$  can execute as it still might NEED (0, 0, 2) and **AVAILABLE** = (2, 3, 6)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	0	6	3				0	0	2
	Total				1	11	5	2	3	6			



# Banker's Algorithm: Example

$T_3$  can execute as it still might NEED (0, 0, 2) and **AVAILABLE** = (2, 3, 6)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	0	6	5				0	0	0
	Total				1	11	7	2	3	4			

# Banker's Algorithm: Example

$T_3$  eventually finishes and releases all its resources

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	5	2				0	2	3
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	-	-	-				-	-	-
	Total				1	5	2	2			9	9	

# Banker's Algorithm: Example

$T_1$  can now execute since NEED (0, 2, 3) and **AVAILABLE** = (2, 9, 9)

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	1	7	5				0	0	0
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	-	-	-				-	-	-
	Total				1	7	5	2					

# Banker's Algorithm: Example

We have found a sequence of execution  $T_0, T_2, T_3, T_1$  which leads to safe state!

		RESOURCES											
		MAX			ALLOCATION			AVAILABLE					
		A	B	C	A	B	C	A	B	C	A	B	C
T H R E A D S	T <sub>0</sub>	0	0	1	-	-	-				-	-	-
	T <sub>1</sub>	1	7	5	-	-	-				-	-	-
	T <sub>2</sub>	2	3	5	-	-	-				-	-	-
	T <sub>3</sub>	0	6	5	-	-	-				-	-	-
	Total				-	-	-	3	14	11			

# Summary

- **Deadlock** → a situation in which a set of threads/processes cannot proceed because each one requires resources held by another

# Summary

- **Deadlock** → a situation in which a set of threads/processes cannot proceed because each one requires resources held by another
- **Detection and Recovery** → recognize deadlock after it has occurred and break it

# Summary

- **Deadlock** → a situation in which a set of threads/processes cannot proceed because each one requires resources held by another
- **Detection and Recovery** → recognize deadlock after it has occurred and break it
- **Prevention** → design resource allocation strategies which guarantee at least one of the 4 necessary deadlock conditions never holds

# Summary

- **Deadlock** → a situation in which a set of threads/processes cannot proceed because each one requires resources held by another
- **Detection and Recovery** → recognize deadlock after it has occurred and break it
- **Prevention** → design resource allocation strategies which guarantee at least one of the 4 necessary deadlock conditions never holds
- **Avoidance** → runtime checks to avoid deadlock online



# Summary

In practice, most OSs don't do anything and leave it all to applications

