Systems and Networking I

Applied Computer Science and Artificial Intelligence

2023-2024

SAPIENZA
UNIVERSITÀ DI ROMA

Gabriele Tolomei

Dipartimento di Informatica

Sapienza Università di Roma

tolomei@di.uniroma1.it

Where Are We?

- So far, we have addressed:
  - Processes and Threads
  - CPU Scheduling
  - Synchronization and Deadlock

Where Are We?

- So far, we have addressed:
  - Processes and Threads
  - CPU Scheduling
  - Synchronization and Deadlock
- Today, we will be talking about:
  - Memory Management

Where Are We?

- So far, we have addressed:
  - Processes and Threads
  - CPU Scheduling
  - Synchronization and Deadlock
- Today, we will be talking about:
  - Memory Management
- … Later on:
  - File Systems and I/O Storage
  - Advanced Topics (?)

Part IV: Memory Management

Goals of Memory Management

- Allocate memory resources among multiple competing processes
  - maximizing memory utilization and system throughput

Goals of Memory Management

- Allocate memory resources among multiple competing processes
  - maximizing memory utilization and system throughput
- Guarantee isolation between processes
  - addressability and protection

Goals of Memory Management

- Allocate memory resources among multiple competing processes
  - maximizing memory utilization and system throughput
- Guarantee isolation between processes
  - addressability and protection
- Provide a convenient abstraction to the programmer
  - illusion of unlimited amount of memory

From Source Code To Binary Executable

- User programs typically refer to instructions and data with **symbolic names**, such as "+", "&&", "x", "count", etc.

From Source Code To Binary Executable

- User programs typically refer to instructions and data with **symbolic names**, such as "+", "&&", "x", "count", etc.
- For a user program to be executed it first needs to be:
  1) **Translated** from source code to binary executable and stored on disk

From Source Code To Binary Executable

- User programs typically refer to instructions and data with **symbolic names**, such as "+", "&&", "x", "count", etc.
- For a user program to be executed it first needs to be:
  1) **Translated** from source code to binary executable and stored on disk
  2) **Loaded** from disk into main memory (RAM)

From Source Code To Binary Executable

- Translation is done via Compiler/Assembler/Linker

From Source Code To Binary Executable

- Translation is done via Compiler/Assembler/Linker
- Loading is done by the (OS) Loader

From Source Code To Binary Executable

- Translation is done via Compiler/Assembler/Linker
- Loading is done by the (OS) Loader

NOTE:
In case of purely-interpreted language implementations, translation from source code to executable is done "on-the-fly" by the loaded interpreter

CPU Must Refer To Memory Addresses

- CPU repeatedly fetches, decodes, and executes instructions from memory while executing a program

CPU Must Refer To Memory Addresses

- CPU repeatedly fetches, decodes, and executes instructions from memory while executing a program
- Most instructions involve retrieving data from memory or storing data in memory, or both

CPU Must Refer To Memory Addresses

- CPU repeatedly fetches, decodes, and executes instructions from memory while executing a program
- Most instructions involve retrieving data from memory or storing data in memory, or both
- Memory chips only respond to actual physical addresses

CPU Must Refer To Memory Addresses

- CPU repeatedly fetches, decodes, and executes instructions from memory while executing a program
- Most instructions involve retrieving data from memory or storing data in memory, or both
- Memory chips only respond to actual physical addresses
- It turns out that symbolic names used by user programs must be eventually bound to actual physical memory addresses

CPU Must Refer To Memory Addresses

- CPU repeatedly fetches, decodes, and executes instructions from memory while executing a program
- Most instructions involve retrieving data from memory or storing data in memory, or both
- Memory chips only respond to actual physical addresses
- It turns out that symbolic names used by user programs must be eventually bound to actual physical memory addresses

How?

Generating Memory Addresses: Example

```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

Generating Memory Addresses: Example

```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

x is a symbolic name

Generating Memory Addresses: Example

```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

x is a symbolic name

```
128: MOV %R1, [%R2] // assuming R2 contains the
                    // address of x in memory
136: ADD 5, %R1
144: MOV [%R2], %R1
```

Generating Memory Addresses: Example

```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

x is a symbolic name

```
128: MOV %R1, [%R2] // assuming R2 contains the
                    // address of x in memory
136: ADD 5, %R1
144: MOV [%R2], %R1
```

references to logical addresses containing both instructions and data

Generating Memory Addresses: Example

```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

x is a symbolic name

```
128: MOV %R1, [%R2] // assuming R2 contains the
                    // address of x in memory
136: ADD 5, %R1
144: MOV [%R2], %R1
```

references to logical addresses containing both instructions and data

1. Fetch instruction at address 128

Generating Memory Addresses: Example

```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

x is a symbolic name

```
128: MOV %R1, [%R2] // assuming R2 contains the
                    // address of x in memory
136: ADD 5, %R1
144: MOV [%R2], %R1
```

references to logical addresses containing both instructions and data

1. Fetch instruction at address `128`
2. Execute istruction: load from address `[%R2]` (e.g., `1234`)

Generating Memory Addresses: Example

```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

x is a symbolic name

```
128: MOV %R1, [%R2] // assuming R2 contains the
                    // address of x in memory
136: ADD 5, %R1
144: MOV [%R2], %R1
```

references to logical addresses containing both instructions and data

1. Fetch instruction at address `128`
2. Execute istruction: load from address `[%R2]` (e.g., `1234`)
3. Fetch instruction at address `136`
4. Execute instruction: addition (no memory reference)
5. Fetch instruction at address `144`
6. Execute instruction: store to address `[%R2]` (`1234`)

Symbolic Name vs. Logical vs. Physical Address

symbolic name: symbolic memory reference used by user programs

Symbolic Name vs. Logical vs. Physical Address

symbolic name: symbolic memory reference used by user programs



logical address: memory address generated by user programs via the CPU

Symbolic Name vs. Logical vs. Physical Address

symbolic name: symbolic memory reference used by user programs



logical address: memory address generated by user programs via the CPU

physical address: actual memory address which memory chip operates on

Address Binding

Mapping from logical to physical address

Address Binding



Address Binding



Address Binding



Address Binding: Compile Time

- The starting physical location `k` of a program in memory is known at compile time (e.g., `k = 0`)

Address Binding: Compile Time

- The starting physical location `k` of a program in memory is known at compile time (e.g., `k = 0`)
- The compiler generates so-called **absolute code**

Address Binding: Compile Time

- The starting physical location `k` of a program in memory is known at compile time (e.g., `k = 0`)
- The compiler generates so-called **absolute code**
- No intervention by the OS

Address Binding: Compile Time

- The starting physical location `k` of a program in memory is known at compile time (e.g., `k = 0`)
- The compiler generates so-called **absolute code**
- No intervention by the OS
- physical address == logical address

Address Binding: Compile Time

- The starting physical location `k` of a program in memory is known at compile time (e.g., `k = 0`)
- The compiler generates so-called **absolute code**
- No intervention by the OS
- physical address == logical address

What if the starting physical memory address `k` where the program is loaded changes into `k'` at some point later?

Address Binding: Compile Time

- The starting physical location `k` of a program in memory is known at compile time (e.g., `k = 0`)
- The compiler generates so-called **absolute code**
- No intervention by the OS
- physical address == logical address

What if the starting physical memory address `k` where the program is loaded changes into `k'` at some point later?

The program must be recompiled!

Address Binding: Compile Time




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

Address Binding: Compile Time

starting physical address known by the compiler (e.g., `k = 0`)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

Address Binding: Compile Time

starting physical address known by the compiler (e.g., `k = 0`)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

Address Binding: Compile Time

starting physical address known by the compiler (e.g., `k = 0`)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

logical addresses do not change after they are emitted as the result of compilation/assembling

Address Binding: Compile Time

starting physical address known by the compiler (e.g., `k = 0`)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

logical addresses do not change after they are emitted as the result of compilation/assembling

physical addresses == logical addresses

Address Binding: Load Time

- If the starting physical location `k` of a program is not known at compile time

Address Binding: Load Time

- If the starting physical location `k` of a program is not known at compile time
- The compiler generates (**statically**) **relocatable code**, which references relative addresses to `k`

Address Binding: Load Time

- If the starting physical location `k` of a program is not known at compile time
- The compiler generates (**statically**) **relocatable code**, which references relative addresses to `k`
- The OS loader determines each process' starting physical location `k`

Address Binding: Load Time

- If the starting physical location `k` of a program is not known at compile time
- The compiler generates (**statically**) **relocatable code**, which references relative addresses to `k`
- The OS loader determines each process' starting physical location `k`
- physical address == logical address

Address Binding: Load Time

- If the starting physical location `k` of a program is not known at compile time
- The compiler generates (**statically**) **relocatable code**, which references relative addresses to `k`
- The OS loader determines each process' starting physical location `k`
- physical address == logical address

What if the OS decides to use a different starting physical memory address `k'`?

Address Binding: Load Time

- If the starting physical location `k` of a program is not known at compile time
- The compiler generates (**statically**) **relocatable code**, which references relative addresses to `k`
- The OS loader determines each process' starting physical location `k`
- physical address == logical address

What if the OS decides to use a different starting physical memory address `k'`?

The program must be reloaded but not recompiled!

Address Binding: Load Time




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

Address Binding: Load Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

Address Binding: Load Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

Address Binding: Load Time

compiler still assumes addresses starting from `0`

starting physical address known by the loader (e.g., `k = 100`)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

Address Binding: Load Time

compiler still assumes addresses starting from `0`

starting physical address known by the loader (e.g., `k = 100`)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

```
228: MOV %R1, [%R2+100]
236: ADD 5, %R1
244: MOV [%R2+100], %R1
```

Address Binding: Load Time

compiler still assumes addresses starting from 0

starting physical address known by the loader (e.g., k = 100)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

```
228: MOV %R1, [%R2+100]
236: ADD 5, %R1
244: MOV [%R2+100], %R1
```

The OS loader updates logical addresses before loading the executable

Address Binding: Load Time

compiler still assumes addresses starting from `0`

starting physical address known by the loader (e.g., `k = 100`)




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

```
228: MOV %R1, [%R2+100]
236: ADD 5, %R1
244: MOV [%R2+100], %R1
```

The OS loader updates logical addresses before loading the executable

physical addresses == logical addresses

Address Binding: Execution Time

- If the program can be moved around in main memory during its execution

Address Binding: Execution Time

- If the program can be moved around in main memory during its execution
- The compiler generates (dynamically) relocatable code or virtual addresses

Address Binding: Execution Time

- If the program can be moved around in main memory during its execution
- The compiler generates (**dynamically**) **relocatable code** or **virtual addresses**
- The OS maps virtual addresses to physical memory locations using special HW support (MMU)

Address Binding: Execution Time

- If the program can be moved around in main memory during its execution
- The compiler generates (**dynamically**) **relocatable code** or **virtual addresses**
- The OS maps virtual addresses to physical memory locations using special HW support (MMU)
- physical address != logical/virtual address

Address Binding: Execution Time

- If the program can be moved around in main memory during its execution
- The compiler generates (**dynamically**) **relocatable code** or **virtual addresses**
- The OS maps virtual addresses to physical memory locations using special HW support (MMU)
- physical address != logical/virtual address

Most flexible solution implemented by the majority of modern OSs

Address Binding: Execution Time




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

Address Binding: Execution Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

Address Binding: Execution Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

Address Binding: Execution Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

MMU

Address Binding: Execution Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

logical/virtual address

136

MMU

Address Binding: Execution Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

logical/virtual address

136

MMU

physical address

42086

Address Binding: Execution Time

compiler still assumes addresses starting from 0




```
void foo() {
    int x = 42;
    …
    x = x + 5;
    …
}
```

```
128: MOV %R1, [%R2]
136: ADD 5, %R1
144: MOV [%R2], %R1
```

logical/virtual address

136

MMU

physical address

42086

Every logical address referenced by the CPU is translated by HW at run time

physical addresses != logical addresses

Manage Uniprogramming Memory

- Easiest memory management requirements

Manage Uniprogramming Memory

- Easiest memory management requirements
- The OS gets a fixed part of physical memory (e.g., highest memory addresses in MS-DOS)

Manage Uniprogramming Memory

- Easiest memory management requirements
- The OS gets a fixed part of physical memory (e.g., highest memory addresses in MS-DOS)
- Run one process at a time, always loaded starting at physical address `k = 0` up to maximum address (`memory_size - os_size - 1`)

Manage Uniprogramming Memory

- Easiest memory management requirements
- The OS gets a fixed part of physical memory (e.g., highest memory addresses in MS-DOS)
- Run one process at a time, always loaded starting at physical address `k = 0` up to maximum address (`memory_size - os_size - 1`)
- Each process executes in a contiguous segment of memory

Manage Uniprogramming Memory

- Easiest memory management requirements
- The OS gets a fixed part of physical memory (e.g., highest memory addresses in MS-DOS)
- Run one process at a time, always loaded starting at physical address `k = 0` up to maximum address (`memory_size - os_size - 1`)
- Each process executes in a contiguous segment of memory
- Address binding can occur at compile time

Manage Uniprogramming Memory

```
memory_size = 4000B = 4kB
```



Manage Uniprogramming Memory

memory_size = 4000B = 4kB	os_size = 500B



Manage Uniprogramming Memory

memory_size = 4000B = 4kB	os_size = 500B	k = 0	free_space = 3.5kB



Manage Uniprogramming Memory

memory_size = 4000B = 4kB	os_size = 500B	k = 0	free_space = 3.5kB



Manage Uniprogramming Memory



Manage Uniprogramming Memory



Manage Uniprogramming Memory



Manage Uniprogramming Memory



Very simple! But only one process executes at a time and no OS protection

Manage Multiprogramming Memory: Goals (1)

- **Sharing**
  - Several processes coexist in main memory at the same time
  - Cooperating processes can share portions of address space

Manage Multiprogramming Memory: Goals (1)

- **Sharing**
  - Several processes coexist in main memory at the same time
  - Cooperating processes can share portions of address space
- **Transparency**
  - Processes should not be aware that memory is shared
  - Processes should not be aware of which portions of physical memory they are assigned to

Manage Multiprogramming Memory: Goals (2)

- **Protection/Security**
  - Processes must not be able to corrupt each other or the OS
  - Processes must not be able to read data of other processes

Manage Multiprogramming Memory: Goals (2)

- **Protection/Security**
  - Processes must not be able to corrupt each other or the OS
  - Processes must not be able to read data of other processes
- **Efficiency**
  - CPU and memory performance should not degrade badly due to sharing
  - Keep memory fragmentation low

Relocation: Initial Idea

- Assume the OS is allocated to the highest memory addresses

Relocation: Initial Idea

- Assume the OS is allocated to the highest memory addresses
- Assume logical addresses generated by each user process starts at `0` up to (`memory_size - os_size - 1`)

Relocation: Initial Idea

- Assume the OS is allocated to the highest memory addresses
- Assume logical addresses generated by each user process starts at `0` up to (`memory_size - os_size - 1`)
- Load a process by allocating the first **contiguous segment** of memory in which the process fits

Relocation: Initial Idea

- Assume the OS is allocated to the highest memory addresses
- Assume logical addresses generated by each user process starts at `0` up to (`memory_size - os_size - 1`)
- Load a process by allocating the first **contiguous segment** of memory in which the process fits
- Allow transparent sharing of memory: each process' address space may be placed anywhere in memory

Static Relocation

- The OS loader rewrites the addresses generated by a process to main memory addresses (**load time binding**)

Static Relocation

- The OS loader rewrites the addresses generated by a process to main memory addresses (**load time binding**)
- PRO:
  - No HW support is needed

Static Relocation

- The OS loader rewrites the addresses generated by a process to main memory addresses (**load time binding**)
- PRO:
  - No HW support is needed
- CONs:
  - No protection/privacy → processes can corrupt the OS or other processes
  - Address space must be allocated contiguously → assuming worst-case stack and heap request
  - The OS cannot move a process (address space) once allocated in memory

Static Relocation



Static Relocation



Static Relocation



Dynamic Relocation

- Protect OS and processes from one another

Dynamic Relocation

- Protect OS and processes from one another
- Requires hardware support (Memory Management Unit)

Dynamic Relocation

- Protect OS and processes from one another
- Requires hardware support (Memory Management Unit)
- Address binding at execution/run time

Dynamic Relocation

- Protect OS and processes from one another
- Requires hardware support (Memory Management Unit)
- Address binding at execution/run time
- MMU dynamically translates each logical/virtual address generated by a process into a corresponding physical address

Dynamic Relocation

- Protect OS and processes from one another
- Requires hardware support (Memory Management Unit)
- Address binding at execution/run time
- MMU dynamically translates each logical/virtual address generated by a process into a corresponding physical address



Dynamic Relocation

- Protect OS and processes from one another
- Requires hardware support (Memory Management Unit)
- Address binding at execution/run time
- MMU dynamically translates each logical/virtual address generated by a process into a corresponding physical address

HW Support for Dynamic Relocation

- MMU contains at least 2 registers:

HW Support for Dynamic Relocation

- MMU contains at least 2 registers:
  - base → start physical memory location of address space

HW Support for Dynamic Relocation

- MMU contains at least 2 registers:
  - base → start physical memory location of address space
  - limit → size limit of address space

HW Support for Dynamic Relocation

- MMU contains at least 2 registers:
  - base → start physical memory location of address space
  - limit → size limit of address space
- CPU supports at least 2 operating modes:

HW Support for Dynamic Relocation

- MMU contains at least 2 registers:
  - base → start physical memory location of address space
  - limit → size limit of address space
- CPU supports at least 2 operating modes:
  - privileged (kernel) mode when the OS is running
    - after issuing any trap (system call, interruption, or exception)
    - when manipulating sensitive resources (e.g., the content of MMU registers)

HW Support for Dynamic Relocation

- MMU contains at least 2 registers:
  - base → start physical memory location of address space
  - limit → size limit of address space
- CPU supports at least 2 operating modes:
  - privileged (kernel) mode when the OS is running
    - after issuing any trap (system call, interruption, or exception)
    - when manipulating sensitive resources (e.g., the content of MMU registers)
  - user mode when user process is running
    - while executing process instructions on the CPU

Base and Limit Registers: Idea



Each process is given a contiguous segment of main memory when loaded

Base and Limit Registers: Idea



Each process is given a contiguous segment of main memory when loaded

As such, each process can only access to memory locations belonging to the segment it is assigned to

Base and Limit Registers: Idea



Each process is given a contiguous segment of main memory when loaded

As such, each process can only access to memory locations belonging to the segment it is assigned to

Protection implemented using two MMU registers: base and limit

Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process

Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Implementing Dynamic Relocation

CPU must check every memory access generated in user mode (i.e., by a user process) is within the correct [base, base + limit) range for that process



Dynamic Relocation

- PROs:
  - Provides protection (both read and write) across address spaces
  - OS can easily move a process during execution
  - OS can allow process to dynamically grow over time
  - Simple, fast hardware implementation (MMU):
    - 2 special registers, one add and one compare operation (can be done in parallel)

Dynamic Relocation

- CONs:
  - Little hardware overhead to pay at each memory reference
  - Each process must still be allocated contiguously in physical memory (possible memory waste)
  - Process is still limited to physical memory size
  - Degree of multiprogramming is bound since all memory of all active processes must fit in memory
  - No partial sharing of address space (e.g., processes can't share program's text)

Relocation: Properties

- Sharing/Transparency → processes are unaware of sharing memory
- Protection/Security → each memory reference is checked in HW
- Efficiency → somewhat achieved but if a process grows it may need to be moved to other location (very slow)

Relocation: Properties

Static Relocation

- Sharing/Transparency → processes are unaware of sharing memory
- Protection/Security → each memory reference is checked in HW
- Efficiency → somewhat achieved but if a process grows it may need to be moved to other location (very slow)

Relocation: Properties

Dynamic Relocation

- Sharing/Transparency → processes are unaware of sharing memory
- Protection/Security → each memory reference is checked in HW
- Efficiency → somewhat achieved but if a process grows it may need to be moved to other location (very slow)

Summary

- Effective memory management is crucial for system performance
- Very basic management doesn't even require OS intervention
- When memory is multiplexed across several processes (multiprogramming) the OS must step in!

Summary

- Modern OSs manage memory ensuring:
  - Transparency → logical/virtual vs. physical address space
  - Protection/Flexibility → dynamic relocation
  - Efficiency → hardware support (e.g., MMU)
- We are still assuming the whole virtual address space of a process is fully and contiguously loaded in main memory → **serious limitation!**