

Teoria degli Algoritmi

Corso di Laurea Magistrale in Matematica Applicata

a.a. 2020-21



SAPIENZA
UNIVERSITÀ DI ROMA

Gabriele Tolomei

Dipartimento di Informatica

Sapienza Università di Roma

tolomei@di.uniroma1.it

Recap from Last Lecture(s)

2 unsupervised learning techniques to extract "structural" patterns from raw data

Recap from Last Lecture(s)

2 unsupervised learning techniques to extract "structural" patterns from raw data



Clustering

- Group together similar objects according to a specific distance function
- Formalized as an NP-hard optimization problem
- K-means and its variants as effective heuristics that work in practice

Recap from Last Lecture(s)

2 unsupervised learning techniques to extract "structural" patterns from raw data



Clustering

- Group together similar objects according to a specific distance function
- Formalized as an NP-hard optimization problem
- K-means and its variants as effective heuristics that work in practice

Principal Component Analysis (PCA)

- Reduce data dimensionality
- Automatically extract features from raw data
- Resort to computing the eigenvectors and eigenvalues of the covariance matrix

SUPERVISED LEARNING

Human vs. Computer

- Computers are designed to be **programmed** by humans in order to solve a task/problem quicker and better than humans

Human vs. Computer

- Computers are designed to be **programmed** by humans in order to solve a task/problem quicker and better than humans
- Example
 - **Task/Problem:** Find the maximum element of a list of 1 million unsorted numbers

Human vs. Computer

- Computers are designed to be **programmed** by humans in order to solve a task/problem quicker and better than humans
- Example
 - **Task/Problem**: Find the maximum element of a list of 1 million unsorted numbers
 - **Solution/Algorithm**: Scan all the numbers in the set and keep track of the largest found "so far"

Human vs. Computer

- Computers are designed to be **programmed** by humans in order to solve a task/problem quicker and better than humans
- Example
 - **Task/Problem**: Find the maximum element of a list of 1 million unsorted numbers
 - **Solution/Algorithm**: Scan all the numbers in the set and keep track of the largest found "so far"
 - **Code/Program**: Encode the algorithm above into one specific programming language (e.g., C/C++, Java, Python)

Programming a Computer



Problem


Programming a Computer

Problem


Solution/Algorithm
explicitly designed by human




Programming a Computer




Programming a Computer




Programming a Computer



Programming a Computer




Programming a Computer



Can We Always Do That?

Chihuahua or Muffin?



[Copyright @teenybiscuit]

Chihuahua



Muffin



Programming vs. "Training" a Computer


- There exist some problems like the **chihuahua** vs. **muffin** above which are too hard to be solved directly

Programming vs. "Training" a Computer

- There exist some problems like the **chihuahua** vs. **muffin** above which are too hard to be solved directly
- Hard to design an algorithm which is general enough to capture all the nuances of the problem and gives the correct output for any input

Programming vs. "Training" a Computer

- There exist some problems like the **chihuahua** vs. **muffin** above which are too hard to be solved directly
- Hard to design an algorithm which is general enough to capture all the nuances of the problem and gives the correct output for any input



Programming vs. "Training" a Computer


"Training" a Computer

Problem




Labeled Data


"Training" a Computer




"Training" a Computer




"Training" a Computer




"Training" a Computer



"Training" a Computer



"Training" a Computer



Eventually, the function f is **learned** by the learning algorithm from a (large) set of **labeled data**

Machine Learning

- A broad discipline concerned with how to teach machines to learn (i.e., extract knowledge) from data

Machine Learning

- A broad discipline concerned with how to teach machines to learn (i.e., extract knowledge) from data
- 2 main definitions of it:

Machine Learning

- A broad discipline concerned with how to teach machines to learn (i.e., extract knowledge) from data
- 2 main definitions of it:

"The field of study that gives computers the ability to learn without being explicitly programmed"

Arthur Samuel

Machine Learning

- A broad discipline concerned with how to teach machines to learn (i.e., extract knowledge) from data
- 2 main definitions of it:

"The field of study that gives computers the ability to learn without being explicitly programmed"

Arthur Samuel

"A computer program is said to learn from experience E with respect to some class of tasks T and performance measure P , if its performance at tasks in T , as measured by P , improves with experience E "

Tom Mitchell

Machine Learning: Taxonomy

Machine Learning

Machine Learning: Taxonomy


Machine Learning




Unsupervised Learning

Extract patterns from input data without any information on the output (target) variable


Machine Learning: Taxonomy



Machine Learning: Taxonomy



Machine Learning: Taxonomy



Supervised Learning: What Do We Predict?

Supervised Learning

Supervised Learning: What Do We Predict?


Supervised Learning



Regression

The target y we want to predict is a
continuous real value
e.g., $y = \text{price of a house}$

Supervised Learning: What Do We Predict?



A Bit of Notation

$$\mathcal{X} \subseteq \mathbb{R}^n$$

input feature space

A Bit of Notation

$$\mathcal{X} \subseteq \mathbb{R}^n$$

\mathcal{Y}

input feature space

output space

A Bit of Notation

$$\mathcal{X} \subseteq \mathbb{R}^n$$

input feature space

\mathcal{Y}

output space

$$\mathcal{Y} \subseteq \mathbb{R}$$

real-value label (**regression**)

$$\mathcal{Y} = \{1, \dots, k\}$$

discrete-value label (**k-ary classification**)

A Bit of Notation

$$\mathcal{X} \subseteq \mathbb{R}^n$$

input feature space

$$\mathcal{Y}$$

output space

$$\mathcal{Y} \subseteq \mathbb{R}$$

real-value label (**regression**)

$$\mathcal{Y} = \{1, \dots, k\}$$

discrete-value label (**k-ary classification**)

$$(\mathbf{x}_i, y_i)$$

i -th labeled instance

A Bit of Notation

$$\mathcal{X} \subseteq \mathbb{R}^n$$

input feature space

$$\mathcal{Y}$$

output space

$$\mathcal{Y} \subseteq \mathbb{R}$$

real-value label (**regression**)

$$\mathcal{Y} = \{1, \dots, k\}$$

discrete-value label (**k-ary classification**)

$$(\mathbf{x}_i, y_i)$$

i -th labeled instance

$$\mathbf{x}_i = (x_{i,1}, \dots, x_{i,n}) \in \mathcal{X}$$

n -dimensional feature vector of the i -th instance

A Bit of Notation

$$\mathcal{X} \subseteq \mathbb{R}^n$$

input feature space

$$\mathcal{Y}$$

output space

$$\mathcal{Y} \subseteq \mathbb{R}$$

real-value label (**regression**)

$$\mathcal{Y} = \{1, \dots, k\}$$

discrete-value label (**k-ary classification**)

$$(\mathbf{x}_i, y_i)$$

i -th labeled instance

$$\mathbf{x}_i = (x_{i,1}, \dots, x_{i,n}) \in \mathcal{X}$$

n -dimensional feature vector of the i -th instance

$$y_i \in \mathcal{Y}$$

label of the i -th instance

A Bit of Notation

$$\mathcal{X} \subseteq \mathbb{R}^n$$

input feature space

$$\mathcal{Y}$$

output space

$$\mathcal{Y} \subseteq \mathbb{R}$$

real-value label (**regression**)

$$\mathcal{Y} = \{1, \dots, k\}$$

discrete-value label (**k-ary classification**)

$$(\mathbf{x}_i, y_i)$$

i -th labeled instance

$$\mathbf{x}_i = (x_{i,1}, \dots, x_{i,n}) \in \mathcal{X}$$

n -dimensional feature vector of the i -th instance


$$y_i \in \mathcal{Y}$$

label of the i -th instance


$$\mathcal{D} = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_m, y_m)\}$$

dataset of m **i.i.d.** labeled instances


Model Training: Labeled Dataset



Model Training: Labeled Dataset




Model Training: Labeled Dataset



Model Training: Labeled Dataset

Each instance comes with the **class label** (**classification**) or the **value** (**regression**) we want to predict



Model Training: Intuition

Idea

There is an **unknown target function** f which puts in a relationship elements of X with elements of Y

Model Training: Intuition

Idea

There is an **unknown target function** f which puts in a relationship elements of X with elements of Y



$$f = X \rightarrow Y$$

Model Training: Intuition

Idea

There is an **unknown target function** f which puts in a relationship elements of X with elements of Y



$$f = X \rightarrow Y$$



Problem

We cannot write down an algorithm which just implements f

Model Training: Learning f from Labeled Data

- Learning f means "finding" another function h^* which best approximates f using the data we observed

Model Training: Learning f from Labeled Data

- Learning f means "finding" another function h^* which best approximates f using the data we observed
- h^* is chosen among a family of functions H called **hypothesis space** by specifying two components:

Model Training: Learning f from Labeled Data

- Learning f means "finding" another function h^* which best approximates f using the data we observed
- h^* is chosen among a family of functions H called **hypothesis space** by specifying two components:
 - **loss function**: measures the error of using h^* instead of the true f

Model Training: Learning f from Labeled Data

- Learning f means "finding" another function h^* which best approximates f using the data we observed
- h^* is chosen among a family of functions H called **hypothesis space** by specifying two components:
 - **loss function**: measures the error of using h^* instead of the true f
 - **learning algorithm**: explores the hypothesis space to pick the function which minimizes the loss on the observed data

The Hypothesis Space H



- The set of functions the learning algorithm will search through to pick the hypothesis h^* which best approximates the true target f

The Hypothesis Space H



- The set of functions the learning algorithm will search through to pick the hypothesis h^* which best approximates the true target f
- The larger the hypothesis space:
 - the larger will be the set of functions that can be represented



The Hypothesis Space H

- The set of functions the learning algorithm will search through to pick the hypothesis h^* which best approximates the true target f
- The larger the hypothesis space:
 - the larger will be the set of functions that can be represented 
 - the harder will be for the learning algorithm to pick h^* 

The Hypothesis Space H

- The set of functions the learning algorithm will search through to pick the hypothesis h^* which best approximates the true target f
- The larger the hypothesis space:
 - the larger will be the set of functions that can be represented 
 - the harder will be for the learning algorithm to pick h^* 

Trade-off

Put some constraints on H , e.g., limit the search space only to **linear functions**

The Loss Function

- Measures the error we would make if a hypothesis h is used instead of the true (yet unknown) mapping f

The Loss Function

- Measures the error we would make if a hypothesis h is used instead of the true (yet unknown) mapping f
- It can be computed only on the data we observed, therefore depends on the hypothesis and the dataset

$$L : \mathcal{H} \times \mathcal{D} \mapsto \mathbb{R}$$

The Loss Function

- Measures the error we would make if a hypothesis h is used instead of the true (yet unknown) mapping f
- It can be computed only on the data we observed, therefore depends on the hypothesis and the dataset

$$L : \mathcal{H} \times \mathcal{D} \mapsto \mathbb{R}$$

- This **in-sample error** (a.k.a. empirical loss) is an estimate of the **out-of-sample error** (a.k.a. expected loss or risk)

The Learning Algorithm

- Defines the strategy we use to search the hypothesis space H for picking our **best** hypothesis h^*

The Learning Algorithm

- Defines the strategy we use to search the hypothesis space H for picking our **best** hypothesis h^*
- Here, "**best**" means the hypothesis that **minimizes** the loss function on the observed data (**Empirical Risk Minimization**)

The Learning Algorithm

- Defines the strategy we use to search the hypothesis space H for picking our **best** hypothesis h^*
- Here, "**best**" means the hypothesis that **minimizes** the loss function on the observed data (**Empirical Risk Minimization**)
- In other words, among all the hypotheses specified by H the learning algorithm will pick the one that minimizes L

The Learning Algorithm

- Defines the strategy we use to search the hypothesis space H for picking our **best** hypothesis h^*
- Here, "**best**" means the hypothesis that **minimizes** the loss function on the observed data (**Empirical Risk Minimization**)
- In other words, among all the hypotheses specified by H the learning algorithm will pick the one that minimizes L as measured on D


$$h^* = \operatorname{argmin}_{h \in \mathcal{H}} L(h, \mathcal{D})$$

unknown target
(e.g., ideal credit approval function)

$$f = X \rightarrow Y$$


unknown target
(e.g., ideal credit approval function)

$$f = X \rightarrow Y$$



A diagram showing a grid of training data. It consists of two rows of three blue squares each, followed by a vertical ellipsis. To the right of the blue squares are three green squares, followed by a horizontal ellipsis. This represents a set of feature-target pairs.

...




A second row of the training data grid, identical in structure to the first, showing two rows of three blue squares each, followed by a vertical ellipsis, and three green squares followed by a horizontal ellipsis.

$(x_1, y_1), (x_2, y_2), \dots, (x_m, y_m)$

training data D
(e.g., historical records of customers)

unknown target
(e.g., ideal credit approval function)

$$f = X \rightarrow Y$$




Hypothesis Space

H

candidate formulas


unknown target
(e.g., ideal credit approval function)

$$f = X \rightarrow Y$$



unknown target
(e.g., ideal credit approval function)

$$f = X \rightarrow Y$$



Learning f as an Optimization Problem

- We define the supervised learning problem as an optimization one

Learning f as an Optimization Problem

- We define the supervised learning problem as an optimization one
- By plugging in different loss functions combined with various hypothesis spaces we must solve a specific optimization problem

Learning f as an Optimization Problem

- We define the supervised learning problem as an optimization one
- By plugging in different loss functions combined with various hypothesis spaces we must solve a specific optimization problem
- Those choices are usually "mathematically convenient": e.g., **convex objective functions** are guaranteed to have a unique global minimum

Learning f as an Optimization Problem

- We define the supervised learning problem as an optimization one
- By plugging in different loss functions combined with various hypothesis spaces we must solve a specific optimization problem
- Those choices are usually "mathematically convenient": e.g., **convex objective functions** are guaranteed to have a unique global minimum
- Even though closed-form solutions to the optimization problem rarely exist, there are numerical methods which work: e.g., **gradient descent**

In-Sample vs. Out-of-Sample Error

- Minimizing the loss function on the observed data D just limits the in-sample error

In-Sample vs. Out-of-Sample Error

- Minimizing the loss function on the observed data D just limits the in-sample error
- Our ultimate hypothesis is to pick h^* which is able to generalize to **unseen instances** (i.e., minimize the out-of-sample error)

In-Sample vs. Out-of-Sample Error

- Minimizing the loss function on the observed data D just limits the in-sample error
- Our ultimate hypothesis is to pick h^* which is able to generalize to **unseen instances** (i.e., minimize the out-of-sample error)
- If we pick a hypothesis which just memorizes all the training instances, we will obtain a 0 in-sample error but this is not learning!

In-Sample vs. Out-of-Sample Error


- Minimizing the loss function on the observed data D just limits the in-sample error
- Our ultimate hypothesis is to pick h^* which is able to generalize to **unseen instances** (i.e., minimize the out-of-sample error)
- If we pick a hypothesis which just memorizes all the training instances, we will obtain a 0 in-sample error but this is not learning!
- At the same time we do not want h^* to perform poorly on D

Overfitting (High Variance)

Regression



Classification




The hypothesis h^* is not learning the true f but it mimics its noise

Overfitting (High Variance)


Regression



Classification



The hypothesis h^* is not learning the true f but it mimics its noise




low in-sample error high out-of-sample error

Overfitting (High Variance)


Regression



Classification



The hypothesis h^* is not learning the true f but it mimics its noise




low in-sample error high out-of-sample error


- Regularization
- Get more data

Underfitting (High Bias)

Regression




Classification




The hypothesis h^* is too "simple" for approximating the true f

Underfitting (High Bias)


Regression



Classification




The hypothesis h^* is too "simple" for approximating the true f




high in-sample error high out-of-sample error

Underfitting (High Bias)


Regression



Classification



The hypothesis h^* is too "simple" for approximating the true f



high in-sample error high out-of-sample error


- Increase model complexity
- Add more features

Bias-Variance Tradeoff

Regression



Classification



The hypothesis h^* is just right:
the simplest one explaining the data


Occam's razor

Bias-Variance Tradeoff

Regression




Classification



The hypothesis h^* is just right:
the simplest one explaining the data

Occam's razor



low in-sample error low out-of-sample error

Estimating Generalization Performance

- Measuring the generalization performance online may be too risky


Estimating Generalization Performance

- Measuring the generalization performance online may be too risky
- **Example:** Don't want to deploy your new spam classifier in production knowing only its training (i.e., in-sample) performance


Estimating Generalization Performance

- Measuring the generalization performance online may be too risky
- **Example:** Don't want to deploy your new spam classifier in production knowing only its training (i.e., in-sample) performance
- **Solution:** Estimate the generalization performance using training set
 - As long as it holds true the assumption that training and test instances are both drawn from the same probability distribution (**i.i.d. assumption**)


Dataset Splitting




Dataset Splitting



Dataset Splitting



Dataset Splitting



How Much Data Do We Need?

In general, the more data we have the better we learn

