

Efficient simulation of identity-by-descent and ancestry in large datasets

Georgia Tsambos
University of Melbourne, Australia


Georgia Tsambos (1, 2), Peter Ralph (3), Jerome Kelleher (4), Stephen Leslie (1, 2, 5), Damjan Vukcevic (1, 2). (1) School of Mathematics and Statistics, University of Melbourne, Australia (2) Melbourne Integrative Genomics, University of Melbourne, Australia, (3) Department of Mathematics, University of Oregon, United States, (4) Big Data Institute, University of Oxford, United Kingdom, (5) School of Biosciences, University of Melbourne, Australia.

Presenting author: gtsambos (at) student.unimelb.edu.au

0. Introduction


To assess the performance of methods in population genetics, we often wish to simulate realistic genetic datasets while retaining detailed information about the history of the simulated genomes. This poster briefly describes how we can efficiently simulate genetic information with full information about the common ancestry of particular genomic segments, as well as information about the populations that these segments have been inherited from. Although the software is still under development in **tskit** [1], our progress to date suggests that our methods are scalable and fast enough to be useful in high-powered studies of subtle demographic questions.

1. The data structure: tree sequences



The **tree sequence** data structure [1,2] encodes a complete genealogy for a sample of chromosomes in a succinct set of tables. Compared with traditional sequence-based formats, tree sequences are *compact*, *fast* to process and *informative* of the history of the sample.

3. Example: total IBD sharing over time



5. Acknowledgements, references and further information

GT is funded by the Helen Freeman scholarship, the Maurice Belz Fund and the Australian Government's Research Training Scheme.

[1] <https://tskit.readthedocs.io/en/latest/>


[2] Kelleher, J., et al. (2016). Efficient Coalescent Simulation and Genealogical Analysis for Large Sample Sizes. PLOS Computational Biology, 12(5).

[3] Gladstein, A and Hammer, M. (2019). Substructured Population Growth in the Ashkenazi Jews Inferred with Approximate Bayesian Computation. Molecular Biology and Evolution, 36(6), 1162-1171.

[4] Raynal, L., et al. (2019). ABC random forests for Bayesian parameter inference. Bioinformatics, 35(10), 1720 - 1728.

[5] Csillery, K., et al. (2012). Abc: An R package for approximate Bayesian computation (ABC). Methods in Ecology and Evolution, 3(3), 475 - 479.

2. IBD and ancestry in tree sequences



Questions about inheritance and ancestry can be reframed as questions about the underlying tree sequence that represent our datasets:

- *Identity-by-descent: which samples share a common ancestor where?*
- *Local ancestry: which ancestors have what population labels, and which samples descend from them?*

Extracting this information efficiently is challenging due to correlations in genealogical structure between samples, and across chromosomes; in an upcoming paper, we will describe algorithms that allow us to do this.

4. Application: demography inference

To explore the power of our method, we attempted to recreate some of the important findings from a recent study of Ashkenazi Jewish (AJ) demographic history [3]. This work provided evidence for a recent divergence event between Eastern and Western communities of AJ people. It was estimated that this happened about 15 generations ago.

Closely following [3], we performed 50 000 simulations of various demographic scenarios. For each simulation, we calculated moments of IBD segment lengths at multiple time points. We used the **abcrf** package [4] to infer the most plausible demographic scenario, and the **abc** package [5] with neural-net regression to estimate parameter values.

Results: inference of demographic scenario

Posterior probability	Votes for correct scenario	Prior error rate
93.36% ± 4.69%	0.9633 ± 0.0268	0.0993 ± 0.0008

Results: inference of divergence time

Mode	True value	Our 95% HPDI	95% HPDI in [3]
13.59	14.93	(11.22, 19.90)	(2.00, 29.00)

All simulations and analyses ran on a standard desktop in < 12 hours.

Come say hi!

