

# PyRe: A Cyclus Pyroprocessing Archetype

Greg Westphal  
Advanced Reactors and Fuel Cycles Group

University of Illinois at Urbana-Champaign

November 12, 2018



I L L I N O I S



# Outline

- 1 Motivation
- 2 Methods
- 3 Results
- 4 Future Work



# Motivation

## What is the goal?

PyRe will be used to answer the following questions

- What is the effect of introducing pyroprocessing plants in the fuel cycle?
- How do various facility designs affect throughput and efficiency?
- Where in a pyroprocessing plant will monitoring most effectively detect material diversion?

The first two can be directly answered by the archetype. The third requires data analysis via diversion algorithms.



# Diversion




Figure 1: Diversion detection methods within Cyclus ??.



# Outline

① Motivation

② **Methods**

③ Results

④ Future Work



# Methodology

## How does PyRe work?

PyRe does the following with an input stream and facility configuration parameters:

- Pass fuel to voloxidation.
- Generate efficiencies from parameters.
- Multiply stream by efficiency matrix.
- Record stream compositions.
- Repeat for each process.





# Cyclus

## What is Cyclus?

Cyclus is a modular agent based fuel cycle simulator for tracking commodity transactions between facilities.




Figure 2: Cyclus Archetype framework and API??.



## Why Cyclus?

Cyclus allows the construction of specific scenarios through the addition of archetypes. These archetypes are modular and the transactions can be tracked.




Figure 3: Cyclus tracks material flow through the fuel cycle.





# Assumptions

## Cyclus Requirements

- Modular.
- Time step  $\geq 1$  month
- Streams must be in a trade-able form.
- Parameters are constant for the simulation.
  - Equation input toolkit under development.
- Diversion detection must be added after.




Figure 4: PyRe material flowchart ??.



## Subprocesses




Figure 5: Voloxidation material balance area ??.




Figure 6: Reduction material balance area ??.




Figure 7: Refining material balance area ??.




Figure 8: Winning material balance area.



# Outline

① Motivation

② Methods

③ Results

④ Future Work



## Average Sim




Figure 9: Product time series of a simple simulation.




Figure 10: Waste time series of a simple simulation.



# Isotopic Composition of Waste Streams




Figure 11: Isotopic Composition of Average Waste Streams



# Current Diversion




Figure 12: Isotopic Composition of Current Diverted Waste Streams



# Isotopic Range




Figure 13: Range of Isotopic Values



# Outline

① Motivation

② Methods

③ Results

④ Future Work





## Future Work

We have shown that PyRe allows Cyclus to simulate a simple pyroprocessing scenario. Future work includes:

- Increase scenario complexity - test shadow diversion
- Improve user input
  - Allow user-defined equations as input
- Chemistry detail

### Uses of PyRe:

In the beginning we marked the following objectives:

- What is the effect of introducing pyroprocessing plants in the fuel cycle?
- How do various facility designs affect throughput and efficiency?
- Where in a pyroprocessing plant will monitoring most effectively detect material diversion?



## Diversion Algorithm

The first two questions can be answered through the addition of PyRe to Cyclus. However, to address the last we must employ an algorithm to analyze small differences between multiple simulations. The following are being considered to provide 'online' diversion detection:

- Cumulative Sum (CUSUM)
- Maximum likelihood




Figure 14: Example of a cumulative sum alarm from Basseville. ??



## Acknowledgement

This material is based upon work supported by the Department of Energy National Nuclear Security Administration under Award Number(s) DE-NA0002576 via the Consortium for Nonproliferation Enabling Capabilities.

Prof. Huff is supported by the Nuclear Regulatory Commission Faculty Development Program, the Blue Waters sustained-petascale computing project supported by the National Science Foundation (awards OCI-0725070 and ACI-1238993) and the state of Illinois, the NNSA Office of Defense Nuclear Nonproliferation R&D through the Consortium for Verification Technologies and the Consortium for Nonproliferation Enabling Capabilities (awards DE-NA0002576 and DE-NA0002534), and the International Institute for Carbon Neutral Energy Research (WPI-I2CNER), sponsored by the Japanese Ministry of Education, Culture, Sports, Science and Technology.

# References I

