CONSTRUCTION AND CAPACITY STUDY

A 10,000-query/s key–value database in ten-party honest-majority MPC

Updated 13 October 2026, America/New_York

Target: 2^{28} and 2^{32} records, 32-byte keys and values; ten parties, at most four malicious corruptions, security with abort; average response time at most five seconds.

Updated comparison. The interactive reference costs approximately \$2.33B/year and \$5.16B/year, respectively, at modeled mean latencies 4.77 and 3.97 seconds. Local arithmetic is the critical resource; RAM capacity also constrains the larger case. Under the requested network-bottleneck assumption, the conditional garbled-RAM model costs \$10.33–18.52B/year and \$21.59–38.71B/year using the best prepared horizons in its grid. Preprocessing dominates its communication; SSD retention is strongly horizon-dependent. Concrete correlation generation and secure epoch renewal remain unpriced. Sections 10 and 11 give the calculations, sensitivities and limits. The earlier detailed interactive sections use $N = 2^{28}$ unless stated otherwise.

1 Decision for the proposal

Continue with two cuckoo tables over binary Circuit OPRAM, but make the arithmetic compilation and private routing the research contribution. Probe both tables in parallel; use a shared central batcher, grouped recursive-map updates, private dot products, a larger flat base, and a sweep of position-map packing. The important distinction is between increasing the number of labels per recursive record and changing the ORAM tree's branching factor: this study changes the former and retains the binary-tree eviction invariant.

A low annual budget is not yet supported. The explicit all-arithmetic reference used here has millions of secure reduction outputs per logical read. Its AWS sensitivity scenarios land in the billion-dollar/year range. That is a warning about this compilation, not an impossibility result for the problem. No complete malicious ten-party Circuit OPRAM benchmark or proof of these new compiled circuits was produced. In particular, the model does not establish the best achievable construction among mixed-domain, shuffle-based, hierarchical, or other MPC memory protocols.

The useful budget milestone is to measure and reduce the complete per-read work vector. A backend-conditional envelope below shows that even 10,000–30,000 secure outputs per read can consume millions of dollars/year across ten parties. Those counts are *optimization targets*, not achieved costs of the proposed system.

Suggested proposal language.


> We will develop an honest-majority MPC key–value service using batched oblivious access rather than a direct multiparty garbled-RAM extension. Our design combines parallel cuckoo probes, arithmetic-aware recursive position maps, private inner products, and optimized oblivious routing. We target 10,000 reads per second and mean response time below five seconds. Preliminary circuit and cloud accounting identifies metadata conversion and pool routing as the principal bottlenecks; meeting a practical cost target requires reducing these costs. We will validate throughput and annual operating costs with a complete malicious ten-party implementation including preprocessing, maintenance, and all-party communication.

2 What the numerical search found

The program searches batches 64–2048, fanouts 4–256, flat cutoffs 256–65536, compact versus field-bit metadata, sorting networks versus a checked-shuffle quicksort template, five EC2 instance sizes, and machines/replicas. It minimizes EC2 expenditure among points with modeled mean latency below five seconds. The cutoffs are requested limits; the actual flat map may be larger when another recursive tree would be too small to support its parallel batch.

Scenario	Batch	Fanout	Actual base	$/year (B)	Mean (s)
central	128	128	32,768	2.33	4.77
faster_cpu	128	128	32,768	1.52	4.65
slower_cpu	128	128	32,768	6.06	2.92
low_exchange	512	32	16,384	1.69	2.61
slow_exchange	64	128	32,768	4.68	4.79
two_second_target	128	128	32,768	4.32	1.67
no_overlap	128	128	32,768	3.96	4.56

These are independently optimized scenarios, not confidence intervals. The two-second-target row tightens the mean-latency cap to two seconds while retaining the central hardware assumptions. All other rows use five seconds. The CPU capacity assumptions are 0.5, 2, and 8 billion *weighted* local field operations per 64-vCPU node/s. They are not measured EC2 performance. Exchange-delay assumptions are 0.05, 0.2, and 0.5 ms; the central value is 0.2 ms. No-overlap sums CPU, network and RAM service time; other rows take their maximum. The latency simulation assumes Poisson arrivals and service-time coefficient of variation 0.05, and cannot predict real network tails or failures.



The central minimum uses 128 queries, fanout 128, 32,768 scalar labels in each flat base, and 3 recursive tree levels per cuckoo table. Its state occupies 1,926 GiB per party per replica. It uses 6 machines per party per replica and 530 independent replica groups (31,800 machines across all parties). Its modeled mean latency is 4.77 s, of which 1.29 s is dependent exchange time. This enormous deployment is an accounting result, not a recommended AWS launch. No EC2 capacity availability, quota increase, or linear scaling to this size has been established.

Level	Records per table	Payload words	Pool records	Lower path buckets
0	536,870,912	6	893	22
1	4,194,304	128	893	15
2	32,768	128	893	8

Per logical read, this point charges 3.36 million reduction outputs, 182.2 thousand preprocessed random bits, and 629.2 MB transmitted per party. The byte count includes the leading backend costs and 5% framing. Stored-field-bit metadata reduces conversion work but expands persistent state to roughly 12–13 TiB per party for typical grid points. That is *not* the memory cost of a properly packed Boolean-sharing implementation; this model charges every bit as an authenticated arithmetic share.

Fanout 128 wins the central scenario because it removes recursive levels; the low-exchange scenario instead favors fanout 32. Thus neither "largest payload" nor "smallest base" is a robust optimum. For prototyping, test batches 128–1024, fanouts 16, 32, 64, and 128, and actual bases of a few thousand to 32768 labels. Small batches keep formation latency low; the model's several-second delay comes mainly from computation and dependent communication, not waiting to fill batches.

3 A cost envelope for optimization targets


For G scalar reductions or private-dot-product *outputs* per read, the leading SY-Shamir traffic proxy is

$$V_{\text{party/read}} = G \cdot \frac{59}{6} \cdot 16 \text{ bytes}, \qquad V_{\text{party/sec}} = 10^4 V_{\text{party/read}}.$$

This excludes additional random bits, long-dot local work, conversions, routing, and special openings unless they are charged separately. It is a conditional backend relation, not an information-theoretic MPC lower bound.

Outputs/read	Peak NIC floor	NIC + headroom	Assumed CPU + NIC
	USD millions/year, all ten parties		
10,000	0.98	1.95	2.93
30,000	1.95	4.89	8.80
100,000	6.84	16.62	29.32
1,000,000	61.57	159.31	290.28

The table uses `r6in.32xlarge`, 200 Gbps, $11.15712/hour. Headroom includes 65% NIC utilization, 70% operating utilization, a 1.12 hottest-party factor, and 5% framing. CPU+NIC assumes 83 weighted operations/scalar output and 2 billion operations/s per 64 vCPU. It does not provision RAM, state replicas, dependent-round latency, intraparty routing, failover, or database initialization. Consequently even the rightmost column is not a sufficient deployment budget.



The gap from the reference's roughly 3 million outputs/read to a 30,000-output target is about 100-fold. Packing position maps alone cannot credibly be assigned that improvement. A substantially different metadata/routing implementation is needed before such a target can be presented as an expected system result.

4 Backend and scheduling assumptions

The accounting is tied to MP-SPDZ revision `73eb8556cdfc670c5d3dc1067a3ae5b4ad0d4441`, using authenticated SY-Shamir, $n = 10, t = 4, p = 2^{127} - 1$. The source-derived leading coefficient is approximately 59/6 field words sent per party per scalar/dot output; a checked opening costs 8 words, and an authenticated random bit about 24 words. A scalar multiplication has one exchange; the current dot-product path has two sequential exchanges. An active-check barrier adds at least four phases. Leading coefficients are not complete measured wall-clock costs.[1]

Keep these three kinds of arithmetic separate:

- One secret-selector payload mux uses one scalar product per field word.
- A k-bit secret comparison uses a prefix circuit of about $3k - 2$ products before its conditional movement; it is not one arithmetic gate.
- An inner product of length$k$ has one communicated output but$\Theta(k)$ local arithmetic. Random bits and exact field-to-bit conversion require their own preprocessing ledger.

The model's exact canonical-mask conversion and path-planning circuits have explicit proxy coefficients. The mask acceptance work is charged offline; conversion/opening phases are charged online. For a simple sustainable service schedule, the batch resource time includes *both* online and offline work. Ready preprocessing and overlapped maintenance can lower online latency, but their steady-state compute and network capacity must still be provisioned.

For K machines per party in one replica, the capacity model uses

$$T_{\text{service}} = D\tau + \max\{T_{\text{network}}, T_{\text{CPU}}, T_{\text{RAM}}\}, \qquad J = \left\lceil \frac{10^4 T_{\text{service}}}{0.7B} \right\rceil .$$

[1] Pinned protocol source: https://github.com/data61/MP-SPDZ/tree/73eb8556cdfc670c5d3dc1067a3ae5b4ad0d4441/Protocols.

J is the number of independent evolving ORAM replicas. Each replica stores the entire shared database; K shards its physical state and computation. A 0.7 distributed-efficiency factor and explicit intraparty share-routing traffic limit ideal scaling. The model adds scratch and a rough traffic-derived preprocessing inventory proxy. An implementation must replace that proxy with actual material sizes. The price is $10JKp_{\text{hour}} \cdot 8760$.

A central dispatcher forms a batch before choosing a replica. Mean formation waiting is approximately $(B-1)/(2R)$: 6.35 ms at $B = 128$ and 51.15 ms at $B = 1024$. Splitting arrivals into$J$ independent batchers would multiply that delay and is not the deployment being priced. Every replica finishes maintenance before accepting its next batch. The script also simulates dispatch queues, and tests that inadequate service capacity causes queues to grow.

5 AWS placement changes the answer

The official Linux/shared-tenancy US East (N. Virginia) offer snapshot is `20261012193925`, published 12 October 2026, with selected prices effective 1 October 2026. Raw rows and a refresh script are retained.[2]

Same physical AZ VPC-peering traffic can avoid transfer fees, including across accounts. Cross-AZ peering is$0.01/GB at each endpoint, or$0.02 for a transmitted GB counted once.[3] Thus at 10,000 outputs/read, the leading all-cross-AZ transfer bill alone is $99.2 million/year under this backend. For the central reference circuit it is $39.7 billion/year, before compute. A 4/3/3-party placement gives crossing fraction 66/90 only for uniformly weighted all-to-all communication; actual protocol traffic needs a byte-weighted graph. AWS billing-unit assumptions are exposed.

Advertised NIC bandwidth is per direction; single-flow limits and multi-NIC configuration matter. In particular, `r6in.32xlarge` needs both network cards to attain the aggregate 200 Gbps. No sustained MPC bandwidth or collective latency is guaranteed by the instance specification.[4] The interactive prices exclude EBS, snapshots, setup, backups, client transfer, NAT, orchestration, failover reserve, support, taxes, and engineering. Same-provider or same-AZ placement does not by itself establish independent corruption domains.

6 Construction choice and what the estimates establish

The design target is a read service for $N = 2^{28}$ key–value pairs, each containing a 32-byte key and a 32-byte value, at 10,000 logical requests per second. The security target is ten parties with at most four malicious corruptions and security with abort. Mean response time should remain below five seconds, with lower latency preferred. The raw database is 16 GiB; cuckoo slack, tree buckets, shares, authentication, recursive maps, and independent service replicas add to this substantially. Logical reads still modify the ORAM's position maps and placement state. Application writes and their replication protocol are outside this estimate.

The proposed starting point is two-choice cuckoo hashing over recursive Circuit OPRAM, with both candidates probed on every lookup. Two separate cuckoo tables permit two independent OPRAMs to run in parallel; this modestly reduces individual pool sizes without requiring secret-dependent shard routing.

[2] Official offer feed: https://pricing.us-east-1.amazonaws.com/offers/v1.0/aws/AmazonEC2/current/us-east-1/index.csv.

[3] https://docs.aws.amazon.com/vpc/latest/peering/what-is-vpc-peering.html; https://aws.amazon.com/vpc/pricing/.

[4] https://docs.aws.amazon.com/ec2/latest/UserGuide/ec2-instance-network-bandwidth.html; https://docs.aws.amazon.com/ec2/latest/instancetypes/mo.html.

The model uses single-slot hashing with explicit slack and a scanned overflow stash. Hash-table and ORAM stash capacities remain parameters that need a failure analysis. If clients supply secret shares of indices computed using public hash functions, the interface must specify which input consistency properties are checked. A keyed hash evaluated inside MPC is a different, additional cost; it has not been selected and is not implicitly free.

Circuit OPRAM is more than a batch of Circuit ORAM paths. For b probes into a binary tree with leaf depth H, let $r = \lceil \log_2(2b) \rceil$. The parallel construction keeps disjoint subtrees below depth r and represents the upper tree and stash in a pool. Its algorithms include private conflict resolution, pool retrieval, eviction candidate selection, and pool cleanup. The deterministic eviction paths occupy distinct subtrees. These are essential costs, not an optional implementation detail.[5]

For accounting, the reference template uses

$$P = Z(2^r - 1) + R_{\text{stash}}, \qquad h = H - r + 1,$$

where Z is bucket capacity and R_{stash} is an exposed slack parameter. A conservative temporary allocation allows $P + 3b$ records while fetched blocks and returned eviction candidates are processed. The pool replaces the upper tree buckets; their storage must not be counted twice. Recursion stops before an additional tree would have fewer than $2b$ leaves. This capacity accounting does not certify the chosen concrete stash slack.

Reference compilation versus the best achievable system. The program constructs an explicit operation ledger for a plausible Circuit-OPRAM-inspired compilation. It includes pool operations, metadata conversion, record movement, duplicate handling, and eviction planning. Some scan and planning coefficients are deliberately exposed estimates. It is neither a complete circuit implementation nor a proven upper bound on every implementation detail. Large reduction counts therefore demonstrate the expense of this specified compilation; they are not a lower bound on MPC lookup, a proof that the throughput goal is infeasible, or a claim to have found the globally optimal construction. AWS prices translate these conditional workloads into dollars; they do not validate the workload or processor-throughput assumptions.

The accounting distinguishes scalar products, private inner-product outputs, local arithmetic, random bits, openings, memory traffic, and dependent communication phases. In an appropriate Shamir backend, an inner product can communicate per output rather than per scalar term. Its local computation still grows with its length. This distinction is particularly valuable for retrieval and flat position-map bases.

7 Optimizations with a concrete implementation path

Use private shuffles to reduce repeated payload movement. The optimized reference sort augments each sorting key with a secret unique ordinal, securely shuffles records, and then opens comparison outcomes. Subsequent sorting moves are public local operations. The unique ordinal is essential: otherwise duplicate-key comparison patterns can disclose multiplicity. Vectorizing comparisons across quicksort recursion levels exposes parallelism, although its height and latency remain random. This shuffle-then-sort approach is described in the Orq implementation. [6]

[5] Chan and Shi, *Circuit OPRAM: Unifying Statistically and Computationally Secure ORAMs and OPRAMs*, https://eprint.iacr.org/2016/1084.

[6] *Orq: Complex Analytics on Private Data with Strong Security Guarantees*, SOSP 2025, https://cs-people.bu.edu/vkalavri/assets/pdf/orq-sosp25.pdf.

A generic realization has five fixed parties each choose a uniform private permutation and input checked switching-network controls. Under static corruption of at most four parties, at least one permutation remains hidden. Uniform switch bits alone would not produce uniform permutations. Restoring request order requires both undoing public sorting moves and applying the secret networks in reverse; the latter is charged. This is a useful reproducible baseline, but five sequential networks are expensive.

For a more ambitious implementation, benchmark a Shamir-specific permutation primitive. The 2026 Shuffle2 work uses inner products and preprocessing to obtain linear online shuffle communication in the malicious honest-majority setting. Its published implementation measures semi-honest execution; the paper's malicious overhead factors are estimates. Its offline cost also remains substantial. Consequently, it motivates an optimization experiment, not an unqualified replacement throughput assumption.[7]

Specialize pool operations rather than sorting everything alike. Pool cleanup is stable compaction on validity bits. Local prefix sums and scalar products can compute a unique secret destination permutation, leaving private routing as the expensive primitive; long-key comparisons are unnecessary. Maintaining the pool in logical-address order also permits a derived finite-difference gather: attach differences of adjacent payloads to pool records, insert zero increments for requests, merge by address, and use local prefix sums to recover candidate values. Secret equality still decides whether an exact match exists. Candidate-selection routing must subsequently be undone and stable compaction must preserve the sorted-pool invariant. This optimization needs an implemented invariant check and security argument; it is not assumed by the reference scan coefficients.

Choose metadata representation separately from payload encoding. Moving one field word and comparing a secret integer have different costs. Repeatedly converting compact arithmetic metadata to bits is expensive; retaining every address and leaf bit as an arithmetic share expands both storage and routing. A practical comparison should include compact metadata, retained bit metadata, and a mixed representation with narrow comparisons and explicit conversion costs. Retained bits must be charged whenever their record moves. Leaf compatibility against a public eviction path can reuse prefix-match products; target-depth comparisons use roughly $\log_2 H$ bits, rather than the full key width.

The published depth analysis of Circuit ORAM provides a starting point for parallel eviction planning. Its word-depth bound is not directly an MPC-round bound: comparison, selection, and authentication phases remain to be compiled.[8]

Tune recursive packing and the base together. Packing F parent labels per recursive block reduces record counts but increases record width, private subblock selection, and routing cost. Moderate powers of two, for example $F = 8$ through 128, are useful search points rather than a predetermined optimum. The binary eviction tree can remain unchanged. Several requests may update different offsets of the same map block: group those updates privately and commit the block once. Independent whole-block writes would overwrite each other.

The base contains one scalar label per record in the last instantiated tree. It is not smaller by another factor of F unless another recursive tree has been paid for. With $n = 2^d$ base labels, a divide-and-conquer one-hot decoder has the derived multiplication recurrence

$$T(d) = T(\lfloor d/2 \rfloor) + T(\lceil d/2 \rceil) + 2^d, \qquad T(0) = T(1) = 0,$$

[7] Gao et al., *SLIDE: Shuffle Shamir Secret Shares Uniformly with Linear Online Communication and Guaranteed Output Delivery*, especially Sections 5 and Appendix C.4, https://arxiv.org/html/2608.27129v1. Implementation: https://github.com/GJCPP/ShamirShuffle.

[8] Chan, Chung, and Shi, *On the Depth of Oblivious Parallel RAM*, https://eprint.iacr.org/2017/861.

and depth $\lceil \log_2 d \rceil$. For $n = 4096$, this is 4,272 products per request and four product layers, before validity gating and read/write operations. After duplicate resolution, dot-product retrieval and aggregated updates need about $b + n$ reduction outputs, while local work remains proportional to bn. Compare this against a complete additional recursive level. The reference program uses the divide-and-conquer decoder, adding one product and a conservative extra phase for a secret representative-valid bit.

Optimize scheduling after retaining dependencies. At one level, pool fetch and subtree fetch can overlap once old labels are available. Maintenance on an already accessed recursive tree can overlap fetching from the next tree if remapping labels have been sampled beforehand and state updates are coordinated. Recursion still has a base-to-data fetch dependency, and the next batch must not observe an uncommitted state. A sum of all phase counts is a conservative serial schedule; replacing it by the maximum level depth would be unjustified. Centrally forming batches before dispatching them to independent replicas avoids multiplying formation delay by the number of replicas. At 10,000 requests/s, batch size Q alone adds approximately $(Q - 1)/(2 \cdot 10{,}000)$ seconds of mean formation delay.

8 Validation needed before using a deployment budget

The next experiment should implement and measure one complete recursive batch, including duplicates and misses, on the selected malicious backend. Separately measure comparison/conversion, shuffle and inverse routing, pool cleanup, subblock updates, eviction, and preprocessing replenishment. Then measure the composed dependency schedule and memory footprint, rather than inferring end-to-end performance from multiplication throughput alone.

Failure parameters must cover the intended deployment lifetime. One year at 10,000 requests/s contains about $2^{38.2}$ logical requests, before counting two probes, recursive levels, replicas, and checking events. If A events each have failure probability at most ϵ, a simple lifetime bound is $A\epsilon$. For example, an annual target of 2^{-40} with 2^{42} relevant events would require per-event probability at most 2^{-82}. The ORAM stash, cuckoo overflow, statistical checks, and any randomized sorting limits need their own justified bounds. A simulated absence of overflow is useful testing evidence but does not establish such a bound.

Finally, capacity should include authentication and preprocessing, local routing between machines of one party, batch queues, and the full memory of each independently evolving replica. Cross-availability-zone placement changes both communication charges and latency. The resulting estimate is a proposal-planning scenario until an end-to-end malicious implementation has been calibrated on the intended topology.

9 Bottleneck clarification and scan comparison (13 October update)

The current model is limited first by total CPU demand, then by online communication. Storage is large, but is not the binding constraint at the selected point. This is a diagnosis of the analytical model, not a measured profile of an implemented MPC service. The earlier report combined online and preprocessing work; the new ledger separates them without changing its total costs.

For the selected 128-query batch on six `r6in.24xlarge` machines per party:

Resource or dependency	Time per batch
CPU, including preprocessing	3.452 s
Network, including preprocessing and internal routing	2.225 s
Modeled RAM traffic	0.094 s
Dependent exchanges	1.291 s
Service time: $1.291 + \max(3.452, 2.225, 0.094)$	4.743 s


These resource times are not additive under the model's overlap assumption. Total mean response time is about 4.77 s after batch formation and fixed response overhead. Faster CPUs eventually make networking or round latency dominant.

9.1 What is offline and what is online?

The selected SY-Shamir backend does not consume one Beaver triple per scalar multiplication. Its main product/degree-reduction traffic depends on the live inputs. Preprocessing supplies fresh checking randomness, random bits, and canonical masks. Thus importing a triple-generation bottleneck from a different SPDZ backend would misdiagnose this model.

Per party, per logical read	Preprocessing	Online	Total
Sent traffic, decimal MB	148.0	481.1	629.2
CPU proxy, million weighted operations	122.9	216.9	339.8

The traffic includes 5% framing, counts each send once, and excludes intraparty redistribution. CPU units are weighted source-operation estimates, not measured cycles or seconds. All ten parties incur the corresponding resource demand.



For O scalar/dot outputs, C canonical masks, and B_r random bits, the leading preprocessing allocation is

$$W_{\text{off}} = \tfrac{5}{6}O + 9(126C) + 24B_r + 8C,$$
$$A_{\text{off}} = 15O + 68(126C) + 330B_r + 35C.$$

W counts transmitted field words per party; A is the local CPU proxy. A full output costs $9 + 5/6$ words: 9 for query-dependent resharing and 5/6 for a fresh secret checking coefficient. Mask acceptance uses 126 outputs and an opening offline. Fixed checks add small terms retained in the program. The online column is the unchanged total minus this allocation.[9]

The CPU phase boundary can move. Precomputing random polynomial contributions to scalar resharing can shift another 48 operations per live scalar output out of the online loop. In this sensitivity, preprocessing rises from 36.2% to about 81.1% of total CPU work, with unchanged steady-state arithmetic. This requires additional material storage, memory traffic, and a correct scheduling implementation. It does not make that computation or its dollar cost disappear. The 9-word live communication remains query-dependent. Likewise, ready preprocessing can improve response time even when the service's sustainable throughput is still limited by generating it. The existing 4.74 s service estimate charges full resource production per batch; it is not an online-only latency benchmark.

9.2 Storage and replication

The selected state is 1,926 GiB (1.88 TiB) per party per ORAM replica, or about 2,217 GiB including the modeled scratch/reserve. At 75% usable memory, each 768 GiB instance provides 576 GiB, so four machines suffice for capacity. Six are selected to meet the latency/throughput model. Removing the memory constraint and re-searching the same instance size leaves the selected price unchanged. Storage would become binding under another representation or scheduling policy; field-bit metadata in particular expands it substantially.

The previous $2.33B/year deployment dedicates machines to each of 530 independently evolving ORAM states. An asynchronous scheduler could share machines across those states during round waits. The aggregate CPU-capacity requirement is 2,312 machines per party (about $1.69B/year), and their aggregate RAM could hold those 530 states. That is a resource-capacity estimate, not proof that a scheduler achieves the latency bound. The extra dedicated-instance cost is not an inherent cryptographic lower bound. Do not allocate VM dollars proportionally to the CPU/traffic percentages: one fleet serves overlapping demands.

9.3 Naive parallel full-key scan

The direct baseline compares every query key with all $N = 2^{28}$ stored keys, then returns $\sum_i [k_i = q]v_i$. Comparisons run in parallel across rows and queries; rows are visited in a public order. Values use three private dot products, so their selection communicates per output, not per record. There is no ORAM maintenance. The dictionary has unique keys; the sum of match bits gives a private hit indicator.

The baseline uses *exact* equality optimized for this field. Represent a key with the same three field limbs as the ORAM. Since $p = 2^{127} - 1 \equiv 3 \pmod 4$, -1 is a quadratic nonresidue and $a^2 + b^2 = 0$ holds exactly when both inputs are zero. For limb differences d_0, d_1, d_2, compute

$$u = d_0^2 + d_1^2, \qquad v = u^2 + d_2^2, \qquad e = 1 - v^{p-1}.$$

[9] Source accounting is pinned to MP-SPDZ commit `73eb8556cdfc670c5d3dc1067a3ae5b4ad0d4441`; see https://github.com/data61/MP-SPDZ/tree/73eb8556cdfc670c5d3dc1067a3ae5b4ad0d4441/Protocols and the local ledger `data/mpc_sources.txt`. These are derived counts, not an official benchmark table.

Each sum of squares is a length-two private dot product with one reduced output; the 135-product exponentiation is the addition-chain routine from the model. Thus each comparison costs 137 secure outputs, versus 407 for independently zero-testing and combining three limbs. This equality also improves the ORAM's few final key checks, but changes its millions-of-outputs total by less than 0.1%. Intermediate dot results must be degree-reduced before reuse.

Ignoring the tiny shared frontend, the full scan requires

$$G_{\text{scan}} = 137N + 3 \simeq 36.8 \text{ billion outputs/read.}$$

Batching does *not* divide this count by batch size: a batch has $137NB$ comparison outputs. It reduces communication scheduling overhead and permits database-cache reuse. Use row/query tiling, not an $N \times B$ materialized equality matrix. The read-only 48 GiB of authenticated database shares per party can be shared across concurrent workers, unlike independent mutable ORAM placements.

9.4 An indexed alternative using private dot products

An indexed scan is another baseline: keep the same two cuckoo tables and scan their arrays without ORAM. Private dot products allow a two-dimensional read. Arrange each $D = 2^{29}$-cell table as an $A \times C$ matrix, with $AC = D$. For private row and column one-hot vectors a, b, compute, for each payload word,

$$z_i = \sum_j b_j X_{ij}, \qquad y = \sum_i a_i z_i.$$

This reads every cell through local arithmetic, but only $AW + W$ dot outputs are reduced. With $W = 6$ key/value words, communication is minimized near $A = \sqrt{D/(W+1)}$. The model chooses $A = 8192, C = 65536$. One-hot generation is charged, both tables are always probed, and full keys plus the cuckoo stash are checked exactly. Empty-cell validity can use an unused bit in the last key limb, so the six-word payload need not grow. This is a derived exact read construction; it does not imply a fast write protocol.

Its approximately 249,000 outputs/read are *fewer* than the ORAM reference, but its dot products still process both full arrays. The current source proxy charges approximately $4 \cdot 2DW = 25.77$ billion local operations/read before the small remaining costs. Packing the batch as matrix multiplication can change the actual cycles/operation; this must be measured independently. Our CPU-rate assumption is not a benchmark of that dense kernel. Both scan variants can pipeline queries and reuse immutable shares without paying for one full state per worker.

9.5 Side-by-side work and cost

Per logical read / party	OPRAM	Full-key scan	Indexed 2D scan
Secure outputs	3.36M	36.78B	0.249M
Local CPU proxy	0.340B	3,059B	25.79B
Sent bytes, including framing	629MB	6.08TB	41.2MB
Persistent shares	1,926GiB	48GiB	192GiB
Exchange-depth contribution	1.291s	0.030s	0.031s

Storage is per complete state per party, not per read. Exchange-depth figures are only the phase-delay term at 0.2 ms/exchange; they are not achievable response latencies without sufficient computation and networking. Memory traffic is optimistically tiled/reused for scans; detailed scratch and reduction aggregation are not claimed to be free in an implementation.

Under the *same unmeasured* 2-billion-weighted-operations/s per 64-vCPU assumption, the common aggregate resource-capacity calculation gives:

Construction	Annual resource equivalent, ten parties
OPRAM reference	$1.69 billion
Naive full-key scan	$15.25 trillion
Indexed 2D dot scan	$128.6 billion

These all use `r6in.24xlarge` at the same 12 October price snapshot, 70% distributed efficiency and 70% utilization. They are not new deployment quotes. The scan fleets are astronomically large extrapolations, not plausible AWS reservations. The common calculation excludes detailed sharded-dot aggregation, queue/SLA feasibility, setup and scratch provisioning; its purpose is to expose the scale of work. The previous $2.33B ORAM figure includes a particular dedicated replica policy and should not be compared with a CPU-only scan calculation as if both were equally complete deployments.

Relative to the OPRAM reference, the naive scan needs about 9,000 times the CPU proxy and 9,656 times the traffic. The stronger indexed scan needs about 76 times the CPU proxy but only 6.5% of the traffic. Therefore "scan is communication-heavy" is true for the naive full-key implementation, but false as a universal statement.

Practical conclusion. The next measurements should isolate (1) total preprocessing production, (2) live product/resharing throughput, (3) checked network exchanges and (4) a batched local matrix-contraction kernel. The current arithmetic OPRAM reference uses less modeled CPU work than these scans, while the two-dimensional scan is a serious bandwidth-oriented comparator. Neither the numerical CPU split nor the cheapest real system is settled without those measurements.

Reproduce the comparison with `python -m mpc_cost.compare_scans`; the complete ledger is `results/bottleneck_scan_comparison.json`.

10 Scaling the interactive MPC service to 2^{32} records

The larger proposal case retains 32-byte keys, 32-byte values, ten parties, four malicious corruptions with abort, and 10,000 logical reads/s. We repeat the complete parameter sweep and its CPU/exchange sensitivities. Both cases use two cuckoo arrays whose combined capacity is $4N$ at the rounded 40% load ceiling; the actual occupancy is 25%. These estimates cover flat key/value lookups, not Merkle-proof retrieval. The 2^{28} case is a power-of-two planning size, not the proposal's exact 206.8-million-account count.

Selected central reference	Smaller database	Larger database
Logical records	2^{28}	2^{32}
Raw key/value database	16 GiB	256 GiB
Batch / map packing fanout	128 / 128	512 / 256
Actual flat base (labels/table)	32,768	131,072
Recursive ORAM trees/table	3	3
Secure outputs/read	3.36M	6.10M
Sent MB/read/party	629.2	1,085.8
State TiB/party/replica	1.88	30.05
Nodes/party/replica	6	96
Independent replicas	530	110
All-party EC2 instances	31,800	105,600
Modeled mean latency	4.77 s	3.97 s
Conditional EC2 USD/year	$2.33B	$5.16B

The smaller selection uses `r6in.24xlarge`; the larger uses `r6in.16xlarge`. Prices, throughput assumptions and the 5-second mean limit are unchanged. The full search includes batches 64–2048, fanouts 4–256, both metadata representations and both sorting templates. The larger selection is on the upper fanout boundary; it is the best point in this grid, not a global optimum. The flat base contains 131,072 labels despite a nominal cutoff of 256, because the next tree would have fewer than $2B$ leaves. The model stops recursion there. The complete sensitivity runs are saved in `results/size_2p32/`.

The bottleneck changes with size. For the 2^{32} selection, CPU demand is 2.180 s/batch, network demand is 1.595 s and dependent exchanges add 1.742 s. CPU still controls the resource term, but RAM capacity also constrains provisioning: the state plus modeled scratch/buffer requires 34.57 TiB per party per replica. Each selected 512-GiB instance provides 384 GiB of usable RAM, requiring at least 93 nodes; the grid selects 96. At the same fixed circuit and instance type, removing only the memory constraint gives 66 nodes, 138 replicas and approximately $4.45 B/year. Thus the earlier statement that storage does not affect the chosen fleet applies to the 2^{28} reference.

Per 2^{32} logical read and party, preprocessing accounts for 192.1 MB and 168.1 million weighted CPU operations; online work accounts for 893.7 MB and 404.2 million operations. These are the same source-derived phase allocations as Section 9, not new measured rates. The selected mean is lower than in the smaller case because memory capacity forces a larger parallel allocation, not because larger databases inherently have lower latency.

10.1 Scan comparison at both sizes

Records	Construction	Weighted Gops/read per party	GB sent/read	USD B/year all parties
2^{28}	OPRAM	0.34	0.629	1.69
2^{28}	Full-key scan	3,058.82	6,075.355	15,252.97
2^{28}	Indexed 2D scan	25.79	0.041	128.61
2^{32}	OPRAM	0.57	1.086	2.85
2^{32}	Full-key scan	48,941.15	97,205.683	244,047.48
2^{32}	Indexed 2D scan	412.40	0.163	2,056.45

The last column uses the common aggregate resource-capacity model from Section 9; it does not include a latency-feasible replica schedule. In particular, its ORAM figures differ from the dedicated-replica costs above. Scan state remains shared across concurrent read workers: at 2^{32}, it is 768 GiB/party for full-key scanning and 3,072 GiB/party for the indexed two-array scan. Full scanning grows almost exactly 16-fold in computation and traffic. Indexed scanning grows about 16-fold in local work and fourfold in transmitted data because of the balanced two-dimensional layout. All figures still depend on unmeasured CPU rates.

11 Multiparty garbled RAM: both database sizes

Under the requested communication-bottleneck assumption, recurring garbling preprocessing is the main traffic cost. About 97.7% of modeled bytes are preprocessing, not the delivered garbled tables. SSD capacity can nevertheless dominate the dollar bill if a long future execution is retained in full. The reference policy below costs \$10.33–18.52B/year at 2^{28} records and \$55.07–65.69B/year at 2^{32}. Shortening the latter's prepared horizon reduces the conditional estimate substantially. None of these ranges includes a measured, finite OT-only correlation generator or a complete malicious epoch-renewal protocol.

11.1 Scope and Boolean work ledger

We use *Multiparty Garbling from OT with Linear Scaling and RAM Support* (ePrint 2025/444), including Appendix H and its tri-state encoding in Appendix F. The local 49-page PDF was checked directly. The ten-party setting tolerates four static malicious corruptions with abort. Field elements and labels have width 128 bits; this is a parameter choice, not a demonstrated 128-bit service-lifetime failure bound.[10]

As requested, all garbled-stack and associated adaptor costs are set to zero, assuming the two-party improvement in ePrint 2026/761 can be migrated. That paper optimizes the stack subroutine; it does not remove ordinary RAM reads, eviction, recursive maps, or initialization. Its measured regime is two-party, up to 2^{24} cells. Our extrapolation is consequently a conditional multiparty construction, not a published benchmark.[11]

`garbled_circuit.py` counts Boolean AND and XOR work separately from the interactive arithmetic model. The layout still has two $2N$-cell cuckoo arrays, two fixed probes, exact 256-bit key comparisons,

[10] https://eprint.iacr.org/2025/444. The retained local source is `multiparty_ot.pdf`; detailed equation notes are in `data/garbling_backend_notes.txt`.

[11] https://eprint.iacr.org/2026/761, local `garbled_merge.pdf`, final August revision, Sections 3.4, 5.3 and 6.2. The public code artifact at https://zenodo.org/records/20751401 supplies the structural Circuit ORAM and recursive-map templates used here.

256-bit output selection, occupancy bits and an eight-entry dictionary stash. Each data payload has 513 bits. The main frontend accepts privately supplied hash indices, as in the interactive comparison; exact key checks prevent a false hit. Two internal SHA3 hashes are priced separately. Malformed supplied indices can force a miss for that client's query; internal hashing provides the stricter key-only functionality. Position labels, conditional payload movement, recursive block selection, and the final flat map are charged explicitly.

The source-inspired garbled tree has mostly four children per node; the position-map packing fanout is a separate parameter. We sweep packing factors 2–128 and flat-base thresholds 16–4096, both powers of two, and the source's compute- and communication-oriented stash/bucket/eviction choices. The selected packing is eight for both sizes. These are source-derived circuit templates, not counters from an executed ten-party implementation. Stash parameters and lifetime failure probabilities still need validation at the larger sizes.

The distinction between *visited* and *generated* gates is essential. For a horizon of T logical KV queries, the source provisions $(1+E)T$ root invocations, where E is the number of extra evictions. Child budgets use rounded division by the number of children, with a root-level D/way allowance for a D-cell RAM, capped by the parent's budget. We sum every provisioned node's circuit and divide by T. Summing only the online visited path underprices the offline factory and SSD programme. Both probes are already in this count.

11.2 What an AND gate costs with ten parties

Let A, I, O be generated AND gates, input bits and output bits, each amortized per logical query in an epoch of T queries. XOR is free in communication, but still has local work. With outer packing $\ell = 5$, the ciphertext parameter is $c = \lceil 10/5 \rceil = 2$. Each of the nine non-evaluators sends

$$4(c+1) \cdot 16 = 192 \text{ bytes/AND}; \qquad V_{\text{table}} = 9 \cdot 192A = 1728A \text{ bytes}.$$

The evaluator receives this aggregate. The additive mask in each row is a *field element*, not one bit. Appendix H's printed equation uses n in this final delivery term; the protocol sends from $i \neq 1$, so we use $n-1$. Charging every party 1728 bytes as its own transmitted table would overcount. Appendix H prices Boolean circuits; Appendix F's full tri-state protocol has additional preprocessing whose finite coefficient is not specified there. We use H for Boolean RAM kernels and F for retained state, under the free stack migration assumption. Any necessary non-stack, cross-gadget or Boolean-to-tri-state conversion remains an unpriced compiler component; ignoring the stack does not prove those conversions free. This combined accounting template is not an exact finite-cost instantiation of the paper's complete tri-state RAM protocol.

For finite preprocessing parameters, outer $\ell/n = 0.5$ and the inner SuperPack choice $k = 3$, $\epsilon_{\text{SP}} = 0.4$ are distinct. They support the requested threshold; substituting one common ϵ would obscure integer packing. The leading global preprocessing traffic, with a conservative repair of the paper's multiplication-count algebra, is

$$V_{\text{prep}} = 16(2747.5I + 4618.5A + 36O + 1440/T) \quad \text{bytes/query}.$$

Thus an AND contributes 73,896 global preprocessing bytes, or 7,389.6 bytes averaged over the ten parties, before table delivery and framing. Input delivery adds 434.25 bytes/bit globally and output delivery adds 288 bytes/bit. We use $O = 257$ (value and membership), and charge query/position inputs plus all initial physical-state bits amortized over T. Shared randomness generation and valid hidden state construction remain separate protocol obligations.

The repair is explicit: the first, exact line of Appendix H equation (8) expands to three times its whole-circuit input count plus five times its AND count, plus $1 + \ell$ multiplication gates. Its approximation

and later equation (10) disagree; the latter uses $2I + 4A$. Keeping that printed latter choice instead gives $16(2575I + 4446A + 36O + 1440/T)$ bytes/query. We show its effect below. The once-per-circuit constant is amortized over an epoch; these are leading counts, so remaining lower-order checks and protocol wrappers are not certified finite costs.

Correlation generation is an explicit unresolved cost. The paper's numerical ledger assumes efficient correlation generation; the OT-only variant adds OLE correlations without a complete finite byte coefficient. Corrections sent after receiving VOLE are not the cost of producing that VOLE. Our default uses the reported leading ledger with negligible amortized correlation traffic. The +25% and +100% preprocessing cases below are sensitivities, not measured implementations or proven upper bounds. This prevents the estimate from being misread as a fully priced OT-only malicious backend.

11.3 Network capacity and SSD retention

All parties together transmit V bytes per query, including 5% framing. Let s_i, r_i be party i's sent/received bytes. Since AWS NIC bandwidth is full duplex, its capacity demand is $\max(s_i, r_i)$, and

$$V \;\le\; \sum_i \max(s_i, r_i) = V + \tfrac{1}{2}\sum_i |s_i - r_i| \;\le\; 2V.$$

This gives a role-independent fleet envelope without assuming that preprocessing traffic is perfectly balanced. It does not identify an actual assignment of machines. We use `c6in.32xlarge`, 200 Gbps in each direction, \$7.2576/hour, with efficiency factors $0.65 \cdot 0.70 \cdot 0.70$: 7.9625 GB/s per node per direction. At rate $R = 10^4$, the fleet ranges from $\max(10, \lceil RV/C \rceil)$ to $\max(10, \lceil 2RV/C \rceil + 9)$ machines; the nine cover separate party ceilings. Annual EC2 cost is machines times $8760 \cdot \$7.2576$. The range describes role imbalance only; it is not an uncertainty interval covering omitted costs. The x86 SKU avoids assuming an ARM port.[12]

Same-AZ inter-party transfer has no marginal data-transfer fee under the chosen placement. SSD capacity uses gp3 at \$0.08/GiB-month, or \$0.96/GiB-year. Per the requested assumption we do not constrain SSD throughput or charge additional provisioned IOPS/throughput. No inference about local evaluation speed is made. CPU, EBS attachment/IO scheduling, AWS capacity and quotas need a deployment validation before this resource envelope becomes a feasible service. [13]

Let L be retained physical Boolean state bits, including bucket slack and recursive maps. We retain the literal Appendix F packs: 224 bytes/bit at the evaluator and 64 at each of the other nine parties, totaling $800L$ bytes. This is a conservative policy; garbler packs can potentially be retired. Only one aggregate copy of the garbled programme is charged, at the evaluator:

$$S_{\text{one epoch}} = 1728AT + 800L, \qquad S_{\text{reference}} = 2S_{\text{one epoch}}.$$

The two copies represent the current and next prepared epoch for one independent state. Preprocessing transcripts are not counted as retained programme. A short streaming buffer would require a concrete scheduling argument, so it is not silently substituted for a complete epoch.

[12] Official AWS US East (N. Virginia) feed snapshot `20261012193925`; raw selected rows and URLs are in `data/aws_garbled_prices_2026-10-13.json`. https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-instance-network-bandwidth.html.

[13] https://aws.amazon.com/ebs/pricing/. AWS explicitly defines the capacity-pricing GB unit as 2^{30} bytes. Network GB and plotted EB are decimal.

Reference: $T = 2N$, two complete epochs	Smaller database	Larger database
Logical records	2^{28}	2^{32}
Packing fanout / flat base	8 / 256	8 / 512
ANDs visited/query	1.193M	1.562M
ANDs generated/query	1.288M	1.672M
Prep. GB/query, all parties	95.43	123.83
Table GB/query, all parties	2.23	2.89
Framed sent GB/query, average party	10.25	13.31
Epoch length at 10k QPS	14.91 h	238.61 h
One epoch of tables, decimal EB	1.195	24.815
Two epochs + state, decimal EB	2.394	49.711
Network EC2/year	\$8.19–16.38B	\$10.62–21.25B
SSD capacity/year	\$2.14B	\$44.44B
Total/year, reference epoch	\$10.33–18.52B	\$55.07–65.69B


The throughput bottleneck here is offline communication, by assumption. Preprocessing is about 97.7% of traffic; generated tables and encoded I/O account for the rest. Even table delivery can occur before a query, so the remaining 2.3% is not all online interaction. We have not measured whether computing the preprocessing or evaluating the programme would overtake networking. A ready garbling can have few online rounds while being very expensive to sustain at 10,000 queries/s. The large-size reference's SSD bill exceeds its network EC2 bill, making retention the largest dollar item despite the stipulated NIC throughput bottleneck.

11.4 Choose the prepared horizon rather than fixing it to database size

An epoch of T queries is an offline provisioning horizon, *not* a batch that must accumulate before answering. Smaller T reduces retained tables but amortizes fixed per-node invocation allowances and initial-state encoding over fewer queries. We reoptimize the same finite layout grid at each power-of-two horizon from $(2N)/256$ to $16(2N)$. The table shows representative points; all points are saved in JSON.

Records	Queries/epoch	Hours	AND M/query	SSD \$B/year	Total/year
2^{28}	2^{23}	0.23	2.740	0.08	\$18.82–37.56B
2^{28}	2^{25}	0.93	2.124	0.22	\$14.04–27.85B
2^{28}	2^{27}	3.73	1.581	0.66	\$10.77–20.88B
2^{28}	2^{28}	7.46	1.386	1.15	\$9.99–18.83B
2^{28}	2^{29}	14.91	1.288	2.14	\$10.33–18.52B
2^{28}	2^{30}	29.83	1.241	4.12	\$12.00–19.88B
2^{32}	2^{27}	3.73	3.346	1.46	\$24.06–46.66B
2^{32}	2^{29}	14.91	2.646	4.46	\$21.59–38.71B
2^{32}	2^{31}	59.65	2.012	13.42	\$26.27–39.11B
2^{32}	2^{32}	119.30	1.786	23.78	\$35.15–46.52B
2^{32}	2^{33}	238.61	1.672	44.44	\$55.07–65.69B
2^{32}	2^{34}	477.22	1.617	85.90	\$96.17–106.43B

Minimizing the *upper endpoint* in this grid selects 14.91 hours at 2^{28} and 14.91 hours at 2^{32}, costing \$10.33–18.52B and \$21.59–38.71B/year, respectively. These are conditional optima inside the chosen template and epoch policy. The lower and upper fleet endpoints can prefer different horizons. Do not treat the reference's large SSD footprint as an unavoidable lower bound for garbled RAM.



Shorter epochs are not a solved free refresh. Re-inputting existing state pays for encoding; it does not compute a valid jointly hidden layout, sample and validate private routing controls, or transfer a live state securely to the next garbling. The two-party source knows controls at its sole garbler; that role cannot simply be assigned to one possibly corrupted party here. Also, the cited multiparty theorem uses static corruptions and standalone function evaluation. Continuously injecting new, possibly adaptive external client requests through an epoch needs a service-security argument. Internal RAM adaptivity alone does not establish that API. These integration assumptions apply at every horizon, including the reference.

11.5 Sensitivity and comparison with interactive MPC

Change from the $T = 2N$ reference	$N = 2^{28}$	$N = 2^{32}$
Printed multiplication algebra	\$10.03–17.92B	\$54.68–64.92B
Additional correlation traffic: +25% of prep.	\$12.33–22.52B	\$57.66–70.88B
Additional correlation traffic: +100% of prep.	\$18.33–34.52B	\$65.45–86.46B
One complete epoch retained	\$9.26–17.45B	\$32.85–43.47B
Ten independent states, two epochs each	\$29.59–37.78B	\$455.07–465.70B
Compute two SHA3 hashes inside the circuit	\$10.94–19.62B	\$57.59–68.70B
Routing-only initialization allowance	\$12.78–22.91B	\$66.68–79.54B
All inter-party bytes cross AZs	\$657.09–665.28B	\$894.27–904.89B

Each row changes one assumption. The routing-only allowance applies a padded Beneš permutation to every tree's physical slots with block width $w + 2h + 1$: for K padded slots, it charges $(K/2)(2\log_2 K - 1)$ secret switches, one AND per moved bit per switch, plus encoding the supplied control bits. It excludes generation and verification of valid controls. Thus it is a concrete additional kernel, not a complete setup budget. Ten states multiply SSD capacity while sharing the aggregate 10k QPS; they do not multiply the same query traffic by ten. A one-epoch policy halves retention, not recurring production cost. Cross-AZ traffic charges both billed endpoints once per transmitted byte, at \$0.02/decimal GB in total.

The interactive reference costs \$2.33B/\$5.16B per year at the two sizes, with modeled mean latencies 4.77/3.97 seconds. Its resource bottleneck is local arithmetic, mostly online work under the baseline phase attribution; at 2^{32} RAM capacity also forces additional machines. The garbled model instead gives a network/SSD resource envelope under the user-specified network bottleneck, with costly recurring offline production. We do not claim a five-second garbled-service latency without an evaluation and

scheduling benchmark. Both models include ten parties and sustainable repeated query work, but their CPU assumptions and replica policies differ. These dollar figures do not establish a universal protocol ranking.

For the proposal, retain interactive arithmetic compilation as the working direction and state the concrete benchmark milestones. Neither this garbled construction nor the unimplemented all-arithmetic reference currently supports a low-cost production commitment. A tighter garbled estimate requires finite malicious correlation costs, a joint initialization/renewal implementation, reactive input handling, a concrete party traffic graph, and measured local evaluation, including any representation adapters. SSD streaming and independent-state scheduling are additional optimization opportunities rather than assumed free savings.

12 Reproduction and next decision

From the repository root:

```
python -m mpc_cost.run --full
python -m mpc_cost.compare_scans
python -m mpc_cost.run --full `
  --config mpc_cost/data/design_2p32.json `
  --output mpc_cost/results/size_2p32
python -m mpc_cost.compare_scans --results mpc_cost/results/size_2p32
python -m mpc_cost.garbled_cost
python -m unittest discover -s mpc_cost -p "test_*.py" -v
python -m mpc_cost.render_report
```

Compile `mpc_cost/mpc_oram_cost_report.tex` with its working directory set to `mpc_cost`. The program has no runtime dependencies beyond Python's standard library; generating figures additionally needs Matplotlib and PDF compilation needs LaTeX. `README.txt` explains overrides and price refresh. The backticks above continue a command in PowerShell; elsewhere put its arguments on one line. The garbled sweep saves `results/garbled_ram_comparison.json`.

The tests validate arithmetic witnesses (comparison, gated decoding, duplicate updates, Fermat equality), recursive base dimensions, metadata movement, all-party and replica billing, transfer send-counting, and queue saturation. They do not validate an unimplemented ORAM security proof or MPC performance. Additional checks validate both database sizes, finite garbling coefficients, generated versus visited gate counts, routing-only setup, arbitrary traffic-graph fleet bounds, framing, SSD-copy scaling and transfer accounting.

Before choosing a proposal budget, benchmark checked scalar batches, long dot products, mask production, and a complete recursive read with duplicate updates. Measure online latency and sustainable total resource use separately, then replace the proxy counts and sweep the parameters again.