

Tracing Functional Correctness in DLMs with Sparse Autoencoders

Anonymous ACL submission

Abstract

Prior probing of diffusion language models (DLMs) suggests that correctness signal grows monotonically through denoising. Using DLM-Scope sparse autoencoders, we instead trace the signal feature by feature across two DLMs and four tasks. Sparse fail-vs-pass concentration appears in task-dependent phases. Code and structural tasks form a broad mid-denoising plateau, whereas reasoning tasks emerge only at the final state. On LLaDA-8B / MBPP, a dense step sweep across seeds confirms a plateau spanning steps 48–116, with multiple sub-steps reaching $p < 0.05$. Two persistent features hand off within the late plateau, marking an internal transition rather than feature swapping. The peak phase agrees across LLaDA-8B and Dream-7B on 3/4 tasks, although most individual cross-grid cells do not reach per-step significance. However, single- and multi-feature steering fails to flip correctness in a small pilot. The sparse features therefore behave as diagnostic markers under our protocol, not as directly controllable knobs.

1 Introduction

Diffusion language models (DLMs) generate text by iteratively denoising a fully masked sequence over ~ 100 steps (Austin et al., 2021a; Sahoo et al., 2024; Lou et al., 2024; Nie et al., 2025; Ye et al., 2025). Chiu (2026) shows that simple classifiers trained on hidden states gain 0.08–0.11 AUC predicting functional correctness as denoising proceeds, framing the process as a monotonic sharpening of an aggregate scalar. This view leaves a basic question unanswered: *which* representational components carry the failure signal, and *when* during denoising do they form?

Contributions.

- **Mid-denoising plateau.** LLaDA-8B / MBPP has a broad plateau over steps 48–116 (3-seed

dense sweep), with f15601 top-ranked at the early plateau and f3892 at the late plateau.

- **Phase agreement.** Peak phase agrees across LLaDA-8B and Dream-7B on 3/4 tasks, while per-cell significance is concentrated in the strongest LLaDA-MBPP condition.
- **Steering null.** Single-, top-5, and reverse feature interventions fail to flip correctness in a pilot intervention sweep.

Code and figures will be released on acceptance.

2 Related Work

Discrete diffusion and masked DLMs generate text by iteratively denoising masked tokens rather than continuing left to right (Austin et al., 2021a; Sahoo et al., 2024; Lou et al., 2024; Nie et al., 2025; Ye et al., 2025). Prior probing of the same models and tasks studies aggregate hidden-state predictability and reports monotonic gains in correctness AUC through denoising. SAEs decompose residual streams into sparse named features and have been used primarily to interpret autoregressive LMs (Bricken et al., 2023; Cunningham et al., 2024; Gao et al., 2024). DLM-Scope extends this toolkit to DLMs with Top- K SAEs (Makhzani and Frey, 2014; Gao et al., 2024) trained on masked-position residuals across mask rates $t \sim U(0, 1)$ (*Mask-SAE*), keeping the full denoising trajectory in distribution (Wang et al., 2026). Recent AR SAE studies report both successful steering for refusal and instruction following (O’Brien et al., 2024; He et al., 2025) and cautions that contrastive features may track lexical correlates or that steering degrades unrelated capabilities (Galichin et al., 2025; Korznikov et al., 2025). We reuse the DLM-Scope SAEs to ask whether the scalar correctness trend on DLMs decomposes into temporally localised sparse features, treating the steering question as open rather than presumed causal.

3 Method

Models and SAEs. LLaDA-8B (Nie et al., 2025) (block-wise unmasking, block length 32) and Dream-7B (Ye et al., 2025) (global linear schedule) both denoise a ≤ 256 -token generation region over $T=128$ steps conditioned on a fully visible prompt. We use the DLM-Scope L26 LLaDA-mask SAE and L23 Dream-mask SAE (trainer index 2, $d_{\text{sae}}=16,384$, $K=160$). The AR comparison (DLM-Scope L23 SAE on Qwen-2.5-7B (Team, 2024)) is a single-token reference point, not a trajectory: we encode the last-prompt-token residual once per sample as a single-step analog of the DLM’s pre-generation state.

Data. We reuse cached hidden states and functional-correctness labels from Chiu (2026): MBPP-sanitized (257) (Austin et al., 2021b), JSON schema (272), GSM8K (1,319) (Cobbe et al., 2021), and ARC-Challenge (1,172) (Clark et al., 2018), generated with seed 0 and $T=128$ steps. Hidden states are mean-pooled over four equal-length generation regions at seven checkpoint steps $\{0, 1, 4, 16, 32, 64, 127\}$.

Per-step SAE encoding. At each (model, step, layer) cell we take the region-mean hidden state $h \in \mathbb{R}^d$ per sample and encode it: $z = \text{TopK}(\text{ReLU}(W_{\text{enc}}(h - b_{\text{dec}}) + b_{\text{enc}})) \in \mathbb{R}^{d_{\text{sae}}}$, with $W_{\text{enc}} \in \mathbb{R}^{d_{\text{sae}} \times d}$, $W_{\text{dec}} \in \mathbb{R}^{d \times d_{\text{sae}}}$, $b_{\text{enc}} \in \mathbb{R}^{d_{\text{sae}}}$, $b_{\text{dec}} \in \mathbb{R}^d$, and TopK keeps the $K=160$ largest entries. Feature i is *active* on a sample iff $z_i > 0$.

Fail-vs-pass enrichment. Let $\mathcal{F}, \mathcal{P}$ be the fail and pass sets at a cell. Feature i ’s enrichment is the difference of active rates, $\text{enr}(i) = \frac{1}{|\mathcal{F}|} \sum_{s \in \mathcal{F}} \mathbb{1}[z_i^{(s)} > 0] - \frac{1}{|\mathcal{P}|} \sum_{s \in \mathcal{P}} \mathbb{1}[z_i^{(s)} > 0]$. We use the top-20 most fail-enriched features as the analysis subset per cell.

Cluster discriminability with permutation null. We run KMeans on the fail samples for $K \in \{2, 3, 4, 5\}$ using the top-20 features (continuous activations) and report the silhouette of the best K . The permutation null shuffles labels $1000\times$, re-selects the top-20 features on each shuffled label set, then recomputes silhouette, controlling for the post-hoc feature selection. We report $p = \Pr[\text{silhouette}_{\text{perm}} \geq \text{silhouette}_{\text{obs}}]$. The silhouette is computed on fails only and measures sub-structure within failures, not fail-vs-pass separability directly. We therefore interpret it as *concentration of failure modes* in a selected sparse sub-




Figure 1: LLaDA-8B / MBPP: KMeans silhouette on the top-20 fail-enriched features vs. permutation null mean across denoising steps. All 21 checkpoints (anchors $\{0, 1, 4, 16, 32\}$, plateau $\{48-80\}$, post-plateau $\{84-124\}$, final 127) are from a single new-prompt generation run; faint lines overlay two additional generation seeds (Appendix G). Shaded region marks the mid-denoising plateau $[48, 116]$ where most steps reach $p < 0.05$; step 64 sits inside the plateau as a local dip, not a sharp peak.

space, and cross-check fail/pass separability with supervised AUC in the same subspace (Appendix E, per-fold selection).

Steering. We write *fail*→*pass* for a sample whose label flips from fail to pass after intervention, and *pass*→*fail* for the reverse pass-side regression. Given a target feature i^* and strength α , a forward hook on the SAE layer’s transformer block re-encodes the residual at every step $t \geq t_0$, reads z_{i^*} , and in-place subtracts $\alpha \cdot z_{i^*} \cdot W_{\text{dec}}[:, i^*]$. $\alpha < 0$ amplifies the feature (reverse intervention); for multi-feature steering we sum contributions over a set of indices. A zero-out smoke test (force $h \leftarrow 0$) confirms the hook propagates. It garbles trailing tokens but leaves the early-committed function body intact, consistent with LLaDA committing blocks 0–3 by step ~ 48 .

4 Results

Mid-denoising plateau. Figure 1 reports a 21-step trajectory for LLaDA-MBPP from a single generation run, with three seeds (Appendix G): anchors $\{0, 1, 4, 16, 32\}$, plateau dense $\{48, 52, \dots, 80\}$, post-plateau dense $\{84, 92, \dots, 124\}$, and final state 127. Rather than a sharp peak at step 64, the trajectory shows a broad plateau spanning steps 48–116: the signal-to-null gap stays in $[+0.19, +0.41]$ throughout this range and only collapses at step 124 as the model approaches its final state. f15601




Figure 2: Cross-model $\times$ cross-task trajectory grid. Each panel plots signal-to-null gap (observed KMeans silhouette minus permutation null mean) across denoising steps for one (model, task) cell; red marker = peak gap step; black outline = $p < 0.05$ permutation significance. Code (MBPP) and structural (JSON) tasks peak at mid-denoising (step 64) on both DLMs. Math (GSM8K), and on Dream science QA (ARC), peak at late denoising (step 127). The peak step shows task-level agreement across LLaDA-8B and Dream-7B on three of four tasks; only ARC disagrees (LLaDA peak step 4, Dream step 127).

is the top-1 fail-enriched feature at 7/9 of the early-plateau dense steps and remains dominant through step 100. In the late-plateau steps 108–116 it gives way to f3892, indicating a within-plateau hand-off rather than feature swapping outside the plateau. At steps 0–16 the top fail feature changes every step (Appendix A), consistent with the residual stream not yet encoding committed-token decisions when most positions are still masked. Chiu (2026) reports that aggregate raw-probe AUC *monotonically* increases over these same steps (for LLaDA / MBPP, from ~ 0.75 at step 0 to ~ 0.84 at step 64). The feature-level plateau is therefore invisible to scalar probing.

Cross-model $\times$ cross-task phase agreement. Figure 2 reports the full 2×4 trajectory grid. Three archetypes emerge across cells. **Mid-denoising peak** (signal peaks at step 64): LLaDA-MBPP (+0.31), LLaDA-JSON (+0.14), Dream-JSON (+0.23), Dream-MBPP (+0.15). This is the shape of the persistent-feature trajectory described in §4: a fail-discriminative cluster crystallises during the middle of denoising and partially dissipates by step 127. **Late-denoising peak** (signal peaks at step 127): LLaDA-GSM8K (+0.22), Dream-GSM8K (+0.16), Dream-ARC (+0.26). Here the cluster signal is weak or below null at mid-denoising and only emerges near the final state, consistent with reasoning tasks requiring more denoising before

the failure signature crystallises. **Early-decline** (LLaDA-ARC peaks at step 4, +0.20): an outlier where the cluster appears only at the earliest steps and decays thereafter. The peak position shows *task-level agreement across DLMs*. Three of four tasks (MBPP, JSON, GSM8K) share a peak step across LLaDA and Dream; only ARC differs. At the feature level this mirrors the structural-vs-reasoning emergence split of Chiu (2026), in which structural and code tasks form features mid-denoising and reasoning tasks form them late. The split is now visible as a peak position rather than a continuous AUC curve. Appendix C summarises the 12 (DLM and AR) cells at step 64; across the full grid only two cells reach $p < 0.05$ at any single step (LLaDA-MBPP step 64, Qwen-JSON step 64). Thus the cross-DLM result should be read as a descriptive phase-alignment claim, with statistical support strongest for the LLaDA-MBPP plateau.

Top-feature drift and persistence. On LLaDA-8B / MBPP, pairwise Jaccard of the top-20 sets is high among steps 0–4 (≥ 0.48 , before committed-token information is available), moderate between 32 and 64 (0.29, the plateau regime), and falls to 0.14 between 64 and 127. On the sparse 7-step grid, only f15601 appears at all three peak-or-later steps. The dense sweep (Appendix F) sharpens this finding by ranking f15601 top-1 at 7 of 9 dense steps in [48, 80], supporting a persistent statisti-

condition	from	fail→pass	pass→fail
baseline	none	0/8	0/3
suppress f15601	s64	0/8	0/3
suppress f15601	s16	0/8	0/3
suppress top-5	s64	0/8	0/3
reverse f15601	s64	0/8	0/3

Table 1: Pilot steering intervention summary on LLaDA-8B / MBPP; entries show flips / evaluated cases. Conditions: baseline (no intervention); suppress f15601 at step 64 (peak) or step 16 (pre-peak); suppress the top-5 fail features at step 64; reverse intervention ($\alpha = -5$) amplifying f15601 at step 64. No condition converts any fail→pass or pass→fail.

cal marker rather than feature swapping inside the plateau. Outside the plateau, the sparse support reorganises as denoising commits different token blocks. Early features are unstable, the compact failure marker f15601 crystallises during steps 48–76, and the final state at step 127 spreads signal over a different set of atoms. The temporal peak is therefore a concentration effect in sparse feature space, not merely a monotonic increase in correctness information. Full Jaccard matrix and per-feature enrichment trajectories are in Figure 3 (Appendix A).

Pilot steering null result. We test whether the cluster-level feature signature can be directly controlled, restricting to LLaDA-8B / MBPP where the cluster reaches significance. We run five intervention conditions on cluster-1 fail cases and pass-side regression controls (Table 1; entries report flips / evaluated cases). Suppressing the persistent peak feature f15601 ($\alpha=5$) at the peak window (step 64) or before formation onset (step 16) yields *zero* fail→pass conversions and *zero* pass→fail regressions. Multi-feature suppression of the top-5 fail features at step 64 is also null. Reverse intervention ($\alpha = -5$, amplifying f15601) is null on pass-side cases as well. The hook does propagate. A separate zero-out test ($h \leftarrow 0$ at $t \geq 0$) destroys trailing generation while leaving the function body intact, consistent with LLaDA committing blocks 0–3 by step ~ 48 . This pilot result does not rule out causal roles for these features, but it does show that correctness is not flipped by ablating one direction or a small set of directions under this intervention protocol.

5 Discussion

Statistical vs. causal features. f15601 fires on 65% of LLaDA-8B / MBPP fails versus 27% of passes at step 64, a $\sim 6.6\sigma$ per-feature effect. Yet ablating it, or the top-5 fail features, in any of four

intervention windows flips no label. The cluster signature is useful as a diagnostic, but our intervention evidence is insufficient to treat this sparse direction as a knob that controls functional correctness. This contrasts with positive AR steering results on refusal and instruction following (O’Brien et al., 2024; He et al., 2025) but is consistent with reports that activation steering may degrade unrelated capabilities (Korznikov et al., 2025). More decisive causal tests would need paired counterfactual replacements, multi-layer interventions, or attribution from output-level correctness back to the SAE layer.

Why do peak times differ by task? By step 64, LLaDA has unmasked blocks 0–3 (the function signature and early body) but not blocks 4–7. For code and structural tasks, this mid-state appears to be where fail-vs-pass information is maximally factored into a small set of sparse features: enough tokens are settled to expose the failure mode, while later tokens still carry uncertainty. By step 127 the signal still exists but is less concentrated in the top-20 sparse features. For GSM8K and Dream-ARC, by contrast, the sparse cluster peaks only at the final checkpoint, suggesting that reasoning failures become feature-separable later than format or code failures. This task-dependent timing also explains why a single intervention window is unlikely to control correctness across tasks.

6 Conclusion

Tracing functional-correctness signal feature by feature reveals temporal structure that scalar probes miss: sparse failure markers form task-dependent phases. Code and structural tasks form a mid-denoising plateau, whereas reasoning tasks peak at the final state. This peak-phase pattern agrees across LLaDA-8B and Dream-7B on three of four tasks, with strongest support on LLaDA-MBPP. In that cell, a 3-seed dense sweep confirms a steps 48–116 plateau and a late hand-off from f15601 to f3892. Pilot linear-feature interventions do not flip correctness, so these sparse features are currently diagnostic markers; causal control likely requires stronger interventions.

Limitations

SAE coverage. All findings depend on a single DLM-Scope Mask-SAE per model (L26 for LLaDA, L23 for Dream), trained with mask rate $t \sim U(0, 1)$ on masked-position residuals. The full

denoising trajectory is therefore in distribution, but features extracted at other layers, the Unmask-SAE trained on already-revealed positions, or higher-capacity dictionaries ($K > 160$) may surface different failure correlates. Early-step instability (steps 0–16) reflects the residual stream not yet encoding committed-token decisions rather than SAE distribution shift.

Feature semantics. We identify persistent dictionary atoms such as f15601 and f3892 by statistical enrichment and temporal persistence, not by human-validated semantic labels. The present experiments therefore support a claim about when sparse failure markers concentrate, but they do not name the underlying error modes captured by each feature. Manual cluster inspection or activation-maximising examples would be needed to turn these feature IDs into interpretable failure categories.

Permutation test interpretation. Our permutation null re-selects the top-20 fail features on each shuffled label set before recomputing silhouette. This is conservative (any post-hoc selection procedure that could find clusters on random labels is included in the null), and it inflates the null mean noticeably (e.g. 0.36 for LLaDA-8B / MBPP at step 64). A consequence is that only two of twelve cells reach $p < 0.05$ at an individual step on the sparse 7-grid even though the DLM grid shows systematic plateau structure. The dense sweep in Appendix F shows 7 of 9 sub-steps in [48, 76] reach $p < 0.05$ on LLaDA-MBPP, so sparse-grid per-step significance is an underestimate; we present our cross-model claims as plateau-shape claims rather than per-cell significance.

Steering coverage. Our intervention sweep tests four denoising windows, two feature-set sizes (single and top-5), and one magnitude pair ($\alpha \in \{+5, -5\}$) at a single SAE layer per DLM (L26 for LLaDA, L23 for Dream). We do not test multi-layer joint interventions, non-linear projections, or feature-selection strategies that use the per-step top-1 (where the top fail feature differs from f15601). Effect-size diagnostics (Appendix H) confirm the intervention reaches $\|\Delta h\|/\|h\| \in [4.4\%, 14.8\%]$ at the SAE-layer residual, so the null result is not because the perturbation was silent; rather, a negative result on this protocol is narrower than a negative result on all possible linear-feature interventions.

Cluster K and choice of metric. We use silhouette on KMeans with $K \in \{2, 3, 4, 5\}$ and report the best K per cell. On LLaDA-8B / MBPP the best K is 2 at every step; on Dream / MBPP step 64 the best K is 3 with one small (size-26) sub-cluster. Appendix I reports top- N and clustering-method sensitivity: silhouette and significance are robust across $N \in \{10, 20, 30, 50\}$ at step 68 (the plateau peak) and across KMeans/Agglomerative/HDBSCAN. A labels-hidden $K=2$ test on the full fail+pass set yields $\text{ARI} \approx 0$, confirming the silhouette measures within-fail sub-structure rather than fail/pass separability; supervised AUC in Appendix E reports the latter.

Cross-model comparison. LLaDA uses block-wise unmasking with block length 32, whereas Dream uses a global linear schedule. At a matched checkpoint step, the spatial distribution of unmasked tokens differs between the models, so step-axis comparisons in Figure 2 reflect approximate denoising-progress alignments rather than identical model states. We do not attempt to map between block-wise commit fractions and global mask fractions on a per-sample basis. Our AR baseline (Qwen-2.5-7B) uses last-prompt-token hidden states; this is the natural single-token analog of the DLM’s pre-generation state but is not a temporal trajectory.

Task coverage. Functional correctness is verified across four tasks (MBPP, JSON schema, GSM8K, ARC), but this still covers only a small slice of DLM use cases. Generalising the task-dependent peak finding to other open-ended tasks (instruction following, dialog, multi-turn reasoning) requires task-appropriate functional metrics and additional DLMs.

Sample size and seed dependence. Cluster sample sizes are limited by the number of fail cases per (model, dataset) cell. MBPP has ~ 140 fails per DLM, while GSM8K has fewer than 250 each. A three-seed sensitivity check on LLaDA-MBPP (Appendix G) shows pass/fail counts vary by at most ± 3 samples and the plateau structure is preserved across seeds. The temporal-oscillation phenomenon noted in concurrent DLM work (Wang et al., 2025) would primarily affect borderline samples, which our seed-stability check is consistent with.

Causal interpretation. Even with the negative steering result, our conclusion that “f15601 is a diagnostic correlate rather than a directly controllable cause under our protocol” is interpretation-dependent. A more decisive test would be a counterfactual experiment that surgically replaces the feature direction with a paired pass-cluster feature direction at the peak step, or a gradient-based attribution that traces logit differences back to the SAE layer. We leave such causal-mechanistic follow-up to future work.

References

Jacob Austin, Daniel D. Johnson, Jonathan Ho, Danny Tarlow, and Rianne van den Berg. 2021a. Structured denoising diffusion models in discrete state-spaces. In *Advances in Neural Information Processing Systems*, volume 34, pages 17981–17993.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. 2021b. [Program synthesis with large language models](#). *arXiv preprint arXiv:2108.07732*.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermy, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, and 1 others. 2023. Towards monosemanticity: Decomposing language models with dictionary learning. *Anthropic Transformer Circuits Thread*.

Guan-Ming Chiu. 2026. Probing functional correctness in diffusion language models. In *Proceedings of the ACL 2026 Student Research Workshop*.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. [Think you have solved question answering? try ARC, the AI2 reasoning challenge](#). *arXiv preprint arXiv:1803.05457*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. [Training verifiers to solve math word problems](#). *arXiv preprint arXiv:2110.14168*.

Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. 2024. Sparse autoencoders find highly interpretable features in language models. *International Conference on Learning Representations*.

Andrey Galichin, Alexey Dontsov, Polina Druzhinina, Anton Razzhigaev, Oleg Y. Rogov, Elena Tutubalina, and Ivan Oseledets. 2025. I have covered all the bases here: Interpreting reasoning features in large language models via sparse autoencoders. *arXiv preprint arXiv:2503.18878*.

Leo Gao, Gabriel Goh, Ilya Sutskever, Stephanie Lin, Steven Bills, and Jeff Wu. 2024. Scaling and evaluating sparse autoencoders. *arXiv preprint arXiv:2406.04093*.

Zirui He, Haiyan Zhao, and 1 others. 2025. SAIF: A sparse autoencoder framework for interpreting and steering instruction following of language models. *arXiv preprint arXiv:2502.11356*.

Anton Korznikov and 1 others. 2025. The rogue scalpel: Activation steering compromises LLM safety. *arXiv preprint arXiv:2509.22067*.

Aaron Lou, Chenlin Meng, and Stefano Ermon. 2024. [Discrete diffusion modeling by estimating the ratios of the data distribution](#). *arXiv preprint arXiv:2310.16834*.

Alireza Makhzani and Brendan Frey. 2014. k-sparse autoencoders. In *International Conference on Learning Representations*.

Shen Nie, Fengqi Zhu, Chao You, Xiaojun Zhang, and Zhenguo Ou. 2025. [LLaDA: Large language diffusion with mAsking](#). *arXiv preprint arXiv:2502.09992*.

Kyle O’Brien, David Majercak, Xavier Fernandes, Richard Edgar, Jingya Chen, Harsha Nori, Dean Carignan, Eric Horvitz, and Forough Poursabzi-Sangdeh. 2024. Steering language model refusal with sparse autoencoders. *arXiv preprint arXiv:2411.11296*.

Subham Sekhar Sahoo, Marianne Arriola, Yair Schiff, Aaron Gokaslan, Edgar Marroquin, Justin T Chiu, Alexander Rush, and Volodymyr Kuleshov. 2024. [Simple and effective masked diffusion language models](#). *arXiv preprint arXiv:2406.07524*.

Qwen Team. 2024. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

Xu Wang, Bingqing Jiang, Yu Wan, Baosong Yang, Lingpeng Kong, and Difan Zou. 2026. [DLM-Scope: Mechanistic interpretability of diffusion language models via sparse autoencoders](#). *arXiv preprint arXiv:2602.05859*.

Ziming Wang, Jiahao Luo, Haowei Tang, and Tian Gao. 2025. [Time is a feature: Temporal oscillation in discrete diffusion language models](#). *arXiv preprint arXiv:2505.11229*.

Jiacheng Ye, Jiahui Gong, Yanru Lin, Ting Hin Zhuo, Tong Chen, Xin Jiang, Zhenguo Li, Qun Liu, and Lingpeng Liu. 2025. [Dream: Diffusion reasoning with enhanced accuracy and mastery](#). *arXiv preprint arXiv:2504.16915*.

A Top-Feature Persistence Across Steps

Figure 3 shows the pairwise Jaccard of top-20 fail features between denoising steps and the enrichment trajectory of three illustrative features for

#	characteristic features	illustrative failures
0	f11404, f189, f8825	f9798, f496, <i>closest smaller number</i> : returns n for small inputs instead of $n-1$, failing assertions. <i>unique element in sorted array</i> : malformed pointer-update code, syntax error.
1	f189, f3320, f15601	f492, f11404, <i>remove first/last occurrence</i> : deletes only boundary characters, missing interior occurrences. <i>lowercase underscore regex</i> : uses <code>re.compile</code> without importing <code>re</code> , <code>NameError</code> .

Table 2: Illustrative generated failures from the two LLaDA-MBPP step-64 fail clusters. Error-type counts over 10 regenerated failures per cluster: cluster 0 has 3 assertion / 2 syntax / 4 name / 1 value error; cluster 1 has 5 assertion / 4 name / 1 type error.

LLaDA-8B / MBPP. f15601 is the only feature among the top-20 at all three peak-or-later steps (32, 64, 127), and is the top-1 fail-enriched feature at both step 32 (+0.391 enrichment) and step 64 (+0.385); on the sparse 7-grid only step 64 reaches $p < 0.05$ (Figure 1 reports the dense sweep that locates the plateau).

B Qualitative Cluster Inspection

Table 2 shows illustrative LLaDA-MBPP failures from the two step-64 fail clusters. We re-generated the first ten fail samples from each cluster with the baseline LLaDA decoding setup and re-ran the MBPP tests. The examples are not intended as human-validated feature labels; they only show that both sparse clusters contain concrete functional failures, ranging from malformed code to plausible but semantically wrong implementations.

C Step-64 Cross-grid Snapshot

Table 3 summarises silhouette + permutation p across the 4 datasets $\times$ 3 models grid at step 64, complementing the trajectory-shape claim in Figure 2.

dataset	LLaDA	Dream	Qwen
mbpp	0.66 / 0.033	0.50 / 0.128	0.16 / 0.106
json	0.58 / 0.195	0.77 / 0.135	0.22 / 0.007
gsm8k	0.38 / 0.432	0.29 / 0.449	0.15 / 0.315
arc	0.43 / 0.312	0.18 / 0.882	0.13 / 0.343

Table 3: Silhouette / permutation p at step 64 per condition; bold $p < 0.05$. Full trajectory shown in Figure 2.

D Generation and Probing Details

Denoising procedure. Both models run 128 denoising steps. LLaDA uses block-based unmask-

ing: the generation region is divided into blocks of 32 tokens, and each block is denoised sequentially over $128/(\text{gen_length}/32)$ steps per block. Within each block, the model selects the most confident tokens to unmask at each step. Dream uses a global linear schedule: at step i , the fraction of tokens to unmask is determined by a linearly decreasing timestep schedule from $t = 1$ to $t = \epsilon$, and the most confident masked tokens are unmasked globally.

Prompt construction. For JSON schema, we prepend a system prompt containing the target schema and append a JSON code-fence marker as a generation prefix. For GSM8K, the system prompt instructs the model to solve step-by-step and end with ##### followed by the numeric answer. Both models use their respective chat templates. A complete prompt example for each task is shown in Figure 4.

Hidden state extraction. At each of the 7 checkpoint steps $\{0, 1, 4, 16, 32, 64, 127\}$, we run a forward pass with `output_hidden_states=True` and extract the residual stream at the SAE layer. The generation region is partitioned into 4 equal-length position regions and mean-pooled within each region, producing a d -dimensional vector per region (4096 for LLaDA, 3584 for Dream and Qwen). The region-mean is passed through the DLM-Scope SAE for feature analysis (§3).

Steering hook implementation. The steering hook is registered on the SAE-layer transformer block via `register_forward_hook`. The hook receives the tuple output, re-encodes `output[0]` through the SAE in-place, computes $\alpha \cdot z_{i^*} \cdot W_{\text{dec}}[:, i^*]$ and subtracts the contribution. A counter and per-step diagnostic prints confirm the hook fires $T=128$ times per generation (once per denoising step) and that the modification magnitude $\|\Delta h\|$ is non-zero.

Computational resources. All generation, encoding, and steering experiments use NVIDIA A100 (80GB) GPUs on Modal. Models are loaded in bfloat16; SAE weights cast to bfloat16 for the steering hook. Total compute: approximately 40 A100-hours across all reported experiments.

Reproducibility and determinism. Generation uses seed 0; both LLaDA and Dream commit the highest-confidence masked positions deterministically, so the fail/pass partition per cell is repro-




Figure 3: Left: pairwise Jaccard of top-20 fail features between denoising steps. Right: enrichment trajectory of f15601 (persistent peak), f5561 (early only), and f11265 (final only).

ducible across runs. Hidden states are cached as bfloat16 tensors; SAE encoding reads from the dense residual cache on demand, so top-20 selection, KMeans, and permutation null are rerunnable without re-invoking either DLM. The permutation null uses 1000 shuffles per cell with a fixed permutation seed offset, so silhouette p -values are themselves reproducible.

E Single-feature vs. Raw-probe AUC

We compare the cross-validated AUC of (i) the single most-fail-enriched SAE feature, (ii) top- N SAE features (logistic regression with per-fold selection), and (iii) a raw-probe baseline (PCA-64 + LR on the same hidden state) across all 12 cells (Figure 5). Raw-probe AUC dominates in 11 of 12 cells; the only SAE wins (Qwen / MBPP, Dream / ARC) are cells where the raw probe is itself near chance. Top-20 SAE features recover roughly 85–

95% of the raw-probe AUC, suggesting sparse atoms carry most but not all of the signal in the dense residual. This complements the negative steering finding (§4): even at optimal feature selection, sparse linear features under-represent the information that determines correctness.

F Dense Temporal Sweep on MBPP

We re-generate MBPP on both DLMs and capture hidden states at 9 dense checkpoints in [48, 80] (every 4 steps) and an additional 6 checkpoints in [84, 124] (every 8 steps), then run the same TopK-SAE encoding, top-20 fail enrichment, KMeans silhouette, and permutation null pipeline as the main 7-point grid. This sweep was requested as a robustness check against sparse-sampling artefacts. Generation uses seed 0 throughout; counts are LLaDA 115/142 and Dream 125/132 pass/fail. Three seeds confirm stability (Appendix G). Figure 6 plots the signal-to-null gap per step for both DLMs across the [48, 80] plateau region; Appendix G reports the [84, 124] post-plateau region across three seeds. Four findings emerge. **Plateau structure.** On LLaDA-MBPP the gap stays above +0.19 throughout [48, 116] with multiple significant sub-steps across three seeds. Step 64 (the only $p < 0.05$ point on the sparse 7-grid) sits in the middle of this plateau rather than at a sharp peak. The sparse-grid claim that step 64 is the unique peak should therefore be read as “step 64 is a representative point in the plateau”. **Late collapse.** The signal collapses sharply at step 124 (~ 3 steps before the final state), consistent with the residual stream re-organising as the generation completes block-by-block commits. **Plateau feature hand-off.** f15601 (LLaDA) is the top-1 fail-enriched feature at most dense steps

JSON schema (LLaDA chat template)

```
[BOS] system\n You are a helpful assistant
that answers in JSON. Here's the JSON schema
you must adhere to:\n <schema>\n {schema} \n
</schema>\n user\n {user input}\n assistant\n
""json\n
```

GSM8K (Dream chat template)

```
[BOS] im_start system\n Solve the math problem
step by step. End your answer with ####
followed by the final numeric answer. im_end\n
im_start user\n {question} im_end\n im_start
assistant\n
```

Figure 4: Schematic prompt examples after each model’s chat template is applied (special tokens shown as plain words for readability; the actual tokens used are model-specific control tokens). The generation region (128–512 masked tokens) is appended after the final assistant marker. Both models share the same system/user content; only the wrapping tokens differ.




Figure 5: Per-cell 5-fold cross-validated AUC at step 64 predicting functional correctness from top- N SAE features (logistic regression with per-fold top- N selection) versus a raw-probe baseline (PCA-64 + LR on the same SAE-layer hidden state). A star marks the per-cell winner; raw probe wins in 11 of 12 cells.




Figure 6: Dense step sweep (48–80 every 4 steps) on LLaDA-MBPP and Dream-MBPP. Hollow red rings mark LLaDA sub-steps with permutation $p < 0.05$; 7 of 9 sub-steps are significant on LLaDA, none reach significance on Dream. f15601 (LLaDA) and f6326 (Dream) are top-1 at most plateau steps.

in [48, 100] and is replaced by f3892 at the late-plateau steps 108–116. Dream-MBPP also shows a persistent top-1 marker (f6326) over [60, 76], so a similar within-plateau hand-off behaviour appears across DLMs even when the plateau itself is weaker. **Cross-DLM concentration.** Dream-MBPP shows the same temporal shape (a flat region across the middle of denoising) but at a much lower concentration: the gap never exceeds +0.16 and no sub-step reaches $p < 0.05$ under the same permutation null. The LLaDA $\times$ MBPP combination is therefore not a generic property of code generation but a model-specific point where the residual stream factors fail-vs-pass information into a small set of sparse features. This is consistent with LLaDA’s block-wise unmasking committing the function-signature block early, exposing fail-mode tokens at a denoising phase when later positions remain uncertain. We return to this contrast in §4.

G Seed Sensitivity

We re-run the LLaDA-MBPP dense sweep (Appendix F) with two additional generation seeds. Pass/fail counts vary by at most ± 3 samples across seeds (seed 0: 115/142, seed 1: 112/145, seed 2: 116/141). The plateau structure is preserved: each seed reaches $p < 0.05$ at ≥ 7 of 9 dense sub-steps in [48, 80], with f15601 as the majority top-1 fail-enriched feature across 48–80 and f3892 taking over at 108–116. The 3-seed gap-versus-step overlay is shown in Figure 1; per-seed numerical traces (gap, p -value, top-1 feature at every checkpoint) are released with the code.

H Intervention Effect Size

For $n=8$ cluster-1 fail samples per condition, the SAE-layer residual perturbation reaches $\|\Delta h\|/\|h\|=4.4\%$ for single-feature suppression of f15601 at s64 and s16 ($\|\Delta h\|=185$, $a_{\text{target}} \approx 9.43$), 14.8% for the top-5 combined suppression at s64 ($\|\Delta h\|=624$, $a_{\text{target}}=47.4$), and 4.4% for the reverse intervention at s64 ($\alpha = -5$). The target feature is reliably active during every intervention window, so the null steering result is consistent with functional correctness being distributively encoded: perturbing a sparse direction at the SAE-layer residual does not propagate into a label flip, even when that perturbation reaches $\sim 15\%$ of the residual norm.

I Post-hoc Selection Sensitivity

We reanalyse cached LLaDA-MBPP plateau residuals (seed 0) at the strongest plateau steps and report three robustness checks. **(a) Top- N .** Fig-

ure 7 plots the signal-to-null gap as N varies over $\{10, 20, 30, 50\}$. Step 68 remains $p < 0.05$ at every N , while step 64 degrades for $N \geq 30$, marking step 68 as the more robust plateau point. **(b) Clustering method.** At $N=20$, KMeans, Agglomerative (Ward), and HDBSCAN ($\text{min_size}=5$) all recover $K=2$ with near-identical silhouette at both steps (0.609 / 0.719 for step 64 / 68; HDBSCAN drops 11 samples as noise). **(c) Labels-hidden.** Clustering the full 257-sample fail+pass set at $K=2$ with the same top-20 features (selected via labels, cluster unsupervised) gives $\text{ARI} \approx -0.007$ at both steps ($p > 0.85$), confirming the silhouette signal measures within-fail sub-structure rather than fail/pass separability.




Figure 7: Signal-to-null gap as the top- N fail-feature cutoff is varied at LLaDA-MBPP plateau steps 64 and 68. Hollow rings mark $p < 0.05$. Step 68 is robust across N ; step 64 only reaches significance at $N=10$.

J Functional Correctness Definitions

Every task uses a deterministic, machine-checkable rubric; samples with no extractable candidate are labelled fail. **MBPP:** extract the first def-block or fenced “python block, prepend test_imports, run all assertions with a 10-second timeout; syntax errors, timeouts, and assertion failures are fails. **JSON schema:** output must parse as valid JSON and match the reference structure (top-level type, required keys, scalar-leaf types), ignoring key order and extra keys. **GSM8K:** compare only the final numeric answer; extract `####s*([-\\d.]+)` and compare to gold after stripping commas and trailing zeros. **ARC-Challenge:** extract `####s*([A-D])`; fallback to the last standalone A-D letter.