

Maximal Couplings of the Metropolis–Hastings Algorithm

Guanyang Wang (Rutgers Stats)

joint work with

John O’Leary

Harvard Stats

Pierre E. Jacob

Harvard Stats

AISTATS 2021

Outline

Introduction

Status Quo: Johnson's Coupling

Maximal Couplings

Numerical Examples

Concluding Remarks

What is a coupling?

Informal Definition: Given two random variables $X \sim p, Y \sim q$, a coupling of X and Y means a joint distribution such that its first marginal is p and second marginal is q .

What is a coupling?

Informal Definition: Given two random variables $X \sim p, Y \sim q$, a coupling of X and Y means a joint distribution such that its first marginal is p and second marginal is q .

Formal Definition: Let p, q be two probability measures on the same measurable space (S, \mathcal{S}) . A **coupling** of (p, q) is a probability measure γ on $(S \times S, \mathcal{S} \times \mathcal{S})$ such that for every $A \in \mathcal{S}$:

$$\gamma(A \times S) = p(A) \quad \text{and} \quad \gamma(S \times A) = q(A).$$

What is a coupling?

Informal Definition: Given two random variables $X \sim p, Y \sim q$, a coupling of X and Y means a joint distribution such that its first marginal is p and second marginal is q .

Formal Definition: Let p, q be two probability measures on the same measurable space (S, \mathcal{S}) . A **coupling** of (p, q) is a probability measure γ on $(S \times S, \mathcal{S} \times \mathcal{S})$ such that for every $A \in \mathcal{S}$:

$$\gamma(A \times S) = p(A) \quad \text{and} \quad \gamma(S \times A) = q(A).$$

Example: If X and Y are both (fair) coin flips, then


- ▶ Identity coupling: Flip a coin once, and set $X = Y =$ the outcome
- ▶ Negation coupling: Flip a coin once, and set $X =$ the outcome $= 1 - Y$
- ▶ Independent coupling: Flip a coin twice, $X =$ outcome of the first flip, $Y =$ outcome of the second flip.

Coupling inequality and maximal coupling

The Coupling Inequality: Let γ be any coupling of p and q , the coupling inequality says:

$$\mathbb{P}_{\gamma}(X = Y) \leq 1 - d_{\text{TV}}(p, q)$$

- ▶ $1 - d_{\text{TV}}(p, q)$ is the area of the shaded region




Coupling inequality and maximal coupling

The Coupling Inequality: Let γ be any coupling of p and q , the coupling inequality says:

$$\mathbb{P}_{\gamma}(X = Y) \leq 1 - d_{\text{TV}}(p, q)$$

- ▶ $1 - d_{\text{TV}}(p, q)$ is the area of the shaded region
- ▶ A coupling γ_0 is called a **maximal coupling** if


$$\mathbb{P}_{\gamma_0}(X = Y) = 1 - d_{\text{TV}}(p, q)$$



Coupling and Markov chain Monte Carlo

Coupling plays a central role in MCMC theory and methods. People use coupling for


- ▶ Analyzing convergence rates
- ▶ Perfect sampling
- ▶ Unbiased estimation
- ▶ Convergence diagnosis
- ▶ ...



Coupling and Markov chain Monte Carlo

Coupling plays a central role in MCMC theory and methods. Coupling has been used for

- ▶ Analyzing convergence rates
- ▶ Perfect sampling
- ▶ Unbiased estimation
- ▶ Convergence diagnosis
- ▶ ...



In many cases, **better** coupling design \approx **shorter** meeting time

Outline

Introduction

Status Quo: Johnson's Coupling

Maximal Couplings

Numerical Examples

Concluding Remarks

Johnson's Coupling: $\text{Max}^2 \neq \text{Max}$

- ▶ Theorists can construct any virtual coupling algorithm as long as it is mathematically correct. In practice, it is important for coupling algorithm to be **implementable**.

Johnson's Coupling: $\text{Max}^2 \neq \text{Max}$

- ▶ Theorists can construct any virtual coupling algorithm as long as it is mathematically correct. In practice, it is important for coupling algorithm to be **implementable**.
- ▶ The state of the art implementable coupling of Metropolis-Hastings (MH) transition kernels is introduced in Johnson [3] and used in Jacob, O'Leary, and Atchadé [2].

Johnson's Coupling: $\text{Max}^2 \neq \text{Max}$

- ▶ Theorists can construct any virtual coupling algorithm as long as it is mathematically correct. In practice, it is important for coupling algorithm to be **implementable**.
- ▶ The state of the art implementable coupling of Metropolis-Hastings (MH) transition kernels is introduced in Johnson [3] and used in Jacob, O'Leary, and Atchadé [2].
- ▶ Idea of Johnson's coupling: a **maximal** coupling of the proposal distribution followed by a **maximal** coupling of the acceptance/rejection step.

Johnson's Coupling: $\text{Max}^2 \neq \text{Max}$

- ▶ Theorists can construct any virtual coupling algorithm as long as it is mathematically correct. In practice, it is important for coupling algorithm to be **implementable**.
- ▶ The state of the art implementable coupling of Metropolis-Hastings (MH) transition kernels is introduced in Johnson [3] and used in Jacob, O'Leary, and Atchadé [2].
- ▶ Idea of Johnson's coupling: a **maximal** coupling of the proposal distribution followed by a **maximal** coupling of the acceptance/rejection step.
 - Works for very general MH algorithms, easy to implement 😊
 - Not a maximal coupling: $\text{Max proposal coupling} \times \text{Max acceptance/rejection coupling} \neq \text{Max transition kernel coupling}$ (which may result in slower meeting time) 😞

Johnson's Coupling: $\text{Max}^2 \neq \text{Max}$

- ▶ Theorists can construct any virtual coupling algorithm as long as it is mathematically correct. In practice, it is important for coupling algorithm to be **implementable**.
- ▶ The state of the art implementable coupling of Metropolis-Hastings (MH) transition kernels is introduced in Johnson [3] and used in Jacob, O'Leary, and Atchadé [2].
- ▶ Idea of Johnson's coupling: a **maximal** coupling of the proposal distribution followed by a **maximal** coupling of the acceptance/rejection step.
 - Works for very general MH algorithms, easy to implement 😊
 - Not a maximal coupling: $\text{Max proposal coupling} \times \text{Max acceptance/rejection coupling} \neq \text{Max transition kernel coupling}$
(which may result in slower meeting time) 😞
- ▶ Our contribution: We design three classes of implementable maximal couplings of the MH transition kernel.

Outline

Introduction

Status Quo: Johnson's Coupling

Maximal Couplings

Numerical Examples


Concluding Remarks

High level idea: go to a higher dimension

Sample $X \sim p \Leftrightarrow \text{Sample } (X, H) \sim \text{Unif}(S), S := \{(x, h) | h \leq p(x)\}$


A simple algorithm to sample from $\text{Unif}(S)$:

- ▶ Sample $x \sim p$
- ▶ Sample $u \sim \text{Unif}[0, 1]$
- ▶ Set $h = u \cdot p(x)$
- ▶ $(x, h) \sim \text{Unif}(S)$



Maximal coupling design

Maximally couple $P(x, \cdot)$ and $P(y, \cdot) \Leftrightarrow$ Couple everything in area A




Maximal coupling design

Maximally couple $P(x, \cdot)$ and $P(y, \cdot) \Leftrightarrow$ Couple everything in area A

A heuristic algorithm:

- ▶ Sample $x' \sim P(x, \cdot)$
- ▶ Sample h' such that $(x', h') \sim \text{Unif}(A \cup B)$
- ▶ If (x', h') in A : Set $y' = x'$ and we are done 😊
- ▶ Otherwise: Sample $(y', h'') \sim \text{Unif}(C)$




Maximal coupling design

Maximally couple $P(x, \cdot)$ and $P(y, \cdot) \Leftrightarrow$ Couple everything in area A

A heuristic algorithm:


- ▶ Sample $x' \sim P(x, \cdot)$
- ▶ Sample h' such that $(x', h') \sim \text{Unif}(A \cup B)$
- ▶ If (x', h') in A : Set $y' = x'$ and we are done 😊
- ▶ Otherwise: Sample $(y', h'') \sim \text{Unif}(C)$



The last step still needs to be carefully designed. The easiest way is to repeatedly sample $(y_{\text{new}}, h_{\text{new}}) \sim \text{Unif}(A \cup C)$ until it falls into C . Many other choices are available.

Maximal coupling design

- ▶ In our paper, we introduce three classes of maximal couplings: \bar{P}_{MI} , \bar{P}_{MR} , \bar{P}_{C}
- ▶ Numerical examples suggest \bar{P}_{C} works best when proposal has suitable symmetry.
- ▶ Big idea: \bar{P}_{C} uses **reflection coupling** for the proposal + **conditional acceptance coupling** depending on the region.
- ▶ In some regions, the acceptance probability is higher than the standard MH rate, while in some other regions is lower.



Outline

Introduction

Status Quo: Johnson's Coupling

Maximal Couplings

Numerical Examples

Concluding Remarks


- ▶ Question: In practice, is maximal coupling a big improvement?

- ▶ Question: In practice, is maximal coupling a big improvement?
- ▶ Answer: Sometimes, but not always!

- ▶ Question: In practice, is maximal coupling a big improvement?
- ▶ Answer: Sometimes, but not always!
 - In low dimensional cases, the maximal couplings will outperform non-maximal couplings,
 - In high dimensional cases, the advantage of maximal coupling is limited. Sometimes the non-maximal coupling perform better than than maximal couplings.

Example (Biased Random Walk MH)



- ▶ Take $\pi = \text{Expo}(1)$ and $Q(z, \cdot) = N(z + \kappa, \sigma^2)$ with $\kappa > 0$.
- ▶ Q tends to propose increasing values while a favors decreasing ones.
- ▶ We set $\kappa = \sigma^2 = 3$, draw $X_0, Y_0 \stackrel{iid}{\sim} \pi$, run 10,000 replications for each coupling, and record the meeting times.



Coupling	Avg. Meeting Time	S.E.
Non-maximal	74.0	0.94
Maximal	61.3	0.87

Example (Dimension Scaling with a Normal Target)

- Take $\pi = N(0, I_d)$ and $Q(z, \cdot) = N(z, I_d \sigma_d^2)$, $\sigma_d^2 = \frac{2.38^2}{d}$
- Upper plot: we draw $X_0, Y_0 \stackrel{iid}{\sim} \pi$, run 1,000 replications for each coupling, and record the meeting times for $d \in \{1, 2, \dots, 10\}$.
- Lower plot: we draw $X_0, Y_0 \stackrel{iid}{\sim} \pi$, run 1,000 replications for each coupling, and record the distance $\|X_t - Y_t\|$ for $d = 100$.
- In low dimensions they all perform similarly, in high dimensions \bar{P}_C performs best while \bar{P}_{MI} performs worst.



Outline

Introduction

Status Quo: Johnson's Coupling

Maximal Couplings

Numerical Examples

Concluding Remarks

Take-home Message

- ▶ We introduce three classes of implementable maximal couplings of MH transition kernels.

Take-home Message

- ▶ We introduce three classes of implementable maximal couplings of MH transition kernels.
- ▶ Their cost is roughly the same as the non-maximal couplings.

Take-home Message

- ▶ We introduce three classes of implementable maximal couplings of MH transition kernels.
- ▶ Their cost is roughly the same as the non-maximal couplings.
- ▶ They have **advantages**: easy to implement; can naturally generalize to other methods such as Metropolis-adjusted Langevin algorithm, pseudo-marginal Monte Carlo, MH-within-Gibbs; outperforms previous methods at least in low dimensional settings.
- ▶ They have **limitations**: The improvement in high-dimensional settings are very limited, sometimes not as good as previous methods.

Take-home Message

- ▶ We introduce three classes of implementable maximal couplings of MH transition kernels.
- ▶ Their cost is roughly the same as the non-maximal couplings.
- ▶ They have **advantages**: easy to implement; can naturally generalize to other methods such as Metropolis-adjusted Langevin algorithm, pseudo-marginal Monte Carlo, MH-within-Gibbs; outperforms previous methods at least in low dimensional settings.
- ▶ They have **limitations**: The improvement in high-dimensional settings are very limited, sometimes not as good as previous methods.
- ▶ What we have learned:
 - Maximizing contraction rates (the whole process) may be more important than maximizing the single step meeting probability (every single step).

Take-home Message

- ▶ Formal descriptions of algorithms, more theory and discussions are in our paper:

“Maximal couplings of the Metropolis–Hastings algorithm.” by O’Leary, Wang, and Jacob (2020).

- ▶ Code available on Github:

<https://github.com/johnoleary/mh-max-couplings>

- ▶ To learn more about coupling and Monte Carlo, please check out Pierre’s excellent lecture notes:

Couplings and Monte Carlo

Thanks!



Pierre E Jacob.

Lecture notes: Couplings and monte carlo.



Pierre E Jacob, John O'Leary, and Yves F Atchadé.

Unbiased Markov chain Monte Carlo methods with couplings.

Journal of the Royal Statistical Society: Series B (Statistical Methodology), 82(3):543–600, 2020.



Valen E Johnson.

A coupling-regeneration scheme for diagnosing convergence in markov chain monte carlo algorithms.

Journal of the American Statistical Association, 93(441):238–248, 1998.



John O'Leary, Guanyang Wang, and Pierre E Jacob.

Maximal couplings of the Metropolis-Hastings algorithm.

arXiv preprint arXiv:2010.08573, 2020.