Unified Batch & Stream Processing in Apache Flink



Apache Flink Meetup Berlin #6

April 29, 2015

Ufuk Celebi uce@apache.org

Batch vs. Stream Processing

Batch Processing

Stream Processing

High Latency

Low Latency

Batch Processors


Stream Processors

Static Files

Event Streams


What's the *difference* between a **Batch** and **Streaming** *Runtime*?

Batch Processing



O Romeo, Romeo, wherefore art thou Romeo? Write out Romeo, 1 intermediate Romeo, 1 data set wherefore, 1 art, 1 thou, 1 Romeo, 1 Romeo, 3 wherefore, 1 art, 1 thou, 1

Stream Processing



```
Romeo
               Romeo
wherefore art
                thou
                        Romeo
          Romeo, 1
          Romeo, 1
        wherefore, 1
            art, 1
           thou, 1
          Romeo, 1
          Romeo, 3
        wherefore, 1
            art, 1
           thou, 1
```

Batch VS. Stream Processing

Do we *really* need two **separate systems** for this?

Apache Flink

Batch

Processing

Stream

Processing

DataSet (Java/Scala)

DataStream (Java/Scala)


Flink Runtime

Flink Runtime




Intermediate Result

Operators



Operators represent computations over data.

Operators




Intermediate Results



Logical handle to data produced by operators.

Intermediate Results




Logical handle to data produced by operators.

Map-Reduce Example

```
DataSet<Tuple2<String, Integer>>
   counts;

counts = input
   .flatMap(new LineSplitter())
   .groupBy(0)
   .sum(1);
```



Logical handle to data produced by operators.

Result Characteristics

Pipelined vs. Blocking


Ephemeral vs. Checkpointed


Result Characteristics


Pipelined vs. Blocking


Ephemeral vs. Checkpointed


How and when to do data exchange?































































Result Characteristics


| | Ephemeral | Checkpointed |
|-----------|---|---|
| Pipelined | Low-latency | Low-latency |
| Blocking | Easy to reason about resource consumption | Easy to reason about resource consumption |


Result Characteristics


Pipelined vs. Blocking


Ephemeral vs. Checkpointed


How long to keep results around?






















































































Result Characteristics

| | Ephemeral | Checkpointed |
|-----------|---|---|
| Pipelined | Low-latency | Low-latency |
| | | Fine-grained fault tolerance |
| Blocking | Easy to reason about resource consumption | Fine-grained fault tolerance Easy to reason about resource consumption |

Benefits


- Very flexible design
- Decouples high-level requirements from runtime
 - Fault tolerance for batch vs. streaming
 - Different program optimization paths
 - Iterative programs
 - Interactive queries

Use cases




Graph analytics


Real-time stream processing



Large-scale Machine Learning



Flink Stack



Current Implementations

Pipelined vs. Blocking

Ephemeral vs. Checkpointed

Backpressure vs. No Backpressure

Current Implementations

Pipelined vs. Blocking

Ephemeral vs. Checkpointed

Backpressure vs. No Backpressure

Pipelined vs. Blocking in Flink

- Default type for both batch and streaming programs:
 Pipelined
- In batch mode only: use blocking exchange if necessary (e.g. to avoid deadlocks or break up long pipelines)
- More details: https://cwiki.apache.org/confluence/display/FLINK/Data+exchange+between+tasks

ExecutionConfig

```
// Set up the execution environment
ExecutionEnvironment env = ExecutionEnvironment
  .getExecutionEnvironment();
ExecutionConfig conf = env.getConfig();
// Remote data exchange is blocking (local is pipelined)
conf.setExecutionMode(ExecutionMode.BATCH);
// Remote and local data exchange is blocking
conf.setExecutionMode(ExecutionMode.BATCH_FORCED);
// Remote and local data exchange is pipelined except
// when necessary to avoid deadlocks etc. [DEFAULT]
conf.setExecutionMode(ExecutionMode.PIPELINED);
// Remote and local data exchange is always pipelined
conf.setExecutionMode(ExecutionMode.PIPELINED_FORCED);
```



flink.apache.org

@ApacheFlink