

CPSC 121: Models of Computation

Unit 2 Conditionals and Logical Equivalences

Based on slides by Patrice Belleville and Steve Wolfman

Unit 2 - Conditionals

1

Pre-Class Learning Outcomes

- By the start of this class you should be able to
 - Translate back and forth between simple natural language statements and propositional logic, now with conditionals and biconditionals.
 - Evaluate the truth of propositional logical statements that include conditionals and biconditionals using truth tables
 - Given a propositional logic statement and an equivalence rule, apply the rule to create an equivalent statement.

Unit 2 - Conditionals

2

Quiz 2 feedback

- Most frequent mistakes:

- Open-ended question?

Unit 2 - Conditionals

3

In-Class Learning Goals

By the end of this unit, you should be able to:

- Explore alternate forms of propositional logic statements by application of equivalence rules, especially in order to simplify complex statements or massage statements into a desired form.
- Evaluate propositional logic as a “model of computation” for combinational circuits and identify at least one explicit shortfall (e.g., referencing gate delays, wire length, instabilities, shared sub-circuits, etc.).

4

Where We Are in The Big Stories

Theory

- How do we model computational systems?

Now:

- practicing a second technique for formally establishing the truth of a statement (logical equivalence proofs).
- (the first technique was truth tables.)

Hardware

- How do we build devices to compute?

Now:

- learning to modify circuit designs using our logical model
- gaining more practice designing circuits
- identifying a flaw in our model for circuits.

5

The Meaning of \rightarrow

- The meaning of **if p then q** in propositional logic is not quite the same as in normal language.

➤ Consider:

if it's at least 20°C tomorrow, then I will come to UBC in shorts and T-shirt

- Suppose it's -2°C and snowing. Based on the above proposition, will I come to UBC in shorts and T-shirt?

- A. Yes
- B. No
- C. Maybe

Unit 2 - Conditionals

6

The Meaning of \rightarrow

- Consider the proposition

p: *If you fail the final exam, then you will fail the course*

- You need to distinguish between

- The truth value of p (whether or not I lied).
- The truth value of the conclusion (whether or not you failed the course).

Unit 2 - Conditionals

7

The Meaning of \rightarrow

Consider again:

p: *If you fail the final exam, then you will fail the course*

- If you fail the final exam, will you pass the course?

- A. Yes
- B. No
- C. Maybe

- If you pass the final exam, will you pass the course?

- A. Yes
- B. No
- C. Maybe

Unit 2 - Conditionals

8

More on the Meaning of \rightarrow

■ Which of the following statements is equivalent to :

if p then q ?

1. if not p then not q

A. YES B. NO

2. if not q then not p

A. YES B. NO

3. p unless q

A. YES B. NO

4. q unless not p

A. YES B. NO

5. q only if p

A. YES B. NO

6. p only if q

A. YES B. NO

p	q	$p \rightarrow q$	p unless q	p only if q
F	F	T		
F	T	T		
T	F	F		
T	T	T		

Note:

r unless s
means
if $\sim s$ then r

Unit 2 - Conditionals

9

Equivalence Proofs

■ How do we write a logical equivalence proof?

- We state the theorem we want to prove.
- We indicate the beginning of the proof by **Proof:**
- We start with one side and work towards the other,
 - one step at a time, using the basic equivalences shown on next page
 - without forgetting to justify each step
 - usually we will simplify the more complicated proposition, instead of trying to complicate the simpler one.
- We indicate the end of the proof by QED or \square

Unit 2 - Conditionals

10

Basic Logical Equivalences

Name	Rule	Name	Rule
Identity law	$p \wedge T \equiv p$ $p \vee F \equiv p$	Domination law	$p \wedge F \equiv F$ $p \vee T \equiv T$
Idempotent law	$p \wedge p \equiv p$ $p \vee p \equiv p$	Commutative law	$p \wedge q \equiv q \wedge p$ $p \vee q \equiv q \vee p$
Associative law	$p \wedge (q \wedge r) \equiv (p \wedge q) \wedge r$ $p \vee (q \vee r) \equiv (p \vee q) \vee r$	Distributive law	$p \vee (q \wedge r) \equiv (p \vee q) \wedge (p \vee r)$ $p \wedge (q \vee r) \equiv (p \wedge q) \vee (p \wedge r)$
Absorption law	$p \vee (p \wedge q) \equiv p$ $p \wedge (p \vee q) \equiv p$	Negation law	$p \wedge \sim p \equiv F$ $p \vee \sim p \equiv T$
Double negative law	$\sim(\sim p) \equiv p$	DeMorgan's law	$\sim(p \wedge q) \equiv (\sim p) \vee (\sim q)$ $\sim(p \vee q) \equiv (\sim p) \wedge (\sim q)$
Definition of \oplus	$p \oplus q \equiv (p \vee q) \wedge \sim(p \wedge q)$	Definition of \rightarrow	$p \rightarrow q \equiv \sim p \vee q$
Contrapositive law	$p \rightarrow q \equiv (\sim q) \rightarrow (\sim p)$		

Writing an Equivalence Proof

Theorem: $(\sim a \wedge b) \vee a \equiv a \vee b$

Proof:

$$\begin{aligned}
 & (\sim a \wedge b) \vee a \\
 & \equiv a \vee (\sim a \wedge b) && \text{commutative} \\
 & \equiv (a \vee \sim a) \wedge (a \vee b) && \text{distribution} \\
 & \equiv \underline{\hspace{2cm}} \\
 & \equiv a \vee b && \text{identity}
 \end{aligned}$$

QED

What's missing?

- $(a \vee b)$
- $F \wedge (a \vee b)$
- $a \wedge (a \vee b)$
- None of these, but I know what it is.
- None of these, and there's not enough information to tell.

12

Examples of Equivalence Proofs

■ Prove that

- $\sim p \rightarrow \sim q \equiv q \rightarrow p$
- $\sim p \wedge q \equiv (\sim p \vee q) \wedge \sim(\sim q \vee p)$

■ We will do these on the board .

How Good Propositional Logic Is?

■ Propositional Logic is not a perfect model of how gates work.

■ To understand why, we will look at a multiplexer

- A circuit that chooses between two or more values.
- In its simplest form, it takes 3 inputs
 - An input **a**, an input **b**, and a control input **select**.
 - It outputs **a** if **select** is false, and **b** if **select** is true.


Multiplexer

■ Truth table:

a	b	c	output
F	F	F	F
F	F	T	F
F	T	F	F
F	T	T	T
T	F	F	T
T	F	T	F
T	T	F	T
T	T	T	T


Outputs **a**'s value
when **c** is F and **b**'s
when **c** is T:

$$\begin{aligned}
 &(\sim a \wedge b \wedge c) \vee \\
 &(a \wedge \sim b \wedge \sim c) \vee \\
 &(a \wedge b \wedge \sim c) \vee \\
 &(a \wedge b \wedge c) \\
 &\equiv \\
 &(a \wedge \sim c) \vee (b \wedge c)
 \end{aligned}$$




MUX Design


■ Here is one possible implementation (call select "c"):



■ Let us see why this may not work as we expect...



Truthy MUX




What is the intended output if both a and b are T?

- A. T
- B. F
- C. Unknown... but could be answered given a value for c.
- D. Unknown... and might still be unknown even given a value for c.

17

Glitch in MUX Design

■ Suppose the circuit is in steady-state with a, b, c all T



■ Assume the gate delay is 10ns


Unit 2 - Conditionals

18

Trace

■ How long will it take before output reflects any changes in a, b, c and is stable?

- 5ns
- 10ns
- 20ns
- 30ns
- 40ns
- It may never be stable
- None of the above.




Unit 2 - Conditionals

19

Trace – 5 ns

■ Suppose that at time 0 we switch c to F.

■ At time 5ns:




Unit 2 - Conditionals

20

Trace – 10 ns

■ At time 10ns:




Unit 2 - Conditionals

21

Trace – 20 ns

■ At time 20ns:




■ Note: the output is now F

Unit 2 - Conditionals

22

Trace – 30 ns

■ At time 30ns:




■ Note: the output is now T again.

Unit 2 - Conditionals

23

Trace – 40 ns

■ At time 40ns:




Unit 2 - Conditionals

24


More MUX Glitches

- Cause of the problem: information from c travels two paths with different delays. Output can be incorrect until the longer path “catches up”.
- Which one(s) of the following operation may cause an instability?
 - A. Changing a only
 - B. Changing b only
 - C. Changing c, when at least one of a, b is F
 - D. Both (a) and (b)
 - E. None of (a), (b) and (c)



A Correct Design for MUX

- Here is a multiplexer that avoid the instability:



- **Exercise:** Prove that it's logically equivalent to the original MUX

➤ Hint: write $(a \wedge b)$ as $(a \wedge b \wedge (c \vee \sim c))$

Exercises

- Consider the code:
 - if target = value then
 - if lean-left-mode = true then
 - call the go-left() routine
 - else
 - call the go-right() routine
 - else if target < value then
 - call the go-left() routine
 - else
 - call the go-right routine

Let gl mean “the go-left() routine is called”. Complete the following:

➤ $gl \leftrightarrow$

Exercises

- Consider the sentence: “Two strings s1 and s2 are equal if either both strings are null or neither s1 nor s2 is null and both strings have the same sequence of characters”.
- Let
 - n1: the string s1 is null
 - n2: the string s2 is null
 - eq: s1 and s2 are equal
 - s: the two strings have the same sequence of characters.
- Is the given sentence logically equivalent to $eq \leftrightarrow (n1 \wedge n2) \vee s$?

Exercises

- Prove:

$$(a \wedge \sim b) \vee (\sim a \wedge b) \equiv (a \vee b) \wedge \sim (a \wedge b)$$

What is coming up?

- The third online quiz is due _____
 - Assigned reading for the quiz:
 - Epp, 4th edition: 2.5
 - Epp, 3rd edition: 1.5
 - Rosen, any edition: not much
 - http://en.wikipedia.org/wiki/Binary_numeral_system
 - Also read:
 - <http://www.ugrad.cs.ubc.ca/~cs121/2009W1/Handouts/signed-binary-decimal-conversions.html>
- Assignment #1 is due Friday, Jan 24 at 5:00pm.