Questions 1-5 and 11

Question 1:

a) Userinput, age , firstname, $price
b) 1stPlace, it starts with a digit. Java identifiers can contain numbers, but they must always begin with a letter, an underscore (_), or a dollar sign ($).

   User-name, it contains a hyphen (-). Java interprets the hyphen as a subtraction operator, which breaks the compiler.

   total , it contains an illegal symbol (#). The only special characters allowed in identifiers are underscores and dollar signs.

   class: It is a reserved keyword in Java used to define new classes, so it cannot be used as a name.

Question 2:

a) int numBeads;

   numBeads = 5;

b) int numBeads = 5;

Question 3:

a) myNumber = 4 x 2 = 8
   Your number = 8 + 5 = 13
   Answer: 13
b) myNumber = 4 + 7 =11
   Your number = myNumber = 11
   Answer: 11

Question 4:

a)int
b)double
c)int
d)double
e)boolean
f)char

Question 5:

a) A primitive data type stores simple values, int, double, boolean, or char. Abstract data type stores more complex stuff like lists or teams.
b) A class is a blueprint, an object is an instance of that class

Question 11:

a) y = (int) Math.round(j * k);
b) z = j * k; //no casting needed because the result already double
c) z= k*k; //no casting needed because result is already double
d) j = (int) Math.round(k);
e) k = j; //no casting needed because Java automatically converts an int to a double
f) y = j + 3; //no casting cause j and 3 fit in int