The ExaHyPE story & Profiling for ExaHyPE
Part I

Fabian Güra

www.exahype.eu

August 2016

The project has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement No 671698 (ExaHyPE).

Introduction

What this presentation is not about:

- **Numerics** deep dive (ADER-DG, Limiting, etc.)
- Performance analysis **case studies** and **scaling graphs** (next time)
- **Demo session** ;-(

Introduction

What this presentation is not about:

- **Numerics** deep dive (ADER-DG, Limiting, etc.)
- Performance analysis **case studies** and **scaling graphs** (next time)
- **Demo session** ;-(

What this presentation is about:

- **Context** and **motivation** behind the project
- Overview on **key objectives** of ExaHyPE
- Summary on **techniques** employed by the framework
- **Current state** and next steps on the agenda
- **Profiling** infrastructure for ExaHyPE

Context & Motivation

Important aspects in the context of Scientific Computing:

Simulation Pipeline



Exascale Computing

Hyperbolic Conservation Laws



Simulation Pipeline

Observations from practice:

- All steps are **repeated** over and over again!
- Nobody can be an **expert** in everything!
- Why not **focus** on what you are best in and consider the other problems **solved**?



The Simulation Pipeline
(via Hans-Joachim Bungartz: Modeling and Simulation (IN2010), 2015)

Exascale Computing

Major challenges*

- **Energy** consumption
- Multi-level **parallelism** on hybrid architectures
- Fault tolerance and **resilience**
- Memory and network **bandwidth bottlenecks**
- ...

* e.g. according to the U.S. Department of Energy: science.energy.gov/ascr/research/scidac/exascale-challenges/

Exascale Computing

Sunway TaihuLight, Wuxi, China, 2016
125 PFlop/s, 15.3 MW, 237M USD

An exascale system, Europe, 2020?

Exascale Computing

Sunway TaihuLight, Wuxi, China, 2016
125 PFlop/s, 15.3 MW, 237M USD

An exascale system, Europe, 2020?

Sorry, 148 SuperMUCs don't fit on a slide. . .

Hyperbolic Conservation Laws

General form:

$$\frac{\partial}{\partial t}\,[\boldsymbol{u}]_v + \frac{\partial}{\partial x_d}\,[\boldsymbol{F}(\boldsymbol{u})]_{vd} = [\boldsymbol{s}\,(\boldsymbol{u})]_v\,,$$

where $v \in \{1, 2, \dots, V\}$ and for $\boldsymbol{F} = [\boldsymbol{f}_1, \boldsymbol{f}_2, \dots, \boldsymbol{f}_D]$, $\frac{\partial [\boldsymbol{f}_d]_i}{\partial x_j}$ has **real eigenvalues** for all $d \in \{1, 2, \dots, D\}$.

Areas of application:

Geophysics



Simulation of ground shaking of the 1992 Landers Earthquake (via Alexander Heinecke, 2014)

Gas dynamics



Simulated pressure wave in a compressible gas (via Dominic E. Charrier, 2016)

Astrophysics



Simulation of the merger of two magnetized neutron stars (via Luciano Rezzolla, 2008)

Hyperbolic Conservation Laws

General form:

$$\frac{\partial}{\partial t}[\boldsymbol{u}]_v + \frac{\partial}{\partial x_d}[\boldsymbol{F}(\boldsymbol{u})]_{vd} = [\boldsymbol{s}(\boldsymbol{u})]_v\,,$$

where $v \in \{1, 2, \ldots, V\}$ and for $\boldsymbol{F} = [\boldsymbol{f}_1, \boldsymbol{f}_2, \ldots, \boldsymbol{f}_D]$, $\frac{\partial [\boldsymbol{f}_d]_i}{\partial x_j}$ has **real eigenvalues** for all $d \in \{1, 2, \ldots, D\}$.

Challenges:

- Long-term **accuracy**
- **Stability** at shocks
- Time step restrictions
  (e.g. for stiff source terms)
- **Arithmetic density** and **data locality**



Example: Linear Advection

(via Eleuterio F. Toro, 2009)

Hyperbolic Conservation Laws

General form:

$$\frac{\partial}{\partial t}[\boldsymbol{u}]_v + \frac{\partial}{\partial x_d}[\boldsymbol{F}(\boldsymbol{u})]_{vd} = [\boldsymbol{s}(\boldsymbol{u})]_v \,,$$

where $v \in \{1, 2, \ldots, V\}$ and for $\boldsymbol{F} = [\boldsymbol{f}_1, \boldsymbol{f}_2, \ldots, \boldsymbol{f}_D]$, $\frac{\partial [\boldsymbol{f}_d]_i}{\partial x_j}$ has **real eigenvalues** for all $d \in \{1, 2, \ldots, D\}$.

Challenges:

- Long-term **accuracy**
- **Stability** at shocks
- Time step restrictions (e.g. for stiff source terms)
- **Arithmetic density** and **data locality**



Example: Linear Advection

(via Eleuterio F. Toro, 2009)

ExaHyPE: The Project

Vision:

- Three pillars of scientific progress:
  Theory, Experiment and **Simulation**
- Programming (exascale) supercomputers is a key challenge
- The ExaHyPE project seeks to address the **software aspect** of supercomputer development
  - Development of new mathematical and algorithmic approaches
  - Initial focus on applications in geo- and astrophysics
  - In correspondence with Europe's **2020 exascale strategy**

ExaHyPE: The Project

Objectives:

- **Energy efficiency** on tomorrow's supercomputing hardware
- Scalable algorithms through well-balanced **dynamic adaptivity**
- **Compute-bound** simulations in spite of slow memory and networks
- Extreme parallelism on **unreliable hardware**

ExaHyPE: The Project

Benefit:

- Simulation of **risk scenarios**
  - Assess the effects of earthquake and aftershocks
  - Quantify seismic hazards
- Enable fundamental **scientific findings**
  - Study some of the longest-standing mysteries in astrophysics. . .
  - . . . and other disciplines
- **Open-source** (BSD3,)



Simulation of the 1992 Landers Earthquake
(via Alexander Heinecke, 2014)

ExaHyPE: The Project

Approach:

- High-order space-time Discontinuous Galerkin method (**ADER-DG**) with a-posteriori FVM based subcell limiting
- Dynamically adaptive Cartesian grids (**AMR**), space filling curves and dynamic load balancing (**Peano**)
- Hardware specific optimization of dominant compute kernels (**libxsmm**)



Adaptive grids in Peano
(via Tobias Weinzierl, 2014)

ExaHyPE: Applications

Hyperbolic Conservation Laws:

$$\frac{\partial}{\partial t}\left[\boldsymbol{u}\right]_v + \frac{\partial}{\partial x_d}\left[\boldsymbol{F}(\boldsymbol{u})\right]_{vd} = \left[\boldsymbol{s}\left(\boldsymbol{u}\right)\right]_v$$

Initial focus:

Geophysics



Simulation of ground shaking of the 1992 Landers Earthquake

Gas dynamics



Simulation of the merger of two magnetized neutron stars

ExaHyPE: From a User's Perspective



ExaHyPE: From a User's Perspective

```
peano-path                  = ./Peano/peano
tarch-path                  = ./Peano/tarch
multiscalelinkedcell-path   = ./Peano/multiscalelinkedcell
sharedmemoryoracles-path    = ./Peano/sharedmemoryoracles
exahype-path                = ./ExaHyPE

libxsmm-path                = ../mypath
output-directory            = ./Applications/eulerflow2d
architecture                = noarch

computational-domain
  dimension                 = 2
  width                     = 1.0
  offset                    = 0.0, 0.0
  end-time                  = 0.1
end computational-domain


solver ADER-DG MyEulerSolver
  unknowns   = 5
  parameters = 0
  order      = 3
  kernel     = generic::fluxes::nonlinear
  language   = C
  /* language  = Fortran */

  plot vtk::binary
    time     = 0.0
    repeat   = 0.05
    filename = ./solution
  end plot
end solver

shared-memory
  identifier                = dummy
  cores                     = 2
  properties-file           = sharedmemory.properties
end shared-memory

optimisation
  fuse-algorithmic-steps    = off
end optimisation

end exahype-project
```

+

Implement:

- Flux
- Eigenvalues
- Source
- Initial conditions

ExaHyPE: Agenda

Current state:

- ADER-DG (unlimited) and FVM **solvers**
- Shared- and distributed-memory **parallelization**
- Static mesh refinement
- ”Shu vortex” **analytic benchmark**
- Advanced **export** capabilities

Next steps:

- ADER-DG with a-posteriori subcell **limiting**
- Dynamic **AMR**
- Additional analytic benchmarks
- Improved **load balancing**
- **Petascale prototype**
- Parallel IO

ExaHyPE: Summary



Associated Partner

Profiling for ExaHyPE: Motivation

You can't optimize for what you don't measure!

Profiling provides metrics to

- obtain a **baseline**,
- **track progress** of optimization efforts,
- **compare** current status to other state of the art solutions.

We don't need a third one of these on campus!

Profiling for ExaHyPE: Architecture



Profiling for ExaHyPE: Architecture



Profiling for ExaHyPE: Metrics

What we can measure at the moment:

- Kernel call counts
- Cycles and wall clock time
- RAM reads/writes
- **Flop/s** (estimate)
- **Energy consumption** (Core, RAM, package; estimate)
- Cache hits/misses/ratio (I, L2, L3)
- **Cycles lost** due to cache misses (L2, L3)
- Instructions retired
- Branch prediction ratio
- …

Profiling for ExaHyPE: Outlook

Profiling: Next steps

- Comparison **cell update time**:
  Generic C++ vs. optimized C++ vs. Fortran baseline
- Case study: Fast, **metric-driven optimization** of generic kernels
- Relation polynomial degree, energy consumption/runtime
  \+ **explanation** based on **profiling insights**
- Analytic benchmark, AMR, fixed error:
  Relation polynomial degree, energy consumption
  Goal: Find real world **break-even point**
- ...

Profiling for ExaHyPE - Part II

Conclusion

Key aspects:

1. Exascale Computing is about both hardware and **software**
2. ExaHyPE as an **answer to future challenges** in Scientific Computing
3. **Frameworks** are necessary to manage the increasing complexity in HPC
4. Profiling is important: **Measure, then optimize!**

The ExaHyPE story & Profiling for ExaHyPE
Part I

Fabian Güra

www.exahype.eu

August 2016

The project has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement No 671698 (ExaHyPE).

ADER-DG



via Dominic E. Charrier, 2016