

# Lab 3: Cocktail Sort

## 1. Objective

Write an assembly programs to implement Cocktail Sort, a bidirectional variation of the Bubble Sort algorithm.

## 2. Background

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in the wrong order. It traverses elements from left and moves the largest element to its correct position in the first iteration and second-largest in the second iteration and so on.

<https://www.geeksforgeeks.org/dsa/bubble-sort-algorithm/>

Sorting Algorithms Redux 03: Bubble Sort

<https://www.youtube.com/watch?v=jAoBsroEow4>

Cocktail Sort is a variation of Bubble Sort. Cocktail Sort traverses through a given array in both directions alternatively.

<https://www.geeksforgeeks.org/dsa/cocktail-sort/>

Sorting Algorithms Redux 04: Cocktail Sort

[https://www.youtube.com/watch?v=Xmx\\_6YRBaq8](https://www.youtube.com/watch?v=Xmx_6YRBaq8)

The following table compares these two algorithms:

| Feature                  | Basic Bubble Sort | Cocktail Sort                    |
|--------------------------|-------------------|----------------------------------|
| Sorting direction        | Forward only      | Forward + backward passes        |
| Loop boundaries          | Stays constant    | Shifts left and right boundaries |
| Swap flag for early exit | Yes               | Yes                              |

## 3. Lab Steps

You are given an assembly program [bubblesort.s](#) that implements the Bubble Sort algorithm as the starting point, and a main.c file as a test harness. Your task is to implement the Cocktail Sort algorithm based on the C program at <https://www.geeksforgeeks.org/dsa/cocktail-sort/>. Your implementation must be derived from the provided Bubble Sort algorithm, with the same code for Forward pass (left to right), and adding a separate Backward pass (right to left), i.e., you cannot write an implementation that is completely different from the provided code.

Compile and run:

```
arm-linux-gnueabi-hf-as -o bubblesort.o bubblesort.s
```

```
arm-linux-gnueabi-hf-gcc -o main main.c bubblesort.o
```

## 4. Report

Put your implementation as a subroutine cocktail\_sort in bubblesort.s and upload both this file and main.c file. Use the project report template and submit the report in PDF format. Please copy and paste your

implemented Cocktail Sort algorithm into the report, and provide a line-by-line explanation of the new code that you wrote.