

# CSC 112: Computer Operating Systems

## Lecture 6

### Real-Time Scheduling

### Exercises ANS

Department of Computer Science,  
Hofstra University

## Q1. Schedulability under RM or EDF


---

- Determine schedulability of the following tasksets under (1) Rate Monotonic (RM) scheduling, using Utilization Bound test and/or Response Time Analysis (RTA) to determine taskset schedulability. (2) Earliest Deadline First (EDF) scheduling, using Utilization Bound test. We use the notation  $\tau_i (C_i, T_i, D_i)$  to denote task  $\tau_i$  with WCET  $C_i$  Period  $T_i$ , Deadline  $D_i$  (c.f. Slide 33 in Lecture 6)
- 1) Taskset  $\tau_1 (3, 6, 6), \tau_2 (4, 9, 9)$
- 2) Taskset  $\tau_1 (3, 6, 6), \tau_2 (3, 9, 9)$
- 3) Taskset  $\tau_1 (3, 6, 6), \tau_2 (2, 9, 9)$
- 4) Taskset  $\tau_1 (2, 4, 4), \tau_2 (4, 8, 8)$
- 5) Taskset  $\tau_1 (2, 5, 5), \tau_2 (4, 7, 7)$
- 6) Taskset  $\tau_1 (1, 2, 2), \tau_2 (2.5, 5, 5)$


# Tasks	RM Util Bound
1	1.00
2	0.828
3	0.780

# Q1. Schedulability under RM or EDF ANS

- 1) Taskset  $\tau_1(3, 6, 6), \tau_2(4, 9, 9)$
- System utilization  $U = \frac{3}{6} + \frac{4}{9} = 0.944 > 0.828$  (UB for 2 tasks under RM). Since utilization exceeds the RM bound, we cannot determine its schedulability under RM, so we perform RTA to compute WCRT of each task, by solving  $R_i = C_i + \sum_{j \in hp(i)} \left\lceil \frac{R_i}{T_j} \right\rceil C_j$
- For higher-priority (smaller period) task  $\tau_1, R_1 = C_1 = 3 \leq D_1 = 6$ , hence  $\tau_1$  is schedulable
- For lower-priority (larger period) task  $\tau_2, R_2 = C_2 + \left\lceil \frac{R_2}{T_1} \right\rceil C_1 = 4 + \left\lceil \frac{R_2}{6} \right\rceil \cdot 3$ , solving it iteratively gives  $R_2 = 10 > D_2 = 9$ , hence  $\tau_2$  is not schedulable
- This taskset is unschedulable under RM.
- System utilization  $U = \frac{3}{6} + \frac{4}{9} = 0.944 \leq 1$  (UB under EDF), hence this taskset is schedulable under EDF
- (You are not required to draw the Gantt charts below, they are FYI only.)




Gantt chart for RM



Gantt chart for EDF


# Q1. Schedulability under RM or EDF ANS

- 2) Taskset  $\tau_1(3, 6, 6), \tau_2(3, 9, 9)$
- System utilization  $U = \frac{3}{6} + \frac{3}{9} = 0.833 > 0.828$ . Since utilization exceeds the RM bound, we cannot determine its schedulability under RM, so we perform RTA to compute WCRT of each task, by solving  $R_i = C_i + \sum_{j \in hp(i)} \left\lceil \frac{R_i}{T_j} \right\rceil C_j$
- For higher-priority (smaller period) task  $\tau_1, R_1 = C_1 = 3 \leq D_1 = 6$ , hence  $\tau_1$  is schedulable
- For lower-priority (larger period) task  $\tau_2, R_2 = C_2 + \left\lceil \frac{R_2}{T_1} \right\rceil C_1 = 3 + \left\lceil \frac{R_2}{6} \right\rceil \cdot 3$ , solving it iteratively gives  $R_2 = 6 \leq D_2 = 9$ , hence  $\tau_2$  is schedulable
  - $R_2 = 9$  is another possible solution for the recursive equation, but we consider the **minimum fixed-point solution** of  $R_2 = 6$
- We determine this taskset to be schedulable under RM.
- System utilization  $U = \frac{3}{6} + \frac{4}{9} = 0.833 \leq 1$ , hence this taskset is schedulable under EDF




## Q1. Schedulability under RM or EDF ANS

- 3) Taskset  $\tau_1(3, 6, 6), \tau_2(2, 9, 9)$
- System utilization  $U = \frac{3}{6} + \frac{2}{9} = 0.722 \leq 0.828$ . Since utilization is within the RM bound, we determine this taskset to be schedulable under RM, without the need for RTA
- System utilization  $U = \frac{3}{6} + \frac{2}{9} = 0.722 \leq 1$ , hence this taskset is schedulable under EDF




Gantt chart for RM



Gantt chart for EDF (same as RM)

# Q1. Schedulability under RM or EDF ANS

- 4) Taskset  $\tau_1(2, 4, 4), \tau_2(4, 8, 8)$
- System utilization  $U = \frac{2}{4} + \frac{4}{8} = 1.0 > 0.828$ . Since utilization exceeds the RM bound, we cannot determine its schedulability under RM, so we perform RTA to compute WCRT of each task, by solving  $R_i = C_i + \sum_{\forall j \in hp(i)} \left\lceil \frac{R_i}{T_j} \right\rceil C_j$
- For higher-priority (smaller period) task  $\tau_1, R_1 = C_1 = 2 \leq D_1 = 4$ , hence  $\tau_1$  is schedulable
- For lower-priority (larger period) task  $\tau_2, R_2 = C_2 + \left\lceil \frac{R_2}{T_1} \right\rceil C_1 = 4 + \left\lceil \frac{R_2}{4} \right\rceil \cdot 2$ , solving it iteratively gives  $R_2 = 8 \leq D_2 = 8$ , hence  $\tau_2$  is schedulable
- We determine this taskset to be schedulable under RM.
  - We can also skip RTA, and use this condition to this taskset to be schedulable under RM. “If periods are harmonic (larger periods divisible by smaller periods), then utilization bound is 1.”
- System utilization  $U = \frac{2}{4} + \frac{4}{8} = 1.0 \leq 1$ , hence this taskset is schedulable under EDF




Gantt chart for RM

Gantt chart for EDF (same as RM)


# Q1. Schedulability under RM or EDF ANS

- 5) Taskset  $\tau_1(2, 5, 5), \tau_2(4, 7, 7)$
- System utilization  $U = \frac{2}{5} + \frac{4}{7} = 0.97 > 0.828$ .  
Since utilization exceeds the RM bound, we cannot determine its schedulability under RM, so we perform RTA to compute WCRT of each task, by solving  $R_i = C_i + \sum_{\forall j \in hp(i)} \left\lceil \frac{R_i}{T_j} \right\rceil C_j$
- For higher-priority (smaller period) task  $\tau_1, R_1 = C_1 = 2 \leq D_1 = 5$ , hence  $\tau_1$  is schedulable
- For lower-priority (larger period) task  $\tau_2, R_2 = C_2 + \left\lceil \frac{R_2}{T_1} \right\rceil C_1 = 4 + \left\lceil \frac{R_2}{5} \right\rceil \cdot 2$ , solving it iteratively gives  $R_2 = 8 > D_2 = 7$ , hence  $\tau_2$  is not schedulable
- This taskset is unschedulable under RM
- System utilization  $U = \frac{2}{5} + \frac{4}{7} = 0.97 \leq 1$ , hence this taskset is schedulable under EDF



# Q1. Schedulability under RM or EDF ANS

- 6) Taskset  $\tau_1(1, 2, 2)$ ,  $\tau_2(2.5, 5, 5)$
- System utilization  $U = \frac{1}{2} + \frac{2.5}{5} = 1 > 0.828$ . Since utilization exceeds the RM bound, we cannot determine its schedulability under RM, so we perform RTA to compute WCRT of each task, by solving  $R_i = C_i + \sum_{\forall j \in hp(i)} \left\lceil \frac{R_i}{T_j} \right\rceil C_j$
- For higher-priority (smaller period) task  $\tau_1$ ,  $R_1 = C_1 = 1 \leq D_1 = 2$ , hence  $\tau_1$  is schedulable
- For lower-priority (larger period) task  $\tau_2$ ,  $R_2 = C_2 + \left\lceil \frac{R_2}{T_1} \right\rceil C_1 = 2.5 + \left\lceil \frac{R_2}{2} \right\rceil \cdot 1$ , solving it iteratively gives  $R_2 = 5.5 > D_2 = 5$ , hence  $\tau_2$  is not schedulable
- This taskset is unschedulable under RM
- System utilization  $U = \frac{1}{2} + \frac{2.5}{5} = 1 \leq 1$ , hence this taskset is schedulable under EDF






## Q2. Schedulability under RM, DM, or EDF

---


- Determine schedulability of the following tasksets under (1) Rate Monotonic (RM) scheduling, using Utilization Bound test and/or Response Time Analysis (RTA) to determine taskset schedulability. (2) Deadline Monotonic (DM) scheduling (3) Earliest Deadline First (EDF) scheduling, using Utilization Bound test.
- 1) Taskset  $\tau_1 = (0.5, 3, 3)$ ,  $\tau_2 = (1, 4, 4)$ ,  $\tau_3 = (2, 6, 6)$
- 2) Taskset  $\tau_1 = (0.5, 3, 3)$ ,  $\tau_2 = (1, 4, 2)$ ,  $\tau_3 = (2, 6, 6)$
- 3) Taskset  $\tau_1 = (1, 3, 3)$ ,  $\tau_2 = (1, 4, 2)$ ,  $\tau_3 = (2, 6, 6)$

## Recall: RM vs. DM Example

- Three tasks:  $\tau_1 = (0.5, 3, 3)$ ,  $\tau_2 = (1, 4, 4)$ ,  $\tau_3 = (2, 6, 6)$
- Under RM (or DM), priority ordering  $\tau_1 > \tau_2 > \tau_3$



- Three tasks with  $\tau_2$  assigned a smaller deadline of  $D_2 = 2$ :  $\tau_1 = (0.5, 3, 3)$ ,  $\tau_2 = (1, 4, \textcolor{red}{2})$ ,  $\tau_3 = (2, 6, 6)$
- Under DM, priority ordering  $\tau_2 > \tau_1 > \tau_3$



## Q2. Schedulability under RM, DM, or EDF ANS

---

- Three tasks:  $\tau_1 = (0.5, 3, 3)$ ,  $\tau_2 = (1, 4, 4)$ ,  $\tau_3 = (2, 6, 6)$ 
  - For RM: priority ordering  $\tau_1 > \tau_2 > \tau_3$ 
    - » System utilization  $U = \frac{0.5}{3} + \frac{1}{4} + \frac{2}{6} = 0.75 \leq 0.780$  (UB for 2 tasks under RM), hence the taskset is schedulable under RM
  - For DM: priority ordering  $\tau_1 > \tau_2 > \tau_3$ 
    - » Since  $D_i = T_i$ , DM scheduling is the same as RM scheduling, hence it is also schedulable under DM
  - For EDF: System utilization  $U = \frac{0.5}{3} + \frac{1}{4} + \frac{2}{6} = 0.75 \leq 1$  (UB for EDF), hence the taskset is schedulable under EDF

## Q2. Schedulability under RM, DM, or EDF ANS

---

- Three tasks:  $\tau_1 = (0.5, 3, 3)$ ,  $\tau_2 = (1, 4, 2)$ ,  $\tau_3 = (2, 6, 6)$
- No Utilization Bound test for RM or DM, for taskset with  $D_i < T_i$ ; need to use Response Time Analysis (RTA)
- For RM: priority ordering  $\tau_1 > \tau_2 > \tau_3$ 
  - $R_1 = C_1 + 0 = 0.5 + 0 = 0.5 \leq D_1 = 3$
  - $R_2 = C_2 + \left\lceil \frac{R_1}{T_1} \right\rceil \cdot C_1 = 1 + \left\lceil \frac{0.5}{3} \right\rceil \cdot 0.5 = 1.5 \leq D_2 = 2$
  - $R_3 = C_3 + \left\lceil \frac{R_3}{T_1} \right\rceil \cdot C_1 + \left\lceil \frac{R_3}{T_2} \right\rceil \cdot C_2 = 2 + \left\lceil \frac{R_3}{3} \right\rceil \cdot 0.5 + \left\lceil \frac{R_3}{4} \right\rceil \cdot 1 = 4 \leq D_3 = 6$ 
    - Since all tasks meet their deadlines, the taskset is schedulable
- For DM: priority ordering  $\tau_2 > \tau_1 > \tau_3$ 
  - $R_2 = C_2 + 0 = 1 + 0 = 1 \leq D_2 = 2$
  - $R_1 = C_1 + \left\lceil \frac{R_1}{T_2} \right\rceil \cdot C_2 = 0.5 + \left\lceil \frac{0.5}{4} \right\rceil \cdot 1 = 1.5 \leq D_1 = 3$
  - $R_3 = C_3 + \left\lceil \frac{R_3}{T_2} \right\rceil \cdot C_2 + \left\lceil \frac{R_3}{T_1} \right\rceil \cdot C_1 = 2 + \left\lceil \frac{R_3}{4} \right\rceil \cdot 1 + \left\lceil \frac{R_3}{3} \right\rceil \cdot 0.5 = 4 \leq D_3 = 6$ 
    - Since all tasks meet their deadlines, the taskset is schedulable
- For EDF:
  - System density  $\Delta = \frac{0.5}{3} + \frac{1}{2} + \frac{2}{6} = 1.0 \leq 1$ , hence this taskset is schedulable under EDF

## Q2. Schedulability under RM, DM, or EDF ANS

---

- Three tasks:  $\tau_1 = (1, 3, 3), \tau_2 = (1, 4, 2), \tau_3 = (2, 6, 6)$
- No Utilization Bound test for RM or DM, for taskset with  $D_i < T_i$ ; need to use Response Time Analysis (RTA)
- For RM: priority ordering  $\tau_1 > \tau_2 > \tau_3$ 
  - $R_1 = C_1 + 0 = 1 + 0 = 1 \leq D_1 = 3$
  - $R_2 = C_2 + \left\lceil \frac{R_1}{T_1} \right\rceil \cdot C_1 = 1 + \left\lceil \frac{1}{3} \right\rceil \cdot 1 = 2 \leq D_2 = 2$
  - $R_3 = C_3 + \left\lceil \frac{R_3}{T_1} \right\rceil \cdot C_1 + \left\lceil \frac{R_3}{T_2} \right\rceil \cdot C_2 = 2 + \left\lceil \frac{R_3}{3} \right\rceil \cdot 1 + \left\lceil \frac{R_3}{4} \right\rceil \cdot 1 = 6 \leq D_3 = 6$
  - Since all tasks meet their deadlines, the taskset is schedulable
- For DM: priority ordering  $\tau_2 > \tau_1 > \tau_3$ 
  - $R_2 = C_2 + 0 = 1 + 0 = 1 \leq D_2 = 2$
  - $R_1 = C_1 + \left\lceil \frac{R_1}{T_2} \right\rceil \cdot C_2 = 1 + \left\lceil \frac{1}{4} \right\rceil \cdot 1 = 2 \leq D_1 = 3$
  - $R_3 = C_3 + \left\lceil \frac{R_3}{T_2} \right\rceil \cdot C_2 + \left\lceil \frac{R_3}{T_1} \right\rceil \cdot C_1 = 2 + \left\lceil \frac{R_3}{4} \right\rceil \cdot 1 + \left\lceil \frac{R_3}{3} \right\rceil \cdot 1 = 6 \leq D_3 = 6$
  - Since all tasks meet their deadlines, the taskset is schedulable
- Three tasks:  $\tau_1 = (1, 3, 3), \tau_2 = (1, 4, 2), \tau_3 = (2, 6, 6)$  under EDF
  - System density  $\Delta = \frac{1}{2} + \frac{1}{2} + \frac{2}{6} = 1.17 > 1$ , hence we CANNOT determine this taskset's schedulability under EDF

## Q3 RM, EDF, LLF

- Consider the set of 2 periodic tasks whose period, deadline and WCET parameters are given.
- 1. For each scheduling algorithm (RM, EDF, LLF), draw the Gantt chart by filling in the table with the task ID that runs in each time slot until time 10, and calculate the WCRT for each task.
- 2. Under RM scheduling, use utilization bound and Response Time Analysis (RTA) to determine taskset schedulability.

Task ID	T=D	C	RM Resp. Time	EDF Resp. Time	LLF Resp. Time
1	8	3			
2	10	4			

RM										
EDF										
LLF										

Time 0 1 2 3 4 5 6 7 8 9 10  
Gantt Chart

Time	$\tau_1$ Laxity	$\tau_2$ Laxity	Running Task
t=0			
t=1			
t=2			
t=3			
t=4			
t=5			
t=6			
t=7			
t=8			
T=9			

## Q3 RM, EDF, LLF ANS

- Consider the set of 2 periodic tasks whose period, deadline and WCET parameters are given.
- 1. For each scheduling algorithm (RM, EDF, LLF), draw the Gantt chart by filling in the table with the task ID that runs in each time slot until time 10, and calculate the WCRT for each task.
- 2. Under RM scheduling, determine taskset schedulability using utilization bound and/or Response Time Analysis (RTA) to

Task ID	T=D	C	RM Resp. Time	EDF Resp. Time	LLF Resp. Time
1	8	3	3	3	5
2	10	4	7	7	7

RM	1	1	1	2	2	2	2	X	1	1
EDF	1	1	1	2	2	2	2	X	1	1
LLF	1	1	2	2	1	2	2	X	1	1

Time 0 1 2 3 4 5 6 7 8 9 10  
Gantt Chart

Time	$\tau_1$ Laxity	$\tau_2$ Laxity	Running Task
t=0	8-0-3=5	10-0-4=6	1
t=1	8-1-2=5	10-1-4=5	1 (tie)
t=2	8-2-1=5	10-2-4=4	2
t=3	8-3-1=4	10-3-3=4	2 (tie)
t=4	8-4-1=3	10-4-2=4	1
t=5	T1 done	10-5-2=3	2
t=6	T1 done	10-6-1=3	2
t=7	T1 done	T2 done	X
t=8	16-8-3=5	T2 done	1
T=9	16-9-2=5	T2 done	1

## Q3 RM, EDF, LLF ANS

---

- System utilization  $U = \frac{3}{8} + \frac{4}{10} = 0.775 \leq 0.828$ . Since utilization is within the RM bound, we determine this taskset to be schedulable under RM, without the need for RTA
- System utilization  $U = \frac{3}{8} + \frac{4}{10} = 0.775 \leq 1.0$ , hence this taskset is schedulable under EDF and LLF



## Recall: PCP Blocking Time

---

A given task  $i$  is blocked (or delayed) by at most one critical section of any lower priority task locking a semaphore with priority ceiling greater than or equal to the priority of task  $i$ . We can explain that mathematically using the notation:

$$B_i = \max_{\{k,s \mid k \in lp(i) \wedge s \in used\_by(k) \wedge ceil(s) \geq pri(i)\}} CS_{k,s} \quad (4.5)$$

- Consider all lower-priority tasks ( $k \in lp(i)$ ), and the semaphores they can lock ( $s$ )
- Select from those semaphores ( $s$ ) with ceiling higher than or equal to  $pri(i) = P_i$
- Take max length of all tasks ( $k$ )'s critical sections that lock semaphores ( $s$ )
- (Note: this formula applies only when task  $i$  requests some semaphore. If task  $i$  does not require any semaphores itself, then it does not experience any blocking time, i.e.,  $B_i = 0$ .)

## Q5. Schedulability with Shared Resources

---

- Consider the set of 8 periodic tasks scheduled with RM, with period, deadline, priority (larger number denotes higher priority), and WCET parameters given in the table. The tasks may require one or more of the 5 semaphores.
- 1) Calculate priority ceilings of the semaphores
- 2) Calculate worst-case blocking time  $B_i$ , and WCRT  $R_i$  of all tasks based on RTA  
for RM  $R_i = C_i + B_i + \sum_{\forall j \in hp(i)} \left\lceil \frac{R_i}{T_j} \right\rceil C_j$

## Q5. Schedulability with Shared Resources

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	s <sub>4</sub>	1		
B	500	200	50	7	s <sub>3</sub>	4		
C	800	400	90	6	s <sub>1</sub>	30		
D	800	800	20	5	s <sub>1</sub> , s <sub>2</sub> , s <sub>4</sub>	9,3,3		
E	1000	1000	50	4	s <sub>3</sub>	4		
F	2000	2000	10	3	s <sub>5</sub>	7		
G	2000	2000	10	2	/	/		
H	2000	2000	30	1	s <sub>2</sub> , s <sub>5</sub>	13,7		

Sem	Ceiling
s <sub>1</sub>	
s <sub>2</sub>	
s <sub>3</sub>	
s <sub>4</sub>	
s <sub>5</sub>	

## Q5. Schedulability with Shared Resources ANS

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	s <sub>4</sub>	1	3	17
B	500	200	50	7	s <sub>3</sub>	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	s <sub>1</sub> , s <sub>2</sub> , s <sub>4</sub>	9,3,3	13	187
E	1000	1000	50	4	s <sub>3</sub>	4	13	237
F	2000	2000	10	3	s <sub>5</sub>	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	s <sub>2</sub> , s <sub>5</sub>	13,7	0	288

Sem	Ceiling
s <sub>1</sub>	6
s <sub>2</sub>	5
s <sub>3</sub>	7
s <sub>4</sub>	8
s <sub>5</sub>	3

## Q5. Schedulability with Shared Resources ANS

---

- Each semaphore is assigned a ceiling, equal to maximum priority of all tasks that require it:  $C(s_k) = \max\{P_j: \tau_j \text{ uses } s_k\}$ . Hence we can fill in the semaphore ceiling table.

Sem	Ceiling
$s_1$	5
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3

## Q5. Task A

- Consider task A:
- The set of lower priority tasks  $lp(A)$  includes tasks B, C, D, E, F, G, H
- The set of semaphores used/required by these tasks includes  $s_1, s_2, s_3, s_4$ , and  $s_5$
- Ceilings  $C(s_4)=8 \geq prio(A)=8$
- Maximum blocking time of task A is  $B_A=cs(D, s_4)=3$ 
  - Task D has a CS with length 3, associated with  $s_4$
- $R_A = C_A + B_A = 14 + 3 = 17 \leq D_A = 50$
- Hence task A is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	$s_4$	1	3	17
B	500	200	50	7	$s_3$	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	$s_1, s_2, s_4$	9,3,3	13	187
E	1000	1000	50	4	$s_3$	4	13	237
F	2000	2000	10	3	$s_5$	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	$s_2, s_5$	13,7	0	288

Sem	Ceiling
$s_1$	6
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3

## Q5. Task B

- Consider task B:
- The set of lower priority tasks  $lp(B)$  includes tasks C, D, E, F, G, H
- The set of semaphores used/required by these tasks includes  $s_1, s_2, s_3, s_4$ , and  $s_5$
- Ceilings  $C(s_3)=7, C(s_4)=8 \geq prio(B)=7$
- Maximum blocking time of task B is  $B_B = \max\{cs(D, s_4), cs(E, s_3)\} = \max(3, 4) = 4$
- $R_B = C_B + B_B + \left\lceil \frac{R_B}{T_A} \right\rceil C_A = 50 + 4 + \left\lceil \frac{R_B}{250} \right\rceil 14 = 68 \leq D_B = 200$
- Hence task B is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	$s_4$	1	3	17
B	500	200	50	7	$s_3$	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	$s_1, s_2, s_4$	9,3,3	13	187
E	1000	1000	50	4	$s_3$	4	13	237
F	2000	2000	10	3	$s_5$	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	$s_2, s_5$	13,7	0	288

Sem	Ceiling
$s_1$	6
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3

## Q5. Task C

- Consider task C:
- The set of lower priority tasks  $lp(C)$  includes tasks D, E, F, G, H
- The set of semaphores used/required by these tasks includes  $s_1, s_2, s_3, s_4$ , and  $s_5$
- Ceilings  $C(s_3)=7, C(s_4)=8 \geq prio(C)=6$
- Maximum blocking time of task C is  $B_C = \max\{cs(D, s_4), cs(E, s_3)\} = \max(3, 4) = 4$
- $R_C = C_C + B_C + \left\lceil \frac{R_C}{T_A} \right\rceil C_A + \left\lceil \frac{R_C}{T_B} \right\rceil C_B = 90 + 4 + \left\lceil \frac{R_C}{250} \right\rceil 14 + \left\lceil \frac{R_C}{500} \right\rceil 50 = 158 \leq D_C = 400$
- Hence task C is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	$s_4$	1	3	17
B	500	200	50	7	$s_3$	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	$s_1, s_2, s_4$	9,3,3	13	187
E	1000	1000	50	4	$s_3$	4	13	237
F	2000	2000	10	3	$s_5$	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	$s_2, s_5$	13,7	0	288

Sem	Ceiling
$s_1$	6
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3



## Q5. Task D

- Consider task D:
- The set of lower priority tasks  $lp(D)$  includes tasks E, F, G, H
- The set of semaphores used/required by these tasks includes  $s_2$ ,  $s_3$  and  $s_5$
- Ceilings of  $C(s_2)=5$ ,  $C(s_3)=7 \geq prio(D)=5$
- Maximum blocking time of task D is  $B_D = \max\{cs(E, s_3), cs(H, s_2)\} = \max(4, 13) = 13$ 
  - Task E has a CS with length 4, associated with  $s_3$
  - Task H has a CS with length 13, associated with  $s_2$
  - (Note that task B has higher priority than D, so it is not included even though it also requires  $s_3$ )
- $$R_D = C_D + B_D + \left\lceil \frac{R_D}{T_A} \right\rceil C_A + \left\lceil \frac{R_D}{T_B} \right\rceil C_B + \left\lceil \frac{R_D}{T_C} \right\rceil C_C = 20 + 13 + \left\lceil \frac{R_D}{250} \right\rceil 14 + \left\lceil \frac{R_D}{500} \right\rceil 50 + \left\lceil \frac{R_D}{800} \right\rceil 90 = 187 \leq D_D = 800$$
- Hence task D is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	$s_4$	1	3	17
B	500	200	50	7	$s_3$	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	$s_1, s_2, s_4$	9,3,3	13	187
E	1000	1000	50	4	$s_3$	4	13	237
F	2000	2000	10	3	$s_5$	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	$s_2, s_5$	13,7	0	288

Sem	Ceiling
$s_1$	6
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3

## Q5. Task E

- Consider task E:
- The set of lower priority tasks  $lp(E)$  includes tasks F, G, H
- The set of semaphores used/required by these tasks includes  $s_2$  and  $s_5$
- Ceiling  $C(s_2)=5 \geq prio(E)=4$
- Maximum blocking time of task E is  $B_E=cs(H, s_2)=13$
- $$R_E = C_E + B_E + \left\lceil \frac{R_E}{T_A} \right\rceil C_A + \left\lceil \frac{R_E}{T_B} \right\rceil C_B + \left\lceil \frac{R_E}{T_C} \right\rceil C_C + \left\lceil \frac{R_E}{T_D} \right\rceil C_D = 50 + 13 + \left\lceil \frac{R_E}{250} \right\rceil 14 + \left\lceil \frac{R_E}{500} \right\rceil 50 + \left\lceil \frac{R_E}{800} \right\rceil 90 + \left\lceil \frac{R_E}{800} \right\rceil 20 = 237 \leq D_E = 1000$$
- Hence task E is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	$s_4$	1	3	17
B	500	200	50	7	$s_3$	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	$s_1, s_2, s_4$	9,3,3	13	187
E	1000	1000	50	4	$s_3$	4	13	237
F	2000	2000	10	3	$s_5$	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	$s_2, s_5$	13,7	0	288

Sem	Ceiling
$s_1$	6
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3

## Q5. Task F

- Consider task F:
- The set of lower priority tasks  $lp(F)$  includes tasks G, H
- The set of semaphores used/required by these tasks includes  $s_2$  and  $s_5$
- Ceilings  $C(s_2)=5$ ,  $C(s_5)=3 \geq \text{prio}(F)=3$
- Maximum blocking time of task E is  $B_E = \max(cs(H, s_2), cs(H, s_5)) = \max(13, 7) = 13$
- $$R_F = C_F + B_F + \left\lceil \frac{R_F}{T_A} \right\rceil C_A + \left\lceil \frac{R_F}{T_B} \right\rceil C_B + \left\lceil \frac{R_F}{T_C} \right\rceil C_C + \left\lceil \frac{R_F}{T_D} \right\rceil C_D + \left\lceil \frac{R_F}{T_E} \right\rceil C_E = 10 + 13 + \left\lceil \frac{R_E}{250} \right\rceil 14 + \left\lceil \frac{R_E}{500} \right\rceil 50 + \left\lceil \frac{R_E}{800} \right\rceil 90 + \left\lceil \frac{R_E}{800} \right\rceil 20 + \left\lceil \frac{R_E}{1000} \right\rceil 50 = 247 \leq D_F = 2000$$
- Hence task F is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	$s_4$	1	3	17
B	500	200	50	7	$s_3$	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	$s_1, s_2, s_4$	9,3,3	13	187
E	1000	1000	50	4	$s_3$	4	13	237
F	2000	2000	10	3	$s_5$	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	$s_2, s_5$	13,7	0	288

Sem	Ceiling
$s_1$	6
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3

## Q5. Task G

- Consider task G:
- The set of lower priority tasks  $lp(G)$  includes task H
- The set of semaphores used/required by these tasks includes  $s_2$  and  $s_5$
- Ceilings  $C(s_2)=5, C(s_5)=3 \geq prio(G)=2$
- Maximum blocking time of task E is  $B_E = \max(cs(H, s_2), cs(H, s_5)) = \max(13, 7) = 13$
- $$R_G = C_G + \left\lceil \frac{R_G}{T_A} \right\rceil C_A + \left\lceil \frac{R_G}{T_B} \right\rceil C_B + \left\lceil \frac{R_G}{T_C} \right\rceil C_C + \left\lceil \frac{R_G}{T_D} \right\rceil C_D + \left\lceil \frac{R_G}{T_E} \right\rceil C_E + \left\lceil \frac{R_G}{T_F} \right\rceil C_F = 10 + 13 + \left\lceil \frac{R_G}{250} \right\rceil 14 + \left\lceil \frac{R_G}{500} \right\rceil 50 + \left\lceil \frac{R_G}{800} \right\rceil 90 + \left\lceil \frac{R_G}{800} \right\rceil 20 + \left\lceil \frac{R_G}{1000} \right\rceil 50 + \left\lceil \frac{R_G}{2000} \right\rceil 10 = 271 \leq D_G = 2000$$
- Hence task G is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	$s_4$	1	3	17
B	500	200	50	7	$s_3$	4	4	68
C	800	400	90	6	/	/	4	158
D	800	800	20	5	$s_1, s_2, s_4$	9,3,3	13	187
E	1000	1000	50	4	$s_3$	4	13	237
F	2000	2000	10	3	$s_5$	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	$s_2, s_5$	13,7	0	288

Sem	Ceiling
$s_1$	6
$s_2$	5
$s_3$	7
$s_4$	8
$s_5$	3

## Q5. Task H

- Consider task H:
- Task H is the lowest priority task, so it does not experience any blocking  $B_H=0$
- $$R_H = C_H + \left\lceil \frac{R_H}{T_A} \right\rceil C_A + \left\lceil \frac{R_H}{T_B} \right\rceil C_B + \left\lceil \frac{R_H}{T_C} \right\rceil C_C + \left\lceil \frac{R_H}{T_D} \right\rceil C_D + \left\lceil \frac{R_H}{T_E} \right\rceil C_E + \left\lceil \frac{R_H}{T_F} \right\rceil C_F + \left\lceil \frac{R_H}{T_G} \right\rceil C_G = 30 + \left\lceil \frac{R_H}{250} \right\rceil 14 + \left\lceil \frac{R_H}{500} \right\rceil 50 + \left\lceil \frac{R_H}{800} \right\rceil 90 + \left\lceil \frac{R_H}{800} \right\rceil 20 + \left\lceil \frac{R_H}{1000} \right\rceil 50 + \left\lceil \frac{R_H}{2000} \right\rceil 10 + \left\lceil \frac{R_H}{2000} \right\rceil 10 = 288 \leq D_H = 2000$$
- Hence task H is schedulable

Task	T	D	C	Prio	sems	CS Len	B	R
A	250	50	14	8	s <sub>4</sub>	1	3	17
B	500	200	50	7	s <sub>3</sub>	4	4	68
C	800	400	90	6	s <sub>1</sub>	30	4	158
D	800	800	20	5	s <sub>1</sub> , s <sub>2</sub> , s <sub>4</sub>	9,3,3	13	187
E	1000	1000	50	4	s <sub>3</sub>	4	13	237
F	2000	2000	10	3	s <sub>5</sub>	7	13	247
G	2000	2000	10	2	/	/	13	271
H	2000	2000	30	1	s <sub>2</sub> , s <sub>5</sub>	13,7	0	288

Sem	Ceiling
s <sub>1</sub>	5
s <sub>2</sub>	5
s <sub>3</sub>	7
s <sub>4</sub>	8
s <sub>5</sub>	3