CSC 112: Computer Operating Systems
Lecture 15

Memory 3: Caching and TLBs (Con't), Demand Paging

Department of Computer Science,
Hofstra University

Acknowledgement: Lecture slides based on UC Berkeley CS 162: Operating Systems and System Programming

Recall: The two-level page table



- Tree of Page Tables
  - "Magic" 10b-10b-12b pattern!
- Tables fixed size (1024 entries)
  - On context-switch: save single PageTablePtr register (i.e. CR3)
- Valid bits on Page Table Entries
  - Don't need every 2nd-level table
  - Even when exist, 2nd-level tables can reside on disk if not in use

How is the Translation Accomplished?



- The MMU must translate virtual address to physical address on:
  - Every instruction fetch
  - Every load
  - Every store
- What does the MMU need to do to translate an address?
  - 1-level Page Table
    - » Read PTE from memory, check valid, merge address
    - » Set "accessed" bit in PTE, Set "dirty bit" on write
  - 2-level Page Table
    - » Read and check first level
    - » Read, check, and update PTE
  - N-level Page Table …
- MMU does *page table Tree Traversal* to translate each address

Where and What is the MMU ?



- The processor requests READ Virtual-Address to memory system
  - Through the MMU to the cache (to the memory)
- Some time later, the memory system responds with the data stored at the physical address (resulting from virtual → physical) translation
  - Fast on a cache hit, slow on a miss
- So what is the MMU doing?
- On every reference (I-fetch, Load, Store) read (multiple levels of) page table entries to get physical frame or FAULT
  - Through the caches to the memory
  - Then read/write the physical location

Recall: CS61c Caching Concept



- Cache: a repository for copies that can be accessed more quickly than the original
  - Make frequent case fast and infrequent case less dominant
- Caching underlies many techniques used today to make computers fast
  - Can cache: memory locations, address translations, pages, file blocks, file names, network routes, etc…
- Only good if:
  - Frequent case frequent enough and
  - Infrequent case not too expensive
- Important measure: Average Access time =
  (Hit Rate x Hit Time) + (Miss Rate x Miss Time)

Recall: In Machine Structures (eg. 61C) …

- Caching is the key to memory system performance



Average Memory Access Time (AMAT)

= (Hit Rate x HitTime) + (Miss Rate x MissTime)

Where HitRate + MissRate = 1

HitRate = 90% => AMAT = (0.9 x 1) + (0.1 x 101)=11 ns

HitRate = 99% => AMAT = (0.99 x 1) + (0.01 x 101)=2.01 ns

$MissTime_{L1}$ includes $HitTime_{L1}$+$MissPenalty_{L1}$ ≡ $HitTime_{L1}$ +$AMAT_{L2}$

Another Major Reason to Deal with Caching



- Cannot afford to translate on every access
  - At least three DRAM accesses per actual DRAM access
  - Or: perhaps I/O if page table partially on disk!
- Even worse: What if we are using caching to make memory access faster than DRAM access?
- Solution? Cache translations!
  - Translation Cache: TLB ("Translation Lookaside Buffer")

Why Does Caching Help? Locality!



- Temporal Locality (Locality in Time):
  - Keep recently accessed data items closer to processor
- Spatial Locality (Locality in Space):
  - Move contiguous blocks to the upper levels



Recall: Memory Hierarchy

- Caching: Take advantage of the principle of locality to:
  - Present the illusion of having as much memory as in the cheapest technology
  - Provide average speed similar to that offered by the fastest technology



How do we make Address Translation Fast?

- Cache results of recent translations !
  - Different from a traditional cache
  - Cache Page Table Entries using Virtual Page # as the key



Translation Look-Aside Buffer

- Record recent Virtual Page # to Physical Frame # translation
- If present, have the physical address without reading any of the page tables !!!
  - Even if the translation involved multiple levels
  - Caches the end-to-end result
- On a *TLB miss*, the page tables may be cached, so only go to memory when both miss

Caching Applied to Address Translation



- Question is one of page locality: does it exist?
  - Instruction accesses spend a lot of time on the same page (since accesses sequential)
  - Stack accesses have definite locality of reference
  - Data accesses have less page locality, but still some…
- Can we have a TLB hierarchy?
  - Sure: multiple levels at different sizes/speeds

What kind of Cache for TLB?



- Remember all those cache design parameters and trade-offs?
  - Amount of Data = N * L * K
  - Tag is portion of address that identifies line (w/o line offset)
  - Write Policy (write-thru, write-back), Eviction Policy (LRU, …)

How might organization of TLB differ from that of a conventional instruction or data cache?

- Let's do some review …

A Summary on Sources of Cache Misses

- Compulsory (cold start or process migration, first reference): first access to a block
  - "Cold" fact of life: not a whole lot you can do about it
  - Note: If you are going to run "billions" of instruction, Compulsory Misses are insignificant
- Capacity:
  - Cache cannot contain all blocks access by the program
  - Solution: increase cache size
- Conflict (collision):
  - Multiple memory locations mapped to the same cache location
  - Solution 1: increase cache size
  - Solution 2: increase associativity
- Coherence (Invalidation): other process (e.g., I/O) updates memory

How is a Block found in a Cache?



- Block is minimum quantum of caching
  - Data select field used to select data within block
  - Many caching applications don't have data select field
- Index Used to Lookup Candidates in Cache
  - Index identifies the set
- Tag used to identify actual copy
  - If no candidates match, then declare cache miss

Review: Direct Mapped Cache

- Direct Mapped 2^N byte cache:
  - The uppermost (32 - N) bits are always the Cache Tag
  - The lowest M bits are the Byte Select (Block Size = 2^M)
- Example: 1 KB Direct Mapped Cache with 32 B Blocks
  - Index chooses potential block
  - Tag checked to verify block
  - Byte select chooses byte within block



Review: Set Associative Cache

- N-way set associative: N entries per Cache Index
  - N direct mapped caches operates in parallel
- Example: Two-way set associative cache
  - Cache Index selects a "set" from the cache
  - Two tags in the set are compared to input in parallel
  - Data is selected based on the tag result



Review: Fully Associative Cache

- Fully Associative: Every block can hold any line
  - Address does not include a cache index
  - Compare Cache Tags of all Cache Entries in Parallel
- Example: Block Size=32B blocks
  - We need N 27-bit comparators
  - Still have byte select to choose from within block



Where does a Block Get Placed in a Cache?

- Example: Block 12 placed in 8 block cache

32-Block Address Space:



Block no. 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

Direct mapped:
block 12 can go only into block 4 (12 mod 8)



Set associative:
block 12 can go anywhere in set 0 (12 mod 4)



Fully associative:
block 12 can go anywhere



Which block should be replaced on a miss?

- Easy for Direct Mapped: Only one possibility
- Set Associative or Fully Associative:
  - Random
  - LRU (Least Recently Used)

- Miss rates for a workload:

	2-way		4-way		8-way	
Size	LRU	Random	LRU	Random	LRU	Random
16 KB	5.2%	5.7%	4.7%	5.3%	4.4%	5.0%
64 KB	1.9%	2.0%	1.5%	1.7%	1.4%	1.5%
256 KB	1.15%	1.17%	1.13%	1.13%	1.12%	1.12%

Review: What happens on a write?

- Write through: The information is written to both the block in the cache and to the block in the lower-level memory
- Write back: The information is written only to the block in the cache
  - Modified cache block is written to main memory only when it is replaced
  - Question is block clean or dirty?
- Pros and Cons of each?
  - WT:
    - » PRO: read misses cannot result in writes
    - » CON: Processor held up on writes unless writes buffered
  - WB:
    - » PRO: repeated writes not sent to DRAM
      processor not held up on writes
    - » CON: More complex
      Read miss may require writeback of dirty data

What TLB Organization Makes Sense?



- Needs to be really fast
  - Critical path of memory access
    - » In simplest view: before the cache
    - » Thus, this adds to access time (reducing cache speed)
  - Seems to argue for Direct Mapped or Low Associativity
- However, needs to have very few conflicts!
  - With TLB, the Miss Time extremely high! (PT traversal)
  - Cost of Conflict (Miss Time) is high
  - Hit Time – dictated by clock cycle
- Thrashing: continuous conflicts between accesses
  - What if use low order bits of virtual page number as index into TLB?
    - » First page of code, data, stack may map to same entry
    - » Need 3-way associativity at least?
  - What if use high order bits as index?
    - » TLB mostly unused for small programs

TLB organization: include protection

- How big does TLB actually have to be?
  - Usually small: 128-512 entries (larger now)
  - Not very big, can support higher associativity
- Small TLBs usually organized as fully-associative cache
  - Lookup is by Virtual Address
  - Returns Physical Address + other info
- What happens when fully-associative is too slow?
  - Put a small (4-16 entry) direct-mapped cache in front
  - Called a "TLB Slice"
- Example for MIPS R3000:

Virtual Address	Physical Address	Dirty	Ref	Valid	Access	ASID
0xFA00	0x0003	Y	N	Y	R/W	34
0x0040	0x0010	N	Y	Y	R	0
0x0041	0x0011	N	Y	Y	R	0

Example: R3000 pipeline includes TLB “stages”

MIPS R3000 Pipeline



TLB

64 entry, on-chip, fully associative, software TLB fault handler

Virtual Address Space



0xx User segment (caching based on PT/TLB entry)
100 Kernel physical space, cached
101 Kernel physical space, uncached
11x Kernel virtual space

Allows context switching among
64 user processes without TLB flush

Reducing translation time for physically-indexed caches

- As described, TLB lookup is in serial with cache lookup
  - Consequently, speed of TLB can impact speed of access to cache



- Machines with TLBs go one step further: overlap TLB lookup with cache access
  - Works because offset available early
  - Offset in virtual address exactly covers the "cache index" and "byte select"
  - Thus can select the cached byte(s) in parallel to perform address translation



Overlapping TLB & Cache Access

- Here is how this might work with a 4K cache:



- What if cache size is increased to 8KB?
  - Overlap not complete
  - Need to do something else. See CS152/252
- Another option: Virtual Caches would make this faster
  - Tags in cache are virtual addresses
  - Translation only happens on cache misses

What happens on a Context Switch?

- Need to do something, since TLBs map virtual addresses to physical addresses
  - Address Space just changed, so TLB entries no longer valid!
- Options?
  - Invalidate TLB: simple but might be expensive
    - » What if switching frequently between processes?
  - Include ProcessID in TLB
    - » This is an architectural solution: needs hardware
- What if translation tables change?
  - For example, to move page from memory to disk or vice versa…
  - Must invalidate TLB entry!
    - » Otherwise, might think that page is still in memory!
  - Called "TLB Consistency"
- Aside: with Virtually-Indexed cache, need to flush cache!
  - Remember, everyone has their own version of the address "0"!

Putting Everything Together: Address Translation



Putting Everything Together: TLB



Putting Everything Together: Cache



Page Fault

- The Virtual-to-Physical Translation fails
  - PTE marked invalid, Priv. Level Violation, Access violation, or does not exist
  - Causes an Fault / Trap
    - » Not an interrupt because synchronous to instruction execution
  - May occur on instruction fetch or data access
  - Protection violations typically terminate the instruction
- Other Page Faults engage operating system to fix the situation and retry the instruction
  - Allocate an additional stack page, or
  - Make the page accessible - Copy on Write,
  - Bring page in from secondary storage to memory – demand paging
- Fundamental inversion of the hardware / software boundary

Demand Paging

- Modern programs require a lot of physical memory
  - Memory per system growing faster than 25%-30%/year
- But they don't use all their memory all of the time
  - 90-10 rule: programs spend 90% of their time in 10% of their code
  - Wasteful to require all of user's code to be in memory
- Solution: use main memory as "cache" for disk



Page Fault ⇒ Demand Paging



Summary (1/2)

- The Principle of Locality:
  - Program likely to access a relatively small portion of the address space at any instant of time.
    - » Temporal Locality: Locality in Time
    - » Spatial Locality: Locality in Space
- Three (+1) Major Categories of Cache Misses:
  - Compulsory Misses: sad facts of life. Example: cold start misses.
  - Conflict Misses: increase cache size and/or associativity
  - Capacity Misses: increase cache size
  - Coherence Misses: Caused by external processors or I/O devices
- Cache Organizations:
  - Direct Mapped: single block per set
  - Set associative: more than one block per set
  - Fully associative: all entries equivalent

Summary (2/2)

- "Translation Lookaside Buffer" (TLB)
  - Small number of PTEs and optional process IDs (< 512)
  - Often Fully Associative (Since conflict misses expensive)
  - On TLB miss, page table must be traversed and if located PTE is invalid, cause Page Fault
  - On change in page table, TLB entries must be invalidated
- Demand Paging: Treating the DRAM as a cache on disk
  - Page table tracks which pages are in memory
  - Any attempt to access a page that is not in memory generates a page fault, which causes OS to bring missing page into memory
- Replacement policies
  - FIFO: Place pages on queue, replace page at end
  - MIN: Replace page that will be used farthest in future
  - LRU: Replace page used farthest in past